Market Rates System

(MRS)

1st February to 31st July, 2012

haroon_01@hotmail.com

TABLE OF CONTENTS

Sr No.	Chapter	Pa	ge N	<i>los</i>
01.	Carriage	03	to	22
02.	Loading, Unloading & Stacking	23	to	25
03.	Earthwork (Excavation & Embankment)	26	to	32
04.	Dismentling (Demolition)	33	to	37
05.	Mortar	38	to	39
06.	Concrete	40	to	50
07.	Brickwork	51	to	56
08.	Stone Masonary	57	to	59
09.	Roofing	60	to	65
10.	Flooring	66	to	71
11.	Surface Rendering	72	to	76
12.	Wood Work	77	to	87
13.	Painting & Varnishing	88	to	94
14.	Lining of Canals	9 5	to	96
15.	Sheet Piling	97	to	<i>98</i>
16.	Protection & Diversion Work	99	to	109
17.	Outlets	110	to	112
18.	Road & Road Structure	113	to	117
19.	Plumbing, Sanitary Installation & Gas Fittings	118	to	124
20.	Surface Drainage	125	to	126
21.	Sewerage	127	to	131
22.	Sinking of Wells	132	to	134
23.	Tubewell & Water Supply	135	to	147
24.	Electric Installation	148	to	161
	Iron Work	162	to	167
26.	Miscellaneous	168	to	171

1. CARRIAGE

				1. Сля	QUAG:	L							
Note:	1	The rates are applicable to carriage of material on pacca roads only. For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.											
Note:	2	For hilly areas 25% above the rates in the plain areas shall be allow	ved for total mile	eage (Km) cover	ed.								
Note:	3	In case of articles longer than 15 ft. (4.6 m) carried in trucks, the fo	ollowing rates sh	all be allowed:-									
		i) Above 15 ft. to 25 ft. (4.6 to 7.6 m) :- Total rates to be paid for rate given in the Composite Schedule of Rates.	15 ft. to 25 ft. (4	4.6 to 7.6 m) len	gth will be 1.5 ti	mes of the							
	ii) Above 25 ft. (7.6 m) :- The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.												
	The length measured shall not be the actual length, but the length of the form of consignment as actually received.												
Note:	4	The term 'mile' (Km) whenever used is to mean statute mile (Km).		1 1	()								
Note:	5	The rates include loading and unloading of material from the conve	eyance and stack	ing as directed.		1.							
Note:	6	The rates for carriage by boat or steamer shall be the same as by ar	v other mechani	ical means on lar	ıd	- U.							
		MRS, BI-ANNUAL PI				1st JULY, 20	012) DIST	RICT LODH	RAN				
Sr.		Description		A Martin		Rate	e (Metric Sys	stem)	Spec.	Remarks			
No.			1			Unit of M/ment	Labour	Composite	No.				
	aggr 150	iage of 100 Cft. (2.83 cu.m) of all materials like stone egate, spawl, kankar lime (unslaked), surkhi, etc. or Cft. (4.25 cu.m) of timber, by truck or by any other as owned by the contractor.	Fi	nance	Depar	iment			16.1				
		1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30M 30M 300 Metre Km Km Km	74.25 13.65 8.50 83.50 147.74 69.97 53.83						
		4th Km 5th Km 6th Km 7th Km 8th Km 9th Km 10th Km 11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms				Km Km Km Km Km Km Km Km Km	37.66 34.97 34.37 31.96 31.60 29.61 27.56 19.98 3.25 2.00						
	Carr (unsl	iage of 5 tons of all material like coal, stone lime laked), etc. B.G. Rail fastenings, points and crossing, ge Girders, pipes, sheets, Rail, M.S. bars, etc. etc.							16.1	Cement carried in containers other than bags will be paid according to this item. The word "pipes" covers			

	MRS, BI-ANNUAL P	ERIOD (1st FEBRUARY, 20	012 TO 31s	st JULY, 20	12) DIST	RICT LODH	RAN	
Sr.	Description			Rate	(Metric Sys	stem)	Spec.	Remarks
No.				Unit of M/ment	Labour	Composite	No.	
	by truck or any other means owned by the contractor.				Lubour			G.I,C.I,R.C.C. and P.C.C.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km			30M 30M 300M 300M Km Km Km Km	74.25 13.65 8.50 83.50 147.74 69.97 53.83 37.66 34.97 34.37			
	7th Km	and the second se		Km	31.96			
	8th Km 9th Km			Km Km	31.60 29.61			
	10th Km			Km	27.56			
3	11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms Carriage of 100 maunds of fuel wood by truck or any other means owned by the contractor:		le la	Km Km Km	19.98 3.25 2.00		16.1	
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km	Finance D)epart:	30 M 30 M 30 M 300 M Km Km Km	74.25 13.65 8.50 83.50 147.74 69.97 53.83 37.66			
	5th Km			Km	34.97			
	6th Km			Km	34.37			
	7th Km			Km	31.96			
	8th Km			Km	31.60			
	9th Km			Km	29.61			
	10th Km			Km	27.56			
4	11th & subsequent Kms Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm) or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or any other means owned by the contractor :-			Km	19.98		ditto	Reduce the rate by 33% in case of carriage of 1000 Nos. tiles size 12"x6"x1 ¹ /4" (300 x 150 x 30 mm).

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY, 20	012) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m)				30 M	74.25			
	2nd chain (2nd 30 m)				30 M	13.65			
	3rd to 10th chain (60 to 300 m)				30 M	8.50			
	1000 to 3000 ft. (300 to 900 m)				300 M	83.50			
	1st Km				Km	147.74			
	2nd Km				Km	69.97			
	3rd Km 4th Km				Km Km	53.83 37.66			
	401 Km				Km	57.00			
	5th Km				Km	34.97			
	6th Km				Km	34.37			
	7th Km				Km	31.96			
	8th Km		1	5	Km	31.60			
	9th Km				Km	29.61			
	10th Km	1	00.05		Km	27.56			
	11th & subsequent Kms	1.36%			Km	19.98			
5	Carriage of 100 cft. (2.83 cu.m) of all material like stone,	1/03/	1.	/	113			16.1	Material trolly to be supplied by the
	aggregate, spawl, kankar lime(unslaked), surkhi, etc. or	1	200						Government and maintained and run
	150 cft. (4.25 cu.m) of timber, by means of material trolly			San Chi	Sola				by the contractor.
	1st chain (1st 30 m)		2-2	2000	30 M 30 M	74.25			
	2nd chain to 10th chain (2nd 30 m to 300 m) 1000 to 3000 ft. (300 to 900 m)	-2722-021			30 M	13.65 83.50			
	1st Km	2.3	nance	Devar	Km	121.17			
	2nd Km				Km	92.75			
	3rd Km				Km	49.84			
	4th Km				Km	39.16			
	5th Km				Km	34.44			
	6th Km				Km	33.10			
	7th Km				Km	28.00			
	8th Km				Km	27.69			
	9th Km				Km	25.93			
	10th Km				Km	24.13			
	11th Kms to 200Kms				Km	19.23			
	201 Kms to 250 Kms				Km	3.25			
	251 Kms & susequent Kms				Km	2.00			
6	Carriage of 5 tons of all material like coal, stone lime							16.1	Material trolly to be supplied by the
	(unslaked), etc. B.G. Rail fastening, points and crossing,								Government and maintained and run
	Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by								by the contractor.
	means of material trolly. 1st chain (1st 30 m)				30 M	74.25			
	2nd chain (2nd 30 m)				30 M	13.65			
	1000 to 3000 ft. (300 to 900 m)				300 M	83.50			
	1st Km				Km	121.17			
	2nd Km				Km	92.75			

	MRS, BI-ANNUAL P	ERIOD (1st I	FEBRUARY	, 2012 TO 3 1	st JULY, 20	12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	3rd Km				Km	49.84			
	4th Km				Km	39.16			
	5th Km 6th Km				Km Km	34.44 33.10			
	7th Km				Km	28.00			
	8th Km				Km	23.69			
	9th Km				Km	25.93			
	10th Km				Km	24.13			
	11th Kms to 200Kms				Km	19.23			
	201 Kms to 250 Kms				Km	3.25			
7	251 Kms & susequent Kms Carriage of 100 maunds of fuel wood, by means of				Km	2.00		ditto	Material trolly to be supplied
Ĺ	material trolly.							anto	by the Government and
	1st chain (1st 30 m)				30 M	74.25			maintained and run by the
	2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m)				30 M 300 M	13.65 83.50			contractor.
	1st Km		/ ``		Km	121.17			
	2nd Km				Km	92.75			
	3rd Km 4th Km				Km Km	49.84 39.16			
		101	100 - VA						
	5th Km	1556		61	Km	34.44			
	6th Km	20			Km	33.10			
	7th Km			R P	Km	28.00			
	8th Km	Ti	nance	Depar	Km	27.69			
	9th Km				Km	25.93			
	10th Km				Km	24.13			
0	11th & subsequent Kms				Km	19.23			
8	Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm), by means of material trolly.							ditto	Material trolly to be supplied by the Government and maintained and run
	1st chain (1st 30 m)				30 M	74.25			by the contractor.
	2nd chain (2nd 30 m)				30 M	13.65			
	1000 to 3000 ft. (300 to 900 m)				300 M	83.50			
	1st Km 2nd Km				Km Km	121.17 92.75		16.1	
	3rd Km				Km	49.84		10.1	
	4th Km				Km	39.16			
	5th Km				Km	34.44			
	6th Km				Km	33.10			
	7th Km				Km	28.00			
	8th.				Km	27.69			

	MRS, BI-ANNUAL P	ERIOD (1st	1st JULY, 2012) DISTRICT LODHRAN						
Sr.	Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
					ivi/ment	Lubbul	composite		
	9th Km				Km	25.93			
	10th Km				Km	24.13			
	11th & subsequent Kms				Km	19.23			
9	Carriage of 1000 No. bricks, 9"x4½"x3" (225x113x75 mm) or 8"x4"x4" (200x100x100							ditto	
	mm) (nominal)				20.14				
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	60.84 12.20			
	3rd to 10th chain (60 to 300 m)				30 M	6.98			
	1000 to 3000 ft. (300 to 900 m)				300 M	68.36			
	1st Km				Km	121.11			
	2nd Km 3rd Km		/ ×	61	Km Km	57.24 44.10			
	4th Km		$\langle \cdot \cdot \rangle$	1	Km	31.08			
	5th Km	1	240X - 540		Km	29.52			
	6th Km	100	10 AYA		Km	28.85			
	7th Km	S.		المحرمت	Km	26.19			
	8th Km			R P	Km	25.89			
	9th Km	105		15 marine second	Km	24.26			
	10th Km	F	nance	Depar	Km	22.58			
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½"				Km	16.28		16.1	
	(225x113x38 mm).								
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	36.72 6.74		16.1	
	3rd to 10th chain (60 to 300 m)				30 M	4.17		10.1	
	1000 to 3000 ft. (300 to 900 m)				300 M	41.30			
	1st Km				Km	73.11			
	2nd Km 3rd Km				Km Km	34.64 26.66			
	4th Km				Km	18.63			
	5th Km				Km	17.19			
	6th Km				Km	16.91			
	7th Km				Km	15.80			
	8th Km				Km	15.62			
	9th Km				Km	14.65			

	MRS, BI-ANNUAL P	ERIOD (1st I	st JULY, 20)12) DIST	RICT LODH	RAN			
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	10th Km				Km	13.68			
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.				Km	9.87		ditto	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	1.40 0.17 0.08			
	1000 to 3000 ft. (300 to 900 m)				300 M	0.82			
	1st Km				Km	1.83			
	2nd Km				Km	1.26			
	3rd Km		1	-	Km	0.56			
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including		(Km	0.34		16.1	
	bundling. 1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft. 1st Km	Stan-			300 M 300 M Km	20.48 2.55 4.44			
	2nd Km		n - Sh		Km	4.60			
	3rd Km	T	nance	Depar	Km	2.19			
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash or brushwood, by boat or road :-			8	Km	1.98		ditto	Previous lead of collection not to be deducted from the next lead of carriage.
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	30.38 13.65			
	3rd to 10th chain (60 to 300 m)				30 M	4.17			
	1000 to 3000 ft. (300 to 900 m)				300 M	34.30			
	1st Km				Km	67.11			
	2nd Km				Km	34.64			
	3rd Km				Km	26.66			
	4th Km				Km	18.63			
	5th Km				Km	17.19			

	MRS, BI-ANNUAL PI	ERIOD (1st	1st JULY, 2012) DISTRICT LODHRAN						
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	6th Km				Km	16.91			
	7th Km				Km	15.80			
	8th Km 9th Km				Km Km	15.62 14.65			
	10th Km				Km	13.68			
	11th Km & subsequent				Km	9.87			
14	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre)				Tonne 300 M	248.20		ditto	
	Execceding 1000 to 5000 ft (300 to 1500metre)				"	60.14			
	lst Km				Km	145.35			
	2nd Km		$\langle \cdot \rangle$	0	Km	68.15			
	3rd Km				Km	46.60			
	4th Km	1			Km	30.53			
	5th Km	Sec.	K		Km	28.87			
	6th Km	1		Z	Km	27.75			
	7th Km			200	Km	24.13			
	8th Km 9th Km	F	nance	Depar	Km Km	23.77 23.26			
	10th Km 11th Km & susequent				Km Km	18.47 15.04			
15					T T T	15.01		161	
15	Carriage of small consignments weighing upto 5 maunds (job rates) :							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%;
									and for consignments weighing 10 to 20 maunds, rate be increased by
	Upto 1000 ft. (300 metre)				Consign- ment/	20.16			100%.
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				300 M	13.82			
	lst Km				Consign-	22.74			
	2nd Km				ment/ Km	14.27			
	3rd Km & subsequent					4.82			
16	Carriage of consignments job.								
	i) Cooly load for distance:-				Each				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rat	e (Metric Sy	stem)	Spec.	Remarks				
No.			Unit of M/ment	Labour	Composite	No.					
	a) Upto 5 Km b) Above 5 to 13 Km		Consignment	46.80 112.40							
	 ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ¹/₂ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km 		Each Consignment " " "	10.85 16.45 20.80 26.00 45.95 82.25							
	 iii) Cart load for a distance :- a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to10 Miles(16 Km) 	0	Each Consig- nment "	89.85 163.55							
	 iv) Camel load for a distance:- a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km) 			66.45 100.75							
17	Hire charges of:- i) truck (10 Ton Capacity)		Per day	3000.00			 This item will be allowed with prior concurrence of Superintending Engineer. The rate includes pay of driver 				
	ii) tractor with trolly	Finance Dep	"	1000.00			and cleaner only. The repairs shall be the responsibility of the owner				
	iii) tractor without trolly	a manco aropi	artme <u>n</u> t	800.00			and the cost of lubrication, fuel, loading and unloading shall be paid by the borrower.				
18	Carriage of bitumen, tar or other lubricants, in drums:					16.1					
	1st Km		Per Tonne	24.23							
	2nd Km		"	16.80							
	3rd Km & subsequent Kms		"	6.93							
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-										
	 i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 		30 M 30 M 30 M 300 M Km	2.95 0.55 0.35 3.30 5.84							

	1	MRS, BI-ANNUAL P	ERIOD (1st	, 2012 TO 3 1	1st JULY, 2012) DISTRICT LODHRAN							
Sr.		Description				Rate	(Metric Sys	stem)	Spec.	Remarks		
No.		-				Unit of M/ment	Labour	Composite	No.			
		2nd Km				Km	2.74					
		3rd Km				Km	2.10					
		4th Km				Km	1.46					
		5th Km				Km	1.36					
		6th Km				Km	1.33					
		7th Km				Km	1.23					
		8th Km				Km	1.21					
		9th Km				Km	1.13					
		10th Km		$\langle \rangle$	5	Km	1.07					
		11th Km & Susequent				Km	1.03					
	ii)	4" (100 mm) i/d pipes:-				38						
		1st chain (1st 30 m)	and			30 M	3.85					
		2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	161	1.10	كرهيت	30 M 30 M	0.70 0.45					
			1			63-						
		1000 to 9000 ft. (300 to 900 m)			200	300 M	4.30					
		1st Km	Ŧ	nance	Depar	Km	7.64					
		2nd Km				Km	3.59					
		3rd Km				Km	2.76					
		4th Km				Km	1.92					
		5th Km				Km	1.77					
		6th Km				Km	1.74					
		7th Km				Km	1.61					
		8th Km				Km	1.59					
		9th Km				Km	1.51					
		10th Km 11th Km & subsequent Km				Km Km	1.38 1.33					
	iii)	6" (150 mm) i/d pipes:-				ixin	1.55					
)	1st chain (1st 30 m)				30 M	5 75					
		2nd chain (2nd 30 m)				30 M 30 M	5.75 1.05					
		3rd to 10th chain (60 to 300 m)				30 M	0.65					

	MRS, BI-ANNUAL PI	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY, 20)12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1000 to 9000 ft. (300 to 900 m)				300 M	6.50			
	1st Km				Km	11.46			
	2nd Km 3rd Km				Km Km	5.41 4.17			
	Jukin				Kill	4.17			
	4th Km				Km	2.91			
	5th Km				Km	2.68			
	6th Km				Km	2.64			
	7th Km				Km	2.45			
	8th Km				Km	2.42			
	9th Km		/ ×	()	Km	2.27			
	10th Km		/ `		Km	2.11			
	11th Km & subsequent Km iv) 8'' (200 mm) i/d pipes:	41	And and a state of the state of		Km	1.78			
	(v) 8 (200 mm) //a pipes:	1			123				
	1st chain (1st 30 m)	19			30 M	9.75			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	100	1.	67	30 M 30 M	1.80 1.10			
	1000 to 3000 ft. (300 to 900 m)				300 M	10.95			
	1st Km	4		6	Km	19.39			
	2nd Km			22	Km	9.43			
	3rd Km	1200		15%	Km	7.18			
	4th Km	2.1	nance	Depar	Km	4.98			
	5th Km				Km	4.62			
	6th Km				Km	4.54			
	7th Km				Km	4.22			
	8th Km				Km	4.06			
	9th Km				Km	3.71			
	10th Km 11th Km & subsequent Km				Km Km	2.47 1.75			
	-				13111	1.75			
	v) 10" (250 mm) i/d pipes:-				20.14				
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	13.10 2.40			
	3rd to 10th chain (60 to 300 m)				30 M 30 M	1.50			
	1000 to 3000 ft. (300 to 900 m)				300 M	14.75			
	1st Km				Km	26.07			
	2nd Km 3rd Km				Km Km	12.24 9.37			
	JIU KIII				IXIII	9.57			

	MRS, BI-ANNUAL P	ERIOD (1st FEI	BRUARY,	2012 TO 31	st JULY, 20	12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.	·				Unit of M/ment	Labour	Composite	No.	
	4th Km				Km	6.52	composite		
	5th Km				Km	6.04			
	6th Km				Km	5.94			
	7th Km				Km	5.77			
	8th Km				Km	5.70			
	9th Km				Km	5.35			
	10th Km 11th Km & subsequent Kms				Km Km	4.99 3.58			
	 vi) 12" (300 mm) i/d pipes: 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km 8th Km 		ance	Depar	30 M 30 M 30 M 300 M Km Km Km Km Km	17.05 3.15 1.95 19.15 33.90 16.90 12.60 8.49 7.87 7.73 7.18 7.10			
	9th Km 10th Km				Km Km	6.64 6.17			
	11th Km & subsequent Kms				Km	4.56			
	 viii) 16" (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 				30 M 30 M 30 M 300 M Km Km Km	27.90 5.15 3.20 31.40 55.55 26.56 20.20 14.12			
	5th Km				Km	13.12			

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY, 20	12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	Description				Unit of			No.	Reliar K5
					M/ment	Labour	Composite		
	6th Km				Km	12.89			
	7th Km				Km	11.97			
	8th Km				Km	11.84			
	9th Km				Km	11.11			
	10th Km				Km	10.35			
	11th Km & subsequent Kms				Km	7.53			
	viii) 18" (450 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	35.85			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)			6.	30 M 30 M	6.60 4.10			
	1000 to 3000 ft. (300 to 900 m)		/		300 M	40.35			
	1st Km		/ ``		Km	71.37			
	2nd Km				Km	33.82			
	3rd Km	192			Km	26.01			
	4th Km	100			Km	18.20			
	4th Kin	1855			KIII	16.20			
	5th Km	1620	1.14	/ هومت	Km	16.90			
	6th Km	1			Km	16.61			
	7th Km	05	nance	Devar	Km	15.46			
	8th Km		88-88648-9.227	2010 g 1000 i	Km	15.28			
	9th Km				Km	14.33			
	10th Km				Km	13.31			
	11th Km & subsequent Kms				Km	9.57			
	ix) 20" (500 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	38.10			
	2nd chain (2nd 30 m)				30 M	7.00			
	3rd to 10th chain (60 to 300 m)				30 M	4.35			
	1000 to 3000 ft. (300 to 900 m)				300 M	42.80			
	1st Km				Km	75.75			
	2nd Km				Km	35.87			
	3rd Km				Km	27.60			
	4th Km				Km	19.31			
	5th Km				Km	17.94			
	6th Km				Km	17.62			

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY, 20	12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
					ivi, inclit		composite		
	7th Km				Km	16.37			
	8th Km				Km	16.19			
	9th Km				Km	15.18			
	10th Km 11th Km & subsequent Kms x) 24" (600 mm) i/d pipes:-				Km Km	14.12 10.36			
	1st chain (1st 30 m)				30 M	42.20			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	7.75 4.85			
	1000 to 5000 ft. (300 to 1500 m)		and the second sec		300 M	47.45			
	1st Km 2nd Km		/ >	E) \	Km Km	83.95 39.72			
	3rd Km		(_	Km	30.54			
	4th Km	100			Km	21.89			
	5th Km				Km	19.84			
	6th Km	Ŵ	N.S.S.	الطومت	Km	19.49			
	7th Km	4			Km	18.10			
	8th Km	65	nance	(Prana and	Km	17.90			
	9th Km	12.1 8	92.6832.6.65	Depar	Km	16.78			
20	10th Km 11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading, unloading and stacking (Rate per 1000 ft.) (300 metre) :-				Km Km	15.60 11.25			
	i) 3'' (75 mm) i/d pipes:-								
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	5.75 1.05 0.65 6.45 11.43 5.40 4.15			
	4th Km				Km	2.90			
	5th Km				Km	2.70			

	MRS, BI-ANNUAL PE	RIOD (1st FEBRUARY,	, 2012 TO 31	st JULY, 20)12) DIST	RICT LODH	RAN	
Sr.	Description			Rate	e (Metric Sys	stem)	Spec.	Remarks
No.				Unit of M/ment	Labour	Composite	No.	
	6th Km			Km.	2.65	composite		
	7th Km			Km	2.47			
	8th Km			Km	2.42			
	9th Km			Km	2.25			
	10th Km 11th Km & subsequent Kms ii) 4'' (100 mm) i/d pipes:-			Km Km	2.09 1.70			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		0	30 M 30 M 30 M 300 M Km Km	8.85 1.65 1.00 9.95 17.62 8.52 6.43			
	4th Km			Km	4.40			
	5th Km		(کو می ت	Km	4.08			
	6th Km			Km	4.01			
	7th Km			Km	3.72			
	8th Km	Finance	Depart	Km	3.68			
	9th Km			Km	3.46			
	10th Km 11th Km & subsequent Kms iii) 5'' (125 mm) i/d pipes:-			Km Km	3.20 2.74			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km			30 M " 300 M Km "	12.10 2.20 1.40 13.60 24.02 11.52 8.90			
	4th Km			"	6.27			
	5th Km			Km.	5.64			
I	6th Km			"	5.54			

	MRS, BI-ANNUAL PI	RIOD (1st	FEBRUARY	, 2012 TO 3 1	st JULY, 20	012) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	-				Unit of M/ment	Labour	Composite	No.	
	7th Km				"	5.14	•		
	8th Km					5.09			
	9th Km					4.76			
	10th Km 11th Km & subsequent Kms					4.43 3.25			
	iv) 6" (150 mm) i/d pipes:								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 300 m) 1st Km. 2nd Km 3rd Km			6	30 M 30 M 30 M 300 M Km. Km. Km.	16.65 3.05 1.90 18.70 33.12 15.68 12.06			
	4th Km				Km.	8.43			
	5th Km	ŝ			Km.	7.83			
	6th Km	- E	X	(کوم یہ ر	Km.	7.70			
	7th Km	1			Km.	7.17			
	8th Km	1975	6		Km.	7.09			
	9th Km	2.1	nance	Depar	Km.	6.63			
	10th Km 11th Km & subsequent Kms				Km. Km.	6.17 4.46			
	v) 8'' (200 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	29.20 5.35 3.35 32.85 58.10 27.54 21.18			
	4th Km				Km	14.82			
	5th Km				Km	13.77			
	6th Km				Km	13.53			
	7th Km				Km	12.56			

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 3 1	st JULY, 20	012) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	-				Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	12.42			
	9th Km				Km	11.66			
	10th Km 11th Km & subsequent Kms vi) 10'' (250 mm) i/d pipes:-				Km Km	10.81 7.81			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	45.30 8.30 5.20 50.90 90.07 42.67			
	3rd Km				Km	32.81			
	4th Km		1	5	Km	22.95			
	5th Km				Km	21.33			
	6th Km	100			Km	20.96			
	7th Km	Sec.	Kat	67	Km	19.49			
	8th Km	The second se			Km	19.27			
	9th Km		-0-7	22	Km	18.05			
	10th Km 11th Km & subsequent Kms	Ŧ	nance	Depar	Km Km	16.80 12.24			
	vii) 12" (300 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	63.75 11.70 7.30 71.65 126.83 60.08 46.21			
	4th Km				Km	32.33			
	5th Km				Km	30.03			
	6th Km				Km	29.51			
	7th Km				Km	27.42			
	8th Km				Km	27.11			

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY, 20	012) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	25.42	•		
	10th Km 11th Km & subsequent Kms				Km Km	23.61 17.19			
	viii) 14" (350 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	82.95			
	2nd chain (2nd 30 m)				30 M	15.25			
	3rd to 10th chain (60 to 300 m)				30 M	9.50			
	1000 to 3000 ft. (300 to 900 m)				300 M	93.30			
	1st Km				Km	165.08			
	2nd Km				Km	78.19			
	3rd Km				Km	60.14			
	4th Km				Km	42.08			
	5th Km		1	\mathcal{O}	Km	39.08			
	6th Km				Km	38.40			
	7th Km				Km	35.70			
	8th Km	US -	N-lis	(کومت	Km	35.30			
	9th Km	1			Km	33.07			
	10th Km 11th Km & subsequent Kms	185			Km Km	30.82 22.45			
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-	The second secon	nance	Depar	. 331. 6 5 5. 1.				
	i) 2'' (50 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	4.20			
	2nd chain (2nd 30 m)				30 M	0.75			
	3rd to 10th chain (60 to 300 m)				30 M	0.50			
	1000 to 3000 ft. (300 to 900 m)				300 M	4.70			
	1st Km				Km	8.36			
	2nd Km				Km	3.97			
	3rd Km				Km	3.06			
	4th Km				Km	2.13			
	5th Km				Km	1.96			
	6th Km				Km	1.93			
	7th Km				Km	1.81			
	8th Km				Km	1.78			

	MRS, BI-ANNUAL PI	ERIOD (1st FE	EBRUARY	2012 TO 31	st JULY, 20)12) DIST	RICT LODH	RAN	
Sr.	Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.	-				Unit of M/ment	Labour	Composite	No.	
							F		
	9th Km				Km	1.67			
	10Km				Km	1.57			
	11th Km & subsequent Kms ii) 2½" (63 mm) i/d pipes:-				Km	1.17			
	1st chain (1st 30 m)				30 M	6.55			
	2nd chain (2nd 30 m) 2nd to 10th chair (60 to 200 m)				30 M 30 M	1.20 0.75			
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				300 M	7.35			
	1st Km				Km	13.02			
	2nd Km 3rd Km				Km Km	6.20 4.78			
	4th Km		/ ×	\sum	Km	3.36			
	5th Km	/			Km	3.13			
	6th Km				Km	3.07			
	7th Km	199			Km	2.84			
	8th Km	N.	1.54	الطوميت	Km	2.61			
	9th Km	100			Km	2.55			
	10Km	and a			Km	2.38 1.80			
	11th Km & subsequent Kms iii) 3'' (75 mm) i/d pipes:-	Fin	iance	Depar	Km	1.80			
	1st chain (1st 30 m)				30 M	9.05			
	2nd chain $(2nd 30 m)$ 2nd to 10th chain $(60 to 200 m)$				30 M 30 M	1.65			
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				300 M	1.05 10.20			
	1st Km				Km	18.02			
	2nd Km 3rd Km				Km Km	8.56 6.60			
	4th Km								
					Km	4.62			
	5th Km				Km	4.27			
	6th Km				Km	4.20			
	7th Km				Km	3.91			
	8th Km				Km	3.87			
	9th Km				Km	3.53			
	10th Km				Km	3.29			

	I	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 3 1	st JULY, 20)12) DIST	RICT LODH	RAN	
Sr.		Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.		_				Unit of M/ment	Labour	Composite	No.	
		11th Km & subsequent Kms				Km	2.48			
	iv)	4" (100 mm) i/d pipes:-								
		1st chain (1st 30 m)				30 M	15.00			
		2nd chain (2nd 30 m)				30 M	2.75			
		3rd to 10th chain (60 to 300 m)				30 M	1.70			
		1000 to 3000 ft. (300 to 900 m)				300 M	16.85			
		1st Km				Km	29.83			
		2nd Km				Km	14.12			
		3rd Km				Km	10.87			
		4th Km				Km	7.60			
		5th Km				Km	7.05			
		6th Km		1	5	Km	6.93			
		7th Km		(1	Km	6.50			
		8th Km	-100			Km	6.33			
		9th Km	100	0		Km	5.95			
		10th Km	100	1.	1. 1. 20/	Km	5.47			
		11th Km & subsequent Kms	1		Z	Km	4.14			
	v)	5" (125 mm) i/d pipes:-		~~~???	200					
		1st chain (1st 30 m)	05	nance	Depart	30 M	22.40			
		2nd chain (2nd 30 m)			20.000.0000	30 M	4.10			
		3rd to 10th chain (60 to 300 m)				30 M	2.55			
		1000 to 3000 ft. (300 to 900 m)				300 M	25.20			
		1st Km				Km	44.59			
		2nd Km				Km	21.11			
		3rd Km				Km	16.24			
		4th Km				Km	11.36			
		5th Km				Km	10.54			
		6th Km				Km	10.36			
		7th Km				Km	9.65			
		8th Km				Km	9.54			
		9th Km				Km	8.94			
		10th Km				Km	8.22			
		11th Km & subsequent Kms				Km	6.14			
	vi)	6" (150 mm) i/d pipes:-								
										I

	MRS, BI-ANNUAL P	ERIOD (1st FEBRU	JARY, 2012 TO 31	O 31st JULY, 2012) DISTRICT LODHRAN						
Sr.	Description			Rate	e (Metric Sys	stem)	Spec.	Remarks		
No.				Unit of			No.			
				M/ment	Labour	Composite				
	1st chain (1st 30 m)			30 M	32.30					
	2nd chain (2nd 30 m)			30 M	5.95					
	3rd to 10th chain (60 to 300 m)			30 M	3.70					
	1000 to 3000 ft. (300 to 900 m)			300 M	36.30					
	1st Km 2nd Km			Km Km	64.22 30.42					
	3rd Km			Km Km						
					23.40					
	4th Km			Km	16.38					
	5th Km			Km	15.20					
	6th Km			Km	14.94					
	7th Km			Km	13.89					
	8th Km			Km	13.73					
	9th Km	/		Km	12.86					
	10th Km			Km	11.95					
	11th Km & subsequent Kms	/	A COLOR	Km	8.80					
22	Hand shunting loaded Railway wagons or			1.						
	trucks:-	100		- U.						
	a) upto ¼ mile / ¼ Km	18X	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	Each	135.75					
	b) upto ¹ / ₂ mile / ¹ / ₂ Km	AND THE	JOHL AND AND	No	245.75					
	c) upto ³ / ₄ mile / ³ / ₄ Km	1 189	67	122	331.80					
	d) upto 1 (1.6 Km) mile	123	- 10 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	and Q. B.	394.80					
	e) 2nd mile and subsequent miles/	A STR		Each						
	2nd and subsequent kilometres	and the second se	24	No/Km	249.05					
23	Hand shunting empty Railway wagons or trucks.									
		Finan	ce Depar	tmant						
	a) upto $\frac{1}{4}$ mile / $\frac{1}{4}$ Km		- and the second s	Each	78.75					
	b) upto $\frac{1}{2}$ mile $\frac{1}{2}$ Km			No.	130.45					
	c) upto ¾ mile / ¾ Km d) upto 1 mile / 1 Km				172.05 206.55					
	 d) upto 1 mile / 1 Km e) 2nd mile and subsequent miles/ 			Each	200.33					
	2nd and subsequent kilometres			No/Km	122.30					
	2nd and subsequent knomenes			110/1111	122.30					

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

Sr.	Description	R	ate (British Sy	vstem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laoding or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	285.10		cu.m	100.70			
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-			*					
	a) Bricks 10" (250 mm) size.	1000 Nos.	356.40	0	1000 Nos.	356.40			
	b) Bricks 9" (225 mm) or smaller size.	ditto	285.10		ditto	285.10			
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	356.40	مربع من برا مربع من برا	100 Bags	356.40			
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	34.20	7 C	100 Nos.	34.20			
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	213.85	: Depai	100 Kg	5.75			
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	171.05		Per Tonne	168.35			
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	21.40		Each	21.40			
8 9	Loading or unloading packages of all sorts, upto one Cwt (50 Kg). Loading or unloading sleepers other than wooden,	Each	10.70		Each	10.70			Except cement in jute or paper bags.
	including stacking lead within one chain:-	100 Nos.	712.80		100 Nos.	712.80			
	a) Broad gauge sleepersb) Metre gauge and narrow gauge sleepers.	ditto	356.40		ditto	356.40			
0	Loading or unloading timber logs or timber for shuttering, into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Per Ton	89.10		Per Tonne	87.70			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	R	Rate (British Sy	vstem)	Ra	ate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	855.35		100 Kg	22.9						
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	142.55		Per Tonne	140.30						
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	105.50		cu.m	37.25						
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	136.85		cu.m	48.35						
15	Unloading oil, bitumen tar, etc.			*)								
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	356.40		100 litres	7.85						
	b) Crude oil (drained by gravity).	1000 Gallon	356.40		100 litres	7.85						
	c) Crude oil materials from railway wagons.	100 Cft.	45.60	مطومت بخل	cu.m	16.10						
	 Fuel oil from tank into empty drums, including stacking within one chain (30 m). 	Per Ton	126.70	R G	Per Tonne	124.70						
	e) Petrol (2 gallon tin)	100 Nos.	179.65		100 Nos.	179.65			The rate includes checking			
16	 f) Kerosine oil (4 gallon tin) Removing and stacking within one chain (30 m) lead: 	100 Nos.	356.40		100 Nos.	356.40			and weighing the tins.			
	 a) Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc. 	100 Cft.	142.55		cu.m	50.35						
	b) Bricks.	1000 Nos.	380.15		1000 Nos.	380.15						
	c) Broad gauge wooden sleepers.	100 Nos.	228.1		100 Nos.	228.1						
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	135.75		100 Nos.	135.75						
	e) Rails girders, pipes, cement etc.	Per Ton	63.35		Per Tonne	62.35						
	f) Bridge and crossing timbers, etc.	100 No.	760.30		100 No.	760.30						
	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	142.55		Per Tonne	140.30						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	F	ate (British Sy	/stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	81.45		Per Tonne	80.20							
	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	570.25		100 Nos.	570.25							
	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	271.55		100 Nos.	271.55							
	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	285.10	*)	100 Nos.	285.10							
	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	150.05		100 Nos.	150.05							
	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	1140.50		100 Nos.	1140.50							
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	570.25	(حکومہ سے بیڈی	100 Nos.	570.25							
	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	85.55	de la compañía de la	Per Tonne	84.20							

Finance Department

3. EARTHWORK (EXCAVATION & EMBANKMENT)

1 Special allowances for the hardness, wetness and slush:-

The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.

- 2 Deduction for shrinkage from bank measurements:-
 - The following allowances should be provided for material which is not rammed, or equally consolidated:-
 - a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour...... 10%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description		Rate (British Sy	stem)		ate (Metric S	System)	Spec.	Remarks	
No.		Unit of M/ment	Labour *	Composite	Unit of M/ment	Labour	Composite	No.		
1	Earthwork excavation underessed lead upto a single throw		****					171 to 17.5		
	of Kassi, phaorah or shovel:-	120			Ni.					
	a) In ashes, sand, soft soil or silt clearance.	1000 Cft.	1,069.20		cu.m	37.75				
	b) In ordinary soil.	1000 Cft.	1,283.05	5	cu.m	45.30				
2	Earthwork excavation in ashes, sand and soft soil or silt	1000 Cft.	1,568.15	-///	cu.m	55.40		ditto		
	clearance, undressed lead upto 50 ft (15 metre).	~~~~	SP	S. G. ²⁸						
3	Bed clearance and dressing slopes of drains to required							ditto	The rate is applicable where the earth	
	sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead.	2.83	tance 9	Departi	nent				of the bed to be removed is of the type of ordinary soil. When it is silt or	
	a) Excavated material undressed.	1000 Cft.	1,995.85		cu.m	70.50			1 or 2 above, whichever is applicable.	
	b) Excavated material dressed in the specified manner.	1000 Cft.	2,153.80		cu.m	76.05			the drains of each category.	
4	Borrowpit excavation undressed lead upto 100 ft (30 metre).									
	a) Ordinary soil b) Hard soil	1000 Cft. 1000 Cft.	1,995.85		cu.m	70.50 86.60				
	b) Hard soli	1000 Cit.	2,452.05		cu.m	80.00				
5	Earthowrk in ordinary soil for embankments lead upto 100							*411-1 to	The rate includes hire charges of	
	ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and							411-13 and 301-1 &	machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also	
	compaction by mechanical means at optimum moisture							202-3	includes clearing and grubbing	
	content and dressing to designed section, complete in all								where necessary.	
	respects:- i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.	2,173.65	3.075.15	cu.m	76.75	108.60			
	ii) 90% maximum modified AASHO dry density.	1000 Cft.	2,173.65	2,959.90	cu.m	76.75	104.55			
	iii) 85% maximum modified AASHO dry density.	1000 Cft.	2,173.65	2,844.65	cu.m	76.75	100.45	* 411.0		
6	Regular excavation dressed.	1000 Cft.	1,461.50		cu.m	51.60		*411-2		
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m)							17.1 to		
	depth for storm water channels, drains, sullage drains in							17.5		
	open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and									
L	wans and shoring to protect existing works, shuttering and								1	

	MRS, BI-ANNUAL PERI	OD (1st Fl	EBRUARY, 2	2012 TO 31st	JULY, 2	012) DIST		RAN	
Sr.	Description		Rate (British Sy	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	 timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 50 ft. (15 m) lead:- i) ordinary ii) hard iii) very hard iv) gravel & shingle 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,483.70 2,939.90 3,424.60 5,764.70	2,554.35 3,010.55 3,495.25 5,835.35	cu.m cu.m cu.m cu.m	87.70 103.85 120.95 203.60	90.20 106.35 123.45 206.10		
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to 10.0 ft. (3.0 mm) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 100 ft. (30 m) lead:- i) ordinary ii) hard iii) very hard iv) gravel & shingle	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,710.75 3,166.95 3,651.65 6,276.85	2,851.30 3,307.50 3,792.20 6,417.40	cu.m cu.m cu.m	95.75 111.85 129.00 221.70	100.70 116.80 133.95 226.65	ditto	
	 Excavation in shingle or gravel formation and rock, not requiring blasting, undressed lead upto 100 ft (30 m). i) Dry ii) Wet iii) In flowing water 	1000 Cft. 1000 Cft. 1000 Cft.	5,417.30 6,272.65 7,983.35	Dep <u>i</u> arts 	cu.m cu.m cu.m	191.35 221.55 281.95	 	17.1 to 17.5	
10	Earthwork excavation in irrigation channels, drains, etc. to designed section, grades and profiles, excavated material disposed off and dressed within 50 ft. (15 m) lead:-							ditto	
1.	 i) ordinary ii) hard iii) very hard iv) gravel & shingle 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,283.05 2,739.25 3,223.95 5,706.60	 	cu.m cu.m cu.m	80.65 96.75 113.85 201.55	 		
	 Excavation in rock dressed to designed section, grades and profiles, excavated material disposed off within 100 ft. (30 m) and lift upto 5'-0" (1.5 m). a) Soft rock, slate, shale, schist laterite work, with pick and 	1000 Cft.	5,425.75		cu.m	191.65		17.1 to 17.5	Tools and plants shall be the liability of the contractor.
	crow bar.b) Medium hard rock, requiring occasional blasting.	1000 Cft.	8,478.90	9,054.90	cu.m	299.50	319.80		
12	 a) Excavation in hard rock requiring blasting and disposal of excavated material (blasted material) upto 50 ft. (15 m) lead, (including dressing and levelling to designed section, etc. complete). 								1) Tools and plants required shall be the liability of the Contractor
	i) Grade I	1000 Cft.	5,136.90	5,712.90	cu.m	181.45	201.80		2) Reduce the rate by 8% if the excavated section is not dressed or

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British Sy	stem)		ate (Metric S	System)	Spec.	Remarks		
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
	ii) Grade II	1000 Cft.	5,567.25	6,527.25	cu.m	196.65	230.55		levelled to designed section.		
	iii) Grade III	1000 Cft.	6,640.15	7,792.15	cu.m	234.55	275.20				
	iv) Grade IV	1000 Cft.	7,356.60	8,700.60	cu.m	259.85	307.30				
	v) Grade V vi) Grade VI	1000 Cft. 1000 Cft.	8,141.75 8,715.70	9,677.75 10,443.70	cu.m cu.m	287.55 307.85	341.80 368.85				
	VI) Glade VI	1000 Cit.	8,715.70	10,443.70	cu.m	507.85	508.85				
	 b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50 ft. (15 m) lead (including dressing and levelling to designed section, etc. complete):- 							17.1 to 17.5	1) Tools and plants required shall be the liability of the contractor.		
									2) Reduce the rate by 8% if the		
	i) Grade I	1000 Cft.	10,273.80	11,425.80	cu.m	362.85	403.55		excavated section is not dressed or		
	ii) Grade II	1000 Cft.	11,134.45	13,054.45	cu.m	393.25	461.10		levelled to designed section.		
	iii) Grade III	1000 Cft.	13,280.25	15,584.25	cu.m	469.05	550.45				
	iv) Grade IV	1000 Cft.	14,713.25	17,401.25	cu.m	519.65	614.60				
	v) Grade V	1000 Cft.	16,283.55	19,355.55	cu.m	575.15 615.70	683.65 737.75				
	vi) Grade VI	1000 Cft.	17,431.40	20,887.40	cu.m	015.70	131.15				
13	Rehandling of earthwork:			-							
	a) Lead upto a single throw of Kassi, phaorah or shovel	1000 Cft.	712.80	<u>=</u>	cu.m	25.20		ditto			
	b) Upto a lead of 50 ft. (15 m).	1000 Cft.	997.90	6-19	cu.m	35.25					
		1000 60		C. Car		100 50		151.155			
14	Rehandling of gravel work or excavated rock,	1000 Cft.	2,851.20		cu.m	100.70		17.1 to 17.5			
	lead upto 50 ft.(15 m)	110	tance 9	Departs	nent-						
15	Filling, watering and ramming earth under floors:-							ditto			
	i) with surplus earth from foundation, etc.	1000 Cft.	1,427.70		cu.m	50.45					
	ii) with new earth excavated from outside,	1000 Cft.	2,742.00		cu.m	96.85					
	lead upto one chain (30 m).		,								
16	Extra for every 50 ft. (15 m) additional lead or part thereof :-								This rate shall be applicable upto		
									1000 ft. total distance, including the		
	i) for earhtwork soft, ordinary, hard and very hard.	1000 Cft.	24.40		cu.m	0.85			lead covered in the item of earthwork		
	ii) for gravel, shingle or rock.	1000 Cft.	28.30		cu.m	1.00					
17	Transportation of earth all transportion the total distance								This rate will be paid inaddition to the		
17	Transportation of earth all types when the total distance, including the lead covered in the item of work, is more than								This rate will be paid inaddition to the rate of earthwork, without deducting		
	1000 ft. (300 m)								the lead covered in the item of		
	a) upto $\frac{1}{4}$ mile (400 m).	1000 Cft.	1,150.50		cu.m	40.65			earthwork		
	b) for every 330 ft. (100 m) additional lead or part thereof,		, 0								
	beyond ¼ mile (400 m) upto one mile. (1.6 Km.)	1000 Cft.	102.25		cu.m	3.60					
	c) for every ¹ / ₄ mile (400 m) additional lead or part thereof,										
	beyond one mile (1.6 Km.) upto 5 mile (8 Km).	1000 Cft.	149.15		cu.m	5.25					
	d) for every $\frac{1}{2}$ mile (800 m) additional lead	1005									
	or part thereof, beyond 5 miles (8 Km).	1000 Cft.	131.10		cu.m	4.65					
18	Dressing and levelling of earhtwork to designed section, etc. complete:-							17.10 to 17.5			
	· · · · · · · · · · · · · · · · · · ·	1				I					

	MRS, BI-ANNUAL PERIO	DD (1st Fl	EBRUARY, 2	2012 TO 31st	JULY, 2	012) DIST	FRICT LODH	RAN	
Sr.	Description	1	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	 a) Ashes, sand, silt or soft soil. b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting. 	1000 Cft. 1000 Cft. 1000 Cft.	91.65 177.85 427.70		cu.m cu.m cu.m	3.25 6.30 15.10			
19	Dowel dressing.	Per Chain	83.60		Metre	2.75		ditto	This rate is in addition to payment for dressed earhtwork.
20	a) Dressing slopes of banks or ground surface.	100Sft.	37.30		sq.m	4.00		ditto	To be paid only when exclusively dressing is done and no earthwork is carried out in embankment or cutting.
	 b) Dressing of earthwork (done by machinery or otherwise and left undressed) to designed section. 	100Sft.	67.00		sq.m	7.20			i) The surface area dressed is to be taken for measurement.
21	Excavation in foundation of building, bridges and other structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and rammiing lead	- All Contraction						17.1 to 17.5	ii) The item is applicable where the dressing is done by the contractor other than the one who executed the work.
22	 upto one chain (30 m) and lift upto 5 ft. (1.5 m) a) in sand, ashes or loose soil b) in ordinary soil. c) in hard soil or soft murum. Cutting hard rock such as granite, ballast, hard lime stone or sand stone, etc. with chisels and hammers, for small foundations. 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,568.20 2,996.95 3,353.85 20,202.35	 Dep[prin 23,961.30	cu.m cu.m cu.m cu.m	90.70 105.85 118.45 713.55	 846.30	17.1 to 17.5	Tools and plants required shall be the liability of the contractor.
23 24	Extra for excavation requiring shoring. Compaction of earthwork (soft, ordinary or hard soil) :-	1000 Cft.	357.70	594.25	cu.m	12.65	21.00	17.1 to 17.5 ditto	Composite rate includes materials, i.e. plank, etc.
24	 a) Mixing, moistening earth to optimum moisture content in layers for compaction, etc. complete. 	1000 Cft.	335.15		cu.m	11.85		ditto	
	 b) Compaction by rolling with animal driven roller/hand rammed: 								
	i) soft or sandy soil	1000 Cft.	427.70		cu.m	15.10			1) The rote does not in the de him
	ii) ordinary soil	1000 Cft.	498.95		cu.m	17.60			 The rate does not include hire charges of the roller. Paller to be 'sumplied by
	iii) hard soil	1000 Cft.	570.25		cu.m	20.15			2) Roller to be 'supplied by Government
	iv) admixture of shingle	1000 Cft.	641.50		cu.m	22.65			
	c) Ramming earthwork (all types of soil).	1000 Cft.	427.70		cu.m	15.10			

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUARY, 2	2012 TO 31st	JULY, 2	012) DIST		RAN	
Sr.	Description		Rate (British Sy	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
25	 Ramming earhtwork behind retaining walls. Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture 	1000 Cft.	570.25		cu.m	20.15		17.1 (a)	The rate also includes hire charges of
	content in layers, etc. complete:i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.		901.50	cu.m	-	31.85	202-3	machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		786.25	cu.m	-	27.75		
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.	- ×	671.00	cu.m	-	23.70		
26	Extra for wet earthwork.	1000 Cft.	997.90	/ - \	cu.m	35.25	-	17.1 to 17.5	That will support a man's weight.
27	Extra for slush or Daldal including dewatering.	1000 Cft.	2,280.95		cu.m	80.55	-	17.1 to 17.5	That will not support a man's weight.
28	Extra for puddling.	1000 Cft.	1,782.00		cu.m	62.95	-	ditto	
29	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	270.85		Metre	8.90	-	ditto	
30	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.(15 m).	1000 Cft.	2,566.10		cu.m	90.65		17.1 to 17.5	
31	Dag bailing 3" (75 mm) deep.	Per mile	1,061.60	Departs 	Per Km	659.80		ditto	Dag bailing for layout of borrow pit, to be done by contractors at their own cost.
32	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	475.20		sq.m	51.15		ditto	
33	Berm cutting:-							17.1 to 17.5	
	 a) lead upto a single throw of Kassi, phaora or shovel (without dressing). 	1000 Cft.	1,283.05		cu.m	45.30			
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	2,283.05		cu.m	80.65			
34	Berm trimming both sides of channels:-							17.1 to 17.5	
	a) upto 3½ ft. (1.06 m) depth.	Per Mile	3,329.90		Per Km.	2081.20			
	 b) exceeding 3½ ft. to 5 ft. (1.06 to 1.5 m) depth. c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth 	Per Mile Per Mile	4,640.25 7,255.60		Per Km. Per Km.	2900.15 4534.75			
35	Ploughing and levelling borrowpits.							ditto	Area ploughed to be measured.
	 i) upto 3 ft. (0.9 m) depth. ii) above 3 ft. (0.9 m) depth. 	Per Acre Per Acre	712.80 1,425.60		Per Hect. Per Hect.	1761.35 3522.75			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
		Wi/ment	Labour	Composite	Wi/ment	Labour	Composite				
36	Making boundary or service roads, including dag-belling, levelling and dressing:							ditto			
	i) in unploughed land:										
	 a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide. 	Per Chain Per Chain	357.30 476.95		Metre Metre	11.70 15.65					
	ii) in ploughed land:										
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide.b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	369.75 489.45		Metre Metre	12.15 16.05					
37	Earthwork by boats, including hire of boats:-	/						17.1 to 17.5	For ordinary soil.		
	 i) Digging and loading into boats, upto 50 ft. (15 m) lead. ii) Carriage by boats upto 10 chains (300 m). iii) Extra for every additional one chain (30 m) or part 	1000 Cft. 1000 Cft. 1000 Cft.	2,138.40 536.05 57.00	Ì	cu.m cu.m cu.m	75.55 18.95 2.00	 				
	thereof beyond 10 chains (300 m).iv) Unloading earth from boats.	1000 Cft.	997.90		cu.m	35.25					
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	855.35	R G S	cu.m	30.20		17.1 to 17.5			
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	1,995.85	Dep <u>a</u> rts	cu.m	70.50		17.1 to 17.5			
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	1,603.80		cu.m	56.65		ditto			
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	280.00	300.00	cu.m	98.90	105.95		The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.		
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface								The rate does not include back filling after laying of sewer, which is payable separately.		
	 water, in all types of soil except shingle, gravel and rock:- i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth iii) above 15.0 ft. (4.5 m) depth 	1000 Cft. 1000 Cft. 1000 Cft.	2,314.00 3,930.30 5,070.80	2,661.60 4,446.75 5,587.20	cu.m cu.m cu.m	81.75 138.80 179.10	94.00 157.05 197.35		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.		
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to							17.1 to 17.5 **13.3 &	The rate does not include back filling after laying of sewer, which is payable		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit of		, ,	Unit of		•	No.				
		M/ment	Labour	Composite	M/ment	Labour	Composite					
	correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:							13.5	separately.			
	i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL.	1000 Cft.	3,224.10	5,677.65	cu.m	113.90	200.55					
	ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL.	1000 Cft.	4,030.70	7,226.30	cu.m	142.35	255.25					
	iii) Exceeding 8 ft. (2.4 m) depth below SSWL.	1000 Cft.	6,046.05	9,514.60	cu.m	213.55	336.05					
44	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	2,139.45	-	cu.m	75.55		17.1 to 17.5 **8.1	The rate does not include back filling after laying of pipe line, which is payable separately.			
45	Cutting and removing trees within a distance of 100 ft. (30 m)											
	 a) upto 2½ ft. (760 mm) girth. b) above 2½ ft. to 6 ft. (760 to 1800 mm) girth. 	Each Each	410.85 803.55		Each Each	410.85 803.55						
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	534.60		Each	534.60						
47	Jungle clearance and removing within 100 ft. (30 m).		SÐ	S. C. C.	-							
	a) light b) thick	1000 Sft. 1000 Sft.	71.30 142.55	Dep <u>t</u> arts	sq.m sq.m	0.75 1.55						
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	34.20		sq.m	3.70						
49	Ploughing 3 times.	Per Acre	289.60		Per Hect.	715.55						
50	Levelling, dressing and making lawns.	100Sft.	142.55		sq.m	15.35						
51	Turfing lawns (excluding cost of turf).	100Sft.	118.80		sq.m	12.80						
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry,wet slush,daldal and under water) including its disposal and prepartion of working pad for operation of machinery. (Rates includes 100 ft lead)	1000 Cft.		2028.00	cu.m		71.65					

* Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 ** Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	<u>Stone Work</u>										
1	Dismantling dry stone masonry.	100Cft.	242.35		cu.m	85.60		18.1			
2	Dismantling stone masonry in mud mortar.	100Cft.	356.40		cu.m	125.90		ditto			
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	855.35	Č,	cu.m	302.10		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.		
4	a) Dismantling dry stone or spawl pitching.	100Cft.	427.70		cu.m	151.05		ditto			
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	541.75	1. 6	cu.m	191.35		ditto			
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	712.80		cu.m	251.75		ditto			
6	Dismantling stone pitching, cement or lime grouted.	100Cft.	1,140.50	a Brann a	cu.m	402.85		ditto			
7	Dismantling stone in crates:		rmanc	e svepa	TIME:	nı					
	a) wooden crates	100Cft.	570.25		cu.m	201.40					
	b) wire crates	ditto	712.80		ditto	251.75					
8	Dismantling stone ware drain including base concrete.	100Cft.	399.15		cu.m	141.00		ditto			
	Brick Work										
9	Dismantling mud/pise walling.	100Cft.	142.55		cu.m	50.35		18.1			
10	Dismantling sun dried brick masonry.	100Cft.	356.40		cu.m	125.90		ditto			
11	Dismantling dry brick masonry.	100Cft.	242.35		cu.m	85.60		ditto			
12	Dismantling brick work in mud mortar.	100Cft.	498.95		cu.m	176.25		18.1	Add extra 13%, 32% and 51% on		
13	Dismantling brick work in lime or cement mortar.	100Cft.	1,211.75		cu.m	428.00		ditto	labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 12, 13, 14 & 15.		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	Dismantling cement block masonry. Dismantling Dhajji walling.	100Cft. 100Cft.	1,069.20 285.10		cu.m	377.65 100.70		ditto ditto			
15		IUUCII.	285.10		cu.m	100.70		anto			
	<u>Concrete</u>										
16	Dismantling mud concrete.	100Cft.	570.25		cu.m	201.40		ditto			
17	Dismantling lime concrete.	100Cft.	784.10		cu.m	276.95			Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th		
18	Dismantling lime or cement concrete, under water.	100Cft.	2,993.75		cu.m	1057.40			and subsequent floors respectively against item No. 17, 19 & 20.		
19	a) Dismantling cement concrete plain	100Cft.	1,568.15	*)	cu.m	553.85		ditto			
	1:4:8.b) Dismantling cement concrete plain1:3:6.	ditto	2,566.10		ditto	906.35					
	c) Dismantling cement concrete 1:2:4	ditto	3,136.30		ditto	1107.75					
	plain.d) Dismantling cement concrete with brick	ditto	855.35		ditto	302.10					
	 aggregate. Dismantling D.P.C. of cement concrete 1¹/₂" thick (40 mm) and clearing the site. 	ditto	427.70	مكرمت بنجا ا	ditto	151.05					
20	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100Cft.	5,132.15	e Depa	cu.m	1812.70		ditto			
	Roofing										
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or ballies.	100Sft.	171.05		sq.m	18.40		18.1			
22	a) Dismantling 1st class tile roofing.	100Sft.	427.70		sq.m	46.00			Add extra 13%, 32 and 51% on		
	b) Dismantling 2nd class tile roofing.	100Sft.	356.40		sq.m	38.35		ditto	labour rate only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 22, 25, 26 and 28.		
	Dismantling from any height, asbestos sheets and ridge coping.	100Sft.	214.35		sq.m	23.05		18.1			
24	 Dismantling roof of wooden planks and battens, from any height. 	100Sft.	172.15		sq.m	18.5		ditto			
	b) Dismantling wooden ceiling above 20' (6.0 m) height	100Sft.	687.45		sq.m	73.95		ditto			

	MRS, BI-ANNUAL	PERIOD (1	Ist FEBRUA	RY, 2012 TO	31st JU	LY, 2012)	DISTRICT L	ODHRAN	-
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in difficult position, including lifting with care and special scaffolding along live electric wires and with machines underneath.								
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	570.25		sq.m	61.35		ditto	
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	712.80		sq.m	76.70		ditto	
27	a) Stripping and stacking slate or tiles from the truss roofing.	100Sft.	356.40		sq.m	38.35			
	b) Stripping and stacking C.I. sheet roof.	ditto	319.60	~	ditto	34.40			
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	361.70		ditto	38.90			
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	570.25	liter and she	sq.m	61.35		18.1	
	Flooring				63				
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	242.35	e Deno	sq.m	26.10		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively
30	Dismantling plank or wooden block flooring, etc.	100Sft.	356.40	er	sq.m	38.35		ditto	against items No. 29 and 30.
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-								i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.
	 a) 6" to 12" (150 to 300 mm) diameter b) 13" to 24" (325 to 600 mm) diameter c) 25" to 36" (625 to 900 mm) diameter d) Above 36" (Above 900 mm) diameter 	Per Lft Per Lft ditto ditto	9.45 15.15 17.75 25.25		Metre Metre ditto ditto	31.00 49.70 58.20 82.80			ii) Bends, elbows, sluice valves, etc. should not be paid for extra if fixed in the length of pipe line that is being dismantled.
32	a) Removing door with chowkat.	Per	118.45		Per	118.45		18.1	Add extra 13%, 32% and 51% on
	b) Removing windows and sky lights with chowkat.	No. ditto	91.30		No. ditto	91.30			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
33	Removing ventilators and wooden sunshade, etc.	Per No.	48.50		Per No.	48.50		ditto				
34	a) Dismantling wooden beams upto 12' (3.65m) length.	Per No.	89.10		Per No.	89.10		ditto				
	 b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length. 	ditto	142.55		ditto	142.55						
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	153.70		sq.m	16.55		ditto				
	b) Dismantling wooden trusses.	100Kg	497.50		%Kg	497.50						
36	Dismantling wooden palisade fencing.	Per Lft.	12.00	*	Metre	39.35		ditto				
	Iron work			9								
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	469.85		%Kg	469.85		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.			
38	Dismantling rolled steel beams or iron rails, etc.	100Kg	234.00	فكومت بنجا	%Kg	234.00		ditto				
39	Dismantling iron latrine.	Per Unit/ 2 Seats	500.00	98 G	Per Unit/ 2 Seats	500.00		ditto				
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per	9.95	e Depa	Each per cm bore	4.00		ditto				
41	a) Dismantling B.G. water column.	Each	3,474.90		Each	3474.90		ditto				
	b) Dismantling M.G. or N.G. water column.	Each	2,288.55		Each	2288.55		ditto				
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	242.35		Metre	7.95		18.1				
	Miscellaneous											
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	114.05		sq.m	12.25		18.1				
44	Dismantling cloth ceiling and supporting timber.	100Sft.	213.85		sq.m	23.00		ditto				
45	Dismantling and removing road metalling.	100Cft.	570.25		cu.m	201.40		ditto				
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead	100Cft.	761.25		cu.m	268.85		ditto				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(30 metre).												
47	Removing mud plaster from walls.	100Sft.	59.40		sq.m	6.40		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th				
48	Removing cement or lime plaster.	100Sft.	118.80		sq.m	12.80		ditto	and subsequent floors against item No. 47, 48, 49, & 50 respectively				
49	Scraping:-							18.1					
	a) White wash or colour wash.	100Sft.	71.30		sq.m	7.65							
	 Ordinary distemper, oil bound distemper, or paint of wall. 	ditto	213.85		ditto	23.00							
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	660.00	*)	sq.m	71.00		18.1					
51	Scraping boulders.	100Cft.	997.90	1000	cu.m	352.45		18.1					
52	Cleaning lime or cement mortar of old stones to be used in masonry.	100Cft.	498.95		cu.m	176.25		18.1					
	Electric Wiring	10	14	الكوم مريتي	7.18								
53	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).	Per point	18.05	18.45	Per point	18.05	18.45						
54	Dismantling plug point and making good damaged surface (building portion).	Per point	15.45	15.80	Per point	15.45	15.80						
55	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-												
	i) on surfaceii) recessed in wall	Per foot Per foot	3.30 7.30	3.35 7.45	P.Mtr P.Mtr	10.80 23.95	11.00 24.45						

5. MORTAR

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN Dry Material Required for Dry Material Required for													
		Dry	Material Require	1 for	Dry I	Material Required	1 for						
			ft. Wet (Ready) N	Aortar		um Wet (Ready)							
S. No.	Ratio of Mortar	Cement	Lime	a 1	Cement	Lime	Sand						
		(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.						
1		Вад	Ctt.	Ctt.	Bag.	Cum	0						
	2	3	4	5	6	7	8						
1	Cement : Sand												
	1 : 2	33.48		82	11.83		0.82						
	1:3	23.11		85	8.16		0.85						
	1 : 4	18.37		90	6.49		0.90						
	1 : 5	14.70		90	5.19		0.90						
	1 : 6	13.61		100	4.81		1.00						
	1:7	11.68		100	4.12		1.00						
	1 : 8	10.21		100	3.61		1.00						
2	Cement : Lime : Sand												
	1:1:6	12.25	15.0	90	4.33	0.15	0.90						
	1 : 1 : 7	10.70	13.1	92	3.78	0.13	0.92						
	1:1:8	9.39	11.5	92	3.32	0.12	0.92						
	1 : 1 : 9	8.52	10.44	94	3.00	0.10	0.94						
	1 : 1 : 10	7.67	9.4	94	2.71	0.09	0.94						
	1:2:8	9.19	22.5	90	3.25	0.23	0.90						
	1:2:9	8.16	20.0	90	2.88	0.20	0.90						
	1 : 2 : 10	7.67	18.8	94	2.71	0.19	0.94						
	1 : 2 : 12	6.39	15.66	94	2.26	0.16	0.94						
	1 : 3 : 12	6.26	23.0	92	2.21	0.23	0.92						
	1 : 3 : 14	5.47	20.1	94	1.93	0.20	0.94						
	1 : 3 : 16	4.82	17.7	94	1.70	0.18	0.94						
	$1 : \frac{1}{4} : 3$	23.11	7.0	85	8.16	0.07	0.85						
3	Lime : Sand	Finan	ce Dem	trt w en i									
	1 : 2		43	86		0.43	0.86						
	1 : 3		31	93		0.31	0.93						

5. MORTAR

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN													
	MRS, BI-ANNUAI	PERIOD (st JULY,	2012) DIS						
			Dry Materia					Dry M	aterial Requi	ired for			
S.	Ratio of Mortar	Clay	Lime	(Ready) Mor Sand	tar Surkhi	Cinder	Clay	Lime	Wet (Ready Sand) Mortar Surkhi	Cinder		
No.	Ratio of Mortal	Cituy	(Putty)	Build	Burkin	Cilider	Ciuy	(Putty)	Build	Burkin	Cilider		
		Cft.	Cft.	Cft.	Cft.	Cft.	M	M	M	M	M		
1	2	3	4	5	6	7	3	4	5	6	1		
4	Mud	135					1.35						
5	Lime : Surkhi												
5	2 : 3		49.00	-	73.5		-	0.49	-	0.74	-		
	1:2		40.75	-	81.5		-	0.41	-	0.82	-		
	1:3		30.30	-	91.0		-	0.30	-	0.91	-		
6	Lime : Sand : Surkhi 1 : 1 : 1		40.50	40.5	40.5			0.41	0.41	0.41			
	1:1:1		40.30	1987 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 -	40.3		-	0.41	0.41	0.41			
7	Lime : Cinder			×-									
	1:1		57.0	~	-	57.0	-	0.57	-	-	0.57		
			1										
		Wet material	required for	100 Cft		一以.	Wet materi	al required f	for 1M3 (35	32 (Cft)			
		masonry (incl	AND THE R. L.	and the second se	and the second division of the second	787		ncluding was		52 CH)			
		ંત				I Nielo	2	U	0 /				
1	Brick Masonry :	1	7.18	See Lin	.67	1. H.S.			1				
	a) Mud Mortar		35.00					0.35	M ³ M ³				
	b) Cement, Sandc) Cement, Lime (Putty) Sand		25.00	Cft Cft	-40	E .		0.25 0.25	M M ³				
	d) Lime (Putty) Sand		25.00					0.25	M ³				
	2)												
2	Stone Masonry :		Finas	rce D	evari								
	a) Random rubble, uncoursed							0.45	1 (2)				
	i) Foundation and Plinthii) Superstructure		45.00 40.00	Cft Cft				0.45 0.40	M ³ M ³				
	iii) Coursed		40.00 35.00	Cft				0.40	M				
	b) Ashlar Block in course or Sca	bled masonry	30.00					0.30	M^3				
	c) Ashlar fine masonry	iorea masoni y	20.00					0.20	M^3				
			20.00	CII				0.20	171				
	(1) Cement	1 Cft.	= 40.8233	Kg									
Notes :	(2) Unslaked lime	1.7 Cft.	= 37.3242	-									
	(3) Slaked lime	2.5 Cft.	= 37.3242	Kg									
	(4) Quick lime	40 Kg	Will yie	ld 2.6 Cft. liı	ne putty.								
	· -	0	•										

6. CONCRETE

Notes 1 Notes (1) Rates for all finished works include the removal of surplus debris, unused material and by products.

2 If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Mud concrete in foundation including watering and ramming, using brick or stone ballast 1 ¹ /2" (40 mm) gauge.	100Cft	1575.60	2835.60	cu.m	556.50	1001.55		The stone ballast, crushed bajri, round shingle from nallah, or brick ballast may be used according to		
2	Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50 mm) gauge.	100Cft	1069.20	2257.20	cu.m	377.65	797.25		their comparative cheaper rates in various areas of the Province.		
3	Cement concrete brick or stone ballast 11/2 " to 2" (40 mm to							20.1	-do-		
3	50 mm) gauge, in foundation and plinth:-		R	E C				20.1	-00-		
	(a) Ratio 1: 3: 6	100Cft	2077.35	10268.55	cu.m	733.70	3626.85				
	(b) Ratio 1: 4: 8	ditto	2077.35	8597.65		733.70	3036.70				
	(c) Ratio 1:5:10	ditto	2077.35	7711.10	"	733.70	2723.55				
	(d) Ratio 1: 6:12	ditto	2077.35	7046.55		733.70	2488.85				
	(e) Ratio 1: 6: 18	ditto	2077.35	6286.95	"	733.70	2220.55				
	(f) Ratio 1: 7:20	ditto	2077.35	5976.65	"	733.70	2110.95				
4	Extra on item No. 3 above, for sedimentation tank or filter										
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri,		
									round shingle from nallah, or brick		
	(a) in bed	100Cft	673.20	-	cu.m	237.75	-		ballast may be used according to		
									their comparative cheaper rates in		
_	(b) on slope	ditto	1003.20	-		354.35	-	20.1	various areas of the Province.		
5	Cement concrete plain including placing,							20.1			

	MRS, BI-ANNUAL PERIOD	(1st FEI	BRUARY, 2	2012 TO 31s	t JULY, 2	2012) DIS	STRICT LOI	OHRAN	
Sr.	Description	R	ate (British S	ystem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
6	compacting, finishing and curing complete (including screening and washing of stone aggregate): (a) Ratio 1: 1:2 (b) Ratio 1: 1!½: 1½ (c) Ratio 1: 1½: 3 (d) Ratio 1: 2: 3 (e) Ratio 1: 3: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 6 (h) Ratio 1: 3: 6 (i) Ratio 1: 3: 6 (i) Ratio 1: 4: 8 Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):- (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-	100Cft ditto ditto ditto 100Cft ditto ditto ditto	2820.85 2820.85 2820.85 2820.85 2820.85 2820.85 2820.85 2820.85	22854.85 22194.85 18556.45 17643.25 15540.35 16253.15 14761.10 14103.25 12566.75	cu.m " " cu.m "	996.30 996.30 996.30 996.30 996.30 996.30 996.30 996.30	8072.35 7839.20 6554.15 6231.60 5488.85 5740.60 5213.60 4981.25 4438.60	20.4	 The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring. Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid extra. This item shall not be applicable to factory made units.
	 (1) Type A (nominal mix 1:1:2) (2) Type B (nominal mix 1: 1½: 3) (3) (c) Type C (nominal mix 1: 2: 4) (a)(ii) Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 	Per Cft ditto ditto	63.65 63.65 63.65	311.20 268.75 246.05	cu.m " "	2248.10 2248.10 2248.1	10991.60 9492.25 8690.5		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 2	2012 TO 31s	t JULY,	2012) DIS	STRICT LOD	DHRAN	
Sr. No.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks
INO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
	5(a) (i) above not requiring form work (i.e. horizental								
	shuttering) complete in all respects:-								
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	36.90	254.90	cu.m	1303.30	9003.05		
	(2) Type B (nominal mix 1: 1 ¹ / ₂ : 3)	ditto	36.90	208.75	"	1303.30	7373.05		
	(3) Type C (nominal mix 1: 2: 4)	ditto	36.90	186.00	"	1303.30	6569.50		
	(b) Precast reinforced cement concrete and prestressed								
	reinforced cement concrete in columns, beams, lintels, stair								
	cases, shelves, etc.								
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	47.65	284.90	cu.m	1683.00	10062.65		
	(2) Type B (nominal mix 1:1 ¹ / ₂ : 3)	ditto	47.65	242.15	"	1683.00	8552.75		
	(3) Type C (nominal mix 1: 2: 4)	ditto	47.65	219.70		1683.00	7759.80		
		JUL -			1 U.				
	(c) Erecting and fixing in position, precast cement concrete	感ア			182				
	or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m)	Per Cft	22.50	33.85	cu.m	794.70	1195.60		
	including all charges.	Car -	1.	- 20	49				
		1000		200	5				
	(d) Add extra labour for R.C. concrete in	Per Cft	10.70	2 an	cu.m	377.90	-		
	2nd and subsequent storeys.	Fin	ance (Depart					
7	Providing and casting in situ bored reinforced concrete piles							*851-1	Composite rate shall be reduced by
	with type C concrete (nominal mix 1: 2: 4), using 10% extra							to	Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab
	cement in dry mix, and course sand, including all labour and							851-10	sand and local sand respectively is used.
	material (except the cost of steel reinforcement and its								
	labour for bending and laying in position, etc. which will be								
	paid separately, including, screening & washing of shingle								
	and curing:-								
	i) 18 " (450 mm) dia pile	Per Rft	632.30	910.20	Metre	2073.95	2985.45		
	ii) 20" (500 mm) dia pile	Per Rft	697.30	1040.25	Metre	2287.15	3412.00		
	iii) 22" (550 mm) dia pile	Per Rft	812.85	1210.5	Metre	2666.15	3970.45		
	iv) 24" (600 mm) dia pile	Per Rft	925.75	1419.95	Metre	3036.45	4657.5		
8	Fabrication of mild steel reinforcement bar cage for R.C.C.							*851-5	The rate includes wastage, overlaps,
	bored piles, including cutting, bending, laying in position,								etc. but does not apply to the laps and

	MRS, BI-ANNUAL PERIC	D (1st FE	BRUARY, 2	2012 TO 31s	t JULY,	2012) DIS	STRICT LOI	OHRAN	
Sr.	Description	ŀ	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	welding and fastening, including cost of binding wire and								spiral reinforcement which are specifically shown in the structural / working drawings
	labour charges for binding of steel reinforcement (also includes removal of rust from the bars):-								of piles as per lapping requirements of design.
	(a) plain bars	Per Cwt.	719.40	4141.80	100 kg	1416.15	8153.15		
	(b) deformed bars	ditto	719.40	5393.85	"	1416.15	10617.80		
9	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints							*851.5	The rate includes wastage, overlaps and chairs, etc.
	and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes	/	×						
	removal of rust from bars):-	1.1							
	(a) plain bars	Per Cwt.	179.85	3779.75	100 kg	354.05	7440.45		
	(b) deformed bars	ditto	179.85	5132.75		354.05	10103.85		
10	Precast cement concrete solid or face blocks (1:2:4), including cost of templates.	Per Cft	25.45	145.25	cu.m	898.90	5130.25	20.2	
11	Precast cement concrete hollow blocks (1: 2: 4), including cost of templates and constructing walls thereof.	Per Cft	56.75	135.80	cu.m	2004.40	4796.45	20.2	
12	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	Per Sft	16.50	36.85	sq.m	177.55	396.50	20.1 to 20.4	
13	Extra labour for laying concrete plain or reinforced:								
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	1140.50	-	cu.m	402.85	-		
	(b) for every additional 10'(3 m) height.	100Cft	712.80	-	cu.m	251.75	-		
14	Extra labour for work of weirs, rail or road bridges, syphons, and concreting in superstructure	100Cft	285.10	-	cu.m	100.70	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr. No.	Description	R	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks		
190.		Unit	Labour	Composite	Unit	Labour	Composite	190.			
15	Making reinforced cement concrete spout, including fixing in position (2 ¹ / ₂ ' x 6" x5") (760 mmx150 mm x 125 mm)	Each	206.25	349.00	Each	206.25	349.00	20.4			
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement concrete or stone masonry walls and repairing.	Per hole	495.00	-	Each	495.00	-	20.1			
17	Extra labour for skipping concrete in wells.	100Cft	1667.60	-	cu.m	589.00	-	20.1			
18	Nicking concrete surface: (a) Cement concrete surface (b) Lime concrete surface	100Sft ditto	187.45 61.85		sq.m "	20.15 6.65	-				
19	Preparing, watering and ramming surface for laying concrete (for Headworks only):- (a) Horizontal floor (b) Glacis and crest (c) Inverted filters	100Sft ditto ditto	176.25 258.70 82.50		sq.m "	18.95 27.85 8.90	- -				
20	Fabrication of high tensile steel prestressing cables for prestressed (post tensioned) concrete, including assembling by drawing the H.T. wire through metal spacer plate, inserting in helix core and taping or tying, sheathing in longitudinally welded metal corrugated sheath, positioning , anchorage with male and female set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule, maintaining stressing record and supply the same in the approved proforma to the Engineer-in-charge, making loop at blind end, including all materials required for it, grouting the cable ducts with cement, cutting projected ends and making good recesses, etc., complete in all respects.	100 Kg.	2313.50	28830.75	100 Kg.	2313.50	28830.75	*811-1 to 811-11	The rate includes wastage in cutting and breakage in stressing, etc.		
21	Fabrication of High Tensile steel reinforcement for prestressed (pretension) concrete work, including inserting wire in moulds, providing M.S. shear bars, spacers and lift hooks, male and	100kg	1428.00	27170.85	%kg	1428.00	27170.85		 The rate includes wastage in cutting and breakage in stressing,etc. 		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	female anchorage, tie down, struts, stressing cables, maintaining stress record and supply the same in approved proforma to the Engineer-in-charge, cutting wires and projecting ends and making good recesses, etc., complete in all respects.								 Quantity of H. T. wire will form basis of payment. This item shall not be applicable to factory made units. 		
22	Lifting, transporting and placing precast prestressed concrete B eam, Girder and other members (excluding battens) etc. in Position on the bridge to correct alignment and level, etc. complete		×					*811-1 to 811-11			
23	 i) Beam upto 50 ft. (15 m) length ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length iv) Beam above 100ft. (30m) upto 150ft.(45m) length v) Beam above 150ft. (45m) length Providing and laying foam concrete 3 inch (75 mm) thick, 	100Cft 100Cft 100Cft 100Cft 100Cft Per Sft.	15.40	1085.75 1598.70 2020.50 2575.60 3093.90 46.05	cu.m cu.m cu.m cu.m cu.m	165.70	383.50 564.65 713.65 909.70 1092.75 495.50				
	using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,		SI	Depart.	nent						
24	Providing and fixing 6 in(150 mm). wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-										
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	8.55 7.65			28.05 25.10	114.95 247.00				
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-										

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	F	ate (British S	ystem)	Rat	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	a) On interior surface (without mastic strip)	Per Rft.	6.90	33.40		22.65	109.55				
	b) On exterior surface (with mastic strip)	ditto	6.90	36.30		22.65	119.05				
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on	Per Sft.	7.20	88.55	Sq.m	77.45	952.80				
	expansion joints complete in all respects.				1						
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG.	Per Rft.	2.75	67.10	Metre	9.00	220.10				
	stopper to expansion joint.										
28	Providing embeding 10" (250 mm) wide 1/4" (6 mm) thick	Per Rft.	11.70	53.70	Metre	38.40	176.10				
_	rubber water stopper in expansion joints of R.C.C. roof	1									
	slab complete in all respects.	1.6			\						
		sk E			12						
29	Filling expansion joints with bitumen. sand & saw dust in	Per Rft	11700		P.Metre/						
	ratio 1:2:2.	per inch	1.80	16.35	Per 25 mm	5.90	53.65				
		width			Width						
30	Filling expansion joints with bitumen.	Per Rft.	23.60	9 Carro	Metre	77.40	-				
	6 · 1 · · · · J.	1 Care	ana ma E	Name work	na ana S						
31	Laying asphaltic mixture in expansion joints.	Per Rft.	24.95	Dep <u>art</u> i	Metre	81.85	-		Material to be paid on actuals.		
32	Providing and fixing theremopore (foamed polythene)										
	sheet in horizontal and vertical expansion joints:										
	a) 1" (25 mm) thick thermopore sheet	Per Sft.	3.30	8.00	Sq.m	35.50	86.10				
	b) 1 ¹ / ₂ " (40 mm) thick thermopore sheet	ditto	3.30	12.10	"	35.50	130.20				
33	Providing and laying damp proof course of cement concrete										
	1:2: 4(using cement, sand and shingle), including bitumen										
	coating :-										
	(a) with one coat bitumen and one coat polythene sheet										
	500gauge										

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 2	2012 TO 31s	t JULY,	2012) DIS	STRICT LOD	OHRAN	
Sr.	Description	ŀ	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 1½" thick (40 mm)	100Sft	727.10		sq.m	78.25	364.25		
	ii) 2" thick (50 mm)	100Sft	727.10	3834.30	sq.m	78.25	412.55		
	iii) 3" thick (75 mm)	100Sft	751.30	4837.50	sq.m	80.85	520.50		
	(b) with 2 coats of bitumen:								
	i) 1½" thick (40 mm)	100Sft	727.10	3748.20	sq.m	78.25	403.30		
	ii) 2" thick (50 mm)	100Sft	727.10	4196.45	sq.m	78.25	451.55		
	iii) 3" thick (75 mm)	100Sft	751.30	5199.60	sq.m	80.85	559.50		
34	Providing and laying damp proof course with cement sand	- /		0					
54	plaster and bitumen coating:-	det			111				
	praser and ordiner coaring	18 E			18				
	(a) with one coat of bitumen and one coat of polythene sheet	1.28			12				
	500 gauge :-	A. 17	1.50	-1/	409				
		100	So a	643					
	i) Ratio 1: 4		0	0.2					
	a) ¹ / ₂ " thick (13 mm)	100Sft	690.80	2139.20	sq.m	74.35	230.20		
	b) ¾" thick (20 mm)	100Sft	690.80	2371.25	sq.m	74.35	255.15		
	ii) Ratio 1:3								
	a) ½ " thick (13 mm)	100Sft	690.80	2213.15	sq.m	74.35	238.15		
	b) ³ / ₄ " thick (20mm)	100Sft	690.80	2458.50	sq.m	74.35	264.55		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	690.80	2314.65	sq.m	74.35	249.05		
	b) ³ / ₄ " thick (20 mm)	100Sft	690.80		sq.m	74.35	285.90		
		100010	070.00	2037.13	5 4 .m	74.33	205.70		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4	10000	COD 000	0070.05		74.05	0.55.10		
	a) ½" thick (13 mm)	100Sft	690.80	2370.85	sq.m	74.35	255.10		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	b) ¾" thick (20 mm)	100Sft	690.80	2603.20	sq.m	74.35	280.10					
	ii) Ratio 1:3											
	a) ½ " thick (13 mm)	100Sft	690.80	2445.45	sq.m	74.35	263.15					
	b) ³ / ₄ " thick (20 mm)	100Sft	690.80	2690.80	sq.m	74.35	289.55					
	iii) Ratio 1:2 a) ½ " thick (13 mm)	100Sft	690.80	2629.80	sa m	74.35	282.95					
	b) ³ / ₄ " thick (20 mm)	100Sft	690.80	2996.30	sq.m sq.m	74.35	322.40					
		roobit	070.00	2770.50	54.111	71.55	522.10					
35	Providing and laying vertical damp proof course with cement		-									
	sand plaster and bitumen coating:-	1.6			1							
		sk E			18							
	(a) with one coat of bitumen and one coat of polythene sheet	1 12			1 H.							
	500 gauge:	113	1-6.	- 107	189							
	i) Ratio 1: 4			Z/IA								
	a) ½" thick (13 mm)	100Sft	690.80	2055.95	sq.m	74.35	221.20					
	b) ¾" thick (20 mm)	100Sft	690.80	2288.45	sq.m	74.35	246.25					
		12. 8.12	KALLO Y	vo pres e	192.67 9.8.6-							
	ii) Ratio 1:3											
	a) ½ " thick (13 mm)	100Sft	690.80	2130.35	sq.m	74.35						
	b) ³ / ₄ " thick (20 mm)	100Sft	690.80	2375.65	sq.m	74.35	255.60					
	iii) Ratio 1:2											
	a) ½ " thick (13 mm)	100Sft	690.80	2314.65	sq.m	74.35	249.05					
	b) ¾ " thick (20 mm)	100Sft	690.80	2681.15		74.35						
	(b) with 2 coats of bitumen:-											
	i) Ratio 1: 4											
	a) ½" thick (13 mm)	100Sft	690.80	2370.80	sq.m	74.35	255.10					
	b) ¾" thick (20 mm)	100Sft	690.80	2603.20	sq.m	74.35	280.10					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	1	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ii) Ratio 1:3	100Sft	600.80	2445 10		74.25	262.10					
	a) ½ " thick (13 mm) b) ¾ " thick (20 mm)	100Sft	690.80 690.80	2445.10 2690.45	-	74.35 74.35	263.10 289.50					
	0) % unck (20 mm)	10051	090.80	2090.43	sq.m	74.55	289.30					
	iii) Ratio 1:2											
	a) ½ " thick (13 mm)	100Sft	690.80	2629.55	sq.m	74.35	282.95					
	b) ¾ " thick (20 mm)	100Sft	690.80	2995.90	sq.m	74.35	322.35					
36	Grouting concrete between, the grooves of gates, including	100Cft	3257.10) - \	cu.m.	1150.40	-					
	shuttering.		~~~									
27		10000	102.10		Ante	11.10						
37	Chiesel dressing concrete surface on sides of grooves.	100Sft	103.10		sq.m	11.10	-					
38	Laying and ramming dry ballast or kankar.	100Cft	1158.30		cu.m	409.10	_					
50	Eaging and raining dry bandst of Kankar.	rooen	1130.50	- 19/2	49	409.10						
39	Hoisting and placing in position R.C.C. shelves.	per No.	36.90	Z-123	per No.	36.90	-					
		-	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	2.2	-							
40	Breaking brick ballast, screening and stacking:-	(Tim	an ca b	Devart								
	(a) 2"(50 mm) ring	100Cft.	891.00	un pres el	cu.m	314.70	-					
	(b) 1 ¹ / ₂ "(40 mm) ring	ditto	997.90	-	"	352.45	-					
	(c) 1" (25 mm) ring	ditto	1158.30	-	"	409.10	-					
	(d) Jhama ballast ³ / ₄ "(20 mm) ring	ditto	1336.50	-	"	472.05	-					
41	Supplying and fixing broken glasses on court yard walls,	Per Rft	27.85	68.05	matra	91.35	223.20					
41	including 1:3: 6 cement concrete coping.	Pel Kli	27.85	08.05	metre	91.55	225.20					
	including 1.5. 0 cement concrete coping.											
42	Crushing stone ballast by machine.	100Cft	891.00	-	cu.m.	314.70	-		This does not include the charges			
									for working of crushers, but includes			
									manual labour for carriageof stone to			
									crusher within three chains (90 m)			
									and also stacking the product after			
									crushing within three chains (90 m).			

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 2	2012 TO 31s	t JULY,	2012) DIS	STRICT LOI	DHRAN	
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
43	Breaking stone ballast screened and stacked:-								
	(a) 2" ring (50 mm)	100Cft.	997.90	-	cu.m.	352.45	-		
	(b) 1½ " ring (40 mm)	ditto	1158.30	-	"	409.10	-		
	(c) 1" ring (25 mm)	ditto	1336.50	-	"	472.05	-		
	d) ½ " ring (13 mm)	ditto	1782.00	-	"	629.40	-		
	(e)1/8" to ¹ /4" ring (3 mm to 6 mm)	ditto	3029.40	-	"	1070.00	-		
44	Screening and stacking stone ballast shingle or bajri, etc.	100Cft.	285.10		cu.m.	100.70	-		
45	Washing ballast, bajri or shingle.	100Cft.	285.10		cu.m.	100.70	-		
	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2 ¹ / ₂ ' (1.50 m x 0.76 m)	Each	160.90		Each	160.90	-		

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

Finance Department

7. BRICK WORK

1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.

2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4" x4" (200x100x100 mm) nominal.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec. No.	Remarks		
INO.		Unit	Labour	Composite	Unit	Labour	Composite	INO.			
1	Pacca brick work in mud mortar in buildings:							21.1 to	Masonry of boundary wall to be considered as masonry other than		
	i) in foundation and plinthii) in ground floor	100Cft. ditto	1454.75 1927.30	10490.75 10963.30	cu.m ditto	513.80 680.70	3705.35 3872.25	21.4	building.		
				*					The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.		
2	Add extra labour on item No. 1 for brick work in:-		/	9							
	i) first floor	100Cft.	378.85		cu.m	133.80	-				
	ii) second floor	ditto	851.40		ditto	300.70	-				
	iii) third floor	ditto	1323.95		ditto	467.60	-				
	iv) fourth & subsequent floors	ditto	2126.50		ditto	751.10	-				
3	Pacca brick work in mud mortar other than building:-				53			21.1 to 21.4	Same remarks as against item No. 1 above		
	i) upto 20 ft. (6.1 m) height	100Cft.	1984.35	11020.35	cu.m	700.85	3892.40				
	ii) extra labour for every 5 ft. (1.5 m)	ditto	378.85	Depart	ditto	133.80	-				
	additional height, or part thereof.	-82-	975-86995-9.789	-2016 grader a		()					
4	Pacca brick work in foundation and plinth in:-							ditto	Same remarks as against item No. 1 above.		
	i) Cement, sand mortar:-										
	Ratio 1:2	100Cft.	1913.05	15152.65	cu.m	675.65	5351.90				
	Ratio 1:3	ditto	1913.05	14160.25	ditto	675.65	5001.40				
	Ratio 1:4 Ratio 1:5	ditto	1913.05 1913.05	13564.80 13167.85	ditto	675.65	4791.10 4650.90				
	Ratio 1:5 Ratio 1:6	ditto ditto	1913.05	13167.85	ditto ditto	675.65 675.65	4545.55				
	Ratio 1:0	ditto	1913.05	12674.65	ditto	675.65	4476.70				
	Ratio 1:8	ditto	1913.05	12502.90	ditto	675.65	4416.00				
	ii) lime, cement sand mortar:-							21.1	The rate of lime mortar also includes grinding of mortar.		
	Ratio 1:1:6	100Cft.	1913.05	13176.85	cu.m	675.65	4654.05				
	Ratio 1:1:7	ditto	1913.05	12958.95	ditto	675.65	4577.10				
	Ratio 1:1:8	ditto	1913.05	12782.95	ditto	675.65	4514.95				
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	1913.05	12635.20 12524.50	ditto	675.65	4462.75				
	Kaulo 1:1:10	utto	1913.05	12524.50	ditto	675.65	4423.65				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	iii) lime, sand mortar 1:2	100Cft.	1913.05	12358.00	cu.m	675.65	4364.85	ditto	ditto				
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to				
	i) cement, sand mortar:-								be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.				
	Ratio 1:2	100Cft.	2528.15	15767.75	cu.m	892.95	5569.15		ii) Masonry of boundary wall				
	Ratio 1:3	ditto	2528.15	14775.35	ditto	892.95	5218.65		to be considered as masonry				
	Ratio 1:4	ditto	2528.15	14179.95	ditto	892.95	5008.35		other than building.				
	Ratio 1:5 Ratio 1:6	ditto ditto	2528.15 2528.15	13782.95 13484.65	ditto ditto	892.95 892.95	4868.15 4762.80						
	Ratio 1:7	ditto	2528.15	13484.03	ditto	892.93	4693.95						
	Ratio 1:8	ditto	2528.15	13116.80	ditto	892.95	4632.85						
		unto	2020.10	10110100	unio	0/21/0	1002100						
	ii) lime, cement, sand mortar:-		1						The rate of lime mortar also				
	Ratio 1:1:6	100Cft.	2528.15	13792.00	cu.m	892.95	4871.35		includes grinding of mortar.				
	Ratio 1:1:0	ditto	2528.15	13792.00	ditto	892.93	4795.30						
	Ratio 1:1:8	ditto	2528.15	13398.05	ditto	892.95	4732.20						
	Ratio 1:1:9	ditto	2528.15	13250.30	ditto	892.95	4680.00						
	Ratio 1:1:10	ditto	2528.15	13140.05	ditto	892.95	4641.05						
				56-12	53								
	iii) lime, sand mortar 1:2	100Cft.	2528.15	12973.10	cu.m	892.95	4582.10		The rate of lime mortar also includes grinding of mortar.				
		G.	100000	Depart	men	6							
6	Add extra labour on item No. 5 for brickwork	-255	0792, 0- 02405, 00- 40°9, 0054.		· 01.01 00-009- 22 00- 1	9e*							
	in:-												
	i) first floor	100Cft.	378.85		cu m	133.80							
	i) lifst floor ii) second floor	ditto	378.85 851.40		cu.m ditto	300.70	-						
	iii) third floor	ditto	1323.95		ditto	467.60	_						
	iv) fourth & subsequent floors	ditto	2126.50		ditto	751.10	-						
	, <u> </u>												
7	Pacca brick work other than building upto 10ft. (3 m)							21.1	i) The composite rate is to be				
	height.							to	reduced by 7% and 14%, if 2nd or				
								21.5	3rd class bricks are used.				
	i) cement, sand mortar:-								ii) Workshops, and arrest him.				
	Ratio 1:2	100Cft.	2220.25	15459.85	cu m	784.20	5460.40		ii) Workshops, godowns,, bins, house type godowns, reservoirs,				
	Ratio 1:2 Ratio 1:3	ditto	2220.23	13439.83	cu.m ditto	784.20	5109.90		filter beds, storage tanks, wells,				
	Ratio 1:5	ditto	2220.25	13872.00	ditto	784.20	4899.60		screening chambers, collecting				
	Ratio 1:5	ditto	2220.25	13475.05	ditto	784.20	4759.40		tanks, manholes etc. are to be				
	Ratio 1:6	ditto	2220.25	13176.70	ditto	784.20	4654.00		treated as masonry other than				
	Ratio 1:7	ditto	2220.25	12981.85	ditto	784.20	4585.20		buildings.				
	Ratio 1:8	ditto	2220.25	12810.05	ditto	784.20	4524.50		-				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	ii) lime, cement, sand mortar:-								The rate of lime mortar also includes grinding of mortar.				
	Ratio 1:1:6	100Cft.	2220.25	13484.05	cu.m	784.20	4762.55						
	Ratio 1:1:7 Ratio 1:1:8	ditto ditto	2220.25 2220.25	13266.10 13090.15	ditto ditto	784.20 784.20	4685.60 4623.45						
	Ratio 1:1:9	ditto	2220.25	12942.30	ditto	784.20	4571.20						
	Ratio 1:1:10	ditto	2220.25	12831.70	ditto	784.20	4532.15						
	iii) lime, sand mortar 1:2	100Cft.	2220.25	12665.15	cu.m	784.20	4473.35		ditto				
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	378.85	-	cu.m	133.80	-						
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	704.90	9-7	cu.m	248.95	-	21.5					
10	Extra for pacca brick work in steining of wells or any other	100Cft.	468.60	1009.80	cu.m	165.50	356.65	21.1	The composite rate is to be				
	circular masonry.	- 181			120			to 21.4	reduced by 7% and 14%, if 2nd or 3rd class bricks are used.				
		380			1 Siel			21.4	3rd class bricks are used.				
11	Extra labour for profile and flared walls.	100Cft.	161.20	/ طو ر ت ز	cu.m	56.95	-						
12	Extra labour for pacca brick work in piers and abutment:-			X.C.	53								
	i) from 10ft. to 20ft. $(3 \text{ m to } 6 \text{ m})$ height	100Cft.	187.55		cu.m	66.25	-						
	ii) above 20 ft. (6 m) height.	100Cft.	378.85	Depan	cu.m	133.80	-						
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.		3453.05	cu.m		1219.60		This item is to be executed only under the written permission of Superintending Engineer.				
14	Reinforced brick work in lintel of openings, laid in 1:3	Per Cft.	63.05	191.85	cu.m	2226.50	6776.15						
	cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	i er en.	05.05	191105	cuim	2220.50	0110110						
15	Extra for dressing or chamfering bricks for:-												
	a) special architectural bricksb) all other purposes	100 Nos. ditto	1221.60 610.80	-	% Nos. ditto	1221.60 610.80	-						
16	Perforated pacca brick walling half brick thick, in ground floors:-							21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.				
	i) mud mortar	100 Sft.	962.25	3224.55	Sqm.	103.55	346.95	21.4					

	MRS, BI-ANNUAL PE	HRAN							
Sr.	Description		Rate (British Sy	vstem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	1266.95	4580.15	sq.m.	136.30	492.80		
	Ratio 1:3	ditto	1266.95	4331.75	ditto	136.30	466.10		
	Ratio 1:4	ditto	1266.95	4183.20	ditto	136.30	450.10		
	Ratio 1:5	ditto	1266.95	4083.95	ditto	136.30	439.45		
	Ratio 1:6	ditto	1266.95	4014.15	ditto	136.30	431.90		
	Ratio 1:7	ditto	1266.95	3960.10	ditto	136.30	426.10		
	Ratio 1:8	ditto	1266.95	3920.30	ditto	136.30	421.80		
	iii) lime, cement sand mortar								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Sft.	1266.95	4086.20	sq.m	136.30	439.70		
	Ratio 1:1:7	100Sft.	1266.95	4031.00	sq.m	136.30	433.75		
	Ratio 1:1:8	100Sft.	1266.95	3990.40	sq.m	136.30	429.35		
	Ratio 1:1:9	100Sft.	1266.95	3950.15	sq.m	136.30	425.05		
	Ratio 1:1:10	100Sft.	1266.95	3926.75	sq.m	136.30	422.50		
	iv) lime, sand mortar 1:2	100Sft.	1266.95	3879.10	sq.m	136.30	417.40		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	1		الطومت ب	L.S.				
	i) first floor	100Sft.	191.30	and the	sa m	20.60			
	ii) second floor	ditto	423.85		sq.m ditto	45.60	-		
	iii) third floor	ditto	663.85		ditto	71.45			
	iv) fourth & subsequent floors	ditto	1024.30	Depart	ditto	110.20	-		
18	Perforated pacca brick walling one brick thick, in ground							21.1	The composite rate is to be
10	floor:							to	reduced by 7% and 14%, if 2nd or
								21.4	3rd class bricks are used.
	i) mud mortar	100Sft.	1352.45	5870.45	sq.m	145.50	631.65		
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	1904.05	8523.85	sq.m	204.90	917.15		
	Ratio 1:2 Ratio 1:3	ditto	1904.05	8027.65	ditto	204.90	863.80		
	Ratio 1:4	ditto	1904.05	7729.95	ditto	204.90	831.75		
	Ratio 1:4	ditto	1904.05	7531.45	ditto	204.90	810.40		
	Ratio 1:5	ditto	1904.05	7391.95	ditto	204.90	795.35		
	Ratio 1:0	ditto	1904.05	7283.45	ditto	204.90	793.33		
	Ratio 1:7	ditto	1904.05	7199.05	ditto	204.90	774.60		
		ano	1701.05	1177.05	ano	20100	, , 1.50		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	1904.05	7536.00	sq.m	204.90	810.85		includes grinding of mortar
	Ratio 1:1:7	ditto	1904.05	7424.45	ditto	204.90	798.85		
	Ratio 1:1:8	ditto	1904.05	7339.10	ditto	204.90	789.70		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	1904.05 1904.05	7265.15 7211.15	ditto ditto	204.90 204.90	781.75 775.90						
	iv) lime, sand mortar 1:2	100Sft.	1904.05	7125.30	sq.m	204.90	766.70		ditto				
19	Add extra labour on item No. 18 for perforated pacca brick work in:-												
	 i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors 	100Sft. ditto ditto ditto	284.15 638.55 992.95 1594.90		sq.m ditto ditto ditto	100.35 225.55 350.70 563.35	- - -						
20	Fire brick masonry in fireclay mortar:-i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	24.10	484.00	cu.m	850.40	17094.50	21.1 to 21.2					
	Extra for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	378.85		ditto	133.80	-		A&C No.I dated 2.9.1998				
21	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-	Sec. 1			A A			21.19					
	 i) 4¹/₂" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart. 	100Sft.	1057.65	6714.75	sq.m	113.80	722.50						
	 ii) 4¹/₂" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	100Sft.	950.40	6178.70	sq.m	102.25	664.85						
	 iii) 3" (75 mm) thick walling with hoop iron, bonding 6" (150 mm) apart. 	ditto	833.60	4998.95	ditto	89.70	537.90						
	 (iv) 3" (75 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	ditto	666.85	4355.95	ditto	71.75	468.70						
22	Ghilafi work (1½ brick thick wall)	100Cft.	1938.70	6843.70	cu.m	684.75	2417.20	21.18					
23	Dry brick pitching	100Cft.	1181.40	10091.40	cu.m	417.25	3564.30	21.1					
24	Sun dried bricks in mud mortar	100Cft.	1631.50	2405.50	cu.m	576.25	849.60	21.16					
25	Pise wall (mud walling)	100Cft.	860.65		cu.m	304.00	-	21.17					
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2					
	 i) 3" (75 mm) thick drip course cornice ii) 4¹/₂" (113 mm) thick drip course cornice. iii) 4¹/₂" (113 mm) thick eave brick with back brick. 	Rft. ditto ditto	12.25 13.90 9.45	41.55 82.80 97.10	Metre ditto ditto	40.20 45.60 31.00	136.30 271.60 318.50		correction vide A&C No.I dated 2.9.98				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2				
	 i) 1 brick ii) 2 bricks iii) 3 bricks iv) 4 bricks 	Rft. ditto ditto ditto	13.90 20.50 27.35 34.45	26.75 59.80 93.30 128.25	Metre ditto ditto ditto	45.60 67.25 89.70 113.00	87.75 196.15 306.00 420.65					
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	498.95		1,000 Nos	498.95	-					
29	Scraping bricks dismantled from pacca masonry	1,000 Nos	940.90		1,000 Nos	940.90	-					
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	118.80	1318.80	cu.m	41.95	465.80					
	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart. First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG hoop iron strips bonding placed at 2.0' (600 mm) apart horizontally, and at 1.0' (300 mm) interval vertically.	Rft.	51.55	106.25	Metre	169.10	348.50		This item is to be executed only under the written permission of the Superintending Engineer.			
	i) 1:3 ii) 1:4	100Sft. ditto	950.40 950.40	7335.95 7097.80	sq.m ditto	102.25 102.25	789.35 763.70					
33	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	27.50		sq.m	295.90	-					
34	Replacing kallar eaten bricks	Each No.	21.55	27.10	Each	21.55	27.10					
35	Repairing corners of bridges and other hydraulic masonry works	Each No.	137.50	207.55	Each	137.50	207.55					
36	Extra labour for drains of bath rooms, etc.	Per Lft.	11.70		Metre	38.40						
37	Maroo corners	Each Corner	75.00		Each Corner	75.00			Payable in addition to brick work			

8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- 3 Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description]	Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Random, rubble masonry (uncoursed), in foundation and plinth:	1000	E	5	目際			22.10, 22.11				
	 a) dry masonry b) in mud mortar c) in lime, sand mortar 1:2 d) in cement, sand mortar i) ratio 1:3 	100 Cft. 100 Cft. 100 Cft. 100 Cft.	2006.40 2508.00 3834.60 3834.60	2756.40 3420.00 6557.40 9590.40	cu.m cu.m cu.m	708.65 885.85 1354.40 1354.40	973.55 1207.95 2316.05 3387.35					
	ii) ratio 1:4 iii) ratio 1:6 iv) ratio 1:8	100 Cft. 100 Cft. 100 Cft.	3834.60 3834.60 3834.60	8697.25 7675.00 7109.40	cu.m cu.m cu.m	1354.40 1354.40 1354.40	3071.85 2710.80 2511.05	22.0				
2	Coursed rubble masonry hammer dressed, in foundation and plinth:							22.8				
	 a) dry masonry b) in mud mortar c) in lime, sand mortar 1:2 d) in cement, sand mortar: i) ratio 1:3 ii) ratio 1:4 iii) ratio 1:6 iv) ratio 1:8 	100 Cft. 100 Cft. 100 Cft. 100 Cft. 100 Cft. 100 Cft. 100 Cft.	2475.00 3478.20 4275.15 4275.15 4275.15 4275.15 4275.15 4275.15	3225.00 4390.20 6778.00 9744.75 8950.85 8041.75 7542.20	cu.m cu.m cu.m cu.m cu.m cu.m	874.15 1228.50 1510.00 1510.00 1510.00 1510.00 1510.00	1139.05 1550.60 2394.00 3441.85 3161.45 2840.35 2663.90					
3	Random rubble masonry (uncoursed) in ground floor or 20 ft.(6 m) height, building/other than building.							22.10				
	a) dry masonry b) in mud mortar	100 Cft. 100 Cft.	2240.70 3009.60	2990.70 3921.60	cu.m cu.m	791.40 1063.00	1056.30 1385.10					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	c) in lime, sand mortar 1:2	100 Cft.	4158.00	6880.80	cu.m	1468.60	2430.30						
	d) in cement, sand mortar:i) ratio 1:3	100 Cft.	4158.00	9913.80		1468.60	3501.55						
	i) ratio 1:5	100 Cft.	4158.00 4158.00	9020.65	cu.m cu.m	1468.60	3186.10						
	iii) ratio 1:6	100 Cft.	4158.00	7998.40	cu.m	1468.60	2825.05						
	iv) ratio 1:8	100 Cft.	4158.00	7432.80	cu.m	1468.60	2625.25						
4	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8					
	a) dry masonry	100 Cft.	2887.50	3637.50	cu.m	1019.85	1284.75						
	b) in mud mortar	100 Cft.	4303.20	5208.00	cu.m	1519.90	1839.45						
	c) in lime, sand mortar 1:2d) in cement, sand mortar:	100 Cft.	4804.80	7307.65	cu.m	1697.05	2581.05						
	i) ratio 1:3	100 Cft.	4804.80	10274.40	cu.m	1697.05	3628.90						
	ii) ratio 1:4	100 Cft.	4804.80	9480.50	cu.m	1697.05	3348.50						
	iii) ratio 1:6	100 Cft.	4804.80	8571.40	cu.m	1697.05	3027.40						
	iv) ratio 1:8	100 Cft.	4804.80	8071.85	cu.m	1697.05	2851.00						
5	Ashlar block in course or scabbled masonry (including	120			1 56	í.		22.5					
	dressing, etc.,) in ground floor or 20 ft. (6 m) height,		1.1	E P.				&					
	building/other than building.		-		65			22.6					
	a) in lime, sand mortar 1:2	100 Cft.	12606.00	14991.55	cu.m	4452.45	5295.00						
	b) in cement, sand mortar:												
	i) ratio 1:3	100 Cft.	12606.00	17013.80	cu.m	4452.45	6009.25						
	ii) ratio 1:4	100 Cft.	12606.00	16418.35	cu.m	4452.45	5798.95						
	iii) ratio 1:6	100 Cft.	12606.00	15743.55	cu.m	4452.45	5560.60						
6	Ashlar fine masonry (including dressing, etc.) in ground							22.3					
	floor or 20 ft. 6 m) height, building/other than building.							(A) to (C) &					
	a) in lime, sand mortar 1:2	100 Cft.	23030.70	25170.40	cu.m	8134.45	8890.20	(C) & 22.4					
	b) in cement, sand mortar:							••					
	i) ratio 1:3	100 Cft.	23030.70	26181.50	cu.m	8134.45	9247.30						
	ii) ratio 1:4	100 Cft.	23030.70	25883.35	cu.m	8134.45	9142.00						
	iii) ratio 1:6	100 Cft.	23030.70	25552.85	cu.m	8134.45	9025.25						
7	Extra labour on items 3, 4, 5 & 6 above for work in:-												
	i) first floor	100 Cft.	534.85	-	cu.m	188.90	-						
	ii) second floor	100 Cft.	1191.15	-	cu.m	420.70	-						
	iii) third floor	100 Cft.	1861.75	-	cu.m	657.55	-						
	iv) fourth floor	100 Cft.	2946.25	-	cu.m	1040.60	-						
8	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m) additional height, other than building, or part thereof.	100 Cft.	472.55	-	cu.m	166.90	-						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	1407.90	-	cu.m	497.25	-	22.12					
10	Extra labour for:-							22.7					
	a) coping and caps, etc.b) cornice & string course	100 Cft. 100 Rft.	6747.85 6747.85	- -	cu.m Rm.	2383.35 221.35	-						
11	Dressing stones:- a) hammer dressed b) rough tooled dressed c) chisel dressed d) fine dressed	100 Sft. 100 Sft. 100 Sft. 100 Sft.	2587.20 4889.30 5924.15 12212.65		sq.m sq.m sq.m sq.m	278.40 526.10 637.45 1314.10		22.2	 i) This rate of dressing shall be paid only when the supply of undressed stone is made. ii) In case of masonry, dressing is already included and this rate shall not be added thereto. iii) Only dressed surface of stone shall be measured. 				
12	Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft.	4900.65	10129.65	sq.m	527.30	1089.95	22.13	shan be measured.				
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	218.40	245.05	cu.m	7713.90	8655.15						
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	123.40	153.10	cu.m	4358.50	5407.50						

9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100Sft.	3435.45	8504.75	sq.m	369.65	915.10	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	2647.90	6288.00	sq.m	284.90	676.60	23.2	ditto			
3 4	Covering mud roof with coal tar, and fine sand. Filling spaces in between:-	100Sft.	145.35 1.631.68	881.90 Daparta	sq.m	15.65	94.90	23.1 to 23.2	ditto			
	 a) Wooden battens over beams, filled with deodar wood pieces (spacers). b) RCC battens, filled with CC block 1:3:6. c) Spaces filled with bricks. 	100Sft. roof area -ditto- -ditto-	239.80 508.20 140.70	1816.80 843.75 548.95	sq.m	25.80 54.70 15.15	195.50 90.80 59.05		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100Sft.	806.75	4910.45	sq.m	86.80	528.35	23.1	ditto			
6	Jack arch roofing 4 ¹ / ₄ " (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm)							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.			

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUARY, 2	2012 TO 31st	t JULY, 2	2012) DIST		RAN	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ¹/₂" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:- a) cement concrete in haunches 1:6:12. 	100Sft.	3738.25	13891.30	sq.m	402.25	1494.70		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
7	 b) cement concrete in haunches 1:3:6. Jack arch roofing 4¹/₂" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ¹/₂" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster 	ditto	3738.25	14910.95	ditto	402.25	1604.40	23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.
	and gobri) soffit of arches cement plastered. The rate also includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
	a) cement concrete in haunches 1:6:12.b) cement concrete in haunches 1:3:6.	100Sft. ditto	3029.40 3029.40	13681.05 14041.85	sq.m ditto	325.95 325.95	1472.10 1510.90		
8	Extra for vaulted jack arch roofing.	100Sft.	665.30	E C S	sq.m	71.60	-		ditto
9	Jack arch roofing of shingle and cement concrete 1:3:6, 4½" (113 mm) thick at crown, with ½" (13 mm) cement plaster including cost of supplying, erecting and dismantling centring.	100Sft.	4161.30	11587.20	sq.m	447.75	1246.80	23.3 to 23.5	ditto
10	Earth filling over roof including watering, ramming with 1" (25 mm) mud plaster finished, with gobri leeping:							23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 3" (75 mm) thick earth filling and 1" (25 mm) mud plaster	100Sft.	364.30	570.70	sq.m	39.20	61.40	2010	& sub- sequent floors, respectively.
	 b) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster 	100Sft.	476.80	719.15	sq.m	51.30	77.40		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	51.75	63.45	sq.m	5.55	6.85	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or	100Sft.	285.10	1690.60	sq.m	30.70	181.90	23.1	

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)								
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively,
	a) 20 BWG b) 22 BWG c) 24 BWG	100Sft. 100Sft. 100Sft.	479.60 479.60 479.60	14515.80 12245.30 9831.00	sq.m sq.m sq.m	51.60 51.60 51.60	1561.90 1317.60 1057.80		on items 13 to 18.
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300 mm) outside width finished smooth with a floating coat of neat cement.	Rft.	39.00	56.90	Metre	127.90	186.65	23.10	
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	146.25	310.60	Each	Each	310.60	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4½" (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	146.25	635.65	Each	146.25	635.65	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.				459 G				
	 a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe 	Per Rft. Per Rft.	28.50 28.50	134.10 158.05	Metre Metre	93.50 93.50	439.85 518.40		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	28.50	109.25	sq.m	306.65	1175.55	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	7.25	68.70	Sq.m	78.00	739.20		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23%
	 a) 4" dia (100 mm) cast iron down pipe. b) 3" (75 mm) cast iron down pipe. 	Per Rft. Per Rft.	27.50 27.50	176.20 150.80	Metre Metre	90.20 90.20	577.95 494.60		on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	106.55	388.90	Each	106.55	388.90		
22	Shoes, bends or offsets for cast iron rain water down pipe,	Each	35.75	256.65	Each	35.75	256.65		

	MRS, BI-ANNUAL PERIC	TRICT LODH	RAN						
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	including fixing and painting.								
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	118.80	238.60	Each	118.80	238.60	23.10	
24	Laying ¹ / ₂ " (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100Sft.	2521.20	14782.80	sq.m	271.30	1590.65	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	a) 22 BWG sheets roofingb) 24 BWG sheets roofing	100Sft. 100Sft.	1545.05 1545.05	14186.70 12580.65	sq.m sq.m	166.25 166.25	1526.50 1353.70	23.60	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and ridges, etc).	100Sft.	1075.80	4644.60	sq.m	115.75	499.75	23.8	
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100Sft.	133.15		sq.m	14.35	-	23.6	
28	Fixing asbestos cement sheet ridges and valleys ¹ /4" (6 mm) thick.	Per Rft.	12.55	58.00	Metre	41.15	190.25	23.8	
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-							23.6	
	a) 6" (150 mm) lap and 18" (450 mm) overall, of 22 gauge G.I sheet ridging.	Per Rft.	32.45	336.35	Per Metre	106.45	1103.25		
	 b) 9" (225 mm) lap and 24" (600 mm) overall, of 24 gauge G.I sheet ridging. 	Per Rft.	43.15	328.40	Per Metre	141.55	1077.15		
	 c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging. 	Per Rft.	43.15	397.65	Per Metre	141.55	1304.30		
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	21.60	141.50	Per Metre	70.85	464.10	23.11	
31	Making masonry ventilators in cement, sand mortar 1:4	Each	550.00	977.45	Each	550.00	977.45		

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUARY,	2012 TO 31st	JULY, 2	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
<u> </u>									
32	Fixing water spouts or parnalas.	Each	165.00		Each	165.00	-	23.10	
33	Making drip course 2"x ¹ / ₂ " (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	6.95	8.00	Metre	22.80	26.25		
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	18.50	308.15	sq.m	199.05	3315.70		
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:- i) Thermopore sheet ½ " (13 mm) thick ii) Thermopore sheet ½ " (20 mm) thick iii) Thermopore sheet 1" (25 mm) thick	100Sft. 100Sft. 100Sft.	1245.75 1245.75 1248.10	5423.05 5549.05 5677.40	sq.m sq.m sq.m	134.05 134.05 134.30	583.50 597.10 610.90		
36	Providing and fixing AC rain water down pipe 4" (100 mm) dia, with shoe, T-bend, clamp, etc.	Rft.	7.20	177.95	Metre	23.60	583.70		
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:-		10 10-00195 (10 157 15.0-7 10-7	uur uur gur kennen kenne	n mr. 10° - 10° - 10°				Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.
	 i) for slabs upto 6" (150 mm) thick ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick. 	Rft. Rft.	9.35 15.85	10.95 18.75	Metre Metre	30.65 52.00	35.90 61.50		
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-								Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times for reinforced cement concrete.
	i) upto 1.0' (300 mm) height of girder or beam.	Each	39.05	44.35	Each	39.05	44.35		is removed complete concrete.
	ii) for every 6" (150 mm) additional height or part thereof.	Each	18.75	21.30	Each	18.75	21.30		
39	Hoisting RS. Beams and wooden beams and placing in	Each	153.80	-	Each	153.80	-		

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUARY,	2012 TO 31st	JULY, 2	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	position.								
40	Hoisting and placing in position sahl ballies, over roof.	Each	23.55	-	Each	23.55	-		
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.								
	a) 5' to 6' (1.50 to 1.83 m) long	Each	21.95	-	Each	21.95	-		
	b) 6' to 7' (1.83 to 2.13 m) long	Each	30.75	-	Each	30.75	-		
	c) 7' to 8' (2.13 to 2.44 m) long	Each	38.45	-	Each	38.45	-		
	d) 8' to 9' (2.44 to 2.74 m) long	Each	51.25	-	Each	51.25	-		
	e) above 9' (2.74 m) length	Each	61.50	-	Each	61.50	-		
42	Hoisting and placing in position R.C. trough:		*	>					Applicable only to roof trough (inverted tees & trough) for height of
	a) upto 10' (3 m) in length	Each	61.50	-	Each	61.50	-		1st storey only.
	b) 10' to 11' (3 to 3.36 m) in length	ditto	76.90		ditto	76.90	-		5 5
	c) 11' to 12' (3.36 to 3.66 m) in length	ditto	102.50		ditto	102.50	-		
	d) 12' to 13' (3.66 to 3.96 m) in length	ditto	118.30		ditto	118.30	-		
	e) 13' to 14' (3.96 to 4.26 m) in length	ditto	128.15		ditto	128.15	-		
	f) 14' to 15' (4.26 to 4.57 m) in length	ditto	139.80	5 J	ditto	139.80	-		
	g) 15' to 16' (4.57 to 4.88 m) in length	ditto	153.80	20 - Ja	ditto	153.80	-		
	h) 16' to 17' (4.88 to 5.19 m) in length	ditto	170.85	- 11/6	ditto	170.85	-		
	i) 17' to 18' (5.19 to 5.49 m) in length	ditto	219.70	Contraction of the second	ditto	219.70	-		
	j) 18' to 19' (5.49 to 5.80 m) in length	ditto	236.60	-	ditto	236.60	-		
	k) 19' to 20' (5.80 to 6.10 m) in length	ditto	256.30	The same second by	ditto	256.30	-		
		2.23	usuco s	vepusu	none				
43	Hoisting and placing in position R.C. inverted battens:-								
	i) upto 10' (3.05 m) span	Each	47.35	-	Each	47.35	-		
1	ii) from 10' to 12' (3.05 to 3.66 m) span	ditto	105.25	-	ditto	105.25	-		
1	iii) from 12' to 13' (3.66 to 3.96 m) span	ditto	126.30	-	ditto	126.30	-		
	iv) from 13' to 14' (3.96 to 4.26 m) span	ditto	157.85	-	ditto	157.85	-		
	v) from 14' to 15' (4.26 to 4.57 m) span	ditto	172.20	-	ditto	172.20	-		
	vi) from 15' to 16' (4.57 to 4.88 m) span	ditto	189.40	-	ditto	189.40	-		
	vii) from 16' to 18' (4.88 to 5.49 m) span	ditto	236.80	-	ditto	236.80	-		
	viii) from 18' to 20' (5.49 to 6.10 m) span	ditto	378.85	-	ditto	378.85	-		
44	Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	Each	220.00	475.25	Each	220.00	475.25		

10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproduct:

	MRS, BI-ANNUAL F	PERIOD (1st	FEBRUARY	, 2012 10 319	st JULY,	2012) DIS		KAN	
Sr.	Description		Rate (British Sy	vstem)	R	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	1481.70	2700.30	sq.m	159.45	290.55		
2	Earth flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	504.10	684.10	sq.m	54.25	73.60	24.1	
3	Providing, laying, watering and ramming brick ballast 1 ¹ / ₂ " to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	1140.50	2520.50	cum.	402.85	890.25		
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	919.05	1215.15	sq.m	98.90	130.75	24.2	
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	486.80	2878.40	sq.m	52.40	309.70	24.12	
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by ½ "(13 mm) thick mud plaster.	100 Sft.	877.05	4435.65	sq.m	94.35	477.30	24.12	
7	Grouting 4 ¹ / ₂ "(113 mm) dry brick work with cement mortar ratio 1:5	100 Sft.	472.55	884.40	sq.m	50.85	95.15		
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	851.40	3945.95	sq.m	91.60	424.60	24.4	
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of ³ / ₄ " (20 mm) thick cement mortar 1:6.	100 Sft.	1,087.70	5,593.05	sq.m	117.05	601.80	24.4	
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of ³ / ₄ " (20 mm) thick cement mortar 1:6.	100 Sft.	1,064.25	3,058.15	sq.m	114.50	329.05	ditto	
11	Brick ties (9"x4 ¹ / ₂ "x1 ¹ / ₂ ")(225 mm x 113 mm x 40 mm) laid	100 Sft.	1,181.40	4,141.10	sq.m	127.10	445.60	24.4	

	MRS, BI-ANNUAL PEF	RAN							
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.								
12	Cement tiles (8"x8"x ³ /4")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2.	100 Sft.	709.85	4,602.20	sq.m	76.40	495.20	24.7	
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm)	100 Sft.	709.85	3,223.60	sq.m	76.40	346.85		
	(b) 9"x9"x ³ 4" (225 x 225 x 20 mm)	ditto	709.85	4,171.95	ditto	76.40	448.90		
	(c) 6"x6"x¾"(150 x 150 x 20 mm)	ditto	709.85	5,770.00	ditto	76.40	620.85		
14	Coloured cement tiles (8"x8"x¾")(200 x 200 x 20 mm) of approved dark shade laid flat in 1:2 cement mortar, over ¾" (20 mm) bedding mortar of 1:2.	100 Sft.	709.85	4,627.40	sq.m	76.40	497.90	24.7	
1.7					-1.93			24.0	
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-	100	FE		7			24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick	100 Sft.	773.20	1,792.35	sq.m	83.20	192.85		
	(b) $1\frac{4}{30}$ mm) thick	ditto	773.20	2,016.60	ditto	83.20	217.00		
	(c) 1 ¹ / ₂ "(40 mm) thick (d) 1 ³ / ₄ "(45 mm) thick	ditto ditto	969.20 969.20	2,436.90 2,673.35	ditto ditto	104.30 104.30	262.20 287.65		
	(d) $1/4$ (45 mm) thick (e) $2"(50 \text{ mm})$ thick	ditto	1,165.25	3,146.65	ditto	125.40	338.60		
	(f) $2^{1/4}$ (56 mm) thick	ditto	1,200.85	3,393.15	ditto	129.20	365.10		
	(g) 21/2"(62 mm) thick	ditto	1,361.25	3,704.60	ditto	146.45	398.60		
	(h)2¾"(70 mm) thick	ditto	1,361.25	4,012.65	ditto	146.45	431.75		
	(i) 3"(75 mm) thick	ditto	1,361.25	4,274.75	ditto	146.45	459.95		
16	Providing and laying conglomerate flooring (two coat work) with top layer of ¹ / ₂ "(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone chips passing 3/16"(6 mm) sieve, over bottom layer of cement concrete 1:3:6, including surface finishing and							24.10	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	dividing in panels:-								
	 (a) 1¹/₂"(40 mm) thick (b) 1³/₄"(45 mm) thick (c) 2"(50 mm) thick 	100 Sft. ditto ditto	1,129.25 1,129.25 1,437.15	2,549.60 2,699.00 3,235.20	sq.m ditto ditto	121.50 121.50 154.65	274.35 290.40 348.10		
17	Add extra in cement concrete floor topping, if finished with pigment and polishing.	100 Sft.	275.00	709.35	sq.m	29.60	76.35		

	MRS, BI-ANNUAL PI	TRICT LODH	RAN						
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	213.85	-	sq.m	23.00	-		On items 19-25 & 29-34
19	Flag stone flooring in lime mortar 1:2, over ³ / ₄ "(20 mm) bedding mortar, in platforms and floors, etc.							24.5	
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	2,355.40 2,355.40	3,888.05 4,208.40	sq.m ditto	253.45 253.45	418.35 452.80		
20	Asphalt flooring , including preparation of proper base remelting, setting out, and finishing complete:-							24.10	
	 (a) 1"(25 mm) thick topping (b) ½"(13 mm) thick topping (c) ¼"(6 mm) thick topping 	100 Sft. ditto ditto	920.70 719.05 526.80	13,069.50 6,923.60 3,724.80	sq.m ditto ditto	99.05 77.35 56.70	1406.30 745.00 400.80		
21	$1^{3}/_{8}$ "(35 mm) thick mosaic flooring, consisting of 3/8"(10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete :-	19 m							If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement(b) using white cement	100 Sft. ditto	3,203.10 3,203.10	5,315.70 5,602.25	sq.m ditto	344.65 344.65	571.95 602.80		
22	1½"(40 mm) thick mosaic flooring, consisting of ½ "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-	99	mance	Depart					If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement(b) using white cement	100 Sft. ditto	3,203.10 3,203.10	5,471.20 6,041.75	sq.m ditto	344.65 344.65	588.70 650.10		
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over 3/4"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	1,981.30	5,516.35	sq.m	213.20	593.55	24.8	
24	Laying floor of approved white glazed tile ¹ /4" (6 mm) thick	100 Sft.	2,541.00	7,317.20	sq.m	273.40	787.35	24.7	

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description		Rate (British S	vstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in white cement 1:2 over ³ / ₄ " (20mm) thick cement mortar 1:2, complete.								
25	Laying floor of approved coloured glazed tiles ¹ / ₄ "(6 mm) thick, laid in white cement and pigment on a bed of ³ / ₄ " (20 mm) thick cement mortar 1:2.	100 Sft.	2,541.00	7,607.00	sq.m	273.40	818.50	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	646.80	767.25	sq.m	69.60	82.55		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	689.55	811.60	sq.m	74.20	87.35		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	106.60	148.35	sq.m	11.45	15.95	24.6	
29	Shisham wood boarding or strip flooring $3/4"$ (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens $1\frac{1}{2}"x2"(40 \times 50 \text{ mm})$,size placed at $12"(300 \text{ mm})$ centre to centre, including two coats of bitumen laid hot on the base.	100 Sft.	1,815.00	32,050.60	sq.m	195.30	3448.65	24.13	
		19	mance	Depan	ment				
30	Deodar wood boarding or strip flooring $3/4$ " (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens $1\frac{1}{2}$ "x2"(40 x 50 mm) size , placed at 12"(300 mm) centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	2,158.20	35,738.10	sq.m	232.20	3845.40	ditto	
31	Teak wood boarding or strip flooring $\frac{1}{2}$ " (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens $\frac{1}{2}$ " x2"(40 x 50 mm) size, placed at 12"(300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	1,804.00	42,156.70	sq.m	194.10	4536.05	ditto	
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	1,980.00	37,594.95	sq.m	213.05	4045.20	24.13	

	MRS, BI-ANNUAL PER	RIOD (1st	FEBRUAR	ί, <mark>2012 ΤΟ</mark> 31	st JULY, :	2012) DIS		AN	I
Sr.	Description		Rate (British Sy	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
33	Teak wood block 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	1,804.00	72,559.80	sq.m	194.10	7807.45	ditto	
34	Laying wooden paving of hard wood on edge in coal tar							ditto	
	and asphalt:-	100 Sft.			sq.m				
	1	Per Inch			per cm				
	(a) Shisham wood	thickness	1,267.20	23,423.05	thickness	136.35	2520.30		
	(b) Kikar wood	ditto	1,267.20	11,726.65	ditto	136.35	1261.80		
35	Tile skirting laid in 1:2 cement mortar, over 3/4"(20 mm) thick cement mortar, 1:2 including cement washing and filling joints complete:-								
		100 00							
	(a) cement tiles	100 Sft.	1,162.15	5,404.35	sq.m	125.05	581.50		
	(b) mosaic tiles	ditto	1,917.30	7,422.85	ditto	206.30	798.70		
			1		1				
36	Providing grey cement skirting or dado 3/8"(10 mm) thick				-1 ni :				
	including rounding of corner and straight ening of top edge			And a second sec	-1.826				
	and finishing to smooth surface afterplastering :-	- NSI			181				
		1.00%		and the second s	7 5.656				
	(a) 1:2 cement, sand mortar	100 Sft.	1,461.80	1,982.55	sq.m	157.30	213.30		
	(b) 1:3 cement, sand mortar	ditto	1,461.80	1,829.80	ditto	157.30	196.90		
	(c) Extra if skirting or dado is finished	ditto	89.10	317.60	ditto	9.60	34.15		
	with pigment of any colour.								
37	White glazed tile $(6"x6"x^{1/4}")$ (6 mm) thick dado jointed in white	100 Sft.	3,131.70	7,907.90	sq.m	336.95	850.90	24.7	
	cement and laid over 1:2 cement sand mortar 3/4" (20mm)	1	nance	Depart	mant				
	thick, including finishing.								
38	Coloured glazed tile dado (6"x6" ¹ / ₄ ") (6mm) thick in pigment over 1:2	100 Sft.	3,131.70	8,182.70	sq.m	336.95	880.45	ditto	
	cement, sand mortar 3/4"(20mm) thick, including finishing.								
39	Mosaic dado or skirting with one part of cement and								
	marble powder in the ratio of 3:1 and two parts of marble								
	chips, laid over ¹ /2"(13 mm) thick cement plaster 1:3,								
	including rubbing and polishing, complete with finishing:								
	(a) using grey cement:								
	i) 3/8"(10 mm) thick	100 Sft.	3,821.40	4,895.70	sq.m	411.20	526.80		
	ii) ½"(13 mm) thick	ditto	3,821.40	5,603.00	ditto	411.20	602.90		
	(b) using white cement :								
	'i) 3/8"(10 mm) thick	100 Sft.	3,821.40	5,707.40	sq.m	411.20	614.10		
	1) 5/6 (10 mm) thek	100 511.	5,021.40	5,707.40	5 q .m	711.20	014.10		1

	MRS, BI-ANNUAL PEI	RIOD (1st	FEBRUAR	(, 2012 TO 31	st JULY,	2012) DIS	TRICT LODHE	RAN	
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) ¹ /2"(13 mm) thick	ditto	3,821.40	5,990.10	ditto	411.20	644.55		
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	10.05	67.05	sq.m	108.15	721.45	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	3.95	Metre	-	12.95		Labour for fixing already included in items No. 15, 16, 21and 22 of this Chapter.
	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels								
	a) Size 1 ¹ /2" x ³ / ₈ " (40 x 10 mm) b) Size 1 ¹ /2" x ¹ /4" (40 x 6 mm)	Per Rft. ditto		5.30 3.70	Metre ditto	-	17.40 12.15		
					36				
		S.	R	in and	J.				
		1		The second s	55				

Finance Department

11. SURFACE RENDERING

1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PEI			, 2012 TO 31	st JULY,	, 2012) DI	STRICT LOD	HRAN	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7	
	 a) ¹/₂" (13 mm) thick b) 1" (25 mm) thick 	100 Sft. ditto	220.55 308.75	278.15 423.95	sq.m ditto	23.75 33.20	29.95 45.60		
2	Mud plaster on floor or roof (excluding Gobri leeping):-		1	EN				ditto	Add extra 13%, 32% and 51% above the labour rates only or 6%, 15% &
	a) ¹ / ₂ " (13 mm) thick	100 Sft.	198.80	256.40	sq.m	21.40	27.60		23% on the composite rates for 2nd,3rd, 4th and subsequenct floors,
	b) 1" (25 mm) thick	ditto	198.80	314.00	ditto	21.40	33.80		respectively.
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.	100	F		78,			25.1 to 25.6	
	a) ¹ /4" (6 mm) thick	100 Sft.	637.55	796.90	sq.m	68.60	85.75		
	b) ¹ / ₂ " (13 mm) thick	ditto	637.55	956.15	ditto	68.60	102.90		
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-	T	nance	Depart				ditto	
	a) ¹ / ₄ " (6 mm) thick b) ¹ / ₂ " (13 mm) thick	100 Sft. ditto	637.55 637.55	1013.50 1242.75	sq.m ditto	68.60 68.60	109.05 133.70		
5	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand	100 Sft.	1600.90	3869.15	sq.m	172.25	416.30	ditto	
5	and shingle) upto 20' (6.00 m) height.	100 511.	1000.90	5007.15	5q.m	172.20	110.50	unto	
6	Providing and laying machine sprayed plaster ¹ /2" (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto	
	i) ratio 1:1	100 Sft.	564.00	1860.95	sq.m	60.70	200.25		
	ii) ratio 1:1 ¹ / ₂ iii) ratio 1:2	ditto ditto	564.00 564.00	1754.05 1692.60	ditto ditto	60.70 60.70	188.75 182.10		
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	637.55 637.55 802.55	1158.30 1312.55 1844.05	sq.m ditto ditto	68.60 68.60 86.35	124.65 141.25 198.40					
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto				
	 a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick 	100 Sft. ditto ditto	637.55 637.55 802.55	1005.55 1128.20 1538.55	sq.m ditto ditto	68.60 68.60 86.35	108.20 121.40 165.55					
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto				
	 a) 3/8" (10 mm) thick b) 1/2" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	637.55 637.55 802.55	964.95 1053.95 1451.35	sq.m ditto ditto	68.60 68.60 86.35	103.85 113.40 156.15					
10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, upto 20' height.	and the			1				 i) This item shall be applicable to buildings meant for human habitation only, such as buildings like residences, offices, 			
	a) 1:2 b) 1:3 c) 1:4	100 Sft. ditto ditto	731.30 731.30 731.30	1354.85 1201.50 1160.90	sq.m ditto ditto	78.70 78.70 78.70	145.80 129.30 124.90		educational institutions and hospitals, etc. It shall not be admissible on godowns; bins; agriculture, poultry and animal sheds; cycle stands; garrages; etc. ii) The thickness of the plaster will			
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-								not be more than 3/8" (10 mm) thick.			
	 a) 3/8" (10 mm) thick b) 1/2" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	637.55 637.55 802.55	929.15 992.30 1385.75	sq.m ditto ditto	68.60 68.60 86.35	100.00 106.75 149.10					
12	Cement plaster 1:6 upto 20' (6.00 mm)							ditto				
	height:- a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	637.55 637.55 802.55	878.05 956.50 1283.50	sq.m ditto ditto	68.60 68.60 86.35	94.50 102.90 138.10					
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	380.95	585.45	sq.m	41.00	63.00	25.4 to 25.6				
14	Lime pointing flush upto 20' (6.00 m) height including	100 Sft.	472.55	590.95	sq.m	50.85	63.60	25.8				

	MRS, BI-ANNUAL PE	RIOD (1st	FEBRUARY	, 2012 TO 31	st JULY	, 2012) DI	STRICT LOD	HRAN	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	raking joints, in lime, sand mortar 1:2.	_							
	raking joints, in line, sand mortar 1.2.								
15	Lime pointing struck joints on walls, upto 20' (6.00 m) height, including raking joints in lime sand mortar 1:2.	100 Sft.	731.30	849.65	sq.m	78.70	91.40	ditto	
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2	100 Sft.	637.55	1027.20	sq.m	68.60	110.55		
	b) ratio 1:3	ditto	637.55	937.60	ditto	68.60	100.90		
17		100.00	170.55	0.62.20		50.05	00.55		
17	Cement pointing 1:2 flush on floor.	100 Sft.	472.55	862.20	sq.m	50.85	92.75	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-		1	5					
	a) ratio 1:2	100 Sft.	731.30	1120.95	sq.m	78.70	120.60		
	b) ratio 1:3	ditto	731.30	1031.35	ditto	78.70	110.95		
19	Pointing flush on stone work, upto 20' (6.00 m) height.	ŝ	1		78.			25.8	
	a) in lime mortar 1:2 (lime, sand)	100 Sft.	588.70	747.05	sq.m	63.35	80.40		
	b) in cement mortar 1:3	ditto	588.70	888.75	ditto	63.35	95.65		
	c) on stone work raised:-i) in lime mortar 1:2	100 Sft.	1106.15	1264.50	57 m	119.00	136.05		
	i) in time mortar 1:2 ii) in cement mortar 1:3	ditto	1106.15	1406.20	sq.m ditto	119.00	151.30		
		unto	1100.15	1100.20	unto	115.00	101.50		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	290.40	wepan	sq.m	31.25	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	145.20	-	sq.m	15.60	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	66.00	71.45	sq.m	7.10	7.70	25.11	
23	Distempering:-							ditto	
	a) new surface:-								
	i) one coat	100 Sft.	60.90	135.20	sq.m	6.55	14.55		
	ii) two coats	ditto	90.10	186.95	ditto	9.70	20.10		
	iii) three coats	ditto	119.35	238.65	ditto	12.85	25.70		
	b) old surface:-								
	i) one coat	100 Sft.	55.95	107.80	sq.m	6.00	11.60		
	ii) two coats	ditto	90.10	141.95	ditto	9.70	15.25		

	MRS, BI-ANNUAL PEF	RIOD (1st	FEBRUARY	, 2012 TO 31	st JULY	, 2012) DI	STRICT LOD	HRAN	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
24	Colour washing:-							25.10	
24	Colour washing							23.10	
	a) new surface:-								
	i) one coat	100 Sft.	51.95	78.90	sq.m	5.60	8.50		
	ii) two coats	ditto	77.95	117.30	ditto	8.40	12.60		
	b) old surface:-								
	i) one coat	100 Sft.	51.95	68.50	sq.m	5.60	7.35		
	ii) two coats	ditto	77.95	105.05	ditto	8.40	11.30		
25	White washing:-							25.9	
	a) new surface:-	100.00	51.05	74.05		5.60	0.00		
	i) one coat ii) two coats	100 Sft. ditto	51.95 77.95	74.25 111.30	sq.m ditto	5.60 8.40	8.00 12.00		
	iii) three coats	ditto	101.00	145.50	ditto	10.85	15.65		
					111				
	b) old surface:-	100 66	51.05	(0.70	120	5.60	7.40		
	i) one coat ii) two coats	100 Sft. ditto	51.95 77.95	68.70 105.75	sq.m ditto	5.60 8.40	7.40 11.40		
		unto		67	unto	0.10	11.10		
26	Gobri leeping:-	1			-492			25.7	
	a) on walls	100 Sft.	73.35	76.65	60 m	7.90	8.25		
	a) on walls b) over roofs	ditto	62.10	65.40	sq.m ditto	6.70	7.05		
		783		15° marine second		- 6-			
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	93.70	Depan	sq.m	10.10	-	25.8	Payable with fresh masonry, when
									the face of the work is not to be plastered/pointed.
28	Extra for lime, mud or cement plaster and pointing from	100 Sft.	116.25	-	sq.m	12.50	-		plustered, pointed.
	20' (6.00 m) and above for each additional 10' (3.00 m)								
	height or part thereof.								
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	287.75	704.35	sq.m	30.95	75.80		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	287.75	305.75	sq.m	30.95	32.90		
31	Extra cost of labour and material for red oxide pigment in	100 Sft.	90.75	183.15	sq.m	9.75	19.70		
51	cement pointing to match with the colour of bricks.	100 511.	20.75	105.15	5 4 .m	2.15	17.70		
32	Providing grooved cement sand plaster 1:3 over existing plastered and roughened surface upto 20' (6.00 m) height.								
	prasiered and roughened surface upto 20 (0.00 m) height.								
	i) 3/8" (10 mm) thick	100 Sft.	731.30	1099.25	sq.m	78.70	118.30		

	MRS, BI-ANNUAL PER	IOD (1st	FEBRUARY,	2012 TO 31	st JULY	, 2012) DI	STRICT LOD	HRAN	
Sr.	Description		Rate (British Sys	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) ½" (13 mm) thick	ditto	731.30	1221.95	ditto	78.70	131.50		
33	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	4.30	29.75	Metre	14.10	97.60		
34	Petty repairs to fire place.								
	i) Single ii) Double	Each Each	115.50 231.00	158.90 317.80	Each Each	115.50 231.00	158.90 317.80		
35	Petty repair to main rooms.	Each	238.35	354.35	Each	238.35	354.35		Area above 100 Sft (10.76 sq.m)
36	Petty repair to small rooms.	Each	119.15	177.15	Each	119.15	177.15		Area upto 100 Sft (10.76 sq.m)
37	Petty repair to verandah.	Each	238.35	331.05	Each	238.35	331.05		
38	Extra labour for white washing, colour washing, priming coat and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	100 Sft. Per coat	8.65		sq.m Per coat	0.95	-		The height will be taken from the floor, roof or ground uderneath as the case may be on the side towards which the work is to be done.

Tinance Department

12. WOOD WORK

1 No extra rate is to be paid for sawing as the rates are inclusive of these

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERI	OD (1st	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1						
2	 a) Deodar wood b) Shisham wood 	Per Cft. ditto	319.45 363.00	3096.25 2588.15	cu.m ditto	11282.95 12821.15	109359.55 91413.45	26.1						
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.	- 11		2	1			20.1						
	a) Deodar woodb) Shisham wood	Per Cft. ditto	206.90 206.90	3018.05 2480.40	cu.m ditto	7307.70 7307.70	106597.55 87607.75							
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-	S.	nance	Depart	AS B meni	ç.		26.1 to 26.3 & 26.7						
	 i) 2" (50 mm) thick ii) 1³/₄" (45 mm) thick iii) 1¹/₂" (40 mm) thick 	Per Sft. ditto ditto	56.85 56.85 56.85	1297.35 1207.75 1120.30	sq.m ditto ditto	611.70 611.70 611.70	13959.50 12995.40 12054.45							
4	 First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cm²) including brass fittings, sash bars, etc. complete:- a) teak wood framing 1¾" (45 mm) thick with wire gauze fixed in position:- 							26.8 to 26.10	 i) This also includes the cost of wood required for extra thickness of chowkat. ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and Rs.50.60 per sq.m. 					
	i) without springs or spring hinges.	Per Sft.	10.10	537.60	sq.m	108.70	5784.60							
	ii) with springs or spring hinges.	ditto	10.10	541.20	ditto	108.70	5823.30							

sr.	Description		Rate (British Sy	stem)	F	Rate (Metric Sy	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 b) teak wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:- i) without springs or spring hinges. ii) with springs or spring hinges. 	Per Sft. ditto	10.10 10.10	494.95 498.85	sq.m ditto	108.70 108.70	5325.65 5367.65		
	 c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes per cm²) fixed to chowkat with ¾" (20 mm) teak wood strips and screws. 	Per Sft.	18.15	148.80	sq.m	195.30	1601.10		
	 d) G.I. wire gauze 22 SWG, 12x12 meshes per square inch (5x5 meshes per cm²) fixed with ½" (13 mm) strip on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc. 	Per Sft.	17.00	507.75	sq.m	182.90	5463.40		
	P/F expanded metal ¹ / ₂ " to ³ / ₄ " (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	22.70	248.05	sq.m	244.25	2669.00		
	Providing and fixing expanded metal ¹ / ₂ " (13 mm) to ³ / ₄ " 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	22.70	376.45	sq.m	244.25	4050.60		
	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-	Ŧ	nance	Depart Depart	men	2°.		26.1 to 26.3 & 26.7	
	a) 2" thick (50 mm) b) 1 ³ / ₄ " thick (45 mm) c) 1 ¹ / ₂ " thick (40 mm)	Per Sft. ditto ditto	53.80 53.80 53.80	932.95 869.90 826.30	sq.m ditto ditto	578.90 578.90 578.90	10038.55 9360.20 8891.00		
	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	a) 2 ¹ / ₄ " (56 mm) thick, with 1 ¹ / ₄ " (30 mm) battens and 1" (25 mm) planks.	Per Sft.	60.50	561.95	sq.m	651.00	6046.60		
	b) 1 ³ / ₄ " (40 mm) thick with 1" (25 mm) battens and ³ / ₄ " (20 mm) planks.	ditto	55.85	484.60	ditto	600.95	5214.30		

	MRS, BI-ANNUAL PE	, 2012) DIS	TRICT LODI	HRAN					
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
~									
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	68.95	300.15	sq.m	741.90	3229.60		
10	Deodar battened ledged and braced doors and windows 2 ¹ / ₄ " (56 mm) thick (1 ¹ / ₄ " (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	65.15	545.70	sq.m	701.00	5871.75	26.1, 26.2 26.4 to 26.6	
11	a) Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the Engineer incharge:-							26.1, 26.2 & 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60 Sq.m) for G.I. facing on one side and Rs.9.40 per Sft. (Rs.101.20
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	28.35 31.20	481.35 501.80	sq.m ditto	305.05 335.70	5179.35 5399.35		per Sq.m) for G.I. sheet facing on both sides.
	b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges and locking arrangements, as directed by the Engineer-in-charge:-	97 and							-ditto-
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	28.35 31.20	179.50 199.95	sq.m ditto	305.05 335.70	1931.40 2151.45		
12	First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm ²) including iron fittings etc. complete:-	H	nance	Depart		ç.		26.8 to 26.10	 i) This also includes the cost of wood required for extra thickness of chowkat.
	 a) deodar wood framing 1¾" (45 mm) thick with wire gauze fixed in position:- 								ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	i) without springs or spring hinges.ii) with springs or spring hinges.	Per Sft. ditto	30.25 30.25	397.80 401.70	sq.m ditto	325.50 325.50	4280.35 4322.30		ixs.50.00 per sq.m.
	 b) deodar wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:- i) without appinge or spring binges 	Dor Sft	20.25	260 AE		225 50	2061 50		
	i) without springs or spring hingesii) with springs or spring hinges	Per Sft. ditto	30.25 30.25	368.45 370.90	sq.m ditto	325.50 325.50	3964.50 3990.90		
	 c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm²) fixed to chowkat, with ³/₄" ('20 mm) thick deodar wood strip and screws. 	Per Sft.	22.70	122.40	sq.m	244.25	1317.00		

	MRS, BI-ANNUAL PE	RIOD (1st	FEBRUARY	, 2012 TO 31	st JULY,	2012) DIS		IRAN	1
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		_							
	 d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to chowkat, with ¹/₂" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm). 	Per Sft.	34.05	334.15	sq.m	366.40	3595.45		
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	50.40	366.60	sq.m	542.30	3944.60	26.1 26.2	
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-								
	a) M.S. angle iron 1½"x 1½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	12.60	130.80	sq.m	135.60	1407.40		
	b) M.S. tee iron 1 ¹ / ₂ "x 1 ¹ / ₂ "x ¹ / ₄ " (40x40x6 mm) welded with M.S. flat 2"x ¹ / ₄ " (50 mm x 6 mm)	Per Sft.	12.60	97.20	sq.m	135.60	1045.85		
15	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 1¼" x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:	T	nance	Depart	nen i	sin a			
	a) single rebateb) double rebate	Per Sft. ditto	19.35 22.55	113.85 129.80	sq.m ditto	208.20 242.65	1225.05 1396.65		
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	1.75	30.35	sq.m door area	18.85	326.55	26.2	
17	Providing and fixing brass spring hinges to wire gauzed doors.	Each	36.30	156.30	Each	36.30	156.30		
18	Providing and fixing sliding bolt to doors:-								
	 iron sliding bolt, 10" (250 mm) long iron sliding bolt, 12" (300 mm) long 	Each ditto	34.05 34.05	82.05 118.05	Each ditto	34.05 34.05	82.05 118.05		
	iii) brass sliding bolt, 10" (250 mm) long	ditto	34.05	124.05	ditto	34.05	124.05		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	iv) brass sliding bolt, 12" (300 mm) long	ditto	34.05	286.05	ditto	34.05	286.05					
19	Extra for brass fittings to doors and windows, except for hinges, which shall be of iron:-											
	 deodar wood panelled or panelled and glazed or fully glazed. 	Per Sft.	1.05	9.85	sq.m	11.30	106.00					
	ii) deodar wood wire gauzed shutters.	ditto	1.05	7.20	ditto	11.30	77.45					
20	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	108.90	296.10	Each	108.90	296.10					
21	Providing and fixing, approved quality mortice lock.	Each	151.25	336.05	Each	151.25	336.05					
22	Providing and fixing, expended metal ¹ / ₂ " to ³ / ₄ " (13 mm to 20 mm) mesh 16 gauge.			\mathcal{O}								
	a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc.	Per Sft.	22.70	195.90	sq.m	244.25	2107.90					
	 b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm) 	ditto	22.70	283.80	ditto	244.25	3053.70					
23	 a) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. complete. 	Per Sft.	72.60	1337.15	sq.m	781.20	14387.95		For hollow frame shutter with commercial ply on one side, the composite rate shall be reduced by Rs.54.00 per Sft;or Rs.580.00 per Sqm and for hollow frame			
		55 5	12 6-629 9 1-92 7 10 P						shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per Sft. or Rs.245.00 per Sq. metre.			
	 b) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm)depth with shelves, shutters, brass fittings, etc., without boxing and back, complete. 	Per Sft.	54.45	418.05	sq.m	585.90	4498.20					
24	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ¹ / ₄ " (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1 ¹ / ₂ :3) shelves 1 ¹ / ₂ " (40 mm) thick including 3 coats of painting.	Per Sft.	45.70	301.65	Sq.m	491.50	3245.75					

	MRS, BI-ANNUAL PER	IOD (1st	FEBRUARY	2012 TO 31	st JULY	, 2012) DIS		IRAN	
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
25	Providing and fixing wooden box type wardrobe 22" (550 mm) deep including ³ / ₄ " (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods, etc. including three coats of enamel paint:- i) Partal wood boxing and deodar wood								If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood bracing and deodar wood lipping is used, the composite rate will be reduced by Rs.13.00 per Sft. or
	shelves and leaves, etc.	Per Sft.	83.75	543.60	sq.m	901.35	5849.05		Rs.140.00 per Sq. metre.
	Deodar wood boxing, and deodar wood shelves and leaves, etc.	ditto	83.15	716.95	ditto	894.80	7714.55		
	Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete.	Per Sft.	32.50	480.60	Sq.m	349.65	5171.25		
27	Providing and fixing chowkat for doors, windows and C. windows, including holdfast, etc.			200					
	 a) Teak wood b) Deodar wood c) Shisham wood 	Per Sft. ditto ditto	16.15 10.10 12.10	446.55 314.50 161.40	Sq.m ditto ditto	173.60 108.50 130.20	4804.70 3383.85 1736.65		
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	 a) 1" (25 mm) thick b) 3/4" (20 mm) thick c) 1/2" (13 mm) thick 	Sft. ditto ditto	18.15 18.15 18.15	246.45 189.30 132.45	sq.m ditto ditto	195.30 195.30 195.30	2651.65 2037.05 1425.05		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	 i) 1" (25 mm) thick ii) 1¹/₂" (40 mm) thick iii) 2" (50 mm) thick 	Sft. ditto ditto	18.15 18.15 18.15	246.45 360.45 474.45	sq.m ditto ditto	195.30 195.30 195.30	2651.65 3878.30 5104.95		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
30	 Making and fixing cleats for doors and windows, including hinges and screws. 	Each	21.80	83.20	Each	21.80	83.20	26.1 and 26.2					
	 Making and fixing cleats with brass hooks for roof ventilators. 	Each	29.05	60.25	Each	29.05	60.25						
	 Providing and fixing door stops of 1¹/₂" (40 mm) dia rubber block. 	Each	3.05	46.55	Each	3.05	46.55						
	d) Providing and fixing G.I. hook with clamps for doors.	Each	0.95	6.05	Each	0.95	6.05						
31	Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.		1	5				ditto					
	a) Shisham wood	Per Rft.	83.00	231.20	Metre	272.30	758.40						
	b) Teak wood	ditto	61.65	585.05	ditto	202.15	1919.05						
	Deodar wood dado or picture rail 3"x1½" (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete.	Per Rft.	30.80	177.50	Metre	101.10	582.15	26.1 26.2					
33	Sawing wood by hand:-		2	Ser Ser									
	a) Soft wood (deodar, kail or chir).b) Hard wood (shisham, kikar, teak or sahl).	100Sft. ditto	363.00 484.00	Depart	sq.m ditto	39.05 52.10	-						
34	Sawing wood by machine:												
	a) Soft wood b) Hard wood	100Sft. ditto	214.17 321.85	-	sq.m ditto	23.05 34.65	-						
35	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	25.40	298.05	sq.m	273.40	3207.00	26.1					
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	30.25	97.45	sq.m	325.50	1048.55	ditto					
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	108.90	6137.70	Each	108.90	6137.70	ditto					
38	Dismantling and refixing eave boards.	Per Rft.	7.80		Metre	25.50							

	MRS, BI-ANNUAL P	ERIOD (1st	FEBRUARY	, 2012 TO 31	st JULY,	2012) DIS	TRICT LODE	IRAN	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	1
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1 ¹ / ₂ " (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	120.85	1887.85	Metre	396.45	6192.15	26.1	
40	Providing and fixing partition, including frame work:-								
	a) Sheets on one side of framework:-								
	i) Hard boardii) Ply wood ¼" (6 mm) thickiii) Masonite	100Sft. ditto ditto	567.20 567.20 567.20	11283.00	sq.m ditto ditto	61.05 61.05 61.05	1078.50 1214.05 1268.30		
	b) Sheets on both sides of frame work:-		/ ×	6					
	 i) Hard board ii) Ply wood ¹/₄" (6 mm) thick iii) Masonite 	100Sft. ditto ditto	680.65 680.65 680.65	11166.00 21413.05 14694.00	sq.m ditto ditto	73.25 73.25 73.25	1201.45 2304.05 1581.10		
41	Providing and fixing ceiling, including frame work:-				1 Site				
	 i) Hard board ii) Chip board iii) Ply wood ¹/4" (6 mm) thick iv) Masonite 	100Sft. ditto ditto ditto	1130.95 1130.95 1130.95 1130.95	7105.85 9145.85 9385.85 9025.85	sq.m ditto ditto ditto	121.70 121.70 121.70 121.70	764.60 984.10 1009.90 971.20		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-	Ŧ	nance	Depart		5			In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	 i) ³/₄" (20 mm) thick ii) 1" (25 mm) thick 	100Sft. ditto	1276.45 1276.45	7200.25 7278.95	sq.m ditto	137.35 137.35	774.75 783.20		
	b) Partal wood frame panelling:								
	i) ³ / ₄ " (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	1276.45 1276.45	4650.25 4776.25	sq.m ditto	137.35 137.35	500.35 513.95		
43	a) Fixing door, including chowkats.	Each	206.25	-	Each	206.25	-		
	b) Fixing windows, including chowkats.	ditto	103.15	-	ditto	103.15	-		

	MRS, BI-ANNUAL PER	RIOD (1st	FEBRUARY	, 2012 TO 31	st JULY	, 2012) DIS		IRAN	
Sr.	Description		Rate (British Sy	stem)	I	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	1
44	 a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty. 	Per Sft.	12.90	35.05	sq.m	138.75	377.05	26.12	
	 b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty. 	Per Sft.	16.25	61.95	sq.m	175.00	666.60		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	24.55	69.05	sq.m	263.90	742.95	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	9.00	10.05	sq.m	97.05	108.10		
	 b) Cutting to required size and fixing glass panes with wooden fillets and putty. 	Per Sft.	13.55	29.45	sq.m	145.95	317.00		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-			\mathcal{I}					
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	20.80	79.85	sq.m	223.70	858.95		
	b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sft (2.25 sq.m).	Per Sft.	20.80	80.00	sq.m	223.70	860.90		
48	Providing and fixing 1 ¹ / ₂ " (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with:-	1			53				
	 i) M.S. angle iron 1¹/₂"x1¹/₂"x¹/₄", welded i) (40 mmx 40 mmx 6mm) with M.S. flat 2"x¹/₄" (50 mm x 6 mm) 	Per Sft.	77.80	539.00	sq.m	837.35	5799.90		
	 ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm) 	Per Sft.	77.80	495.30	sq.m	837.35	5329.40		
49	Providing and fixing 1 ¹ / ₂ " (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1 ¹ / ₄ " (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1 ¹ / ₂ "x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complet¢ in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	 M.S. angle iron 1¹/₂"x1¹/₂"x¹/₄", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¹/₄" (50 mm x 6 mm) 	Per Sft.	54.00	455.15	sq.m	581.30	4897.25		

Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) M.S. tee iron 1¹/₂"x1¹/₂"x¹/₄", welded (40 mmx40 mmx 6mm) with M.S. flat ¹/₂"x¹/₄" (13 mm x 6 mm) 	Per Sft.	54.00	421.55	sq.m	581.30	4535.85		
50	Providing and fixing 1½" (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	29.65	311.30	sq.m	318.85	3349.75		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	52.75	307.85	sq.m	567.50	3312.65		
52	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	10.90	18.45	Metre	35.70	60.50		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	4.55 11.011 CB	107.20 Depart	Metre	14.90	351.55		
54	Providing and fixing M.S. flat ¹ / ₂ "x1/8" (13mm x 3mm) grill including ³ / ₄ " x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	29.30	155.55	sq.m	315.15	1673.60		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cm ²) fixed to steel window, complete with flat iron patti ½"x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	9.25	44.25	sq.m	99.40	475.90		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 per square metre.
56	Providing and fixing wooden moulding stopper 2 ¹ / ₂ "x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	a) Teak wood moulding	Per Sft.	11.35	93.40	sq.m	122.05	1005.10		

	MRS, BI-ANNUAL PE	TRICT LOD	IRAN						
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) Deodar wood moulding	ditto	11.35	47.95	ditto	122.05	515.90		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between braces with 1:3:6 PCC fixing ply of approved quality including holdfasts complete in all respects.								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))
	a) Teak wood plyb) With commercial ply	Per Sft. ditto	27.90 27.90	261.30 253.25	sq.m ditto	300.45 300.45	2811.50 2724.95		
58	Providing and fixing ornamental wooden architrave $3" \times (1\frac{1}{2}" \text{ tapered to }\frac{1}{4}")$ all along the door frame complete in all respect.			5					
	a) Teak wood architraveb) Deodar wood architrave	Per Sft. ditto	5.25 5.25	59.80 28.70	sq.m ditto	56.55 56.55	643.30 308.80		
59	Providing and fixing Vin board cabinet 3/4" thick with drawers 3"deep in 'Kitchen including termite proofing and polishing with synthetic enamel as specified, with handles hinges, screws etc., complete in all respects.	100			7				
	 i) 1-1/2' deep,without back ii) 1-1/2' deep,with back iii) 2' deep,without back iv) 2' deep,with back 	Per Sft Per Sft Per Sft Per Sft	61.90 61.90 61.90 61.90	400.70 442.70 441.65 483.65	sq.m sq.m sq.m sq.m	665.80 665.80 665.80 665.80	4311.55 4763.50 4752.20 5204.10		

13. PAINTING AND VARNISHING

1 The rates include charges for scaffolding and other arrangements

2 The rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERI			2012 TO 31	st JULY,	2012) DIS	STRICT LOD	HRAN	
Sr.	Description	1	Rate (British Sy	stem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	a) Cleaning painted wood work with oil and water.	100 Sft.	71.30	103.35	sq.m	7.65	11.10		
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	47.50	87.10	sq.m	5.10	9.35	27.7	
2	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	142.55	-	sq.m	15.35	-	27.3	
3	Scraping, brushing and removing old paint from metal surface.	100 Sft.	570.25) -)	sq.m	61.35	-	27.9	
4	Painting old surfaces:-	1000			日間			27.1 27.3 &	
	 Painting corrugated surfaces, patent roofing, etc. with oil paint. 		No.	- 16	LØ.			27.9	
	i) first coatii) each subsequent coat	100 Sft. ditto	158.25 119.90	317.85 201.50		17.05 12.90	34.20 21.70		
	 b) Painting sashes, fanlights, glazed or gauzed doors and windows:- 	Ŧ	nance	Depart	ment				
	i) first coatii) each subsequent coat	100 Sft. ditto	95.90 81.55	181.10 151.15		10.30 8.75			
	c) Painting doors and windows, any type:								
	i) first coatii) each subsequent coat	100 Sft. ditto	158.25 119.90	321.45 244.10	-	17.05 12.90	34.60 26.25		
	 Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:- 								
	 i) first coat ii) each subsequent coat e) Painting fillets, framings, skirtings, pipes, gutters and similar linear work not exceeding 6" in girth:- 	100 Sft. ditto	95.90 81.55	181.10 151.15	-	10.30 8.75	19.50 16.25		

	MRS, BI-ANNUAL PERI	OD (1st I	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	OHRAN	
Sr.	Description]	Rate (British Sys	stem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) first coatii) each subsequent coat	100 Lft. ditto	81.55 57.55	166.75 127.15	Metre ditto	2.65 1.90	5.45 4.15		
	 f) Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:- 								
	i) first coatii) each subsequent coat	100 Nos. ditto	226.05 206.50	385.65 291.70	100 Nos. ditto	226.05 206.50	385.65 291.70		
	 g) Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:- 								
	i) first coatii) each subsequent coat	100 Nos ditto	516.70 309.25	991.90 546.85	100 Nos ditto	516.70 309.25	991.90 546.85		
5	Painting new surface:-				JU.			27.1 27.2 &	
	 Preparing surface and painting corrugated surface, patent roofing, etc. 		E	-67	7 % 1			27.9	
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	224.25 79.50	397.05 278.10	sq.m ditto	24.15 8.55	42.75 29.90		
	 b) Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):- 	Ŧ	nance	Depar					
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	95.40 69.05	239.10 181.85	sq.m ditto	10.25 7.45	25.75 19.55		
	 Preparing surface and painting of doors and windows any type (including edges):- 								
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	224.25 79.50	393.45 278.10	sq.m ditto	24.15 8.55	42.35 29.95		
	 d) Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:- i) priming coat. ii) each subsequent coat of paint. 	100 Sft. ditto	151.35 69.05	255.15 181.85	sq.m ditto	16.30 7.45	27.45 19.55		

	Description	I	Rate (British Sys	stem)	Rat	te (Metric Sy	stem)	Spec.	Remarks
•		Unit	Labour	Composite	Unit	Labour	Composite	No.	
e)	Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-								
	i) priming coat.ii) each subsequent coat of paint.	100 Lft. ditto	122.30 46.05	201.25 139.05	Metre ditto	4.00 1.50	6.60 4.55		
f)	Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-								
	i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	359.70 175.20	854.40 568.80	100 Nos. ditto	359.70 175.20	854.40 568.80		
g)	Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-	. ide			Juli.				
	i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	991.65 300.30	1661.25 1005.90	100 Nos. ditto	991.65 300.30	1661.25 1005.90		
h)	Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	14.50	28.55	sq.m	1.55	3.05		
Ap	pplying Khanki Mixture hot to barrage			0-3				27.10	
	tes:-	Ti	nance	Depart					
i) ii)	first coat second coat	100 Sft. ditto	119.90 98.10	340.90 239.25	sq.m ditto	12.90 10.55	36.70 25.75		
Fre	ench polishing complete:-							27.6	
a) b)	on new work on old work	100 Sft. ditto	1137.10 618.50	1188.45 646.85	sq.m ditto	122.35 66.55	127.90 69.60		
	rnishing wood work, including cleaning and preparing face.								
a) b) c)	first coat second coat third coat	100 Sft. ditto ditto	95.90 35.95 35.95	193.10 109.75 94.15	sq.m ditto ditto	10.30 3.85 3.85	20.80 11.80 10.15		

	MRS, BI-ANNUAL PERI	OD (1st I	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	HRAN	Γ
Sr.	Description	1	Rate (British Sy	stem)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m)	100 Sft.	118.80	949.70	sq.m	12.80	102.20		
	 ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m) iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m) 	ditto ditto	114.05 94.10	535.05 515.10	ditto ditto	12.25 10.10	57.55 55.40		
	iii) 10 lbs. per 100 Sit. (4.54 Kg per 5q.iii)	unto	94.10	515.10	unto	10.10	55.40		
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	4.80	5.35	Per No.	4.80	5.35	27.1	
11	Writing letters or figures at any surface with reflective paint	Per Letter	4.80	5.10	Per Letter	4.80	5.10	27.1	
	of approved quality and colour per letter per inch height.	per inch			per 25 mm				
		height			height				
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	5.40	6.20	ditto	5.40	6.20	ditto	
			(
13	Coaltar painting:	101			一点			27.8	
	a) first coat, laid hot	100 Sft.	95.85	752.05	sq.m	10.30	80.90	to 27.11	
	b) second coat, laid hot	ditto	58.10	470.80	ditto	6.25	50.65		
		NOS -	No.	& /	1436				
14	Solignum painting:-	1.3						27.8	
	a) one coat, applied hot	100 Sft.	79.85	102.65	sq.m	8.60	11.05		
	b) two coats, applied hot	ditto	121.00	157.10	ditto	13.00	16.90		
15	Creosote painting:-	T	nance	Depart	ment			ditto	
	errore Lummô.								
	a) one coat, applied hot	100 Sft.	95.85	199.05	sq.m	10.30	21.40		
	b) two coats, applied hot	ditto	145.20	318.00	ditto	15.60	34.20		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	361.70	376.10	sq.m	38.90	40.45	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	142.55	149.75	sq.m	15.35	16.10	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	24.00	28.40	Each	24.00	28.40	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	47.95	56.50	per Metre	157.30	185.25	ditto	
20	Painting sounding rods and other gauges, reading to 10th	Per Lft.	24.00	26.70	per Metre	78.65	87.50	27.1	

	MRS, BI-ANNUAL PERI	OD (1st I	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	DHRAN	
Sr.	Description]	Rate (British Sy	stem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	of a foot (metre)								
21	Painting leveling staves.	Per Lft.	72.15	76.40	per Metre	236.70	250.65		
22	 Painting and lettering mile/Km stones, on both sides: 							ditto	
	i) one coatii) two coats	Each ditto	51.40 89.95	82.30 137.95	Each ditto	51.40 89.95	82.30 137.95		
	 b) Painting and lettering Furlong^{1/2} Km stones, on both sides:- 							27.1	
	i) one coatii) two coats	Each ditto	6.85 12.00	10.40 18.30	Each ditto	6.85 12.00	10.40 18.30		
	c) Painting and lettering Sign posts:-	, ide			- W.				
	i) one coatii) two coats	Each ditto	57.55 94.95	77.35 128.55	Each ditto	57.55 94.95	77.35 128.55		
23	Removing paint or varnish from wall.	100 Sft.	285.10	<u> </u>	sq.m	30.70	-	27.12	
24	Scraping from hydraulic gates:-		n Sta	R P	S.S.			27.1	
	a) Khanki paint b) Aluminium paint	100 Sft. ditto	570.25 570.25	Depari	sq.m ditto	61.35 61.35	-		
25	Painting letters with shade.	per letter per inch height	7.65	7.65	per letter per 25 mm height	7.65	7.65	27.1	
26	Scraping rust from old rail or girders.	100 Sft.	427.70	463.70	sq.m	46.00	49.90	27.9 27.10	
27	Chiselling old paint from brick work.	100 Sft.	570.25	594.25	sq.m	61.35	63.95	27.12	
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	475.20	485.20	sq.m	51.15	52.20		
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	142.55	185.80	sq.m	15.35	20.00	27.9	
30	Cleaning and painting punkha poles, including fixing	Each	90.75	98.05	Each	90.75	98.05	27.3	

	MRS, BI-ANNUAL PEF	RIOD (1st	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	OHRAN	
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	hooks.								
31	Preparing surface and painting with emulsion paint:-							27.12	
	a) first coatb) 2nd and each subsequent coat	100 Sft. ditto	112.95 86.85	256.10 200.00	sq.m ditto	12.15 9.35	27.55 21.50		
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.							27.12	
	a) new surface:								
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	112.95 86.85	178.65 144.85	sq.m ditto	12.15 9.35	19.20 15.60		
	b) old surface:	, ide			Juli.				
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	112.95 86.85	141.15 114.40	sq.m ditto	12.15 9.35	15.20 12.30		
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	100711			1,953				
	a) new surface:								
	i) 1st coat ii) 2nd coat	% sft % sft	430.30 233.30	723.50 353.10	sq.m sq.m	46.30 25.10	77.85 38.00		
	b) old surface:	%sft	233.30	353.10	sq.m	25.10	38.00		
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	0.70	1.40	Metre	2.35	4.65		
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads comlpete	Per Rft.	0.95	8.00	Metre	3.15	26.25	AASHTO M248-91	Rates shall be reduced by Rs.0.50 P.Rft or Rs.1.65 P.Mtr. If glass beads
35	in all respect. Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	25.95	56.55	Job	25.95	56.55	(2000)	are not used.
36	Repainting of iron poles with cross arms, with bitumen or	Per Job	60.50	169.10	Job	60.50	169.10		

	MRS, BI-ANNUAL I	PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	HRAN	
Sr.	Description	R	ate (British Syst	tem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	other approved paint.								
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:								
	 i) upto 40 mm (1¼") dia ii) above 40 mm (1½") to 50 mm (2") dia iii) above 50 mm (2") to 100 mm (4") dia 	Per Rft. ditto ditto	0.55 1.10 1.85	1.80 2.90 4.55	Metre ditto ditto	1.80 3.65 6.05	5.30 9.55 14.95		
38	Repainting main switches and branch distribution boards of all sizes and types, with approved paint (complete set).	Per Job	12.00	55.90	Job	12.00	55.90		
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	45.60		sq.m	4.90	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.

Finance Department

14. LINING OF CANALS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts

- 2 The rates also include curing for specified period wherever necessary.
- 3 Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

	MRS, BI-ANNUAL P			RY, 2012 TO	31st JU	ILY, 2012)	DISTRICT LC	DHRAN	
Sr.	Description		Rate (British Sy	rstem)	ŀ	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3	
	a) in bedb) on slope	100Sft. ditto	314.35 428.75	-	sq.m ditto	33.80 46.15	-		
2	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	757.70	1229.30	sq.m	81.55	132.25	ditto	
3	Cement plaster 1⁄2" (13 mm) thick ratio 1:10.		. ($\langle \rangle$			ditto	
	a) in bed b) on slope	100Sft. ditto	551.40 686.40	775.60 910.60	sq.m ditto	59.35 73.85	83.45 98.00		
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	1	1 18	فكومت ينجا-	7,28	1999 1997		ditto	
	a) in bed b) on slope	100Sft. ditto	551.40 686.40	939.25 1074.25	sq.m ditto	59.35 73.85	101.05 115.60		
5	Cement plaster 1 ¹ / ₂ " (40 mm) thick ratio 1:6.		Financ	e Deva	rtme	72.L		ditto	
	a) in bedb) on slope	100Sft. ditto	686.40 851.40	1624.25 1789.25	sq.m ditto	73.85 91.60	174.75 192.55		
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bedb) on slope	100Cft. ditto	3220.80 3694.35	12919.75 13393.30	cu.m ditto	1137.60 1304.85	4563.25 4730.50		payable separately.
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are
	a) in bed	100Cft.	3220.80	14190.00	cu.m	1137.60	5011.90		payable separately.
	b) on slope	ditto	3694.35	14663.55	ditto	1304.85	5179.15		

	MRS, BI-ANNUAL	PERIOD (1st FEBRUA	RY, 2012 TO	31st JU	JLY, 2012)	DISTRICT LO	DHRAN	
Sr.	Description		Rate (British Sy	rstem)]	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
8	Brick lining 9"x4 ¹ / ₂ "x3" (225x113x75 mm) in 1:6 cement, sand mortar:- a) in bed b) on slope	100Cft. ditto	3220.80 3694.35	14197.75 14671.30	cu.m ditto	1137.60 1304.85	5014.65 5181.90	28.2	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are payable separately.
9	Brick lining 9"x41/2"x3" (225x113x75 mm), in 1:3 cement, sand mortar:- a) in bed	100Cft.	3220.80	15468.00	cu.m	1137.60	5463.30	ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are payable
10	 b) on slope Cement concrete lining, using washed screened and graded stone aggregate:- a) in bed:- 	ditto	3694.35	15941.55	ditto	1304.85	5630.55	20.1, 28.1 & 28.3	separately.
	 i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8 b) on slope:- 	100Cft. ditto ditto	2820.85 2820.85 2820.85	16253.15 14103.25 12566.75	cu.m ditto ditto	996.30 996.30 996.30	5740.60 4981.25 4438.60		
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	3258.75 3258.75 3258.75	16691.05 14541.15 13004.65	cu.m ditto ditto	1151.00 1151.00 1151.00	5895.30 5135.95 4593.25		

15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Cutting Ransome and Larson piles.	Per cut	72.60	-	Per cut	72.60	-	29.1- 29.3					
2	Cutting universal piles.	Per cut	107.45	-	Per cut	107.45	-	ditto					
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	1804.45		sq.m	194.15	-	ditto	 The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre). The rates are for the tackle gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government. T-piles and adjustable junction 				
4	Driving steel piles, more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	1731.85	ce Dep	sq.m	186.35	-	ditto	piles will be counted as two piles. ditto				
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	1296.25	-	sq.m	139.50	-	ditto	ditto				
6	Dolleying piles.	Each	115.10	-	Each	115.10	-	ditto	Upto 5' (1.5 m) dolleying.				
7	Drilling holes in piles by hand.	Each	10.00	-	Each	10.00	-	ditto					
8	Raising and lowering machine.	Per Ft.	1682.55	-	Metre	5518.80	-	ditto					
9	Turning Machine, 90°.	Per Job	2584.05	-	Per Job	2584.05	-	29.1 to 29.3					
10	Turning Machine, 135°.	Per Job	3164.85	-	Per Job	3164.85	-	ditto					
11	Turning Machine, 180°.	Per Job	4315.85	-	Per Job	4315.85	-	29.1 to 29.3					

	MRS, BI-ANNUAL	PERIOD	(1st FEBRU	ARY, 2012 T	۲O 31st J	IULY, 201	12) DISTRIC		AN
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
12	Travelling machine (light).	Per Chain	5105.75	-	30 M.	5105.75	-	ditto	
13	Loading and unloading piles.	Ton	105.50	-	Tonne	103.85	-	ditto	To be done by hand carts or ramps, including cost of ropes.
14	Dismantling piling machine.	Each	10314.50	-	Each	10314.50	-	ditto	
15	Erecting piling machine.	Each	11901.30	-	Each	11901.30	-	ditto	
16	Carriage of piling machine under different conditions.	per chain	2082.45	*	30 M	2082.45	-	ditto	



Finance Department

16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- 4 Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
 - i) the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
 - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
 - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the point of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, BI-ANNUAL P	ERIOD (1st I	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	Ra	ate (British Syste	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	541.75		cu.m	191.30								
2	Weaving matresses.	100Cft.	1026.45		cu.m	362.50								
3	 a) Supplying and filling jute bags 1.25 (0.035 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	16.05	28.40	Per Baq	16.05	28.4		The rate does not include supply of sand or earth for filling bags, which will be paid extra.					
	 b) Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water. 	ditto	24.95	37.30	Per Baq	24.95	37.3		-ditto-					
4	 a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	38.40	85.20	Per Bag	38.40	85.20		The rate does not include supply of sand or earth for filling bags, which will be paid extra.					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
_	 b) Supply and filling new jute bags 4 to 5 cft (0.11 to 0.14 cu.m) capacity, with sand or earth, sewing and laying in position, under water. 	ditto	54.85	101.65	ditto	54.85	101.65		-ditto-		
5	Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled with sand or earth:-										
	a) 1st chain (30 m)	100 Nos	142.55		% Nos	142.55					
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	51.30	5	Per 30 m Per 100 Nos/	51.30					
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	19.95		ditto	19.95					
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-				C. C.						
	a) 1st chain (Ist 30 metre)	100 Nos	570.25	Depar	% Nos	570.25					
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	199.60	10	Per 30 m per %Nos	199.60					
	 c) 5th and subsequent chains (150 m and subsequent every 30 m) 	ditto	77.00		ditto	77.00					
7	Rolling matresses to river edge and floating, after unroling:-										
	a) area of matress upto 2,000 Sft. (186 sq.m)	100Sft.	320.75		sq.m	34.50					
	b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m)	100Sft.	534.60		sq.m	57.50					
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	623.70		ditto	67.10					
8	Sewing empty cement bags in sheets.	100 Nos	498.95	526.95	% Nos	498.95	526.95				
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	695.00	767.20	cu.m	245.45	271		Measured in the shape of compact round bundles and of size specified		

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description	R	ate (British Syst	em)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
									for the work, before filling at site.
10	Launching the above and placing in position.	100Cft.	342.15		cu.m	120.85			
11	Supply within 5 chains (150 m):-								
	a) Boulders 9" (225 mm) and above	100Cft.	1032.15		cu.m	364.50			
	b) Over size shingle 3" to 9"(75 to 225 mm)	ditto	690.00		ditto	243.65			
	c) Mixed graded shingle	ditto	818.30		ditto	289.00			
12	Supplying Munj or Patha Trungers 6" (150 mm) mesh to hold 3 Cft. (0.085 cu.m)	Each	44.55	75.95	Each	44.55	75.95		
13	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to make crate):-								
	a) 6" (150 mm) mesh				习袋				
	i) 15 SWG wireii) 10 SWG wire	100Sft. ditto	503.60 539.55	762.30 1379.55	sq.m ditto	54.20 58.05	82.00 148.45		
	iii) 8 SWG wire	ditto	539.55	1856.65	ditto	58.05	199.8		
	b) 4" (100 mm) mesh		n Sta	R. C	Ser.				
	i) 15 SWG wire ii) 10 SWG wire	100Sft. ditto	647.45 719.40	1036.40 1976.90	sq.m ditto	69.65 77.40	111.5 212.70		
	iii) 8 SWG wire	ditto	719.40	2690.90	ditto	77.40	289.55		
14	Providing and laying shingle on top of bund, including handling of materials within three chains.	100Cft.	356.40	646.80	cu.m	125.85	228.45		
15	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)								
	a) stone or boulder	100Cft.	623.70	1019.70	cu.m	220.25	360.1		The rate includes supply of brick
	b) shingle or spawlc) brick bats	ditto ditto	623.70 481.15	914.10 1207.15	ditto ditto	220.25 169.95	322.8 426.35		bats to site of work.
16	Supply and dumping by boat, including loading into boat within three chains (90 m) lead, and hire charges of boat and boatman.								The rate includes supply of brick bats to site of work.
	a) stone or boulder	100Cft.	1095.60	1491.60	cu.m	386.95	526.85		
	b) shingle or spawl	ditto	1095.60	1386.00	ditto	386.95	489.55		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	R	ate (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	c) brick bats	ditto	953.05	1679.05	ditto	336.60	593.05					
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	826.30	1552.30	cu.m	291.85	548.3		The rate includes supply of brick bats to site of work.			
18	Supplying and filling bricks in crates and hand packing (excluding cost of crates).	100Cft.	1004.50	10904.50	cu.m	354.80	3851.5		The rate includes supply of bricks to site of work.			
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-											
	i) stone or boulderii) shingle or spawl	100Cft. ditto	1147.10 1147.10	1543.10 1437.50	cu.m ditto	405.15 405.15	545.00 507.70					
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	125.45) -	cu.m	44.30	-					
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	627.25		cu.m	221.55	-					
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	356.40	756.40	sq.m	38.35	81.4	30.1				
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	891.00	931.00	sq.m	95.85	100.20	ditto				
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1 ¹ /2' (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	1972.10	D 2911.20	sq.m	212.20	313.25		The cost of placing earth between rolls shall be paid separately, as earthwork.			
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	664.95	726.45	sq.m	71.55	78.15		Measurement to be made of the area of elevation on one face only.			
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	1148.40	1221.80	sq.m	123.55	131.45					
27	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	719.40	1391.70	cu.m	254.10	491.55					
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	2123.55	2721.15	cu.m	750.05	961.1					

	MRS, BI-ANNUAL PE	RIOD (1st I	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr. No.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks									
INO.		Unit	Labour	Composite	Unit	Labour	Composite	No.										
29	Providing and laying stone pitching, for top layer only:-																	
	a) one slopeb) on level	100Cft. ditto	1772.10 1593.90	2369.70 2191.50	cu.m ditto	625.90 562.95	837 774.05											
30	Providing and laying stone or spawl filling:-																	
	a) on level	100Cft.	473.55	737.55	cu.m	167.25	260.50											
	b) on slope	ditto	581.35	845.35	ditto	205.35	298.55											
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.			0														
	 i) top layer on slope ii) top layer on level iii) stone pitching/filling on slope or on level (other than top layer). 	100Cft. ditto ditto	2340.50 2162.30 1252.20	4635.15 4456.95 3621.55	cu.m ditto ditto	826.65 763.70 442.30	1637.15 1574.20 1279.15											
32	Grouting stone pitching or apron, etc. in:-	100			53													
	a) cement, sand mortar 1:3b) cement, sand mortar 1:8	100Sft. ditto	801.00 679.80	4135.80 2376.85	sq.m ditto	86.20 73.15	445 255.75											
33	Sand grouting in stone apron, with high pressure hose.	100Sft.	271.90	871.90	sq.m	29.25	93.80											
34	Grouting stone filling or pitching, with bajri.	100Cft.	445.50	1237.50	cu.m	157.35	437.1											
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	1660.05	-	cu.m	586.30	-											
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cft.	570.25	-	cu.m	201.40	-											
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	473.55	1265.55	cu.m	167.25	447.00											
38	Grouting jharies between blocks with bajri.	100Cft.	473.55	1001.55	cu.m	167.25	353.75											
39	Breaking stone into spawls and stacking	100Cft.	427.70	-	cu.m	151.05	-											
	Canal and Roads																	

	MRS, BI-ANNUAL PEI	RIOD (1st	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOI	DHRAN	
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	rstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-								
	a) upto 2.0' (600 mm) F.S. depth	Each	14.30	-	Each	14.30	-		
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	16.10	-	ditto	16.10	-		
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	21.45	-	ditto	21.45	-		
	d) above 4.0' (1200 mm) F.S. depth	ditto	53.60	-	ditto	53.60	-		
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-		~	5					
	 a) i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead. 	100 Nos	712.80	740.80	% Nos	712.80	740.80		
	ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	287.75	(فارب	100 Nos	287.75	-		
	iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	406.55		100 Nos	406.55	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	35.65	57.50	Per 30 Metre of one row	35.65	57.50		
	 v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	536.70	687.10	ditto	536.70	687.10		
	 b) i) Cutting and supplying unsharpened pegs 4.0' (1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	79.65	111.50	100 Nos	79.65	111.50		
	ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	287.75	-	100 Nos	287.75	-		
	iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	498.55	-	100 Nos	498.55	-		

	MRS, BI-ANNUAL PE								
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	rstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	35.65		Per 30 M of one row	35.65			
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1254.00		ditto	1254.00			
	 c) i) Cutting and supplying unsharpened pegs 5.0' (1.5 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	99.65	139.50	100 Nos	99.65	139.50		
	ii) Sharpening one end of 5' (1.5 m) long pegs, 3" to6" (75 to 150 mm) dia.	100 Nos	302.30		100 Nos	302.30	-		
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	575.50		100 Nos	575.50	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	35.65	57.50	Per 30 M of one row	35.65	57.50		
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	Per chain of one row	11.6312.68 544.50	754.90	ment	544.50	754.90		
	 d) i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1425.60	1473.45	100 Nos	1425.60	1473.45		
	ii) Sharpening one end of 6' (1.8 m) long pegs, 3" to6" (75 to 150 mm) dia.	100 Nos	359.85	-	100 Nos	359.85	-		
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	690.60	-	100 Nos	690.60	-		
	iv) Tying pegs with Munj, Patha ban (one line,	Per			Per Chain				

	MRS, BI-ANNUAL PE								
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	incuding tying around the pegs).	Chain of one row	35.65	57.50	of one row	35.65	57.50		
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	1432.20	1687.70	ditto	1432.20	1687.70		
	 e) i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1069.20	1168.40	100 Nos	1069.20	1168.40		
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	460.40) - 	100 Nos	460.40	-		
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3" to 6" (75 to 150 mm) dia driven 2' (600 mm) below the available bed or ground (average).	100 Nos	762.45		100 Nos	762.45	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per chain of one row	35.65	47.75	Per 30 M of one row	35.65	47.75		
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	Per Chain of one row	1613.70	1914.30	Per 30 M of one row	1613.70	1914.30		
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-								
	 a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2¹/₂" to 5" (63 m to 125 mm) dia. 	100 Nos	6600.00	-	100 Nos	6600.00	-		
	ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	402.85	-	100 Nos	402.85	-		
	iii) Driving Bamboos 8'-1" to $10.0'$ (2.46 to 3.05 m) long $2\frac{1}{2}"$ to 5" (63 to 125 mm) dia, driven 2.5' (750 mm) below the available bed or ground (average).	100 Nos	834.50	-	100 Nos	834.50	-		

	MRS, BI-ANNUAL PE	HRAN							
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	53.45	87.75	Per 30 M of one Row	53.45	87.75		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1973.40	2363.80	ditto	1973.40	2363.80		
b	i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2 ¹ / ₂ " to 5" (63 to 125 mm) dia.	100 Nos	-	10200.00	100 Nos	-	10200		
	 ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia. 	100 Nos	460.40	5	100 Nos	460.40	-		
	iii) Driving Bamboos 10'-1" to 12.0' $(3.07 \text{ to } 3.66 \text{ m})$ long 2½" to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average).	100 Nos	906.30		100 Nos	906.30	-		
	iv) Tying Bamboos $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	178.20	788.90	Per 30 M of one Row	178.20	788.90		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	2420.55	2916.55	ditto	2420.55	2916.55		
c)	i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2 ¹ / ₂ " to 5" (63 to 125 mm) dia.	100 Nos	-	10800.00	100 Nos	-	10800.00		
	 ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	517.95	-	100 Nos	517.95	-		
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long $2\frac{1}{2}$ " to 5" dia, driven 3.5 ' (1.07 mm) below the available bed or ground (average).	100 Nos	1035.95	-	100 Nos	1035.95	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	178.20	788.90	Per 30 M of one row	178.20	788.90		
	v) Cutting and supplying brushwood from canal	ditto	2867.70	3438.90	ditto	2867.70	3438.90		

	MRS, BI-ANNUAL PI	ERIOD (1st	FEBRUARY,	2012 TO 31	st JULY,	2012) DIS	STRICT LOD	OHRAN	T
Sr.	Description	R	ate (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).								
	 d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	-	12000.00	100 Nos	-	12000.00		
	ii) Sharpening one end of $14'-1"$ to $16.0'$ (4.30 to 4.90 m) long Bamboos, $2\frac{1}{2}"$ to $5"$ (63 to 125 mm) dia.	100 Nos	575.50	-	100 Nos	575.50	-		
	 iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average). 	100 Nos	1151.05	-	100 Nos	1151.05	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one Row	178.20	788.90	Per 30 M of one Row	178.20	788.90		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	3298.70	3960.00	ditto	3298.70	3960.00		
	 e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	a contraction of the second se	12600.00	100 Nos	-	12600.00		
	ii) Sharpening one end of 16'-1" to 20' (4.9 to6.10 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia.	100 Nos	690.60	Depar	100 Nos	690.60	-		
	iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1381.25	-	100 Nos	1381.25	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	178.20	788.90	Per 30 M of one row	178.20	788.90		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	4125.00	4966.60	ditto	4125.00	4966.60		
43	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	178.20	238.20	cu.m	62.95	84.15		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	Description Rate (British System) Rate (Metric System)		ystem)	Spec.	Remarks							
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
44	Filling brush wood only, thoroughly packed.	100Cft.	142.55	-	cu.m	50.35	-		Measured in compacted and packed shape before filling.				
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	342.15	-	Per 30 M	342.15	-						
46	a) Gachi pitching 1' (300 mm) thick.b) Gachi pitching done with silt clearance and berm dressing.	100Sft. 100Sft.	1853.30 1568.15	-	Sq.m Sq.m	199.40 168.75							



Finance Department

17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	Y, 2012 TO	31st JUI	LY, 2012)	DISTRICT	LODHRAN	
Sr.	Description	I	Rate (British Sys	tem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.
	a) channels, discharge upto 50 cusecs.	Job	594.00	-	Job	594.00	-	17.5	
	b) channels, discharge from 51 to 100 cusecs.	Job	784.10		Job	784.10	-		
	c) channels, discharge from 101 to 200 cusecs.	Job	1188.00	*) - C	Job	1188.00	-		
	d) channels, discharge from 201 to 350 cusecs.	Job	1603.80	-	Job	1603.80	-		
	e) channels, discharge over 350 cusecs.	Job	2376.00		Job	2376.00	-		
2	Dismantling outlets:-	100		. 6	7 %	100		18.1	These rates are for total dismantlement and removal
	a) old types, such as K.G.O's orifices, etc.	Each	594.00		Each	594.00	-		of material. The rates do not include earth work for which
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	891.00	97 S	ditto	891.00	-		rates are given in item 1, above.
	c) A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm)	ditto 🧃	1188.00	Depa	ditto	1188.00	-		
	 A.P.M. or O.F., "H" above 3.0'. (900 mm) 	ditto	1485.00	-	ditto	1485.00	-		
	e) Tail cluster bifurcation	ditto	891.00	-	ditto	891.00	-		
	f) Tail cluster trifurcation	ditto	1188.00	-	ditto	1188.00	-		
	g) Tail cluster quardification	ditto	1485.00	-	ditto	1485.00	-		
3	Making temporary A.P.M. bricks block and fixing at site.	Each	272.25	544.05	Each	272.25	544.05	21.1 & 21.2	
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	566.30	-	Job	566.30	-	18.1, 21.1 & 21.2	

	MRS, BI-ANNUAL PE	DISTRICT	LODHRAN						
Sr.	Description	1	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	Dismantling walls and fitting iron block of O.F. outlet.	Each	566.30	-	Each	566.30	-	18.1, 21.1 & 21.2	
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to 17.2	
	 a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth 	Each ditto	1425.60 1924.55	-	Each ditto	1425.60 1924.55	-		
7	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	303.15	678.50	Each	303.15	678.50	18.1, 21.1 & 21.2	
8	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	590.70	1200.30	Each	590.70	1200.30	ditto	
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-				JU			21.1 & 21.2	Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no O.F. iron block.
	 a) for channel depth of 5.0'. (1.5 m) b) for channel depth of 4.0'. (1.2 m) c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) e) for channel depth of less than 2.0'. (600 mm) 	Each ditto ditto ditto ditto	660.00 495.00 396.00 330.00 264.00	774.25 609.25 510.25 418.70 327.10	Each ditto ditto ditto ditto	660.00 495.00 396.00 330.00 264.00	774.25 609.25 510.25 418.70 327.10		O.P. HOH BIOCK.
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	272.25	456.45	Each	272.25	456.45		
11	Laying iron pipes for outlets.	Per Lft.	13.20	r sospa	Metre	43.30	-	21.1, 21.2 & 17.1 to 17.5	
12	Water allowance for constructing outlets or culverts, when canal water is not flowing.	Each	289.85 to 594.00		Each	289.85 to 594.00			At the discretion of the Engineer-in-charge depending upon the distance and source of supply.
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	216.90	-	Each	216.90	-		
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	55.35 24.05	62.95 31.70	Metre ditto	181.55 78.95	206.5 103.95		

	MRS, BI-ANNUAL PE	LODHRAN							
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
16	 Removing pipe outlet, refilling earth and puddling. a) portion under bank. b) portion under road, beyond bank. Changing pipe outlets by removing one pipe and replacinş it at the same site with another pipe complete with earth and puddling. 	Rft. ditto	47.50 17.80	-	Metre ditto	155.90 58.45		17.1 to 17.5	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	65.65 32.80	73.25 40.45	Metre ditto	215.40 107.70			



Finance Department

18. ROAD & ROAD STRUCTURE

1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".

- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 3 The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.

	MRS, BI-ANNUAL PERI	DHRAN							
Sr.	Description	R	ate (British Sys	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Sub-base & base construction								
1	Providing and laying sub-base course of brick on edge 4 ¹ / ₂ " (113 mm) thick, including compaction to required camber and grade.	100Cft.	1974.70	11478.70	cu.m	697.45	4054.30	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	1812.00	2868.60	cu.m	640.00	1013.20	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.
3	 a) Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and. aggregate. 	Gin	ance 9	KIS Depart	e noni			ditto	
	i) Pit run or bed run gravel.ii) Crushed stone aggregate.	100Cft. 100Cft.	1812.00 1812.00		cu.m cu.m	640.00 640.00	792.60 907.00		
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
									 It shall be payable from the nearest approved quarry. The quantity of pit run

Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	 a) Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and. aggregate. b) Subsequent carriage of crushed stone aggregate. 	100Cft. 100Cft. of console- dated base	1993.50	3807.90	cu.m	704.10	1344.95	501-1 to 501-6	 or bed run gravel and crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft. 1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
		Gen.		Depart:	nønt				 It shall be payable from the nearest approved quarry. The quantity of crushed stone aggreg for payment of carriage shall be taken as actual loose volume but not more than 1 Cft.
	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	4.15	23.15	Metre	13.65	76.00	552-1 to 552-5	
	Bituminous Work & Resurfacing.								
7	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre. Providing and laying bituminous tack coat, using 10 lbs. of	100Sft. 100Sft.	71.30 71.30	974.20 472.65		7.65 7.65		601-1 to 601-6 611-1 to	
8	 bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.) a) Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate o 							611-5 612-1 to 612-6	

	Description	R	ate (British Sys	tem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.								
	1) 1st coat:-			Contract of the American					
	i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre	100Sft.	75.50	1958.05	Sq.m	8.10	210.70		
	ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size 34" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre.	100Sft.	75.50	1709.25	Sq.m	8.10	183.90		
	2) 2nd coat:-		1.00	-19	499				
	i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size $\frac{1}{2}$ " (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre.	100Sft.	58.05	1223.10	Sq.m	6.25	131.60		
	ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre.	100Sft.	58.05	897.30	Sq.m	6.25	96.55		
	3) 3rd coat:-								
	14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	39.75	691.15	sq.m	4.30	74.35		
b)	Subsequent carriage of crushed stone aggregate/bajri,	100Cft.			cu.m				1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rai as the case may be.

Sr.	Description	Ra	nte (British Syst	tem)	Rat	e (Metric Sy	/stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work.		*					612-1 to 612-6	2) It shal be payable from the nearest approved quarry.
	 i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m. ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre. b) Subsequent carriage of crushed stone aggregate/bajri. 	100Sft. 100Sft. 100Cft.	50.30 50.30	1076.80 977.65	sq.m sq.m cu.m	5.40 5.40	115.85 105.20		Same remarks as against item 8(b) above.
	 Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density. (i) 3% Bitumen (ii) 3.5% Bitumen (iii) 4% Bitumen (iv) 4.5% Bitumen (v) 5% Bitumen (vi) 5.5% Bitumen (vii) 6% Bitumen 	per inch thickness per 100Sft. -do- -do- -do- -do- -do- -do- -do-	1030.30 1030.30 1030.30 1030.30 1030.30 1030.30 1030.30	2953.65 3200.20 3446.75 3693.30 3939.70 4186.45 4433.00	-do- -do- -do-	110.90 110.90 110.90 110.90 110.90 110.90 110.90	317.95 344.45 371.00 397.55 424.05 450.60 477.15	641-1 to 642-6	
	Scarifying old road surface including removal of debris within 1 chain (30 m). Incidental Construction	100Sft.	118.80	-	Sq.m	12.80	-		
	Providing R.C.C. railing on bridges, as per standard drawing.	Per Rft.	60.70	775.70	Metre	199.15	2544.85	901-1 to 901-4	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of binding

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	R	ate (British Syst	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
									wire and removal of rust from the bars, etc.				
13	Providing and fixing G.I. pipe railing, as per standard drawing.	Per Rft. of 3 rows of Pipes	46.15	626.35	Metre	151.45	2055.00	ditto					
14	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end	- *	2184.00	Each set of one end	-	2184.00	911-1 to 911-6					
15	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch		15.60	cu.cm	-	0.95	ditto					
16	Providing and laying expansion joint of neoprine strip 4"x¼" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	36.30	151.80	Metre	119.10	498.05	921-1 to 921-4					
17	Providing and fixing rain water outlet of A.C. pipe.	Each	18.15	194.75	Each	18.15	194.75	931-1 to 933-4					
18	Providing and erection at site of work:-	104	S. P.	E C C C C C C C C C C C C C C C C C C C	and a second			941-1 to 941-5	The rate is for complete item of work according to Standard design				
	i) R.C.C. mile/Km. stone	Each	1170.35	3100.65	Each	1170.35	3100.65		including cement concrete				
	 ii) R.C.C. furlong/½ Km. stone iii) R.C.C. boundary pillar. iv) Sign post of M.S. plate 1/8" thick (3 mm) 	Each Each	58.30 112.20	252.55 434.15	Each Each	58.30 112.20			foundation block and painting letters etc.				
	a) Mandatory.	Each	382.70	3686.70	Each	382.70	3686.70						
	b) Warning/Direction/Informatory.	Each	371.20	3447.70	Each	371.20	3447.70						
	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	1470.15	10974.15	cu.m	519.25	3876.05		The nominal thickness of bricks (2-11/16" shall be taken for the purpose of measurement and payment. (9" x 4-3/8"x 2-11/16")				

19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- 1 Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN													
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-													
	i) white ii) coloured	Each Each	181.50 181.50	1,884.70 2,049.10	Each Each	181.50 181.50	1,884.70 2,049.10							
2	Providing and fixing, double seat and cover only.		WE -			144								
	i) bakelite ii) plastic	Each Each	1.90 1.90	361.90 229.90	Each Each	1.90 1.90	361.90 229.90							
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.					34 34								
	i) white ii) coloured	Each Each	135.30 135.30	1,046.70 1,190.70	Each Each	135.30 135.30	1,046.70 1,190.70							
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	135.30	1,788.90	Each	135.30	1,788.90							
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	135.30	446.70	Each	135.30	446.70							
	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.													
	i) white, with pedestal	Each	179.85	2,158.65	Each	179.85	2,158.65							
	ii) coloured, with pedestaliii) white, without pedestal	Each Each	179.85 157.60	2,305.05 1,452.40	Each Each	179.85 157.60	2,305.05 1,452.40							
	iv) coloured, without pedestal	Each	157.60	1,452.40	Each	157.60	1,452.40							
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	157.60	4,015.80	Each	157.60	4,015.80							
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18")	Each	157.60	970.40	Each	157.60	970.40							

	MRS, BI-ANNUAL	. PERIO	D (1st FEBR	2 TO 31st JULY, 2012) DISTRICT LODHRAN						
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	-	
	with drain board of mosaic, including bracket set, waste pipe and waste coupling.									
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-									
	 i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18") 	Each Each	157.60 157.60	1,441.60 1,261.60	Each Each	157.60 157.60	1,441.60 1,261.60			
10	Providing and fixing glazed earthen ware flat back urinal.	Each	90.75	754.35	Each	90.75	754.35			
11	Providing and fitting glazed earthen ware low down flushing cistern 13,63 litres (3 gallons) capacity, including bracket set, copper connection, etc.		/	*)						
	i) white ii) coloured	Each Each	157.60 157.60	1,116.80 1,227.20	Each Each	157.60 157.60	1,116.80 1,227.20			
12	Providing and fitting plastic made low down flushing cistern 1363 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.		N TH		T					
	i) white ii) coloured	Each Each	157.60 157.60	1,002.80 1,002.80	Each Each	157.60 157.60	1,002.80 1,002.80		If rubber connection is used, the composite rate will be reduced by Rs. 12.50	
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	157.60	1,105.00	Each	157.60	1,105.00			
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.									
	 i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity 	Each Each	166.65 166.65	2,182.05 1,402.05	Each Each	166.65 166.65	2,182.05 1,402.05			
15	Providing and fixing, chromium plated soap dish.	Each	9.10	167.50	Each	9.10	167.50			
16	Providing and fitting, glazed earthen ware soap dish.									
	i) white ii) coloured	Each Each	9.10 9.10	437.50 215.50	Each Each	9.10 9.10	437.50 215.50			
17	Providing and fixing, chromium plated toilet paper holder.	Each	12.10	297.55	Each	12.10	297.55			
18	Providing and fixing, chromium plated towel rail:-									

	MRS, BI-ANNUAL	PERIO	D (1st FEBR	UARY, 2012	TO 31st	t JULY, 2	012) DISTR	CT LODH	RAN
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 60 cm (24") long, and 2 cm (³/₄") dia. ii) 50 cm (20") long, and 1.5 cm (¹/₂") dia. 	Each Each	12.10 12.10	315.70 255.70	Each Each	12.10 12.10	315.70 255.70		
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	22.70	339.50	Each	22.70	339.50		
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-								
	 i) with chromium plated brackets and railing. ii) glass shelf only, without chromium plated brackets and railing. 	Each Each	28.35 18.15	319.80 72.15	Each Each	28.35 18.15	319.80 72.15		
21	Providing and fitting glazed earthen ware shelf 60x13 cm (24"x5"), with chromium plated bracket and railing:-			0					
	i) White ii) Coloured	Each Each	28.35 28.35	637.80 697.80	Each Each	28.35 28.35	637.80 697.80		
22	Providing and fitting:-		7 13	-4-	50	LE -			
	 i) plastic soap dish ii) plastic toilet paper holder iii) plastic towel rail iv) plastic shelf 60x13 cm (24"x5") with bracket and railing. 	Each Each Each Each	9.10 12.10 12.10 12.10	146.40 155.95 215.95 368.40	Each Each Each Each	9.10 12.10 12.10 12.10 12.10	146.40 155.95 215.95 368.40		
23	Providing and fixing chromium plated pillar-cock, heavy:-				ľ				
	i) 2 cm (³ / ₄ ") ii) 1.5 cm (¹ / ₂ ")	Each Each	12.10 12.10	492.10 649.30	Each Each	12.10 12.10	492.10 649.30		
24	Providing and fixing chromium plated stop cock, heavy:-								
	i) 2 cm (3/4") ii) 1.5 cm (1/2")	Each Each	12.10 12.10	276.10 171.70	Each Each	12.10 12.10	276.10 171.70		
25	Providing and fixing underground stop cock 13 mm (1/2"), with chromium plated cover.	Each	18.10	442.15	Each	18.10	442.15		
	Providing and fixing chromium plated bib cock:- i) 2 cm (³ / ₄ ") ii) 1.5 cm (¹ / ₂ ")	Each Each	12.10 12.10	366.10 297.70	Each Each	12.10 12.10	366.10 297.70		
27	Providing and fixing chromium plated tee stop cock 15mm (½").	Each	12.10	424.90	Each	12.10	424.90		

	MRS, BI-ANNUAL	PERIO	D (1st FEBR	UARY, 2012	TO 31st	t JULY, 2	012) DISTR	ICT LODH	RAN
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
28	Providing and fixing chromium plated shower rose:-								
	i) 1.5x10 cm (½"x4") ii) 2x15 cm (¾"x6")	Each Each	12.10 12.10	310.90 372.10	Each Each	12.10 12.10	310.90 372.10		
29	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.	Each	15.15	1,446.75	Each	15.15	1,446.75		
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)
	 i) 30 mm (1¹/₄") dia ii) 40 mm(1¹/₂") dia iii) 50 mm(2") dia iv) 65 mm(2¹/₂") dia v) 80 mm(3") dia 	Each Each Each Each Each	18.15 18.15 18.15 18.15 18.15	402.15 558.15 762.15 1,206.15 1,788.15	Each Each Each Each Each	18.15 18.15 18.15 18.15 18.15 18.15	402.15 558.15 762.15 1,206.15 1,788.15		will be reduced by Rs. 66, 77, 95, 107 and 120 respectively.
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (½") dia.								
	i) single wayii) two wayiii) three way	Each Each Each	12.10 18.15 24.20	348.10 600.15 726.20	Each Each Each	12.10 18.15 24.20	348.10 600.15 726.20		
32	Providing and fixing, union brass cock.		194 <u>8</u>	D P C	Î				
	 i) 13 mm (¹/₂") dia ii) 20 mm (³/₄") dia 	Each Each	12.10 12.10	66.10 204.10	Each Each	12.10 12.10	66.10 204.10		
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-								
	 i) 10x5 cm (4"x2") ii) 10x7.5 cm (4"x3") 	Each Each	36.30 36.30	349.20 337.20	Each Each	36.30 36.30	349.20 337.20		
34	Providing and fitting "P" trap:-								
	 i) 10 cm (4") of cast iron. ii) 10 cm (4") glazed. 	Each Each	30.25 30.25	402.50 102.50	Each Each	30.25 30.25	402.50 102.50		
35	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	45.40	560.85	Each	45.40	560.85		
36	Providing and fitting, cast iron soil pipe with:-								
	i) lead caulked, yarn joint:-								

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN													
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	 a) 10 cm (4") i/d b) 5 cm (2") i/d ii) cement caulked joint:- 	Per foot Per foot	16.40 6.55	185.75 92.90	Metre Metre	53.80 21.50	609.35 304.70						
37	 a) 10 cm (4") i/d b) 5 cm (2") i/d Providing and fitting, A.C. soil pipe with cement caulked 	Per foot Per foot	3.45 1.40	121.15 82.70	Metre Metre	11.30 4.50	397.35 271.35						
	joint, including all specials:- i) 60 (2¼)" mm i/d ii) 80 (3") mm i/d iii) 100 (4") mm i/d iv) 150 (6") mm i/d	Per foot Per foot Per foot Per foot	2.75 3.05 3.45 4.60	25.00 61.50 96.00 120.45	Metre Metre Metre Metre	9.05 10.05 11.30 15.05	82.00 201.80 314.85 395.10						
38	Providing and fitting cast iron specials, such as tee bend, collar, cross, etc. plain type:- i) lead caulked joint	Kg	13.20	131.40 100.50	Kg	13.20	131.40		In case of plug type, the composite rate shall be increased by Rs.2 per kg.				
39	ii) cement caulked jointSupply and fitting of cast iron manhole cover with frame, etc. complete.	Kg	8.00	100.50	Kg	8.00	100.50						
	 i) 30 cm (12") dia ii) 45 cm (18") dia iii) 60 cm (24") dia 	Each Each Each	18.15 18.15 30.15	162.15 768.15 1,242.15	Each Each Each	18.15 18.15 30.15	162.15 768.15 1,242.15						
40	Providing and fitting R.C.C. pipe 10 cm (4") dia, including laying and jointing in trenches.	Per foot	8.20	32.20	Metre	26.90	105.60						
41	Providing and fitting chromium plated or oxidised, gas cock 6'mm (1/4"):-												
	i) single wayii) two wayiii) three way	Each Each Each	12.10 18.15 24.20	177.70 270.15 462.20	Each Each Each	12.10 18.15 24.20	177.70 270.15 462.20						
42	Providing and fitting nipple or bush, 6 mm to 10 mm (¼" to 3/8") i/d.	Each	9.10	21.10	Each	9.10	21.10						
43	Providing and fixing, brass gas cock:-												
	a) 15 mm (¹ / ₂ ") dia b) 20 mm (³ / ₄ ") dia	Each Each	1.90 68.75	73.90 91.90	Each Each	1.90 68.75	73.90 91.90						

	MRS, BI-ANNUA	L PERIO	D (1st FEBR	UARY, 2012	TO 31st	t JULY, 2	012) DISTRI	CT LODH	RAN
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
44	Providing and fixing brass stop cock/bib cock:-								
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	3.05 3.05	78.65 111.05	Each Each	3.05 3.05	78.65 111.05		
45	Hoisting and placing in position, precast R.C. latrine seats.	Each	181.50	-	Each	181.50	-		
	Replacement								
1	Providing and fixing, chromium plated waste coupling:-								
	i) 3 cm (1 ¹ / ₄ ") ii) 4 cm (1 ¹ / ₂ ")	Each Each	18.15 18.15	114.15 120.15	Each Each	18.15 18.15	114.15 120.15		
2	Providing and fixing rubber plug with chain:-								
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	0.75 0.75	45.15 48.75	Each Each	0.75 0.75	45.15 48.75		
3	Providing and fixing, waste pipe of PVC:-		7 189	-15-	50 J	L.S.			
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	9.10 9.10	41.50 51.10	Each Each	9.10 9.10	41.50 51.10		
4	Providing and fixing, flushing bend of PVC.		Fina	ice De	parti	nent			
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	8.05 8.05	38.05 50.05	Each Each	8.05 8.05	38.05 50.05		
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-								
	i) 3 cm (1¼") i/d ii) 4 cm (1½")	Each Each	18.15 18.15	528.15 618.15	Each Each	18.15 18.15	528.15 618.15		
6	Providing and fixing, angle iron brackets for:-								
	i) wash hand basin and cisternii) sinks	Each Each	18.15 18.15	135.75 142.95	Each Each	18.15 18.15	135.75 142.95		
7	Providing and fixing 1.5 cm (1/2") dia connection, including check nuts, etc.:-								
	i) plastic rubber connectionii) copper connection	Each Each	7.25 7.25	49.25 79.25	Each Each	7.25 7.25	49.25 79.25		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN													
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
8	Providing and fixing brass ball float valve:-													
	i) 1.5 cm (¹ / ₂ ") dia	Each	15.15	195.15	Each	15.15	195.15							
	ii) 2.0 cm (¾") dia	Each	15.15	255.15	Each	15.15	255.15							
	iii) 2.5 cm (1") dia	Each	15.15	315.15	Each	15.15	315.15							
	iv) 3 cm (1¼") dia	Each	15.15	339.15	Each	15.15	339.15							
	v) $4.0 \text{ cm} (1\frac{1}{2}") \text{ dia}$	Each	15.15	483.15	Each	15.15	483.15							
	vi) 5 cm (2") dia	Each	15.15	555.15	Each	15.15	555.15							



Finance Department

20. SURFACE DRAINAGE

1. Specification No. correspond to Book of Specification (B & R Department) Vol. 11, 1966 (public Health Works).

2. Rates for all finished works include the removal of surplus debris, unused material and by products

2. 10	Rates for all finished works include the removal of surplus debris, unused material and by products MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description]	Rate (British Sy	stem	Rat	te (Metric S	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-		~	5				17.1				
	 a) 3" thick (75 mm) i) ratio 1:3 ii) ratio 1:5 B) 4¹/₂" thick (113 mm) 	100Rft ditto	607.55 607.55	2,852.70 2,698.75	Metre ditto	19.95 19.95	93.55 88.50					
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	910.90 910.90	4,139.85 3,905.60	ditto ditto	29.90 29.90	135.80 128.10					
	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled and struck flush:-	T	nance	Depar				17.1				
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	896.65 896.65 896.65	4,040.65 3,792.85 3,723.10	Sqm. ditto ditto	96.50 96.50 96.50	434.75 408.10 400.60					
	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1				
	 a) ratio 1:3 b) ratio 1:5 c) ratio 1:6 	100Sft. ditto ditto	1,275.10 1,275.10 1,275.10	6,018.50 5,620.90 5,522.05	Sqm. ditto ditto	137.20 137.20 137.20	647.60 604.80 594.15					
	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2				

	MRS, BI-ANNUAL PERI	OD (1st F	EBRUARY	, 2012 TO 3 ⁴	Ist JULY	, 2012) D I	STRICT LC	DHRAN	
Sr.	Description]	Rate (British Sy	stem	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 a) ratio 1:3 b) ratio 1:5 c) ratio 1:6 	100Sft. ditto ditto	851.40 851.40 851.40	3,995.40 3,747.60 3,677.85	Sqm. ditto ditto	91.60 91.60 91.60	429.90 403.25 395.75		
5	Pacca brick on edge, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,315.80 1,315.80 1,315.80	6,059.15 5,661.60 5,562.70	Sqm. ditto ditto	141.60 141.60 141.60	651.95 609.20 598.55		
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ¹ / ₂ :5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ¹ / ₄ " (6 mm) thick, as per Engineer's drawing (excluding excavation):-	State-						17.1	
	a) Type I b) Type II c) Type II d) Type IV e) Type V f) Type VI g) Type VII h) Type VIII i) Type IX j) Type X k) Type XI l) Type XII	Per Rft ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto	20.40 40.80 53.15 63.35 83.60 96.15 106.60 119.05 159.30 174.95 195.55 208.45	72.10 128.50 166.30 197.95 270.75 309.75 340.30 381.55 547.55 599.80 666.75 706.25	Metre ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto	66.90 133.80 174.35 207.75 274.25 315.40 349.60 390.45 522.50 573.90 641.35 683.75	$\begin{array}{c} 236.55\\ 421.40\\ 545.40\\ 649.20\\ 888.10\\ 1,015.90\\ 1,116.25\\ 1,251.45\\ 1,796.05\\ 1,967.35\\ 2,186.95\\ 2,316.45\end{array}$		
7	Laying R.C.C hume pipes in position, including jointing:- a) 6" to 12" (150 mm to 300 mm) dia b) 12" to 24" (300 mm to 600 mm) dia c) 24" to 36" (600 mm to 900 mm) dia	Per Lft. ditto ditto	37.90 59.25 75.75	40.75 64.95 84.35	Metre ditto ditto	124.25 194.40 248.50	133.60 213.05 276.60		

21. SEWERAGE

Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works). Rate for all finished works include the removal of surplus debris, unused material and byproducts. 1

2

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
	Unit	Labour	Composite	Unit	Labour	Composite	No.			
Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1 ¹ / ₂ :3, with spigot socket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L" including carriage of pipe fron factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., completo			5				Chapter - 8			
i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 225 mm (9:) i/d	Rft. Rft. Rft.	9.55 11.60 22.55	62.00 99.45 258.35	Metre Metre Metre	31.30 38.05 73.95					
Providing and laying non-reinforced concrete pipe moulded with cement concrete 1:11/2:3, conforming t ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complete	The state of the s						ditto			
i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 200 mm (8") i/d iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm) v) 250 mm (10") i/d	Rft. Rft. Rft. Rft. Rft.	7.15 8.70 14.00 15.25 15.60	30.35 44.10 60.40 77.65 86.55	Metre Metre Metre Metre Metre	23.45 28.55 45.90 50.00 51.15	144.65 198.10 254.70				
Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:11/2:3 conforming to ASTN Specification C-76-79, Class II. Wall B, including carriag- of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc., complet							ditto			
 i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d 	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	23.65 29.75 36.00 45.15 52.20 76.45 91.65 113.90 140.20	331.00 405.40 437.40 563.95 677.25 945.05 1005.55 1173.95 1595.50	Metre Metre Metre Metre Metre Metre Metre Metre Metre	77.55 97.60 118.10 148.10 171.20 250.75 300.60 373.60 459.85	1329.70 1434.65 1849.75 2221.40 3099.75 3298.20				
	Description Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, ett including cost of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L." including carriage of pipe fron factory to site of work, lowering in trenches to correal alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 225 mm (9:) i/d Providing and laying non-reinforced concrete pip moulded with cement concrete 1:1½:3, conforming t ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complet i) 100 mm (4") i/d ii) 100 mm (4") i/d iii) 100 mm (4") i/d iii) 100 mm (4") i/d iii) 200 mm (8") i/d iii) 200 mm (8") i/d iii) 200 mm (8") i/d iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm v) v) 250 mm (10") i/d iv) 250 mm (10") i/d iv)<	Description I Unit Unit Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L." including carriage of pipe fron factory to site of work, lowering in trenches to correc alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet Rft. i) 100 mm (4") i/d Rft. iii) 225 mm (9:) i/d Rft. Providing and laying non-reinforced concrete pip: moulded with cement concrete 1:1½:3, conforming t Rft. ASTM Specification C-14-73, Class 2, including carriago of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complet Rft. i) 100 mm (4") i/d Rft. Rft. ii) 250 mm (0") i/d Rft. Rft. iii) 200 mm (8") i/d Rft. Rft. v) 250 mm (10") i/d Rft. Rft. ii) 310 mm (12") i/d Rft. Rft. ii) 300 mm (15") i/d Rft. Rft. ii) 300 mm (12") i/d Rft. Rft. iii)	Description Rate (British Sy Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L" including carriage of pipe fron factory to site of work, lowering in trenches to corree alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet i) 100 mm (4") i/d ii) 225 mm (9:) i/d Rft. 9.55 Providing and laying non-reinforced concrete pip moulded with cement concrete 1:1½:3, conforming t ASTM Specification C-14-73, Class 2, including carriag of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complet i) 100 mm (4") i/d ii) 200 mm (6") i/d iii) 200 mm (6") i/d iii) 200 mm (6") i/d iii) 200 mm (7") i/d Rft. 7.15 Rft. 8.70 Rft. 14.00 Rft. 8.70 Rft. 15.00 Rft. 15.20 Rft. 15.00 Rft. 15.20 Rft. 8.70 Rft. 15.20 Rft. 15.20 Rft. 15.20 Rft. 15.20 Rft. 15.60 Rft. 15.60 Rft. 15.60 Rft. 15.60 Rft. 15.60 Rft. 15.60 Rft. 15.60 Rft. 15.20 Rft. 15.60 Rft. 15.20 Rft. 15.60 Rft. 15.20 Rft. 15.60 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft. 16.70 Rft.<	Description Rate (British System) Unit Labour Composite Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part 1: 1981. Class 'L' including carriage of pipe fron factory to site of work, lowering in trenches to corree alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet Rft. 9.55 62.00 ii) 100 mm (4") i/d Rft. 2.55 62.00 iii) 120 mm (6") i/d Rft. 9.55 62.00 ii) 100 mm (4") i/d Rft. 2.55 62.00 ii) 100 mm (4") i/d Rft. 7.15 30.35 ii) 100 mm (6") i/d Rft. 7.15 30.35 ii) 100 mm (6") i/d Rft. 15.60 86.55 Providing and laying R.C.C. pipe sewers, moulded wit Rft. 15.60	Description Rate (British System) Ra Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½.3, with spigot socket or collar joint, etc including cort of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., completi Rft. 9.55 62.00 Metre 10 0 mm (4") i/d Rft. 9.55 62.00 Metre ii) 100 mm (4") i/d Rft. 9.55 62.00 Metre iii) 100 mm (4") i/d Rft. 9.55 62.00 Metre Rft. 9.55 62.00 Metre Metre Providing and laying non-reinforced concrete pip Rft. 22.55 258.35 Metre NSTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches i correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. completi Rft. 7.15 30.35 Metre ii) 100 mm (4") i/d 11 form m6" i/d Rft. 7.15 30.35 Metre ii) 100 mm (4") i/d 12.50 mm Rft. 15.00 86.55 Metre <td>Description Rate (British System) Rate (Metric S Unit Labour Composite Unit Labour Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost or reinforcement, conforming to B.S. 591: Part 1:1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complete ii) 100 mm (4°) i/d Rft. 9.55 62.00 Metre 31.30 Providing and laying non-reinforced concrete pip moulded with cement concrete 1:1½:3, conforming t ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complete ii) 200 mm (10°) i/d Rft, 7.15 30.35 Metre 23.45 ii) 10 00 mf (6°) i/d Rft, 7.15 30.35 Metre 23.45 ii) 10 00 mf (6°) i/d Rft, 7.15 30.35 Metre 23.45 iii) 2020 mm (10°) i/d Rft, 15.60 86.55 Metre 51.15 Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:1½:3: conforming to ASTN Specification C-76-79. Class IL Wall B, including carriage of pipe from factory to site of work, lowering in trenche</td> <td>Description Rate (British System) Rate (Metric System) Unit Labour Composite Unit Labour Composite Providing and laying R.C.C. pipe, moulded with cemer concrete 11/23, with spigo socket or collar joint, ett including cost of reinforcement, conforming to B.S. 591; Part 1: 1981. Chosering in trenches to corres alignment and grade, jointing, cutting pipes wher mecessary, finishing and testing, etc, complete Rft, 10 00 mm (4") i/d 9.55 62.00 Metre 31.30 203.35 iii) 1200 mm (6") i/d Rft, 10 00 mm (4") i/d Rft, 10 00 mm (4") i/d 8.65 Metre 31.30 203.35 iii) 1200 mm (6") i/d Rft, 10 00 mm (4") i/d Rft, 10 00 mm (4") i/d 73.95 847.40 Providing and laying non-reinforced concrete pip moulded with cement concrete 11/9:3, conforming 1 Rft, 12.55 73.55 02.00 Metre 23.45 99.55 ii) 150 mm (6") i/d Bip device Rft, 10 100 mm (4") i/d Rft, 15.60 77.65 Metre 23.45 99.55 iii) 120 mm (6") i/d Rft, 11 300 mm (12") i/d Rft, 15.60 86.55 Metre 50.00 254.70 Rft, 10 310 mm (12") i/d Rft, 12.20,77,54 <td< td=""><td>Description Rate (British System) Rate (Metric System) Spec. No. Providing and laying R.C.C. pipe, moulded with cemer concrete 11:9.3, with spigo tocket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part 1: 1981, Class U': including carriage of pipe from factory to site of work, lowering in trenches to correc alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet Rft. 9.55 62.00 Metre 31.30 203.35 i) 100 mm (4") idd Rft. 9.55 62.00 Metre 31.30 203.35 ii) 150 mm (6") id Rft. 9.55 62.00 Metre 31.30 203.35 iii) 150 mm (6") id Rft. 7.15 30.35 Metre 33.05 23.53 iii) 100 mm (6") id Rft. 7.15 30.35 Metre 23.45 99.55 ii) 100 mm (6") id Rft. 7.15 30.35 Metre 50.45 44.10 Metre 23.45 99.55 ii) 200 mm (6") id Rft. 7.15 30.31 Metre 50.91 44.10 Metre 50.91 99.55 ii) 20 mm (10") id <t< td=""></t<></td></td<></td>	Description Rate (British System) Rate (Metric S Unit Labour Composite Unit Labour Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost or reinforcement, conforming to B.S. 591: Part 1:1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complete ii) 100 mm (4°) i/d Rft. 9.55 62.00 Metre 31.30 Providing and laying non-reinforced concrete pip moulded with cement concrete 1:1½:3, conforming t ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complete ii) 200 mm (10°) i/d Rft, 7.15 30.35 Metre 23.45 ii) 10 00 mf (6°) i/d Rft, 7.15 30.35 Metre 23.45 ii) 10 00 mf (6°) i/d Rft, 7.15 30.35 Metre 23.45 iii) 2020 mm (10°) i/d Rft, 15.60 86.55 Metre 51.15 Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:1½:3: conforming to ASTN Specification C-76-79. Class IL Wall B, including carriage of pipe from factory to site of work, lowering in trenche	Description Rate (British System) Rate (Metric System) Unit Labour Composite Unit Labour Composite Providing and laying R.C.C. pipe, moulded with cemer concrete 11/23, with spigo socket or collar joint, ett including cost of reinforcement, conforming to B.S. 591; Part 1: 1981. Chosering in trenches to corres alignment and grade, jointing, cutting pipes wher mecessary, finishing and testing, etc, complete Rft, 10 00 mm (4") i/d 9.55 62.00 Metre 31.30 203.35 iii) 1200 mm (6") i/d Rft, 10 00 mm (4") i/d Rft, 10 00 mm (4") i/d 8.65 Metre 31.30 203.35 iii) 1200 mm (6") i/d Rft, 10 00 mm (4") i/d Rft, 10 00 mm (4") i/d 73.95 847.40 Providing and laying non-reinforced concrete pip moulded with cement concrete 11/9:3, conforming 1 Rft, 12.55 73.55 02.00 Metre 23.45 99.55 ii) 150 mm (6") i/d Bip device Rft, 10 100 mm (4") i/d Rft, 15.60 77.65 Metre 23.45 99.55 iii) 120 mm (6") i/d Rft, 11 300 mm (12") i/d Rft, 15.60 86.55 Metre 50.00 254.70 Rft, 10 310 mm (12") i/d Rft, 12.20,77,54 <td< td=""><td>Description Rate (British System) Rate (Metric System) Spec. No. Providing and laying R.C.C. pipe, moulded with cemer concrete 11:9.3, with spigo tocket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part 1: 1981, Class U': including carriage of pipe from factory to site of work, lowering in trenches to correc alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet Rft. 9.55 62.00 Metre 31.30 203.35 i) 100 mm (4") idd Rft. 9.55 62.00 Metre 31.30 203.35 ii) 150 mm (6") id Rft. 9.55 62.00 Metre 31.30 203.35 iii) 150 mm (6") id Rft. 7.15 30.35 Metre 33.05 23.53 iii) 100 mm (6") id Rft. 7.15 30.35 Metre 23.45 99.55 ii) 100 mm (6") id Rft. 7.15 30.35 Metre 50.45 44.10 Metre 23.45 99.55 ii) 200 mm (6") id Rft. 7.15 30.31 Metre 50.91 44.10 Metre 50.91 99.55 ii) 20 mm (10") id <t< td=""></t<></td></td<>	Description Rate (British System) Rate (Metric System) Spec. No. Providing and laying R.C.C. pipe, moulded with cemer concrete 11:9.3, with spigo tocket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part 1: 1981, Class U': including carriage of pipe from factory to site of work, lowering in trenches to correc alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet Rft. 9.55 62.00 Metre 31.30 203.35 i) 100 mm (4") idd Rft. 9.55 62.00 Metre 31.30 203.35 ii) 150 mm (6") id Rft. 9.55 62.00 Metre 31.30 203.35 iii) 150 mm (6") id Rft. 7.15 30.35 Metre 33.05 23.53 iii) 100 mm (6") id Rft. 7.15 30.35 Metre 23.45 99.55 ii) 100 mm (6") id Rft. 7.15 30.35 Metre 50.45 44.10 Metre 23.45 99.55 ii) 200 mm (6") id Rft. 7.15 30.31 Metre 50.91 44.10 Metre 50.91 99.55 ii) 20 mm (10") id <t< td=""></t<>		

	MRS, BI-ANNUAL PE	RIOD (1st I	EBRUARY	, 2012 TO 3 1	lst JUL`	Y, 2012) [DISTRICT L	ODHRAN	
br.	Description		Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	xi) 1220 mm (48") i/d	Rft.	340.05	2720.3	Metre	1115.35	8922.6		
	xii 1370 mm (54") i/d	Rft.	465.15	3388.45	Metre	1525.7	11114.1		
	xiii) 1520 mm (60") i/d	Rft.	599.25	3847.35	Metre	1965.55	12619.3		
	xiv) 1680 mm (66") i/d	Rft.	925.75	4498.65	Metre	3036.45	14755.55		
	xv) 1830 mm (72") i/d	Rft.	1143.10	5040.80	Metre	3749.35	16533.80		
4	Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:11/2:3 conforming to ASTM Specificatio C-76-79, Class III, Wall B, including carriage of pipes fror factory to site of work, lowering in trenches to corre- alignment and grade, jointing with rubber ring, cutting pipe where necessary, testing, etc. complete		-					Chapter-8	
	i) 310 mm (12") i/d	Rft.	23.65	401.30	Metre	77.55	1316.25		
	ii) 380 mm (15") i/d	Rft.	29.75	494.15	Metre	97.60	1620.80		
	iii) 460 mm (18") i/d	Rft.	36.00	623.85	Metre	118.00	2046.25		
	iv) 530 mm (21":) i/d	Rft.	45.15	762.60	Metre	148.00	2501.35		
	v) 610 mm (24") i/d	Rft.	52.20	887.05	Metre	171.25	2909.50		
	vi) 690 mm (27") i/d	Rft.	76.45	1053.15	Metre	250.80	3454.35		
	vii) 760 mm (30") i/d	Rft.	91.65	1271.40	Metre	300.65	4170.20		
	viii) 840 mm (33") i/d	Rft.	113.90	1411.55	Metre	373.55	4629.90		
	ix) 910 mm (36") i/d	Rft.	140.20	1903.45	Metre	459.80	6243.30		
	x) $1070 \text{ mm} (42") i/d$	Rft.	182.45	2474.20	Metre	598.40	8115.40		
	xi) 1220 mm (48") i/d	Rft.	345.25	2964.40	Metre	1132.40	9723.25		
	xii 1370 mm (54") i/d	Rft.	472.40	3723.20	Metre	1549.55	12212.10		
	xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d	Rft. Rft.	608.35 940.35	4601.80 5915.20	Metre Metre	1995.35 3084.30	15093.90 19401.85		
	xv) 1830 mm (72") i/d	Rft.	1161.30	7295.00	Metre	3084.30	23927.60		
								Chantan 9	
5	Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:11/2:3 conforming to ASTN							Chapter - 8	
	Specification C-76-79, Class IV, Wall B, including carriag								
	of pipes from factory to site of work, lowering in trench								
	to correct alignment and grade, jointing with rubber ring								
	cutting pipes where necessary, testing, etc. complete								
	i) 310 mm (12") i/d	Rft.	23.65	502.25	Metre	77.55	1647.45		
	ii) 380 mm (15") i/d	Rft.	23.03	628.05	Metre	97.60	2059.90		
	iii) 460 mm (18") i/d	Rft.	36.00	753.90	Metre	118.00	2472.80		
	iv) 530 mm (21":) i/d	Rft.	45.15	882.70	Metre	148.00	2895.30		
	v) $610 \text{ mm} (24") \text{ i/d}$	Rft.	52.20	1009.45	Metre	171.25	3311.00		
	vi) 690 mm (27") i/d	Rft.	76.45	1328.55	Metre	250.80	4357.60		
	vii) 760 mm (30") i/d	Rft.	91.65	1528.35	Metre	300.65	5013.20		
	viii) 840 mm (33") i/d	Rft.	113.90	1694.30	Metre	373.55	5557.35		
	ix) 910 mm (36") i/d	Rft.	140.20	2411.40	Metre	459.80	7909.45		
	x) 1070 mm (42") i/d	Rft.	182.45	2951.55	Metre	598.40	9681.10		
	xi) 1220 mm (48") i/d	Rft.	345.25	3509.85	Metre	1132.15	11512.40		

Sr.	Description	F	Rate (British Sys	stem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	xii) 1370 mm (54") i/d	Rft.	472.40	4739.20	Metre	1549.75	15544.45		
	xiii) 1520 mm (60") i/d	Rft.	608.35	5978.80	Metre	1995.35	19610.50		
	xiv) 1680 mm (66") i/d	Rft.	940.35	7702.20	Metre	3084.30	25263.25		
	xv) 1830 mm (72") i/d	Rft.	1161.30	9063.65	Metre	3809.05	29728.80		
5	Lowering of sub-soil water table, by installation of tubewel								1) This rate shall be payable, ir
0	along sewer line and pumping out water, for excavation i								addition to the item of excavation
	open cutting below sub-soil water level, concreting, curing								below SSWL for sewers and
	laying and jointing pipes, filling haunches, etc. till th								manholes under Chapter
	completion of sewer line, including disposal of pumped of								EARTHWORK
	water:-								2) The grant of these rates shall be
		Rft of	1 14	1	Metre of				subject to Superintending Engineer
	1) 0-1 ft. (0 to 310 mm) below SSWI	laid sewer	/	156.80		_	514.35		approval.
	$\begin{array}{c} 1 \\ 2 \\ 0 \\ -2 \\ \text{ft.} \\ (0 \\ \text{to} \\ 610 \\ \text{mm}) \\ \text{below SSWI} \end{array}$	ditto	· . ·	304.30	ditto	_	998.20		-FF-0.
	3) 0-3 ft. (0 to 910 mm) below SSWL	ditto	100 March 100 Ma	513.10	ditto	_	1682.90		3) The rate includes cost of
	4) 0-4 ft. (0 to 1220 mm) below SSWL	ditto	and the second se	737.40	ditto	-	2418.65		providing pumps, POL and al
	5) 0-5 ft. (0 to 1520 mm) below SSWL	ditto	Manager and Street and Stree	1019.75	ditto	_	3344.85		operation charges at the site
	6) 0-6 ft. (0 to 1830 mm) below SSWL	ditto		1262.30	ditto	_	4140.30		of work, etc.
	7) 0-7 ft. (0 to 2170 mm) below SSWL	ditto		1506.80	ditto	_	4942.35		of work, etc.
	8) 0-8 ft. (0 to 2480 mm) below SSWL	ditto	No.	1730.50	ditto	_	5675.95		
	9) 0-9 ft. (0 to 2790 mm) below SSWL	ditto	100	1880.55	ditto	_	6168.30		
	10) 0-10 ft. (0 to 3100 mm) below SSWL	ditto		2163.70	ditto	_	7097.00		
	11) 0-11 ft. (0 to 3410 mm) below SSWL	ditto		2403.05	ditto	-	7882.00		
	12) 0-12 ft. (0 to 3720 mm) below SSWL	ditto		2403.05		-	8729.15		
	12) 0-12 II. (0 to 5720 IIIII) 000 55 WL		-			6	6729.13		
7	Constructing gully grating chamber, 12"x12", (300x300 mm) complete in all respects	Et:	nance	Depart	3M. 872.	5		16.2	Pipe connection to be paid separately.
	a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) fram hinged safety type	Each	423.70	2043.90	Each	423.70	2043.90		
	b) concrete Gully trap.	ditto	423.70	2083.90	ditto	423.70	2083.90		
8	Constructing standard gully grating chamber, 3'x2½ (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects	Each	1268.75	6560.55	Each	1268.75	6560.55	ditto	Pipe connection to be paid separately.
9	Extra for making and finishing benching floor work i manhole chamber, with 1/8" (3 mm) thick cement finish	100Sft.	541.35	965.65	Sq.m	58.25	103.90	14.4	
0	Restoration of brick pavement on edge, over laid servic line, with 2" (50 mm) sand cushion under soling	100Sft.	778.60	2134.00	Sq.m	83.80	229.60	13.1	
1	Restoration of flat brick pavement sand grouted, over 2 (50 mm) thick dry sand cushion, under soling on laisservice line.	100Sft.	472.55	1445.15	Sq.m	50.85	155.50	13.1	

Sr.	Description	ŀ	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
12	Restoration of metalled road, on laid service line, includin compaction:-							13.1	
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base	100Sft.	2558.85	8003.75	Sq.m	275.35	861.20		
	 b) Carpeted road, with 1¹/₂" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base 	100Sft.	1848.00	5914.70	Sq.m	198.85	636.40		
	 c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base. 	100Sft.	636.90	3725.95	Sq.m	68.55	400.90		
13	Providing and fixing 1 ¹ /4"x1 ¹ /4"x3/16" (31x31x5 mm) angle iron step, in manhole chambers, including carriage an setting the same in work to correct lines and level:	Each	57.00	209.95	Each	57.00	209.95	14.7	
4	Fixing manhole frame and cover in R.C.C. slab includin carriage to site.	Per set	139.00		Per set	139.00	-	ditto	
15	Providing and fixing 3" (75 mm) thick R.C.C. manhol cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20 (500 mm) clear i/d (frame weighing 37.324 Kg. or on maund) as per Standard Drawing STD/PD No. 5, of 1977 complete in all respects	Per set	89.45	2656.50	Per set	89.45	2656.50	ditto	
5-A	Providing and fixing 6" thick R.C.C. manhol cover with tee shaped C.I. frame of 22" I/d (fram weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect	Perset	172.35	3815.05	Per set	172.35	3815.05		
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects	Per set	156.45	2333.35	Per set	156.45	2333.35	ditto	
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhol cover with 3"x3"x¼" (75x75x6mm) angle iron frame, 22 (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects	Per set	133.35	3784.30	Per set	133.35	3784.30	ditto	
18	Desilting of disposal work collecting tank, includin removal of sludge within 3 chains (90 metre)	100Cft.	407.30	461.60	cum	143.85	163.05	16.2	
19	Providing and installing, C.I. ventilating shaft painted wit bituminous paint with foundation bolts, as per PHEI Standard Drawing STD/PD No. 4 of 1977, complete in al							14.6	

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	F	ate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	respects (except concrete foundation block)											
	a) 6" (150 mm) i/d shaft											
	 i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long 	Per Cwt ditto ditto ditto	111.55 123.95 133.85 140.05	2143.10 2161.10 2169.70 2176.20	U	219.55 243.95 263.50 275.70	4218.70 4254.15 4271.00 4283.85					
	 b) 9" (225 mm) i/d shaft i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long 	Per Cwt ditto ditto ditto	99.90 107.65 115.25 138.75	2127.70 2135.00 2143.05 2166.35	%kg ditto ditto ditto	196.65 211.90 226.90 273.10	4188.45 4202.70 4218.60 4264.50					
20	 c) 12" (300 mm) i/d shaft i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long Silt clearing 10' (3.00 m) dia wells, and 	Per Cwt ditto ditto	89.15 114.65 133.75	2118.15 2140.95 2159.40	%kg ditto ditto	175.55 225.70 263.30	4169.55 4214.45 4250.80					
	removal of slush outside the compound: a) upto 10' (3.00 m) depth of slusł b) beyond 10' (3.00 m) depth of slusł	Per well Per well	3049.20 6091.80	Depart	Per well Per well	3049.20 6091.80	-					

22. SINKING OF WELLS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

2 Well curbs to be laid at spring level or as deep as possible.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN Sr. Description Rate (British System) Rate (Metric System) Spec. Remarks No. No. Unit Labour Composite Unit Labour Composite Excavation of well in dry upto 20'(6 metre) below ground 1 level, and disposal of soil within one chain (30 metre) a) in ordinary soil or sand :-1000 Cft. cu.m 74.80 i) from 0' to 5' (o to 1.5 m) depth ditto 2118.45 ditto ii) from 5.1' to 10' (1.5 to 3.0 metre) depth ditto 2212.55 26ditto 78.15 iii) from 10.1' to 15' (3.0 to 4.5 metre) depth 2489.10 ditto 87.90 ditto iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth ditto 2856.90 ditto 100.90 b) in hard soil i) from 0' to 5'(0 to 1.5 metre) depth 1000 Cft. 2580.35 91.15 cu.m 2697.25 ii) from 5.1' to 10'(1.5 to 3.0 metre) depth ditto ditto 95.25 iii) from 10.1' to 15'(3.0 to 4.5 metre) depth 2948.15 ditto 104.15 ditto iv) from 15.1' to 20'(4.5 to 6.0 metre) depth 3315.95 117.10 ditto ditto in hard strata, such as shingle, gravel, etc. c) i) from 0' to 5'(0 to 1.5 metre) depth 1000 Cft. 5565.55 cu.m 196.60 ii) from 5.1' to 10'(1.5 to 3.0 metre) depth 203.60 ditto 5765.15 ditto iii) from 10.1' to 15'(3.0 to 4.5 metre) depth ditto 6010.35 ditto 212.30 -iv) from 15.1' to 20'(4.5 to 6.0 metre) depth 6452.25 227.90 ditto ditto 2 Dry sinking of well, including loading, and removing excavated material within one chain (30 m):in ordinary soil :a) i) from 10' to 15'(3.0 to 4.5 m) depth 1000 Cft. 11404.80 402.80 cu.m ii) from 15.1' to 20'(4.5 to 6.0 m) depth 14256.00 503.50 ditto ditto iii) from 20.1' to 25'(6.0 to 7.5 m) depth ditto 17107.20 ditto 604.25 iv) from 25.1' to 30'(7.5 to 9.0 m) depth 19958.40 704.95 ditto ditto 22809.60 805.65 v) from 30.1' to 35'(9.0 to 10.5 m) depth ditto ditto vi) from 35.1' to 40'(10.5 to 12.0 m) depth 25660.80 ditto 906.35 ditto vii) from 40.1'to 45'(12.0 to 13.5 m) depth ditto 28512.00 ditto 1007.05 viii) from 45'(13.5 Sm) to any depth ditto 31363.20 ditto 1107.75 in hard soil :b) i) from 10' to 15'(3.0 to 4.5 m) depth 1000 Cft. 15681.60 cu.m 553.85

	MRS, BI-ANNUAL PI	LODHRA	N						
Sr.	Description]	Rate (British Sys	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	18532.80	-	ditto	654.60	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	21384.00	-	ditto	755.30	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	24235.20	-	ditto	856.00	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	27086.40	-	ditto	956.70	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	29937.60	-	ditto	1057.40	-		
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	32788.80	-	ditto	1158.10	-		
	viii) from 45'(13.5 m) to any depth	ditto	35640.00	-	ditto	1258.80	-		
	c) in hard strata, such as shingle, gravel, etc.								
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	21384.00	× -	cu.m	755.30	-		
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	24235.20	71	ditto	856.00	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	27086.40		ditto	956.70	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	27442.80	-	ditto	969.30	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	32788.80		ditto	1158.10	-		
	vi) from $35.1'$ to $40'(10.5 \text{ to } 12.0 \text{ m})$ depth	ditto	35640.00		ditto	1258.80	-		
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	38491.20	and a second sec	ditto	1359.50	-		
	viii) from 45'-1" (13.5 m) to any depth	ditto	41342.40	1 6	ditto	1460.20	-		
3	Wet sinking of well in ordinary soil (value of C upto 5), for depths below spring level, including charges of machinery, shoring, kentledge and removal of excavated spoil within							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.
	one chain (30 m):-	1	trnanc	e Depu	art mi	882.2			
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	16849.40	-	cu.m	595.10	-		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	35805.00	-	ditto	1264.65	-		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	44067.70	-	ditto	1556.45	-		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	57288.00	-	ditto	2023.40	-		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	63653.35	-	ditto	2248.25	-		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	71610.00	-	ditto	2529.25	-		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	73446.15	-	ditto	2594.10	-		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	75378.95	-	ditto	2662.40	-		
	ix) above 80'(24.0 m) to any depth	ditto	81840.00	-	ditto	2890.60	-		
4	Wet sinking of well in cohesive soil (value of Cmore than 5), for depths below spring level, including charges of machinery shoring, kentledge and removal of excavated							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.
	spoil within one chain (30 m):-								
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	-	28085.70	cu.m	-	992.00		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	-	35107.15	ditto	-	1240.00		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	42128.55	ditto	-	1488.00		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	56171.40	ditto	-	1983.95		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	1	Rate (British Sys	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	-	64813.15	ditto	-	2289.20				
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	-	70214.25	ditto	-	2479.95				
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	-	76597.35	ditto	-	2705.40				
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	-	79487.85	ditto	-	2807.50				
	ix) above 80'(24.0 m) to any depth	ditto	-	84257.10	ditto	-	2975.95				
5	Wet sinking of well in shingle, or gravel, etc, for depths below spring level, including charges of machinery, shoring, kentledge and removal of excavated spoil within one chain (30 m) :-							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.		
	i) from o' to $10'(0$ to 3.0 m) depth	1000 Cft.		38298.70	cu.m	-	1352.70				
	ii) above $10'$ to $20'(3.0 \text{ to } 6.0 \text{ m})$ depth	ditto		46809.50	ditto		1653.30				
	iii) above 10 to $20(5.0 \text{ to } 0.0 \text{ m})$ depth iii) above $20'$ to $30'(6.0 \text{ to } 9.0 \text{ m})$ depth	ditto		56171.40	ditto	_	1983.95				
	iv) above 20 to $30(0.0 \text{ to } 9.0 \text{ m})$ depth iv) above $30'$ to $40'(9.0 \text{ to } 12.0 \text{ m})$ depth	ditto		76597.35	ditto		2705.40				
	v) above $40'$ to $50'(12.0 \text{ to } 15.0 \text{ m})$ depth	ditto	1	84257.10	ditto	13	2975.95				
	vi) above $50'$ to $60'(15.0 \text{ to } 15.0 \text{ m})$ depth	ditto	S.	93619.00	ditto	85 <u>-</u>	3306.60				
	vii) above 50 to 50 (13.0 to 10.0 m) depth	ditto	0	97973.40	ditto	Sec.	3460.40				
	viii) above 00 to 70 (10.0 to 24.0 m) depth	ditto	1 10	100306.10	ditto	25	3542.80				
	ix) above $80'(24.0 \text{ m})$ to any depth	ditto	22	110864.60	ditto	× .	3915.75				
		unto	ALC: NO	110001.00	ante		5715.75				
6	Making and fixing in position, kiker wood well curb.	Per Cft.	457.80	1779.30	cu.m	16169.70	62844.40				
7	Laying well curb in position only.	Each	145.20	e Depa	Each	145.20	-				
8	Providing, making and laying R.C.C. well curb in position,							*841-1	1) If concrete mixer is supplied by		
	using coarse sand, including all kinds of form, moulds,							to	Government, all charges including		
	curing, shuttering, rendering and finishing the exposed surface, (including screening and washing of aggregate :-							841-9	depreciation will be recovered from the contractor.		
									2) The rate does not include cost of		
	a) Ratio 1:11/2:3	Per Cft.	106.90	298.90	cu.m	3776.40	10558.00		steel reinforcement and its labour for		
	b) ratio 1:2:4	ditto	106.90	276.35	ditto	3776.40	9761.45		bending, which is payable, separately.		
		unito									
9	Providing and fixing structural steel for cutting edge.	100Kg	357.70	10206.60	100Kg	357.70	10206.60	841-1 to 841-9			
	сч <u>с</u> с.							0-1-7			
10	Making and removing false masonry on well.	100Cft.	3549.05	13692.85	cu.m	1253.50	4836.30	21.1 to 21.5 & 18.1	The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.		

* Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

23. TUBEWELL AND WATER SUPPLY

Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)". Rates for all finished works include the removal of surplus debris, unused material and byproducts. 1 2

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Boring for tubewell in all types of soil except shingle and rock, from ground level to 100 ft. (30 m) depth, including sinking and withdrawing of casing pipe, complete:-							Chap. 2			
2	 a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle, 	Per Rft. of bore ditto ditto ditto ditto ditto ditto	É	30.80 43.00 77.55 118.10 153.40 194.20 212.05 313.60 334.05	Per Metre of bore ditto ditto ditto ditto ditto ditto ditto		101.00 141.00 254.30 387.35 503.15 636.90 695.60 1028.60 1095.70	ditto			
-	 a) a solution of the second matrix provide the solution of the second matrix provided the solution of the solution of	Per Rft. of bore ditto ditto ditto ditto ditto	inanci	131.60 184.50 207.00 237.65 263.35 367.75 388.25	Per Metre of bore ditto ditto ditto ditto ditto ditto		431.70 605.15 678.95 779.50 863.75 1206.30 1273.40	uno			
3	Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 200.1 ft. to 300 ft. (60 to 90 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle,	Per Rft. of bore ditto ditto ditto ditto ditto		183.30 236.20 260.60 294.80 313.30 403.90 425.55	Per Metre of bore ditto ditto ditto ditto ditto		601.20 774.65 854.75 967.00 1027.65 1324.75 1395.80	ditto Chap. 2			
	gravel & rock, from a depth of 300.1 ft. to 400 ft. (90 to 120 m) below ground level, including sinking and withdrawing of casing pipe, complete:-										

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	RY, 2012 TO 3 [.]	lst JULY,	2012) DIS	TRICT LODHI	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	ite (Metric S	bystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	Rft of bore ditto ditto ditto ditto		314.20 351.95 372.85 493.00 497.20	Per Metre of bore ditto ditto ditto		1030.55 1154.45 1223.00 1616.95 1630.75		
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells, in all types of soil except shingle, gravel and rock:-							ditto	
	 a) from ground level to 250 ft. (75 m) below ground level:- i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d b) exceeding 250 ft. (75 m) depth below ground level:- 	Per Rft. of bore ditto		362.60 521.45	Per Metre of bore ditto		1189.30 1710.45		Upto 2 cusec discharge Above 2 cusec discharge
6	 i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d Boring for tubewell in shingle, gravel and rock, including sinking and withdrawing of casing pipe:- 	Rft of bore ditto		362.60 521.45	Per Metre of bore ditto		1189.30 1710.45	ditto	Upto 2 cusec discharge Above 2 cusec discharge Location and depth of shingle, gravel or rock is to be determined from the bore log.
	 a) from ground level to 200 ft. (60 m) below ground level:- i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d b) exceeding 200 ft. (60 m) depth below 	Per Rft. of bore ditto	inanci	1106.00	Per Metre of bore ditto		2682.25 3627.65		Upto 2 cusec discharge Above 2 cusec discharge
	ground level:- i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	ditto ditto		817.75 1106.00	ditto ditto		2682.25 3627.65		Upto 2 cusec discharge Above 2 cusec discharge
7	Providing strong substantially built box of deodar wood 4'x2½'x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	378.90	9664.50	Job for compl- ete bore	378.90	9664.50	ditto	
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	108.00	156.00	Per Set of 2 bottles	108.00	156.00	Chap. 2	
9	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc. complete:-							ditto	Cost/labour of jointing both ends is included in the rate.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	 a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick j) 10" i/d, 1/4" (250 mm i/d 6 mm) thick k) 12" i/d, 1/4" (300 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	$15.25 \\ 15.25 \\ 20.10 \\ 22.75 \\ 25.60 \\ 29.85 \\ 36.90 \\ 36.90 \\ 41.50 \\ 41.50 \\ 42.70 \\ $	636.85 960.25 1175.10 1387.75 1495.60 1762.35 2241.90 2294.40 2351.50 2981.50 3402.70	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	50.00 50.00 66.00 74.60 83.95 98.00 121.00 121.00 136.05 136.05 140.00	2088.85 3149.60 3854.40 4551.80 4905.55 5780.60 7353.40 7525.60 7712.85 9779.25 11160.80					
10	 15" i/d, ¹/4" (375 mm i/d 6 mm) thick m) 18" i/d, ¹/4" (450 mm i/d 6 mm) thick n) 20" i/d, ¹/4" (500 mm i/d 6 mm) thick o) 22" i/d, ¹/4" (550 mm i/d 6 mm) thick Providing and installing M.S. Bail plug in tubewell bore 	Per Rft. Per Rft. Per Rft. Per Rft.	48.80 48.80 57.35 58.55	4248.80 4758.05 5244.35 6064.55	Per Metre Per Metre	160.05 160.05 188.10 192.05	13936.05 15606.35 17201.45 19891.70		In the case of increase or decrease			
	hole: a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long. b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long. c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long. d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long. e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long. f) 7" i/d, 2 ft. (175 mm i/d 600 mm) long. g) 8" i/d, 2 ft. (200 mm i/d 600 mm) long h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long i) 10" i/d, 2 ft. (250 mm i/d 600 mm) long j) 12" i/d, 2 ft. (300 mm i/d 600 mm) long k) 15" i/d, 2 ft. (450 mm i/d 600 mm) long l) 18" i/d, 2 ft. (450 mm i/d 600 mm) long m) 20" i/d, 2 ft. (500 mm i/d 600 mm) long m) 20" i/d, 2 ft. (550 mm i/d 600 mm) long	Each Each Each Each Each Each Each Each	67.60 67.60 112.85 112.85 152.25 152.25 187.75 187.75 187.75 225.35 225.35 270.90 294.70	411.80 559.90 1145.90 1462.90 1851.55 2144.80 2377.80 2649.00 3451.05 4152.80 5131.40 5829.05 6498.95 7153.35	Each Each Each Each Each Each Each	67.60 67.60 112.85 152.25 152.25 187.75 187.75 187.75 225.35 225.35 270.90 294.70 294.70	411.80 559.90 1145.90 1462.90 1851.55 2144.80 2377.80 2649.00 3451.05 4152.80 5131.40 5829.05 6498.95 7153.35		in the length of Bail plug, the rates will be increased or decreased as per rates given in serial No. 14 of this chapter for the respective diameter.			
	Providing and installing, P.V.C. strainer B.S.S. Class 'B', in tubewell bore hole, including sockets and solvents, etc. complete:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) Providing and installing P.V.C. strainer B.S.S. Class `D',	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	10.80 12.30 13.00 15.45 21.30 21.80 21.80	144.35 200.70 265.10 643.85 964.25	Per Metre Per Metre Per Metre Per Metre	35.40 40.30 42.70 50.70 69.90 71.50 71.50	658.30 869.55 2111.90 3162.65	Chap. 2				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	complete:-										
	a) 1 ¹ / ₄ " i/d (30 mm) b) 1 ¹ / ₂ " i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	7.25 7.50 7.65 10.80 12.40 13.35 23.55	40.45 47.50 73.05 153.10 244.80 359.15 511.25	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	23.75 24.65 25.00 35.45 40.65 43.80 77.25	132.6 155.85 239.65 502.1 802.95 1178 1676.85				
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:- i) B.S.S. Class `B'										
	 a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) ii) B.S.S. Class `D' 	Each Each Each Each Each Each Each	5.65 6.45 7.20 8.95 11.05 11.60 13.35 13.35	53.65 72.45 110.40 158.95 311.05 438.80 589.35 620.55	Each Each Each Each Each Each Each Each	5.65 6.45 7.20 8.95 11.05 11.60 13.35 13.35	53.65 72.45 110.40 158.95 311.05 438.80 589.35 620.55				
	 a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Each Each Each Each Each Each Each	3.70 4.00 4.20 5.65 6.45 7.20 8.95	27.70 40.00 58.20 77.65 102.45 145.20 188.95	Each Each Each Each Each Each Each Each	3.70 4.00 4.20 5.65 6.45 7.20 8.95	27.70 40.00 58.20 77.65 102.45 145.20 188.95				
14	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:-							Chap. 2			
	 a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 1/4" (250 mm i/d 6 mm) thick j) 12" i/d, 1/4" (300 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	40.55 40.55 50.70 50.70 72.35 72.35 84.40 84.40 84.40 101.30	221.45 300.35 396.05 738.90 885.95 1021.55 1261.80 1435.60 1856.80 2186.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	133.00 133.00 166.30 237.30 237.30 276.85 276.85 276.85 332.25	726.40 985.15 1299.05 2423.65 2905.90 3350.70 4138.75 4708.75 6090.30 7171.05				

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	Y, 2012 TO 3	1st JULY,	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 k) 15" i/d, ¹/₄" (375 mm i/d 6 mm) thick l) 18" i/d, ¹/₄" (450 mm i/d 6 mm) thick m) 20" i/d, ¹/₄" (500 mm i/d 6 mm) thick n) 22" i/d, ¹/₄" (550 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft.	101.30 124.10 133.70 133.70	2707.55 3364.45 3734.10 4094.10	Per Metre Per Metre Per Metre Per Metre	332.25 407.05 438.55 438.55	8880.75 11035.35 12247.80 13428.70		
15	Providing and installing P.V.C. blind pipe, B.S.S. Class `B', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete.							ditto	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	14.00 15.80 16.55 20.30 26.95 28.10 33.40 31.00	108.05 157.90 210.45 294.85 449.35 743.30 1031.80 1231.00	Per Metre Per Metre Per Metre Per Metre	45.85 51.80 54.25 65.05 88.40 92.20 109.50 101.65	354.40 517.85 690.30 965.60 1473.90 2438.05 3384.25 4037.65		
16	 Providing and installing P.V.C. blind pipe, B.S.S. Class `D', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete. a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	8.50 8.75 9.35 12.15 15.95 16.85 20.30	42.10 51.95 76.55 156.15 257.85 376.85 543.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	27.90 28.75 30.70 39.90 52.30 55.35 66.60	138.15 170.45 251.15 512.20 845.80 1236.15 1782.70		
17	Testing and developing of tubewell of size 6" (150 mm) i/d and above continuously.								
	i) upto 1.5 cs. dischargeii) above 1.5 cs. discharge	Per Hour ditto		1038.80 1249.55	Per Hour ditto		1038.80 1249.55		
18	Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3 mm), around tubewell in bore hole.	Per Cft.	15.60	73.55	cu.m	550.95	2597.75		The rate includes wastage, etc.
19	Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc. complete in all respects:-							Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d	Per Rft. Per Rft. Per Rft.		34.05 42.45 52.90	Per Metre Per Metre Per Metre		111.65 139.20 173.50		

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	Y, 2012 TO 31	Ist JULY,	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.		63.05 78.00 115.80 135.65 176.40 234.45	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		206.85 255.90 379.75 444.90 578.55 769.05		
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:-							ditto	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the
	 a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	C	14.45 16.10 25.00 27.40 32.35 45.90 53.45 72.85 89.75	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		47.35 52.80 82.05 89.80 106.05 150.60 175.30 238.75 294.30		rate, which is payable separately.
21	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches with Tyton joints, complete in all respects:- a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	inanci	7.35 8.55 0012.45 16.90 21.50 25.80 39.90 47.90	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		24.20 28.10 36.10 40.90 55.45 70.45 84.65 130.90 157.10	Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
22	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves.							Chap. 2	Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	 i) Light Quality a) ¼" i/d (15 mm) 2mm thick b) ¾" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1¼" i/d (32 mm) 2.65mm thick e) 1½" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"½ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	6.90 7.35 8.20 8.30 9.60 10.20 11.90 12.80	53.25 73.80 103.15 132.95 165.90 207.15 281.55 330.10 462.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	22.60 24.20 26.85 27.20 27.55 31.55 33.45 39.05 41.90	174.70 242.05 338.25 436.00 544.20 679.50 923.40 1082.70 1515.65		

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	Y, 2012 TO 31	Ist JULY, 2	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) Medium Quality a) ¹/₄" i/d (15 mm) 2.65mm thick b) ³/₄" i/d (20 mm) 2.65mm thick c) 1" i/d (25 mm) 3.25mm thick d) 1¹/₄" i/d (32 mm) 3.25mm thick e) 1¹/₄" i/d (32 mm) 3.25mm thick e) 1¹/₄" i/d (40 mm) 3.25mm thick f) 2" i/d (50 mm) 3.65mm thick g) 2"¹/₂ i/d (65 mm) 3.65mm thick h) 3" i/d (75 mm) 4.05mm thick i) 4" i/d (100 mm) 4.5mm thick j) 5" i/d (150 mm) 4.85mm thick k) 6" i/d (200 mm) 4.85mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	6.90 7.35 8.20 8.30 9.60 10.20 11.90 12.80 14.80 15.10	62.80 79.30 119.05 151.95 172.60 237.90 303.25 381.90 544.10 746.40 870.30	Per Metre Per Metre	22.60 24.20 26.85 27.20 28.25 31.55 33.45 39.05 41.90 48.50 49.45	205.90 260.15 390.50 498.40 566.10 780.30 994.60 1252.65 1784.60 2448.15 2854.60		 i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia, 3/4"dia & 1/2"dia) for Bath rooms/ Levorotary. ii. For internal G.I piping (1"dia, 3/4"dia & 1/2"dia) Bath room(s)/ Levorotary of rate (composite) shall be reduced by 8% and specials mentioned above may be paid at the rates placed on Website as per actual quantity used.
	 iii) Heavy Quality a) ¹/₄" i/d (15 mm) 3.25mm thick b) ³/₄" i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick d) 11/₄" i/d (32 mm) 4.05mm thick e) 11/₂" i/d (40 mm) 4.05mm thick f) 2" i/d (50 mm) 4.5mm thick g) 2"/₂ i/d (65 mm) 4.5mm thick h) 3" i/d (75 mm) 4.85mm thick i) 4" i/d (100 mm) 5.4mm thick j) 5" i/d (125 mm) 5.4mm thick Providing, laying, cutting, jointing, testing and disinfecting 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	6.90 7.35 8.20 8.30 9.60 10.20 11.90 12.80 14.80 15.10	88.80 115.30 170.35 219.55 249.45 342.55 429.50 552.35 752.15 930.40 1099.20	Per Metre Per Metre	22.60 24.20 26.85 27.20 28.25 31.55 33.45 39.05 41.90 48.50 49.45	291.25 378.2 558.75 720.15 818.2 1123.5 1408.8 1811.8 2467.1 3051.7 3605.4		
	Asbestos cement/Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:- B Class WOrking Pressure a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	6.75 7.15 9.80 13.50 17.70 22.60 26.35 29.90	139.30 181.70 286.70 482.20 656.60 867.30 1114.55 1415.45	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	22.20 23.50 32.15 44.30 58.05 74.10 86.50 98.05	456.85 596.00 940.35 1581.60 2153.70 2844.75 3655.80 4642.70	PS 428 & ISO 160	Providing and installing specials and valves is not included in the rate, which is payable separately.
	i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)	Per Rft. Per Rft. Per Rft.	35.35 41.55 50.50	2060.35 2170.50 2994.90	Per Metre Per Metre Per Metre	115.90 136.35 165.70	6757.90 7119.25 9823.20		

	MRS, BI-ANNUAL P	ERIOD (1	st FEBRUAR	Y, 2012 TO 3	lst JULY, 2	2012) DIS	TRICT LODH	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
24	C Class Working Pressure							PS 428 &	
	a) 3" i/d (75 mm)	Per Rft.	6.75	139.30	Per Metre	22.20		ISO 160	
	b) 4" i/d (100 mm)	Per Rft.	7.15	200.00	Per Metre	23.50	656.05		
	c) 6" i/d (150 mm) d) 8" i/d (200 mm)	Per Rft.	9.80	343.80	Per Metre	32.15	1127.60		
	d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Per Rft. Per Rft.	13.50 17.70	544.65 760.00	Per Metre Per Metre	44.30 58.05	1786.50 2492.85		
	f) 12" i/d (300 mm)	Per Rft. Per Rft.	22.60	1057.95	Per Metre	74.10	3470.10		
	g) 14" i/d (350 mm)	Per Rft.	26.35	1625.15	Per Metre	86.50	5330.40		
	h) $16'' i/d (400 \text{ mm})$	Per Rft.	29.90	2075.75	Per Metre	98.05	6808.40		
	i) 18" i/d (450 mm)	Per Rft.	35.35	2945.30	Per Metre	115.90	9660.55		
	j) 20" i/d (500 mm)	Per Rft.	41.55	3030.05	Per Metre	136.35	9938.55		
	k) $24'' i/d (600 \text{ mm})$	Per Rft.	51.10	4267.55	Per Metre	167.60	13997.55		
25	D Class Working Pressure			and the second se				PS 428 &	
	a) 3" i/d (75 mm)	Per Rft.	6.75	139.30	Per Metre	22.20	456.85	ISO 160	
	b) 4" i/d (100 mm)	Per Rft.	7.15	226.95	Per Metre	23.50	744.40		
	c) 6" i/d (150 mm)	Per Rft.	9.80	413.80	Per Metre	32.15	1357.25		
	d) 8" i/d (200 mm)	Per Rft.	13.50	729.95	Per Metre	44.30	2394.15		
	e) 10" i/d (250 mm)	Per Rft.	17.70	1077.75	Per Metre	58.05	3535.05		
	f) 12" i/d (300 mm)	Per Rft.	22.60	1572.80	Per Metre	74.10	5158.85		
	g) 14" i/d (350 mm)	Per Rft.	26.35	2342.50	Per Metre	86.50	7683.35		
	h) 16" i/d (400 mm)	Per Rft.	29.90	3025.75	Per Metre	98.05	9924.50		
	i) 18" i/d (450 mm)	Per Rft.	35.35	3634.40	Per Metre	115.90	11920.85		
	j) 20" i/d (500 mm)	Per Rft.	41.55	4445.40	Per Metre	136.35	14580.85		
	k) 24" i/d (600 mm)			26 22	Ser.				
				200				~	
26	Providing, laying, cutting, jointing, testing and disinfecting							Chap	Providing and installing specials
	P.V.C. pipe line of B.S.S. with `B' Class working pressure	0	Finan cz	Depar	tment			2	and valves is not included in the
	pipe, in trenches, complete in all respects:-	.22	. 107-77 E- 0409-97 10- 10,700	20.00 80 80 80 1	P. 9-31 21-324-37 (0-32)				rate, which is payable separately.
	a) 3" i/d (75 mm)	Per Rft.	2.30	98.25	Per Metre	7.55	322.30		
	b) 4" i/d (100 mm)	Per Rft.	2.85	147.80	Per Metre	9.40	484.70		
	c) 5" i/d (125 mm)	Per Rft.	3.55	201.35	Per Metre	11.60	660.35		
	d) 6" i/d (150 mm)	Per Rft.	3.85	283.90	Per Metre	12.55	931.15		
	e) 8" i/d (200 mm)	Per Rft.	5.40	436.25	Per Metre	17.75	1430.90		
	f) 10" i/d (250 mm)	Per Rft.	6.95	736.45	Per Metre	22.75	2415.50		
	h) 12" i/d (300 mm)	Per Rft.	8.55	1026.90	Per Metre	28.00	3368.25		
	g) 14" i/d (350 mm)	Per Rft.	10.80	1234.80	Per Metre	35.40	4050.10		
27	Providing, laying, cutting, jointing, testing and disinfecting							ditto	Providing and installing specials
21								uno	
	Class working pressure complete in all respects:-								rate, which is payable separately.
	a) 2" i/d (50 mm)	Per Rft.	1.90	70.45	Per Metre	6.30	231.10		rate, which is payable separately.
	b) $3'' i/d (75 \text{ mm})$	Per Rft.	2.30	149.20	Per Metre	7.55	489.30		
	c) $4'' i/d (100 \text{ mm})$	Per Rft.	2.85	249.60	Per Metre	9.40	818.75		
	d) 5" i/d (125 mm)	Per Rft.	3.55	370.75	Per Metre	11.60	1216.00		
	e) 6" i/d (150 mm)	Per Rft.	3.85	537.50	Per Metre	12.55	1763.00		
								1	
28	Providing and fixing cast iron special of B.S.S. Class `B'							9.1	i) Labour rates include the cost of
	(such as bend, tee cross collar, reducer, tail piece,	<u> </u>							jointing material & labour.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description		Rate (British Sy	vstem)	Ra	ate (Metric Sy	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	 flanged spigot, cap, flanged socket, taper, angle branch, plug etc.) for cast iron pipe line , complete:- a) C.I.S.S. Specials, with spigot. and socket joint:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d 	Per Kg. Per Kg. Per Kg.	12.90 7.20 4.00	90.85 85.15 81.95	Per Kg Per Kg Per Kg	12.90 7.20 4.00	90.85 85.15 81.95		ii) The internal dia of the pipe, from which the oralich is taken out with be considered the internal dia for the purpose of payments of specials.	
	 b) C.I. flanged specials, with flanged and flanged joints:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d c) C.I. Specials, with tyton joints:- 	Per Kg Per Kg Per Kg	6.15 2.25 2.70	84.10 80.20 80.20	Per Kg Per Kg Per Kg	6.15 2.25 2.70	84.10 80.20 80.20			
•	 i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d 	Per Kg Per Kg Per Kg	5.70 5.70 5.70	83.65 83.65 83.65	Per Kg Per Kg Per Kg	5.70 5.70 5.70	83.65 83.65 83.65			
29	 Providing and fixing cast iron specials of B.S.S. Class 'B' (such as bend, tee, cross collar, reducer, tail piece, flanged socket, flanged spigot, cap, taper, angle branch, plug, etc) for Asbestos cement pipe line, with comet joint and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 18" (200 to 450 mm) i/d iii) 20" to 24" (500 to 600 mm) i/d 	Per Kg Per Kg Per Kg	10.20 5.45 4.35	Der 88.15 83.40 82.30	Per Kg Per Kg Per Kg	10.20 5.45 4.35	88.15 83.40 82.30	9.1	 Labour rates include the cost of jointing material and labour. The internal dia of the pipe, from which the branch is taken out, will be considered the internal dia for the purpose of payment. 	
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class `B', for cast iron pipe line, and Asbestos cement pipe line (including cost of jointing material):- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) Providing and fixing, sluice valve of B.S.S. quality and weight, for Asbestos cement pipe line, with comet joint	Each Each Each Each Each Each Each Each	370.25 402.95 725.25 773.20 902.80 1601.80 1800.00 2387.40 2747.75	5650.25 6642.95 7925.25 10973.20 19502.80 25001.80 32400.00 59987.40 105947.75	Each Each Each Each Each Each Each Each	370.25 402.95 725.25 773.20 902.80 1601.80 1800.00 2387.40 2747.75	5650.25 6642.95 7925.25 10973.20 19502.80 25001.80 32400.00 59987.40 105947.75	9.1	Labour rates include cost of jointing material and labour. Labour rates include cost of jointing material and labour.	
	and rubber ring, complete (including cost of jointing materials):- a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	318.55 395.55	4638.55 5435.55	Each Each	318.55 395.55	4638.55 5435.55			

	MRS, BI-ANNUAL F	ERIOD (1	st FEBRUAR	Y, 2012 TO 3 [°]	lst JULY,	2012) DIS	TRICT LODHI	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) 6" i/d (150 mm)	Each	505.20	9145.20	Each	505.20	9145.20		
	d) 8" i/d (200 mm)	Each	847.15	16687.15	Each	847.15	16687.15		
	e) 10" i/d (250 mm)	Each	1093.75	20773.75	Each	1093.75	20773.75		
	f) $12'' i/d (300 \text{ mm})$	Each	1260.00	25740.00	Each	1260.00	25740.00		
	g) 16" i/d (400 mm) h) 18" i/d (450 mm)	Each Each	1495.40 1811.75	49495.40 88211.75	Each Each	1495.40 1811.75	49495.40 88211.75		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2 ¹ / ₂ " (65 mm) dia (including cost of jointing material).	Each	47.60	4007.60	Each	47.60	4007.60	9.1	1) Labour rates include cost of jointing material and labour.
									2) Connecting pipes and specials, if used, will be paid extra.
33	Providing and fixing, air valve 2½ (65mm) dia of B.S.S. quality and weight (complete with jointing material).			*)				ditto	
	a) single	Each	96.20	2976.20	Each	96.20	2976.20		
	b) double	Each	96.20	6456.20	Each	96.20	6456.20		
34	Providing and fitting C.I. flanges on pipes, including	386			1 Site				
	turning, threading, facing and fitting, etc. complete in all respects:-	1. Contraction of the second s		الطومت بنج	All -			ditto	
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	16.45	85.30	Per Kg	16.45	85.30		
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	10.25	79.15 Dep	Per Kg	10.25	79.15		
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	8.80	77.65	Per Kg	8.80	77.65		
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:								
		Per Inch			Per cm i/d				
	a) $3''$ to $6''$ (75 to 150 mm) i/d b) $8''$ to $12''$ (200 to 200 mm) i/d	i/d of pipe		32.90	of pipe		13.15		
	b) 8" to 12" (200 to 300 mm) i/d c) 15" to 18" (375 to 450 mm) i/d	ditto ditto		39.45 36.85	ditto ditto		15.80 14.75		
	c, 15 to 16 (575 to 450 mm) //d	uno		50.05	unto		14.73		
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I. pipe of B.S.S. 1387-1967 complete in all respects,								Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	including specials and valves:-								
	i) G.I. flanged joints (Heavy Quality)								
	a) 1½" i/d (40 mm)	Per Rft.	11.75	239.55		38.55	785.80		
	b) 2" i/d (50 mm)	Per Rft.	11.75	331.80	Per Metre	38.55	1088.20		
	c) 2 ¹ / ₂ " i/d (65 mm)	Per Rft.	12.90	422.40	Per Metre	42.35	1385.55		
	d) 3" i/d (75 mm) e) 4" i/d (100 mm)	Per Rft. Per Rft.	13.00 14.60	548.60 775.30	Per Metre Per Metre	42.60 47.90	1799.45 2543.05		
	$c_{j} + 1/u (100 \text{ mm})$	ref Kit.	14.00	775.30	rei meue	47.90	2545.05		

	MRS, BI-ANNUAL PE	RIOD (1s	st FEBRUAR	Y, 2012 TO 3	lst JULY, 2	2012) DIS	TRICT LODHI	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft.	16.15 16.20	954.50 1130.85	Per Metre Per Metre	53.00 53.15	3130.80 3709.10		
	ii) C.I. flanged joints (Medium Quality)								
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	12.95 12.30 14.10 14.15 15.90 17.55 17.65	174.20 234.10 292.80 373.25 541.40 733.55 863.70	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	42.50 40.40 46.20 46.45 52.05 57.55 57.80	571.40 767.90 960.30 1224.25 1775.75 2406.05 2832.90		
37	Providing and installing P.V.C. bends, of B.S.S.			*					
	 i) Class `B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- a) 1¼" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Each Each Each Each Each Each Each Each	60.50 72.05 90.05 93.75 36.90 40.80 40.80 45.25 60.50 72.05 90.05 93.75	173.30 313.25 559.25 786.15 66.90 73.20 108.85 228.50 466.85 1002.05 1374.15	Each Each Each Each Each Each Each Each	60.50 72.05 90.05 93.75 36.90 40.80 45.25 60.50 72.05 90.05 93.75	$\begin{array}{c} 173.30\\ 313.25\\ 559.25\\ 786.15\\ \end{array}$		
38	Providing and installing P.V.C. tees, of B.S.S.								
	 i) Class `B' working pressure:- a) 3" i/d (80 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- 	Each Each Each Each	90.80 109.75 132.55 140.60	507.20 953.35 1820.95 1880.60	Each Each Each Each	90.80 109.75 132.55 140.60	507.20 953.35 1820.95 1880.60		
	a) 1 ¹ /4" i/d (30 mm) b) 1 ¹ /2" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each	56.75 61.45 67.45 90.80 109.75 132.55 140.60	171.95 203.05 255.85 507.20 953.35 1820.95 1880.60	Each Each Each Each Each Each Each	56.75 61.45 67.45 90.80 109.75 132.55 140.60	171.95 203.05 255.85 507.20 953.35 1820.95 1880.60		

	MRS, BI-ANNUAL PE	RIOD (1s	t FEBRUAR	RY, 2012 TO 31	st JULY, 2	2012) DIS	TRICT LODHI	RAN	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Providing and installing P.V.C. sockets, B.S.S.								
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	46.70 58.20	121.10 191.40	Each Each	46.70 58.20	121.10 191.40		
	c) 5" i/d (125 mm)	Each	72.75	252.75	Each	72.75	252.75		
	d) 6" i/d (150 mm)	Each	76.45	329.65	Each	76.45	329.65		
	e) 8" i/d (200 mm)	Each	111.85	697.45	Each	111.85	697.45		
	f) 10" i/d (250 mm)	Each	134.05	1718.05	Each	134.05	1718.05		
	g) 12" i/d (300 mm)	Each	154.50	3828.90	Each	154.50	3828.90		
	h) 14" i/d (350 mm)	Each	175.65	3055.65	Each	175.65	3055.65		
	ii) Class `D' working pressure:-	_		45.90	_				
	a) 1¼" i/d (30 mm)	Each	25.40	45.80	Each	25.40	45.80		
	b) 1½" i/d (40 mm)	Each	29.30	56.90	Each	29.30	56.90 78.10		
	c) 2" i/d (50 mm) d) 3" i/d (75 mm)	Each Each	33.70 46.70	78.10 189.50	Each Each	33.70 46.70	78.10 189.50		
	e) 4" i/d (100 mm)	Each	58.20	322.20	Each	58.20	322.20		
	f) 5" i/d (125 mm)	Each	72.75	552.75	Each	72.75	552.75		
	g) 6" i/d (150 mm)	Each	76.45	916.45	Each	76.45	916.45		
		100	110	E 101	1.3				
40	Providing and installing P.V.C. Tapered core, B.S.S.		1000	1000					
	D Class D section and a sector		The second second	200	See.				
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm)	Each	60.50	96.50	Each	60.50	96.50		
	b) 4" i/d (100 mm)	Each	72.05	120.05	Each	72.05	120.05		
	c) 5" i/d (125 mm)	Each	90.05	150.05	Each	90.05	150.05		
	d) 6" i/d (150 mm)	Each	93.75	165.75	Each	93.75	165.75		
	e) 8" i/d (200 mm) f) 10" i/d (250 mm)	Each	134.85	254.85	Each	134.85	254.85		
	f) 10" i/d (250 mm) g) 12" i/d (300 mm)	Each Each	157.05 182.15	313.05 374.15	Each Each	157.05 182.15	313.05 374.15		
	h) 14" i/d (350 mm)	Each	203.25	443.25	Each	203.25	443.25		
	ii) Class `D' working pressure:-								
	a) 1¼" i/d (30 mm)	Each	36.90	54.90	Each	36.90	54.90		
	b) 1½" i/d (40 mm)	Each	40.80	64.80	Each	40.80	64.80		
	c) 2" i/d (50 mm)	Each	45.25	75.25	Each	45.25	75.25		
41	Making connection for new watersupply lines with the								The rate includes the component of
	running main, including excavation of trench and refilling,								bailing out water from the trench
	complete, but excluding cost of pipe and specials, etc.								and cutting of existing pipe line.
	Diameter of running main:								
	(1) = 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1	Per	002.55		Per	902.55			
	i) upto 6" i/d (150 mm) ii) upto 8" i/d (200 mm)	Connection ditto	803.55 1017.40		Connection ditto	803.55 1017.40			
	ii) upto 8" i/d (200 mm) iii) upto 10" i/d (250 mm)	ction	1017.40		ction	1017.40			
	iv) upto 12" i/d (300 mm)	ditto	1963.50		ditto	1963.50			
	v) upto 16" i/d (400 mm)	ditto	2401.75		ditto	2401.75			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	vi) upto 20" i/d (500 mm) vii) upto 24" i/d (600 mm)	ditto ditto	3123.45 3748.80		ditto ditto	3123.45 3748.80							



Finance Department

24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PER	IOD (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) D	ISTRICT LC	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Supply and erection of G.I. pipes for wiring purposes, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.								
	a) on surface, including clamps, etc.							38.4	
	 i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d vii) 80 mm i/d b) recessed in walls, including hooks, cutting jharries and repairing surface: i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d vi) 50 mm i/d vii) 80 mm i/d 	Per Rft. Per Rft.	8.85 8.85 8.85 11.05 11.05 13.20 16.75 13.30 13.30 13.30 13.30 13.85 13.85 15.10 20.75 33.20	52.15 66.70 89.30 114.40 142.00 177.60 280.70 55.60 71.10 94.80 118.00 146.65 185.85 298.65	Per Metre Per Metre	29.05 29.05 29.05 36.30 43.20 55.00 43.55 43.55 43.55 45.40 45.40 49.50 68.05 108.90	171.10 218.75 292.85 375.15 465.70 582.50 920.65 182.35 233.30 310.90 386.95 481.10 609.65 979.60	38.3	
2	Supply and erection of M.S. conduit pipes for wiring, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.	T CI KII.	55.20	270.03	i ci Mede	100.90	777.00	38.4 & 38.6	
	a) on surface, including clamps, etc.								
	 i) 16 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	6.15 6.15 6.15 6.90 8.50	23.40 28.40 34.75 38.15 49.20 60.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	20.15 20.15 20.15 20.15 22.70 27.90	76.75 93.15 114.00 125.15 161.40 197.85		
	 b) recessed in walls, including cutting jharries, cost of hooks and repairing surface etc. 							38.3 & 38.7	
	i) 16 mm i/d	Per Rft.	11.85	30.75	Per Metre	38.90	100.90		

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUAR	Y, 2012 TO 🤅	31st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 20 mm i/d	Per Rft.	11.85	35.50	Per Metre	38.90	116.40		
	iii) 25 mm i/d	Per Rft.	13.30	42.75	Per Metre	43.55	140.25		
	iv) 32 mm i/d	Per Rft.	13.85	47.20	Per Metre	45.40	154.85		
	v) 40 mm i/d	Per Rft.	14.45	57.30	Per Metre	47.35	188.00		
	vi) 50 mm i/d	Per Rft.	15.10	69.30	Per Metre	49.50	227.30		
3	Supply and erection of PVC pipe for wiring recessed in walls,							38.3 &	
	including inspection boxes, pull boxes, hooks, cutting jharries,							38.5	
	and repairing surface, etc., complete with all specials.								
	i) 12 mm i/d	Per Rft.	10.70	20.20	Per Metre	35.15	66.20		
	ii) 20 mm i/d	Per Rft.	11.05	23.95	Per Metre	36.30	78.65		
	iii) 25 mm i/d	Per Rft.	12.30	29.05	Per Metre	40.35	95.30		
	iv) 32 mm i/d	Per Rft.	13.30	36.90	Per Metre	43.55	121.05		
	v) 40 mm i/d	Per Rft.	13.85	45.95	Per Metre	45.40	150.80		
	vi) 50 mm i/d	Per Rft.	14.45	57.70	Per Metre	47.35	189.30		
4	Supply and erection of PVC pipe for wiring on surface	3.57 N			- Civil				
-	including clamps inspection boxes, pull boxes, bends, tees,	1430	5	. 6	7 (22)				
	repairing surface, etc., complete with all specials:-	- Carl		1	and a second				
		105			153				
	i) 12 mm i/d	Per Rft.	2.75	11.80	Per Metre	9.10	38.65		
	ii) 20 mm i/d	Per Rft.	2.75	15.05	Per Metre	9.10	49.30		
	iii) 25 mm i/d	Per Rft.	2.75	19.55	Per Metre	9.10	64.15		
	iv) 32 mm i/d	Per Rft.	3.15	27.10	Per Metre	10.35	88.85		
	v) 40 mm i/d	Per Rft.	3.15	36.60	Per Metre	10.35	120.10		
	vi) 50 mm i/d	Per Rft.	3.80	51.50	Per Metre	12.50	168.95		
5	Supply and erection of G.I. flexible pipe for wiring, including							38.4	
	welding of sockets, nipples and check nuts, etc. complete:-								
	i) 12 mm i/d	Per Rft.	7.25	33.60	Per Metre	23.80	110.20		
	i) 20 mm i/d	Per Rft.	7.75	42.10	Per Metre	25.35	138.15		
	iii) 25 mm i/d	Per Rft.	8.00	56.30	Per Metre	26.25	184.65		
	iv) 32 mm i/d	Per Rft.	9.65	74.80	Per Metre	31.70	245.30		
	v) 40 mm i/d	Per Rft.	10.55	92.50	Per Metre	34.60	303.40		
	vi) 50 mm i/d	Per Rft.	11.60	127.55		38.05	418.45		
	vii) 80 mm i/d	Per Rft.	15.45	283.25	Per Metre	50.70	929.10		
6	Supply and erection PVC pipe for recessed wiring (main and							38.2 &	
	sub-main) purpose, including bends, specials, etc. in floor,							38.3	
	wall or trenches:-								
	i) 50 mm i/d	Per Rft.	14.45	59.15	Per Metre	47.35	194.05		
	i) 80 mm i/d	Per Rft.	16.60	78.75	Per Metre	54.45	258.25		
	iii) 100 mm i/d	Per Rft.	16.60	103.55		54.45	339.70		
	,		10.00	100.00		55	2022.00		

	MRS, BI-ANNUAL PERIO	OD (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
7	Supply and erection of PVC pipe for surface wiring (main and sub-main) including clamps, inspection boxes, pull boxes bends etc., complete with all specials:-								
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	3.80 5.55 6.30	47.85 79.60 100.25	Per Metre Per Metre Per Metre	12.50 18.15 20.75	157.00 261.10 328.85		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	1.10	2.80	Per Metre	3.65	9.10	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	1.10	10.40	Per Metre	3.65	34.10	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):- a) 250/440 volts, PVC insulated:				P			38.1	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052") viii) 19/1.63 mm (19/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.20 2.20 2.20 2.45 2.75 3.40 7.90 9.20	8.15 8.55 12.10 18.30 26.50 65.90 105.45 145.20	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	7.25 7.25 7.25 8.05 9.10 11.15 25.95 30.25	26.75 28.05 39.70 60.00 86.95 216.20 345.95 476.20		
	b) 250/440 volts, PVC insulated cotton braided and compounded cables:-								
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.45 2.45 2.45 2.60 2.90 3.35	8.40 8.80 12.35 18.45 26.65 65.85	Per Metre	8.05 8.05 8.05 8.55 9.55 11.00	27.55 28.85 40.50 60.45 87.40 216.05		
11	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):-								

	MRS, BI-ANNUAL PERIO	DD (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.20 2.20 2.45 2.75 3.40	7.75 10.50 14.50 21.05 30.05 60.00	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	7.25 7.25 7.25 8.05 9.10 11.15	25.45 34.50 47.50 69.05 98.60 196.75		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-		/	*)				38.1 to 38.7	
	 i) 7/1.63 mm (7/0.064") ii) 19/1.32 mm (19/0.052") iii) 19/1.63 mm (19/0.064") iv) 19/2.11 mm (19/0.083") v) 37//1.83 mm (37/0.072") vi) 37/2.11 mm (37/0.083") vii) 37/2.62 mm (37/0.103") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.35 3.70 4.00 4.45 7.65 9.20 13.00	68.00 115.35 156.45 300.25 416.30 522,50 802.15	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	11.00 12.10 13.20 14.50 25.05 30.25 42.70	223.05 378.40 513.15 984.85 1,365.50 1,713.85 2,631.10		
13	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- a) PVC insulated, PVC sheathed twin core, 250/440 volts.	Ti	ian ce	Sepa Depa	s» tmen	No. 1		ditto	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.45 2.45 2.45 2.60 2.90 3.35	14.75 21.05 28.95 42.55 60.70 121.70	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	8.05 8.05 8.05 8.55 9.55 11.00	48.30 69.05 95.00 139.60 199.05 399.15		
	 b) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:- 								
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.60 2.60 2.60 2.90 3.05 3.50	22.40 32.30 44.15 64.80 92.80 188.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	8.55 8.55 8.55 9.55 10.10 11.50	73.45 105.90 144.80 212.60 304.40 619.40		
	 c) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:- 								
	i) 3/0.74 mm (3/0.029")	Per Rft.	2.75	28.90	Per Metre	9.10	94.75		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	ii) 3/0.91 mm (3/0.036")	Per Rft.	2.75	40.75	Per Metre	9.10	133.65				
	iii) 7/0.74 mm (7/0.029")	Per Rft.	2.90	56.20	Per Metre	9.55	184.35				
	iv) 7/0.91 mm (7/0.036")	Per Rft.	2.90	83.65	Per Metre	9.55	274.30				
	v) $7/1.12 \text{ mm} (7/0.044'')$	Per Rft.	3.05	120.60	Per Metre	10.10	395.65				
	vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052")	Per Rft. Per Rft.	3.50 4.90	246.45 460.60	Per Metre Per Metre	11.50 16.15	808.35 1,510.80				
	 d) PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG. 								Cost of trenches where necessary is included in the rates.		
	i) 19/1.32 mm (19/0.052")	Per Rft.	4.90	513.90	Per Metre	16.15	1,685.60				
	ii) 19/1.63 mm (19/0.064")	Per Rft.	5.25	687.45	Per Metre	17.30	2,254.80				
	iii) 19/1.83 mm (19/0.072")	Per Rft.	5.55	931.80	Per Metre	18.15	3,056.35				
	iv) 19/2.11 mm (19/0.083")	Per Rft.	6.00	1,304.90	Per Metre	19.60	4,280.05				
	v) 37//1.83 mm (37/0.072")	Per Rft.	6.15	1,778.40	Per Metre	20.15	5,833.15				
	vi) 37/2.11 mm (37/0.083")	Per Rft.	7.40	2,248.25	Per Metre	24.20	7,374.25				
	vii) 37/2.36 mm (37/0.093")	Per Rft.	8.85	2,740.30	Per Metre	29.05	8,988.15				
	viii) 37/2.62 mm (37/0.103")	Per Rft.	11.05	3,410.60	Per Metre	36.30	11,186.70				
14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")	1.63	1	in a star	1.3			38.1			
	deep, with 4.75 mm thick (3/16") bakelite sheet top, for	Y. She		10000	Carrie .			to			
	recessed wiring, including making holes for regulators,	140		100	18000			38.7			
	switches, plugs, etc.			200-2							
	i) 10 x 10 cm (4"x4")	Each	36.30	90.00	Each	36.30	90.00				
	ii) 17.5 x 10 cm (7"x4")	Each	45.40	125.75	Each	45.40	125.75				
	iii) 22.5 x 10 cm (9"x4")	Each	60.50	155.80	Each	60.50	155.80				
	iv) 20 x 25 cm (8"x10")	Each	72.60	236.80	Each	72.60	236.80				
	v) 25 x 30 cm (10"x12")	Each	90.75	320.65	Each	90.75	320.65				
	vi) 30 x 35 cm (12"x14")	Each	121.00	419.75	Each	121.00	419.75				
15	Supply and erection of round block of Sahl wood, 10x4 cm (4"x1½") thick.	Each	10.35	20.00	Each	10.35	20.00	38.1			
16	Supply and erection of teak wood board, 4.5 cm (1¾") thick.							38.1			
1	i) 17.5 x 10 cm (7"x4")	Each	14.50	66.10	Each	14.50	66.10				
	i) $22.5 \times 10 \text{ cm}(7 \text{ x}^4)$	Each	14.50	78.10	Each	14.50	78.10				
	iii) $20 \times 25 \text{ cm} (8"x10")$	Each	16.15	91.75		16.15	91.75				
	iv) 25 x 30 cm (10"x12")	Each	18.15	123.75	Each	18.15	123.75				
	v) 30 x 35 cm (12"x14")	Each	20.75	174.35	Each	20.75	174.35				
17	Supply and erection of Sahl wood board, 4.5 cm (1 ³ / ₄ ") thick.										
	i) 17.5 x 10 cm (7"x4")	Each	14.50	45.70	Each	14.50	45.70				
	ii) 22.5 x 10 cm (9"x4")	Each	14.50	62.50	Each	14.50	62.50				
	iii) $20 \times 25 \text{ cm} (8"x10")$	Each	16.15	77.35	Each	16.15	77.35				
	iv) 25 x 30 cm (10"x12")	Each	18.15	93.75	Each	18.15	93.75				

	MRS, BI-ANNUAL PERIO	D (1st F	EBRUAR	Y, 2012 TO 3	B1st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) 30 x 35 cm (12"x14")	Each	20.75	109.55	Each	20.75	109.55		
18	Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc. a) double pole:							38.1	When the base frame is already installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.
	 i) 15/20 Amp. ii) 30/35 Amp. iii) 60/65 Amp. iv) 100 Amp. 	Each Each Each Each	242.00 242.00 363.00 363.00	1,045.30 1,309.30 1,748.30 2,259.50	Each Each Each Each	242.00 242.00 363.00 363.00	1,045.30 1,309.30 1,748.30 2,259.50		by KS. 38.60 and KS. 350.60.
	 b) triple pole: i) 15/20 Amp. ii) 30/35 Amp. 	Each Each	363.00 242.00	1,467.50 1,723.30	Each Each	363.00 242.00	1,467.50 1,723.30		
	 c) triple pole with neutral link: i) 30/35 Amp. ii) 60/65 Amp. iii) 100 Amp. 	Each Each Each	242.00 363.00 475.55	1,843.30 2,344.15 2,960.70	Each Each Each	242.00 363.00 475.55	1,843.30 2,344.15 2,960.70		
19	Supply and erection of iron/aluminum clad, 500 volts main switches with triple pole and neutral link and HRC fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and	Fi	iance	Depa				38.1	When the base frame is already installed, the labour & composite rates will be reduced as follows:-
	thimbles. 60/65 Amp 100 Amp 150 Amp 200 Amp 300 Amp 400 Amp 500 Amp	Each Each Each Each Each Each Each	363.00 475.55 475.55 1,089.00 1,089.00 1,542.75 1,633.50	2,407.80 3,469.55 4,909.55 7,733.40 8,986.20 12,048.15 15,417.15	Each Each Each Each Each Each Each	363.00 475.55 475.55 1,089.00 1,089.00 1,542.75 1,633.50	2,407.80 3,469.55 4,909.55 7,733.40 8,986.20 12,048.15 15,417.15		 i) For 60/65 Amp. by Rs. 21.20 and Rs. 145.50. ii) For 100 to 300 Amp. by Rs. 21.20 and Rs. 350.80 iii) For 400 to 500 Amp. by Rs. 42.20 and Rs. 526.20
20	Supply and erection of iron/aluminum clad, branch distribution board, 250 volt, on angle iron frame of suitable size with 3 mm (1/8") M.S. sheet covering:							ditto	When the base frame is already installed the labour and composite rates will be reduced by Rs. 19.50 & Rs. 152.20 respectively.
	 i) 2 way, 15 Amp per way ii) 3 way, 15 Amp per way iii) 4 way, 15 Amp per way iv) 5 way, 15 Amp per way v) 6 way, 15 Amp per way 	Each Each Each Each Each	121.00 121.00 121.00 121.00 121.00	441.40 441.40 507.40 561.40 603.40	Each Each Each Each Each	121.00 121.00 121.00 121.00 121.00	441.40 441.40 507.40 561.40 603.40		

	MRS, BI-ANNUAL PERIC	DD (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 vi) 7 way, 15 Amp per way vii) 8 way, 15 Amp per way viii) 9 way, 15 Amp per way ix) 10 way, 15 Amp per way ix) 10 way, 15 Amp per way xi) 12 way, 15 Amp per way xii) 12 way, 15 Amp per way xiii) 2 way, 30 Amp per way xiii) 3 way, 30 Amp per way xiv) 4 way, 30 Amp per way xiv) 4 way, 30 Amp per way xiv) 6 way, 30 Amp per way xvii) 7 way, 30 Amp per way xviii 8 way, 30 Amp per way xviii 8 way, 30 Amp per way xviii 9 way, 30 Amp per way xx) 10 way, 30 Amp per way 	Each Each Each Each Each Each Each Each	121.00 121.00 121.00 121.00 121.00 121.00 181.50 181.50 181.50 181.50 181.50 181.50 181.50	651.40 699.40 747.40 819.40 867.40 921.40 501.90 507.90 561.90 621.90 663.90 723.90 771.90 819.90 891.90	Each Each Each Each Each Each Each Each	121.00 121.00 121.00 121.00 121.00 181.50 181.50 181.50 181.50 181.50 181.50 181.50	651.40 699.40 747.40 819.40 867.40 921.40 501.90 507.90 561.90 621.90 663.90 723.90 771.90 819.90 891.90		
21	 Supply and erection of bus bars, for 500 volts 3 phase A.C. supply with four copper bars, including glazed porcelain bridges, on angle iron board, fixed with rag bolts and M.S. sheet box 1.5 mm thick, etc. complete:- i) 60 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm) ii) 100 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm) iii) 200 Amp with 4 copper bars size 2"x1/8" (50x 3 mm) iv) 300 Amp with 4 copper bars size 2"x3/16" (50x 5 mm) v) 500 Amp with 4 copper size 2"x1/4" (50x 6 mm) 	Each Each Each Each Each	450.45 450.45 719.40 816.75 541.20	2,272.80 2,272.80 2,661.75 2,759.10 2,999.00	Each Each Each Each Each Each	450.45 450.45 719.40 816.75 541.20	2,272.80 2,272.80 2,661.75 2,759.10 2,999.00	38.1	When the base frame is already installed the labour and composite rates will be reduced by Rs. 21.20 and Rs. 145.50 respectively.
22	 Supply and erection of plain pendent lamp holder, complete with bakelite lamp holder and flexible twin wire 23/0.0076" upto 2 metre length (without bulb and shade). 	Each	7.55	85.20	Each	7.55	85.20	38.1	
	ii) Extra for additional length of flexible wire, beyond2 metres.	Per Rft.		1.65	Per Metre		5.45		
23	Supply and erection of counter weight pedent with porcelain counter weight, and fitting on bakelite lamp holder, with flexible twin wire 23/0.0076" complete (without bulb and shade).	Each	15.15	198.80	Each	15.15	198.80	38.1	
24	Supply and erection of stiff pedent with brass/metal pipe 6.3 cm (2.5") long, and 15 mm (½") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm	Each	24.00	352.60	Each	24.00	352.60	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(3/0.029").												
25	Supply and erection of 22.5 cm (9") long swan neck plain brass/steel brass oxidised bracket lamp holder, complete.	Each	24.80	66.45	Each	24.80	66.45	ditto					
26	Supply and erection of wall type/pole type bracket, with double cover water tight reflector, flexible wire and brass bolder.	Each	34.25	369.40	Each	34.25	369.40	ditto					
27	Supply and erection of bakelite button holder shade, large size.	Each	5.40	33.05	Each	5.40	33.05	ditto					
28	Supply and erection of call bell 220/250 volts, fixed on teak wood board 17.5x10 cm (7"x4").	Each	24.00	187.30	Each	24.00	187.30	38.1					
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	4.55	184.25	Each	4.55	184.25	38.1					
30	Supply and erection of ceiling rose, bakelite.	Each	7.55	18.05	Each	7.55	18.05	ditto					
31	Supply and erection of switches 5 Amp.	S.		الطومت وتأ	and and a second se								
	 i) open type ii) piano type iii) ring type, recessed iv) plate type, recessed v) double control, open type vi) double control, ring type recessed vii) double control, piano type 	Each Each Each Each Each Each Each	7.25 7.25 7.25 7.25 10.30 10.30 10.30	18.95 18.95 14.45 39.35 28.30 29.50 25.90	Each Each Each Each Each Each Each	7.25 7.25 7.25 7.25 10.30 10.30 10.30	18.95 18.95 14.45 39.35 28.30 29.50 25.90	ditto					
32	Supply and erection of switches 10/15 Amp.							ditto					
	i) open typeii) recessed type	Each Each	7.25 7.25	30.05 38.45	Each Each	7.25 7.25	30.05 38.45						
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	7.25	60.05	Each	7.25	60.05	ditto					
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	7.25	44.45	Each	7.25	44.45	ditto					
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.							ditto					
	i) open typeii) recessed type	Each Each	7.25 7.25	38.45 74.45	Each Each	7.25 7.25	38.45 74.45						
36	Supply and erection of 3 pin switch and plug combined, recessed type.							ditto					
	i) 5 Amp	Each	7.25	57.65	Each	7.25	57.65						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN												
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	ii) 10/15 Amp	Each	7.25	82.25	Each	7.25	82.25						
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe, open type.	Each	7.25	117.65	Each	7.25	117.65	ditto					
38	Supply and erection of cut out, bakelite.							ditto					
	i) open typeii) recessed type	Each Each	4.05 4.05	23.25 29.25	Each Each	4.05 4.05	23.25 29.25						
39	Supply and erection of button holder.							38.1					
	i) bakelite large sizeii) brass	Each Each	4.55 4.55	20.15 20.15	Each Each	4.55 4.55	20.15 20.15						
40	Supply and erection of brass bracket with holder.	Each	6.05	21.65	Each	6.05	21.65	ditto					
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	4.05	14.85	Each	4.05	14.85	ditto					
42	Supply and erection of kitkat, 500 volt:				53			ditto					
	 i) 15/20 Amp ii) 30/35 Amp iii) 60/65 Amp iv) 100 Amp v) 200 Amp vi) 300 Amp vii) 400 Amp viii) 500 Amp 	Each Each Each Each Each Each Each Each	7.55 8.20 12.55 14.15 16.15 16.15 21.65 21.65	32.75 33.40 52.75 87.95 128.35 275.95 346.25 495.65	Each Each Each Each Each Each Each Each	7.55 8.20 12.55 14.15 16.15 16.15 21.65 21.65	32.75 33.40 52.75 87.95 128.35 275.95 346.25 495.65						
43	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete.							38.1					
	i) double rod (80 watts) with two chokes and 2 starters.	Per set	135.30	930.40	Per set	135.30	930.40						
	ii) single rod (40 watts) with one choke and one starter.	ditto	108.25	465.35	ditto	108.25	465.35						
	iii) round tube, 32 watt, with one choke and one starter, without cover.	Each	108.25	527.75	Each	108.25	527.75						
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	90.20	629.70	ditto	90.20	629.70						
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking							ditto					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	arrangement, including painting:-											
	 i) 60x35x15 cm (24"x14"x6") ii) 95x40x20 cm (38"x16"x8") 	Each Each	281.95 406.20	2,219.95 2,768.10	Each Each	281.95 406.20	2,219.95 2,768.10					
	iii) 105x52.5x22.5 cm (42"x21"x9")	Each	617.45	3,802.30	Each	617.45	3,802.30					
	iv) 135x70x27.5 cm (54"x28"x11")	Each	677.35	5,732.45	Each	677.35	5,732.45					
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate $25x6$ mm (1"x ¹ /4"), with bolts and nuts for hanging ceiling fans.	Each	18.05	123.65	Each	18.05	123.65	38.1 & 38.10				
46	Supply and erection of girder strut, of M.S. tee section 40x40x6 mm (11/2"11/2"x 1/4"), complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	24.00	750.40	Each	24.00	750.40	ditto				
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with $75x40x3$ mm ($3"x1\frac{1}{2}"x1/8"$) M.S. steel channel, with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	25.70	1,159.85	Each	25.70	1,159.85	38.1				
48	Supply and erection of roof suspension hook of M.S plate 75x40x12.7mm (3"x1½"x½") with 16 mm (5/8") hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Each	34.25	456.30	Each	34.25	456.30					
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	9.30	23.70	Each	9.30	23.70	ditto				
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	324.10	2,100.10	Each	324.10	2,100.10	38.12				
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x¼") section:-											
	 i) 0.60 metre (2') long for 2 lines. ii) 1.200 metre (4') long for 4 lines. 	Each Each	64.80 75.65	496.05 1,015.45	Each Each	64.80 75.65	496.05 1,015.45					
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.	Per Rft.	4.70	16.70	Per Metre	15.35	54.70	38.14				
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	6.30	25.40	Per Metre	20.75	83.35	ditto				
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line, include shackle insulator for holding	Per Rft.	27.65	223.65	Per Metre	90.75	733.65					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description	Ra	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	insulated wire and straining devices for bearer wire and other accessories etc., complete.									
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	27.35	221.80	Per Metre	89.65	727.50			
56	Supply and erection of lightning arrestor horn type, complete.	Each	143.90	2,063.90	Each	143.90	2,063.90			
57	Supply and erection of shackle insulator, medium size.	Each	17.10	167.10	Each	17.10	167.10	38.12		
58	Supply and erection of pin insulator, green medium size.	Each	17.10	59.10	Each	17.10	59.10	ditto		
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	8.90	1,146.30	Per Kg	8.90	1,146.30	38.1		
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire, pole to pole etc.	Per Kg	8.90	96.30	Per Kg	8.90	96.30	ditto		
61	Wiring overhead line in 2 single core, PVC/weather proof cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.	20		× C	1922			38.12		
	i) 3/0.74 mm (3/0.029") ii) 7/0.74 mm (7/0.029") iii) 7/0.91 mm (7/0.036") iv) 7/1.12 mm (7/0.044")	Per Rft. ditto ditto ditto	2.45 2.45 2.45 2.45 2.45	9.40 17.10 23.40 31.90	Per Metre ditto ditto ditto	8.00 8.00 8.00 8.00 8.00	30.80 56.05 76.85 104.55			
62	Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft.	4.25	16.55	Per Metre	13.95	54.30	38.1		
63	Supply and erection of street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp.	Each	119.90	847.80	Each	119.90	847.80			
64	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):									
	i) G.E.C. designii) Philips design	Each ditto	239.80 239.80	2,483.80 2,909.80	Each ditto	239.80 239.80	2,483.80 2,909.80			
65	Supply and fitting of mercury vapour lamp, complete with choke set. i) 125 watt lamp	Each	90.20	930.20	Each	90.20	930.20			
	ii) 250 watt lamp	ditto	108.25	1,728.25	ditto	108.25	1,728.25			
66	Manufacture and erection of angle iron lattice steel structure	Each	4,020.50	19,514.30	Each	4,020.50	19,514.30	38.13	The composite rate will be reduced	

	MRS, BI-ANNUAL PERIC	D (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) D I	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1 ¹ / ₄ "x1 ¹ / ₄ "x3/16" (30x30x5 mm) angle iron legs and ³ / ₄ "x ³ / ₄ "1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1 ³ / ₄ "x1 ³ / ₄ "x3/16" (45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x ¹ / ₄ " (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.								or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3 ¹ /2'x3 ¹ /2' (2400x1050x1050 mm), etc. complete in all respects.	Each	3,944.35	31,006.15	Each	3,944.35	31,006.15	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (½") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	537.90	3,100.05	Job	537.90	3,100.05		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in							38.11	
	 15 mm (¹/₂") dia G.I. pipe, best quality:- i) on surface, including clamps, etc. ii) recessed in wall, including hooks, jharries and making good surface. 	Per Rft. ditto	5.50 13.10	48.50 57.45	Per Metre ditto	18.00 43.05	159.05 188.50		
70	Bonding to earth with wire on surface, including cost of wire, clamps, thimbles, etc.							ditto	
	a) G.I. wire:								
	i) 8 SWG ii) 16 SWG	Per Rft. ditto	2.20 2.20	7.35 3.60	Per Metre ditto	7.25 7.25	24.20 11.80		
	b) Copper wire:								
	i) 16 SWG	Per Rft.	2.20	9.70	Per Metre	7.25	31.80		

	MRS, BI-ANNUAL PERIO	D (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 20 SWG	ditto	2.20	4.90	ditto	7.25	16.10		
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	8.75	12.40	Per Metre	28.80	40.70	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	358.60	3,842.70	Each	358.60	3,842.70	ditto	
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.			*)					
	 i) tape 40x3 mm (1¹/₂"x1/8") ii) tape 50x3 mm (2"x1/8") 	Per Rft. ditto	13.10 13.10	243.05 291.15	Per Metre ditto	43.05 43.05	797.25 954.90		
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	239.80	2,129.80	Job	239.80	2,129.80		
75	Supply and erection of electric energy meter, including meter testing fee, etc.	10		No.	553			38.1	
	a) single phase:	Fi	1ance	Depai	tmen:	ť.			
	 i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts 	Each ditto	90.75 90.75	1,854.75 1,854.75	Each ditto	90.75 90.75	1,854.75 1,854.75		
	b) three phase, 4 wires:								
	 i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts 	Each ditto ditto	181.50 270.60 270.60	5,299.50 5,388.60 5,388.60	Each ditto ditto	181.50 270.60 270.60	5,299.50 5,388.60 5,388.60		
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.
	 i) 1200 mm (48") sweep, 275-300 RPM. ii) 1400 mm (56") sweep, 250-275 RPM. 	Each ditto	180.70 202.95	773.35 886.75	Each ditto	180.70 202.95	773.35 886.75		
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.
	 i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM 	Each ditto	121.00 121.00	532.10 605.25	Each ditto	121.00 121.00	532.10 605.25		
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	145.20	705.55	Each	145.20	705.55		The credit of out turn of dismantled material has been accounted for in

	MRS, BI-ANNUAL PERIC	D (1st F	EBRUAR	Y, 2012 TO 3	31st JULY	′, 2012) DI	STRICT LO	DHRAN	
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	22.70	82.70	Each	22.70	82.70	38.1	the rate.
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	18.15	42.15	Each	18.15	42.15	ditto	
	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	22.70	130.70	Each	22.70	130.70	ditto	
	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	45.40	153.50	Each	45.40	153.50		The credit out turn of dismantled material has been accounted for in the rate.
	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	98.00	133.30	Each	98.00	133.30		
		an Chi	S	مار بر مار س		F			

********* Finance Department

25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	Railway Track, etc.											
1	Laying, linking and packing tramway line.	100Lft.	919.10		Metre	30.15						
2	Dismantling tramway track.	100Lft.	306.15	*)	Metre	10.05						
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	2383.70		Metre	78.20						
4	Linking points and crossings, complete with fastenings.	Each	2321.20		Each	2321.20						
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	250.80		Each Point	250.80						
6	Fixing street lamp posts.	Each	302.95	X C	Each	302.95						
7	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	2767.40	Depar	100 Nos	2767.40						
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	356.60		100 Nos	356.60						
	IRON WORK											
9	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	1435.50	6674.25	100 Kg	2825.80	13138.30					
10	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	Per Cwt	504.65	5488.95	100 Kg	993.40	10805.00					
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	159.00		100 Kg	312.95						
12	Fixing corrugated iron sheet, including revitting, etc.	100 Sft.	575.50		sq.m	61.95						
13	Erecting corrugated iron sheet tanks, upto 20'	Per Cwt	288.55		100 Kg	568.00						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	(6 m) height.										
14	Erecting rolled steel beams or old rails, in roofs, etc., erection and fixing in position.	Per Cwt	178.30		100 Kg	351.00					
15	Erecting rolled steel beams or rails, erection for posts etc. (other than in roofs).	Per Cwt	86.25		100 Kg	169.75					
16	Making bolts and nuts of iron rods.	Per Cwt	1081.10	6830.10	100 Kg	2128.10	13445.05				
17	Cutting rails, rolled steel joists and beams, with hacksaw:-		(9							
	a) upto 6" size (150 mm) b) above 6" size (150 mm)	Per Cut Per Cut	107.30 157.45		Per Cut Per Cut	107.30 157.45					
18	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	51.10	in the	Per Cwt Cut	51.10					
19	Bending rolled steel beams or rails.	Per Bend	54.15	255.70	Per Bend	54.15	255.70				
20	Drilling holes, in plates upto ½" (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	22.30	Depar	Per Hole	22.30					
	Extra for drilling holes in plates over ¹ /2" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	12.65		Per Hole	12.65					
22	Rivetting 1/8" dia (3 mm).	100 Nos	324.50		100 Nos	324.50					
23	Cutting out Rivets, all sizes.	100 Nos	897.60		100 Nos	897.60					
24	Fitting and erection of gutters of sheet iron.	Per Lft.	38.20		Metre	125.25					
25	Cutting and fixing iron bars, for barred windows.	Per bar	20.50		Per bar	20.50					
26	Cutting G.I. sheets.	Each Cut	11.05		Each Cut	11.05					
27	Notching web or foot of rail posts, for housing rail beams.	Per	240.70	375.10		240.70	375.10				
28	Hoop iron netted trellis work fixed with nails.	Notch Per Sft.	14.30		Notch sq.m	153.95					
29	Fixing zinc iron or G.I. sheet on table tops.	Per Sft.	8.45		sq.m	91.05					
30	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	89.85	627.65	sq.m	966.85	6753.55				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
31	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm) centre to centre, with locking arrangement.	Per Sft.	93.10	772.40	sq.m	1001.70	8310.95					
32	Making and fixing grating in opening, including fixing at site with flat iron $2^{\circ}x_3/8^{\circ}$ (50x10 mm) and 34° (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	35.95	313.75	sq.m	386.60	3375.90					
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed to 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete.	Per Rft.	176.20	643.70	Metre	578.05	2111.90		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.			
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8" punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	84.55	446.80	Metre	277.45	1465.90					
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	61.35	501.35 Depar	Metre	201.28	1644.85		-do-			
36	Providing and fixing collapsible gate made of 2"x2"x"¼" (50x50x6 mm) tee iron at top and bottom, channel iron verticals ¾"x¼"x1/8" (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of ¾"x¼"x1¼"x1/8" (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	127.50	533.45	sq.m	1371.70	5740.10					
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1¼"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	28.35	202.20	sq.m	305.25	2175.70					
38	Providing and fixing M.S. angle iron 1 ¹ / ₂ "x1 ¹ / ₂ "x ¹ / ₄ "	Per Rft.	13.00	121.70	Metre	42.65	399.30					

	MRS, BI-ANNUAL PE	RIOD (1st	FEBRUAR	Y, 2012 TO 3 1	st JULY	', 2012) D	ISTRICT LO	OHRAN	
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.								
39	Providing and fixing stair railing of 2 ¹ / ₂ " (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.	Per Rft.	80.50	591.00	Metre	264.05	1938.90		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
40	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	12.10	42.45	sq.m	130.20	456.90		
41	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1 ¹ / ₂ "x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ³ / ₄ "x1"x ³ / ₄ "x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the Engineer-in-charge:-	9 1 1 1 1 1 1	inance	Depar	T star Starten	t.			For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	a) without wire gauze:								
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick b) fixed with wire gauze, 22 SWG 	Per Sft. ditto ditto ditto ditto	33.00 33.00 33.00 33.00 33.00	246.15 248.55 253.35 255.75 258.15	sq.m ditto ditto ditto ditto	355.30 355.30 355.30 355.30 355.30	2648.70 2674.50 2726.15 2752.00 2777.80		
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick 	Per Sft. ditto ditto ditto ditto	45.10 45.10 45.10 45.10 45.10	286.05 288.45 293.25 295.65 298.05	sq.m ditto ditto ditto ditto	485.00 485.00 485.00 485.00 485.00	3078.15 3104.00 3155.65 3181.45 3207.25		
42	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1¼"x1¼" (30x30mm) for leaves including M.S. square bars ¼"x¼" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG)								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	 beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects. a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass 	Per Sft.	37.65	236.45	Sq.m	405.20	2543.95			
	panes ¹/₄" (6 mm) thick.b) For fixed panels without wire gauze.	ditto	36.75	131.05	ditto	395.40	1410.05			
43	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	36.30	293.55	Sq.m	390.80	3158.75			
44	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	44.85	347.70 Ocpar	Per Sft.	482.70	3741.20			
45	Flapping G.I. pipes for bath room drains.	Each	269.30	302.90	Each	269.30	302.90			
46	Supply and fixing iron grating for fire place.	Per Sft.	64.70	160.70	sq.m	695.95	1728.90			
47	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	24.00		Metre	78.65				
48	Providing and fixing angle iron railing, using 2¼"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x¼" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long ¾" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	41.65	739.25	Metre	136.65	2425.35			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN										
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
49	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5 mm), angle iron post 3 ¹ /4 ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" (225x225x300 mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	893.55	8897.50	Metre	29.30	291.90				
50	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects.	100Rft.	1450.00	11173.00	Metre	47.55	366.55				
51	Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s AI-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	51.80	390.25 Ocpar	sq. m	557.35	4199.10		 Increase rate by Rs. 30.00 per Sft or Rs.322.80 per Sq-metre if sections thickness is 2 mm. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used. 		
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan Cables having frame size of $100 \times 20 \text{ mm} (4"x34")$ and leaf frame sections of $50 \times 20 \text{ mm} (2"x34")$, all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Sft	74.85	294.80	sq. m	805.40	3172.05		 (1) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if section thickness is 1.2 mm. (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminium shade. (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per sq-metre if local glass is used. 		

26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN											
Sr.	Description		Rate (British Sy	vstem)	Rat	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	35.40	43.80	Per sq.m	380.80	471.10		The board is to be of cement plaster ½" (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.			
2	Fixing handles to iron hammers.	Each	37.80		Each	37.80	-					
3	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete. <u>Surveying</u>	100Lft.	3,369.50	20,331.00	L.m.	110.55	667.05		Vertical bars in straining and stiffening posts to be 4 No. each by 1/2" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be 1/4" (6 mm) dia. at 12" (300 mm) centre to centre.			
4	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	22.45	114.85	Each	22.45	114.85					
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	60.50	76.10	100Nos.	60.50	76.10					
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	145.20	325.20	100Nos.	145.20	325.20					
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	41.25	48.45	Per L.M.	135.35	158.95					
8	Placing boundary pillars in position, including digging pits.	Each	27.50	-	Each	27.50	-					
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	118.15	278.20	Each	118.15	278.20		Composite rate does not include cost of iron distance marks.			
	Hand Pumps & Pressure Pipes											
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	24.00	-	Per cut	24.00	-					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	43.25	-	Per cut	43.25	-			
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	30.05	-	Each End	30.05	-			
13	Assembling 1 ¹ / ₂ " (40 mm) dia pressure pipe.	100Lft.	111.70	-	Per Metre	3.65	-			
14	Boring and fixing 1 ¹ /2" (40 mm) dia pressure pipe:									
	 a) in ordinary soil b) in clay c) in shingle 	Per Lft. Per Lft. Per Lft.	40.15 80.25 120.35	0	Per Metre Per Metre Per Metre	131.75 263.30 394.85	-			
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	17.90		Per Metre	58.70	-			
16	Fixing hand pump (Machine only)	Each	72.60		Each	72.60	-			
	<u>Rest House Furniture & Fuel, etc.</u>	100	R	in	7 🎉					
17	Washing Niwar of bed.	Per bed	267.30	287.45	Per bed	267.30	287.45			
18	Washing Durries.	100Sft.	356.40	404.40	sq.m	38.35	43.55			
19	Recaning chairs:	9	inanci		tmeni	ŀ				
	 i) office chairs, single caning seat only. ii) office chairs, double canning seat only. iii) office chairs, single caning back only. iv) office chairs, double caning back only. v) easy chairs, single caning seat only. vi) easy chairs, double caning seat only. vii) easy chairs, single caning only, back and seat in one piece. viii) easy chairs, double caning back & seat in one piece or couches with caned area about 16 Sft (1.5 Sqm). 	Each Each Each Each Each Each Each	127.05 163.35 90.75 145.20 90.75 254.10 363.00 544.50	157.65 206.55 92.70 161.75 131.80 315.30 615.00 1,156.50	Each Each Each Each Each Each Each	127.05 163.35 90.75 145.20 90.75 254.10 363.00 544.50	157.65 206.55 92.70 161.75 131.80 315.30 615.00 1,156.50			
20	Making and fixing Hat pegs ordinary.	Each	65.35	406.60	Each	65.35	406.60			
21	Weaving charpoy.	Each	235.95	-	Each	235.95	-			
22	Sweeping chimney.	Each	59.40	60.60	Each	59.40	60.60			
23	Picture railing, including making, fixing and painting.	Per Lft.	18.70	80.45	Per LM	61.35	263.90			
24	Cutting fuel wood, from plantation.	100Kg	79.55	-	100Kg	79.55	-			
25	Splitting fuel wood.	100Kg	166.65	-	100Kg	166.65	-			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN								
Sr.	Description	Rate (British System) Rate (Metric Syste		ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	262.25	-	100Kg of Char- coal	262.25	-		
27	Filling cement bags with coal and sewing (including cost of strings).	100Cft.	730.60	733.50	cu.m	258.05	259.05		
28	Supplying manure.	Cart Load	89.10	209.10	Cart Load	89.10	209.10		Capacity of cart, 20 Cft. (0.57 cu.m).
29	Washing punkha frills.	Each	72.60		Each	72.60	-		
30	Washing:-			*)					
	a) table clothb) napkins, dusters, etc.	Each Each	18.15 12.10		Each Each	18.15 12.10	-		
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	32.60		Each No.	32.60	-		
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	35.70	(عادت باند	Each No.	35.70	-		
33	Dredging Sumps.	Per Shift	1,336.50	2. C	Per Shift	1,336.50	-		Not less than five gangmen to be employed for each shift to ensure effective dredging.
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each 🤦	99.00	: Dep <u>a</u> i	Each	99.00	-		
35	Bailing out water:-								
	a) by hand b) by pump	1000 Cft. 1000 Cft.	1,069.20 112.40	253.25	cu.m ditto	37.75 3.95	- 8.95		Rate includes cost of providing pump, POL and operation charges, etc.
36	Drilling holes in R.C. Trough.	Per Nos.	59.95	-	Per Nos.	59.95	-		
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.								The rate includes overlaps.
	 i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick) 	Per Sft. Per Sft.	0.55 1.10	1.65 2.05	sq.m sq.m	5.85 11.70	17.90 21.80		
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100Sft.	734.45	5,377.25	sq.m	79.05	578.60		
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	117.85	-	Per Hole	117.85	-		Same rate to be paid for other type of masonry and R.C.C. work.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) DISTRICT LODHRAN									
Sr. No.	Description	Rate (British System)			Rate (Metric System)			Spec. No.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite		
	Making 1 ¹ / ₂ "x1 ¹ / ₂ " (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	103.15	-	Per Plank	103.15	-		
	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	35.65		Per hole per c.m depth	14.25			
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	36.30	167.10	sq.m of each spray	3.90	18.00		
43	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.	Gt 100-							
	 i) without cement concrete base. ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm). 	100Rft. 100Rft.	4,017.25 4,430.55	19,944.25 21,654.80	Per Metre Per Metre	131.75 145.30	654.15 710.30		

Finance Department