Market Rates System

(MRS)

1st February to 31st July, 2012

haroon_01@hotmail.com

TABLE OF CONTENTS

Sr No.	Chapter	Pa	ge N	<i>los</i>
01.	Carriage	03	to	22
02.	Loading, Unloading & Stacking	23	to	25
03.	Earthwork (Excavation & Embankment)	26	to	32
04.	Dismentling (Demolition)	33	to	37
05.	Mortar	38	to	39
06.	Concrete	40	to	50
07.	Brickwork	51	to	56
08.	Stone Masonary	57	to	59
09.	Roofing	60	to	65
10.	Flooring	66	to	71
11.	Surface Rendering	72	to	76
12.	Wood Work	77	to	87
13.	Painting & Varnishing	88	to	94
14.	Lining of Canals	9 5	to	96
15.	Sheet Piling	97	to	<i>98</i>
16.	Protection & Diversion Work	99	to	109
17.	Outlets	110	to	112
18.	Road & Road Structure	113	to	117
19.	Plumbing, Sanitary Installation & Gas Fittings	118	to	124
20.	Surface Drainage	125	to	126
21.	Sewerage	127	to	131
22.	Sinking of Wells	132	to	134
23.	Tubewell & Water Supply	135	to	147
24.	Electric Installation	148	to	161
	Iron Work	162	to	167
26.	Miscellaneous	168	to	171

1. CARRIAGE

Note:	1	The rates are applicable to carriage of material on pacca roads only. For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.
Note:	2	For hilly areas 25% above the rates in the plain areas shall be allowed for total mileage (Km) covered.
Note:	3	In case of articles longer than 15 ft. (4.6 m) carried in trucks, the following rates shall be allowed:-
		i) Above 15 ft. to 25 ft. (4.6 to 7.6 m) :- Total rates to be paid for 15 ft. to 25 ft. (4.6 to 7.6 m) length will be 1.5 times of the rate given in the Composite Schedule of Rates.
		ii) Above 25 ft. (7.6 m) :- The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.
		The length measured shall not be the actual length, but the length of the form of consignment as actually received.
Note:	4	The term 'mile' (Km) whenever used is to mean statute mile (Km).
Note:	5	The rates include loading and unloading of material from the conveyance and stacking as directed.
Note:	6	The rates for carriage by boat or steamer shall be the same as by any other mechanical means on land
		MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB
		100-1-3

Sr.	Description	1	Y	6	Pot	e (Metric Sys	tom)	Spec.	Remarks
No.	Description				Unit of	(Metric Sys	stem)	No.	Remarks
		1		and the second second	M/ment	Labour	Composite		
1	Carriage of 100 Cft. (2.83 cu.m) of all materials like stone		200					16.1	
	aggregate, spawl, kankar lime (unslaked), surkhi, etc. or	1977							
	150 Cft. (4.25 cu.m) of timber, by truck or by any other	21	nance	Depar	TM BNLT				
	means owned by the contractor.								
	1st chain (1st 30 m)				30M	82.50			
	2nd chain (2nd 30 m)				30M	15.20			
	3rd to 10th chain (60 to 300 m)				30M	9.45			
	1000 to 3000 ft. (300 to 900 m)				300 Metre	92.70			
	1st Km				Km	151.75			
	2nd Km				Km	71.71			
	3rd Km				Km	55.00			
	4th Km				Km	38.34			
	5th Km				Km	35.56			
	6th Km				Km	34.94			
	7th Km				Km	32.45			
	8th Km				Km	32.08			
	9th Km				Km	30.04			
	10th Km				Km	27.93			
	11th Kms to 200Kms				Km	20.32			
	201 Kms to 250 Kms				Km	3.25			
	251 Kms & susequent Kms				Km	2.00			
2	Carriage of 5 tons of all material like coal, stone lime							16.1	Cement carried in containers other
	(unslaked), etc. B.G. Rail fastenings, points and crossing,								than bags will be paid according to
	Bridge Girders, pipes, sheets, Rail, M.S. bars, etc. etc.								this item. The word "pipes" covers

	MRS, BI-ANNUAL PERIOD (1st F	st JULY, 201	012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB					
Sr.	Description			Rate	e (Metric Sys	stem)	Spec.	Remarks
No.				Unit of M/ment	Labour	Composite	No.	
	by truck or any other means owned by the contractor.					•		G.I,C.I,R.C.C. and P.C.C.
3	by truck or any other means owned by the contractor. Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km 11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & usequent Kms Carriage of 100 maunds of fuel wood by truck or any other means owned by the contractor: 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 4th Km 5th Km 6th Km 7th Km 8th Km 9th Km	nance	Depat	30M 30M 30M 30M 300M Km Km Km Km Km Km Km Km Km Xm 30 M 30 M 30 M 30 M 30 M 30 M 30 M 30 M	82.50 15.20 9.45 92.70 151.75 71.71 55.00 38.34 35.56 34.94 32.45 32.08 30.04 27.93 20.32 3.25 2.00 82.50 15.20 9.45 92.70 151.75 71.71 55.00 38.34 35.56 34.94 35.56 34.94 32.45		16.1	G.I,C.I,R.C.C. and P.C.C.
	10th Km 11th & subsequent Kms			Km Km	27.93 20.32			
4	Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm) or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or any other means owned by the contractor :-			Kill	20.32		ditto	Reduce the rate by 33% in case of carriage of 1000 Nos. tiles size 12"x6"x1 ¹ /4" (300 x 150 x 30 mm).

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Pate	e (Metric Sys	stem)	Spec.	Remarks
No.	Description				Unit of M/ment	Labour	Composite	No.	itelitäi K5
	1st chain (1st 30 m)				30 M	82.50	•		
	2nd chain (2nd 30 m)				30 M	15.20			
	3rd to 10th chain (60 to 300 m)				30 M	9.45			
	1000 to 3000 ft. (300 to 900 m)				300 M	92.70			
	1st Km 2nd Km				Km Km	151.75 71.71			
	3rd Km				Km	55.00			
	4th Km				Km	38.34			
	5th Km				Km	35.56			
	6th Km				Km	34.94			
	7th Km				Km	32.45			
	8th Km		1	5	Km	32.08			
	9th Km	- 11			Km	30.04			
	10th Km		20.05		Km	27.93			
	11th & subsequent Kms	1238	-		Km	20.32			
5	Carriage of 100 cft. (2.83 cu.m) of all material like stone,	-109J	1		153			16.1	Material trolly to be supplied by the
	aggregate, spawl, kankar lime(unslaked), surkhi, etc. or	10		-//					Government and maintained and run
	150 cft. (4.25 cu.m) of timber, by means of material trolly 1st chain (1st 30 m)				30 M	82.50			by the contractor.
	2nd chain to 10th chain (2nd 30 m to 300 m)		6		30 M	15.20			
	1000 to 3000 ft. (300 to 900 m)	T		15° anna sand	300 M	92.70			
	1st Km	11.1	nance	snepus	Km	124.47			
	2nd Km 2nd Km				Km Km	95.05			
	3rd Km 4th Km				Km Km	50.83 39.83			
	5th Km				Km	35.00			
	6th Km					33.63			
					Km				
	7th Km				Km Km	28.41			
	8th Km				Km Km	28.08			
	9th Km				Km	26.28			
	10th Km				Km	24.42			
	11th Kms to 200Kms 201 Kms to 250 Kms				Km Km	19.50			
	201 Kms to 250 Kms 251 Kms & susequent Kms				Km Km	3.25 2.00			
6	Carriage of 5 tons of all material like coal, stone lime				1111	2.00		16.1	Material trolly to be supplied by the
	(unslaked), etc. B.G. Rail fastening, points and crossing,								Government and maintained and run
	Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by								by the contractor.
	means of material trolly.				20 M	02 50			
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	82.50 15.20			
	1000 to 3000 ft. (300 to 900 m)				300 M	92.70			
	1st Km				Km	124.47			
	2nd Km				Km	95.05			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB	
Sr.	Description				Pote	e (Metric Sys	stom)	Spec.	Remarks	
No.	Description				Unit of	(Metric Sys	stem)	No.	Kemarks	
					M/ment	Labour	Composite			
	3rd Km				Km	50.83				
	4th Km				Km	39.83				
	5th Km				Km	35.00				
	6th Km				Km	33.63				
	7th Km				Km	28.41				
	8th Km				Km	28.08				
	9th Km				Km	26.28				
	10th Km				Km	24.42				
	11th Kms to 200Kms 201 Kms to 250 Kms				Km Km	19.50 3.25				
	251 Kms & susequent Kms				Km	2.00				
7	Carriage of 100 maunds of fuel wood, by means of							ditto	Material trolly to be supplied	
	material trolly. 1st chain (1st 30 m)				30 M	82.50			by the Government and maintained and run by the	
	2nd chain (2nd 30 m)		2	6 1	30 M 30 M	82.30 15.20			contractor.	
	1000 to 3000 ft. (300 to 900 m)		/ .		300 M	92.70				
	1st Km		1		Km	124.47				
	2nd Km 3rd Km	de la			Km Km	95.05 50.83				
	4th Km				Km	39.83				
		19								
	5th Km	155	500	67	Km	35.00				
	6th Km	150			Km	33.63				
		4		5/2	53-					
	7th Km			200	Km	28.41				
	8th Km	10000		1576	Km	28.08				
		Fi	nance	Depar						
	9th Km				Km	26.28				
	10th Km				Km	24.42				
	11th & subsequent Kms				Km	19.50				
8	Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm),							ditto	Material trolly to be supplied by the	
	by means of material trolly.								Government and maintained and run	
	1st chain (1st 30 m)				30 M	82.50			by the contractor.	
	2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m)				30 M 300 M	15.20 92.70				
	1000 to 5000 ft. (500 to 500 ff)				Km	124.47				
	2nd Km				Km	95.05		16.1		
	3rd Km				Km	50.83				
	4th Km				Km	39.83				
	5th Km				Km	35.00				
	6th Km				Km	33.63				
	7th Km				Km	28.41				
	8th.				Km	28.08				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks		
No.	2 sourpron				Unit of			No.			
					M/ment	Labour	Composite				
	9th Km				Km	26.28					
	10th Km				Km	24.42					
0	11th & subsequent Kms Carriage of 1000 No. bricks, 9"x4½"x3"				Km	19.50		1.0			
9	(225x113x75 mm) or 8"x4"x4" (200x100x100							ditto			
	mm) (nominal) 1st chain (1st 30 m)				30 M	67.60					
	2nd chain (2nd 30 m)				30 M	13.75					
	3rd to 10th chain (60 to 300 m)				30 M	7.76					
	1000 to 3000 ft. (300 to 900 m)				300 M	75.90					
	1st Km 2nd Km				Km Km	124.40 58.65					
	3rd Km		/ ×		Km	45.04					
	4th Km		(1	Km	31.62					
	5th Km	. See	/4107-001		Km	30.01					
	6th Km				Km	29.32					
	7th Km	NY -	No.	الرجومين	Km	26.58					
	8th Km	1			Km	26.28					
	9th Km	185			Km	24.60					
	10th Km	2.18	nance	Depar	Km	22.88					
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½"				Km	16.56		16.1			
	(225x113x38 mm). 1st chain (1st 30 m)				30 M	40.80					
	2nd chain (2nd 30 m)				30 M	7.51		16.1			
	3rd to 10th chain (60 to 300 m)				30 M	4.64					
	1000 to 3000 ft. (300 to 900 m) 1st Km				300 M Km	45.85 75.10					
	2nd Km				Km	35.50					
	3rd Km				Km	27.23					
	4th Km				Km	18.95					
	5th Km				Km	17.46					
	6th Km 7th Km				Km	17.18					
	7th Km 8th Km				Km	16.05					
	8th Km 9th Km				Km Km	15.86 14.86					
	200 Kill				KIII	14.00					

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	NSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	10th Km				Km	13.86	Composite		
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.				Km	10.04		ditto	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	1.56 0.19 0.09			
	1000 to 3000 ft. (300 to 900 m)				300 M	0.91			
	1st Km				Km	1.86			
	2nd Km				Km	1.28			
	3rd Km		1	6	Km	0.56			
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including bundling.				Km	0.34		16.1	
	1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft.	1. KOY-			300 M 300 M	22.74 2.83			
	1st Km	100			Km	4.57			
	2nd Km		- A	N. C.	Km	4.69			
	3rd Km	Fi	nance	Depar	Km	2.20			
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash or brushwood, by boat or road :-				Km	1.98		ditto	Previous lead of collection not to be deducted from the next lead of carriage.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	33.75 15.20 4.64			
	1000 to 3000 ft. (300 to 900 m)				300 M	38.08			
	1st Km				Km	69.10			
	2nd Km				Km	35.50			
	3rd Km				Km	27.23			
	4th Km				Km	18.95			
	5th Km				Km	17.46			

	MRS, BI-ANNUAL PERIOD (1st F	2012 TO 31	st JULY, 201	12) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB					
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	6th Km				Km	17.18			
	7th Km				Km	16.05			
	8th Km 9th Km 10th Km 11th Km & subsequent				Km Km Km	15.86 14.86 13.86 10.04			
	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre) Execeeding 1000 to 5000 ft (300 to 1500metre)				Tonne 300 M "	275.54 66.76		ditto	
	1st Km				Km	149.29			
	2nd Km		/ 3	5	Km	69.89			
	3rd Km	-1-1			Km	47.63			
	4th Km	ŝ			Km	31.08			
	5th Km	Sec.	R	6)	Km	29.37			
	6th Km	1		<u>S</u>	Km	28.22			
	7th Km			2.5	Km	24.51			
	8th Km 9th Km 10th Km 11th Km & susequent	T	nance	Depar	Km Km Km Km	24.15 23.62 18.71 15.27			
15	Carriage of small consignments weighing upto 5 maunds (job rates) :							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%; and for consignments weighing 10
	Upto 1000 ft. (300 metre)				Consign- ment/	22.38			to 20 maunds, rate be increased by 100%.
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				300 M	15.34			
	1st Km				Consign-	23.36			
	2nd Km				ment/ Km	14.64			
16	3rd Km & subsequent Carriage of consignments job.				11	4.92			
	i) Cooly load for distance:-				Each				

	MRS, BI-ANNUAL PERIOD (1st F	BRUARY, 2012 TO 31st JULY, 20	12) TEH:NO	WSHEHR	A, SOAN V	ALLEY M	(HUSHAB	
Sr.	Description		Rate	e (Metric Sy	stem)	Spec.	Remarks	
No.	-		Unit of M/ment	Labour	Composite	No.		
	a) Upto 5 Km b) Above 5 to 13 Km		Consignment	47.95 113.85				
	 ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ½ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km 		Each Consignment " " "	10.85 16.45 20.80 26.00 45.95 82.25				
	 iii) Cart load for a distance :- a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to10 Miles(16 Km) 	5	Each Consig- nment "	89.85 163.55				
15	 iv) Camel load for a distance:- a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km) 			66.45 100.75				
17	Hire charges of:- i) truck (10 Ton Capacity)		Per day	3000.00			 This item will be allowed with prior concurrence of Superintending Engineer. The rate includes pay of driver and characterized and The provine shall. 	
	ii) tractor with trollyiii) tractor without trolly	Finance Depai	tment	1000.00 800.00			and cleaner only. The repairs shall be the responsibility of the owner and the cost of lubrication, fuel, loading and unloading shall be paid by the borrower.	
18	Carriage of bitumen, tar or other lubricants, in drums:					16.1		
	1st Km		Per Tonne	24.89				
	2nd Km		"	17.21				
	3rd Km & subsequent Kms		"	7.06				
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-							
	 i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 		30 M 30 M 30 M 300 M Km	3.25 0.60 0.35 3.65 6.00				

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	NSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	2nd Km				Km	2.80			
	3rd Km				Km	2.15			
	4th Km				Km	1.49			
	5th Km				Km	1.39			
	6th Km				Km	1.36			
	7th Km				Km	1.26			
	8th Km				Km	1.24			
	9th Km				Km	1.16			
	10th Km		1	0	Km	1.07			
	11th Km & Susequent				Km	1.03			
ii)	4" (100 mm) i/d pipes:-				日徽				
	1st chain (1st 30 m)	altr.	Contraction of the second		30 M	4.25			
	2nd chain (2nd 30 m)	US -	1.	- 20	30 M	0.80			
	3rd to 10th chain (60 to 300 m)	1	ALC: NO		30 M	0.50			
	1000 to 9000 ft. (300 to 900 m)				300 M	4.80			
	1st Km	F	nance	Depar	Km	7.86			
	2nd Km				Km	3.68			
	3rd Km				Km	2.81			
	4th Km				Km	1.95			
	5th Km				Km	1.80			
	6th Km				Km	1.77			
	7th Km				Km	1.64			
	8th Km				Km	1.62			
	9th Km				Km	1.51			
	10th Km 11th Km & subsequent Km				Km Km	1.41 1.36			
iii						1.50			
	1st chain (1st 30 m)				30 M	6.40			
	2nd chain (2nd 30 m)				30 M	1.20			
	3rd to 10th chain (60 to 300 m)				30 M	0.75			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 201	st JULY, 201	12) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB					
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.	2 see plot				Unit of M/ment	Labour	Composite	No.	
	1000 to 9000 ft. (300 to 900 m)				300 M	7.20			
	1st Km				Km	11.78			
	2nd Km				Km	5.53			
	3rd Km				Km	4.24			
	4th Km				Km	2.95			
	5th Km				Km	2.75			
	6th Km				Km	2.69			
	7th Km				Km	2.49			
	8th Km				Km	2.46			
	9th Km	/	× ×	\sum	Km	2.29			
	10th Km 11th Km & subsequent Km				Km Km	2.11 1.78			
	v) 8'' (200 mm) i/d pipes:				344	1.70			
		- 後 -			-1667	10.05			
	1st chain (1st 30 m) 2nd chain (2nd 30 m)	1 1988			30 M 30 M	10.85 2.00			
	3rd to 10th chain (60 to 300 m)	1438	See.13	501	30 M	1.25			
	1000 to 3000 ft. (300 to 900 m)	120			300 M	12.15			
	1st Km	1000		10	Km	19.92			
	2nd Km		-2-7	2.2	Km	9.67			
	3rd Km	1997-19		100	Km	7.34			
	4th Km	Tin	ance	Depar	Km	5.08			
	5th Km				Km	4.71			
	6th Km				Km	4.63			
	7th Km				Km	4.29			
	8th Km				Km	4.12			
	9th Km				Km	3.77			
	10th Km 11th Km & subsequent Km				Km Km	2.47 1.76			
	v) 10" (250 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	14.55			
	2nd chain (2nd 30 m)				30 M	2.70			
	3rd to 10th chain (60 to 300 m)				30 M	1.65			
	1000 to 3000 ft. (300 to 900 m)				300 M	16.35			
	1st Km 2nd Km				Km Km	26.75 12.52			
	3rd Km				Km	9.57			
						2.07			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	ALLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	tem)	Spec.	Remarks
No.	Zooripion				Unit of M/ment	Labour	Composite	No.	
	4th Km				Km	6.64			
	5th Km				Km	6.16			
	6th Km				Km	6.05			
	7th Km				Km	5.86			
	8th Km				Km	5.79			
	9th Km				Km	5.44			
	10th Km 11th Km & subsequent Kms				Km Km	5.04 3.63			
	 vi) 12" (300 mm) i/d pipes: 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km 8th Km 9th Km 10th Km 	the second second	nance	Depar	30 M 30 M 30 M 300 M Km Km Km Km Km Km Km Km	18.90 3.50 2.15 21.25 34.80 17.30 12.86 8.64 8.00 7.85 7.28 7.19 6.73 6.23			
	11th Km & subsequent Kms				Km	4.62			
	 vii) 16" (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 				30 M 30 M 30 M 300 M Km Km Km	31.00 5.70 3.55 34.85 57.04 27.20 20.64 14.38			
	5th Km				Km	13.34			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	Description				Unit of	(wheth it by	stem)	No.	ixtinai K5
					M/ment	Labour	Composite		
					¥7	12.10			
	6th Km				Km	13.10			
	7th Km				Km	12.16			
	8th Km				Km	12.02			
					14111				
	9th Km				Km	11.26			
	10th Km				Km	10.47			
	11th Km & subsequent Kms				Km	7.64			
	viii) 18" (450 mm) i/d pipes:-								
	1st chain (1st 30 m)			and the second	30 M	39.85			
	2nd chain (2nd 30 m)				30 M	7.35			
	3rd to 10th chain (60 to 300 m)		1 1		30 M	4.55			
	1000 to 3000 ft. (300 to 900 m) 1st Km		/ .	1	300 M Km	44.80 73.29			
	2nd Km				Km	34.64			
	3rd Km	11			Km	26.56			
						20.30			
	4th Km	101			Km	18.52			
		18556.7		6	122				
	5th Km	650	1.1.1	12	Km	17.17			
		1		- /4	653				
	6th Km		-24	22	Km	16.87			
	7th Km				Km	15.67			
		21	nance	Depar	IM SM L				
	8th Km				Km	15.49			
	9th Km				Km	14.51			
	10th Km				Km	13.49			
	11th Km & subsequent Kms				Km	9.73			
	ix) 20'' (500 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	42.30			
	2nd chain (2nd 30 m)				30 M	7.80			
	3rd to 10th chain (60 to 300 m)				30 M	4.85			
	1000 to 3000 ft. (300 to 900 m)				300 M	47.55			
	1st Km				Km	77.83			
	2nd Km				Km	36.77			
	3rd Km				Km	28.18			
	4th Km				Km	19.64			
	5th Km				Km	18.22			
	6th Km				Km	17.90			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	NSHEHR	A, SOAN VA	ALLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.	F				Unit of			No.	
					M/ment	Labour	Composite		
	7th Km				Km	16.61			
	8th Km				Km	16.43			
	9th Km				Km	15.39			
	10th Km				Km	14.30			
	11th Km & subsequent Kms x) 24" (600 mm) i/d pipes:-				Km	10.52			
	1st chain (1st 30 m)				30 M	46.90			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	8.65 5.35			
	1000 to 5000 ft. (300 to 1500 m)		and the second second		300 M	52.65			
	1st Km		1	63	Km	86.22			
	2nd Km 3rd Km		/ .		Km Km	40.69			
					Km	31.20			
	4th Km	18	07.00		Km	22.27			
	5th Km				Km	20.14			
	6th Km	N.	No.	لرجيري	Km	19.79			
	7th Km	4		R C	Km	18.37			
	8th Km	Ŧ	nance	Bener	Km	18.16			
	9th Km	.2. 8	26-8878-8-9.787		Km	16.99			
	10th Km				Km	15.81			
20	11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading,				Km	11.44			
20	unloading and stacking (Rate per 1000 ft.) (300 metre) :-								
	i) 3'' (75 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	6.40			
	2nd chain (2nd 30 m)				30 M	1.20			
	3rd to 10th chain (60 to 300 m)				30 M	0.75			
	1000 to 3000 ft. (300 to 900 m) 1st Km				300 M Km	7.15 11.74			
	2nd Km				Km	5.54			
	3rd Km				Km	4.24			
	4th Km				Km	2.95			
	5th Km				Km	2.73			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 2	2012 TO 31	st JULY, 201	2) TEH:NO	NSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	6th Km				Km.	2.68			
	7th Km				Km	2.50			
	8th Km				Km	2.45			
	9th Km				Km	2.28			
	10th Km 11th Km & subsequent Kms ii) 4'' (100 mm) i/d pipes:-				Km Km	2.12 1.73			
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	-1+1		5	30 M 30 M 30 M 300 M Km Km Km	9.85 1.80 1.15 11.05 18.08 8.72 6.58			
	4th Km				Km	4.50			
	5th Km		N.	(کومت	Km	4.17			
	6th Km	10			Km	4.09			
	7th Km				Km	3.78			
	8th Km	12-12		Depar	Km	3.73			
	9th Km				Km	3.49			
	10th Km 11th Km & subsequent Kms iii) 5" (125 mm) i/d pipes:-				Km Km	3.26 2.80			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M " 300 M Km "	13.40 2.45 1.55 15.10 24.67 11.80 9.09			
	4th Km					6.39			
	5th Km				Km.	5.73			
	6th Km				"	5.62			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 20	12 TO 31s	st JULY, 201	2) TEH:NO	NSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	7th Km				"	5.21	•		
	8th Km					5.15			
	9th Km					4.82			
	10th Km 11th Km & subsequent Kms					4.46 3.28			
	iv) 6'' (150 mm) i/d pipes:								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 300 m) 1st Km. 2nd Km 3rd Km			5	30 M 30 M 30 M 300 M Km. Km. Km.	18.50 3.40 2.10 20.80 34.02 16.07 12.34			
	4th Km	il -	and a second		Km.	8.61			
	5th Km	US E			Km.	7.99			
	6th Km		N.	(عوري	Km.	7.84			
	7th Km				Km.	7.27			
	8th Km		- 6		Km.	7.18			
	9th Km	Fan	ance	Depar	Km.	6.72			
	10th Km 11th Km & subsequent Kms				Km. Km.	6.26 4.55			
	 v) 8" (200 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 				30 M 30 M 30 M 300 M Km Km Km	32.45 6.00 3.70 36.45 59.69 28.21 21.63 15.08 13.99			
	6th Km				Km	13.74			
	7th Km				Km	12.77			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	·				Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	12.62			
	9th Km				Km	11.81			
	10th Km 11th Km & subsequent Kms vi) 10'' (250 mm) i/d pipes:-				Km Km	10.95 7.95			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	50.30 9.25 5.75 56.50 92.53 43.73 33.52			
	4th Km			S	Km	23.37			
	5th Km	- h			Km	21.67			
	6th Km	ŝ	0.5		Km	21.29			
	7th Km	185	See.		Km	19.77			
	8th Km	1		Z	Km	19.54			
	9th Km			N.S.	Km	18.29			
	10th Km 11th Km & subsequent Kms	T	nance	Depar	Km Km	17.01 12.44			
	vii) 12" (300 mm) i/d pipes:-								
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	70.80 13.05 8.10 79.55 130.25 61.55 47.21			
	4th Km				Km	32.92			
	5th Km				Km	30.53			
	6th Km				Km	29.99			
	7th Km				Km	27.84			
	8th Km				Km	27.52			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	25.75	composite		
					T CHI				
	10th Km 11th Km & subsequent Kms				Km Km	23.91 17.47			
	viii) 14" (350 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	92.20			
	2nd chain (2nd 30 m)				30 M	17.00			
	3rd to 10th chain (60 to 300 m)				30 M	10.55			
	1000 to 3000 ft. (300 to 900 m)				300 M	103.55			
	1st Km				Km Km	169.55			
	2nd Km 3rd Km				Km Km	80.10 61.42			
	Sru Kili				KIII	01.42			
	4th Km				Km	42.81			
	5th Km		/ .		Km	39.69			
	6th Km	法			Km	39.00			
	7th Km	8			Km	36.22			
	8th Km	133	K		Km	35.81			
	9th Km	1			Km	33.53			
	10th Km		-0-7	200	Km	31.21			
	11th Km & subsequent Kms		nance	Damer	Km	22.80			
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-		26-2016-2,-27		r 22 0. 07 2 0- 0r				
	i) 2'' (50 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	4.65			
	2nd chain (2nd 30 m)				30 M	0.85			
	3rd to 10th chain (60 to 300 m)				30 M	0.55			
	1000 to 3000 ft. (300 to 900 m)				300 M	5.25			
	1st Km				Km	8.58			
	2nd Km				Km	4.06			
	3rd Km				Km	3.12			
	4th Km				Km	2.16			
	5th Km				Km	1.99			
	6th Km				Km	1.96			
	7th Km				Km	1.85			
	8th Km				Km	1.81			

	-	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.		Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.						Unit of M/ment	Labour	Composite	No.	
						WI/IIIent	Labour	Composite		
		9th Km				Km	1.70			
		10Km				Km	1.57			
		11th Km & subsequent Kms				Km	1.17			
	ii)	2½" (63 mm) i/d pipes:-				30 M	7.25			
		1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	7.25 1.35			
		3rd to 10th chain (60 to 300 m)				30 M	0.85			
		1000 to 3000 ft. (300 to 900 m)				300 M	8.15			
		1st Km 2nd Km				Km Km	13.36 6.34			
		3rd Km				Km	4.88			
		4th Km			6	Km	3.41			
		5th Km		/ .		Km	3.16			
		6th Km	見	SAU.		Km	3.11			
		7th Km	8			Km	2.90			
				100	61	Km				
		8th Km	1			1000	2.67			
		9th Km		n Sta	X P	Km	2.58			
		10Km 11th Km & subsequent Kms	054	nance	Depar	Km Km	2.41 1.82			
	iii)	3" (75 mm) i/d pipes:-	12. 8	22.2832.2.8>	anopros	-352.032.6				
		1st chain (1st 30 m)				30 M	10.05			
		2nd chain (2nd 30 m)				30 M	1.85			
		3rd to 10th chain (60 to 300 m)				30 M	1.15			
		1000 to 3000 ft. (300 to 900 m) 1st Km				300 M Km	11.30 18.52			
		2nd Km				Km	8.76			
		3rd Km				Km	6.72			
		4th Km				Km	4.69			
		5th Km				Km	4.37			
		6th Km				Km	4.29			
		7th Km				Km	3.97			
		8th Km				Km	3.93			
		9th Km				Km	3.58			
		10th Km				Km	3.32			

		MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.		Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.						Unit of M/ment	Labour	Composite	No.	
		11th Km & subsequent Kms				Km	2.51			
	iv)	4'' (100 mm) i/d pipes:-								
		1st chain (1st 30 m)				30 M	16.65			
		2nd chain (2nd 30 m)				30 M	3.05			
		3rd to 10th chain (60 to 300 m)				30 M	1.90			
		1000 to 3000 ft. (300 to 900 m)				300 M	18.70			
		1st Km				Km	30.64			
		2nd Km 3rd Km				Km Km	14.47 11.09			
						KIII	11.09			
		4th Km				Km	7.73			
		5th Km		11 PT 110 T		Km	7.18			
		6th Km		/ >	()	Km	7.05			
		7th Km				Km	6.62			
		8th Km	184	رم. نور مار		Km	6.45			
		9th Km		1		Km	6.04			
		10th Km	E.		22	Km	5.56			
		11th Km & subsequent Kms	1		6/2	Km	4.22			
	v)	5" (125 mm) i/d pipes:-		-2-7	200					
		1st chain (1st 30 m)	T	nance	Devar	30 M	24.90			
		2nd chain (2nd 30 m)				30 M	4.60			
		3rd to 10th chain (60 to 300 m)				30 M	2.85			
		1000 to 3000 ft. (300 to 900 m)				300 M	27.95			
		1st Km				Km	45.80			
		2nd Km 3rd Km				Km Km	21.64 16.60			
		Sid Kill				Kill	10.00			
		4th Km				Km	11.57			
		5th Km				Km	10.72			
		6th Km				Km	10.53			
		7th Km				Km	9.78			
		8th Km				Km	9.67			
		9th Km				Km	9.06			
		10th Km				Km	8.31			
		11th Km & subsequent Kms				Km	6.23			
	vi)	6" (150 mm) i/d pipes:-								
L	I									1

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 2	2012 TO 31	st JULY, 201	2) TEH:NO	WSHEHR	A, SOAN VA	LLEY K	HUSHAB
Sr.	Description					e (Metric Sy	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m)				30 M	35.85			
	2nd chain (2nd 30 m)				30 M	6.60			
	3rd to 10th chain (60 to 300 m)				30 M	4.10			
	1000 to 3000 ft. (300 to 900 m)				300 M	40.30			
	1st Km				Km	65.96			
	2nd Km				Km	31.16			
	3rd Km				Km	23.91			
	4th Km				Km	16.67			
	5th Km				Km	15.45			
	6th Km				Km	15.18			
	7th Km				Km	14.10			
	8th Km				Km	13.94			
	9th Km			~	Km	13.04			
	10th Km		/ ^		Km	12.10			
	11th Km & subsequent Kms		/ `		Km	8.93			
	nd shunting loaded Railway wagons or				1.				
true	cks:-	100			- W.				
a)	upto ¼ mile / ¼ Km				Each	139.45			
b)	upto ¹ / ₂ mile / ¹ / ₂ Km		- course		No	252.40			
c)	upto ¾ mile / ¾ Km	205	5.0	67	122	340.80			
d)	upto 1 (1.6 Km) mile	100	in the first sector			405.50			
e)	2nd mile and subsequent miles/	-0	100		Each				
	2nd and subsequent kilometres			19 - 19 - 19 - 19 - 19 - 19 - 19 - 19 -	No/Km	253.80			
23 Ha	nd shunting empty Railway wagons or trucks.								
a)	upto ¼ mile / ¼ Km	Fr	nance	Depart	Each	80.90			
a) b)	upto $\frac{1}{2}$ mile / $\frac{1}{2}$ Km				No.	134.00			
c)	upto ³ / ₄ mile / ³ / ₄ Km				"	176.70			
d)	upto 1 mile / 1 Km				"	212.15			
e)	2nd mile and subsequent miles/				Each				
Ĺ	2nd and subsequent kilometres				No/Km	124.65			

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

Sr.	Description	R	ate (British Sy	vstem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laoding or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	316.80		cu.m	111.90			
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-			*					
	a) Bricks 10" (250 mm) size.	1000 Nos.	396.00	0	1000 Nos.	396.00			
	b) Bricks 9" (225 mm) or smaller size.	ditto	316.80		ditto	316.80			
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	396.00	مربع من برا مربع من برا	100 Bags	396.00			
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	38.00	de la compañía de la comp	100 Nos.	38.00			
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	237.60		100 Kg	6.35			
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	190.10		Per Tonne	187.10			
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	23.75		Each	23.75			
8	Loading or unloading packages of all sorts, upto one Cwt (50 Kg).	Each	11.90		Each	11.90			Except cement in jute or paper bags.
9	Loading or unloading sleepers other than wooden, including stacking lead within one chain:-								
	a) Broad gauge sleepers	100 Nos.	792.00		100 Nos.	792.00			
	b) Metre gauge and narrow gauge sleepers.	ditto	396.00		ditto	396.00			
0	Loading or unloading timber logs or timber for shuttering, into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Per Ton	99.00		Per Tonne	97.45			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	R	ate (British Sy	vstem)	Ra	ate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	950.4		100 Kg	25.45						
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	158.40		Per Tonne	155.90						
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	117.20		cu.m	41.40						
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	152.05		cu.m	53.70						
15	Unloading oil, bitumen tar, etc.			*)								
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	396.00		100 litres	8.70						
	b) Crude oil (drained by gravity).	1000 Gallon	396.00		100 litres	8.70						
	c) Crude oil materials from railway wagons.	100 Cft.	50.70	لطومت بخل	cu.m	17.90						
	 Fuel oil from tank into empty drums, including stacking within one chain (30 m). 	Per Ton	140.80	X.C	Per Tonne	138.60						
	e) Petrol (2 gallon tin)	100 Nos.	199.60		100 Nos.	199.60			The rate includes checking and weighing the tins.			
16	 f) Kerosine oil (4 gallon tin) Removing and stacking within one chain (30 m) lead: 	100 Nos.	396.00		100 Nos.	396.00						
	 Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc. 	100 Cft.	158.40		cu.m	55.95						
	b) Bricks.	1000 Nos.	422.40		1000 Nos.	422.40						
	c) Broad gauge wooden sleepers.	100 Nos.	253.45		100 Nos.	253.45						
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	150.85		100 Nos.	150.85						
	e) Rails girders, pipes, cement etc.	Per Ton	70.40		Per Tonne	69.30						
	f) Bridge and crossing timbers, etc.	100 No.	844.80		100 No.	844.80						
17	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	158.40		Per Tonne	155.90						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Sy	vstem)	Ra	te (Metric S	/stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	90.50		Per Tonne	89.10							
19	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	633.60		100 Nos.	633.60							
20	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	301.70		100 Nos.	301.70							
	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	316.80	*)	100 Nos.	316.80							
22	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	166.75		100 Nos.	166.75							
23	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	1267.20		100 Nos.	1267.20							
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	633.60	حکومت پنجا	100 Nos.	633.60							
25	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	95.05	De Co	Per Tonne	93.55							

Finance Department

3. EARTHWORK (EXCAVATION & EMBANKMENT)

1 Special allowances for the hardness, wetness and slush:-

The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.

2 Deduction for shrinkage from bank measurements:-

The following allowances should be provided for material which is not rammed, or equally consolidated:-

- a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour...... 10%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors

	MRS, BI-ANNUAL PERIOD (1st	EBRUARY, 2	012 10 31St	JULY, 2012)	TEH:NU	WOHERK	A, SUAN VA		JSHAB
Sr.	Description		Rate (British Sys	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
1	Earthwork excavation underessed lead upto a single throw of Kassi, phaorah or shovel:-	- h			ai.			171 to 17.5	
		120			1.23				
	a) In ashes, sand, soft soil or silt clearance.	1000 Cft.	1,188.00		cu.m	41.95			
	b) In ordinary soil.	1000 Cft.	1,425.60	67	cu.m	50.35			
2	Earthwork excavation in ashes, sand and soft soil or silt clearance, undressed lead upto 50 ft (15 metre).	1000 Cft.	1,742.40	Lin	cu.m	61.55		ditto	
3	Bed clearance and dressing slopes of drains to required sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead.	Tu	iance 9	Departs	rent			ditto	The rate is applicable where the earth of the bed to be removed is of the type of ordinary soil. When it is silt or
	a) Excavated material undressed.	1000 Cft.	2,217.60		cu.m	78.35			1 or 2 above, whichever is applicable.
	b) Excavated material dressed in the specified manner.	1000 Cft.	2,397.65		cu.m	84.70			the drains of each category.
4	Borrowpit excavation undressed lead upto 100 ft (30 metre).								
	a) Ordinary soil	1000 Cft.	2,217.60		cu.m	78.35			
	b) Hard soil	1000 Cft.	2,724.50		cu.m	96.25			
5	Earthowrk in ordinary soil for embankments lead upto 100 ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete in all respective								The rate includes hire charges of machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also includes clearing and grubbing where necessary.
	respects:- i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.	2,419.30	3,320.80	cu.m	85.45	117.30		
	ii) 90% maximum modified AASHO dry density.	1000 Cft.	2,419.30	3,205.55	cu.m	85.45	113.20		
	iii) 85% maximum modified AASHO dry density.	1000 Cft.	2,419.30	3,090.30	cu.m	85.45	109.15		
6	Regular excavation dressed.	1000 Cft.	1,629.20		cu.m	57.55		*411-2	
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of							17.1 to 17.5	
	walls and shoring to protect existing works, shuttering and								<u> </u>

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOA							RA, SOAN VA	LLEY KHU	JSHAB
Sr.	Description	I	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.	Description	Unit of	· · ·		Unit of	,	. ,	No.	iteliidi k5
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	timbering the trenches, dressed to designed level and								
	dimensions, trimming, removal of surface water from								
	trenches, back filling and surplus excavated material								
	disposed of and dressed within 50 ft. (15 m) lead:-								
	i) ordinary	1000 Cft.	2,769.90	2,840.55	cu.m	97.85	100.35		
	ii) hard	1000 Cft.	3,276.75	3,347.40	cu.m	115.75	118.25		
	iii) very hard	1000 Cft.	3,815.35	3,886.00	cu.m	134.75	137.25		
	iv) gravel & shingle	1000 Cft.	6,423.65	6,494.30	cu.m	226.90	229.40		
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to							ditto	
	10.0 ft. (3.0 mm) depth for storm water channels, drains,								
	sullage drains in open areas, roads, streets, lanes, including								
	under pinning of walls and shoring to protect existing works,		/ *						
	shuttering and timbering the trenches, dressed to designed	1	· · · · · · · · · · · · · · · · · · ·						
	level and dimensions, trimming, removal of surface water	1							
	from trenches, back filling and surplus excavated material	del			Luis -				
	disposed of and dressed within 100 ft. (30 m) lead:-	187 6		2020 ¹⁰	1.26				
	i) ordinary	1000 Cft.	3,020.15	3,160.70	cu.m	106.65	111.65		
	ii) hard	1000 Cft.	3,527.05	3,667.60	cu.m	124.60	129.55		
	iii) very hard	1000 Cft.	4,065.60	4,206.15	cu.m	143.60	148.55		
	iv) gravel & shingle	1000 Cft.	6,990.70	7,131.25	cu.m	246.90	251.90		
9	Excavation in shingle or gravel formation and rock, not	~~			er			17.1 to 17.5	
Í	requiring blasting, undressed lead upto 100 ft (30 m).		- 0					17.1 10 17.5	
	i) Dry	1000 Cft.	6,019.20	Phase and the second second	cu.m	212.60			
	ii) Wet	1000 Cft.	6,969.60	usp <u>a</u> rn	cu.m	246.15			
	iii) In flowing water	1000 Cft.	8,870.40		cu.m	313.30			
10									
10	Earthwork excavation in irrigation channels, drains, etc. to							1.4	
	designed section, grades and profiles, excavated material							ditto	
	disposed off and dressed within 50 ft. (15 m) lead:-								
	i) ordinary	1000 Cft.	2,544.95		cu.m	89.90			
	ii) hard	1000 Cft.	3,051.85		cu.m	107.80			
	iii) very hard	1000 Cft.	3,590.40		cu.m	126.80			
	iv) gravel & shingle	1000 Cft.	6,357.10		cu.m	224.55			
11	Excavation in rock dressed to designed section, grades and								
	profiles, excavated material disposed off within 100 ft. (30 m)							17.1 to 17.5	Tools and plants shall be the liability
	and lift upto 5'-0" (1.5 m).								of the contractor.
	a) Soft rock, slate, shale, schist laterite work, with pick and	1000 Cft.	6,061.45		cu.m	214.10			
	crow bar.	1000 CA	0 401 90	10.077.00		225.25	255 50		
	b) Medium hard rock, requiring occasional blasting.	1000 Cft.	9,491.80	10,067.80	cu.m	335.25	355.60		
12	a) Excavation in hard rock requiring blasting and disposal								
1	of excavated material (blasted material) upto 50 ft. (15							17.1 to 17.5	1) Tools and plants required shall be
1	m) lead, (including dressing and levelling to designed								the liability of the Contractor
1	section, etc. complete).								
1		1000 00				202.0-	222.13		2) Reduce the rate by 8% if the
L	i) Grade I	1000 Cft.	5,720.90	6,296.90	cu.m	202.05	222.40		excavated section is not dressed or

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	012 TO 31st	JULY, 2012)	TEH:NC	WSHEHF	RA, SOAN VA		USHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	ii) Grade II iii) Grade III iv) Grade IV v) Grade V vi) Grade V	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	6,204.00 7,405.20 8,210.40 9,086.90 9,733.70	7,164.00 8,557.20 9,554.40 10,622.90 11,461.70	cu.m cu.m cu.m cu.m	219.15 261.55 290.00 320.95 343.80	253.05 302.25 337.45 375.20 404.85		levelled to designed section.
	 b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50 ft. (15 m) lead (including dressing and levelling to designed section, etc. complete):- 							17.1 to 17.5	1) Tools and plants required shall be the liability of the contractor.
	 i) Grade I ii) Grade II iii) Grade III iv) Grade IV v) Grade V vi) Grade VI 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	11,441.75 12,408.00 14,810.40 16,420.80 18,173.75 19,467.35	12,593.75 14,328.00 17,114.40 19,108.80 21,245.75 22,923.35	cu.m cu.m cu.m cu.m cu.m	404.10 438.25 523.10 580.00 641.90 687.60	444.80 506.05 604.50 674.90 750.40 809.65		2) Reduce the rate by 8% if the excavated section is not dressed or levelled to designed section.
13	 Rehandling of earthwork: a) Lead upto a single throw of Kassi, phaorah or shovel b) Upto a lead of 50 ft. (15 m). 	1000 Cft. 1000 Cft.	792.00 1,108.80		cu.m cu.m	27.95 39.15		ditto	
14	Rehandling of gravel work or excavated rock, lead upto 50 ft.(15 m)	1000 Cft.	3,168.00	Departs	cu.m	111.90		17.1 to 17.5	
15	Filling, watering and ramming earth under floors:-							ditto	
	 i) with surplus earth from foundation, etc. ii) with new earth excavated from outside, lead upto one chain (30 m). 	1000 Cft. 1000 Cft.	1,594.55 3,087.75		cu.m cu.m	56.30 109.05			
16	 Extra for every 50 ft. (15 m) additional lead or part thereof :- i) for earhtwork soft, ordinary, hard and very hard. ii) for gravel, shingle or rock. 	1000 Cft. 1000 Cft.	26.90 31.30		cu.m cu.m	0.95 1.10			This rate shall be applicable upto 1000 ft. total distance, including the lead covered in the item of earthwork
17	Transportation of earth all types when the total distance, including the lead covered in the item of work, is more than 1000 ft. (300 m)								This rate will be paid inaddition to the rate of earthwork, without deducting the lead covered in the item of
	 a) upto ¼ mile (400 m). b) for every 330 ft. (100 m) additional lead or part thereof, beyond ¼ mile (400 m) upto one mile. (1.6 Km.) 	1000 Cft. 1000 Cft.	1,278.80 96.95		cu.m	45.15 3.40			earthwork
	 c) for every ¼ mile (400 m) additional lead or part thereof, beyond one mile (1.6 Km.) upto 5 mile (8 Km). d) for every ½ mile (800 m) additional lead 	1000 Cft.	152.00		cu.m	5.35			
	or part thereof, beyond 5 miles (8 Km).	1000 Cft.	133.95		cu.m	4.75			
18	Dressing and levelling of earhtwork to designed section, etc. complete:-							17.10 to 17.5	

	MRS, BI-ANNUAL PERIOD (1st FEBR	12) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB							
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.	•	Unit of			Unit of			No.	
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	a) Ashes, sand, silt or soft soil.	1000 Cft.	103.50		cu.m	3.65			
	b) Ordinary or hard soil.	1000 Cft. 1000 Cft.	201.70 475.20		cu.m	7.10 16.80			
	 c) Gravel work or soft rock not requiring blasting. 	1000 Cit.	475.20		cu.m	10.80			
	o noting.								
19	Dowel dressing.	Per Chain	94.60		Metre	3.10		ditto	This rate is in addition to payment for dressed earhtwork.
20	a) Dressing slopes of banks or ground surface.	100Sft.	42.25		sq.m	4.55		ditto	To be paid only when exclusively dressing is done and no earthwork is
									carried out in embankment or cutting.
	b) Dressing of earthwork (done by machinery or otherwise	100Sft.	75.10) -	sq.m	8.10			i) The surface area dressed is to be
	and left undressed) to designed section.	/	1900						taken for measurement.
		del			Luis -				ii) The item is applicable where the
		181			- 22				dressing is done by the contractor other than the one who executed the
		- 199			Sec.				work.
21	Excavation in foundation of building, bridges and other	1498	Carlie	50 /	1434				
	structures, including dagbelling, dressing, refilling around	1	11	- 100				17.1 to 17.5	
	structure with excavated earth, watering and rammiing lead upto one chain (30 m) and lift upto 5 ft. (1.5 m)	~Q.		8 4 ²⁹	<i>2</i>				
	a) in sand, ashes or loose soil	1000 Cft.	2,861.75	<u> </u>	cu.m	101.10			
	b) in ordinary soil.	1000 Cft.	3,342.25	Devisete	cu.m	118.05			
22	 c) in hard soil or soft murum. Cutting hard rock such as granite, ballast, hard lime stone or 	1000 Cft.	3,740.90	25 475 05	cu.m	132.15 813.30		17.1 to 17.5	Tools and plants required shall be the
22	sand stone, etc. with chisels and hammers, for small	1000 Cft.	23,026.10	25,475.95	cu.m	815.50	899.80		Tools and plants required shall be the liability of the contractor.
	foundations.								
23	Extra for excavation requiring shoring.	1000 Cft.	399.95	636.50	cu.m	14.15	22.50	17.1 to 17.5	Composite rate includes materials,
									i.e. plank, etc.
24	Compaction of earthwork (soft, ordinary or hard soil) :-							ditto	
	 Mixing, moistening earth to optimum moisture content in layers for compaction, etc. complete. 	1000 Cft.	378.60		cu.m	13.35			
	 Compaction by rolling with animal driven roller/hand rammed: 								
	i) soft or sandy soil	1000 Cft.	475.20		cu.m	16.80			1. 771 / 1 / 1 / 1 / 1
	ii) ordinary soil	1000 Cft.	554.40		cu.m	19.60			 The rate does not include hire charges of the roller. Roller to be 'supplied by
	iii) hard soil	1000 Cft.	633.60		cu.m	22.40			Government
	iv) admixture of shingle	1000 Cft.	712.80		cu.m	25.20			
	c) Ramming earthwork (all types of soil).	1000 Cft.	475.20		cu.m	16.80			

	MRS, BI-ANNUAL PERIOD (1st FEBR	JULY, 2012)	012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB						
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	d) Ramming earhtwork behind retaining walls.	1000 Cft.	633.60		cu.m	22.40			
	Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture content in layers, etc. complete:							17.1 (a) *411-5 and 202-3	The rate also includes hire charges of machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.
	i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.		901.50	cu.m	-	31.85		
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		786.25	cu.m	-	27.75		
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.	- ×	671.00	cu.m	-	23.70		
26	Extra for wet earthwork.	1000 Cft.	1,108.80	- \	cu.m	39.15	-	17.1 to 17.5	That will support a man's weight.
27	Extra for slush or Daldal including dewatering.	1000 Cft.	2,534.40		cu.m	89.50	-	17.1 to 17.5	That will not support a man's weight.
28	Extra for puddling.	1000 Cft.	1,980.00		cu.m	69.95	-	ditto	
	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	300.95		Metre	9.85	-	ditto	
	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.(15 m).	1000 Cft.	2,851.20	Departs	cu.m	100.70		17.1 to 17.5	
31	Dag bailing 3" (75 mm) deep.	Per mile	1,209.90		Per Km	751.95		ditto	Dag bailing for layout of borrow pit, to be done by contractors at their own cost.
	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	528.00		sq.m	56.80		ditto	
33	Berm cutting:-							17.1 to 17.5	
	 a) lead upto a single throw of Kassi, phaora or shovel (without dressing). 	1000 Cft.	1,425.60		cu.m	50.35			
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	2,544.95		cu.m	89.90			
34	Berm trimming both sides of channels:-							17.1 to 17.5	
	a) upto 3 ¹ / ₂ ft. (1.06 m) depth.	Per Mile	3,713.60		Per Km.	2321.00			
	 b) exceeding 3¹/₂ ft. to 5 ft. (1.06 to 1.5 m) depth. c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth 	Per Mile Per Mile	5,183.20 8,096.00		Per Km. Per Km.	3239.50 5060.00			
35	Ploughing and levelling borrowpits.							ditto	Area ploughed to be measured.
	 i) upto 3 ft. (0.9 m) depth. ii) above 3 ft. (0.9 m) depth. 	Per Acre Per Acre	792.00 1,584.00		Per Hect. Per Hect.	1957.05 3914.15			

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	012 TO 31st	JULY, 2012)	2) TEH:NOWSHEHRA, SOAN VALI					
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks	
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.		
		Wi/ment	Labour	Composite	wi/ment	Labour	Composite			
36	Making boundary or service roads, including dag-belling, levelling and dressing:							ditto		
	i) in unploughed land:									
	 a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide. 	Per Chain Per Chain	400.40 536.80		Metre Metre	13.15 17.60				
	ii) in ploughed land:									
	 a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide. 	Per Chain Per Chain	412.85 549.25	1	Metre Metre	13.55 18.00				
37	Earthwork by boats, including hire of boats:-	. /	1000					17.1 to 17.5	For ordinary soil.	
	 i) Digging and loading into boats, upto 50 ft. (15 m) lead. ii) Carriage by boats upto 10 chains (300 m). iii) Extra for every additional one chain (30 m) or part thereof beyond 10 chains (300 m). 	1000 Cft. 1000 Cft. 1000 Cft.	2,376.00 598.40 63.35		cu.m cu.m cu.m	83.90 21.15 2.25	 			
	iv) Unloading earth from boats.	1000 Cft.	1,108.80		cu.m	39.15				
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	950.40	S. G. S.	cu.m	33.55		17.1 to 17.5		
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	2,217.60	Dep <u>a</u> rts	cu.m	78.35		17.1 to 17.5		
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	1,782.00		cu.m	62.95		ditto		
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	308.50	328.50	cu.m	108.95	116.05	ditto	The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.	
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface								The rate does not include back filling after laying of sewer, which is payable separately.	
	 water, in all types of soil except shingle, gravel and rock:- i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth iii) above 15.0 ft. (4.5 m) depth 	1000 Cft. 1000 Cft. 1000 Cft.	2,580.05 4,376.45 5,643.65	2,927.60 4,892.90 6,160.10	cu.m cu.m cu.m	91.15 154.60 199.35	103.40 172.80 217.60		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.	
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to							17.1 to 17.5 **13.3 &	The rate does not include back filling after laying of sewer, which is payable	

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	012 TO 31st	JULY, 2012)	TEH:NO	WSHEHF	RA, SOAN VA		JSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:							13.5	separately.
	 i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL. ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL. iii) Exceeding 8 ft. (2.4 m) depth below SSWL. 	1000 Cft. 1000 Cft. 1000 Cft.	3,668.50 4,586.25 6,879.40	6,122.05 7,781.85 10,347.95	cu.m cu.m cu.m	129.55 162.00 243.00	216.25 274.85 365.50		
	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	2,381.30	-	cu.m	84.10		17.1 to 17.5 **8.1	The rate does not include back filling after laying of pipe line, which is payable separately.
45	Cutting and removing trees within a distance of 100 ft. (30 m)	/	·						
	 a) upto 2¹/₂ ft. (760 mm) girth. b) above 2¹/₂ ft. to 6 ft. (760 to 1800 mm) girth. 	Each Each	458.35 895.95		Each Each	458.35 895.95			
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	594.00		Each	594.00			
47	Jungle clearance and removing within 100 ft. (30 m).		S.S.S.	9. Erro					
	a) light b) thick	1000 Sft. 1000 Sft.	79.20 158.40	Dep <u>ia</u> rts	sq.m sq.m	0.85 1.70			
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	38.00		sq.m	4.10			
49	Ploughing 3 times.	Per Acre	321.75		Per Hect.	795.05			
50	Levelling, dressing and making lawns.	100Sft.	158.40		sq.m	17.05			
51	Turfing lawns (excluding cost of turf).	100Sft.	132.00		sq.m	14.20			
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry,wet slush,daldal and under water) including its disposal and prepartion of working pad for operation of machinery. (Rates includes 100 ft lead)	1000 Cft.		2028.00	cu.m		71.65		
	(Nates includes 100 ft read)			2028.00	cu.III		/1.05		

* Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 ** Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, BI-ANNUAL PERIOD (1st F	EBRUAF	RY, 2012 TO	31st JULY, 2	2012) TEI	H:NOWSH	HEHRA, SOA	N VALLE	(KHUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Stone Work								
1	Dismantling dry stone masonry.	100Cft.	269.30		cu.m	95.10		18.1	
2	Dismantling stone masonry in mud mortar.	100Cft.	396.00		cu.m	139.85		ditto	
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	950.40	Č	cu.m	335.70		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.
4	a) Dismantling dry stone or spawl pitching.	100Cft.	475.20		cu.m	167.85		ditto	
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	601.90	1. 6	cu.m	212.60		ditto	
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	792.00		cu.m	279.75		ditto	
6	Dismantling stone pitching, cement or lime grouted.	100Cft.	1,267.20		cu.m	447.60		ditto	
7	Dismantling stone in crates:	-	e saarae	e Wepa	TIME	nt			
	a) wooden crates	100Cft.	633.60		cu.m	223.80			
	b) wire crates	ditto	792.00		ditto	279.75			
8	Dismantling stone ware drain including base concrete.	100Cft.	443.50		cu.m	156.65		ditto	
	Brick Work								
9	Dismantling mud/pise walling.	100Cft.	158.40		cu.m	55.95		18.1	
10	Dismantling sun dried brick masonry.	100Cft.	396.00		cu.m	139.85		ditto	
11	Dismantling dry brick masonry.	100Cft.	269.30		cu.m	95.10		ditto	
12	Dismantling brick work in mud mortar.	100Cft.	554.40		cu.m	195.80		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th
13	Dismantling brick work in lime or cement mortar.	100Cft.	1,346.40		cu.m	475.55		ditto	and subsequent floors respectively against item No. 12, 13, 14 & 15.

	MRS, BI-ANNUAL PERIOD (1st F	N VALLEY	(KHUSHAB						
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Dismantling cement block masonry.	100Cft.	1,188.00		cu.m	419.60		ditto	
15	Dismantling Dhajji walling.	100Cft.	316.80		cu.m	111.90		ditto	
	Concrete								
16	Dismantling mud concrete.	100Cft.	633.60		cu.m	223.80		ditto	
17	Dismantling lime concrete.	100Cft.	871.20		cu.m	307.70			Add extra 13%, 32% and 51% on
18	Dismantling lime or cement concrete, under water.	100Cft.	3,326.40		cu.m	1174.90			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 17, 19 & 20.
19	 a) Dismantling cement concrete plain 1:4:8. 	100Cft.	1,742.40	*)	cu.m	615.40		ditto	
	b) Dismantling cement concrete plain	ditto	2,851.20		ditto	1007.05			
	 1:3:6. c) Dismantling cement concrete 1:2:4 plain. d) Dismantling cement concrete with brick 	ditto ditto	3,484.80 950.40		ditto ditto	1230.85 335.70			
	 aggregate. Dismantling D.P.C. of cement concrete 1½" thick (40 mm) and clearing the site. 	ditto	475.20	فكومت پنجا ا	ditto	167.85			
20	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100Cft.	5,702.40	e Depa	cu.m	2014.10		ditto	
	Roofing								
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or ballies.	100Sft.	190.10		sq.m	20.45		18.1	
22	a) Dismantling 1st class tile roofing.	100Sft.	475.20		sq.m	51.15			Add extra 13%, 32 and 51% on
	b) Dismantling 2nd class tile roofing.	100Sft.	396.00		sq.m	42.60			labour rate only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 22, 25, 26 and 28.
23	Dismantling from any height, asbestos sheets and ridge coping.	100Sft.	240.25		sq.m	25.85		18.1	
24	 Dismantling roof of wooden planks and battens, from any height. 	100Sft.	193.25		sq.m	20.8		ditto	
	b) Dismantling wooden ceiling above 20' (6.0 m) height	100Sft.	769.80		sq.m	82.85		ditto	

	MRS, BI-ANNUAL PERIOD (1st	FEBRUAF	RY, 2012 TO	31st JULY, 2	2012) TE	H:NOWSI	HEHRA, SOA	N VALLE	KHUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in difficult position, including lifting with care and special scaffolding along live electric wires and with machines underneath.								
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	633.60		sq.m	68.20		ditto	
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	792.00		sq.m	85.20		ditto	
27	 Stripping and stacking slate or tiles from the truss roofing. 	100Sft.	396.00		sq.m	42.60			
	b) Stripping and stacking C.I. sheet roof.	ditto	356.10	×	ditto	38.30			
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	411.85		ditto	44.30			
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	633.60	فكومه مدينانا	sq.m	68.20		18.1	
	Flooring				63.				
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	269.30	e Deno	sq.m	29.00		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively
30	Dismantling plank or wooden block flooring, etc.	100Sft.	396.00		sq.m	42.60		ditto	against items No. 29 and 30.
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-								i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.
	 a) 6" to 12" (150 to 300 mm) diameter b) 13" to 24" (325 to 600 mm) diameter c) 25" to 36" (625 to 900 mm) diameter d) Above 36" (Above 900 mm) diameter 	Per Lft Per Lft ditto ditto	11.70 18.05 21.25 30.10		Metre Metre ditto ditto	38.40 59.20 69.70 98.75			ii) Bends, elbows, sluice valves, etc. should not be paid for extra if fixed in the length of pipe line that is being dismantled.
32	a) Removing door with chowkat.	Per	147.50		Per	147.50		18.1	Add extra 13%, 32% and 51% on
	b) Removing windows and sky lights with chowkat.	No. ditto	114.25		No. ditto	114.25			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.

	MRS, BI-ANNUAL PERIOD (1st F	HEHRA, SOA	N VALLEY	KHUSHAB					
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
33	Removing ventilators and wooden sunshade, etc.	Per No.	61.80		Per No.	61.80		ditto	
34	a) Dismantling wooden beams upto 12' (3.65m) length.	Per No.	99.00		Per No.	99.00		ditto	
	 b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length. 	ditto	158.40		ditto	158.40			
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	172.55		sq.m	18.55		ditto	
	b) Dismantling wooden trusses.	100Kg	553.80		%Kg	553.80			
36	Dismantling wooden palisade fencing.	Per Lft.	13.55	2.	Metre	44.45		ditto	
	Iron work			Č)					
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	526.15		%Kg	526.15		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.
38	Dismantling rolled steel beams or iron rails, etc.	100Kg	259.95	فكومت بنجلج	%Kg	259.95		ditto	
39	Dismantling iron latrine.	Per Unit/ 2 Seats	559.70	R.C.	Per Unit/ 2 Seats	559.70		ditto	
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per	11.20	e Depa	Each per cm bore	4.50		ditto	
41	a) Dismantling B.G. water column.	Each	3,984.75		Each	3984.75		ditto	
	b) Dismantling M.G. or N.G. water column.	Each	2,628.45		Each	2628.45		ditto	
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	269.30		Metre	8.85		18.1	
	Miscellaneous								
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	126.70		sq.m	13.65		18.1	
44	Dismantling cloth ceiling and supporting timber.	100Sft.	237.60		sq.m	25.55		ditto	
45	Dismantling and removing road metalling.	100Cft.	633.60		cu.m	223.80		ditto	
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead	100Cft.	845.85		cu.m	298.75		ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(30 metre).												
47	Removing mud plaster from walls.	100Sft.	66.00		sq.m	7.10		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th				
48	Removing cement or lime plaster.	100Sft.	132.00		sq.m	14.20		ditto	and subsequent floors against item No. 47, 48, 49, & 50 respectively				
49	Scraping:-							18.1					
	a) White wash or colour wash.	100Sft.	79.20		sq.m	8.50							
	 Ordinary distemper, oil bound distemper, or paint of wall. 	ditto	237.60		ditto	25.55							
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	855.35	*)	sq.m	92.05		18.1					
51	Scraping boulders.	100Cft.	1,108.80	1000	cu.m	391.65		18.1					
52	Cleaning lime or cement mortar of old stones to be used in masonry.	100Cft.	554.40		cu.m	195.80		18.1					
	Electric Wiring	669	14	فكوم مدينية	7.28								
53	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).	Per point	20.45	20.85	Per point	20.45	20.85						
54	Dismantling plug point and making good damaged surface (building portion).	Per point	17.55	17.85	Per point	17.55	17.85						
55	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-												
	i) on surfaceii) recessed in wall	Per foot Per foot	3.75 8.25	3.80 8.35	P.Mtr P.Mtr	12.30 27.05	12.45 27.40						

5. MORTAR

RS, BI-A	ANNUAL PERIOD (1st FEBRUA	ARY, 2012 TC	31st JULY,	2012) TEH:N	OWSHEHRA	A, SOAN VAL	LEY KHUSH
			Material Required (Ready) M		Dry One C	Material Require Cum Wet (Ready)	d for Mortar
S. No.	Ratio of Mortar	Cement	Lime		Cement	Lime	Sand
		(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.
		Вag	Ctt.	Ctt.	Bag.	Cum	
1	2	3	4	5	6	7	8
1	Cement : Sand						
	1 : 2	33.48		82	11.83		0.82
	1:3	23.11		85	8.16		0.85
	1 : 4	18.37		90	6.49		0.90
	1:5	14.70		90	5.19		0.90
	1 : 6	13.61		100	4.81		1.00
	1:7	11.68		100	4.12		1.00
	1 : 8	10.21		100	3.61		1.00
2	Cement : Lime : Sand						
	1:1:6	12.25	15.0	90	4.33	0.15	0.90
	1 : 1 : 7	10.70	13.1	92	3.78	0.13	0.92
	1:1:8	9.39	11.5	92	3.32	0.12	0.92
	1:1:9	8.52	10.44	94	3.00	0.10	0.94
	1 : 1 : 10	7.67	9.4	94	2.71	0.09	0.94
	1:2:8	9.19	22.5	90	3.25	0.23	0.90
	1:2:9	8.16	20.0	90	2.88	0.20	0.90
	1 : 2 : 10	7.67	18.8	94	2.71	0.19	0.94
	1 : 2 : 12	6.39	15.66	94	2.26	0.16	0.94
	1 : 3 : 12	6.26	23.0	92	2.21	0.23	0.92
	1 : 3 : 14	5.47	20.1	94	1.93	0.20	0.94
	1 : 3 : 16	4.82	17.7	94	1.70	0.18	0.94
	1 : ¼ : 3	23.11	7.0	85	8.16	0.07	0.85
3	Lime : Sand	Finan	ce Deru	rtment			
	1 : 2	And a second sec	43	86		0.43	0.86
	1 : 3		31	93		0.31	0.93

5. MORTAR

MP	S, BI-ANNUAL PERIOD (1		2Y 2012 T	0 31st J			OWSHEL	IRA SOA	ΝΥΔΙΙ		HΔR
			Dry Material			<i>2)</i> 1 . N			aterial Requi		
			Wet ((Ready) Mor	tar			one M ³	Wet (Ready) Mortar	
S. No.	Ratio of Mortar	Clay	Lime (Putty)	Sand	Surkhi	Cinder	Clay	Lime (Putty)	Sand	Surkhi	Cind
		Cft.	Cft.	Cft.	Cft.	Cft.	M	M	M	M	M
1	2	3	4	5	6	1	3	4	5	6	7
4	Mud	135					1.35				
5	Lime : Surkhi 2 : 3 1 : 2 1 : 3		49.00 40.75 30.30	- -	73.5 81.5 91.0		- -	0.49 0.41 0.30	- -	0.74 0.82 0.91	- -
6	Lime : Sand : Surkhi 1 : 1 : 1		40.50	40.5	40.5		-	0.41	0.41	0.41	
7	Lime : Cinder 1 : 1		57.0	×)		57.0	-	0.57	-	-	0.57
		Wet material masonry (inclu				38		al required f		32 Cft)	
1	Brick Masonry :a) Mud Mortarb) Cement, Sandc) Cement, Lime (Putty) Sandd) Lime (Putty) Sand	1		Cft Cft	Ì	A.S.		0.35 0.25 0.25 0.25	M ³ M ³ M ³		
2	Stone Masonry : a) Random rubble, uncoursed		Finar	ice D	epari						
	i) Foundation and Plinthii) Superstructureiii) Coursed		45.00 40.00 35.00	Cft Cft Cft				0.45 0.40 0.35	M ³ M ³ M ³		
	b) Ashlar Block in course or Sc	abled masonry	30.00					0.30	M^3		
	c) Ashlar fine masonry	····)	20.00					0.20	M^3		
		1	= 40.8233	Ka							
	(1) Cement	1 (11									
es :	(1) Cement(2) Unslaked lime	1 Cft. 1.7 Cft.		-							
tes :	 (1) Cement (2) Unslaked lime (3) Slaked lime 	1 Cft. 1.7 Cft. 2.5 Cft.	= 40.8233 = 37.3242 = 37.3242	Kg							

6. CONCRETE

Notes 1 Notes (1) Rates for all finished works include the removal of surplus debris, unused material and by products.

2 If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20 [°]	12 TO 31st	JULY, 2012) TEH:N	OWSHEH	IRA, SOAN	VALLE	(KHUSHAB
Sr.	Description	F	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Mud concrete in foundation including watering and ramming, using brick or stone ballast 1 ¹ /2" (40 mm) gauge.	100Cft	1770.50		cu.m	625.35	1106.40		The stone ballast, crushed bajri, round shingle from nallah, or brick ballast may be used according to
2	Dry rammed brick or stone ballast, 1 ¹ / ₂ " to 2"(40 mm to 50 mm) gauge.	100Cft	1188.00	2508.00	cu.m	419.60	885.85		their comparative cheaper rates in various areas of the Province.
3	Cement concrete brick or stone ballast 1 ¹ / ₂ " to 2" (40 mm to 50 mm) gauge, in foundation and plinth:-		S.	E Car				20.1	-do-
	(a) Ratio 1: 3: 6	100Cft	2346.30	10718.70	cu.m	828.70	3785.85		
	(b) Ratio 1: 4: 8	ditto	2346.30	9050.95	"	828.70	3196.80		
	(c) Ratio 1:5:10	ditto	2346.30		"	828.70	2884.15		
	(d) Ratio 1: 6:12	ditto	2346.30		"	828.70	2648.90		
	(e) Ratio 1: 6: 18	ditto	2346.30		"	828.70	2380.80		
	(f) Ratio 1: 7:20	ditto	2346.30	6429.05	"	828.70	2270.75		
4	Extra on item No. 3 above, for sedimentation tank or filter								
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri, round shingle from nallah, or brick
	(a) in bed	100Cft	839.50	-	cu.m	296.50	-		ballast may be used according to their comparative cheaper rates in
	(b) on slope	ditto	1267.20	-	"	447.60	-		various areas of the Province.
5	Cement concrete plain including placing,							20.1	

	MRS, BI-ANNUAL PERIOD (1st FEBRUA	ARY, 201	2 TO 31st	JULY, 2012) TEH:NO	OWSHEH	IRA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British S	ystem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	compacting, finishing and curing complete (including screening and washing of stone aggregate): (a) Ratio 1: 1:2 (b) Ratio 1: 1!½: 1½ (c) Ratio 1: 1½: 3 (d) Ratio 1: 2: 3 (e) Ratio 1: 2: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 4 (g) Ratio 1: 2: 6 (h) Ratio 1: 3: 6 (i) Ratio 1: 4: 8 Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):-	100Cft ditto ditto ditto 100Cft ditto ditto ditto	Labour 3286.80 3286.80 3286.80 3286.80 3286.80 3286.80 3286.80 3286.80	22843.80 22350.60 18495.00 17635.20 15631.45 16159.45 14549.90 13977.60 12410.65	Unit cu.m " " cu.m " "	Labour 1160.90 1160.90 1160.90 1160.90 1160.90 1160.90 1160.90	Composite 8068.45 7894.25 6532.45 6228.75 5521.05 5707.50 5139.05 4936.90 4383.45		 The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring. Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid
	(a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-								extra. 3) This item shall not be applicable to factory made units.
	 (1) Type A (nominal mix 1:1:2) (2) Type B (nominal mix 1: 1¹/₂: 3) (3) (c) Type C (nominal mix 1: 2: 4) (a)(ii) Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 	Per Cft ditto ditto	72.55 72.55 72.55		cu.m "	2562.45 2562.45 2562.45	11088.70 9566.40 8750.55		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20 ⁻	12 TO 31st	JULY, 2012) TEH:N	OWSHEH	IRA, SOAN	VALLE	Y KHUSHAB
Sr.	Description	F	Rate (British Sy	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	5(a) (i) above not requiring form work (i.e. horizental								
	shuttering) complete in all respects:-								
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	42.75	254.60		1509.95	8992.45		
					cu.m				
	(2) Type B (nominal mix 1: 1½: 3)	ditto	42.75	207.85		1509.95	7341.25		
	(3) Type C (nominal mix 1: 2: 4)	ditto	42.75	184.70		1509.95	6523.60		
	(b) Precast reinforced cement concrete and prestressed								
	reinforced cement concrete in columns, beams, lintels, stair								
	cases, shelves, etc.								
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	54.85	285.95	cu.m	1937.30	10099.75		
	(2) Type B (nominal mix 1:1 ¹ / ₂ : 3)	ditto	54.85	242.55		1937.30	8566.85		
	(3) Type C (nominal mix 1: 2: 4)	ditto	54.85	219.75		1937.30	7761.55		
		1.00			114.				
	(c) Erecting and fixing in position, precast cement concrete	- 189 F			18				
	or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m)	Per Cft	26.55	38.20	cu.m	937.75	1349.20		
	including all charges.	12	1.	- 19	49				
		100		11/2	3				
	(d) Add extra labour for R.C. concrete in	Per Cft	11.90	a Carry	cu.m	420.30	-		
	2nd and subsequent storeys.	(Gino)	ance (Bonnot					
		78. 8.8.8	1818-1267 - 28	so pus e					
7	Providing and casting in situ bored reinforced concrete piles							*851-1	Composite rate shall be reduced by
	with type C concrete (nominal mix 1: 2: 4), using 10% extra							to	Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab
	cement in dry mix, and course sand, including all labour and							851-10	sand and local sand respectively is used.
	material (except the cost of steel reinforcement and its								
	labour for bending and laying in position, etc. which will be								
	paid separately, including, screening & washing of shingle								
	and curing:-								
	i) 18 " (450 mm) dia pile	Per Rft	655.65	920.90	Metre	2150.55	3020.55		
	ii) 20" (500 mm) dia pile	Per Rft	731.05	1058.40	Metre	2397.85	3471.55		
	iii) 22" (550 mm) dia pile	Per Rft	851.6	1233.3	Metre	2793.25	4045.2		
	iv) 24" (600 mm) dia pile	Per Rft	986.70	1458.45	Metre	3236.40	4783.75		
8	Fabrication of mild steel reinforcement bar cage for R.C.C.							*851-5	The rate includes wastage, overlaps,
	bored piles, including cutting, bending, laying in position,								etc. but does not apply to the laps and

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 20 [.]	12 TO 31st	JULY, 2012) TEH:N	OWSHEF	IRA, SOAN	VALLE	(KHUSHAB
Sr.	Description	F	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	welding and fastening, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from the bars):-								spiral reinforcement which are specifically shown in the structural / working drawings of piles as per lapping requirements of design.
	(a) plain bars	Per Cwt.	807.85	4224.25	100 kg	1590.25	8315.45		C
	(b) deformed bars	ditto	807.85	5476.30	-	1590.25	10780.10		
9	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):-	/	*					*851.5	The rate includes wastage, overlaps and chairs, etc.
	removal of fust from bars)	1 de F			LU.				
	(a) plain bars	Per Cwt.	202.95	3796.40	100 kg	399.50	7473.25		
	(b) deformed bars	ditto	202.95	5149.40		399.50	10136.60		
10	Precast cement concrete solid or face blocks (1:2:4), including cost of templates.	Per Cft	31.40	144.05	cu.m	1109.05	5087.85	20.2	
11	Precast cement concrete hollow blocks (1: 2: 4), including cost of templates and constructing walls thereof.	Per Cft	ance (70.00	144.45	cu.m	2472.40	5101.95	20.2	
12	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	Per Sft	21.40	40.95	sq.m	230.25	440.60	20.1 to 20.4	
13	Extra labour for laying concrete plain or reinforced:								
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	1267.20	-	cu.m	447.60	-		
	(b) for every additional 10'(3 m) height.	100Cft	792.00	-	cu.m	279.75	-		
14	Extra labour for work of weirs, rail or road bridges, syphons, and concreting in superstructure	100Cft	316.80	-	cu.m	111.90	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRU	JULY, 2012	2) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB						
Sr. No.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
15	Making reinforced cement concrete spout, including fixing in position (2 ¹ / ₂ ' x 6" x5") (760 mmx150 mm x 125 mm)	Each	267.30	404.00	Each	267.30	404.00	20.4	
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement concrete or stone masonry walls and repairing.	Per hole	641.50	-	Each	641.50	-	20.1	
17	Extra labour for skipping concrete in wells.	100Cft	1861.20	-	cu.m	657.40	-	20.1	
18	Nicking concrete surface: (a) Cement concrete surface (b) Lime concrete surface	100Sft ditto	269.30 88.85		sq.m "	29.00 9.55	-		
19	Preparing, watering and ramming surface for laying concrete (for Headworks only):- (a) Horizontal floor (b) Glacis and crest (c) Inverted filters	100Sft ditto ditto	230.00 348.50 106.90		sq.m "	24.75 37.50 11.50	- - -		
20	Fabrication of high tensile steel prestressing cables for prestressed (post tensioned) concrete, including assembling by drawing the H.T. wire through metal spacer plate, inserting in helix core and taping or tying, sheathing in longitudinally welded metal corrugated sheath, positioning , anchorage with male and female set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule, maintaining stressing record and supply the same in the approved proforma to the Engineer-in-charge, making loop at blind end, including all materials required for it, grouting the cable ducts with cement, cutting projected ends and making good recesses, etc.,	100 Kg.	2598.60	28937.10	100 Kg.	2598.60	28937.10	*811-1 to 811-11	The rate includes wastage in cutting and breakage in stressing, etc.
21	complete in all respects. Fabrication of High Tensile steel reinforcement for prestressed (pretension) concrete work, including inserting wire in moulds, providing M.S. shear bars, spacers and lift hooks, male and	100kg	1589.70	27317.50	%kg	1589.70	27317.50		 The rate includes wastage in cutting and breakage in stressing,etc.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20 ⁻	12 TO 31st	JULY, 2012) TEH:N	OWSHEF	IRA, SOAN	VALLE	(KHUSHAB
Sr.	Description	F	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	female anchorage, tie down, struts, stressing cables, maintaining stress record and supply the same in approved proforma to the Engineer-in-charge, cutting wires and projecting ends and making good recesses, etc., complete in all respects.								 Quantity of H. T. wire will form basis of payment. This item shall not be applicable to factory made units.
22	Lifting, transporting and placing precast prestressed concrete B eam, Girder and other members (excluding battens) etc. in Position on the bridge to correct alignment and level, etc. complete		×					*811-1 to 811-11	
23	 i) Beam upto 50 ft. (15 m) length ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length iv) Beam above 100ft. (30m) upto 150ft.(45m) length v) Beam above 150ft. (45m) length Providing and laying foam concrete 3 inch (75 mm) thick, 	100Cft 100Cft 100Cft 100Cft 100Cft 100Cft	18.70	1165.85 1705.47 2180.70 2789.10 3368.45 49.60	cu.m cu.m cu.m cu.m cu.m	201.20	411.80 602.35 770.20 985.10 1189.75 533.70		
	using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,	Fin	ance (Depart.	nent				
24	Providing and fixing 6 in(150 mm). wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-								
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	12.30 9.90	38.80 77.55	Metre Metre	40.35 32.45	127.25 254.35		
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-								

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	12 TO 31st	JULY, 2012	2) TEH:NO	OWSHEH	RA, SOAN	VALLEY	KHUSHAB
Sr.	Description	ŀ	Rate (British S	ystem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) On interior surface (without mastic strip)	Per Rft.	9.00	35.55		29.50	116.60		
	b) On exterior surface (with mastic strip)	ditto	9.00	38.40	"	29.50	125.95		
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on	Per Sft.	8.10	89.50	Sq.m	87.15	963.00		
	expansion joints complete in all respects.				-				
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG.	Per Rft.	3.85	68.20	Metre	12.65	223.70		
	stopper to expansion joint.								
28	Providing embeding 10" (250 mm) wide ¹ / ₄ " (6 mm) thick	Per Rft.	16.85	58.85	Metre	55.25	193.00		
	rubber water stopper in expansion joints of R.C.C. roof	- /	·						
	slab complete in all respects.	1.1-			1.1.				
		188			1.88				
29	Filling expansion joints with bitumen. sand & saw dust in	Per Rft	2.00	17.00	P.Metre/	6.55	55 7 5		
	ratio 1:2:2.	per inch width	2.00	17.00	Per 25 mm Width	6.55	55.75		
		width		Z/A	Widdi				
30	Filling expansion joints with bitumen.	Per Rft.	27.05	2.3.	Metre	88.70	-		
31	Laying asphaltic mixture in expansion joints.	Per Rft.	27.70	Dep <u>art</u>	Metre	90.85	-		Material to be paid on actuals.
32	Providing and fixing theremopore (foamed polythene)								
	sheet in horizontal and vertical expansion joints:								
	a) 1" (25 mm) thick thermopore sheet	Per Sft.	4.30	8.95	Sq.m	46.25	96.30		
	b) $1\frac{1}{2}$ " (40 mm) thick thermopore sheet	ditto	4.30	13.05	"	46.25	140.40		
33	Providing and laying damp proof course of cement concrete								
	1:2: 4(using cement, sand and shingle), including bitumen coating :-								
	(a) with one coat bitumen and one coat polythene sheet								
	500gauge								

	MRS, BI-ANNUAL PERIOD (1st FEBRUA	ARY, 20	12 TO 31st	JULY, 2012) TEH:N	OWSHEF	IRA, SOAN	VALLE	(KHUSHAB
Sr.	Description	I	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 1½" thick (40 mm)	100Sft	860.00		sq.m	92.55	373.55		
	ii) 2" thick (50 mm)	100Sft	860.00	3887.65	sq.m	92.55	418.30		
	iii) 3" thick (75 mm)	100Sft	887.70	4837.45	sq.m	95.50	520.50		
	(b) with 2 coats of bitumen:								
	i) 1½" thick (40 mm)	100Sft	860.00	3849.70	sq.m	92.55	414.25		
	ii) 2" thick (50 mm)	100Sft	860.00	4265.15	sq.m	92.55	458.95		
	iii) 3" thick (75 mm)	100Sft	887.70	5214.95	sq.m	95.50	561.15		
34	Providing and laying damp proof course with cement sand	. /	*****						
	plaster and bitumen coating:-	感日			援				
	(a) with one coat of bitumen and one coat of polythene sheet	1.28			12				
	500 gauge :-		12		2098 B				
	i) Ratio 1: 4		SP	C. Ser					
	a) ¹ ⁄2" thick (13 mm)	100Sft	818.40	2314.95	sq.m	88.05	249.10		
	b) ³ / ₄ " thick (20 mm)	100Sft	818.40	2549.75	sq.m	88.05	274.35		
	ii) Ratio 1:3								
	a) ½ " thick (13 mm)	100Sft	818.40	2388.80	sq.m	88.05	257.05		
	b) ³ / ₄ " thick (20mm)	100Sft	818.40	2636.70	sq.m	88.05	283.70		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	818.40	2480.50	sq.m	88.05	266.90		
	b) ¾ " thick (20 mm)	100Sft	818.40	2823.80	sq.m	88.05	303.85		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	818.40	2550.85	sq.m	88.05	274.45		

	MRS, BI-ANNUAL PERIOD (1st FEBRUA	ARY, 201	12 TO 31st	JULY, 2012) TEH:N	OWSHEF	IRA, SOAN	VALLE	(KHUSHAB
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) ¾" thick (20 mm)	100Sft	818.40	2785.90	sq.m	88.05	299.75		
	ii) Ratio 1:3								
	a) ½ " thick (13 mm)	100Sft	818.40	2625.70	sq.m	88.05	282.55		
	b) ¾ " thick (20 mm)	100Sft	818.40	2873.60	sq.m	88.05	309.20		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	818.40	2810.00	sq.m	88.05	302.35		
	b) ¾ " thick (20 mm)	100Sft	818.40	3179.70	sq.m	88.05	342.15		
35	Providing and laying vertical damp proof course with cement	/	×						
	sand plaster and bitumen coating:-	. /			1.				
		14			1以。				
	(a) with one coat of bitumen and one coat of polythene sheet	123			18.				
	500 gauge:		Sele.	6/) AS				
	i) Ratio 1: 4			Z	1				
	a) ½" thick (13 mm)	100Sft	818.40	2221.90	sq.m	88.05	239.10		
	b) ¾" thick (20 mm)	100Sft	818.40	2457.15	sq.m	88.05	264.40		
	ii) Ratio 1:3			0					
	a) ½ " thick (13 mm)	100Sft	818.40	2296.20	sq.m	88.05	247.05		
	b) ¾ " thick (20 mm)	100Sft	818.40	2544.10	sq.m	88.05	273.75		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	818.40	2480.50	sq.m	88.05	266.90		
	b) ¾ " thick (20 mm)	100Sft	818.40	2850.20	sq.m	88.05	306.70		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4								
	a) ¹ /2" thick (13 mm)	100Sft	818.40	2550.75	sq.m	88.05	274.45		
	b) ³ / ₄ " thick (20 mm)	100Sft	818.40	2785.90	sq.m	88.05	299.75		

KHUSHAB	VALLE	IRA, SOAN	OWSHEF) TEH:N	JULY, 2012	12 TO 31st	Y, 20 1	MRS, BI-ANNUAL PERIOD (1st FEBRU	
Remarks	Spec.	ystem)	te (Metric S	Ra	ystem)	Rate (British S	R		Sr.
	No.	Composite	Labour	Unit	Composite	Labour	Unit		No.
								ii) Ratio 1:3	
			88.05	sq.m		818.40	00Sft	a) ¹ / ₂ " thick (13 mm)	
		309.10	88.05	sq.m	2872.85	818.40	00Sft	b) ¾ " thick (20 mm)	
								iii) Ratio 1:2	
		302.30	88.05	sq.m	2809.45	818.40	00Sft	a) ¹ / ₂ " thick (13 mm)	
		342.05	88.05	sq.m	3178.95	818.40	00Sft	b) ³ / ₄ " thick (20 mm)	
					and the second se				
		-	1388.20	cu.m.	1 - 1	3930.30	00Cft	Grouting concrete between, the grooves of gates, including	36
							- /	shuttering.	
				1.1.			1.L		
		-	15.95	sq.m	-	148.10	00Sft	Chiesel dressing concrete surface on sides of grooves.	37
				1 S.J.			9 8		
		-	454.55	cu.m	67	1287.00	00Cft	Laying and ramming dry ballast or kankar.	38
			45.80	per No.	- 100	45.80	er No.	Hoisting and placing in position R.C.C. shelves.	20
		-	45.80	per No.	of the sea	43.80	er no.	Hoisting and placing in position K.C.C. sherves.	39
					n		gradi	Breaking brick ballast, screening and stacking:-	40
		-	349.65	cu.m	vepan	990.00	00Cft.	(a) 2"(50 mm) ring	
		-	391.65		-	1108.80	ditto	(b) 1½ "(40 mm) ring	
		-	454.55		-	1287.00	ditto	(c) 1" (25 mm) ring	
		-	524.50		-	1485.00	ditto	(d) Jhama ballast ¾"(20 mm) ring	
		229.10	104.00	metre	69.85	31.70	er Rft	Supplying and fixing broken glasses on court yard walls,	41
								including 1:3: 6 cement concrete coping.	
			240.65			000.00	0000		40
-		-	349.65	cu.m.	-	990.00	JUCIT	Crusning stone ballast by machine.	42
crushing within three chains (90 m).									
This does not include the ch for working of crushers, but manual labour for carriageo crusher within three chains and also stacking the produc crushing within three chains		-	349.65	metre	-	31.70 990.00	ver Rft 00Cft	Supplying and fixing broken glasses on court yard walls, including 1:3: 6 cement concrete coping. Crushing stone ballast by machine.	41

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	12 TO 31st	JULY, 2012	VALLEY	KHUSHAB			
Sr.	Description	ŀ	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
43	Breaking stone ballast screened and stacked:-								
	(a) 2" ring (50 mm)	100Cft.	1108.80	-	cu.m.	391.65	-		
	(b) 1½ " ring (40 mm)	ditto	1287.00	-	"	454.55	-		
	(c) 1" ring (25 mm)	ditto	1485.00	-	"	524.50	-		
	d) ½ " ring (13 mm)	ditto	1980.00	-	"	699.35	-		
	(e)1/8" to ¼" ring (3 mm to 6 mm)	ditto	3366.00	-	"	1188.85	-		
44	Screening and stacking stone ballast shingle or bajri, etc.	100Cft.	316.80		cu.m.	111.90	-		
45	Washing ballast, bajri or shingle.	100Cft.	316.80		cu.m.	111.90	-		
46	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2 ¹ / ₂ ' (1.50 m x 0.76 m)	Each	194.05		Each	194.05	-		

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

Finance Department

7. BRICK WORK

1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.

2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4" x4" (200x100x100 mm) nominal.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB

Sr.	Description		Rate (British Sy	(stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Pacca brick work in mud mortar in buildings:							21.1	Masonry of boundary wall to be
								to	considered as masonry other than
	i) in foundation and plinth	100Cft.	1799.40	11956.80	cu.m	635.55	4223.15	21.4	building.
	ii) in ground floor	ditto	2385.50	12542.90	ditto	842.55	4430.15		
				42					The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
2	Add extra labour on item No. 1 for brick work in:-		1 .	9					
	i) first floor	100Cft.	451.45		cu.m	159.45	-		
	ii) second floor	ditto	1037.50		ditto	366.45	-		
	iii) third floor	ditto	1623.60		ditto	573.45	-		
	iv) fourth & subsequent floors	ditto	2637.35	67	ditto	931.50	-		
3	Pacca brick work in mud mortar other than building:-	, A			53			21.1 to 21.4	Same remarks as against item No. 1 above
	i) upto 20 ft. (6.1 m) height	100Cft.	2448.85	12606.25	cu.m	864.95	4452.55		
	ii) extra labour for every 5 ft. (1.5 m)	ditto	451.45	Burner	ditto	159.45	-		
	additional height, or part thereof.	18.	6.72.6.6.9.2.C.65	Depart	- 39%. 65 F.C.				
4	Pacca brick work in foundation and plinth in:-							ditto	Same remarks as against item No. 1 above.
	i) Cement, sand mortar:-								
	Ratio 1:2	100Cft.	2369.65	16776.85	cu.m	836.90	5925.60		
	Ratio 1:3	ditto	2369.65	15785.05	ditto	836.90	5575.30		
	Ratio 1:4	ditto	2369.65	15190.00	ditto	836.90	5365.10		
	Ratio 1:5 Ratio 1:6	ditto	2369.65	14793.25 14495.05	ditto ditto	836.90 836.90	5225.00 5119.65		
	Ratio 1:0	ditto ditto	2369.65 2369.65	14495.05 14300.65	ditto	836.90 836.90	5051.00		
	Ratio 1:7	ditto	2369.65	14128.70	ditto	836.90	4990.25		
	ii) lime, cement sand mortar:-							21.1	The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	2369.65	14656.80	cu.m	836.90	5176.80		
	Ratio 1:1:7	ditto	2369.65	14455.50	ditto	836.90	5105.70		
	Ratio 1:1:8	ditto	2369.65	14292.65	ditto	836.90	5048.15		
	Ratio 1:1:9	ditto	2369.65	14156.10	ditto	836.90	4999.95		
	Ratio 1:1:10	ditto	2369.65	14053.80	ditto	836.90	4963.80		

	MRS, BI-ANNUAL PERIOD (1st FEE	HRA, SOAN	VALLEY K	HUSHAB					
Sr.	Description		Rate (British Sy	(stem)	R	ate (Metric	System)	Spec.	Remarks
No.				,		Ì	. ,	No.	
		Unit	Labour	Composite	Unit	Labour	Composite		
	iii) lime, sand mortar 1:2	100Cft.	2369.65	13558.25	cu.m	836.90	4788.75	ditto	ditto
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to
5								unto	be reduced by 7% and 14%,
	i) cement, sand mortar:-								if 2nd or 3rd class bricks are used.
	Ratio 1:2	100Cft.	3114.15	17521.35	cu.m	1099.90	6188.55		ii) Masonry of boundary wall
	Ratio 1:3	ditto	3114.15	16529.55	ditto	1099.90	5838.25		to be considered as masonry
	Ratio 1:4	ditto	3114.15	15934.45	ditto	1099.90	5628.05		other than building.
	Ratio 1:5	ditto	3114.15	15537.75	ditto	1099.90	5487.95		
	Ratio 1:6	ditto	3114.15	15239.55	ditto	1099.90	5382.60		
	Ratio 1:7	ditto	3114.15	15045.15	ditto	1099.90	5313.95		
	Ratio 1:8	ditto	3114.15	14871.85	ditto	1099.90	5252.75		
	ii) lime, cement, sand mortar:-		1						The rate of lime mortar also
	ii) iiiio, comont, sand mortar.				1.1.				includes grinding of mortar.
	Ratio 1:1:6	100Cft.	3114.15	15401.30	cu.m	1099.90	5439.75		morades grinding of moral.
	Ratio 1:1:7	ditto	3114.15	15201.75	ditto	1099.90	5369.25		
	Ratio 1:1:8	ditto	3114.15	15037.15	ditto	1099.90	5311.10		
	Ratio 1:1:9	ditto	3114.15	14900.60	ditto	1099.90	5262.90		
	Ratio 1:1:10	ditto	3114.15	14798.60		1099.90	5226.85		
				55-10	53				
	iii) lime, sand mortar 1:2	100Cft.	3114.15	14302.75	cu.m	1099.90	5051.75		The rate of lime mortar also includes grinding of mortar.
		02		Depart	Sana Jana	6			includes grinning of mortal.
6	Add extra labour on item No. 5 for brickwork		5.92.66.9 <i>2</i> .C.65	ser a prast	352.65 12.	6-			
	in:-								
	i) first floor	100Cft.	451 45			150.45			
	i) first floor ii) second floor	ditto	451.45 1037.50		cu.m ditto	159.45 366.45	-		
	iii) third floor	ditto	1623.60		ditto	573.45	-		
	iv) fourth & subsequent floors	ditto	2637.35		ditto	931.50	-		
	iv) fourin & subsequent noors	unto	2037.33		unto	951.50	-		
7	Pacca brick work other than building upto 10ft. (3 m)							21.1	i) The composite rate is to be
	height.							to	reduced by 7% and 14%, if 2nd or
								21.5	3rd class bricks are used.
	i) cement, sand mortar:-								ii) Workshops, godowns,, bins,
	Ratio 1:2	100Cft.	2772.00	17179.20	cu.m	979.05	6067.70		house type godowns, reservoirs,
	Ratio 1:2 Ratio 1:3	ditto	2772.00	16187.40	ditto	979.03 979.05	5717.40		filter beds, storage tanks, wells,
	Ratio 1:4	ditto	2772.00	15592.30		979.05	5507.20		screening chambers, collecting
	Ratio 1.4	ditto	2772.00	15195.60		979.05	5367.10		tanks, manholes etc. are to be
	Ratio 1:5	ditto	2772.00	14897.40	ditto	979.05	5261.75		treated as masonry other than
	Ratio 1:7	ditto	2772.00	14703.00	ditto	979.05	5193.10		buildings.
	Ratio 1:8	ditto	2772.00	14531.05	ditto	979.05	5132.35		
L									

	MRS, BI-ANNUAL PERIOD (1st FEE	HRA, SOAN	VALLEY M	KHUSHAB					
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) lime, cement, sand mortar:-								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6 Ratio 1:1:7	100Cft. ditto	2772.00 2772.00	15059.15 14857.85	cu.m ditto	979.05 979.05	5318.90 5247.80		
	Ratio 1:1:8 Ratio 1:1:9 Ratio 1:1:10	ditto ditto ditto	2772.00 2772.00 2772.00	14695.00 14558.40 14456.15	ditto ditto ditto	979.05 979.05 979.05	5190.25 5142.05 5105.90		
	iii) lime, sand mortar 1:2	100Cft.	2772.00	13960.60	cu.m	979.05	4930.90		ditto
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	451.45	-	cu.m	159.45	-		
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	966.25	5-7	cu.m	341.30	-	21.5	
10	Extra for pacca brick work in steining of wells or any other circular masonry.	100Cft.	673.20	1283.30	cu.m	237.75	453.25	21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
11	Extra labour for profile and flared walls.	100Cft.	231.60	and and a second	cu.m	81.80	-		
12	Extra labour for pacca brick work in piers and abutment:-			The second s	53				
	 i) from 10ft. to 20ft. (3 m to 6 m) height ii) above 20 ft. (6 m) height. 	100Cft. 100Cft.	223.05 451.45	Depart	cu.m cu.m	78.80 159.45	-		
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.		2762.40	cu.m		975.70		This item is to be executed only under the written permission of Superintending Engineer.
14	Reinforced brick work in lintel of openings, laid in 1:3 cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	Per Cft.	78.20	216.05	cu.m	2762.65	7630.90		
15	Extra for dressing or chamfering bricks for:-								
	a) special architectural bricksb) all other purposes	100 Nos. ditto	1723.40 861.70	-	% Nos. ditto	1723.40 861.70	-		
16	Perforated pacca brick walling half brick thick, in ground floors:-							21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
<u> </u>	i) mud mortar	100 Sft.	1191.15	3734.25	Sqm.	128.15	401.80	21.7	ora orașo orieko are asea.

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY	, 2012 TO 31	st JULY, 201	2) TEH:	NOWSHE	HRA, SOAN	VALLEY P	(HUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	1560.25	5165.75	sq.m.	167.90	555.85		
	Ratio 1:3	ditto	1560.25	4917.50	ditto	167.90	529.10		
	Ratio 1:4	ditto	1560.25	4769.05	ditto	167.90	513.15		
	Ratio 1:5	ditto	1560.25	4669.85	ditto	167.90	502.50		
	Ratio 1:6	ditto	1560.25	4600.10	ditto	167.90	494.95		
	Ratio 1:7	ditto	1560.25	4546.10	ditto	167.90	489.15		
	Ratio 1:8	ditto	1560.25	4506.30	ditto	167.90	484.90		
	iii) lime, cement sand mortar								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Sft.	1560.25	4635.75	sq.m	167.90	498.80		
	Ratio 1:1:7	100Sft.	1560.25	4584.20	sq.m	167.90	493.25		
	Ratio 1:1:8	100Sft.	1560.25	4546.50	sq.m	167.90	489.20		
	Ratio 1:1:9	100Sft.	1560.25	4509.90	sq.m	167.90	485.25		
	Ratio 1:1:10	100Sft.	1560.25	4488.50	sq.m	167.90	482.95		
	iv) lime, sand mortar 1:2	100Sft.	1560.25	4358.25	sq.m	167.90	468.95		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	- S		الطومت ت	A.S.				
	i) first floor	100Sft.	228.40	and the	sq.m	24.60	_		
	ii) second floor	ditto	516.05		ditto	55.55	_		
	iii) third floor	ditto	814.50		ditto	87.65	-		
	iv) fourth & subsequent floors	ditto	1274.80	Depart	ditto	137.15	-		
18	Perforated pacca brick walling one brick thick, in ground							21.1	The composite rate is to be
10	floor:							to	reduced by 7% and 14%, if 2nd or
	11001.							21.4	3rd class bricks are used.
	i) mud mortar	100Sft.	1655.30	6734.00	sq.m	178.10	724.60	21.4	Sid class blicks are used.
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	2347.50	9551.10	sq.m	252.60	1027.70		
	Ratio 1:3	ditto	2347.50	9055.20	ditto	252.60	974.35		
	Ratio 1:4	ditto	2347.50	8757.65	ditto	252.60	942.30		
	Ratio 1:5	ditto	2347.50	8559.30	ditto	252.60	921.00		
	Ratio 1:6	ditto	2347.50	8419.80	ditto	252.60	905.95		
	Ratio 1:7	ditto	2347.50	8311.40	ditto	252.60	894.30		
	Ratio 1:8	ditto	2347.50	8227.05	ditto	252.60	885.25		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	2347.50	8491.05	sq.m	252.60	913.65		includes grinding of mortar
	Ratio 1:1:7	ditto	2347.50	8387.85	ditto	252.60	902.55		includes grinding of mortai
	Ratio 1:1:8	ditto	2347.50	8309.05	ditto	252.60	894.05		
	Natio 1.1.0	unuo	2347.30	0507.05	uno	252.00	074.03		1

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHA										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	2347.50 2347.50	8240.70 8190.50	ditto ditto	252.60 252.60	886.70 881.30			
	iv) lime, sand mortar 1:2	100Sft.	2347.50	7941.00	sq.m	252.60	854.45		ditto	
19	Add extra labour on item No. 18 for perforated pacca brick work in:-									
	 i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors 	100Sft. ditto ditto ditto	338.60 778.15 1217.70 1978.00		sq.m ditto ditto ditto	119.60 274.85 430.10 698.65	- - -			
20	Fire brick masonry in fireclay mortar:-i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	30.40	490.35	cu.m	1074.20	17318.25	21.1 to 21.2		
	ii) Extra for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	451.45		ditto	159.45	-		A&C No.I dated 2.9.1998	
21	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-				AN ST			21.19		
	 i) 4¹/₂" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart. 	100Sft.	1329.55	7441.35	sq.m	143.05	800.70			
	 ii) 4¹/₂" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	100Sft.	1209.80	6892.75	sq.m	130.20	741.65			
	iii) 3" (75 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	ditto	1042.45	5511.80	ditto	112.15	593.05			
	 iv) 3" (75 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	ditto	834.00	4827.05	ditto	89.75	519.40			
22	Ghilafi work (1 ¹ /2 brick thick wall)	100Cft.	2398.20	7938.60	cu.m	847.05	2803.90	21.18		
23	Dry brick pitching	100Cft.	1465.20	11509.20	cu.m	517.50	4065.05	21.1		
24	Sun dried bricks in mud mortar	100Cft.	1995.85	2919.25	cu.m	704.95	1031.10	21.16		
25	Pise wall (mud walling)	100Cft.	966.25		cu.m	341.30	-	21.17		
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2		
	 i) 3" (75 mm) thick drip course cornice ii) 4¹/₂" (113 mm) thick drip course cornice. iii) 4¹/₂" (113 mm) thick eave brick with back brick. 	Rft. ditto ditto	15.75 17.90 11.70	43.95 88.65 103.35	ditto	51.65 58.70 38.40	144.15 290.75 339.00		correction vide A&C No.I dated 2.9.98	

	MRS, BI-ANNUAL PERIOD (1st FE	HRA, SOAN	VALLEY K	HUSHAB					
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2	
	 i) 1 brick ii) 2 bricks iii) 3 bricks iv) 4 bricks 	Rft. ditto ditto ditto	17.90 26.45 35.30 44.35	31.35 67.45 104.30 143.65	Metre ditto ditto ditto	58.70 86.75 115.80 145.45	102.85 221.25 342.10 471.15		
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	554.40		1,000 Nos	554.40	-		
29	Scraping bricks dismantled from pacca masonry	1,000 Nos	1045.45		1,000 Nos	1045.45	-		
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	132.00	1452.00	cu.m	46.60	512.85		
	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart. First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG hoop iron strips bonding placed at 2.0' (600 mm) apart	Rft.	66.85	120.30	Metre	219.25	394.60		This item is to be executed only under the written permission of the Superintending Engineer.
	 horizontally, and at 1.0' (300 mm) interval vertically. i) 1:3 ii) 1:4 	100Sft. ditto	1209.80 1209.80	8095.00 7857.00	sq.m ditto	130.20 130.20	871.00 845.40		
33	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	35.65		sq.m	383.60	-		
34	Replacing kallar eaten bricks	Each No.	29.05	35.30	Each	29.05	35.30		
35	Repairing corners of bridges and other hydraulic masonry works	Each No.	178.20	246.95	Each	178.20	246.95		
36	Extra labour for drains of bath rooms, etc.	Per Lft.	16.85		Metre	55.25			
37	Maroo corners	Each Corner	107.70		Each Corner	107.70			Payable in addition to brick work

8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- 3 Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st	FEBRUAR	′, 2012 TO 3	1st JULY, 20 ⁻	12) TEH	:NOWSHE	EHRA, SOAN	VALLEY I	KHUSHAB
Sr.	Description]	Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Random, rubble masonry (uncoursed), in foundation and plinth:		E		副際	-		22.10, 22.11	
	 a) dry masonry b) in mud mortar c) in lime, sand mortar 1:2 	100 Cft. 100 Cft. 100 Cft.	2534.40 3168.00 4870.80	3284.40 4063.80 7092.00	cu.m cu.m cu.m	895.15 1118.95 1720.35	1160.05 1435.35 2504.90		
	 d) in cement, sand mortar i) ratio 1:3 ii) ratio 1:4 iii) ratio 1:6 iv) ratio 1:8 	100 Cft. 100 Cft. 100 Cft. 100 Cft.	4870.80 4870.80 4870.80 4870.80 4870.80	10677.90 9785.30 8763.65 8198.40	cu.m cu.m cu.m cu.m	1720.35 1720.35 1720.35 1720.35	3771.45 3456.15 3095.30 2895.70		
2	Coursed rubble masonry hammer dressed, in foundation and plinth:	100 014		0170110	cuiii	1,2000	20,000	22.8	
	 a) dry masonry b) in mud mortar c) in lime, sand mortar 1:2 d) in cement, sand mortar: 	100 Cft. 100 Cft. 100 Cft.	3207.60 4474.80 5474.70	3957.60 5370.60 7531.95	cu.m cu.m cu.m	1132.90 1580.50 1933.65	1397.80 1896.90 2660.30		
	 d) in cement, sand mortar: i) ratio 1:3 ii) ratio 1:4 iii) ratio 1:6 iv) ratio 1:8 	100 Cft. 100 Cft. 100 Cft. 100 Cft.	5474.70 5474.70 5474.70 5474.70	10989.90 10196.45 9287.80 8788.75	cu.m cu.m cu.m cu.m	1933.65 1933.65 1933.65 1933.65	3881.65 3601.40 3280.45 3104.20		
3	Random rubble masonry (uncoursed) in ground floor or 20 ft.(6 m) height, building/other than building.							22.10	
	a) dry masonry b) in mud mortar	100 Cft. 100 Cft.	2871.00 3801.60	3621.00 4697.40	cu.m cu.m	1014.05 1342.75	1278.95 1659.10		

	MRS, BI-ANNUAL PERIOD (1st FE	EHRA, SOAN	VALLEY I	KHUSHAB					
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 c) in lime, sand mortar 1:2 d) in cement, sand mortar: 	100 Cft.	5306.40	7527.60	cu.m	1874.20	2658.75		
	i) ratio 1:3	100 Cft.	5306.40	11113.50	cu.m	1874.20	3925.30		
	ii) ratio 1:4 iii) ratio 1:6	100 Cft. 100 Cft.	5306.40 5306.40	10220.90 9199.25	cu.m cu.m	1874.20 1874.20	3610.00 3249.20		
	iv) ratio 1:8	100 Cft.	5306.40	8634.00	cu.m	1874.20	3049.55		
4	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8	
	a) dry masonry	100 Cft.	3742.20	4492.20	cu.m	1321.75	1586.65		
	b) in mud mortar	100 Cft.	5544.00	6433.30	cu.m	1958.15	2272.25		
	c) in lime, sand mortar 1:2d) in cement, sand mortar:	100 Cft.	6177.60	8234.85	cu.m	2181.95	2908.55		
	i) ratio 1:3	100 Cft.	6177.60	11692.80	cu.m	2181.95	4129.90		
	ii) ratio 1:4	100 Cft.	6177.60	10899.35	cu.m	2181.95	3849.65		
	iii) ratio 1:6	100 Cft.	6177.60	9990.70	cu.m	2181.95	3528.70		
	iv) ratio 1:8	100 Cft.	6177.60	9491.65	cu.m	2181.95	3352.45		
5	Ashlar block in course or scabbled masonry (including	100			7 843	i.		22.5	
	dressing, etc.,) in ground floor or 20 ft. (6 m) height,	100	1 1	الطومت بأتج				&	
	building/other than building.				63			22.6	
	a) in lime, sand mortar 1:2b) in cement, sand mortar:	100 Cft.	16612.20	18565.30	cu.m	5867.45	6557.25		
	i) ratio 1:3	100 Cft.	16612.20	20956.05	cu.m	5867.45	7401.70		
	ii) ratio 1:4	100 Cft.	16612.20	20360.95	cu.m	\$\$67.45	7191.50		
	iii) ratio 1:6	100 Cft.	16612.20	19686.55	cu.m	5867.45	6953.30		
6	Ashlar fine masonry (including dressing, etc.) in ground floor or 20 ft. 6 m) height, building/other than building.							22.3 (A) to (C) &	
	a) in lime, sand mortar 1:2	100 Cft.	31709.70	33485.80	cu.m	11199.85	11827.20	22.4	
	b) in cement, sand mortar:i) ratio 1:3	100 Cft.	31709.70	34681.20	cu.m	11199.85	12249.40		
	i) ratio 1:3	100 Cft.	31709.70	34383.45	cu.m	11199.85	12144.25		
	iii) ratio 1:6	100 Cft.	31709.70	34053.35	cu.m	11199.85	12027.65		
7	Extra labour on items 3, 4, 5 & 6 above for work in:-								
	i) first floor	100 Cft.	643.10	-	cu.m	227.15	-		
	ii) second floor	100 Cft.	1469.95	-	cu.m	519.20	-		
	iii) third floor	100 Cft.	2312.65	-	cu.m	816.85	-		
	iv) fourth floor	100 Cft.	3712.90	-	cu.m	1311.40	-		
8	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m) additional height, other than building, or part thereof.	100 Cft.	586.10	-	cu.m	207.00	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	1772.10	-	cu.m	625.90	-	22.12				
10	Extra labour for:-							22.7				
	a) coping and caps, etc.b) cornice & string course	100 Cft. 100 Rft.	9694.10 9694.10	-	cu.m Rm.	3423.95 317.95	-					
11	Dressing stones:- a) hammer dressed b) rough tooled dressed c) chisel dressed d) fine dressed Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft. 100 Sft. 100 Sft. 100 Sft. 100 Sft.	3484.80 6652.80 8046.70 16996.30 6316.55	11511.85	sq.m sq.m sq.m sq.m	374.95 715.85 865.85 1828.80 679.65	1238.70	22.2	 i) This rate of dressing shall be paid only when the supply of undressed stone is made. ii) In case of masonry, dressing is already included and this rate shall not be added thereto. iii) Only dressed surface of stone shall be measured. 			
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	252.55	279.35	cu.m	8920.05	9866.65					
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	145.15	174.95	cu.m	5126.70	6179.25					

9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBR	ALLEY KH	USHAB						
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100Sft.	4262.55	9303.25	sq.m	458.65	1001.05	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	3247.20	6900.70	sq.m	349.40	742.50	23.2	ditto
3	Covering mud roof with coal tar, and fine sand.	100Sft.	179.80	915.10	sq.m	19.35	98.45	23.1 to 23.2	ditto
4	 Filling spaces in between:- a) Wooden battens over beams, filled with deodar wood pieces (spacers). b) RCC battens, filled with CC block 1:3:6. c) Spaces filled with bricks. 	100Sft. roof area -ditto- -ditto-	270.60 625.70 177.10	2081.60 949.05 624.25	sq.m	29.10 67.35 19.05	224.00 102.10 67.15		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100Sft.	976.80	5324.60	sq.m	105.10	572.95	23.1	ditto
6	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm)							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	012 TO 31st	: JULY, 2012)	TEH:NC	OWSHEHI	RA, SOAN VA	LLEY KH	IUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ¹/₂" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:- a) cement concrete in haunches 1:6:12. 	100Sft.	4585.70	14451.65	sq.m	493.40	1555.00		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
7	 b) cement concrete in haunches 1:3:6. Jack arch roofing 4¹/₂" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ¹/₂" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster and gobri) soffit of arches cement plastered. The rate also includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges 	ditto	4585.70	15480.10	ditto	493.40	1665.65	23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred. Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	 of the joints with fine cement concrete 1:2:4 using stone aggregate:- a) cement concrete in haunches 1:6:12. b) cement concrete in haunches 1:3:6. 	100Sft. ditto	3706.55 3706.55	14266.75 14457.45	sq.m ditto	398.85 398.85	1535.10 1555.60		& sub- sequent floors, respectively.
8 9	Extra for vaulted jack arch roofing. Jack arch roofing of shingle and cement concrete 1:3:6, 4 ¹ / ₂ " (113 mm) thick at crown, with ¹ / ₂ " (13 mm) cement plaster including cost of supplying, erecting and dismantling centring.	100Sft.	871.20 4712.40	11777.65 Dagaaraa	sq.m sq.m	93.75 507.05	- 1267.30	23.3 to 23.5	ditto
10	Earth filling over roof including watering, ramming with 1"(25 mm) mud plaster finished, with gobri leeping:a) 3" (75 mm) thick earth filling and 1" (25 mm) mud	100Sft.	419.45	613.70	sq.m	45.15	66.05	23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
	plasterb) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster	100Sft.	548.05	774.70	sq.m	58.95	83.35		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	69.70	81.15	sq.m	7.50	8.75	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or	100Sft.	316.80	1777.80	sq.m	34.10	191.30	23.1	

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	012 TO 31st	: JULY, 2012)	2) TEH:NOWSHEHRA, SOAN VALLE				USHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)								
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively,
	 a) 20 BWG b) 22 BWG c) 24 BWG 	100Sft. 100Sft. 100Sft.	541.20 541.20 541.20	14550.40 12280.10 9865.80	sq.m sq.m sq.m	58.25 58.25 58.25	1565.60 1321.35 1061.55		on items 13 to 18.
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300 mm) outside width finished smooth with a floating coat of neat cement.	Rft.	50.15	68.20	Metre	164.50	223.70	23.10	
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	186.90	343.15	Each	Each	343.15	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4 ¹ ⁄2" (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	186.90	666.65	Each	186.90	666.65	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.				49 9				
	 a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe 	Per Rft. Per Rft.	35.65 35.65	141.20 165.20	Metre Metre	116.95 116.95	463.15 541.85		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	35.65	116.35	sq.m	383.60	1251.95	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	8.30	69.75	Sq.m	89.30	750.50		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23%
	 a) 4" dia (100 mm) cast iron down pipe. b) 3" (75 mm) cast iron down pipe. 	Per Rft. Per Rft.	35.65 35.65	183.10 158.80		116.95 116.95	600.55 520.85		on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	133.05	413.40	Each	133.05	413.40		
22	Shoes, bends or offsets for cast iron rain water down pipe,	Each	40.25	261.15	Each	40.25	261.15		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	012 TO 31st	: JULY, 2012)	TEH:NC	WSHEH	RA, SOAN VA		JSHAB
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec. No.	Remarks
INO.		Unit	Labour	Composite	Unit	Labour	Composite	INO.	
	including firing and pointing								
	including fixing and painting.								
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	148.50	268.80	Each	148.50	268.80	23.10	
24	Laying ¹ / ₂ " (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100Sft.	2851.20	16912.80	sq.m	306.80	1819.80	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	a) 22 BWG sheets roofingb) 24 BWG sheets roofing	100Sft. 100Sft.	1740.40 1740.40	14643.95 13037.00	sq.m sq.m	187.25 187.25	1575.70 1402.80	23.60	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and ridges, etc).	100Sft.	1207.80	4776.60	sq.m	129.95	513.95	23.8	
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100Sft.	148.35		sq.m	15.95	-	23.6	
28	Fixing asbestos cement sheet ridges and valleys ¹ /4" (6 mm) thick.	Per Rft.	14.15	59.60	Metre	46.40	195.50	23.8	
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-							23.6	
	a) 6" (150 mm) lap and 18" (450 mm)	Per Rft.	36.85	369.50	Per Metre	120.85	1211.95		
	overall, of 22 gauge G.I sheet ridging.b) 9" (225 mm) lap and 24" (600 mm)	Per Rft.	48.70	359.10	Per Metre	159.75	1177.85		
	 overall, of 24 gauge G.I sheet ridging. c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging. 	Per Rft.	48.70	428.40	Per Metre	159.75	1405.15		
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	24.35	144.25	Per Metre	79.85	473.15	23.11	
31	Making masonry ventilators in cement, sand mortar 1:4	Each	712.80	1183.50	Each	712.80	1183.50		

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	012 TO 31st	: JULY, 2012)	TEH:NC	WSHEH	RA, SOAN VA	LLEY KH	USHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
-									
32	Fixing water spouts or parnalas.	Each	213.85		Each	213.85	-	23.10	
33	Making drip course 2"x1/2" (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	8.70	9.80	Metre	28.55	32.15		
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	20.75	313.45	sq.m	223.25	3372.70		
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:- i) Thermopore sheet ½ " (13 mm) thick ii) Thermopore sheet ¾ " (20 mm) thick	100Sft. 100Sft.	1504.80 1504.80	5926.15 6052.15	sq.m sq.m	161.90 161.90	637.65 651.20		
	iii) Thermopore sheet 1" (25 mm) thick	100Sft.	1508.15	6181.50		162.30	665.15		
36	Providing and fixing AC rain water down pipe 4" (100 mm) dia, with shoe, T-bend, clamp, etc.	Rft.	8.10	178.90		26.55	586.80		
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:- i) for slabs upto 6" (150 mm) thick	Rft.	163168 9	15.05	Metre	44.10	49.35		Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.
	ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick.	Rft.	22.20	25.10		72.80	82.35		
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-								Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times for reinforced cement concrete.
	i) upto 1.0' (300 mm) height of girder or beam.	Each	56.10	61.45	Each	56.10	61.45		
	ii) for every 6" (150 mm) additional height or part thereof.	Each	26.95	29.50	Each	26.95	29.50		
39	Hoisting RS. Beams and wooden beams and placing in	Each	186.10	-	Each	186.10	-		

Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	position.								
40	Hoisting and placing in position sahl ballies, over roof.	Each	30.55	-	Each	30.55	-		
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.								
	a) 5' to 6' (1.50 to 1.83 m) long	Each	26.60	-	Each	26.60	-		
	b) 6' to 7' (1.83 to 2.13 m) long	Each	37.20	-	Each	37.20	-		
	c) 7' to 8' (2.13 to 2.44 m) long	Each	46.55	-	Each	46.55	-		
	d) 8' to 9' (2.44 to 2.74 m) long	Each	62.05	-	Each	62.05	-		
	e) above 9' (2.74 m) length	Each	74.45		Each	74.45	-		
42	Hoisting and placing in position R.C. trough:		/ *	> \					Applicable only to roof trough (inverted tees & trough) for height of
	a) upto 10' (3 m) in length	Each	74.45	-	Each	74.45	_		1st storey only.
	b) 10' to 11' (3 to 3.36 m) in length	ditto	93.05		ditto	93.05	_		The storey only.
	c) 11' to 12' (3.36 to 3.66 m) in length	ditto	124.10		ditto	124.10	-		
	d) 12' to 13' (3.66 to 3.96 m) in length	ditto	143.15		ditto	143.15	-		
	e) 13' to 14' (3.96 to 4.26 m) in length	ditto	155.10		ditto	155.10	-		
	f) 14' to 15' (4.26 to 4.57 m) in length	ditto	169.20	57	ditto	169.20	-		
	g) 15' to 16' (4.57 to 4.88 m) in length	ditto	186.10	31 m / 1	ditto	186.10	-		
	h) 16' to 17' (4.88 to 5.19 m) in length	ditto	206.80	11/2	ditto	206.80	-		
	i) 17' to 18' (5.19 to 5.49 m) in length	ditto	265.90		ditto	265.90	-		
	j) 18' to 19' (5.49 to 5.80 m) in length	ditto	286.35	~~~	ditto	286.35	-		
	k) 19' to 20' (5.80 to 6.10 m) in length	ditto	310.20	Deviarta	ditto	310.20	-		
43	Hoisting and placing in position R.C. inverted battens:-	_82_ 69-2	6-8894 6-92404 - "S	ហចបូល៖ ស	16.00 1 8. 6				
	i) upto 10' (3.05 m) span	Each	56.45	-	Each	56.45	-		
	ii) from 10' to 12' (3.05 to 3.66 m) span	ditto	125.40	-	ditto	125.40	-		
	iii) from 12' to 13' (3.66 to 3.96 m) span	ditto	150.50	-	ditto	150.50	-		
	iv) from 13' to 14' (3.96 to 4.26 m) span	ditto	188.10	-	ditto	188.10	-		
	v) from 14' to 15' (4.26 to 4.57 m) span	ditto	205.20	-	ditto	205.20	-		
	vi) from 15' to 16' (4.57 to 4.88 m) span	ditto	225.70	-	ditto	225.70	-		
	vii) from 16' to 18' (4.88 to 5.49 m) span	ditto	282.15	-	ditto	282.15	-		
	viii) from 18' to 20' (5.49 to 6.10 m) span	ditto	451.45	-	ditto	451.45	-		
44	Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	Each	285.10	523.95	Each	285.10	523.95		

10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproduct

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB

Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	1722.60	2941.20	sq.m	185.35	316.45		
2	Earth flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	579.15	741.15	sq.m	62.30	79.75	24.1	
3	Providing, laying, watering and ramming brick ballast 1 ¹ / ₂ " to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	1267.20	2797.20	cum.	447.60	987.95		
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	1059.30	1333.50	sq.m	114.00	143.50	24.2	
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	601.90	3291.35	sq.m	64.75	354.15	24.12	
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by $\frac{1}{2}$ "(13 mm) thick mud plaster.	100 Sft.	1076.70	5081.35	sq.m	115.85	546.75	24.12	
7	Grouting 4 ¹ / ₂ "(113 mm) dry brick work with cement mortal ratio 1: 5	100 Sft.	586.10	1004.15	sq.m	63.05	108.05		
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	1037.50	4439.65	sq.m	111.65	477.70	24.4	
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of ³ / ₄ " (20 mm) thick cement mortar 1:6.	100 Sft.	1,330.55	6,294.60	sq.m	143.15	677.30	24.4	
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of ¾" (20 mm) thick cement mortar 1:6.	100 Sft.	1,296.90	3,251.35	sq.m	139.55	349.85	ditto	
11	Brick ties (9"x4½"x1½")(225 mm x 113 mm x 40 mm) laid	100 Sft.	1,465.20	4,650.95	sq.m	157.65	500.45	24.4	

	MRS, BI-ANNUAL PERIOD (1st F	BRUARY	, 2012 TO 31	st JULY, 201	2) TEH:N	OWSHEH	RA, SOAN VA	LLEY KI	HUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	N0.	
	flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.								
12	Cement tiles (8"x8"x¾")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2.	100 Sft.	884.05	4,784.30	sq.m	95.10	514.80	24.7	
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm)	100 Sft.	884.05	3,405.65	sq.m	95.10	366.45		
	(b) 9"x9"x ³ 4" (225 x 225 x 20 mm)	ditto	884.05	4,354.00	ditto	95.10	468.50		
	(c) 6"x6"x¾"(150 x 150 x 20 mm)	ditto	884.05	5,952.20	ditto	95.10	640.45		
14	Coloured cement tiles (8"x8"x¾")(200 x 200 x 20 mm) of approved dark shade laid flat in 1:2 cement mortar, over ¾" (20 mm) bedding mortar of 1:2.	100 Sft.	884.05	4,809.50	sq.m	95.10	517.50	24.7	
		1985			7.64				
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-		F		7			24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick	100 Sft.	1,014.75	1,973.55	sq.m	109.20	212.35		1
	(b) 1 ¹ /4"(30 mm) thick	ditto	1,014.75	2,183.10	ditto	109.20	234.90		
	(c) 1 ¹ / ₂ "(40 mm) thick	ditto	1,232.55	2,610.50	ditto	132.60	280.90		
	(d) 1 ³ / ₄ "(45 mm) thick	ditto	1,232.55	2,832.35	ditto	132.60	304.75		
	(e) 2"(50 mm) thick	ditto	1,450.35	3,311.95	ditto	156.05	356.35		
	(f) $2\frac{1}{1000}$ (f) $2\frac{1}{$	ditto	1,489.95	3,547.80	ditto	160.30	381.75		
	(g) 2½"(62 mm) thick (h)2¾"(70 mm) thick	ditto ditto	1,668.15 1,668.15	3,853.40 4,154.55	ditto ditto	179.50 179.50	414.65 447.05		
	(i) 3"(75 mm) thick	ditto	1,668.15	4,402.15	ditto	179.50	473.65		
16	Providing and laying conglomerate flooring (two coat work)		-,	.,				24.10	If glass or marble strips are used
	with top layer of ¹ / ₂ "(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone								for panelling, it will be paid extra as per item No. 41 or 42.
	chips passing 3/16"(6 mm) sieve, over bottom layer of								per item ino. 41 of 42.
	cement concrete 1:3:6, including surface finishing and								
	dividing in panels:-								
	(a) 1½"(40 mm) thick	100 Sft.	1,459.25	2,821.55	sq.m	157.00	303.60		
	(b) $1^{3}4''(45 \text{ mm})$ thick	ditto	1,459.25	2,967.50	ditto	157.00	319.30		
	(c) $2"(50 \text{ mm})$ thick	ditto	1,832.50	3,541.00	ditto	197.20	381.00		
17	Add extra in cement concrete floor topping, if finished with	100 Sft.	356.40	791.25	sq.m	38.35	85.15		
	pigment and polishing.								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	237.60	-	sq.m	25.55	-		On items 19-25 & 29-34			
19	Flag stone flooring in lime mortar 1:2, over ³ /4"(20 mm) bedding mortar, in platforms and floors, etc.							24.5				
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	2,999.70 2,999.70	4,409.25 4,712.35	sq.m ditto	322.75 322.75	474.45 507.05					
20	Asphalt flooring, including preparation of proper base remelting, setting out, and finishing complete:-							24.10				
	 (a) 1"(25 mm) thick topping (b) ¹/₂"(13 mm) thick topping (c) ¹/₄"(6 mm) thick topping 	100 Sft. ditto ditto	1,064.25 832.60 614.40	13,499.25 7,182.90 3,884.35	sq.m ditto ditto	114.50 89.60 66.10	1452.50 772.90 417.95					
	$1^{3}/_{8}$ "(35 mm) thick mosaic flooring, consisting of 3/8"(10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete :-	197 2000							If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.			
	(a) using grey cement(b) using white cement	100 Sft. ditto	3,916.45 3,916.45	5,969.80 6,255.20	sq.m ditto	421.40 421.40	642.35 673.05					
22	11/2"(40 mm) thick mosaic flooring, consisting of 1/2 "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-		inance	Depart	ment				If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.			
	(a) using grey cement(b) using white cement	100 Sft. ditto	3,916.45 3,916.45	6,125.70 6,694.70	sq.m ditto	421.40 421.40	659.15 720.35					
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over ¾"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	2,482.15	6,023.95	sq.m	267.10	648.20	24.8				
24	Laying floor of approved white glazed tile ¹ /4" (6 mm) thick	100 Sft.	3,128.40	7,913.40	sq.m	336.60	851.50	24.7				

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 201	2) TEH:N	OWSHEH	RA, SOAN VA	LLEY KH	IUSHAB
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in white cement 1:2 over ³ / ₄ " (20mm) thick cement mortar 1:2, complete.								
25	Laying floor of approved coloured glazed tiles ¹ / ₄ "(6 mm) thick, laid in white cement and pigment on a bed of ³ / ₄ " (20 mm) thick cement mortar 1:2.	100 Sft.	3,128.40	8,203.20	sq.m	336.60	882.65	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	728.65	849.10	sq.m	78.40	91.35		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	776.15	898.20	sq.m	83.50	96.65		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	143.90	185.60	sq.m	15.50	19.95	24.6	
29	Shisham wood boarding or strip flooring $3/4"$ (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1/2 "x2"(40 x 50 mm),size placed at 12"(300 mm) centre to centre, including two coats of bitumen laid hot on the base.	100 Sft.	2,079.00	33,609.15	sq.m	223.70	3616.35	24.13	
30	Deodar wood boarding or strip flooring $3/4$ " (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1/2"x2"(40 x 50 mm) size , placed at 12"(300 mm) centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	2,435.40	40,851.15	sq.m	262.05	4395.60	ditto	
31	Teak wood boarding or strip flooring $\frac{1}{2}$ " (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens $\frac{1}{2}$ " x2"(40 x 50 mm) size, placed at 12"(300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	2,046.00	43,692.15	sq.m	220.15	4701.30	ditto	
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	2,237.40	37,975.95	sq.m	240.75	4086.20	24.13	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
33	Teak wood block 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	2,046.00	72,908.60	sq.m	220.15	7844.95	ditto				
34	Laying wooden paying of hard wood on edge in coal tar							ditto				
	and asphalt:-	100 Sft.			sq.m							
		Per Inch			per cm							
	(a) Shisham wood	thickness	1,518.00	23,712.10	thickness	163.35	2551.40					
	(b) Kikar wood	ditto	1,518.00	12,015.70	ditto	163.35	1292.90					
35	Tile skirting laid in 1:2 cement mortar, over ³ / ₄ "(20 mm)											
	thick cement mortar, 1:2 including cement washing and											
	filling joints complete:-											
	(a) cement tiles	100 Sft.	1,449.90	5,702.25	sq.m	156.00	613.55					
	(b) mosaic tiles	ditto	2,435.40	7,951.20	ditto	262.05	855.55					
			/									
36	Providing grey cement skirting or dado 3/8"(10 mm) thick	- 11			al de la compañía de							
	including rounding of corner and straight ening of top edge	1993		Contract of the local division of the local	- 1991							
	and finishing to smooth surface afterplastering :-	. 183			78							
		386			1 5.656							
	(a) 1:2 cement, sand mortar	100 Sft.	1,929.30	2,454.20	sq.m	207.60	264.05					
	(b) 1:3 cement, sand mortar	ditto	1,929.30	2,301.15	ditto	207.60	247.60					
	(c) Extra if skirting or dado is finished with pigment of any colour.	ditto	99.00	327.50	ditto	10.65	35.25					
	with pigment of any colour.			2000								
37	White glazed tile $(6"x6"x'4")$ (6 mm) thick dado jointed in white	100 Sft.	3,861.00	8,646.00	sq.m	415.45	930.30	24.7				
	cement and laid over 1:2 cement sand mortar 3/4" (20mm)	11	Mance	Depan	ment							
	thick, including finishing.											
38	Coloured glazed tile dado (6"x6"1/4") (6mm) thick in pigment over 1:2	100 Sft.	3,861.00	8,920.60	sq.m	415.45	959.85	ditto				
50	cement, sand mortar 3/4"(20mm) thick, including finishing.	100 510	5,001.00	0,720.00	sq.m	115.15	757.05	unto				
39	Mosaic dado or skirting with one part of cement and											
	marble powder in the ratio of 3:1 and two parts of marble											
	chips, laid over 1/2"(13 mm) thick cement plaster 1:3,											
	including rubbing and polishing, complete with finishing:											
	(a) using grey cement:											
	i) 3/8"(10 mm) thick	100 Sft.	4,613.40	5,688.80	sq.m	496.40	612.10					
	i) ½"(13 mm) thick	ditto	4,613.40	6,401.70	ditto	496.40	688.80					
			,	.,, .								
	(b) using white cement :											
	'i) 3/8"(10 mm) thick	100 Sft.	4,613.40	6,504.55	sq.m	496.40	699.90					

Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) ½"(13 mm) thick	ditto	4,613.40	6,787.25	ditto	496.40	730.30		
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	12.65	69.70	sq.m	136.10	749.95	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	3.95	Metre	-	12.95		Labour for fixing already included in items No. 15, 16, 21 and 22 of this Chapter.
42	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels								
	a) sSize 1 ¹ / ₂ " x ³ / ₈ " (40 x 10 mm) b) sSize 1 ¹ / ₂ " x ¹ / ₄ " (40 x 6 mm)	Per Rft. ditto		5.30 3.70	Metre ditto	-	17.40 12.15		
					16				
			R	in when	J.S.				

Finance Department

11. SURFACE RENDERING

1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

2	2 Rates for all finished works include the removal of surplus debris, unused material and byproducts. MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7				
	a) ¹ / ₂ " (13 mm) thick b) 1" (25 mm) thick	100 Sft. ditto	265.80 367.50	321.25 478.35	sq.m ditto	28.60 39.55	34.55 51.45					
2	Mud plaster on floor or roof (excluding Gobri leeping):-							ditto	Add extra 13%, 32% and 51% above the labour rates only or 6%, 15% &			
	a) ¹ / ₂ " (13 mm) thick	100 Sft.	239.20	294.60	sq.m	25.75	31.70		23% on the composite rates for 2nd, 3rd, 4th and subsequenct floors,			
	b) 1" (25 mm) thick	ditto	239.20	350.05	ditto	25.75	37.65		respectively.			
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.	100 A	E		78,			25.1 to 25.6				
	a) ¹ / ₄ " (6 mm) thick	100 Sft.	799.90	930.60	sq.m	86.05	100.15					
	b) ½" (13 mm) thick	ditto	799.90	1061.20	ditto	86.05	114.20					
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-	H	nance	Depart	men	Sec. 1		ditto				
	 a) ¹/₄" (6 mm) thick b) ¹/₂" (13 mm) thick 	100 Sft. ditto	799.90 799.90	1178.45 1409.90	sq.m ditto	86.05 86.05	126.80 151.70					
5	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand and shingle) upto 20' (6.00 m) height.	100 Sft.	1900.80	4047.35	sq.m	204.55	435.50	ditto				
6	Providing and laying machine sprayed plaster ¹ / ₂ " (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto				
	i) ratio 1:1 ii) ratio 1:1 ¹ / ₂ iii) ratio 1:2	100 Sft. ditto ditto	747.65 747.65 747.65	2046.75 1939.45 1877.75	sq.m ditto ditto	80.45 80.45 80.45	220.25 208.70 202.05					
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1				

	MRS, BI-ANNUAL PERIOD (1st FEB	VALLEY K	HUSHAB						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick	100 Sft. ditto ditto	799.90 799.90 1013.75	1324.85 1480.00 2063.55	sq.m ditto ditto	86.05 86.05 109.10	142.55 159.25 222.05	to 25.6	
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto	
	 a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	799.90 799.90 1013.75	1171.75 1295.70 1757.45	sq.m ditto ditto	86.05 86.05 109.10	126.10 139.40 189.10		
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto	
	 a) 3/8" (10 mm) thick b) 1/2" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	799.90 799.90 1013.75	1131.60 1221.50 1670.50	sq.m ditto ditto	86.05 86.05 109.10	121.75 131.45 179.75		
10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, upto 20' height. a) 1:2 b) 1:3 c) 1:4	100 Sft. ditto ditto	934.55 934.55 934.55	1562.60 1408.90 1368.70	sq.m ditto ditto	100.55 100.55 100.55	168.15 151.60 147.25		 i) This item shall be applicable to buildings meant for human habitation only, such as buildings like residences, offices, educational institutions and hospitals, etc. It shall not be admissible on godowns; bins; agriculture, poultry and animal sheds; cycle stands; garrages; etc.
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-	.82. 8	0.0000	2749 27807 1				25.1 to 25.6	ii) The thickness of the plaster will not be more than 3/8" (10 mm) thick.
	 a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	799.90 799.90 1013.75	1095.70 1160.15 1605.35	sq.m ditto ditto	86.05 86.05 109.10	117.90 124.85 172.75		
12	Cement plaster 1:6 upto 20' (6.00 mm) height:- a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	799.90 799.90 1013.75	1044.50 1124.30 1502.90	sq.m ditto ditto	86.05 86.05 109.10	112.40 121.00 161.70		
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	514.80	719.75	sq.m	55.40	77.45	25.4 to 25.6	
14	Lime pointing flush upto 20' (6.00 m) height including	100 Sft.	586.10	674.35	sq.m	63.05	72.55	25.8	

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2012 TO 31s	st JULY, 2012	2) TEH:I	NOWSHE	HRA, SOAN V	ALLEY K	HUSHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	raking joints, in lime, sand mortar 1:2.								
15	Lime pointing struck joints on walls, upto 20' (6.00 m) height, including raking joints in lime sand mortar 1:2.	100 Sft.	934.55	1022.85	sq.m	100.55	110.05	ditto	
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2	100 Sft.	799.90	1192.60	sq.m	86.05	128.30		
	b) ratio 1:3	ditto	799.90	1103.00	ditto	86.05	118.70		
17	Cement pointing 1:2 flush on floor.	100 Sft.	586.10	978.75	sq.m	63.05	105.30	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-		1	5	<u>_</u>				
	a) ratio 1:2	100 Sft.	934.55	1327.25	sq.m	100.55	142.80		
	b) ratio 1:3	ditto	934.55	1237.65	ditto	100.55	133.15		
19	Pointing flush on stone work, upto 20' (6.00 m) height.				18			25.8	
	a) in lime mortar 1:2 (lime, sand)	100 Sft.	776.15	892.15	sq.m	83.50	96.00		
	b) in cement mortar 1:3c) on stone work raised:-	ditto	776.15	1079.25	ditto	83.50	116.15		
	i) in lime mortar 1:2	100 Sft.	1473.10	1589.10	sq.m	158.50	171.00		
	ii) in cement mortar 1:3	ditto	1473.10	1776.20	ditto	158.50	191.10		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	332.65	Depart	sq.m	35.80	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	166.30	-	sq.m	17.90	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	85.55	91.00	sq.m	9.20	9.80	25.11	
23	Distempering:-							ditto	
	a) new surface:-								
	i) one coat	100 Sft.	69.60	143.90	sq.m	7.50	15.50		
	ii) two coats iii) three coats	ditto ditto	102.95 136.35	199.80 255.65	ditto ditto	11.10 14.65	21.50 27.50		
		unio	150.55	255.05	uno	17.05	27.50		
	b) old surface:-	105.77							
	i) one coat ii) two coats	100 Sft. ditto	63.90 102.95	115.70 154.80	sq.m ditto	6.90 11.10	12.45 16.65		
	ii) two coats	unto	102.95	154.80	unto	11.10	10.05		
L		8	1			1			

	MRS, BI-ANNUAL PERIOD (1st FEE	BRUARY,	2012 TO 31	st JULY, 2012	2) TEH:I	NOWSHE	HRA, SOAN V	ALLEY K	(HUSHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
24	Colour working							25.10	
24	Colour washing:-							23.10	
	a) new surface:-	100.00	50.05				0.00		
	i) one coat ii) two coats	100 Sft. ditto	58.95 88.40	82.50 122.75	sq.m ditto	6.35 9.50	8.90 13.20		
		unto	00.10	122.75	unto	7.50	15.20		
	b) old surface:- i) one coat	100 Sft.	58.95	72.95	sa m	6.35	7.85		
	i) two coats	ditto	88.40	111.30	sq.m ditto	9.50	12.00		
	·····							25.0	
25	White washing:-							25.9	
	a) new surface:-								
	i) one coat	100 Sft.	58.95	77.85	sq.m	6.35 9.50	8.40		
	ii) two coats iii) three coats	ditto ditto	88.40 114.50	116.75 152.30	ditto ditto	9.50	12.55 16.40		
		- 11			111				
	b) old surface:- i) one coat	100 Sft.	58.95	73.15	sq.m	6.35	7.85		
	ii) two coats	ditto	88.40	112.00	ditto	9.50	12.05		
26		1697	Nº18	67	143			05.7	
26	Gobri leeping:-	25		-10	0.5			25.7	
	a) on walls	100 Sft.	99.80	103.00	sq.m	10.75	11.10		
	b) over roofs	ditto	83.65	86.85	ditto	9.00	9.35		
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	134.65	Depart	sq.m	14.50	-	25.8	Payable with fresh masonry, when
				_					the face of the work is not to be
28	Extra for lime, mud or cement plaster and pointing from	100 Sft.	143.85	-	sq.m	15.50	-		plastered/pointed.
	20' (6.00 m) and above for each additional 10' (3.00 m)				-				
	height or part thereof.								
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	324.70	763.90	sq.m	34.95	82.20		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	324.70	341.30	sq.m	34.95	36.70		
					- 1				
31	Extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft.	103.95	196.35	sq.m	11.20	21.15		
	concine pointing to match with the colour of officks.								
32	Providing grooved cement sand plaster 1:3 over existing								
	plastered and roughened surface upto 20' (6.00 m) height.								
	i) 3/8" (10 mm) thick	100 Sft.	934.55	1306.40	sq.m	100.55	140.55		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ii) ½" (13 mm) thick	ditto	934.55	1430.35	ditto	100.55	153.90					
33	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	4.95	30.40	Metre	16.25	99.70					
34	Petty repairs to fire place.											
	i) Single ii) Double	Each Each	149.70 299.40	193.65 387.25	Each Each	149.70 299.40	193.65 387.25					
35	Petty repair to main rooms.	Each	302.95	420.60	Each	302.95	420.60		Area above 100 Sft (10.76 sq.m)			
36	Petty repair to small rooms.	Each	151.45	210.25	Each	151.45	210.25		Area upto 100 Sft (10.76 sq.m)			
37	Petty repair to verandah.	Each	302.95	397.00	Each	302.95	397.00					
38	Extra labour for white washing, colour washing, priming coat and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	100 Sft. Per coat	9.80		sq.m Per coat	1.05	-		The height will be taken from the floor, roof or ground uderneath as the case may be on the side towards which the work is to be done.			

Tinance Department

12. WOOD WORK

1 No extra rate is to be paid for sawing as the rates are inclusive of these

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEB	RA, SOAN V		(HUSHAB					
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1	
	a) Deodar woodb) Shisham wood	Per Cft. ditto	365.90 415.80	3556.70 2640.95	cu.m ditto	12923.60 14686.05	125622.65 93278.35		
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.	1		5				26.1	
	a) Deodar woodb) Shisham wood	Per Cft. ditto	237.00 237.00	3451.35 2510.50	cu.m ditto	8370.85 8370.85	121901.70 88670.85		
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-	Ť	nance	Depart	AS S meni	6. P		26.1 to 26.3 & 26.7	
	 i) 2" (50 mm) thick ii) 1³/₄" (45 mm) thick iii) 1¹/₂" (40 mm) thick 	Per Sft. ditto ditto	64.55 64.55 64.55	1305.00 1215.40 1127.90	sq.m ditto ditto	694.55 694.55 694.55	14041.80 13077.70 12136.20		
4	 First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cm²) including brass fittings, sash bars, etc. complete:- a) teak wood framing 1³/₄" (45 mm) thick with wire gauze fixed in position:- 							26.8 to 26.10	 i) This also includes the cost of wood required for extra thickness of chowkat. ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and Rs.50.60 per sq.m.
	i) without springs or spring hinges.	Per Sft.	11.55	539.05	sq.m	124.30	5800.20		
	ii) with springs or spring hinges.	ditto	11.55	542.60	ditto	124.30	5838.40		

	MRS, BI-ANNUAL PERIOD (1st FE	ALLEY K	(HUSHAB						
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) teak wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:-								
	i) without springs or spring hinges.	Per Sft.	11.55	496.35	sq.m	124.30	5340.75		
	ii) with springs or spring hinges.	ditto	11.55	500.30	ditto	124.30	5383.25		
	 c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes per cm²) fixed to chowkat with ¾" (20 mm) teak wood strips and screws. 	Per Sft.	20.80	151.45	sq.m	223.80	1629.60		
	 d) G.I. wire gauze 22 SWG, 12x12 meshes per square inch (5x5 meshes per cm²) fixed with ½" (13 mm) strip on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc. 	Per Sft.	19.50	510.20	sq.m	209.80	5489.75		
5	P/F expanded metal ¹ / ₂ " to ³ / ₄ " (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	26.00	251.35	sq.m	279.75	2704.55		
6	Providing and fixing expanded metal ¹ / ₂ " (13 mm) to ³ / ₄ " 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	26.00	379.75	sq.m	279.75	4086.10		
7	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-	T	nance	Depari	men			26.1 to 26.3 & 26.7	
	a) 2" thick (50 mm)	Per Sft.	61.60	1019.40	sq.m	662.80	10968.75		
	b) 1 ³ / ₄ " thick (45 mm)	ditto	61.60	950.60	ditto	662.80	10228.55		
	c) 1½" thick (40 mm)	ditto	61.60	903.10	ditto	662.80	9717.35		
8	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	a) 2 ¹ / ₄ " (56 mm) thick, with 1 ¹ / ₄ " (30 mm)	Per Sft.	69.30	644.25	sq.m	745.65	6932.15		
	 battens and 1" (25 mm) planks. b) 1³/₄" (40 mm) thick with 1" (25 mm) battens and ³/₄" (20 mm) planks. 	ditto	63.95	554.65	ditto	688.10	5968.05		

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY,	2012 TO 31s	st JULY, 201	2) TEH:N	OWSHEH	RA, SOAN V		(HUSHAB
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	79.00	344.40	sq.m	850.05	3705.75		
10	Deodar battened ledged and braced doors and windows 2¼" (56 mm) thick (1¼" (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	74.65	625.25	sq.m	803.25	6727.70	26.1, 26.2 26.4 to 26.6	
11	 Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the Engineer incharge:- 							26.1, 26.2 & 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60 Sq.m) for G.I. facing on one side and Rs.9.40 per Sft. (Rs.101.20
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	32.50 35.75	524.85 545.70	sq.m ditto	349.70 384.65	5647.40 5871.75		per Sq.m) for G.I. sheet facing on both sides.
	b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges and locking arrangements, as directed by the Engineer-in-charge:-	States							-ditto-
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	32.50 35.75	183.60 204.45	sq.m ditto	349.70 384.65	1975.55 2199.90		
12	First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm ²) including iron fittings etc. complete:-	R	nance	Depart		5- -		26.8 to 26.10	i) This also includes the cost of wood required for extra thickness of chowkat.
	 a) deodar wood framing 1³/₄" (45 mm) thick with wire gauze fixed in position:- 								ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	i) without springs or spring hinges.ii) with springs or spring hinges.	Per Sft. ditto	34.65 34.65	434.15 438.05	sq.m ditto	372.85 372.85	4671.45 4713.40		
	 b) deodar wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:- i) with strengthere being a big strengthere 	D. 50	24.55	400.15		272.05	1007.15		
	i) without springs or spring hingesii) with springs or spring hinges	Per Sft. ditto	34.65 34.65	402.15 404.45	sq.m ditto	372.85 372.85	4327.15 4351.90		
	 c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm²) fixed to chowkat, with ³/₄" ('20 mm) thick deodar wood strip and screws. 	Per Sft.	26.00	133.20	sq.m	279.75	1433.25		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks		
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.			
	 d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to chowkat, with ¹/₂" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm). 	Per Sft.	39.00	364.30	sq.m	419.65	3919.85				
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	57.75	419.85	sq.m	621.40	4517.60	26.1 26.2			
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-										
	a) M.S. angle iron 1 ¹ / ₂ "x 1 ¹ / ₂ "x ¹ / ₄ " (40x40x6 mm) welded with M.S. flat 2"x ¹ / ₄ " (50 mm x 6 mm)	Per Sft.	14.90	133.00	sq.m	160.30	1431.10				
	 b) M.S. tee iron 1¹/₂"x 1¹/₂"x ¹/₄" (40x40x6 mm) welded with M.S. flat 2"x ¹/₄" (50 mm x 6 mm) 	Per Sft.	14.90	99.45	sq.m	160.30	1070.10				
15	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 1¼" x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:	9 1	nance	Depart	meni	Ş- F					
	a) single rebateb) double rebate	Per Sft. ditto	21.90 25.65	117.10 133.80	sq.m ditto	235.65 276.00	1260.00 1439.70				
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	2.00	30.70	sq.m door area	21.50	330.35	26.2			
17	Providing and fixing brass spring hinges to wire gauzed doors.	Each	41.60	161.60	Each	41.60	161.60				
18	Providing and fixing sliding bolt to doors:-										
	 iron sliding bolt, 10" (250 mm) long iron sliding bolt, 12" (300 mm) long 	Each ditto	39.00 39.00	87.00 123.00	Each ditto	39.00 39.00	87.00 123.00				
	iii) brass sliding bolt, 10" (250 mm) long	ditto	39.00	129.00	ditto	39.00	129.00				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description		Rate (British Sys	stem)	ŀ	Rate (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	iv) brass sliding bolt, 12" (300 mm) long	ditto	39.00	291.00	ditto	39.00	291.00				
19	Extra for brass fittings to doors and windows, except for hinges, which shall be of iron:-										
	 deodar wood panelled or panelled and glazed or fully glazed. 	Per Sft.	1.20	10.05	sq.m	12.90	108.15				
	ii) deodar wood wire gauzed shutters.	ditto	1.20	7.40	ditto	12.90	79.60				
20	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	124.75	311.95	Each	124.75	311.95				
21	Providing and fixing, approved quality mortice lock.	Each	173.25	358.05	Each	173.25	358.05				
22	Providing and fixing, expended metal ¹ /2" to ³ /4" (13 mm to 20 mm) mesh 16 gauge.			\mathcal{I}							
	a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc.	Per Sft.	26.00	212.70	sq.m	279.75	2288.65				
	 b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm) 	ditto	26.00	308.70	ditto	279.75	3321.60				
23	 a) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. complete. 	Per Sft.	83.15	1461.00	sq.m	894.80	15720.45		For hollow frame shutter with commercial ply on one side, the composite rate shall be reduced by Rs.54.00 per Sft;or Rs.580.00 per Sqm and for hollow frame		
		32 3	10 8-000 0 0-0,707						shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per Sft. or Rs.245.00 per Sq. metre.		
	 b) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm)depth with shelves, shutters, brass fittings, etc., without boxing and back, complete. 	Per Sft.	62.35	478.75	sq.m	671.10	5151.55				
24	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ¹ / ₄ " (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1 ¹ / ₂ :3) shelves 1 ¹ / ₂ " (40 mm) thick including 3 coats of painting.	Per Sft.	51.55	317.35	Sq.m	554.60	3414.80				

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2012 TO 31s	st JULY, 2012	2) TEH:N	NOWSHEH	RA, SOAN V	ALLEY I	KHUSHAB
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
25	Providing and fixing wooden box type wardrobe 22" (550 mm) deep including ¾" (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods, etc. including three coats of enamel paint:- i) Partal wood boxing and deodar wood	5 66							If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood bracing and deodar wood lipping is used, the composite rate will be reduced by Rs.13.00 per Sft. or
	shelves and leaves, etc.	Per Sft.	95.95	590.50	sq.m	1032.45	6354.00		Rs.140.00 per Sq. metre.
	Deodar wood boxing, and deodar wood shelves and leaves, etc.	ditto	95.35	819.95	ditto	1026.20	8822.70		
26	Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete.	Per Sft.	37.20	505.85	Sq.m	400.55	5442.75		
	windows, including holdfast, etc.		0						
	a) Teak woodb) Deodar woodc) Shisham wood	Per Sft. ditto ditto	18.50 11.55 13.85	448.90 343.30 163.15	Sq.m ditto ditto	198.85 124.30 149.15	4829.95 3693.75 1755.60		
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	a) 1" (25 mm) thick b) 34" (20 mm) thick c) 1/2" (13 mm) thick	Sft. ditto ditto	20.80 20.80 20.80	283.30 217.60 152.20	sq.m ditto ditto	223.70 223.70 223.70	3048.05 2341.25 1637.45		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	 i) 1" (25 mm) thick ii) 1¹/₂" (40 mm) thick iii) 2" (50 mm) thick 	Sft. ditto ditto	20.80 20.80 20.80	283.30 414.40 545.50	sq.m ditto ditto	223.70 223.70 223.70	3048.05 4458.70 5869.35		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSH										
Sr. No.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec. No.	Remarks		
INO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.			
30	 Making and fixing cleats for doors and windows, including hinges and screws. 	Each	24.95	93.95	Each	24.95	93.95	26.1 and 26.2			
	b) Making and fixing cleats with brass hooks for roof ventilators.	Each	33.25	68.05	Each	33.25	68.05				
	c) Providing and fixing door stops of 1¹/₂" (40 mm) dia rubber block.	Each	3.45	46.95	Each	3.45	46.95				
	d) Providing and fixing G.I. hook with clamps for doors.	Each	1.10	6.20	Each	1.10	6.20				
31	Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.		~	5				ditto			
	a) Shisham wood	Per Rft.	95.00	243.20	Metre	311.65	797.75				
	b) Teak wood	ditto	70.55	594.00	ditto	231.45	1948.30				
	Deodar wood dado or picture rail 3"x1 ¹ / ₄ " (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete. Sawing wood by hand:-	Per Rft.	35.30	203.55	Metre	115.70	667.65	26.1 26.2			
55	Suving wood by haid.		0								
	a) Soft wood (deodar, kail or chir).b) Hard wood (shisham, kikar, teak or sahl).	100Sft. ditto	415.80 554.40	Depart	sq.m ditto	44.75 59.65	-				
34	Sawing wood by machine:										
	a) Soft wood b) Hard wood	100Sft. ditto	245.32 0.00	-	sq.m ditto	26.40 0.00	-				
35	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	29.10	342.05	sq.m	313.20	3680.65	26.1			
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	34.65	101.85	sq.m	372.85	1095.90	ditto			
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	124.75	7053.55	Each	124.75	7053.55	ditto			
38	Dismantling and refixing eave boards.	Per Rft.	8.90		Metre	29.25					

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY,	2012 TO 31	st JULY, 2012	2) TEH:N	IOWSHEH	RA, SOAN V	ALLEY	KHUSHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	-
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1 ¹ / ₂ " (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	138.40	2157.30	Metre	453.90	7075.95	26.1	
40	Providing and fixing partition, including frame work:-								
	a) Sheets on one side of framework:-								
	 i) Hard board ii) Ply wood ¹/₄" (6 mm) thick iii) Masonite 	100Sft. ditto ditto	649.70 649.70 649.70	11362.70 12622.70 13126.70	sq.m ditto ditto	69.90 69.90 69.90	1222.65 1358.20 1412.45		
	b) Sheets on both sides of frame work:-		×	62					
	 i) Hard board ii) Ply wood ¹/₄" (6 mm) thick iii) Masonite 	100Sft. ditto ditto	779.65 779.65 779.65	12522.20 22769.25 16050.20	sq.m ditto ditto	83.90 83.90 83.90	1347.40 2449.95 1727.00		
41	Providing and fixing ceiling, including frame work:-		10		7 24				
	 i) Hard board ii) Chip board iii) Ply wood ¹/₄" (6 mm) thick 	100Sft. ditto ditto	1289.05 1289.05 1289.05	7264.05 9304.05 9544.05	sq.m ditto ditto	138.70 138.70 138.70	781.60 1001.10 1026.95		
	iv) Masonite	ditto	1289.05	9184.05	ditto	138.70	988.20		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-	99	nance	Deparl					In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	 i) ³/₄" (20 mm) thick ii) 1" (25 mm) thick 	100Sft. ditto	1481.55 1481.55	8178.35 8255.75	sq.m ditto	159.40 159.40	880.00 888.30		
	b) Partal wood frame panelling:								
	i) ³ /4" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	1481.55 1481.55	4863.35 4989.35	sq.m ditto	159.40 159.40	523.30 536.85		
43	a) Fixing door, including chowkats.	Each	267.30	-	Each	267.30	-		
	b) Fixing windows, including chowkats.	ditto	133.65	-	ditto	133.65	-		

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY,	2012 TO 31s	st JULY, 2012	2) TEH:I	NOWSHEH	RA, SOAN V	ALLEY	KHUSHAB
Sr. No.	Description		Rate (British Sy	stem)	I	Rate (Metric S	ystem)	Spec. No.	Remarks
INO.		Unit	Labour	Composite	Unit	Labour	Composite	110.	
44	 a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty. 	Per Sft.	14.75	36.90	sq.m	158.50	396.85	26.12	
	 b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty. 	Per Sft.	18.60	66.60	sq.m	200.05	716.55		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	27.95	72.60	sq.m	300.60	780.90	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	10.30	11.35	sq.m	110.85	121.90		
	b) Cutting to required size and fixing glass panes with wooden fillets and putty.	Per Sft.	15.50	33.65	sq.m	166.90	362.20		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-			\mathcal{I}					
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	23.75	85.05	sq.m	255.75	915.25		
	 b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sft (2.25 sq.m). 	Per Sft.	23.75	85.25	sq.m	255.80	917.20		
48	Providing and fixing 1 ¹ / ₂ " (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respect: (excluding sliding bolt or lock) with:-			K.C.					
	 M.S. angle iron 1½"x1½"x1½", welded (40 mmx 40 mmx 6mm) with M.S. flat 2"x14" (50 mm x 6 mm) 	Per Sft.	89.30	597.80	sq.m	960.85	6432.50		
	2"x ¹ /4" (50 mm x 6 mm) ii) M.S. tee iron 1 ¹ /2"x1 ¹ /2"x ¹ /4", welded (40 mmx40 mmx 6mm) with M.S. flat ¹ /2"x ¹ /4" (13 mm x 6 mm)	Per Sft.	89.30	554.05	sq.m	960.85	5961.65		
49	Providing and fixing 1 ¹ / ₄ " (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1 ¹ / ₄ " (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1 ¹ / ₂ "x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complete in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	 M.S. angle iron 1¹/₂"x1¹/₂"x¹/₄", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¹/₄" (50 mm x 6 mm) 	Per Sft.	62.05	491.90	sq.m	667.55	5292.65		

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2012 TO 31s	t JULY, 2012	2) TEH:N	NOWSHEH	RA, SOAN V	ALLEY I	KHUSHAB
Sr.	Description		Rate (British Sys	tem)	R	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm) 	Per Sft.	62.05	458.35	sq.m	667.55	4931.75		
50	Providing and fixing 1½" (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	33.95	315.65	sq.m	365.25	3396.10		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	61.40	316.10	sq.m	660.45	3401.30		
	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	12.45	20.05	Metre	40.90	65.70		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	5.20 11.011.CB	115.50 Depart	Metre	17.05	378.80		
	Providing and fixing M.S. flat ¹ / ₄ "x1/8" (13mm x 3mm) grill including ³ / ₄ " x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	36.80	162.95	sq.m	395.95	1753.15		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cm ²) fixed to steel window, complete with flat iron patti ¹ / ₂ "x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	10.60	45.55	sq.m	113.90	490.15		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 per square metre.
56	Providing and fixing wooden moulding stopper 2½"x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	a) Teak wood moulding	Per Sft.	13.00	95.05	sq.m	139.80	1022.85		

	MRS, BI-ANNUAL PERIOD (1st F	RA, SOAN V	ALLEY I	KHUSHAB					
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) Deodar wood moulding	ditto	13.00	54.55	ditto	139.80	586.90		
	b) Deodar wood moulding	anto	15.00	54.55	anto	159.80	380.90		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between braces with 1:3:6 PCC fixing ply of approved quality including holdfasts complete in all respects.								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))
	a) Teak wood ply	Per Sft.	32.00	291.00	sq.m	344.15	3130.90		
l	b) With commercial ply	ditto	32.00	282.95	ditto	344.15	3044.35		
58	Providing and fixing ornamental wooden architrave $3" x$ (1½" tapered to ¼") all along the door frame complete in all respect.		1	5					
	a) Teak wood architrave	Per Sft.	5.95	60.50	sq.m	64.20	650.95		
	b) Deodar wood architrave	ditto	5.95	32.80	ditto	64.20	352.80		
59	Providing and fixing Vin board cabinet 3/4" thick with drawers 3"deep in 'Kitchen including termite proofing and polishing with synthetic enamel as specified, with handles hinges, screws etc., complete in all respects.	a co		I A A A A A A A A A A A A A A A A A A A	78				
	i) 1-1/2' deep, without back	Per Sft	69.90	425.85	sq.m	752.35	4581.95		
	ii) 1-1/2' deep, with back	Per Sft	69.90	467.85	sq.m	752.35	5033.85		
	iii) 2' deep,without back	Per Sft	69.90	466.80	sq.m	752.35	5022.55		
	iv) 2' deep, with back	Per Sft	69.90	508.80	sq.m	752.35	5474.50		

13. PAINTING AND VARNISHING

1 The rates include charges for scaffolding and other arrangements

2 The rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description]	Rate (British Sy	stem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	a) Cleaning painted wood work with oil and water.	100 Sft.	79.20	111.30	sq.m	8.50	12.00						
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	52.80	92.40	sq.m	5.70	9.95	27.7					
2	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	158.40	-	sq.m	17.05	-	27.3					
3	Scraping, brushing and removing old paint from metal surface.	100 Sft.	633.60) -)	sq.m	68.20	-	27.9					
4	Painting old surfaces:-	100			日間			27.1 27.3 &					
	a) Painting corrugated surfaces, patent roofing, etc. with oil paint.		Sec.	- 16	L.			27.9					
	i) first coatii) each subsequent coat	100 Sft. ditto	178.60 135.30	338.20 216.90	sq.m ditto	19.20 14.55	36.40 23.35						
	 b) Painting sashes, fanlights, glazed or gauzed doors and windows:- 	Ŧ	nance	Depart	ment								
	i) first coatii) each subsequent coat	100 Sft. ditto	108.25 92.00	193.45 161.60	sq.m ditto	11.65 9.90	20.80 17.40						
	c) Painting doors and windows, any type:												
	i) first coatii) each subsequent coat	100 Sft. ditto	178.60 135.30	341.80 259.50		19.20 14.55	36.80 27.90						
	 Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:- 												
	i) first coatii) each subsequent coate) Painting fillets, framings, skirtings, pipes, gutters and	100 Sft. ditto	108.25 92.00	193.45 161.60	-	11.65 9.90	20.80 17.40						
	similar linear work not exceeding 6" in girth:-												

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	•]	Rate (British Sy	stem)	Rat	te (Metric Sy	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	i) first coatii) each subsequent coat	100 Lft. ditto	92.00 64.95	177.20 134.55	Metre ditto	3.00 2.15	5.80 4.40					
	 f) Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:- 											
	i) first coatii) each subsequent coat	100 Nos. ditto	257.40 234.75	417.00 319.95	100 Nos. ditto	257.40 234.75	417.00 319.95					
	g) Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:-											
	i) first coatii) each subsequent coat	100 Nos ditto	588.35 350.75	1063.55 588.35	100 Nos ditto	588.35 350.75	1063.55 588.35					
5	Painting new surface:-	18			ゴム			27.1 27.2 &				
	a) Preparing surface and painting corrugated surface, patent roofing, etc.				18			27.9				
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	255.40 90.40	428.20 289.00	sq.m ditto	27.50 9.75	46.10 31.10					
	 b) Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):- 	Ti	nance	Depart								
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	108.50 77.95	252.20 190.75	sq.m ditto	11.70 8.40	27.15 20.50					
	c) Preparing surface and painting of doors and windows any type (including edges):-											
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	255.40 90.45	424.60 289.05	sq.m ditto	27.50 9.75	45.70 31.10					
	 d) Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:- i) priming coat. 	100 Sft.	171.25	275.05	sq.m	18.45	29.60					
	ii) each subsequent coat of paint.	ditto	77.95	190.75	ditto	8.40	20.50					

	1	MRS, BI-ANNUAL PERIOD (1st FEB	IRA, SOAN	VALLEY K	HUSHAB					
Sr.		Description	1	Rate (British Sys	stem)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.			Unit	Labour	Composite	Unit	Labour	Composite	No.	
	e)	Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-								
		i) priming coat.ii) each subsequent coat of paint.	100 Lft. ditto	138.00 51.95	216.95 144.95	Metre ditto	4.55 1.70	7.10 4.75		
	f)	Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-								
		i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	405.90 198.00	900.60 591.60	100 Nos. ditto	405.90 198.00	900.60 591.60		
	g)	Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-	يلي.			Ju.				
		i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	1123.65 339.90	1793.25 1045.50	100 Nos. ditto	1123.65 339.90	1793.25 1045.50		
	h)	Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	16.65	30.65	sq.m	1.80	3.30		
6		plying Khanki Mixture hot to barrage		0	0.0				27.10	
	gate	28:-	27	nance	Depart					
	i) ii)	first coat second coat	100 Sft. ditto	135.30 110.35	366.35 257.70	sq.m ditto	14.55 11.85	39.40 27.75		
7	Frei	nch polishing complete:-							27.6	
	a) b)	on new work on old work	100 Sft. ditto	1295.50 701.50	1346.85 729.80	sq.m ditto	139.40 75.50	144.90 78.55		
8		nishing wood work, including cleaning and preparing face.								
	a)	first coat	100 Sft.	108.25	205.45	sq.m	11.65	22.10		
	b) c)	second coat third coat	ditto ditto	40.60 40.60	114.40 98.80	ditto ditto	4.35 4.35	12.30 10.65		
9	Bitu	umen coating to plastered or cement concrete surface:-								

	MRS, BI-ANNUAL PERIOD (1st FEB	IRA, SOAN	VALLEY M	(HUSHAB					
Sr. No.	Description]	Rate (British Sy	stem)	Rat	e (Metric Sy	vstem)	Spec. No.	Remarks
110.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
	 i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m) ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m) iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m) 	100 Sft. ditto ditto	132.00 126.70 104.55	1000.70 569.20 547.05	sq.m ditto ditto	14.20 13.65 11.25	107.70 61.25 58.85		
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	5.40	6.00	Per No.	5.40	6.00	27.1	
11	Writing letters or figures at any surface with reflective paint of approved quality and colour per letter per inch height.	Per Letter per inch height	5.40	5.75	Per Letter per 25 mm height	5.40	5.75	27.1	
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	6.15	6.90	ditto	6.15	6.90	ditto	
13	Coaltar painting:	, idi			- Juli			27.8 to	
	a) first coat, laid hotb) second coat, laid hot	100 Sft. ditto	109.75 66.55	791.85 498.25	sq.m ditto	11.80 7.15	85.20 53.60	27.11	
14	Solignum painting:-	- El	- 53		AN STA			27.8	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	91.50 138.60	114.30 174.70	sq.m ditto	9.85 14.90	12.30 18.80		
15	Creosote painting:-	T:	nance	Depart	ment			ditto	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	109.75 166.30	212.95 339.10	sq.m ditto	11.80 17.90	22.90 36.50		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	411.85	426.25	sq.m	44.30	45.85	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	158.40	165.60	sq.m	17.05	17.80	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	27.05	31.50	Each	27.05	31.50	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	54.10	62.65	per Metre	177.50	205.45	ditto	
20	Painting sounding rods and other gauges, reading to 10th	Per Lft.	27.05	29.75	per Metre	88.75	97.60	27.1	

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2012 TO 31s	t JULY, 201	2) TEH:N	OWSHEH	IRA, SOAN	VALLEY K	(HUSHAB
Sr.	Description	1	Rate (British Sys	stem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	of a foot (metre)								
21	Painting leveling staves.	Per Lft.	81.85	86.10	per Metre	268.45	282.40		
22	 Painting and lettering mile/Km stones, on both sides: 							ditto	
	i) one coat ii) two coats	Each ditto	58.00 101.50	88.90 149.50	Each ditto	58.00 101.50	88.90 149.50		
	 b) Painting and lettering Furlong/½ Km stones, on both sides:- 							27.1	
	i) one coatii) two coats	Each ditto	7.75 13.55	11.30 19.85	Each ditto	7.75 13.55	11.30 19.85		
	c) Painting and lettering Sign posts:-	id.			Hilli.				
	i) one coatii) two coats	Each ditto	64.95 107.15	84.75 140.75	Each ditto	64.95 107.15	84.75 140.75		
23	Removing paint or varnish from wall.	100 Sft.	316.80	<u></u>	sq.m	34.10	-	27.12	
24	Scraping from hydraulic gates:-		n an	E P	(SP-			27.1	
	a) Khanki paintb) Aluminium paint	100 Sft. ditto	633.60 633.60	Depart	sq.m ditto	68.20 68.20	- -		
25	Painting letters with shade.	per letter per inch height	8.65	8.65	per letter per 25 mm height	8.65	8.65	27.1	
26	Scraping rust from old rail or girders.	100 Sft.	475.20	511.20	sq.m	51.15	55.00	27.9 27.10	
27	Chiselling old paint from brick work.	100 Sft.	633.60	657.60	sq.m	68.20	70.75	27.12	
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	528.00	538.00	sq.m	56.80	57.90		
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	158.40	201.65	sq.m	17.05	21.70	27.9	
30	Cleaning and painting punkha poles, including fixing	Each	103.95	111.25	Each	103.95	111.25	27.3	

	MRS, BI-ANNUAL PERIOD (1st FEI	IRA, SOAN	VALLEY K	HUSHAB					
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	hooks.								
31	Preparing surface and painting with emulsion paint:-							27.12	
	a) first coatb) 2nd and each subsequent coat	100 Sft. ditto	128.80 99.00	271.95 212.10	sq.m ditto	13.85 10.65	29.25 22.85		
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.							27.12	
	a) new surface:								
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	128.80 99.00	194.50 157.00	sq.m ditto	13.85 10.65	20.95 16.90		
	b) old surface:	1.1			Juli.				
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	128.80 99.00	157.00 126.55	sq.m ditto	13.85 10.65	16.90 13.60		
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	120111		. 20 1	////230				
	a) new surface:								
	i) 1st coat ii) 2nd coat	% sft % sft	483.10 262.35	776.30 382.15	sq.m sq.m	52.00 28.25	83.55 41.10		
	b) old surface:	%sft	262.35	382.15	sq.m	28.25	41.10		
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	0.80	1.50	Metre	2.65	4.95		
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads comlpete	Per Rft.	1.05	8.10	Metre	3.50	26.65	M248-91	Rates shall be reduced by Rs.0.50 P.Rft or Rs.1.65 P.Mtr. If glass beads
35	in all respect. Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	29.70	60.30	Job	29.70	60.30	(2000)	are not used.
36	Repainting of iron poles with cross arms, with bitumen or	Per Job	69.30	177.90	Job	69.30	177.90		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	R	ate (British Syst	em)	Ra	te (Metric Sy	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	other approved paint.											
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:											
	 i) upto 40 mm (1¹/₂") dia ii) above 40 mm (1¹/₂") to 50 mm (2") dia iii) above 50 mm (2") to 100 mm (4") dia 	Per Rft. ditto ditto	0.65 1.25 2.10	2.10 3.10 4.85	Metre ditto ditto	2.10 4.15 6.95	5.55 10.10 15.85					
38	Repainting main switches and branch distribution boards of all sizes and types, with approved paint (complete set).	Per Job	13.70	57.65	Job	13.70	57.65					
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	50.70		sq.m	5.45	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.			

Finance Department

14. LINING OF CANALS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts

2 The rates also include curing for specified period wherever necessary.

3 Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB

Sr.	Description		Rate (British Sy	stem)]	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3	
	a) in bed b) on slope	100Sft. ditto	351.95 480.50	-	sq.m ditto	37.85 51.70	-		
2	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	902.90	1396.70	sq.m	97.15	150.30	ditto	
3	Cement plaster 1⁄2" (13 mm) thick ratio 1:10.		. (ditto	
	a) in bed b) on slope	100Sft. ditto	652.95 823.70	882.60 1053.35	sq.m ditto	70.25 88.65	94.95 113.35		
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	1		فكومت بنجا-	7,4			ditto	
	a) in bedb) on slope	100Sft. ditto	652.95 823.70	1044.60 1215.35	sq.m ditto	70.25 88.65	112.40 130.75		
5	Cement plaster 1 ¹ / ₂ " (40 mm) thick ratio 1:6.	1	Financ	e Depa		mt -		ditto	
	a) in bedb) on slope	100Sft. ditto	823.70 1037.50	1777.45 1991.30	sq.m ditto	88.65 111.65	191.25 214.25		
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bed b) on slope	100Cft. ditto	3960.00 4524.30	13405.90 13970.20	cu.m ditto	1398.65 1598.00	4734.95 4934.25		payable separately.
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are
	a) in bed	100Cft.	3960.00	14675.40	cu.m	1398.65	5183.35		payable separately.
	b) on slope	ditto	4524.30	15239.70	ditto	1598.00	5382.65		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description		Rate (British Sy	ystem)	1	Rate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	Brick lining 9"x4 ¹ / ₂ "x3" (225x113x75 mm) in 1:6 cement, sand mortar:- a) in bed	100Cft.	3960.00			1398.65	5688.60	28.2	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are payable separately.		
	 b) on slope Brick lining 9"x4½"x3" (225x113x75 mm), in 1:3 cement, sand mortar:- 	ditto	4524.30	16670.20	ditto	1598.00	5887.90	ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to		
	a) in bedb) on slope	100Cft. ditto	3960.00 4524.30		cu.m ditto	1398.65 1598.00	6137.00 6336.30		5 above are payable separately.		
	Cement concrete lining, using washed screened and graded stone aggregate:- a) in bed:-			C				20.1, 28.1 & 28.3			
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	3286.80 3286.80 3286.80	16159.45 13977.60 12410.65	cu.m ditto ditto	1160.90 1160.90 1160.90	5707.50 4936.90 4383.45				
	 b) on slope:- i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8 	100Cft. ditto ditto	3811.50 3811.50 3811.50	14502.30	cu.m ditto ditto	1346.20 1346.20 1346.20	5892.85 5122.20 4568.75				

15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Cutting Ransome and Larson piles.	Per cut	83.15	-	Per cut	83.15	-	29.1- 29.3					
2	Cutting universal piles.	Per cut	123.10	-	Per cut	123.10	-	ditto					
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	2047.30	C	sq.m	220.30	-	ditto	 The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre). The rates are for the tackle 				
									 gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government. 3) T-piles and adjustable junction piles will be counted as two piles. 				
4	Driving steel piles, more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	1964.15	ce Dep	sq.m	211.35	-	ditto	ditto				
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	1465.20	-	sq.m	157.65	-	ditto	ditto				
6	Dolleying piles.	Each	129.90	-	Each	129.90	-	ditto	Upto 5' (1.5 m) dolleying.				
7	Drilling holes in piles by hand.	Each	11.45	-	Each	11.45	-	ditto					
8	Raising and lowering machine.	Per Ft.	1909.60	-	Metre	6263.50	-	ditto					
9	Turning Machine, 90°.	Per Job	2909.30	-	Per Job	2909.30	-	29.1 to 29.3					
10	Turning Machine, 135°.	Per Job	3574.55	-	Per Job	3574.55	-	ditto					
11	Turning Machine, 180°.	Per Job	4873.45	-	Per Job	4873.45	-	29.1 to 29.3					

	MRS, BI-ANNUAL PERIOD (1st	FEBRUA	RY, 2012 TO	O 31st JULY	′, 2012) T	EH:NOW	/SHEHRA, S	SOAN VAL	LEY KHUSHAB
Sr.	Description	ŀ	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
12	Travelling machine (light).	Per Chain	5763.10	-	30 M.	5763.10	-	ditto	
13	Loading and unloading piles.	Ton	117.20	-	Tonne	115.35	-	ditto	To be done by hand carts or ramps, including cost of ropes.
14	Dismantling piling machine.	Each	11721.60	-	Each	11721.60	-	ditto	
15	Erecting piling machine.	Each	13524.90	-	Each	13524.90	-	ditto	
16	Carriage of piling machine under different conditions.	per chain	2346.95	*	30 M	2346.95	-	ditto	



Finance Department

16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- 4 Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
 - the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
 - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
 - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the point of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	1	Ra	te (British Syste	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks			
No	·	Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	601.90		cu.m	212.55						
2	Weaving matresses.	100Cft.	1140.50		cu.m	402.75						
3	 Supplying and filling jute bags 1.25 (0.035 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	17.80	30.20	Per Baq	17.80	30.2		The rate does not include supply of sand or earth for filling bags, which will be paid extra.			
	 Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water. 	ditto	27.70	40.10	Per Baq	27.70	40.1		-ditto-			
4	 a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	42.65	89.45	Per Bag	42.65	89.45		The rate does not include supply of sand or earth for filling bags, which will be paid extra.			

	MRS, BI-ANNUAL PERIOD (1st FE	VALLEY	KHUSHAB						
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	 b) Supply and filling new jute bags 4 to 5 cft (0.11 to 0.14 cu.m) capacity, with sand or earth, sewing and laying in position, under water. Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled 	ditto	60.90	107.70	ditto	60.90	107.7		-ditto-
	with sand or earth:- a) 1st chain (30 m)	100 Nos	158.40		% Nos	158.40			
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	57.00	5	Per 30 m Per 100 Nos/	57.00			
	 c) 5th and subsequent chains (150 m and subsequent every 30 m) 	ditto	22.20		ditto	22.20			
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-								
	a) 1st chain (Ist 30 metre)	100 Nos	633.60	Depar	% Nos	633.60			
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	221.75		Per 30 m per %Nos	221.75			
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	85.55		ditto	85.55			
7	Rolling matresses to river edge and floating, after unroling:-								
	a) area of matress upto 2,000 Sft. (186 sq.m)	100Sft.	356.40		sq.m	38.35			
	 b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m) 	100Sft.	594.00		sq.m	63.90			
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	693.00		ditto	74.55			
8	Sewing empty cement bags in sheets.	100 Nos	554.40	582.40	% Nos	554.40	582.4		
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	772.20	844.45	cu.m	272.75	298.25		Measured in the shape of compact round bundles and of size specified

	MRS, BI-ANNUAL PERIOD (1st FE	VALLEY	KHUSHAB						
Sr.	Description	Ra	ate (British Syste	em)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
									for the work, before filling at site.
10	Launching the above and placing in position.	100Cft.	380.15		cu.m	134.25			
11	Supply within 5 chains (150 m):-								
	a) Boulders 9" (225 mm) and above	100Cft.	1146.80		cu.m	405.00			
	b) Over size shingle 3" to 9"(75 to 225 mm)	ditto	766.65		ditto	270.75			
	c) Mixed graded shingle	ditto	909.20		ditto	321.10			
12	Supplying Munj or Patha Trungers 6" (150 mm) mesh to hold 3 Cft. (0.085 cu.m)	Each	49.50	80.90	Each	49.50	80.9		
13	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to make crate):-								
	a) 6" (150 mm) mesh]袋.				
	i) 15 SWG wire ii) 10 SWG wire	100Sft. ditto	568.25 608.85	827.00 1448.85	sq.m ditto	61.15 65.50	89.00 155.90		
	iii) 8 SWG wire	ditto	608.85	1925.95	ditto	65.50	207.25		
	b) 4" (100 mm) mesh		* SA	R. P	Sec.				
	i) 15 SWG wire ii) 10 SWG wire	100Sft. ditto	730.60 811.80	1119.55 2069.30	sq.m	78.60 87.35	120.45 222.65		
	iii) 8 SWG wire	ditto	811.80	2783.30	ditto ditto	87.35	222.03 299.50		
14	Providing and laying shingle on top of bund, including handling of materials within three chains.	100Cft.	396.00	686.40	cu.m	139.85	242.40		
15	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)								
	a) stone or boulder	100Cft.	693.00	1089.00	cu.m	244.75	384.6		The rate includes supply of brick
	b) shingle or spawlc) brick bats	ditto ditto	693.00 534.60	983.40 1326.60	ditto ditto	244.75 188.80	347.3 468.55		bats to site of work.
16	Supply and dumping by boat, including loading into boat within three chains (90 m) lead, and hire charges of boat and boatman.								The rate includes supply of brick bats to site of work.
	a) stone or boulder	100Cft.	1234.20	1630.20	cu.m	435.90	575.8		
	b) shingle or spawl	ditto	1234.20	1524.60	ditto	435.90	538.50		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	/stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	c) brick bats	ditto	1075.80	1867.80	ditto	379.95	659.70						
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	930.60	1722.60	cu.m	328.70	608.4		The rate includes supply of brick bats to site of work.				
18	Supplying and filling bricks in crates and hand packing (excluding cost of crates).	100Cft.	1128.60	12288.60	cu.m	398.60	4340.35		The rate includes supply of bricks to site of work.				
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-												
	i) stone or boulderii) shingle or spawl	100Cft. ditto	1287.00 1287.00	1683.00 1577.40	cu.m ditto	454.55 454.55	594.45 557.15						
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	139.40	J -	cu.m	49.25	-						
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	696.95		cu.m	246.15	-						
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	396.00	796.00	sq.m	42.60	85.65	30.1					
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	990.00	1030.00	sq.m	106.50	110.85	ditto					
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1 ¹ / ₂ ' (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	2239.35	3178.45	sq.m	240.95	342.00		The cost of placing earth between rolls shall be paid separately, as earthwork.				
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	749.45	810.90	sq.m	80.65	87.25		Measurement to be made of the area of elevation on one face only.				
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	1290.95	1364.35	sq.m	138.90	146.8						
27	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	811.80	1484.10	cu.m	286.75	524.2						
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	2702.70	3300.30	cu.m	954.60	1165.65						

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY, 1	2012 TO 31s	t JULY, 201	2) TEH:N	OWSHEF	IRA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
29	Providing and laying stone pitching, for top layer only:-								
	a) one slopeb) on level	100Cft. ditto	2197.80 1999.80	2795.40 2597.40	cu.m ditto	776.25 706.35	987.35 917.4		
30	Providing and laying stone or spawl filling:-								
	a) on level	100Cft.	564.30	828.30	cu.m	199.30	292.55		
	b) on slope	ditto	719.15	983.15	ditto	254.00	347.25		
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.			5					
	 i) top layer on slope ii) top layer on level iii) stone pitching/filling on slope or on level (other than top layer). 	100Cft. ditto ditto	2981.90 2783.90 1582.00	5311.45 5113.45 3986.30	cu.m ditto ditto	1053.20 983.25 558.75	1876.00 1806.05 1407.95		
32	Grouting stone pitching or apron, etc. in:-	1996			55				
	a) cement, sand mortar 1:3b) cement, sand mortar 1:8	100Sft. ditto	966.25 831.60	4335.00 2563.55	sq.m ditto	103.95 89.50	466.45 275.85		
33	Sand grouting in stone apron, with high pressure hose.	100Sft.	332.65	992.65	sq.m	35.80	106.80		
34	Grouting stone filling or pitching, with bajri.	100Cft.	495.00	1179.00	cu.m	174.85	416.4		
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	2027.50	-	cu.m	716.10	-		
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cft.	633.60	-	cu.m	223.80	-		
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	564.30	1248.30	cu.m	199.30	440.90		
38	Grouting jharies between blocks with bajri.	100Cft.	564.30	1020.30	cu.m	199.30	360.35		
39	Breaking stone into spawls and stacking	100Cft.	475.20	-	cu.m	167.85	-		
	Canal and Roads								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-												
	a) upto 2.0' (600 mm) F.S. depth	Each	16.00	-	Each	16.00	-						
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	18.00	-	ditto	18.00	-						
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	24.00	-	ditto	24.00	-						
	d) above 4.0' (1200 mm) F.S. depth	ditto	59.95	-	ditto	59.95	-						
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-		~	5									
	 a) i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead. 	100 Nos	792.00	820.00	% Nos	792.00	820.00						
	ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	324.70		100 Nos	324.70	-						
	iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	465.70	R C	100 Nos	465.70	-						
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	39.60	61.45	Per 30 Metre of one row	39.60	61.45						
	 v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	589.50	739.90	ditto	589.50	739.90						
	 b) i) Cutting and supplying unsharpened pegs 4.0' (1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	79.65	111.50	100 Nos	79.65	111.50						
	ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	324.70	-	100 Nos	324.70	-						
	iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	563.90	-	100 Nos	563.90	-						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	39.60		Per 30 M of one row	39.60							
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	1405.80		ditto	1405.80							
c	 i) Cutting and supplying unsharpened pegs 5.0' (1.5 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	99.65	139.50	100 Nos	99.65	139.50						
	ii) Sharpening one end of 5' (1.5 m) long pegs, 3" to6" (75 to 150 mm) dia.	100 Nos	341.35		100 Nos	341.35	-						
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	649.45		100 Nos	649.45	-						
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	39.60	61.45	Per 30 M of one row	39.60	61.45						
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	Per chain of one row	623.70	834.10	ment	623.70	834.10						
c	 i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1584.00	1631.85	100 Nos	1584.00	1631.85						
	ii) Sharpening one end of 6' (1.8 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	406.30	-	100 Nos	406.30	-						
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	779.35	-	100 Nos	779.35	-						
	iv) Tying pegs with Munj, Patha ban (one line,	Per			Per Chain								

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY,	2012 TO 31s	st JULY, 201	2) TEH:N	OWSHEH	IRA, SOAN	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	ystem)	Spec.	Remarks											
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.												
	incuding tying around the pegs).	Chain of one row	39.60	61.45	of one row	39.60	61.45													
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	1603.80	1859.30	ditto	1603.80	1859.30													
	 e) i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1188.00	1287.20	100 Nos	1188.00	1287.20													
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	519.55		100 Nos	519.55	-													
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3" to 6" (75 to 150 mm) dia driven 2' (600 mm) below the available bed or ground (average).	100 Nos	860.10		100 Nos	860.10	-													
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per chain of one row	39.60	51.70	Per 30 M of one row	39.60	51.7													
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	Per Chain of one row	1811.70	2112.30	Per 30 M of one row	1811.70	2112.30													
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-																			
	 a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2¹/₂" to 5" (63 m to 125 mm) dia. 	100 Nos	6600.00	-	100 Nos	6600.00	-													
	 ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	454.60	-	100 Nos	454.60	-													
	iii) Driving Bamboos 8'-1" to $10.0'$ (2.46 to 3.05 m) long $2\frac{1}{2}"$ to 5" (63 to 125 mm) dia, driven 2.5' (750 mm) below the available bed or ground (average).	100 Nos	941.70	-	100 Nos	941.70	-													

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	59.40	93.65	Per 30 M of one Row	59.40	93.65						
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	2217.60	2608.00	ditto	2217.60	2608.00						
b	i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2 ¹ / ₂ " to 5" (63 to 125 mm) dia.	100 Nos	-	10200.00	100 Nos	-	10200						
	 ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	519.55	9-	100 Nos	519.55	-						
	 iii) Driving Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long 2¹/₂" to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average). 	100 Nos	1022.45		100 Nos	1022.45	-						
	iv) Tying Bamboos $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	198.00	808.70	Per 30 M of one Row	198.00	808.70						
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	2717.55	3213.55	ditto	2717.55	3213.55						
c)	 i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	-	10800.00	100 Nos	-	10800.00						
	 ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	584.50	-	100 Nos	584.50	-						
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long $2\frac{1}{2}$ " to 5" dia, driven 3.5 ' (1.07 mm) below the available bed or ground (average).	100 Nos	1169.00	-	100 Nos	1169.00	-						
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	198.00	808.70	Per 30 M of one row	198.00	808.70						
	v) Cutting and supplying brushwood from canal	ditto	3217.50	3788.70	ditto	3217.50	3788.70						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).												
	 d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	-	12000.00	100 Nos	-	12000.00						
	ii) Sharpening one end of 14'-1" to 16.0' (4.30 to 4.90 m) long Bamboos, $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia.	100 Nos	649.45	-	100 Nos	649.45	-						
	 iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average). iii) Tving Bamboos 216" to 5" (62 to 125 mm) dia with 	100 Nos Per Chain	1298.90	-	100 Nos Per 30 M	1298.90	-						
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	of one Row	198.00	808.70	of one Row	198.00	808.70						
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	3702.60	4363.95	ditto	3702.60	4363.95						
	 e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	- A	12600.00	100 Nos	-	12600.00						
	ii) Sharpening one end of 16'-1" to 20' (4.9 to 6.10 m) long Bamboos, 2 ¹ / ₂ " to 5" (63 to 125 mm) dia.	100 Nos	779.35	Depar	100 Nos	779.35	-						
	 iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average). 	100 Nos	1558.65	-	100 Nos	1558.65	-						
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	198.00	808.70	Per 30 M of one row	198.00	808.70						
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	4633.20	5474.80	ditto	4633.20	5474.80						
43	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	198.00	258.00	cu.m	69.95	91.15		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.				

	MRS, BI-ANNUAL PERIOD (1st FE	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	Rate (British System) Rate (Metric System)		Rate (British System) Rate (Metric System		Spec.	Remarks							
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
44	Filling brush wood only, thoroughly packed.	100Cft.	158.40	-	cu.m	55.95	-		Measured in compacted and packed shape before filling.					
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	380.15	-	Per 30 M	380.15	-							
46	 a) Gachi pitching 1' (300 mm) thick. b) Gachi pitching done with silt clearance and berm dressing. 	100Sft. 100Sft.	2059.20 1742.40		Sq.m Sq.m	221.55 187.50								



Finance Department

17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FE	HEHRA, SO	AN VALLE	Y KHUSHAB					
Sr.	Description	1	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.
	a) channels, discharge upto 50 cusecs.	Job	660.00	-	Job	660.00	-	17.5	
	b) channels, discharge from 51 to 100 cusecs.	Job	871.20	_	Job	871.20	-		
	c) channels, discharge from 101 to 200 cusecs.	Job	1320.00	*)	Job	1320.00	-		
	d) channels, discharge from 201 to 350 cusecs.	Job	1782.00	-	Job	1782.00	-		
	e) channels, discharge over 350 cusecs.	Job	2640.00		Job	2640.00	-		
2	Dismantling outlets:-	84			72	ý.		18.1	These rates are for total dismantlement and removal
	a) old types, such as K.G.O's orifices, etc.	Each	660.00	هومت چک	Each	660.00	-		of material. The rates do not include earth work for which
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	990.00	Z S	ditto	990.00	-		rates are given in item 1, above.
	 A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm) 	ditto 🥤	1320.00	в Двра	ditto	1320.00	-		above.
	 A.P.M. or O.F., "H" above 3.0'. (900 mm) 	ditto	1650.00	-	ditto	1650.00	-		
	e) Tail cluster bifurcation	ditto	990.00	-	ditto	990.00	-		
	f) Tail cluster trifurcation	ditto	1320.00	-	ditto	1320.00	-		
	g) Tail cluster quardification	ditto	1650.00	-	ditto	1650.00	-		
3	Making temporary A.P.M. bricks block and fixing at site.	Each	352.85	642.95	Each	352.85	642.95	21.1 & 21.2	
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	720.70	-	Job	720.70	-	18.1, 21.1 & 21.2	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
5	Dismantling walls and fitting iron block of O.F. outlet.	Each	720.70	-	Each	720.70	-	18.1, 21.1 & 21.2					
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to 17.2					
	 a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth 	Each ditto	1584.00 2138.40	-	Each ditto	1584.00 2138.40	-						
7	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	377.50	780.85	Each	377.50	780.85	18.1, 21.1 & 21.2					
8	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	732.60	1387.20	Each	732.60	1387.20	ditto					
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-	1			JU			21.1 & 21.2	Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no O.F. iron block.				
	a) for channel depth of 5.0'. (1.5 m)	Each	855.35	971.05	Each	855.35	971.05		O.I. HOH DICK.				
	b) for channel depth of 4.0° . (1.2 m)	ditto	641.50	757.20	ditto	641.50	757.20						
	 c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) 	ditto ditto	513.20 427.70	628.90 517.75	ditto ditto	513.20 427.70	628.90 517.75						
	 e) for channel depth of less than 2.0'. (600 mm) 	ditto	342.15	406.60	ditto	342.15	406.60						
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	352.85	531.35	Each	352.85	531.35						
11	Laying iron pipes for outlets.	Per Lft.	17.10	r Depa	Metre	56.15	-	21.1, 21.2 & 17.1 to 17.5					
12	Water allowance for constructing outlets or culverts, when	Each	322.10		Each	322.10			At the discretion of the				
	canal water is not flowing.		to 660.00			to 660.00			Engineer-in-charge depending upon the distance and source of supply.				
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	261.35	-	Each	261.35	-						
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2					
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	64.00 28.80	71.75 36.50	Metre ditto	210.05 94.40	235.35 119.7						

	MRS, BI-ANNUAL PERIOD (1st FE	BRUAR	7, 2012 TO 3	1st JULY, 2	012) TEI	H:NOWSH	HEHRA, SO	AN VALLE	Y KHUSHAB
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 Removing pipe outlet, refilling earth and puddling. a) portion under bank. b) portion under road, beyond bank. Changing pipe outlets by removing one pipe and replacinş it at the same site with another pipe complete with earth and puddling. 	Rft. ditto	52.80 19.80	- -	Metre ditto	173.25 64.95	-	17.1 to 17.5	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	75.00 37.50	82.70 45.20		246.00 123.00	271.3 148.3		



Finance Department

18. ROAD & ROAD STRUCTURE

1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".

- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 3 The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 20)12 TO 31st	JULY, 2012	2) TEH:N	OWSHEH	RA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British Sys	tem)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Sub-base & base construction								
1	Providing and laying sub-base course of brick on edge 41/2" (113 mm) thick, including compaction to required camber and grade.	100Cft.	2359.80	13066.20	cu.m	833.50	4615.00	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	1917.60	2893.20	cu.m	677.30	1021.90	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.
3	a) Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and. aggregate.	Gin	Se ance 9	KB Despart	d nont			ditto	
	i) Pit run or bed run gravel.ii) Crushed stone aggregate.	100Cft. 100Cft.	1917.60 1917.60	2277.60 2565.60	cu.m cu.m	677.30 677.30	804.45 906.15		
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
									 2) It shall be payable from the nearest approved quarry. 3) The quantity of pit run

Sr. No.	Description	R	ate (British Sys	tem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
									or bed run gravel and crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft.
4	a) Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and.	100Cft.	2125.50	4013.10	cu.m	750.75	1417.45	501-1 to 501-6	
	aggregate. b) Subsequent carriage of crushed stone aggregate.	100Cft. of console-							 The carriage for the whole distance to the site of work shall be
		dated base							calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
		Fin	ance 9	Depart:	ment				
									 It shall be payable from the nearest approved quarry. The quantity of crushed stone aggre for payment of carriage shall be taken a actual loose volume but not more than Cft.
5	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	5.45	26.85	Metre	17.85	88.15	552-1 to 552-5	
	Bituminous Work & Resurfacing.								
6	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre.	100Sft.	79.20	993.65	sq.m	8.50	106.90	601-1 to 601-6	
7	Providing and laying bituminous tack coat, using 10 lbs. of bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.)	100Sft.	79.20	492.20	sq.m	8.50	52.95	611-1 to 611-5	
8	 Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate o 							612-1 to 612-6	

	Description	R	ate (British Sys	tem)	Rat	e (Metric Sy	vstem)	Spec. No.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite	N0.	
	approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.								
	1) 1st coat:-								
	i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre	100Sft.	81.15	2019.85	Sq.m	8.75	217.35		
	ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size ³ / ₄ " (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre.	100Sft.	81.15	1764.20	Sq.m	8.75	189.85		
	2) 2nd coat:-		1.00		495				
	 i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size ¹/₂" (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 	100Sft.	62.45	1262.65	Sq.m	6.70	135.85		
	ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8"(10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre.	100Sft.	62.45	927.00	Sq.m	6.70	99.75		
	3) 3rd coat:-								
	14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¹ 4" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	42.70	713.85	sq.m	4.60	76.80		
b)	Subsequent carriage of crushed stone aggregate/bajri,	100Cft.			cu.m				 The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rai as the case may be.

Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work.		*					612-1 to 612-6	2) It shal be payable from the nearest approved quarry.
Ī	 i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m. ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre. b) Subsequent carriage of crushed stone aggregate/bajri. 	100Sft. 100Sft. 100Cft.	54.10 54.10	1111.55 1009.60	sq.m sq.m cu.m	5.80 5.80	119.60 108.65		Same remarks as against item 8(b) above.
	 Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density. (i) 3% Bitumen (ii) 3.5% Bitumen (iii) 4% Bitumen (iv) 4.5% Bitumen (v) 5% Bitumen (vi) 5.5% Bitumen (vii) 6% Bitumen 	per inch thickness per 100Sft. -do- -do- -do- -do- -do- -do- -do- -do	1030.30 1030.30 1030.30 1030.30 1030.30 1030.30 1030.30	2936.10 3189.65 3443.15 3696.65 3949.95 4203.65 4457.15	per 25mm thickness per Sq.m -do- -do- -do- -do- -do- -do- -do- -do	110.90 110.90 110.90 110.90 110.90 110.90 110.90	316.05 343.35 370.60 397.90 425.15 452.50 479.75	641-1 to 642-6	
	Scarifying old road surface including removal of debris within 1 chain (30 m).	100Sft.	132.00	-	Sq.m	14.20	-		
:	Incidental Construction								
12	Providing R.C.C. railing on bridges, as per standard drawing.	Per Rft.	69.45	778.20	Metre	227.90	2553.10	901-1 to 901-4	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of bindin;

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British Syst	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
13	Providing and fixing G.I. pipe railing, as per standard drawing.	Per Rft. of 3 rows of Pipes	51.95	632.15	Metre	170.45	2074.00	ditto	wire and removal of rust from the bars, etc.				
	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end		2184.00	Each set of one end	-	2184.00	911-1 to 911-6					
	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch	- C	15.60	cu.cm	-	0.95	ditto					
	Providing and laying expansion joint of neoprine strip 4"x ¹ /4" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	41.60	159.90	Metre	136.40	524.65	921-1 to 921-4					
17	Providing and fixing rain water outlet of A.C. pipe.	Each	20.80	197.40	Each	20.80	197.40	931-1 to 933-4					
18	Providing and erection at site of work:-	1000	S.S.S.	S C P				941-1 to 941-5	The rate is for complete item of work according to Standard design				
	 i) R.C.C. mile/Km. stone ii) R.C.C. furlong/½ Km. stone iii) R.C.C. boundary pillar. iv) Sign post of M.S. plate 1/8" thick (3 mm) 	Each Each Each	1333.00 67.20 127.85	3262.10 261.90 437.55	Each Each Each	1333.00 67.20 127.85	3262.10 261.90 437.55		including cement concrete foundation block and painting letters etc.				
	a) Mandatory.b) Warning/Direction/Informatory.	Each Each	432.75 419.75	3766.65 3526.20	Each Each	432.75 419.75	3766.65 3526.20						
	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	1650.35	12356.75	cu.m	582.90	4364.40		The nominal thickness of bricks (2-11/16") shall be taken for the purpose of measurement and payment. (9" x 4-3/8"x 2-11/16")				

19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- 1 Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, BI-ANNUAL PERIOD (1s	t FEBRL	JARY, 2012	TO 31st JUL	Y, 2012) TEH:NO	WSHEHRA	, SOAN VA	LLEY KHUSHAB
Sr. No.	Description]	Rate (British Sy	stem)	Ra	ate (Metric S	ystem)	Spec. No.	Remarks
INU.		Unit	Labour	Composite	Unit	Labour	Composite	110.	
	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-				_				
	i) white ii) coloured	Each Each	207.90 207.90	1,840.00 1,998.40	Each Each	207.90 207.90	1,840.00 1,998.40		
2	Providing and fixing, double seat and cover only.		*E			<u>从</u>			
	i) bakelite ii) plastic	Each Each	2.15 2.15	314.15 218.15	Each Each	2.15 2.15	314.15 218.15		
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.				I	3			
	i) white ii) coloured	Each Each	153.45 153.45	1,034.95 1,202.95	Each Each	153.45 153.45	1,034.95 1,202.95		
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	153.45	1,807.05	Each	153.45	1,807.05		
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	153.45	464.95	Each	153.45	464.95		
6	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.								
	i) white, with pedestalii) coloured, with pedestal	Each Each	202.95 202.95	2,181.75 2,328.15	Each Each	202.95 202.95	2,181.75 2,328.15		
	iii) white, without pedestaliv) coloured, without pedestal	Each Each	178.20 178.20	1,473.00 1,530.60	Each Each	178.20 178.20	1,473.00 1,530.60		
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	178.20	4,042.65	Each	178.20	4,042.65		
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18")	Each	178.20	937.45	Each	178.20	937.45		

	MRS, BI-ANNUAL PERIOD (1s	t FEBRI	JARY, 2012	TO 31st JUL	Y, 2012)) TEH:NO	WSHEHRA	, SOAN V/	ALLEY KHUSHAB
Sr.	Description		Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	-
	with drain board of mosaic, including bracket set, waste pipe and waste coupling.								
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-								
	 i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18") 	Each Each	178.20 178.20	1,438.45 1,288.45	Each Each	178.20 178.20	1,438.45 1,288.45		
10	Providing and fixing glazed earthen ware flat back urinal.	Each	103.95	767.55	Each	103.95	767.55		
11	Providing and fitting glazed earthen ware low down flushing cistern 13,63 litres (3 gallons) capacity, including bracket set, copper connection, etc.		/	*)					
	i) white ii) coloured	Each Each	178.20 178.20	1,119.75 1,200.15	Each Each	178.20 178.20	1,119.75 1,200.15		
12	Providing and fitting plastic made low down flushing cistern 1363 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.		A SHA		T				
	i) white ii) coloured	Each Each	178.20 178.20	945.75 945.75	Each Each	178.20 178.20	945.75 945.75		If rubber connection is used, the composite rate will be reduced by Rs. 12.50
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	178.20	1,125.70	Each	178.20	1,125.70		
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.								
	 i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity 	Each Each	188.60 188.60	2,204.10 1,424.10	Each Each	188.60 188.60	2,204.10 1,424.10		
15	Providing and fixing, chromium plated soap dish.	Each	10.40	174.80	Each	10.40	174.80		
16	Providing and fitting, glazed earthen ware soap dish.								
	i) white ii) coloured	Each Each	10.40 10.40	438.80 216.80	Each Each	10.40 10.40	438.80 216.80		
17	Providing and fixing, chromium plated toilet paper holder.	Each	13.85	383.40	Each	13.85	383.40		
18	Providing and fixing, chromium plated towel rail:-								

	MRS, BI-ANNUAL PERIOD (1s	t FEBRL	JARY, 2012	TO 31st JUL	Y, 2012)	TEH:NO	WSHEHRA	, SOAN VA	LLEY KHUSHAB
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 60 cm (24") long, and 2 cm (³/₄") dia. ii) 50 cm (20") long, and 1.5 cm (¹/₂") dia. 	Each Each	13.85 13.85	323.45 263.45	Each Each	13.85 13.85	323.45 263.45		
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	26.00	342.80	Each	26.00	342.80		
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-								
	 i) with chromium plated brackets and railing. ii) glass shelf only, without chromium plated brackets and railing. 	Each Each	32.50 20.80	321.60 66.40	Each Each	32.50 20.80	321.60 66.40		
21	Providing and fitting glazed earthen ware shelf 60x13 cm (24"x5"), with chromium plated bracket and railing:-								
	i) Whiteii) Coloured	Each Each	32.50 32.50	822.00 942.00	Each Each	32.50 32.50	822.00 942.00		
22	Providing and fitting:-		7_139	-4-	So .	LE -			
	 i) plastic soap dish ii) plastic toilet paper holder iii) plastic towel rail iv) plastic shelf 60x13 cm (24"x5") with bracket and railing. 	Each Each Each Each	10.40 13.85 13.85 13.85	135.75 199.80 217.80 398.95	Each Each Each Each	10.40 13.85 13.85 13.85 13.85	135.75 199.80 217.80 398.95		
23	Providing and fixing chromium plated pillar-cock, heavy:-		_30 20*/3* 10*-10400*3*		pr 100 10 10 10 10 10 10 10 10 10 10 10 10	27 28-284° 27 18- 89°			
	i) 2 cm (¾") ii) 1.5 cm (½")	Each Each	13.85 13.85	493.85 651.05	Each Each	13.85 13.85	493.85 651.05		
24	Providing and fixing chromium plated stop cock, heavy:-								
	i) 2 cm (¾") ii) 1.5 cm (½")	Each Each	13.85 13.85	259.85 173.45	Each Each	13.85 13.85	259.85 173.45		
25	Providing and fixing underground stop cock 13 mm (1/2"), with chromium plated cover.	Each	20.65	444.70	Each	20.65	444.70		
26	Providing and fixing chromium plated bib cock:- i) 2 cm (³ / ₄ ") ii) 1.5 cm (¹ / ₂ ")	Each Each	13.85 13.85	325.85 299.45	Each Each	13.85 13.85	325.85 299.45		
27	Providing and fixing chromium plated tee stop cock 15mm (1/2").	Each	13.85	426.65	Each	13.85	426.65		

	MRS, BI-ANNUAL PERIOD (1s	t FEBRL	JARY, 2012	TO 31st JUL	.Y, 2012)	TEH:NO	WSHEHRA	, SOAN V	ALLEY KHUSHAB
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
28	Providing and fixing chromium plated shower rose:-								
	i) 1.5x10 cm (½"x4") ii) 2x15 cm (¾"x6")	Each Each	13.85 13.85	312.65 373.85	Each Each	13.85 13.85	312.65 373.85		
29	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.	Each	17.35	1,448.95	Each	17.35	1,448.95		
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)
	 i) 30 mm (1¼") dia ii) 40 mm(1½") dia iii) 50 mm(2") dia iv) 65 mm(2½") dia v) 80 mm(3") dia 	Each Each Each Each Each	20.80 20.80 20.80 20.80 20.80	404.80 560.80 764.80 1,208.80 1,790.80	Each Each Each Each Each	20.80 20.80 20.80 20.80 20.80	404.80 560.80 764.80 1,208.80 1,790.80		will be reduced by Rs. 66, 77, 95, 107 and 120 respectively.
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (1/2") dia.		*E			1			
	i) single wayii) two wayiii) three way	Each Each Each	13.85 20.80 27.70	349.85 602.80 729.70	Each Each Each	13.85 20.80 27.70	349.85 602.80 729.70		
32	Providing and fixing, union brass cock.			D P C	E S				
	i) 13 mm (¹ / ₂ ") dia ii) 20 mm (³ / ₄ ") dia	Each Each	13.85 13.85	121.85 205.85	Each Each	13.85 13.85	121.85 205.85		
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-								
	 i) 10x5 cm (4"x2") ii) 10x7.5 cm (4"x3") 	Each Each	41.60 41.60	340.55 340.55	Each Each	41.60 41.60	340.55 340.55		
34	Providing and fitting "P" trap:-								
	 i) 10 cm (4") of cast iron. ii) 10 cm (4") glazed. 	Each Each	34.65 34.65	406.40 100.40	Each Each	34.65 34.65	406.40 100.40		
35	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	52.00	582.25	Each	52.00	582.25		
36	Providing and fitting, cast iron soil pipe with:-								
	i) lead caulked, yarn joint:-								

	MRS, BI-ANNUAL PERIOD (1	WSHEHRA	, SOAN V	ALLEY KHUSHAB					
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 10 cm (4") i/d b) 5 cm (2") i/d	Per foot Per foot	18.40 7.35	186.75 94.10	Metre Metre	60.40 24.15	612.55 308.65		
37	 ii) cement caulked joint:- a) 10 cm (4") i/d b) 5 cm (2") i/d Providing and fitting, A.C. soil pipe with cement caulked joint, including all specials:- 	Per foot Per foot	3.90 1.55	119.80 82.90	Metre Metre	12.85 5.15	392.90 271.95		
	i) 60 (2 ¹ / ₄)" mm i/d ii) 80 (3") mm i/d iii) 100 (4") mm i/d iv) 150 (6") mm i/d	Per foot Per foot Per foot Per foot	3.15 3.50 3.90 5.25	25.40 61.95 96.45 121.10	Metre Metre Metre Metre	10.30 11.45 12.85 17.15	83.25 203.20 316.45 397.20		
38	 Providing and fitting cast iron specials, such as tee bend, collar, cross, etc. plain type:- i) lead caulked joint ii) cement caulked joint 	Kg Kg	14.85 9.00	135.20 101.55	Kg Kg	14.85 9.00	135.20 101.55		In case of plug type, the composite rate shall be increased by Rs.2 per kg.
39	Supply and fitting of cast iron manhole cover with frame, etc. complete. i) 30 cm (12") dia ii) 45 cm (18") dia	Each Each	20.80 20.80	164.80 812.80	Each Each	20.80 20.80	164.80 812.80		
40	iii) 60 cm (24") diaProviding and fitting R.C.C. pipe 10 cm (4") dia, including laying and jointing in trenches.	Each Per foot	34.30 9.20	1,366.30 33.20	Each Metre	34.30 30.20	1,366.30 108.90		
41	Providing and fitting chromium plated or oxidised, gas cock 6'mm (¼"):-								
	 i) single way ii) two way iii) three way 	Each Each Each	13.85 20.80 27.70	179.45 272.80 465.70	Each Each Each	13.85 20.80 27.70	179.45 272.80 465.70		
42	Providing and fitting nipple or bush, 6 mm to 10 mm (¼" to 3/8") i/d.	Each	10.40	22.40	Each	10.40	22.40		
43	Providing and fixing, brass gas cock:-								
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	2.15 78.75	74.15 92.15	Each Each	2.15 78.75	74.15 92.15		

	MRS, BI-ANNUAL PERIOD (1	st FEBRI	JARY, 2012	TO 31st JUL	Y, 2012) TEH:NO	WSHEHRA	, SOAN VA	LLEY KHUSHAB
Sr.	Description		Rate (British Sy	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
44	Providing and fixing brass stop cock/bib cock:-								
	a) 15 mm (¹ / ₂ ") dia b) 20 mm (³ / ₄ ") dia	Each Each	3.45 3.45	73.05 111.45	Each Each	3.45 3.45	73.05 111.45		
45	Hoisting and placing in position, precast R.C. latrine seats.	Each	207.90	-	Each	207.90	-		
	Replacement								
1	Providing and fixing, chromium plated waste coupling:-								
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	20.80 20.80	98.80 104.80	Each Each	20.80 20.80	98.80 104.80		
2	Providing and fixing rubber plug with chain:-					1.1.			
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	0.85 0.85	39.25 42.85	Each Each	0.85 0.85	39.25 42.85		
3	Providing and fixing, waste pipe of PVC:-		7_189	-15-	£.	L.S.			
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	10.40 10.40	40.40 46.40	Each Each	10.40 10.40	40.40 46.40		
4	Providing and fixing, flushing bend of PVC.		Tina	rce De	parti	nent			
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	9.25 9.25	33.25 39.25	Each Each	9.25 9.25	33.25 39.25		
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-								
	i) 3 cm (1¼") i/d ii) 4 cm (1½")	Each Each	20.80 20.80	524.80 620.80	Each Each	20.80 20.80	524.80 620.80		
6	Providing and fixing, angle iron brackets for:-								
	i) wash hand basin and cisternii) sinks	Each Each	20.80 20.80	133.60 145.60	Each Each	20.80 20.80	133.60 145.60		
7	Providing and fixing 1.5 cm (1/2") dia connection, including check nuts, etc.:-								
	i) plastic rubber connectionii) copper connection	Each Each	8.30 8.30	38.30 80.30	Each Each	8.30 8.30	38.30 80.30		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB													
Sr.	Description Rate (British System) Rate (Metric System)		System)	Spec.	Remarks									
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
8	Providing and fixing brass ball float valve:-													
	i) $1.5 \text{ cm} (\frac{1}{2})$ dia	Each	17.35	203.35	Each	17.35	203.35							
	ii) 2.0 cm (¾") dia	Each	17.35	257.35	Each	17.35	257.35							
	iii) 2.5 cm (1") dia	Each	17.35	317.35	Each	17.35	317.35							
	iv) 3 cm (1 ¹ / ₄ ") dia	Each	17.35	341.35	Each	17.35	341.35							
	v) $4.0 \text{ cm} (1\frac{1}{2})$ dia	Each	17.35	485.35	Each	17.35	485.35							
	vi) 5 cm (2") dia	Each	17.35	845.35	Each	17.35	845.35							



Finance Department

20. SURFACE DRAINAGE

1. Specification No. correspond to Book of Specification (B & R Department) Vol. 11, 1966 (public Health Works).

2. Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBF	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, S									
Sr.	Description]	Rate (British Sy	stem	Rat	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-			5				17.1			
	 a) 3" thick (75 mm) i) ratio 1:3 ii) ratio 1:5 B) 4¹/₂" thick (113 mm) 	100Rft ditto	756.85 756.85	3,225.40 3,071.95	Metre ditto	24.80 24.80	105.80 100.75				
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,134.15 1,134.15	4,689.50 4,455.30	ditto ditto	37.20 37.20	153.80 146.15				
2	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled and struck flush:-	Ti	nance	Depar	imeni			17.1			
	 a) ratio 1:3 b) ratio 1:5 c) ratio 1:6 	100Sft. ditto ditto	1,118.30 1,118.30 1,118.30	4,564.80 4,317.20 4,247.45	Sqm. ditto ditto	120.35 120.35 120.35	491.20 464.55 457.05				
3	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1			
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,599.85 1,599.85 1,599.85	6,797.20 6,399.85 6,301.05	Sqm. ditto ditto	172.15 172.15 172.15	731.40 688.60 678.00				
4	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2			

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	2012 TO 31s	st JULY, 201	12) TEH:N	NOWSHE	HRA, SOAN	N VALLEY	KHUSHAE
Sr.	Description]	Rate (British Sy	stem	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	 a) ratio 1:3 b) ratio 1:5 c) ratio 1:6 Pacca brick on edge, Herring bond pitching in cement, 	100Sft. ditto ditto	1,037.50 1,037.50 1,037.50	4,484.05 4,236.40 4,166.65	Sqm. ditto ditto	111.65 111.65 111.65	482.50 455.85 448.35	17.2	
5	sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3	100Sft.	1,584.00	6,781.40	Sqm.	170.45	729.70		
	b) ratio 1:5	ditto	1,584.00	6,384.00	ditto	170.45	686.90		
	c) ratio 1:6	ditto	1,584.00	6,285.20	ditto	170.45	676.30		
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ½ :5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ¼" (6 mm) thick, as per Engineer's drawing (excluding excavation):-	-var all						17.1	
	a) Type I	Per Rft	24.95	75.05	Metre	81.85	246.20		
	b) Type II	ditto ditto	49.90 63.25	136.50 175.20	ditto ditto	163.65 207.50	447.65 574.55		
	c) Type III d) Type IV	ditto	03.25 75.35	208.70	ditto	207.50	574.55 684.60		
	e) Type V	ditto	99.00	284.60	ditto	324.70	933.50		
	f) Type VI	ditto	113.80	325.85	ditto	373.25	1,068.75		
	g) Type VII	ditto	126.10	358.50	ditto	413.65	1,175.95		
	h) Type VIII	ditto	140.85	402.25	ditto	462.05	1,319.40		
	i) Type IX	ditto	187.15	572.00	ditto	613.90	1,876.20		
	j) Type X	ditto	205.60	626.85	ditto	674.45	2,056.00		
	k) Type XI	ditto	230.00	697.10	ditto	754.35	2,286.55		
	I) Type XII	ditto	245.20	739.00	ditto	804.20	2,424.00		
7	Laying R.C.C hume pipes in position, including jointing:- a) 6" to 12" (150 mm to 300 mm) dia	Per Lft.	45.15	48.00	Metre	148.05	157.50		
	b) 12" to 24" (300 mm to 600 mm) dia	ditto	68.90	74.65	ditto	226.00	244.90		
	c) 24" to 36" (600 mm to 900 mm) dia	ditto	90.30	98.95	ditto	296.15	324.60		

21. SEWERAGE

Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works). Rate for all finished works include the removal of surplus debris, unused material and byproducts. 1

2

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2012 TO 31s	st JULY, 201	12) TEH:	NOWSH	EHRA, SOA	N VALLEY	Y KHUSHAB
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and laying R.C.C. pipe, moulded with cemer concrete 1:1½:3, with spigot socket or collar joint, etc including cost of reinforcement, conforming to B.S. 591: Part I: 1981, Class "L" including carriage of pipe fron factory to site of work, lowering in trenches to corre- alignment and grade, jointing, cutting pipes wher necessary, finishing and testing, etc., complet-		~	5				Chapter - 8	
	i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 225 mm (9:) i/d	Rft. Rft. Rft.	10.65 12.95 25.10	63.10 100.80 260.90	Metre Metre Metre	34.95 42.50 82.35	206.95 330.60 855.75		
2	Providing and laying non-reinforced concrete pipe moulded with cement concrete 1:1½:3, conforming t ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing, cutting pipe wher necessary, finishing and testing, etc. complete	and the second sec						ditto	
	 i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 200 mm (8") i/d iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm) v) 250 mm (10") i/d 	Rft. Rft. Rft. Rft. Rft.	8.00 9.70 15.60 16.95 17.30	31.20 45.10 62.00 79.35 88.25	Metre Metre Metre Metre Metre	26.25 31.80 51.15 55.60 56.75	102.35 147.95 203.35 260.25 289.45		
3	Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:1½:3 conforming to ASTN Specification C-76-79, Class II. Wall B, including carriag of pipe from factory to site of work, lowering in trenches correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc., complet							ditto	
	 i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d 	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	26.20 32.95 39.80 49.90 57.70 84.70 101.55 126.20 155.35 202.20	333.55 408.60 441.20 568.70 682.75 953.30 1015.45 1186.25 1610.65 2097.35	Metre Metre Metre Metre Metre Metre Metre	85.95 108.10 130.55 163.65 189.25 277.80 333.10 413.95 509.55 663.20	1094.05 1340.20 1447.15 1865.35 2239.40 3126.80 3330.70 3890.90 5282.95 6879.30		

Description	I	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks
	Unit	Labour	Composite	Unit	Labour	Composite	N0.	
xi) 1220 mm (48") i/d	Rft.	377.85	2758.1	Metre	1239.35	9046.55		
xi) 1220 mm (48) 1/d xii 1370 mm (54") i/d	Rft.	518.05	3441.35	Metre	1239.33	11287.65		
xiii) 1520 mm (60") i/d	Rft.	665.4	3913.5	Metre	2182.5	12836.3		
xiv) 1680 mm (66") i/d	Rft.	1031.6	4604.5	Metre	3383.65	15102.75		
xv) 1830 mm (72") i/d	Rft.	1275.40	5173.10	Metre	4183.30	16967.75		
Providing and laying R.C.C. pipe sewers, moulded wit cement concrete 1:1 ¹ / ₂ :3 conforming to ASTM Specification C-76-79, Class III, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipe where necessary, testing, etc. complete	a.	-					Chapter-8	
i) 310 mm (12") i/d	Rft.	26.20	403.85	Metre	85.95	1324.65		
ii) 380 mm (15") i/d	Rft.	32.95	497.35	Metre	108.05	1631.30		
iii) 460 mm (18") i/d	Rft.	39.80	627.70	Metre	130.55	2058.85		
iv) 530 mm (21":) i/d	Rft.	49.90	767.40	Metre	163.70	2517.05		
v) 610 mm (24") i/d	Rft.	57.70	892.50	Metre	189.20	2927.40		
vi) 690 mm (27") i/d	Rft.	84.70	1061.35	Metre	277.80	3481.25		
vii) 760 mm (30") i/d	Rft.	101.55	1281.25	Metre	333.00	4202.50		
viii) 840 mm (33") i/d	Rft.	126.20	1423.90	Metre	414.00	4670.40		
ix) 910 mm (36") i/d	Rft.	155.35	1918.65 2493.95	Metre	509.60	6293.15		
x) 1070 mm (42") i/d xi) 1220 mm (48") i/d	Rft. Rft.	202.20 383.65	2493.95 3002.80	Metre Metre	663.15 1258.30	8180.15 9849.20		
xi) 1220 mm (48") i/d xii 1370 mm (54") i/d	Rft.	526.15	3776.95	Metre	1238.30	12388.40		
xiii) 1520 mm (60") i/d	Rft.	675.50	4669.00	Metre	2215.65	12388.40		
xiv) 1680 mm (66") i/d	Rft.	1047.80	6022.65	Metre	3436.80	19754.30		
xv) 1830 mm (72") i/d	Rft.	1295.65	7429.30	Metre	4249.65	24368.10		
Providing and laying R.C.C. pipe sewers, moulded wit							Chapter - 8	
cement concrete 1:11/2:3 conforming to ASTN							-	
Specification C-76-79, Class IV, Wall B, including carriag	5							
of pipes from factory to site of work, lowering in trench								
to correct alignment and grade, jointing with rubber ring								
cutting pipes where necessary, testing, etc. complete								
i) 310 mm (12") i/d	Rft.	26.20	504.80	Metre	85.95	1655.80		
ii) 380 mm (15") i/d	Rft.	32.95	631.20	Metre	108.05	2070.40		
iii) 460 mm (18") i/d	Rft.	39.80	757.75	Metre	130.55	2485.35		
iv) 530 mm (21":) i/d	Rft.	49.90	887.50	Metre	163.70	2910.95		
v) 610 mm (24") i/d	Rft.	57.70	1014.90	Metre	189.20	3328.95		
vi) 690 mm (27") i/d	Rft.	84.70	1336.75	Metre	277.80	4384.60		
vii) 760 mm (30") i/d	Rft.	101.55	1538.25	Metre	333.00	5045.60		
viii) 840 mm (33") i/d iv) 010 mm (26") i/d	Rft.	126.20	1706.65	Metre	414.00	5597.85		
ix) 910 mm (36") i/d x) 1070 mm (42") i/d	Rft. Rft.	155.35 202.20	2426.60 2971.30	Metre Metre	509.60 663.15	7959.25 9745.85		
x) 10/0 IIIII (42) I/u	KIĹ.	202.20	29/1.30	wietre	005.15	7/43.63		

Sr.	Description	F	ate (British Sy	stem)	Rat	te (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	wii) 1270 mm (54") i/d	Rft.	526.15	4792.90	Metre	1725.05	15720.65		
	xii) 1370 mm (54") i/d xiii) 1520 mm (60") i/d	Rft.	675.50	4792.90 6046.00	Metre	1725.95 2215.65	19830.80		
	xiv) 1680 mm (66") i/d	Rft.	1047.80	7809.70	Metre	3436.80	25615.70		
	xv) 1830 mm (72") i/d	Rft.	1295.65	9198.00	Metre	4249.65	30169.40		
5	Lowering of sub-soil water table, by installation of tubewel								1) This rate shall be payable, ir
	along sewer line and pumping out water, for excavation i								addition to the item of excavation
	open cutting below sub-soil water level, concreting, curin								below SSWL for sewers and
	laying and jointing pipes, filling haunches, etc. till th								manholes under Chapter
	completion of sewer line, including disposal of pumped of			and the second sec					EARTHWORK
	water:-		1 .						2) The grant of these rates shall be
		Rft of	/ ~		Metre of				subject to Superintending Engineer
	1) 0-1 ft. (0 to 310 mm) below SSWI	laid sewer	/ - ~	172.95	laid sewer	-	567.35		approval.
	2) 0-2 ft. (0 to 610 mm) below SSWI	ditto	-	333.15	ditto	-	1092.80		
	3) 0-3 ft. (0 to 910 mm) below SSWL	ditto	and the second	564.95	ditto	-	1853.00		3) The rate includes cost of
	4) 0-4 ft. (0 to 1220 mm) below SSWL	ditto	And and a second se	814.00	ditto	-	2669.85		providing pumps, POL and al
	5) 0-5 ft. (0 to 1520 mm) below SSWL	ditto	And and a second second	1129.70	ditto	-	3705.40		operation charges at the site
	6) 0-6 ft. (0 to 1830 mm) below SSWL	ditto		1398.10	ditto	-	4585.75		of work, etc.
	7) 0-7 ft. (0 to 2170 mm) below SSWL	ditto	Se	1669.65	ditto	-	5476.50		
	8) 0-8 ft. (0 to 2480 mm) below SSWL	ditto	1.15	1917.40	ditto	-	6289.10		
	9) 0-9 ft. (0 to 2790 mm) below SSWL	ditto		2083.15	ditto	-	6832.70		
	10) 0-10 ft. (0 to 3100 mm) below SSWL	ditto		2398.60	ditto	-	7867.35		
	11) 0-11 ft. (0 to 3410 mm) below SSWL	ditto		2665.60	ditto	-	8743.20		
	12) 0-12 ft. (0 to 3720 mm) below SSWL	ditto	-	2953.50	ditto		9687.50		
7	Constructing gully grating chamber, 12"x12", (300x300 mm) complete in all respects	1.1	nance	Depart	392.872			16.2	Pipe connection to be paid separately.
	a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) fram hinged safety type	Each	513.95	2508.50	Each	513.95	2508.50		
	b) concrete Gully trap.	ditto	513.95	2283.50	ditto	513.95	2283.50		
8	Constructing standard gully grating chamber, 3'x2½ (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects	Each	1547.20	7063.50	Each	1547.20	7063.50	ditto	Pipe connection to be paid separately.
9	Extra for making and finishing benching floor work i manhole chamber, with 1/8" (3 mm) thick cement finish	100Sft.	693.00	1118.30	Sq.m	74.55	120.35	14.4	
0	Restoration of brick pavement on edge, over laid servic line, with 2" (50 mm) sand cushion under soling	100Sft.	964.25	2486.70	Sq.m	103.75	267.55	13.1	
1	Restoration of flat brick pavement sand grouted, over 2 (50 mm) thick dry sand cushion, under soling on laisservice line.	100Sft.	586.10	1677.00	Sq.m	63.05	180.45	13.1	

	MRS, BI-ANNUAL PERIOD (1st FI	EBRUARY, 2	2012 TO 31s	st JULY, 201	2) TEH:	NOWSH	EHRA, SOA	N VALLE	Y KHUSHAB
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
12	Restoration of metalled road, on laid service line, includin compaction:-							13.1	
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base	100Sft.	2587.90	8019.60	Sq.m	278.45	862.90		
	 b) Carpeted road, with 1¹/₂" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base 	100Sft.	1865.65	5925.30	Sq.m	200.75	637.55		
	 c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base. 	100Sft.	676.30	3759.10	Sq.m	72.75	404.50		
13	Providing and fixing 1 ¹ /4"x1 ¹ /4"x3/16" (31x31x5 mm) angle iron step, in manhole chambers, including carriage an setting the same in work to correct lines and level:	Each	68.20	220.95	Each	68.20	220.95	14.7	
14	Fixing manhole frame and cover in R.C.C. slab includin carriage to site.	Per set	168.30		Per set	168.30	-	ditto	
15	Providing and fixing 3" (75 mm) thick R.C.C. manhol cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20 (500 mm) clear i/d (frame weighing 37.324 Kg. or on maund) as per Standard Drawing STD/PD No. 5, of 1977 complete in all respects	Per set	97.40	2659.05	Per set	97.40	2659.05	ditto	
5-A	Providing and fixing 6" thick R.C.C. manhol- cover with tee shaped C.I. frame of 22" I/d (fram weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect	Per set	192.60	3831.35	Per set	192.60	3831.35		
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhol- cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects	Per set	174.25	2347.20	Per set	174.25	2347.20	ditto	
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhol- cover with 3"x3"x¼" (75x75x6mm) angle iron frame, 22 (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects	Per set	148.40	3785.90	Per set	148.40	3785.90	ditto	
18	Desilting of disposal work collecting tank, includin removal of sludge within 3 chains (90 metre)	100Cft.	452.55	506.85	cum	159.85	179.00	16.2	
19	Providing and installing, C.I. ventilating shaft painted wit bituminous paint with foundation bolts, as per PHEI Standard Drawing STD/PD No. 4 of 1977, complete in al							14.6	

	MRS, BI-ANNUAL PERIOD (1st FEB	EHRA, SOA		Y KHUSHAB					
Sr.	Description	ŀ	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	respects (except concrete foundation block)								
	a) 6" (150 mm) i/d shaft								
	i) 18 ft. (5.5 metre) long	Per Cwt	124.60	2156.15	%kg	245.25	4244.35		
	i) 24 ft. (7.30 metre) long	ditto	138.40	2175.60	ditto	243.23	4244.33		
	iii) 30 ft. (9.15 metre) long	ditto	149.50	2175.00	ditto	294.25	4301.80		
	iv) 36 ft. (11 metre) long	ditto	156.40	2192.55	ditto	307.90	4316.05		
	b) 9" (225 mm) i/d shaft			and the second division of the second divisio					
	i) 18 ft. (5.5 metre) long	Per Cwt	111.40	2139.25	%kg	219.30	4211.10		
	ii) 24 ft. (7.30 metre) long	ditto	120.05	2147.40	ditto	236.30	4227.15		
	iii) 30 ft. (9.15 metre) long	ditto	128.55	2156.35	ditto	253.05	4244.75		
	iv) 36 ft. (11 metre) long	ditto	154.75	2182.35	ditto	304.60	4296.00		
	c) 12" (300 mm) i/d shaft	181			78				
	i) 18 ft. (5.5 metre) long	Per Cwt	99.35	2128.30	%kg	195.60	4189.60		
	ii) 24 ft. (7.30 metre) long	ditto	127.75	2154.05	ditto	251.50	4240.25		
	iii) 30 ft. (9.15 metre) long	ditto	149.05	2174.70	ditto	293.40	4280.90		
	Silt clearing 10' (3.00 m) dia wells, and		~~Z.Ý	18 - C.S.					
	removal of slush outside the compound:	1878		15%					
	a) upto 10' (3.00 m) depth of slusł	Per well	3425.40	Depart	Per well	3425.40	-		
	b) beyond 10' (3.00 m) depth of slusł	Per well	6831.00	-	Per well	6831.00	-		

22. SINKING OF WELLS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

2 Well curbs to be laid at spring level or as deep as possible.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB

	MRS, BI-ANNUAL PERIOD (1st FI	EBRUAR	1,2012 10	SIST JULY,	2012) IE	H:NOWS	HEHRA, SC	JAN VALL	
Sr.	Description	I	Rate (British Sys	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Excavation of well in dry upto 20'(6 metre) below ground level, and disposal of soil within one chain (30 metre)								
	a) in ordinary soil or sand :-	1000 Cft.			cu.m				
	i) from 0' to 5' (o to 1.5 m) depth ii) from 5.1' to 10' (1.5 to 3.0 metre) depth iii) from 10.1' to 15' (3.0 to 4.5 metre) depth iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth	ditto ditto ditto ditto	2353.80 2458.35 2765.65 3174.35	5	ditto ditto ditto ditto	83.15 86.85 97.70 112.10	- - -		
	 b) in hard soil i) from 0' to 5'(0 to 1.5 metre) depth ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth 	1000 Cft. ditto ditto ditto	2867.05 2996.95 3275.70 3684.40		cu.m ditto ditto ditto	101.25 105.85 115.70 130.15	- - -		
	 c) in hard strata, such as shingle, gravel, etc. i) from 0' to 5'(0 to 1.5 metre) depth ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth 	1000 Cft. ditto ditto ditto	6183.95 6405.70 6678.15 7169.20	e Depi	cu.m ditto ditto ditto	218.40 226.25 235.85 253.20	- - -		
2	Dry sinking of well, including loading, and removing excavated material within one chain (30 m):-								
	 a) in ordinary soil :- i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth iv) from 25.1' to 30'(7.5 to 9.0 m) depth v) from 30.1' to 35'(9.0 to 10.5 m) depth vi) from 35.1' to 40'(10.5 to 12.0 m) depth vii) from 40.1'to 45'(12.0 to 13.5 m) depth viii) from 45'(13.5 Sm) to any depth b) in hard soil :- 	1000 Cft. ditto ditto ditto ditto ditto ditto ditto	12672.00 15840.00 19008.00 22176.00 25344.00 28512.00 31680.00 34848.00		cu.m ditto ditto ditto ditto ditto ditto ditto	447.60 559.45 671.35 783.25 895.15 1007.05 1118.95 1230.85			
		1000 CA	17424 00			615 40			
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	17424.00	-	cu.m	615.40	-		

	MRS, BI-ANNUAL PERIOD (1st I	EBRUAR	Y, 2012 TO	31st JULY,	2012) TE	EH:NOWS	HEHRA, SC	DAN VAL	LEY KHUSHAB
Sr.	Description	1	Rate (British Sy	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	20592.00	-	ditto	727.30	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	23760.00	-	ditto	839.20	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	26928.00	-	ditto	951.10	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	30096.00	-	ditto	1063.00	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	33264.00	-	ditto	1174.90	-		
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	36432.00	-	ditto	1286.80	-		
	viii) from 45'(13.5 m) to any depth	ditto	39600.00	-	ditto	1398.65	-		
	c) in hard strata, such as shingle, gravel, etc.								
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	23760.00	* 1	cu.m	839.20	-		
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	26928.00	1.1	ditto	951.10	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	30096.00	-	ditto	1063.00	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	30492.00		ditto	1077.00	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	36432.00	and the second sec	ditto	1286.80	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	39600.00		ditto	1398.65	-		
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	42768.00		ditto	1510.55	-		
	viii) from 45'-1" (13.5 m) to any depth	ditto	45936.00	فكومت بتحا	ditto	1622.45	-		
3	Wet sinking of well in ordinary soil (value of C upto 5), for depths below spring level, including charges of machinery,				1937			*841-1 to	The outer dimensions of the curb shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within		razeraze illi	- 2000				841-9	
	one chain (30 m):-		t ananc	е Дери	rtm	mt			
	i) from o' to $10'(0$ to 3.0 m) depth	1000 Cft.	18868.25	-	cu.m	666.45	-		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	40095.00	-	ditto	1416.15	-		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	49347.70	-	ditto	1742.95	-		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	64152.00	-	ditto	2265.85	-		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	71280.00	-	ditto	2517.60	-		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	80190.00	-	ditto	2832.30	-		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	82246.15	-	ditto	2904.95	-		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	84410.55	-	ditto	2981.40	-		
	ix) above 80'(24.0 m) to any depth	ditto	91645.70	-	ditto	3236.95	-		
4	Wet sinking of well in cohesive soil (value of Cmore than							*841-1	The outer dimensions of the curb
	5), for depths below spring level, including charges of							to	shall form basis of payment.
	machinery shoring, kentledge and removal of excavated							841-9	
	spoil within one chain (30 m):-								
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	-	30374.50	cu.m	-	1072.85		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	-	37968.10	ditto	-	1341.05		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	45561.70	ditto	-	1609.25		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	60748.95	ditto	-	2145.65		

Sr.	Description	I	Rate (British Sys	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	-	70094.95	ditto	_	2475.75		
	(i) above 50' to $60'(15.0 \text{ to } 18.0 \text{ m})$ depth	ditto	-	75936.20	ditto	_	2682.05		
	vii) above 60' to $70'(18.0 \text{ to } 21.0 \text{ m})$ depth	ditto	-	82839.50	ditto	-	2925.90		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	-	85965.50	ditto	-	3036.30		
	ix) above 80'(24.0 m) to any depth	ditto	-	91123.45	ditto	-	3218.50		
5	Wet sinking of well in shingle, or gravel, etc, for depths below spring level, including charges of machinery,							*841-1 to	The outer dimensions of the curb shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within one chain (30 m) :-		_					841-9	
	i) from o' to $10'(0$ to 3.0 m) depth	1000 Cft.	-	41419.75	cu.m	-	1462.95		
	ii) above $10'$ to $20'(3.0 \text{ to } 6.0 \text{ m})$ depth	ditto	<u> </u>	50624.15	ditto	-	1788.05		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	/ -	60748.95	ditto	-	2145.65		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto		82839.50	ditto	-	2925.90		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	No man	91123.45	ditto	V	3218.50		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	8	101248.25	ditto	\$7	3576.10		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	7 -	105957.50	ditto	Selo -	3742.40		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	11 18	108480.30	ditto	- 18	3831.50		
	ix) above 80'(24.0 m) to any depth	ditto	Sec. 1	119899.25	ditto	-	4234.85		
6	Making and fixing in position, kiker wood well curb.	Per Cft.	518.75	1839.55	cu.m	18323.00	64973.40		
7	Laying well curb in position only.	Each	166.30	e Depa	Each	166.30	-		
8	Providing, making and laying R.C.C. well curb in position,							*841-1	1) If concrete mixer is supplied by
	using coarse sand, including all kinds of form, moulds,							to	Government, all charges including
	curing, shuttering, rendering and finishing the exposed surface, (including screening and washing of aggregate :-							841-9	depreciation will be recovered from the contractor.
		D 66	100 50	<u></u>		4.5.5.5.5	11005 5-		2) The rate does not include cost of
	a) Ratio 1:1½:3	Per Cft.	128.70	314.15	cu.m	4545.70	11095.55		steel reinforcement and its labour for
	b) ratio 1:2:4	ditto	128.70	291.20	ditto	4545.70	10285.05		bending, which is payable, separately.
9	Providing and fixing structural steel for cutting edge.	100Kg	402.60	10238.75	100Kg	402.60	10238.75	841-1 to 841-9	
.0	Making and removing false masonry on well.	100Cft.	4197.60	15409.65	cu.m	1482.60	5442.70	21.1 to 21.5 & 18.1	The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.

* Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

23. TUBEWELL AND WATER SUPPLY

Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)". Rates for all finished works include the removal of surplus debris, unused material and byproducts. 1 2

Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
r	Boring for tubewell in all types of soil except shingle and ock, from ground level to 100 ft. (30 m) depth, including inking and withdrawing of casing pipe, complete:-							Chap. 2	
a b c d f f f i i 2	 4" (100 mm) i/d 5" (125 mm) i/d 6" (150 mm) i/d 8" (200 mm) i/d 10" (250 mm) i/d 12" (300 mm) i/d 15" (375 mm) i/d 	Per Rft. of bore ditto ditto ditto ditto ditto ditto ditto		34.55 48.00 86.65 131.75 171.35 216.70 236.30 350.60 373.25	Per Metre of bore ditto ditto ditto ditto ditto ditto ditto		113.35 157.45 284.15 432.15 562.05 710.75 775.15 1150.05 1224.30	ditto	
g (1	 gravel & rock, from a depth of 100.1 ft. to 200 ft. 30 to 60 m) below ground level, including sinking and withdrawing of casing pipe, complete:- 5" (125 mm) i/d 6" (150 mm) i/d 8" (200 mm) i/d 10" (250 mm) i/d 12" (300 mm) i/d 15" (375 mm) i/d 	Per Rft. of bore ditto ditto ditto ditto ditto	ïnanci	146.80 205.75 231.50 265.35 292.80 411.35 433.95	Per Metre of bore ditto ditto ditto ditto ditto ditto		481.45 674.85 759.30 870.40 960.35 1349.15 1423.40	aitto	
g tu v a b c d e 4 E	 b) 6" (150 mm) i/d b) 8" (200 mm) i/d c) 10" (250 mm) i/d 	Per Rft. of bore ditto ditto ditto ditto ditto ditto		204.55 263.50 291.65 329.45 349.70 451.80 475.65	Per Metre of bore ditto ditto ditto ditto ditto		670.90 864.30 956.55 1080.65 1146.95 1481.90 1560.10	ditto Chap. 2	

	MRS, BI-ANNUAL PERIOD (1st FE	BRUAR	<mark>, 2012 ТО</mark> З	1st JULY, 20 ⁻	2012) TEH:NOWSHEHRA, SOAN VALLE				HUSHAB
Sr.	Description		Rate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	Rft of bore ditto ditto ditto ditto ditto		351.75 393.55 416.20 551.80 556.00	Per Metre of bore ditto ditto ditto		1153.75 1290.85 1365.05 1809.85 1823.65		
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells, in all types of soil except shingle, gravel and rock:-							ditto	
	 a) from ground level to 250 ft. (75 m) below ground level:- i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d b) exceeding 250 ft. (75 m) depth below 	Per Rft. of bore ditto		372.10 535.10	Per Metre of bore ditto		1220.40 1755.15		Upto 2 cusec discharge Above 2 cusec discharge
6	ground level:- i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d Boring for tubewell in shingle, gravel and rock, including sinking and withdrawing of casing pipe:-	Rft of bore ditto		372.10 535.10	Per Metre of bore ditto		1220.40 1755.15	ditto	Upto 2 cusec discharge Above 2 cusec discharge Location and depth of shingle, gravel or rock is to be determined
	 a) from ground level to 200 ft. (60 m) below ground level:- i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d 	Per Rft, of bore ditto	* Financi	839.15 1134.90	Per Metre of bore ditto		2752.40 3722.50		from the bore log. Upto 2 cusec discharge Above 2 cusec discharge
	 b) exceeding 200 ft. (60 m) depth below ground level:- i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d 	ditto ditto		839.15 1134.90	ditto ditto		2752.40 3722.50		Upto 2 cusec discharge Above 2 cusec discharge
7	Providing strong substantially built box of deodar wood 4'x2½'x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	414.90	11079.30	Job for compl- ete bore	414.90	11079.30	ditto	
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	108.00	156.00	Per Set of 2 bottles	108.00	156.00	Chap. 2	
9	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc. complete:-							ditto	Cost/labour of jointing both ends is included in the rate.

	MRS, BI-ANNUAL PERIOD (1st F		IUSHAB						
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
10	 a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick j) 10" i/d, 3/16" (250 mm i/d 6 mm) thick k) 12" i/d, 4" (250 mm i/d 6 mm) thick l) 15" i/d, 4" (375 mm i/d 6 mm) thick m) 18" i/d, 4" (500 mm i/d 6 mm) thick o) 22" i/d, 4" (500 mm i/d 6 mm) thick 	Per Rft. Per Rft.	16.80 16.80 22.25 25.20 28.25 33.05 40.85 40.85 40.85 40.85 46.00 46.00 47.20 54.05 54.05 63.70 64.90	638.40 961.80 1177.25 1390.20 1498.25 1765.55 2245.85 2298.35 2356.00 2986.00 3407.20 4254.05 4763.30 5250.70 6070.90	Per Metre Per Metre	55.10 55.15 72.90 82.60 92.60 108.40 134.00 134.00 150.90 150.90 154.85 177.35 177.35 208.90 212.80	2094.00 3154.75 3861.30 4559.80 4914.20 5791.00 7366.40 7538.60 7727.70 9794.10 11175.65 13953.35 15623.70 17222.25 19912.50		In the acce of increase or degreese
10	 Providing and installing M.S. Bail plug in tubewell bore hole: a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long. b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long. c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long. d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long. e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long. f) 7" i/d, 2 ft. (150 mm i/d 600 mm) long. g) 8" i/d, 2 ft. (200 mm i/d 600 mm) long h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long i) 10" i/d, 2 ft. (250 mm i/d 600 mm) long j) 12" i/d, 2 ft. (375 mm i/d 600 mm) long j) 12" i/d, 2 ft. (450 mm i/d 600 mm) long n) 18" i/d, 2 ft. (500 mm i/d 600 mm) long n) 20" i/d, 2 ft. (500 mm i/d 600 mm) long m) 20" i/d, 2 ft. (550 mm i/d 600 mm) long 	Each Each Each Each Each Each Each Each	75.80 75.80 126.50 126.50 170.75 170.75 210.45 210.45 210.45 252.60 252.60 303.75 330.40 330.40	433.90 586.50 1183.60 1506.40 1906.30 2205.15 2448.00 2724.90 3533.70 4251.00 5246.70 5967.00 6651.05 7316.55	Each Each Each Each Each Each	75.80 75.80 126.50 170.75 170.75 210.45 210.45 210.45 252.60 252.60 303.75 330.40 330.40	433.90 586.50 1183.60 1506.40 1906.30 2205.15 2448.00 2724.90 3533.70 4251.00 5246.70 5967.00 6651.05 7316.55		In the case of increase or decrease in the length of Bail plug, the rates will be increased or decreased as per rates given in serial No. 14 of this chapter for the respective diameter.
	Providing and installing, P.V.C. strainer B.S.S. Class 'B', in tubewell bore hole, including sockets and solvents, etc. complete:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	12.15 13.80 14.65 17.45 23.90 24.45 24.45	99.50 145.85 202.35 267.10 646.45 966.90 1291.40	Per Metre Per Metre Per Metre Per Metre	39.75 45.35 48.10 57.15 78.35 80.20 80.20	326.45 478.45 663.70 876.00 2120.35 3171.40 4235.75	Chap. 2	
12	Providing and installing P.V.C. strainer B.S.S. Class `D', in tubewell bore hole, including sockets and solvent, etc.								

	MRS, BI-ANNUAL PERIOD (1st FE	IUSHAB							
Sr.	Description		Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	complete:-						<u> </u>		
	a) 1 ¹ / ₄ " i/d (30 mm) b) 1 ¹ / ₂ " i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	8.10 8.40 8.55 12.15 13.95 15.00 26.70	41.30 48.40 73.95 154.40 246.35 360.80 514.40	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	26.60 27.55 28.00 39.80 45.70 49.20 87.60	135.45 158.75 242.6 506.45 808 1183.4 1687.2		
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:-								
	 i) B.S.S. Class `B' a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) ii) B.S.S. Class `D' 	Each Each Each Each Each Each Each Each	6.35 7.25 8.05 10.05 12.40 13.05 14.95 14.95	54.35 73.25 111.25 160.05 312.40 440.25 590.95 622.15	Each Each Each Each Each Each Each Each	6.35 7.25 8.05 10.05 12.40 13.05 14.95 14.95	54.35 73.25 111.25 160.05 312.40 440.25 590.95 622.15		
	a) 1 ¹ / ₄ " i/d (30 mm) b) 1 ¹ / ₂ " i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each	4.10 4.45 4.65 6.30 7.25 8.10 10.05	28.10 40.45 58.65 78.30 103.25 146.10 190.05	Each Each Each Each Each Each Each Each	4.10 4.45 6.30 7.25 8.10 10.05	28.10 40.45 58.65 78.30 103.25 146.10 190.05		
14	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:-							Chap. 2	
	 a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 1/4" (250 mm i/d 6 mm) thick j) 12" i/d, 1/4" (300 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	45.65 45.65 57.10 57.10 81.50 81.50 95.10 95.10 95.10 114.10	226.55 305.45 402.45 745.30 895.10 1030.70 1272.50 1446.30 1867.50 2199.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	149.75 149.75 187.30 267.30 267.30 311.95 311.95 311.95 374.25	743.15 1001.90 1320.05 2444.65 2935.95 3380.70 4173.85 4743.85 6125.40 7213.05		

	MRS, BI-ANNUAL PERIOD (1st F	EBRUAR	Y, 2012 TO 3	1st JULY, 20 ⁻	12) TEH:N	OWSHEH	IRA, SOAN VA	LLEY K	HUSHAB
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 k) 15" i/d, ¹/₄" (375 mm i/d 6 mm) thick l) 18" i/d, ¹/₄" (450 mm i/d 6 mm) thick m) 20" i/d, ¹/₄" (500 mm i/d 6 mm) thick n) 22" i/d, ¹/₄" (550 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft.	114.10 139.70 150.60 150.60	2720.35 3380.05 3751.00 4111.00	Per Metre Per Metre Per Metre Per Metre	374.25 458.20 493.95 493.95	8922.75 11086.55 12303.20 13484.15		
15	Providing and installing P.V.C. blind pipe, B.S.S. Class `B', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete.							ditto	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	15.75 17.85 18.70 22.85 30.30 31.65 37.65 35.25	109.85 159.90 212.60 297.45 452.70 746.85 1036.05 1235.25	Per Metre	51.65 58.45 61.25 73.50 99.45 103.80 123.45 115.60	360.25 524.50 697.30 974.10 1484.90 2449.65 3398.20 4051.60		
16	 Providing and installing P.V.C. blind pipe, B.S.S. Class `D', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete. a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	9.55 9.85 10.50 13.65 17.95 19.00 22.90	43.15 53.05 77.70 157.65 259.90 379.00 546.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	31.40 32.30 34.50 44.85 58.95 62.35 75.10	141.60 174.00 254.90 517.15 852.45 1243.15 1791.20		
17	Testing and developing of tubewell of size 6" (150 mm) i/d and above continuously.								
	i) upto 1.5 cs. dischargeii) above 1.5 cs. discharge	Per Hour ditto		1038.80 1249.55	Per Hour ditto		1038.80 1249.55		
18	Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3 mm), around tubewell in bore hole.	Per Cft.	17.70	69.35	cu.m	625.15	2449.45		The rate includes wastage, etc.
19	Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc. complete in all respects:-							Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d	Per Rft. Per Rft. Per Rft.		36.70 45.70 57.05	Per Metre		120.40 149.95 187.10		

	MRS, BI-ANNUAL PERIOD (1st FE		HUSHAB						
Sr.	Description		Rate (British Sy	vstem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.		67.90 83.60 124.45 145.80 189.00 251.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		222.65 274.15 408.15 478.15 619.95 823.65		
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:- a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d Laying, cutting, jointing, testing and disinfecting cast iron	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.		15.65 17.40 26.60 29.15 34.35 48.60 56.60 77.35 95.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		51.30 57.10 87.25 95.60 112.75 159.35 185.65 253.50 314.40	ditto Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately. Pipes to be supplied by
21	Laying, cutting, jointing, testing and distincting cast from pipe line in trenches with Tyton joints, complete in all respects:- a) $3" (75 \text{ mm}) i/d$ b) $4" (100 \text{ mm}) i/d$ c) $5" (125 \text{ mm}) i/d$ d) $6" (150 \text{ mm}) i/d$ e) $8" (200 \text{ mm}) i/d$ f) $10" (250 \text{ mm}) i/d$ f) $10" (250 \text{ mm}) i/d$ h) $15" (375 \text{ mm}) i/d$ i) $18" (450 \text{ mm}) i/d$	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	ïnanci	7.90 9.10 00011.70 13.25 18.00 22.85 27.40 41.85 50.15	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		25.85 29.90 38.45 43.50 59.00 75.00 89.95 137.20 164.55	Chap. 2	 Providing and installing specials and valves is not included in the rate, which is payable separately.
22	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves. i) Light Quality							Chap. 2	Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	 a) ¹/₂" i/d (15 mm) 2mm thick b) ³/₄" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1¹/₄" i/d (32 mm) 2.65mm thick e) 1¹/₂" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"¹/₂ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	7.20 7.75 8.65 8.75 8.85 10.10 10.65 12.45 13.35	53.60 74.20 103.55 133.35 166.35 207.65 282.00 330.65 462.65	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	23.70 25.40 28.30 29.00 33.10 35.00 40.75 43.80	175.80 243.30 339.70 437.45 545.65 681.05 924.95 1084.45 1517.55		

	MRS, BI-ANNUAL PERIOD (1st FE	BRUAR	Y, 2012 TO 3	1st JULY, 20	12) TEH:N	OWSHEH	RA, SOAN V	ALLEY KI	HUSHAB
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) Medium Quality a) ¹/₂" i/d (15 mm) 2.65mm thick b) ³/₄" i/d (20 mm) 2.65mm thick c) 1" i/d (25 mm) 3.25mm thick d) 1¹/₄" i/d (32 mm) 3.25mm thick e) 1¹/₄" i/d (40 mm) 3.25mm thick f) 2" i/d (50 mm) 3.65mm thick g) 2"/₂ i/d (65 mm) 3.65mm thick h) 3" i/d (75 mm) 4.05mm thick j) 5" i/d (150 mm) 4.5mm thick k) 6" i/d (200 mm) 4.85mm thick ii) Heavy Quality a) ¹ / ₂ " i/d (15 mm) 3.25mm thick b) ³ / ₄ " i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick b) ³ / ₄ " i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick c) 1" i/d (25 mm) 4.05mm thick c) 1" i/d (25 mm) 4.05mm thick c) 1" i/d (50 mm) 4.05mm thick j) 1/ ₄ " i/d (50 mm) 4.5mm thick j) 2"/ ₂ i/d (65 mm) 4.5mm thick j) 2"/ ₂ i/d (65 mm) 4.5mm thick j) 2"/ ₂ i/d (65 mm) 4.5mm thick j) 3" i/d (75 mm) 4.85mm thick	Per Rft. Per Rft.	7.20 7.75 8.65 9.05 10.10 10.65 12.45 13.35 15.45 15.75 7.20 7.75 8.65 8.75 9.05 10.10 10.65 12.45	63.10 79.70 119.50 152.40 173.05 238.35 303.70 382.45 544.65 747.05 870.95 870.95 89.15 115.70 170.80 220.00 249.90 343.00 430.00 552.90	Per Metre Per Metre	23.70 25.40 28.30 28.60 29.65 33.10 35.00 40.75 43.80 50.65 51.60 23.70 25.40 28.30 28.60 29.65 33.10 35.00 40.75	207.00 261.35 391.95 499.85 567.55 781.85 996.15 1254.40 1786.45 2450.30 2856.75 292.35 379.45 560.2 721.55 819.65 1125.05 1410.35 1813.5		 i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia, 3/4"dia & 1/2"dia) for Bath rooms/ Levorotary. ii. For internal G.I piping (1"dia, 3/4"dia & 1/2"dia) Bath room(s)/ Levorotary of rate (composite) shall be reduced by 8% and specials mentioned above may be paid at the rates placed on Website as per actual quantity used.
23	 a) b) a (100 mm) 4.5mm there b) a) b) a) (100 mm) 5.4mm thick c) b) a) (100 mm) 5.4mm thick c) b) a) (150 mm) 5.4mm thick c) b) a) (150 mm) 5.4mm thick Providing, laying, cutting, jointing, testing and disinfecting Asbestos cement/Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:-	Per Rft. Per Rft. Per Rft.	13.35 15.45 15.75	752.75 931.05 1099.85	Per Metre Per Metre Per Metre	43.80 50.65 51.60	2469 3053.85 3607.55	PS 428 & ISO 160	Providing and installing specials and valves is not included in the rate, which is payable separately.
	B Class WOrking Pressure a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	$\begin{array}{c} 7.60\\ 8.05\\ 11.00\\ 15.15\\ 19.80\\ 25.25\\ 29.35\\ 33.25\\ 39.30\\ 46.20\\ 55.85\end{array}$	140.10 182.60 287.90 483.85 658.70 870.00 1117.60 1418.85 2064.35 2175.20 3000.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	24.85 26.35 36.00 49.65 64.90 82.80 96.35 109.05 128.85 151.55 183.20	459.55 598.90 944.30 1587.00 2160.60 2853.50 3665.75 4653.90 6771.05 7134.60 9840.90		

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description		Rate (British S	ystem)	Ra	nte (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
24	C Class Working Pressure							PS 428 &			
24	a) 3" i/d (75 mm)	Per Rft.	7.60	140.10	Per Metre	24.85	459.55	ISO 160			
	b) 4" i/d (100 mm)	Per Rft.	8.05	200.90	Per Metre	26.35	658.95	100 100			
	c) 6" i/d (150 mm)	Per Rft.	11.00	345.00	Per Metre	36.00	1131.55				
	d) 8" i/d (200 mm)	Per Rft.	15.15	546.30	Per Metre	49.65	1791.90				
	e) 10" i/d (250 mm)	Per Rft.	19.80	762.15	Per Metre	64.90	2499.75				
	f) 12" i/d (300 mm)	Per Rft.	25.25	1060.65	Per Metre	82.80	3478.85				
	g) 14" i/d (350 mm)	Per Rft.	29.35	1628.15	Per Metre	96.35	5340.40				
	h) 16" i/d (400 mm)	Per Rft.	33.25	2079.15	Per Metre	109.05	6819.60				
	i) 18" i/d (450 mm)	Per Rft.	39.30	2949.30	Per Metre	128.85	9673.70				
	j) 20" i/d (500 mm)	Per Rft.	46.20	3034.75	Per Metre	151.55	9953.90				
	k) 24" i/d (600 mm)	Per Rft.	56.50	4273.05	Per Metre	185.40	14015.55				
25	D Class Working Pressure							PS 428 &			
	a) 3" i/d (75 mm)	Per Rft.	7.60	140.10	Per Metre	24.85		ISO 160			
	b) 4" i/d (100 mm)	Per Rft.	8.05	227.80	Per Metre	26.35	747.25				
	c) 6" i/d (150 mm)	Per Rft.	11.00	415.00	Per Metre	36.00	1361.20				
	d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Per Rft.	15.15	731.55	Per Metre	49.65	2399.55				
		Per Rft. Per Rft.	19.80 25.25	1079.90	Per Metre Per Metre	64.90 82.80	3542.00				
		Per Rft.	23.23	1575.50 2345.55	Per Metre	96.35	5167.60 7693.35				
	g) 14" i/d (350 mm) h) 16" i/d (400 mm)	Per Rft.	33.25	3029.15	Per Metre	109.05	9935.65				
	i) 18" i/d (450 mm)	Per Rft.	39.30	3638.40	Per Metre	109.05	11934.00				
	j) 20" i/d (500 mm)	Per Rft.	46.20	4450.05	Per Metre	120.05	14596.20				
	k) 24" i/d (600 mm)	I CI IXII.	+0.20	4150.05	T et Mette	151.55	14570.20				
				der der	Sec. 1						
26	Providing, laying, cutting, jointing, testing and disinfecting			67 NS 1997				Chap	Providing and installing specials		
	P.V.C. pipe line of B.S.S. with `B' Class working pressure	12		. 15%				2	and valves is not included in the		
	pipe, in trenches, complete in all respects:-	1	rnanci	Depar	tment				rate, which is payable separately.		
	a) 3" i/d (75 mm)	Per Rft.	2.50	98.45	Per Metre	8.20	322.95				
	b) 4" i/d (100 mm)	Per Rft.	3.10	148.05	Per Metre	10.25	485.60				
	c) 5" i/d (125 mm)	Per Rft.	3.85	201.65	Per Metre	12.60	661.40				
	d) 6" i/d (150 mm)	Per Rft.	4.15	284.20	Per Metre	13.60	932.20				
	e) 8" i/d (200 mm)	Per Rft.	5.85	436.70	Per Metre	19.20	1432.40				
	f) 10" i/d (250 mm)	Per Rft.	7.55	737.05	Per Metre	24.80	2417.60				
	h) 12" i/d (300 mm)	Per Rft.	9.35	1027.70	Per Metre	30.60	3370.85				
	g) 14" i/d (350 mm)	Per Rft.	11.85	1235.85	Per Metre	38.85	4053.55				
27	Providing, laying, cutting, jointing, testing and disinfecting							ditto	Providing and installing specials		
	pipe line in trenches with P.V.C. pipes of B.S.S. with `D'								and valves is not included in the		
	Class working pressure complete in all respects:-							l	rate, which is payable separately.		
	a) 2" i/d (50 mm)	Per Rft.	2.10	70.60	Per Metre	6.80	231.65				
	b) 3" i/d (75 mm)	Per Rft.	2.50	149.40	Per Metre	8.20	489.95				
	c) 4" i/d (100 mm)	Per Rft.	3.10	249.90	Per Metre	10.25	819.60				
	d) 5" i/d (125 mm)	Per Rft.	3.85	371.05	Per Metre	12.60	1217.05				
	e) 6" i/d (150 mm)	Per Rft.	4.15	537.80	Per Metre	13.60	1764.05				
28	Providing and fixing cast iron special of R S S. Class `B'							91	i) Labour rates include the cost of		
	(such as bend, tee cross collar, reducer, tail piece,							<i>,</i>	jointing material & labour.		
28	Providing and fixing cast iron special of B.S.S. Class `B' (such as bend, tee cross collar, reducer, tail piece,							9.1			

	MRS, BI-ANNUAL PERIOD (1st FE	RA, SOAN VA	LLEY K	HUSHAB					
Sr.	Description		Rate (British Sy	ystem)	Ra	ate (Metric Sy	ystem)	Spec.	Remarks
No.	•	Unit	Labour	Composite	Unit	Labour	Composite	Ño.	
	 flanged spigot, cap, flanged socket, taper, angle branch, plug etc.) for cast iron pipe line , complete:- a) C.I.S.S. Specials, with spigot. and socket joint:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d 	Per Kg. Per Kg. Per Kg.	13.95 7.80 4.50	91.90 85.75 82.45	Per Kg Per Kg Per Kg	13.95 7.80 4.50	91.90 85.75 82.45		ii) The internal dia of the pipe, from which the branch is taken out with be considered the internal dia for the purpose of payments of specials.
	 b) C.I. flanged specials, with flanged and flanged joints:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d c) C.I. Specials, with tyton joints:- 	Per Kg Per Kg Per Kg	6.45 2.25 2.85	84.40 80.20 80.20	Per Kg Per Kg Per Kg	6.45 2.25 2.85	84.40 80.20 80.20		
	i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d	Per Kg Per Kg Per Kg	6.50 6.50 6.50	84.50 84.50 84.50	Per Kg Per Kg Per Kg	6.50 6.50 6.50	84.50 84.50 84.50		
29	 Providing and fixing cast iron specials of B.S.S. Class 'B' (such as bend, tee, cross collar, reducer, tail piece, flanged socket, flanged spigot, cap, taper, angle branch, plug, etc) for Asbestos cement pipe line, with comet joint and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 18" (200 to 450 mm) i/d iii) 20" to 24" (500 to 600 mm) i/d 	Per Kg Per Kg Per Kg	10.35 5.50 4.40	D 88.30 83.45 82.35	Per Kg Per Kg Per Kg	10.35 5.50 4.40	88.30 83.45 82.35	9.1	 Labour rates include the cost of jointing material and labour. The internal dia of the pipe, from which the branch is taken out, will be considered the internal dia for the purpose of payment.
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class `B', for cast iron pipe line, and Asbestos cement pipe line (including cost of jointing material):- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm)	Each Each Each Each Each Each Each Each	424.10 461.55 830.75 885.65 1034.10 1813.05 2037.35 2702.20 3110.10	5704.10 6701.55 8030.75 11085.65 19634.10 25213.05 32637.35 60302.20 106310.10	Each Each Each Each Each Each Each Each	424.10 461.55 830.75 885.65 1034.10 1813.05 2037.35 2702.20 3110.10	5704.10 6701.55 8030.75 11085.65 19634.10 25213.05 32637.35 60302.20 106310.10	9.1	Labour rates include cost of jointing material and labour.
31	 Providing and fixing, sluice valve of B.S.S. quality and weight, for Asbestos cement pipe line, with comet joint and rubber ring, complete (including cost of jointing materials):- a) 3" i/d (75 mm) 	Each	331.40	4651.40	Each	331.40	4651.40	9.1	Labour rates include cost of jointing material and labour.
	b) 4" i/d (100 mm)	Each	409.40	5449.40	Each	409.40	5449.40		

	MRS, BI-ANNUAL PERIOD (1st F	EBRUAR	012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB						
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) 6" i/d (150 mm)	Each	520.50	9160.50	Each	520.50	9160.50		
	d) 8" i/d (200 mm)	Each	868.55	16708.55	Each	868.55	16708.55		
	e) 10" i/d (250 mm)	Each	1119.30	20799.30	Each	1119.30	20799.30		
	f) 12" i/d (300 mm)	Each	1294.30	25774.30	Each	1294.30	25774.30		
	g) 16" i/d (400 mm)	Each	1534.35	49534.35	Each	1534.35	49534.35		
	h) 18" i/d (450 mm)	Each	1852.85	88252.85	Each	1852.85	88252.85		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2 ¹ / ₂ " (65 mm) dia (including cost of jointing material).	Each	48.85	4008.85	Each	48.85	4008.85	9.1	1) Labour rates include cost of jointing material and labour.
									 Connecting pipes and specials, if used, will be paid extra.
33	Providing and fixing, air valve 2 ¹ / ₂ (65mm) dia of B.S.S. quality and weight (complete with jointing material).			*)				ditto	
	a) single	Each	98.70	2978.70	Each	98.70	2978.70		
	b) double	Each	98.70	6458.70	Each	98.70	6458.70		
34	Providing and fitting C.I. flanges on pipes, including	386			1 5656				
	turning, threading, facing and fitting, etc. complete in all	100	11	2 61	184			ditto	
	respects:-		34.	1000					
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	18.65	87.55	Per Kg	18.65	87.55		
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	11.65	80.55	Per Kg	11.65	80.55		
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	9.95	78.85	Per Kg	9.95	78.85		
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:								
		Per Inch			Per cm i/d				
	a) 3" to 6" (75 to 150 mm) i/d	i/d of pipe		35.40	of pipe		14.15		
	b) 8" to 12" (200 to 300 mm) i/d	ditto		42.90	ditto		17.15		
	c) 15" to 18" (375 to 450 mm) i/d	ditto		39.95	ditto		15.95		
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I. pipe of B.S.S. 1387-1967 complete in all respects, including specials and valves:-								Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) G.I. flanged joints (Heavy Quality)								
	a) 1½" i/d (40 mm)	Per Rft.	12.55	240.35	Per Metre	41.20	788.40		
	b) 2" i/d (50 mm)	Per Rft.	12.55	332.55	Per Metre	41.20	1090.85		
	c) 2½" i/d (65 mm)	Per Rft.	13.70	423.20	Per Metre	44.95	1388.15		
	d) 3" i/d (75 mm)	Per Rft.	13.80	549.40	Per Metre	45.20	1802.05		
	e) 4" i/d (100 mm)	Per Rft.	15.60	776.30	Per Metre	51.15	2546.30		

	MRS, BI-ANNUAL PERIOD (1st FE		IUSHAB						
Sr.	Description		Rate (British Sy	rstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft.	17.35 17.40	955.70 1132.00	Per Metre Per Metre	56.95 57.10	3134.75 3713.05		
	ii) C.I. flanged joints (Medium Quality)								
	a) 1 ¹ / ₂ " i/d (40 mm) b) 2" i/d (50 mm) c) 2 ¹ / ₂ " i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	13.95 13.20 15.05 15.15 17.05 18.95 19.05	175.20 235.00 293.75 374.20 542.55 734.95 865.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	45.70 43.35 49.40 49.65 55.95 62.15 62.45	574.60 770.80 963.50 1227.45 1779.60 2410.65 2837.55		
37	Providing and installing P.V.C. bends, of B.S.S.			*					
38	 i) Class `B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) Providing and installing P.V.C. tees, of B.S.S.	Each Each Each Each Each Each Each Each	64.10 75.60 94.50 98.20 39.90 43.75 48.20 64.10 75.60 94.50 98.20	176.90 316.80 563.70 790.60 69.90 76.15 111.80 232.10 470.40 1006.50 1378.60	Each Each Each Each Each Each Each Each	64.10 75.60 94.50 98.20 39.90 43.75 48.20 64.10 75.60 94.50 98.20	176.90 316.80 563.70 790.60 76.15 111.80 232.10 470.40 1006.50 1378.60		
	 i) Class `B' working pressure:- a) 3" i/d (80 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- a) 1¼" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) 	Each Each Each Each Each Each Each	96.15 115.10 139.25 147.30 61.20 65.90 71.90	512.55 958.70 1827.65 1887.30 176.40 207.50 260.30	Each Each Each Each Each Each Each	96.15 115.10 139.25 147.30 61.20 65.90 71.90	512.55 958.70 1827.65 1887.30 176.40 207.50 260.30		
	d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each	96.15 115.10 139.25 147.30	512.55 958.70 1827.65 1887.30	Each Each Each Each	96.15 115.10 139.25 147.30	512.55 958.70 1827.65 1887.30		

	MRS, BI-ANNUAL PERIOD (1st FE	RA, SOAN VA	LLEY K	HUSHAB					
Sr.	Description		Rate (British Sy	vstem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Providing and installing P.V.C. sockets, B.S.S.								
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each	48.50	122.90	Each	48.50	122.90		
	c) 5" i/d (125 mm)	Each Each	60.00 75.00	193.20 255.00	Each Each	60.00 75.00	193.20 255.00		
	d) 6" i/d (150 mm)	Each	75.00	331.90	Each	75.00	331.90		
	e) 8" i/d (200 mm)	Each	114.80	700.40	Each	114.80	700.40		
	f) 10" i/d (250 mm)	Each	137.00	1721.00	Each	137.00	1721.00		
	g) 12" i/d (300 mm)	Each	158.05	3832.45	Each	158.05	3832.45		
	h) 14" i/d (350 mm)	Each	179.20	3059.20	Each	179.20	3059.20		
	ii) Class `D' working pressure:-	F 1	26.00	× 17.20	F 1	26.00	17.20		
	a) 1¼" i/d (30 mm)	Each	26.90	47.30	Each	26.90	47.30		
	b) 1½" i/d (40 mm) c) 2" i/d (50 mm)	Each Each	30.75 35.20	58.35 79.60	Each Each	30.75 35.20	58.35 79.60		
	d) 3" i/d (75 mm)	Each	48.50	191.30	Each	48.50	191.30		
	e) 4" i/d (100 mm)	Each	60.00	324.00	Each	60.00	324.00		
	f) 5" i/d (125 mm)	Each	75.00	555.00	Each	75.00	555.00		
	g) 6" i/d (150 mm)	Each	78.70	918.70	Each	78.70	918.70		
		100	11	E 101	1.3				
40	Providing and installing P.V.C. Tapered core, B.S.S.		1000	1000	1.00				
			The second	a then a lot	Sara				
	i) Class `B' working pressure:-		-	200					
	a) 3" i/d (75 mm)	Each	64.10	100.10	Each	64.10	100.10		
	b) 4" i/d (100 mm)	Each	75.60	123.60	Each	75.60	123.60		
	c) 5" i/d (125 mm)	Each	94.50	154.50	Each	94.50	154.50		
	d) 6" i/d (150 mm)	Each	98.20	170.20	Each	98.20	170.20		
	e) 8" i/d (200 mm)	Each	140.80	260.80	Each	140.80	260.80		
	f) 10" i/d (250 mm)	Each	163.00	319.00	Each	163.00	319.00		
	g) 12" i/d (300 mm) b) 14" i/d (250 mm)	Each	189.25	381.25	Each	189.25	381.25		
	h) 14" i/d (350 mm)	Each	210.40	450.40	Each	210.40	450.40		
	ii) Class `D' working pressure:-								
	a) 1 ¹ /4" i/d (30 mm)	Each	39.90	57.90	Each	39.90	57.90		
	b) 1 ¹ / ₂ " i/d (40 mm)	Each	43.75	67.75	Each	43.75	67.75		
	c) 2" i/d (50 mm)	Each	48.20	78.20	Each	48.20	78.20		
41	Making connection for new watersupply lines with the								The rate includes the component of
+1	running main, including excavation of trench and refilling,								bailing out water from the trench
	complete, but excluding cost of pipe and specials, etc.								and cutting of existing pipe line.
	Diameter of running main:	P			D				
	i) upto 6" i/d (150 mm)	Per	895.95		Per	895.95			
	i) upto 6 1/d (150 mm) ii) upto 8" i/d (200 mm)	Connection ditto	1133.55		Connection ditto	895.95 1133.55			
	iii) upto 10" i/d (250 mm)	ction	1593.90		ction	1593.90			
	iv) upto 12" i/d (300 mm)	ditto	2187.90		ditto	2187.90			
	v) upto 16" i/d (400 mm)	ditto	2677.95		ditto	2677.95			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	system)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	vi) upto 20" i/d (500 mm) vii) upto 24" i/d (600 mm)	ditto ditto	3479.85 4177.80		ditto ditto	3479.85 4177.80							



Finance Department

24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

•	Description	R	ate (British S	System)	Rate (Metric System)			Spec.	Remarks
).	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
]	Supply and erection of G.I. pipes for wiring purposes, including pull boxes, inspection boxes, bends, tees, etc. complete with								
1	all specials.								
	a) on surface, including clamps, etc.							38.4	
	i) 15 mm i/d	Per Rft.	10.15	53.45	Per Metre	33.25	175.35		
	ii) 20 mm i/d	Per Rft.	10.15	68.00	Per Metre	33.25	223.00		
	iii) 25 mm i/d	Per Rft.	10.15	90.55	Per Metre	33.25	297.05		
	iv) 32 mm i/d	Per Rft.	12.70	116.00	Per Metre	41.60	380.45		
	v) 40 mm i/d	Per Rft.	12.70	143.60	Per Metre	41.60	471.00		
	vi) 50 mm i/d	Per Rft.	15.10	179.50	Per Metre	49.50	588.80		
	vii) 80 mm i/d	Per Rft.	19.20	283.15	Per Metre	63.00	928.70		
	b) recessed in walls, including hooks, cutting jharries and repairing surface:	1			Ser.			38.3	
	i) 15 mm i/d	Per Rft.	15.20	57.55	Per Metre	49.90	188.75		
	ii) 20 mm i/d	Per Rft.	15.20	73.05	Per Metre	49.90	239.65		
	iii) 25 mm i/d	Per Rft.	15.85	96.80	Per Metre	52.00	317.55		
	iv) 32 mm i/d	Per Rft.	15.85	120.00	Per Metre	52.00	393.60		
	v) 40 mm i/d	Per Rft.	17.30	148.90	Per Metre	56.70	488.30		
	vi) 50 mm i/d	Per Rft.	23.75	188.90	Per Metre	77.95	619.60		
	vii) 80 mm i/d	Per Rft.	38.05	303.50	Per Metre	124.75	995.50		
]	Supply and erection of M.S. conduit pipes for wiring, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.							38.4 & 38.6	
	a) on surface, including clamps, etc.								
	i) 16 mm i/d	Per Rft.	7.05	24.30	Per Metre	23.10	79.70		
	ii) 20 mm i/d	Per Rft.	7.05	29.30	Per Metre	23.10	96.10		
	iii) 25 mm i/d	Per Rft.	7.05	35.65	Per Metre	23.10	116.95		
	iv) 32 mm i/d	Per Rft.	7.05	39.05	Per Metre	23.10	128.10		
	v) 40 mm i/d	Per Rft.	7.90	50.25	Per Metre	26.00	164.75		
	vi) 50 mm i/d	Per Rft.	9.75	61.55	Per Metre	32.00	201.95		
	b) recessed in walls, including cutting jharries, cost of hooks and repairing surface etc.							38.3 & 38.7	
	i) 16 mm i/d	Per Rft.	13.60	32.50	Per Metre	44.55	106.60		

	MRS, BI-ANNUAL PERIOD (1st FEB	KHUSHAB							
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 20 mm i/d	Per Rft.	13.60	37.20	Per Metre	44.55	122.10		
	iii) 25 mm i/d	Per Rft.	15.20	44.70	Per Metre	49.90	146.60		
	iv) 32 mm i/d	Per Rft.	15.85	49.25	Per Metre	52.00	161.50		
	v) 40 mm i/d	Per Rft.	16.55	59.45	Per Metre	54.25	194.95		
	vi) 50 mm i/d	Per Rft.	17.30	71.50	Per Metre	56.70	234.55		
3	Supply and erection of PVC pipe for wiring recessed in walls,							38.3 &	
	including inspection boxes, pull boxes, hooks, cutting jharries, and repairing surface, etc., complete with all specials.							38.5	
	i) 12 mm i/d	Per Rft.	12.25	21.75	Per Metre	40.25	71.35		
	ii) 20 mm i/d	Per Rft.	12.70	25.60	Per Metre	41.60	83.95		
	iii) 25 mm i/d	Per Rft.	14.10	30.85	Per Metre	46.20	101.20		
	iv) 32 mm i/d	Per Rft.	15.20	38.85	Per Metre	49.90	127.40		
	v) 40 mm i/d	Per Rft.	15.85	48.00	Per Metre	52.00	157.45		
	vi) 50 mm i/d	Per Rft.	16.55	59.80	Per Metre	54.25	196.20		
4	Supply and erection of PVC pipe for wiring on surface	351 N			- Sui				
-	including clamps inspection boxes, pull boxes, bends, tees,	355s.	5.	. 6	アー ふただ				
	repairing surface, etc., complete with all specials:-	100		75-17	and Que				
	repairing surface, etc., comprete with an specials.	-82			103				
	i) 12 mm i/d	Per Rft.	3.15	12.20	Per Metre	10.40	39.95		
	ii) 20 mm i/d	Per Rft.	3.15	15.45	Per Metre	10.40	50.65		
	iii) 25 mm i/d	Per Rft.	3.15	19.95	Per Metre	10.40	65.50		
	iv) 32 mm i/d	Per Rft.	3.60	27.55	Per Metre	11.90	90.40		
	v) 40 mm i/d	Per Rft.	3.60	37.05	Per Metre	11.90	121.60		
	vi) 50 mm i/d	Per Rft.	4.35	52.05	Per Metre	14.35	170.75		
5	Supply and erection of G.I. flexible pipe for wiring, including							38.4	
	welding of sockets, nipples and check nuts, etc. complete:-								
	i) 12 mm i/d	Per Rft.	8.30	34.65	Per Metre	27.25	113.65		
	ii) 20 mm i/d	Per Rft.	8.85	43.25	Per Metre	29.05	141.85		
	iii) 25 mm i/d	Per Rft.	9.15	57.45	Per Metre	30.05	188.45		
	iv) 32 mm i/d	Per Rft.	11.10	76.20	Per Metre	36.35	249.95		
	v) 40 mm i/d	Per Rft.	12.10	94.05	Per Metre	39.65	308.45		
	vi) 50 mm i/d	Per Rft.	13.30	129.25	Per Metre	43.60	424.00		
	vii) 80 mm i/d	Per Rft.	17.70	285.55	Per Metre	58.10	936.50		
6	Supply and erection PVC pipe for recessed wiring (main and							38.2 &	
	sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:-							38.3	
	i) 50 mm i/d	Per Rft.	16.55	61.30		54.25	201.00		
	ii) 80 mm i/d	Per Rft.	19.00	81.15	Per Metre	62.35	266.20		
	iii) 100 mm i/d	Per Rft.	19.00	106.00	Per Metre	62.35	347.65		
L									<u> </u>

	MRS, BI-ANNUAL PERIOD (1st FEBR	HRA, SOAN	I VALLEY	KHUSHAB					
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
7	Supply and erection of PVC pipe for surface wiring (main and sub-main) including clamps, inspection boxes, pull boxes bends etc., complete with all specials:-								
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	4.35 6.35 7.25	48.40 80.40 101.20	Per Metre Per Metre Per Metre	14.35 20.80 23.75	158.85 263.80 331.90		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	1.25	2.95	Per Metre	4.15	9.65	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	1.25	10.55	Per Metre	4.15	34.60	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):- a) 250/440 volts, PVC insulated:				P.A.			38.1	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052") viii) 19/1.63 mm (19/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.55 2.55 2.55 2.80 3.15 3.90 9.05 10.55	8.45 8.85 12.45 18.65 26.90 66.40 106.60 146.55	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	8.30 8.30 9.25 10.40 12.80 29.70 34.65	27.80 29.10 40.75 61.15 88.25 217.85 349.70 480.60		
	 b) 250/440 volts, PVC insulated cotton braided and compounded cables:- i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.80 2.80 2.80 3.00 3.35	8.75 9.15 12.70 18.80 27.10	Per Metre Per Metre Per Metre Per Metre Per Metre	9.25 9.25 9.25 9.80 10.95	28.70 30.00 41.70 61.70 88.80		
11	 vi) 7/1.63 mm (7/0.064") Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):- 	Per Rft.	3.85	66.35	Per Metre	12.60	217.65		

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 2	012 TO 3	1st JULY, 20	012) TEH:I	NOWSHE	HRA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
10	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.55 2.55 2.55 2.80 3.15 3.90	8.10 10.85 14.80 21.40 30.45 60.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	8.30 8.30 9.25 10.40 12.80	26.50 35.55 48.55 70.25 99.95 198.40		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-		/	*)				38.1 to 38.7	
	 i) 7/1.63 mm (7/0.064") ii) 19/1.32 mm (19/0.052") iii) 19/1.63 mm (19/0.064") iv) 19/2.11 mm (19/0.083") v) 37//1.83 mm (37/0.072") vi) 37/2.11 mm (37/0.083") vii) 37/2.62 mm (37/0.103") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.85 4.25 4.60 5.05 8.75 10.55 14.90	68.50 115.90 157.05 300.90 417.40 523.85 804.05	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	12.60 13.85 15.10 16.65 28.70 34.65 48.90	224.65 380.15 515.05 986.95 1,369.15 1,718.25 2,637.30		
13	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- a) PVC insulated, PVC sheathed twin core, 250/440 volts.	Ti	ian ce	XXX Oepa	s» tmen			ditto	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.80 2.80 2.80 3.00 3.35 3.85	15.10 21.40 29.35 42.95 61.10 122.15	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	9.25 9.25 9.25 9.80 10.95 12.60	49.45 70.25 96.20 140.85 200.40 400.75		
	 b) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:- 								
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.00 3.00 3.00 3.35 3.50 4.00	22.75 32.65 44.55 65.25 93.25 189.35	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	9.80 9.80 9.80 10.95 11.55 13.20	74.65 107.10 146.05 214.00 305.85 621.10		
	 c) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:- 								
	i) 3/0.74 mm (3/0.029")	Per Rft.	3.15	29.30	Per Metre	10.40	96.05		

	MRS, BI-ANNUAL PERIOD (1st FEBF	NOWSHE	HRA, SOAN	I VALLEY	KHUSHAB				
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 3/0.91 mm (3/0.036")	Per Rft.	3.15	41.15	Per Metre	10.40	135.00		
	iii) 7/0.74 mm (7/0.029")	Per Rft.	3.35	56.65	Per Metre	10.95	185.75		
	iv) 7/0.91 mm (7/0.036")	Per Rft.	3.35	84.05	Per Metre	10.95	275.70		
	v) 7/1.12 mm (7/0.044")	Per Rft.	3.50	121.05	Per Metre	11.55	397.10		
	vi) 7/1.63 mm (7/0.064")	Per Rft.	4.00	246.95	Per Metre	13.20	810.00		
	vii) 19/1.32 mm (19/0.052")	Per Rft.	5.65	461.35	Per Metre	18.50	1,513.15		
	 PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG. 								Cost of trenches where necessary is included in the rates.
	i) 19/1.32 mm (19/0.052")	Per Rft.	5.65	514.60	Per Metre	18.50	1,687.95		
	ii) 19/1.63 mm (19/0.064")	Per Rft.	6.05	688.20	Per Metre	19.80	2,257.35		
	iii) 19/1.83 mm (19/0.072")	Per Rft.	6.35	932.60	Per Metre	20.80	3,059.00		
	iv) 19/2.11 mm (19/0.083")	Per Rft.	6.85	1,305.75	Per Metre	22.50	4,282.90		
	v) 37//1.83 mm (37/0.072")	Per Rft.	7.05	1,779.30	Per Metre	23.10	5,836.05		
	vi) 37/2.11 mm (37/0.083")	Per Rft.	8.45	2,249.30	Per Metre	27.70	7,377.80		
	vii) 37/2.36 mm (37/0.093")	Per Rft.	10.15	2,741.60	Per Metre	33.25	8,992.40		
	viii) 37/2.62 mm (37/0.103")	Per Rft.	12.70	3,412.20	Per Metre	41.60	11,192.00		
14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")	1,489	5	÷	7 (1833)			38.1	
	deep, with 4.75 mm thick (3/16") bakelite sheet top, for	Your .		1	and the second			to	
	recessed wiring, including making holes for regulators,	103		36-12	Sil			38.7	
	switches, plugs, etc.			100					
	i) 10 x 10 cm (4"x4")	Each	41.60	95.40	Each	41.60	95.40		
	ii) 17.5 x 10 cm (7"x4")	Each	52.00	132.50	Each	52.00	132.50		
	iii) 22.5 x 10 cm (9"x4")	Each	69.30	164.75	Each	69.30	164.75		
	iv) 20 x 25 cm (8"x10")	Each	83.15	247.60	Each	83.15	247.60		
	v) 25 x 30 cm (10"x12")	Each	103.95	334.10	Each	103.95	334.10		
	vi) 30 x 35 cm (12"x14")	Each	138.60	437.60	Each	138.60	437.60		
15	Supply and erection of round block of Sahl wood, 10x4 cm (4"x1½") thick.	Each	11.90	21.50	Each	11.90	21.50	38.1	
16	Supply and erection of teak wood board, 4.5 cm (1¾") thick.							38.1	
	i) 17.5 x 10 cm (7"x4")	Each	16.65	68.25	Each	16.65	68.25		
	ii) 22.5 x 10 cm (9"x4")	Each	16.65	80.25	Each	16.65	80.25		
	iii) 20 x 25 cm (8"x10")	Each	18.50	94.10	Each	18.50	94.10		
	iv) 25 x 30 cm (10"x12")	Each	20.80	126.40	Each	20.80	126.40		
	v) 30 x 35 cm (12"x14")	Each	23.75	177.35	Each	23.75	177.35		
17	Supply and erection of Sahl wood board, 4.5 cm (1 ³ / ₄ ") thick.								
	i) 17.5 x 10 cm (7"x4")	Each	16.65	47.85	Each	16.65	47.85		
	ii) 22.5 x 10 cm (9"x4")	Each	16.65	64.65	Each	16.65	64.65		
	iii) 20 x 25 cm (8"x10")	Each	18.50	79.70	Each	18.50	79.70		
	iv) 25 x 30 cm (10"x12")	Each	20.80	96.40	Each	20.80	96.40		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	012 TO 3 [.]	1st JULY, 20	012) TEH:I	NOWSHE	HRA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) 30 x 35 cm (12"x14")	Each	23.75	112.55	Each	23.75	112.55		
18	Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc. a) double pole:							38.1	When the base frame is already installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps.
	 i) 15/20 Amp. ii) 30/35 Amp. iii) 60/65 Amp. iv) 100 Amp. 	Each Each Each Each	277.20 277.20 415.80 415.80	1,080.65 1,344.65 1,801.25 2,312.45	Each Each Each Each	277.20 277.20 415.80 415.80	1,080.65 1,344.65 1,801.25 2,312.45		by Rs. 38.80 and Rs. 350.80.
	 b) triple pole: i) 15/20 Amp. ii) 30/35 Amp. 	Each Each	415.80 277.20	1,520.45 1,758.65	Each Each	415.80 277.20	1,520.45 1,758.65		
	 c) triple pole with neutral link: i) 30/35 Amp. ii) 60/65 Amp. iii) 100 Amp. 	Each Each Each	277.20 415.80 544.70	1,878.65 2,397.25 3,030.10	Each Each Each	277.20 415.80 544.70	1,878.65 2,397.25 3,030.10		
19	Supply and erection of iron/aluminum clad, 500 volts main switches with triple pole and neutral link and HRC fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles.	Fi	lance	Depa	tmen.			38.1	When the base frame is already installed, the labour & composite rates will be reduced as follows:- i) For 60/65 Amp. by Rs. 21.20 and
	60/65 Amp 100 Amp 150 Amp 200 Amp 300 Amp 400 Amp 500 Amp	Each Each Each Each Each Each Each	415.80 544.70 544.70 1,247.40 1,247.40 1,767.15 1,871.10	2,460.60 3,538.70 4,978.70 7,891.80 9,144.60 12,272.55 15,656.20	Each Each Each Each Each Each Each	415.80 544.70 544.70 1,247.40 1,247.40 1,767.15 1,871.10	2,460.60 3,538.70 4,978.70 7,891.80 9,144.60 12,272.55 15,656.20		Rs. 145.50. ii) For 100 to 300 Amp. by Rs. 21.20 and Rs. 350.80 iii) For 400 to 500 Amp. by Rs. 42.20 and Rs. 526.20
20	Supply and erection of iron/aluminum clad, branch distribution board, 250 volt, on angle iron frame of suitable size with 3 mm (1/8") M.S. sheet covering:							ditto	When the base frame is already installed the labour and composite rates will be reduced by Rs. 19.50 & Rs. 152.20 respectively.
	 i) 2 way, 15 Amp per way ii) 3 way, 15 Amp per way iii) 4 way, 15 Amp per way iv) 5 way, 15 Amp per way v) 6 way, 15 Amp per way 	Each Each Each Each Each	138.60 138.60 138.60 138.60 138.60	459.00 459.00 525.00 579.00 621.00	Each Each Each Each Each	138.60 138.60 138.60 138.60 138.60	459.00 459.00 525.00 579.00 621.00		

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2012 TO 3 ⁻	1st JULY, 2	012) TEH:I	NOWSHE	HRA, SOAN	VALLEY	KHUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	vi) 7 way, 15 Amp per way	Each	138.60	669.00	Each	138.60	669.00		
	vii) 8 way, 15 Amp per way	Each	138.60	717.00	Each	138.60	717.00		
	viii) 9 way, 15 Amp per way	Each	138.60	765.00	Each	138.60	765.00		
	ix) 10 way, 15 Amp per way	Each	138.60	837.00	Each	138.60	837.00		
	x) 11 way, 15 Amp per way	Each	138.60	885.00	Each	138.60	885.00		
	xi) 12 way, 15 Amp per way	Each	138.60	939.00	Each	138.60	939.00		
	xii) 2 way, 30 Amp per way	Each	207.90	528.30	Each	207.90	528.30		
	xiii) 3 way, 30 Amp per way	Each	207.90	534.30	Each	207.90	534.30		
	xiv) 4 way, 30 Amp per way	Each	207.90	588.30	Each	207.90	588.30		
	xv) 5 way, 30 Amp per way	Each	207.90	648.30	Each	207.90	648.30		
	xvi) 6 way, 30 Amp per way	Each	207.90	690.30	Each	207.90	690.30		
	xvii) 7 way, 30 Amp per way	Each	207.90	750.30	Each	207.90	750.30		
	xviii 8 way, 30 Amp per way	Each	207.90	798.30	Each	207.90	798.30		
	xix) 9 way, 30 Amp per way	Each	207.90	846.30	Each	207.90	846.30		
	xx) 10 way, 30 Amp per way	Each	207.90	918.30	Each	207.90	918.30		
		1.28%							
21	Supply and erection of bus bars, for 500 volts 3 phase A.C.	. 88 1			-1 887				When the base frame is already
	supply with four copper bars, including glazed porcelain	1526		Survey of the state of the stat	J 5.69%			38.1	installed the labour and composite
	bridges, on angle iron board, fixed with rag bolts and M.S.	1.838		÷	1 183				rates will be reduced by Rs. 21.20 and
	sheet box 1.5 mm thick, etc. complete:-	1		1000	and a				Rs. 145.50 respectively.
	i) 60 Amp. with 4 copper bars	Each	509.85	2,332.50	Each	509.85	2,332.50		
	size 1½"x1/8" (40 x 3 mm) ii) 100 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm)	Each	509.85	2,332.50	Each	509.85	2,332.50		
	iii) 200 Amp with 4 copper bars size $2"x1/8"$ (50x 3 mm)	Each	811.80	2,754.45	Each	811.80	2,754.45		
	iv) 300 Amp with 4 copper bars size 2"x3/16" (50x 5 mm)	Each	935.55	2,878.20	Each	935.55	2,878.20		
	v) 500 Amp with 4 copper	Each	613.80	3,072.00	Each	613.80	3,072.00		
	size 2"x1/4" (50x 6 mm)								
22	 Supply and erection of plain pendent lamp holder, complete with bakelite lamp holder and flexible twin wire 23/0.0076" upto 2 metre length (without bulb and shade). 	Each	8.65	86.30	Each	8.65	86.30	38.1	
	ii) Extra for additional length of flexible wire, beyond2 metres.	Per Rft.		1.65	Per Metre		5.45		
23	Supply and erection of counter weight pedent with porcelain counter weight, and fitting on bakelite lamp holder, with flexible twin wire 23/0.0076" complete (without bulb and shade).	Each	17.35	201.00	Each	17.35	201.00	38.1	
24	Supply and erection of stiff pedent with brass/metal pipe 6.3 cm (2.5") long, and 15 mm (1/2") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm	Each	27.05	355.70	Each	27.05	355.70	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(3/0.029").												
25	Supply and erection of 22.5 cm (9") long swan neck plain brass/steel brass oxidised bracket lamp holder, complete.	Each	28.00	69.65	Each	28.00	69.65	ditto					
26	Supply and erection of wall type/pole type bracket, with double cover water tight reflector, flexible wire and brass bolder.	Each	38.65	373.80	Each	38.65	373.80	ditto					
27	Supply and erection of bakelite button holder shade, large size.	Each	6.15	33.80	Each	6.15	33.80	ditto					
28	Supply and erection of call bell 220/250 volts, fixed on teak wood board 17.5×10 cm (7"x4").	Each	27.05	190.40	Each	27.05	190.40	38.1					
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	5.20	184.90	Each	5.20	184.90	38.1					
30	Supply and erection of ceiling rose, bakelite.	Each	8.65	19.15	Each	8.65	19.15	ditto					
31	Supply and erection of switches 5 Amp.	1		الطومت الأ	an a								
	 i) open type ii) piano type iii) ring type, recessed iv) plate type, recessed v) double control, open type vi) double control, ring type recessed vii) double control, piano type 	Each Each Each Each Each Each Each	8.30 8.30 8.30 8.30 11.70 11.70 11.70	20.00 20.00 15.50 40.40 29.70 30.90 27.30	Each Each Each Each Each Each Each	8.30 8.30 8.30 11.70 11.70 11.70	20.00 20.00 15.50 40.40 29.70 30.90 27.30	ditto					
32	Supply and erection of switches 10/15 Amp.							ditto					
	i) open typeii) recessed type	Each Each	8.30 8.30	31.10 39.50	Each Each	8.30 8.30	31.10 39.50						
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	8.30	61.10	Each	8.30	61.10	ditto					
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	8.30	45.50	Each	8.30	45.50	ditto					
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.							ditto					
	i) open typeii) recessed type	Each Each	8.30 8.30	39.50 75.50	Each Each	8.30 8.30	39.50 75.50						
36	Supply and erection of 3 pin switch and plug combined, recessed type.							ditto					
	i) 5 Amp	Each	8.30	58.70	Each	8.30	58.70						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	ii) 10/15 Amp	Each	8.30	83.30	Each	8.30	83.30						
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe, open type.	Each	8.30	118.70	Each	8.30	118.70	ditto					
38	Supply and erection of cut out, bakelite.							ditto					
	i) open typeii) recessed type	Each Each	4.60 4.60	23.80 29.80	Each Each	4.60 4.60	23.80 29.80						
39	Supply and erection of button holder.							38.1					
	i) bakelite large sizeii) brass	Each Each	5.20 5.20	20.80 20.80	Each Each	5.20 5.20	20.80 20.80						
40	Supply and erection of brass bracket with holder.	Each	6.95	22.55	Each	6.95	22.55	ditto					
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	4.60	15.40	Each	4.60	15.40	ditto					
42	Supply and erection of kitkat, 500 volt:				1 Alexandre			ditto					
	 i) 15/20 Amp ii) 30/35 Amp iii) 60/65 Amp iv) 100 Amp v) 200 Amp vi) 300 Amp vii) 400 Amp viii) 500 Amp 	Each Each Each Each Each Each Each Each	8.60 9.35 14.30 16.10 18.40 24.55 24.55	33.80 34.55 54.50 89.90 130.60 278.20 349.15 498.55	Each Each Each Each Each Each Each Each	8.60 9.35 14.30 16.10 18.40 24.55 24.55	33.80 34.55 54.50 89.90 130.60 278.20 349.15 498.55						
43	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete.							38.1					
	i) double rod (80 watts) with two chokes and 2 starters.	Per set	153.45	948.55	Per set	153.45	948.55						
	ii) single rod (40 watts) with one choke and one starter.	ditto	122.75	479.90	ditto	122.75	479.90						
	iii) round tube, 32 watt, with one choke and one starter, without cover.	Each	122.75	542.30	Each	122.75	542.30						
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	102.30	641.80	ditto	102.30	641.80						
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking							ditto					

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	arrangement, including painting:- i) 60x35x15 cm (24"x14"x6")	Each	319.90	2,257.70	Each	319.90	2,257.70				
	ii) 95x40x20 cm (38"x16"x8") iii) 105x52.5x22.5 cm (42"x21"x9") iv) 135x70x27.5 cm (54"x28"x11")	Each Each Each	461.20 701.10 769.75	2,822.80 3,885.70 5,824.50	Each Each Each	461.20 701.10 769.75	2,822.80 3,885.70 5,824.50				
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate $25x6$ mm (1"x ¹ /4"), with bolts and nuts for hanging ceiling fans.	Each	20.45	126.05	Each	20.45	126.05	38.1 & 38.10			
46	Supply and erection of girder strut, of M.S. tee section 40x40x6 mm (1½"1½"x ¼"), complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	27.05	772.05	Each	27.05	772.05	ditto			
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with $75x40x3$ mm ($3"x11/2"x1/8"$) M.S. steel channel, with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	29.00	1,163.35	Each	29.00	1,163.35	38.1			
48	Supply and erection of roof suspension hook of M.S plate 75x40x12.7mm (3"x1½"x½") with 16 mm (5/8") hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Each	38.65	461.00	Each	38.65	461.00				
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	10.65	25.05	Each	10.65	25.05	ditto			
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	366.30	2,049.20	Each	366.30	2,049.20	38.12			
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x!4") section:-										
	 i) 0.60 metre (2') long for 2 lines. ii) 1.200 metre (4') long for 4 lines. 	Each Each	74.25 86.65	505.50 1,045.65	Each Each	74.25 86.65	505.50 1,045.65				
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.	Per Rft.	5.25	17.25	Per Metre	17.25	56.50	38.14			
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	7.25	26.30	Per Metre	23.75	86.20	ditto			
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line, include shackle insulator for holding	Per Rft.	31.70	227.65	Per Metre	103.95	746.60				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	insulated wire and straining devices for bearer wire and other accessories etc., complete.											
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	30.70	225.15	Per Metre	100.65	738.55					
56	Supply and erection of lightning arrestor horn type, complete.	Each	162.35	2,082.35	Each	162.35	2,082.35					
57	Supply and erection of shackle insulator, medium size.	Each	19.60	169.60	Each	19.60	169.60	38.12				
58	Supply and erection of pin insulator, green medium size.	Each	19.60	61.60	Each	19.60	61.60	ditto				
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	10.20	1,147.60	Per Kg	10.20	1,147.60	38.1				
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire, pole to pole etc.	Per Kg	10.20	97.60	Per Kg	10.20	97.60	ditto				
61	Wiring overhead line in 2 single core, PVC/weather proof cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.	10	N.	X	153			38.12				
	i) 3/0.74 mm (3/0.029")	Per Rft.	2.75	9.70	Per Metre	9.00	31.80					
	ii) 7/0.74 mm (7/0.029")	ditto	2.75	17.40	ditto	9.00	57.05					
	iii) 7/0.91 mm (7/0.036")	ditto	2.75	23.75	ditto	9.00	77.85					
	iv) 7/1.12 mm (7/0.044")	ditto	2.75	32.20	ditto	9.00	105.60					
62	Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft.	4.90	17.15	Per Metre	16.00	56.30	38.1				
63	Supply and erection of street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp.	Each	135.30	863.20	Each	135.30	863.20					
64	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):											
	i) G.E.C. designii) Philips design	Each ditto	270.60 270.60	2,514.60 2,940.60	Each ditto	270.60 270.60	2,514.60 2,940.60					
65	Supply and fitting of mercury vapour lamp, complete with choke set. i) 125 watt lamp ii) 250 watt lamp	Each ditto	102.30 122.75	942.30 1,742.75	Each ditto	102.30 122.75	942.30 1,742.75					
66	Manufacture and erection of angle iron lattice steel structure	Each	4,596.55	19,988.40	Each	4,596.55	19,988.40	38.13	The composite rate will be reduced			
00	manuracture and erection of angle non fattice steel structure	Lach	4,570.55	19,900.40	Lacii	4,590.55	17,700.40	30.13	The composite rate will be reduced			

	MRS, BI-ANNUAL PERIOD (1st FEBR	HRA, SOAN	I VALLEY	KHUSHAB					
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1¼"x1¼"x3/16" (30x30x5 mm) angle iron legs and ¾"x¾"1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1¾"x1¾"x3/16" (45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x¼" (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.								or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3½'x3½' (2400x1050x1050 mm), etc. complete in all respects.	Each	4,473.80	31,575.55	Each	4,473.80	31,575.55	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (¹ / ₂ ") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	603.90	3,223.95	Job	603.90	3,223.95		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in							38.11	
	 15 mm (¹/₂") dia G.I. pipe, best quality:- i) on surface, including clamps, etc. ii) recessed in wall, including hooks, jharries and making good surface. 	Per Rft. ditto	6.20 14.75	49.20 59.10	Per Metre ditto	20.30 48.30	161.35 193.80		
70	Bonding to earth with wire on surface, including cost of wire, clamps, thimbles, etc.							ditto	
	a) G.I. wire: i) 8 SWG ii) 16 SWG	Per Rft. ditto	2.55 2.55	7.70 3.95	Per Metre ditto	8.30 8.30	25.25 12.90		
	b) Copper wire:								
	i) 16 SWG	Per Rft.	2.55	10.00	Per Metre	8.30	32.85		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	Ra	ate (British S	System)	Rat	e (Metric Sy	rstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ii) 20 SWG	ditto	2.55	5.25	ditto	8.30	17.15					
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	9.90	13.55	Per Metre	32.45	44.40	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).			
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	402.60	3,625.30	Each	402.60	3,625.30	ditto				
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.			*)								
	 i) tape 40x3 mm (1½"x1/8") ii) tape 50x3 mm (2"x1/8") 	Per Rft. ditto	14.75 14.75	244.65 292.75	Per Metre ditto	48.30 48.30	802.50 960.20					
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	270.60	2,160.60	Job	270.60	2,160.60					
75	Supply and erection of electric energy meter, including meter testing fee, etc.	100		× C	SET.			38.1				
	a) single phase:	Fa	1.an.cz	Depa	tmen	line and the second sec						
	 i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts 	Each ditto	103.95 103.95	1,867.95 1,867.95	Each ditto	103.95 103.95	1,867.95 1,867.95					
	b) three phase, 4 wires:											
	 i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts 	Each ditto ditto	207.90 306.90 306.90	5,325.90 5,424.90 5,424.90	Each ditto ditto	207.90 306.90 306.90	5,325.90 5,424.90 5,424.90					
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.			
	 i) 1200 mm (48") sweep, 275-300 RPM. ii) 1400 mm (56") sweep, 250-275 RPM. 	Each ditto	205.45 230.20	798.10 914.00	Each ditto	205.45 230.20	798.10 914.00		ine rate.			
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.			
	 i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM 	Each ditto	138.60 138.60	549.70 622.85	Each ditto	138.60 138.60	549.70 622.85					
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	166.30	726.65	Each	166.30	726.65		The credit of out turn of dismantled material has been accounted for in			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB											
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
79	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	26.00	86.00	Each	26.00	86.00	38.1	the rate.			
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	20.80	44.80	Each	20.80	44.80	ditto				
	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	26.00	134.00	Each	26.00	134.00	ditto				
82	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	52.00	160.10	Each	52.00	160.10		The credit out turn of dismantled material has been accounted for in the rate.			
	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	108.95	144.25	Each	108.95	144.25		uic faic.			
		Ser and	S	مار مارس با	7	÷						

********* Finance Department

25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Railway Track, etc.												
1	Laying, linking and packing tramway line.	100Lft.	1027.70		Metre	33.70							
2	Dismantling tramway track.	100Lft.	341.80	*)	Metre	11.20							
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	2667.50	-	Metre	87.50							
4	Linking points and crossings, complete with fastenings.	Each	2590.50		Each	2590.50							
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	281.15		Each Point	281.15							
6	Fixing street lamp posts.	Each	336.60	X	Each	336.60							
	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	3095.40	Depar	100 Nos	3095.40							
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	396.90		100 Nos	396.90							
	IRON WORK												
	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	1613.70	6785.40	100 Kg	3176.60	13357.10						
	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	Per Cwt	576.20	5500.50	100 Kg	1134.20	10827.75						
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	178.95		100 Kg	352.25							
12	Fixing corrugated iron sheet, including revitting, etc.	100 Sft.	649.45		sq.m	69.90							
13	Erecting corrugated iron sheet tanks, upto 20'	Per Cwt	322.35		100 Kg	634.55							

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB												
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(6 m) height.												
14	Erecting rolled steel beams or old rails, in roofs, etc., erection and fixing in position.	Per Cwt	198.35		100 Kg	390.40							
15	Erecting rolled steel beams or rails, erection for posts etc. (other than in roofs).	Per Cwt	96.05		100 Kg	189.05							
16	Making bolts and nuts of iron rods.	Per Cwt	1227.60	6970.05	100 Kg	2416.55	13720.55						
17	Cutting rails, rolled steel joists and beams, with hacksaw:-		1										
	a) upto 6" size (150 mm)b) above 6" size (150 mm)	Per Cut Per Cut	120.80 177.40		Per Cut Per Cut	120.80 177.40							
18	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	57.50	in the	Per Cwt Cut	57.50							
19	Bending rolled steel beams or rails.	Per Bend	61.90	263.40	Per Bend	61.90	263.40						
20	Drilling holes, in plates upto ¹ /2" (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	24.90	Depar	Per Hole	24.90							
21	Extra for drilling holes in plates over ¹ /2" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	14.05		Per Hole	14.05							
22	Rivetting 1/8" dia (3 mm).	100 Nos	368.50		100 Nos	368.50							
23	Cutting out Rivets, all sizes.	100 Nos	1023.00		100 Nos	1023.00							
24	Fitting and erection of gutters of sheet iron.	Per Lft.	43.85		Metre	143.80							
25	Cutting and fixing iron bars, for barred windows.	Per bar	23.10		Per bar	23.10							
26	Cutting G.I. sheets.	Each Cut	12.60		Each Cut	12.60							
27	Notching web or foot of rail posts, for housing rail beams.	Per	275.00	409.40		275.00	409.40						
28	Hoop iron netted trellis work fixed with nails.	Notch Per Sft.	16.10		Notch sq.m	173.30							
29	Fixing zinc iron or G.I. sheet on table tops.	Per Sft.	9.55		sq.m	102.75							
30	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 34" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	101.85	638.95	sq.m	1095.70	6875.15						

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY	′, 2012 TO 3′	1st JULY, 20 [,]	12) TEH:	NOWSHE	EHRA, SOAN	VALLEY	KHUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
31	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and ³ /4" (20 mm) square bars 4" (100 mm) centre to centre, with locking arrangement.	Per Sft.	105.55	784.15	sq.m	1135.60	8437.60		
32	Making and fixing grating in opening, including fixing at site with flat iron 2"x3/8" (50x10 mm) and 3/4" (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	40.65	318.10	sq.m	437.20	3422.65		
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed to 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete.	Per Rft.	211.15	678.20	Metre	692.75	2225.00		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8" punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	96.85	458.60	Metre	317.75	1504.60		
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	70.40	509.95 Depar	Metre	230.97	1673.06		-do-
36	Providing and fixing collapsible gate made of 2"x2"x"¼" (50x50x6 mm) tee iron at top and bottom, channel iron verticals ¾"x¼"x1/8" (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of ¾"x¼"x1¼"x1/8" (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	145.70	551.25	sq.m	1567.85	5931.20		
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1¼"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	33.30	207.20	sq.m	358.05	2229.60		
38	Providing and fixing M.S. angle iron 1 ¹ /2"x1 ¹ /2"x ¹ /4"	Per Rft.	15.05	123.60	Metre	49.30	405.50		

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY	, 2012 TO 3	1st JULY, 20 [.]	12) TEH:	NOWSHE	EHRA, SOAN	VALLEY	KHUSHAB
Sr.	Description		Rate (British S	ystem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.								
39	Providing and fixing stair railing of 2 ¹ / ₂ " (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.	Per Rft.	98.25	608.40	Metre	322.30	1996.05		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	13.85	44.20	sq.m	149.15	475.70		
41	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1½"x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ¾"x1"x¾"x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the	4	inance	Depat	7 G t m en	- Mark			For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	a) without wire gauze:			22					
	 a) while u whe gauze. i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick b) fixed with wire gauze, 22 SWG 	Per Sft. ditto ditto ditto ditto	38.90 38.90 38.90 38.90 38.90 38.90	251.80 254.20 259.00 261.40 263.80	sq.m ditto ditto ditto ditto	418.65 418.65 418.65 418.65 418.65	2709.60 2735.40 2787.05 2812.90 2838.70		
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick 	Per Sft. ditto ditto ditto ditto	52.45 52.45 52.45 52.45 52.45	293.25 295.65 300.45 302.85 305.25	ditto	564.50 564.50 564.50 564.50 564.50	3258.45		
42	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1¼"x1¼" (30x30mm) for leaves including M.S. square bars ¼"x14" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG)								

	MRS, BI-ANNUAL PERIOD (1st FE	KHUSHAB							
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec. No.	Remarks
INO.		Unit	Labour	Composite	Unit	Labour	Composite	110.	
	 beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects. a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass panes ¹/₄" (6 mm) thick. 	Per Sft.	40.40	239.10	Sq.m	434.60	2572.90		
	b) For fixed panels without wire gauze.	ditto	39.35	133.60	ditto	423.45	1437.80		
43	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	40.40	297.55	Sq.m	434.50	3201.60		
44	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	50.10	352.70 Depar	Per Sft.	538.95	3795.10		
45	Flapping G.I. pipes for bath room drains.	Each	306.90	340.50	Each	306.90	340.50		
46	Supply and fixing iron grating for fire place.	Per Sft.	87.10	183.10	sq.m	937.40	1970.35		
47	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	27.05		Metre	88.75			
48	Providing and fixing angle iron railing, using 2½"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x14" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long 3¼" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	46.50	743.20	Metre	152.60	2438.35		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
49	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5 mm), angle iron post 3¼ ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" (225x225x300 mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	1013.50	9031.80	Metre	33.25	296.30				
50	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects.	100Rft.	1642.15	11365.75	Metre	53.90	372.90				
51	Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s Al-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	58.10	396.50 Depar	sq. m	625.15	4266.35		 Increase rate by Rs. 30.00 per Sft or Rs.322.80 per Sq-metre if sections thickness is 2 mm. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used. 		
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan Cables having frame size of $100 \times 20 \text{ mm} (4"x^34")$ and leaf frame sections of $50 \times 20 \text{ mm} (2"x^34")$, all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Sft	84.15	304.10	sq. m	905.45	3272.10		 (1) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if section thickness is 1.2 mm. (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminium shade. (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per sq-metre if local glass is used. 		

26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB										
Sr.	Description		Rate (British Sy	vstem)	Rat	te (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	45.05	53.50	Per sq.m	484.70	575.90		The board is to be of cement plaster ¹ / ₂ " (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.	
2	Fixing handles to iron hammers.	Each	43.30		Each	43.30	-			
3	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete. <u>Surveying</u>	100Lft.	3,814.40	20,627.25	L.m.	125.15	676.75		Vertical bars in straining and stiffening posts to be 4 No. each by 1/2" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be 1/4" (6 mm) dia. at 12" (300 mm) centre to centre.	
4	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	24.55	116.95	Each	24.55	116.95			
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	69.30	84.90	100Nos.	69.30	84.90			
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	166.30	346.30	100Nos.	166.30	346.30			
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	53.45	60.65	Per L.M.	175.40	199.00			
8	Placing boundary pillars in position, including digging pits.	Each	35.65	-	Each	35.65	-			
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	146.50	297.90	Each	146.50	297.90		Composite rate does not include cost of iron distance marks.	
	Hand Pumps & Pressure Pipes									
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	27.05	-	Per cut	27.05	-			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2012 TO 31st JULY, 2012) TEH:NOWSHEHRA, SOAN VALLEY KHUSHAB									
Sr.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	48.90	-	Per cut	48.90	-			
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	34.00	-	Each End	34.00	-			
13	Assembling 1 ¹ /2" (40 mm) dia pressure pipe.	100Lft.	125.40	-	Per Metre	4.10	-			
14	Boring and fixing 1 ¹ / ₂ " (40 mm) dia pressure pipe:									
	a) in ordinary soilb) in clayc) in shingle	Per Lft. Per Lft. Per Lft.	44.90 89.45 133.98	C	Per Metre Per Metre Per Metre	147.25 293.40 439.55	-			
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	20.00	-	Per Metre	65.60	-			
16	Fixing hand pump (Machine only)	Each	83.15		Each	83.15	-			
	<u>Rest House Furniture & Fuel, etc.</u>	15	R	in a star	7 🎉					
17	Washing Niwar of bed.	Per bed	297.00	317.15	Per bed	297.00	317.15			
18	Washing Durries.	100Sft.	396.00	444.00	sq.m	42.65	47.80			
19	Recaning chairs:	9	inanci		tmeni	ŀ.				
	 i) office chairs, single caning seat only. ii) office chairs, double canning seat only. iii) office chairs, single caning back only. iv) office chairs, double caning back only. v) easy chairs, single caning seat only. vi) easy chairs, double caning seat only. vii) easy chairs, double caning seat only. viii) easy chairs, single caning only, back and seat in one piece. viii) easy chairs, double caning back & seat in one piece or couches with caned area about 16 Sft (1.5 Sqm). 	Each Each Each Each Each Each Each	145.55 187.10 103.95 166.30 103.95 291.05 415.80 623.70	176.15 230.30 105.90 182.90 145.00 352.25 667.80 1,235.70	Each Each Each Each Each Each Each	145.55 187.10 103.95 166.30 103.95 291.05 415.80 623.70	176.15 230.30 105.90 182.90 145.00 352.25 667.80 1,235.70			
20	Making and fixing Hat pegs ordinary.	Each	74.85	416.10	Each	74.85	416.10			
21	Weaving charpoy.	Each	270.25	-	Each	270.25	-			
22	Sweeping chimney.	Each	66.00	67.20	Each	66.00	67.20			
23	Picture railing, including making, fixing and painting.	Per Lft.	21.40	92.15	Per LM	70.25	302.35			
24	Cutting fuel wood, from plantation.	100Kg	88.40	-	100Kg	88.40	-			
25	Splitting fuel wood.	100Kg	185.15	-	100Kg	185.15	-			

	MRS, BI-ANNUAL PERIOD (1st FE	VALLEY	KHUSHAB						
Sr.	Description	Rate (British System)		Rate (Metric System)			Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	298.15	-	100Kg of Char- coal	298.15	-		
27	Filling cement bags with coal and sewing (including cost of strings).	100Cft.	811.80	814.70	cu.m	286.75	287.75		
28	Supplying manure.	Cart Load	99.00	219.00	Cart Load	99.00	219.00		Capacity of cart, 20 Cft. (0.57 cu.m).
29	Washing punkha frills.	Each	83.15	-	Each	83.15	-		
30	Washing:-			×					
	a) table clothb) napkins, dusters, etc.	Each Each	20.80 13.85		Each Each	20.80 13.85	-		
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	38.10		Each No.	38.10	-		
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	39.85	(عاد من بري	Each No.	39.85	-		
33	Dredging Sumps.	Per Shift	1,485.00	No. Co	Per Shift	1,485.00	-		Not less than five gangmen to be employed for each shift to ensure effective dredging.
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each 9	123.75	Dep <u>a</u> i	Each	123.75	-		
35	Bailing out water:-								
	a) by hand b) by pump	1000 Cft. 1000 Cft.	1,188.00 126.85	267.70	cu.m ditto	41.95 4.50	9.45		Rate includes cost of providing pump, POL and operation charges, etc.
36	Drilling holes in R.C. Trough.	Per Nos.	67.65	-	Per Nos.	67.65	-		
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.								The rate includes overlaps.
	 i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick) 	Per Sft. Per Sft.	0.60 1.25	1.75 2.20	sq.m sq.m	6.70 13.40	18.75 23.50		
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100Sft.	890.35	5,674.40	sq.m	95.80	610.55		
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	152.75	-	Per Hole	152.75	-		Same rate to be paid for other type of masonry and R.C.C. work.

Sr.	Description	I	Rate (British System)			Rate (Metric System)			Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
40	Making 1 ¹ / ₂ "x1 ¹ / ₂ " (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	133.65	-	Per Plank	133.65	-		
41	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	39.60		Per hole per c.m depth	15.85			
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	41.60	172.35	sq.m of each spray	4.45	18.55		
43	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.	67 coo-							
	 i) without cement concrete base. ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm). 	100Rft. 100Rft.	4,537.35 5,004.20	20,257.15 22,057.90	Per Metre Per Metre	148.85 164.15	664.45 723.50		

Finance Department