# MARKET RATES SYSTEM (MRS)

BI-ANNUAL PERIOD

(1<sup>ST</sup> FEBRUARY, 2013 TO 31<sup>ST</sup> JULY, 2013)

GOVERNMENT OF THE PUNJAB

FINANCE DEPARTMENT

## TABLE OF CONTENTS

Sr No.	Chapter	Pa	ıge N	<i>(os</i>
01.	Carriage	3	to	23
02.	Loading, Unloading & Stacking	24	to	26
03.	Earthwork (Excavation & Embankment)	27	to	33
04.	Dismentling (Demolition).	34	to	38
05.	Mortar	39	to	40
06.	Concrete	41	to	50
07.	Brickwork	51	to	56
08.	Stone Masonary	57	to	59
09.	Roofing	60	to	65
10.	Flooring	66	to	70
11.	Surface Rendering	71	to	74
12.	Wood Work	75	to	84
13.	Painting L Varnishing	85	to	90
14.	Lining of Canals	91	to	92
15.	Sheet Piling	93	to	94
16.	Protection & Diversion Work	95	to	104
17.	Outlets	105	to	106
18.	Road & Road Structure	107	to	111
19.	Plumbing, Sanitary Installation & Gas Fittings	112	to	117
20.	Surface Drainage	118	to	119
21.	Sewerage	120	to	124
22.	Sinking of Wells	125	to	127
23.	Tubewell & Water Supply	128	to	139
24.	Electric Installation	140	to	152
25.	Iron Work	153	to	158
26.	Miscellaneous	159	to	162

# 1. CARRIAGE

Note: 1 The rates are applicable to carriage of material on pacca roads only.

For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.

Note: 2 For hilly areas 25% above the rates in the plain areas shall be allowed for total mileage (Km) covered.

Note: 3 In case of articles longer than 15 ft. (4.6 m) carried in trucks, the following rates shall be allowed:-

- i) Above 15 ft. to 25 ft. (4.6 to 7.6 m): Total rates to be paid for 15 ft. to 25 ft. (4.6 to 7.6 m) length will be 1.5 times of the rate given in the Composite Schedule of Rates.
- ii) Above 25 ft. (7.6 m): The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.

The length measured shall not be the actual length, but the length of the form of consignment as actually received.

Note: 4 The term 'mile' (Km) whenever used is to mean statute mile (Km).

251 Kms & susequent Kms

Note: 5 The rates include loading and unloading of material from the conveyance and stacking as directed.

Note: 6 The rates for carriage by boat or steamer shall be the same as by any other mechanical means on land.

## MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND Sr. Description Rate (Metric System) Spec. Remarks No. Unit of No. M/ment Labour Composite 1 Carriage of 100 Cft. (2.83 cu.m) of all materials like stone 16.1 aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cft. (4.25 cu.m) of timber, by truck or by any other means owned by the contractor. 1st chain (1st 30 m) 30M 101.75 2nd chain (2nd 30 m) 30M 18.75 30M 3rd to 10th chain (60 to 300 m) 11.65 1000 to 3000 ft. (300 to 900 m) 300 Metre 114.35 1st Km 161.95 Km 2nd Km 76.40 Km 3rd Km 58.50 Km 4th Km Km 40.70 5th Km Km 37.70 37.05 6th Km Km 7th Km Km 34.40 8th Km Km 34.00 9th Km Km 31.80 29.55 10th Km Km 11th Kms to 200Kms 21.90 Km 201 Kms to 250 Kms 3.25 Km

2.00

Km

	MRS, BI-ANNUÂL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 2013) DISTRICT RAWA		RICT RAWA	LPIND	
Sr.	Description		ı			te (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
2	Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastenings, points and crossing, Bridge Girders, pipes, sheets, Rail, M.S. bars, etc. etc. by truck or any other means owned by the contractor.							16.1	Cement carried in containers other than bags will be paid according to this item. The word "pipes" covers G.I,C.I,R.C.C. and P.C.C.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km		35.		30M 30M 30M 300M Km Km Km	101.75 18.75 11.65 114.35 161.95 76.40 58.50 40.70 37.70			
	6th Km	26	-776		Km	37.05			
	7th Km 8th Km	81			Km Km	34.40 34.00			
	9th Km	18	-	.6	Km	31.80			
	10th Km	7.			Km	29.55			
3	11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms Carriage of 100 maunds of fuel wood by truck or any other means owned by the contractor:	Œ.	ian (r (	Departi	Km Km Km	21.90 3.25 2.00		16.1	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 30 M 30 M 300 M Km Km Km	101.75 18.75 11.65 114.35 161.95 76.40 58.50 40.70			
	5th Km				Km	37.70			
	6th Km				Km	37.05			
	7th Km				Km	34.40			
	8th Km				Km	34.00			
	9th Km				Km	31.80			

	MRS, BI-ANNUAL PERIO	DD (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWA	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	10th Km				Km	29.55			
4	11th & subsequent Kms Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm) or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or any other means owned by the contractor:-				Km	21.90		ditto	Reduce the rate by 33% in case of carriage of 1000 Nos. tiles size 12"x6"x1'4" (300 x 150 x 30 mm).
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30 M 30 M 30 M 300 M	101.75 18.75 11.65 114.35			
	1st Km 2nd Km 3rd Km				Km Km Km	161.95 76.40 58.50			
	4th Km 5th Km	j	200		Km	40.70 37.70			
	6th Km				Km	37.05			
	7th Km	555	-	-	Km	34.40			
	8th Km	1	100		Km	34.00			
	9th Km			G. Bern	Km	31.80			
	10th Km	Œi.	nann Car	Departs	Km	29.55			
5	11th & subsequent Kms Carriage of 100 cft. (2.83 cu.m) of all material like stone, aggregate, spawl, kankar lime(unslaked), surkhi, etc. or 150 cft. (4.25 cu.m) of timber, by means of material trolly.				Km	21.90		16.1	Material trolly to be supplied by the Government and maintained and run by the contractor.
	1st chain (1st 30 m) 2nd chain to 10th chain (2nd 30 m to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 300 M Km Km	101.75 18.75 114.35 132.85 101.25			
	3rd Km 4th Km				Km Km	54.00 42.25			
	5th Km				Km	37.10			
	6th Km 7th Km				Km	35.65 30.10			
	7th Km 8th Km				Km Km	29.75			
	9th Km				Km	27.80			
	10th Km				Km	25.85			
	11th Kms to 200Kms 201 Kms to 250 Kms				Km Km	20.85 3.25			

	MRS, BI-ANNUAL PERIC	DD (1st FE	BRUARY,	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
6	251 Kms & susequent Kms Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastening, points and crossing, Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by means of material trolly.				Km	2.00		16.1	Material trolly to be supplied by the Government and maintained and run by the contractor.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km				30 M 30 M 300 M Km Km Km Km	101.75 18.75 114.35 132.85 101.25 54.00 42.25 37.10			
	6th Km		/ >	1	Km	35.65			
	7th Km 8th Km		_		Km Km	30.10 29.75			
	9th Km	11.6			Km	27.80			
	10th Km	8			Km	25.85			
	11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms			(6)	Km Km Km	20.85 3.25 2.00			
7	Carriage of 100 maunds of fuel wood, by means of material trolly.  1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km	Œ	1.031 (8	Departs	30 M 30 M 300 M Km Km Km	101.75 18.75 114.35 132.85 101.25 54.00 42.25		ditto	Material trolly to be supplied by the Government and maintained and run by the contractor.
	5th Km				Km	37.10			
	6th Km				Km	35.65			
	7th Km				Km	30.10			
	8th Km				Km	29.75			
	9th Km				Km	27.80			
	10th Km				Km	25.85			
8	11th & subsequent Kms Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm), by means of material trolly.				Km	20.85		ditto	Material trolly to be supplied by the Government and maintained and run
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	101.75 18.75			by the contractor.

	MRS, BI-ANNUAL PERIO	ן ואנוך על (ואנור)	DRUAK I, Z	013 10 31st	JULY, 20	13) DIST	KICT KAWAL	עמוץ	
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.	2 coverption				Unit of			No.	
					M/ment	Labour	Composite		I .
	1000 to 3000 ft. (300 to 900 m)				300 M	114.35			
	1st Km				Km	132.85		16.1	
	2nd Km 3rd Km				Km	101.25 54.00		16.1	
	4th Km				Km Km	42.25			
	4tii Kiii				Kili	42.23			
	5th Km				Km	37.10			
	6th Km				Km	35.65			
	7th Km				Km	30.10			
	8th.		75	,	Km	29.75			
	9th Km	/	-		Km	27.80			
	10th Km	146			Km	25.85			
	11th & subsequent Kms	8	SAV.		Km	20.85			
9	Carriage of 1000 No. bricks, 9"x4½"x3"	300				20.03		ditto	
	(225x113x75 mm) or 8"x4"x4" (200x100x100	1834	1	50 /					
	mm) (nominal)	Your	100		20				
	1st chain (1st 30 m)	100	0.00	6 2 3	30 M	83.37			
	2nd chain (2nd 30 m)		30	2	30 M	17.30			
	3rd to 10th chain (60 to 300 m)				30 M	9.56			
	1000 to 3000 ft. (300 to 900 m)	A TEN	BARRAN CAR (	Demarti	300 M	93.62			
	1st Km			and the same and	Km	132.75			
	2nd Km 3rd Km				Km	62.45 47.90			
	3rd Km 4th Km				Km Km	33.55			
	5th Km				Km	31.85			
	6th Km				Km	31.10			
	7th Km				Km	28.20			
	8th Km				Km	27.85			
	9th Km				Km	26.05			
	10th Km				Km	24.20			
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½"				Km	17.80		16.1	
	(225x113x38 mm). 1st chain (1st 30 m)				20.14	EO 21			
	2nd chain (2nd 30 m)				30 M 30 M	50.31 9.26		16.1	

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.	-				Unit of M/ment	Labour	Composite	No.	
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 300 M Km Km Km	5.72 56.56 80.15 37.80 28.95 20.10	Composite		
	5th Km				Km	18.55			
	6th Km				Km	18.25			
	7th Km				Km	17.00			
	8th Km		76	1	Km	16.80			
	9th Km	,	-		Km	15.70			
	10th Km	.116	15 700		Km	14.65			
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.	\$ 1			Km	10.80		ditto	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	The state of the s	Level Street	- , , 0	30 M 30 M 30 M	1.92 0.23 0.11			
	1000 to 3000 ft. (300 to 900 m)	arces/II			300 M	1.13			
	1st Km	Tin	MADINI CHI (	Departs	Km	2.00			
	2nd Km				Km	1.35			
	3rd Km				Km	0.60			
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including bundling.				Km	0.35		16.1	
	1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft.				300 M 300 M	28.05 3.49			
	1st Km				Km	4.90			
	2nd Km				Km	4.65			
	3rd Km				Km	2.30			
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash				Km	2.05		ditto	Previous lead of collection not

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWA	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	or brushwood, by boat or road :-								to be deducted from the next lead of carriage.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	41.63 18.75 5.71			
	1000 to 3000 ft. (300 to 900 m)				300 M	46.98			
	1st Km				Km	74.15			
	2nd Km				Km	37.80			
	3rd Km		/ ×		Km	28.95			
	4th Km	/			Km	20.10			
	5th Km				Km	18.55			
	6th Km		7 7		Km	18.25			
	7th Km		100		Km	17.00			
	8th Km 9th Km 10th Km 11th Km & subsequent	Œ	namer (	Departs	Km Km Km Km	16.80 15.70 14.65 10.80			
14	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre) Execeeding 1000 to 5000 ft (300 to 1500metre)				Tonne 300 M	339.89 82.35		ditto	
	1st Km				Km	159.35			
	2nd Km				Km	74.50			
	3rd Km				Km	50.70			
	4th Km				Km	32.95			
	5th Km				Km	31.15			
	6th Km				Km	29.90			
	7th Km				Km	25.95			
	8th Km				Km	25.60			

	MRS, BI-ANNUAL PERIC	D (1st FE	BRUARY, 2	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km 10th Km 11th Km & susequent				Km Km Km	25.00 19.80 16.35			
15	Carriage of small consignments weighing upto 5 maunds (job rates):							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%; and for consignments weighing 10
	Upto 1000 ft. (300 metre)				Consign- ment/	27.60			to 20 maunds, rate be increased by 100%.
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				300 M	18.93			
	1st Km		/ ×		Consign- ment/ Km	24.95			
	2nd Km	1.1			"	15.60			
16	3rd Km & subsequent Carriage of consignments job.	8				5.20			
	i) Cooly load for distance:-	16/17	1.65	- ,50	Each				
	a) Upto 5 Km b) Above 5 to 13 Km	n <sub>ij</sub> e		S 4 18	Consignmen "	51.10 120.55			
	ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ½ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km	Ti	namer (	Depart	Each Consignmen	10.85 16.45 20.80 26.00 45.95 82.25			
	iii) Cart load for a distance :-				Each Consig- nment				
	a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to 10 Miles(16 Km)				"	89.85 163.55			
	iv) Camel load for a distance:-								
	a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km)				"	66.45 100.75			
17	Hire charges of:-								1. This item will be allowed with
	i) truck (10 Ton Capacity)				Per	3000.00			prior concurrence of Superintending Engineer.

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	ii) tractor with trolly iii) tractor without trolly				day "	1000.00	-		2. The rate includes pay of driver and cleaner only. The repairs shall be the responsibility of the owner and the cost of lubrication, fuel, loading and unloading shall be paid by the borrower.
18	Carriage of bitumen, tar or other lubricants, in drums:							16.1	
	1st Km				Per Tonne	26.55			
	2nd Km				"	18.35			
	3rd & subsequent Km		/ 29		"	7.50			
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-  i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km			Separt)	30 M 30 M 30 M 300 M Km Km	4.00 0.75 0.45 4.50 6.40 3.00 2.30			
	5th Km				Km	1.45			
	6th Km				Km	1.40			
	7th Km				Km	1.30			
	8th Km				Km	1.25			
	9th Km				Km	1.25			
	10th Km				Km	1.15			
	11th Km & Susequent				Km	1.10			
	ii) 4" (100 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	5.25			

	MRS, BI-ANNUAL PERIC	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	0.95 0.60			
	1000 to 9000 ft. (300 to 900 m)				300 M	5.90			
	1st Km				Km	8.40			
	2nd Km				Km	3.90			
	3rd Km				Km	3.00			
	4th Km				Km	2.10			
	5th Km		/ ×		Km	1.95			
	6th Km	/			Km	1.85			
	7th Km	8			Km	1.75			
	8th Km 9th Km 10th Km 11th Km & subsequent Km		( ) is	-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Km Km Km Km	1.65 1.60 1.50 1.45			
	iii) 6" (150 mm) i/d pipes:-			and the same					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 9000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Pi	tance (	Departs	30 M 30 M 30 M 300 M Km Km	7.90 1.45 0.90 8.85 12.55 5.90 4.50			
	4th Km				Km	3.15			
	5th Km				Km	2.90			
	6th Km				Km	2.85			
	7th Km				Km	2.65			
	8th Km				Km	2.55			
	9th Km				Km	2.45			
	10th Km 11th Km & subsequent Km iv) 8'' (200 mm) i/d pipes:				Km Km	2.25 1.95			

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	PIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	13.35 2.45 1.55 15.00 21.25 10.30 7.80			
	4th Km				Km	5.35			
	5th Km		100		Km	5.00			
	6th Km		/ ×	1	Km	4.90			
	7th Km	/	_		Km	4.55			
	8th Km	.46	70%		Km	4.40			
	9th Km				Km	3.95			
	10th Km 11th Km & subsequent Km	18/7	19.65	(عارب	Km Km	2.45 1.80			
v)	10" (250 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Œ.		Separts	30 M 30 M 30 M 300 M Km Km	17.95 3.30 2.05 20.15 28.55 13.35 10.20			
	4th Km				Km	7.05			
	5th Km				Km	6.55			
	6th Km				Km	6.40			
	7th Km				Km	6.20			
	8th Km				Km	6.15			
	9th Km				Km	5.75			
	10th Km 11th Km & subsequent Kms				Km Km	5.35 3.95			
vi	) 12" (300 mm) i/d pipes:								

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWA	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	23.35 4.30 2.65 26.25 37.15 18.40 13.65 9.15			
	5th Km				Km	8.50			
	6th Km				Km	8.35			
	7th Km		/ ×	)	Km	7.75			
	8th Km	/			Km	7.65			
	9th Km				Km	7.15			
	10th Km	100	100		Km	6.65			
	11th Km & subsequent Kms	677	100	٠٠٠٠	Km	5.00			
	vii) 16" (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Ti	Lance (	Separt)	30 M 30 M 30 M 300 M Km Km	38.25 7.05 4.40 43.00 60.90 28.95 21.95			
	4th Km				Km	15.30			
	5th Km				Km	14.15			
	6th Km				Km	13.90			
	7th Km				Km	12.90			
	8th Km				Km	12.75			
	9th Km				Km	11.90			
	10th Km 11th Km & subsequent Kms viii) 18" (450 mm) i/d pipes:-				Km Km	11.10 8.25			

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m)				30 M	49.15			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	9.05 5.65			
	1000 to 3000 ft. (300 to 900 m)				300 M	55.25			
	1st Km				Km	78.25			
	2nd Km				Km	36.90			
	3rd Km				Km	28.25			
	4th Km				Km	19.65			
	5th Km				Km	18.20			
	6th Km		35	,	Km	17.90			
	7th Km	/			Km	16.60			
	8th Km	16	20.3(6)		Km	16.40			
	9th Km				Km	15.35			
	10th Km	1887	1.6	- 16	Km Km	14.30 10.50			
	11th Km & subsequent Kms ix) 20" (500 mm) i/d pipes:-	-6			Kili	10.30			
	1st chain (1st 30 m)		-	2	30 M	52.20			
	2nd chain (2nd 30 m)	VENU.		570	30 M	9.60			
	3rd to 10th chain (60 to 300 m)	Tan	KARATE CAST	eserpar es	30 M	6.00			
	1000 to 3000 ft. (300 to 900 m) 1st Km				300 M Km	58.65 83.05			
	2nd Km				Km	39.20			
	3rd Km				Km	29.95			
	4th Km				Km	20.85			
	5th Km				Km	19.30			
	6th Km				Km	19.00			
	7th Km				Km	17.60			
	8th Km				Km	17.40			
	9th Km				Km	16.30			
	10th Km				Km	15.15			
	11th Km & subsequent Kms				Km	11.35			
	x) 24" (600 mm) i/d pipes:-								

Page 15

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	_PIND	
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.	_				Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 5000 ft. (300 to 1500 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	57.80 10.65 6.60 64.95 92.05 43.35 33.20			
	4th Km				Km	23.60			
	5th Km				Km	21.35			
	6th Km				Km	21.00			
	7th Km	,	10		Km	19.50			
	8th Km	116	2016		Km	19.25			
	9th Km	\$ 1			Km	18.05			
20	10th Km 11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading, unloading and stacking (Rate per 1000 ft.) (300 metre):-		\$ 5.50 \$ 7.00 \$		Km Km	16.75 12.35			
	i) 3" (75 mm) i/d pipes:-	Œin	materia care (	Departs	数据制度				
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	-EE- 1997	The second section of the second section of the second section of the second section s	men star film statute pendi	30 M 30 M 30 M 300 M Km Km	7.90 1.45 0.90 8.85 12.50 5.90 4.50			
	4th Km				Km	3.15			
	5th Km				Km	2.90			
	6th Km				Km.	2.85			
	7th Km				Km	2.65			
	8th Km				Km	2.60			
	9th Km				Km	2.45			

	MRS, BI-ANNUAL PERIO	D (1st FEBRUARY, 2013	TO 31st JULY, 20	13) DISTI	RICT RAWA	_PIND	
Sr.				ate (Metric S	System)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	10th Km 11th Km & subsequent Kms ii) 4" (100 mm) i/d pipes:-		Km Km	2.25 1.85			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		30 M 30 M 30 M 300 M Km Km	12.15 2.25 1.40 13.65 19.30 9.30 7.00			
	4th Km	76	Km	4.75			
	5th Km		Km	4.40			
	6th Km	, de (	Km	4.35			
	7th Km		Km	4.05			
	8th Km		Km	4.00			
	9th Km		Km	3.70			
	10th Km 11th Km & subsequent Kms iii) 5" (125 mm) i/d pipes:-	Thance De	Km Km	3.45 3.00			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		30 M " 300 M Km "	16.55 3.05 1.90 18.60 26.35 12.55 9.65			
	4th Km		"	6.75			
	5th Km		Km.	6.05			
	6th Km		"	5.95			
	7th Km		"	5.50			
	8th Km			5.45			
	9th Km			5.10			

	MRS, BI-ANNUAL PE	RIOD (1st FEBRUARY, 2013 TO 3	1st JULY, 20	13) DIST	RICT RAWAI	_PIND	
Sr.	Description			ate (Metric S	System)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	10th Km			4.75			
	11th Km & subsequent Kms			3.55			
	iv) <b>6" (150 mm) i/d pipes:</b>						
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 300 m)		30 M 30 M 30 M 300 M	22.80 4.20 2.60 25.65			
	1st Km.		Km.	36.30			
	2nd Km 3rd Km		Km. Km.	17.15 13.10			
	4th Km	(*)	Km.	9.15			
	5th Km		Km.	8.45			
	6th Km		Km.	8.30			
	7th Km		Km.	7.70			
	8th Km		Km.	7.60			
	9th Km		Km.	7.15			
	10th Km	Finance Depa	Km.	6.65			
	11th Km & subsequent Kms	The seasons are a strong for sea	Km.	4.90			
	v) 8" (200 mm) i/d pipes:-						
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)		30 M 30 M 30 M	40.00 7.35 4.60			
	1000 to 3000 ft. (300 to 900 m)		300 M	44.95			
	1st Km		Km	63.70			
	2nd Km 3rd Km		Km Km	30.05 23.00			
	4th Km		Km	16.00			
	5th Km		Km	14.85			
	6th Km		Km	14.55			
	7th Km		Km	13.50			
	8th Km		Km	13.35			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND									
Sr.	Description					ate (Metric	System)	Spec.	Remarks	
No.					Unit of M/ment	Labour	Composite	No.		
	9th Km				Km	12.50				
	10th Km 11th Km & subsequent Kms vi) 10" (250 mm) i/d pipes:-				Km Km	11.60 8.60				
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	62.05 11.45 7.10 69.75 98.75 46.60 35.65				
	4th Km		/ 4		Km	24.80				
	5th Km	1.6	740)		Km	23.00				
	6th Km	8	22 5		Km	22.60				
	7th Km	1		6	Km	20.95				
	8th Km	-			Km	20.70				
	9th Km			2	Km	19.40				
	10th Km 11th Km & subsequent Kms	Œin	namer (	Departi	Km Km	18.00 13.40				
	vii) 12" (300 mm) i/d pipes:-									
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	87.35 16.10 10.00 98.15 139.05 65.60 50.20				
	4th Km				Km	34.95				
	5th Km				Km	32.35				
	6th Km				Km	31.80				
	7th Km				Km	29.50				
	8th Km				Km	29.15				

	MRS, BI-ANNUAL PERIO	DD (1st FE	BRUARY, 2	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAI	LPIND	
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	27.30			
	10th Km 11th Km & subsequent Kms				Km Km	25.35 18.85			
	viii) 14" (350 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	113.70 20.95 13.00 127.75 181.00 85.35			
	3rd Km				Km	65.30			
	4th Km		26		Km	45.45			
	5th Km	116			Km	42.10			
	6th Km	8			Km	41.35			
	7th Km	18	1	- ,60	Km	38.40			
	8th Km	10		6	Km	37.95			
	9th Km			0	Km	35.50			
	10th Km 11th Km & subsequent Kms	Ti	MAGINE CHE (	Departs	Km Km	33.00 24.55			
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-								
	i) 2" (50 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	5.75 1.05 0.65 6.45 9.15 4.35 3.30			
	5th Km				Km	2.10			
	6th Km				Km	2.10			
	7th Km				Km	1.95			

	MRS, BI-ANNUAL PERIO	D (1st FEBRUARY, 2	013 TO 31st JULY	2013) DIST	RICT RAWA	LPIND	
Sr.	Description	<u></u>		Rate (Metric	System)	Spec.	Remarks
No.			Unit M/me		Composite	No.	
	8th Km		Km	1.95			
	9th Km		Km	1.80			
	10Km 11th Km & subsequent Kms		Km Km				
	ii) 2½" (63 mm) i/d pipes:-  1st chain (1st 30 m)  2nd chain (2nd 30 m)  3rd to 10th chain (60 to 300 m)  1000 to 3000 ft. (300 to 900 m)  1st Km  2nd Km  3rd Km	×	30 M 30 M 30 M 300 M Km Km	1 1.65 1 1.05 M 10.05 14.25 6.75			
	4th Km	- 1 <sub>AVA</sub>	Km	3.65			
	5th Km		Km	3.35			
	6th Km	The same of the sa	Km	3.30			
	7th Km	W. Company	Km	3.05			
	8th Km	pipegii .	Km	2.85			
	9th Km	Timanes (	Km	2.75			
	10Km 11th Km & subsequent Kms		Km Km				
	iii) 3" (75 mm) i/d pipes:-  1st chain (1st 30 m)  2nd chain (2nd 30 m)  3rd to 10th chain (60 to 300 m)  1000 to 3000 ft. (300 to 900 m)  1st Km  2nd Km  3rd Km		30 M 30 M 30 M 300 J Km Km	1 2.30 1 1.40 M 13.95 19.75 9.35			
	4th Km		Km				
	5th Km		Km	4.60			
	6th Km		Km	4.55			
	7th Km		Km	4.20			

	MRS, BI-ANNUAL P	ERIOD (1st FEBRUARY, 2013 TO 31st	JULY, 20	013) DIST	RICT RAWA	LPIND	
Sr.	Description			ate (Metric	System)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	8th Km		Km	4.15			
	9th Km		Km	3.80			
	10th Km 11th Km & subsequent Kms		Km Km	3.55 2.70			
	iv) 4" (100 mm) i/d pipes:-		Kili	2.70			
	1st chain (1st 30 m)		30 M	20.55			
	2nd chain (2nd 30 m)		30 M	3.80			
	3rd to 10th chain (60 to 300 m)		30 M	2.35			
	1000 to 3000 ft. (300 to 900 m)		300 M	23.10			
	1st Km		Km	32.70			
	2nd Km 3rd Km	( × )	Km Km	15.45 11.80			
		100	\				
	4th Km		Km	8.20			
	5th Km		Km	7.60			
	6th Km	6	Km	7.50			
	7th Km		Km	7.00			
	8th Km	200 B B B B B B B B B B B B B B B B B B	Km	6.80			
	9th Km	Tinance Depart	Km	6.40			
	10th Km 11th Km & subsequent Kms		Km Km	5.90 4.55			
	v) 5" (125 mm) i/d pipes:-						
	1st chain (1st 30 m)		30 M	30.70			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)		30 M 30 M	5.65 3.50			
	1000 to 3000 ft. (300 to 900 m)		300 M	34.50			
	1st Km		Km	48.85			
	2nd Km		Km	23.05			
	3rd Km		Km	17.65			
	4th Km		Km	12.30			
	5th Km		Km	11.40			
	6th Km		Km	11.20			
	7th Km		Km	10.35			

r.	Description		Т		Rate (Metric System)			Spec.	Remarks
0.					Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	10.25			
	9th Km				Km	9.60			
	10th Km 11th Km & subsequent Kms				Km Km	8.80 6.70			
vi)					1111	0.70			
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	44.25 8.15			
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30 M 300 M	5.05 49.70			
	1st Km 2nd Km		×	3	Km Km	70.45 33.20			
	3rd Km	/	700		Km	25.45			
	4th Km	1.6			Km	17.70			
	5th Km 6th Km	* E			Km Km	16.40 16.10			
	7th Km	187			Km	14.95			
	8th Km	1337 /	1.	6/3	Km	14.80			
	9th Km	Y	1. 11.		Km	13.85			
	10th Km 11th Km & subsequent Kms	408	20	- 18 a	Km Km	12.80 9.60			
	and shunting loaded Railway wagons or	Tina	ene ciri (S	Departm	atometi.	7.00			
a) b) c) d)	upto ¾ mile / ¾ Km upto 1 (1.6 Km) mile				Each No " " Each	148.80 269.40 363.70 432.80			
	2nd and subsequent kilometres			1	No/Km	269.70			
3 Ha	and shunting empty Railway wagons or trucks.								
a) b) c) d)	upto ¾ mile / ¾ Km				Each No.	86.30 143.05 188.65 226.40			
e)	2nd mile and subsequent miles/ 2nd and subsequent kilometres				Each No/Km	132.40			

# 2. LOADING, UNLOADING & STACKING

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

	MRS, BI-ANNUAL PERIO	D (1st FEI	BRUARY, 20	)13 TO 31st J	IULY, 201	13) DISTE	RICT RAWAL	PINDI	
Sr.	Description	R	ate (British Sy	stem)	Ra	te (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laoding or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	390.70		cu.m	138.00			
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-		×						
	a) Bricks 10" (250 mm) size.	1000 Nos.	488.40		1000 Nos.	488.40			
	b) Bricks 9" (225 mm) or smaller size.	ditto	390.70		ditto	390.70			
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	488.40		100 Bags	488.40			
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	46.90		100 Nos.	46.90			
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	293.05	Depharen	100 Kg	7.85			
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	234.45		Per Tonne	230.75			
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	29.30		Each	29.30			
8	Loading or unloading packages of all sorts, upto one Cwt (50 Kg). Loading or unloading sleepers other than wooden, including stacking lead within one chain:-	Each	14.65		Each	14.65			Except cement in jute or paper bags.
	a) Broad gauge sleepers	100 Nos.	976.80		100 Nos.	976.80			
	b) Metre gauge and narrow gauge sleepers.	ditto	488.40		ditto	488.40			
10	Loading or unloading timber logs or timber for shuttering,	Per	122.1		Per	120.15			

	MRS, BI-ANNUAL PERIO	D (1st FEI	BRUARY, 20	13 TO 31st J	ULY, 201	13) DISTE	RICT RAWAL	PINDI	
Sr.	Description	R	ate (British Sy	stem)	Ra	te (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Ton			Tonne				
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	1172.15		100 Kg	31.4			
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	195.35		Per Tonne	192.30			
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	144.55		cu.m	51.05			
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	187.55		cu.m	66.25			
15	Unloading oil, bitumen tar, etc.	116			Di.				
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	488.40		100 litres	10.75			
	b) Crude oil (drained by gravity).	1000 Gallon	488.40		100 litres	10.75			
	c) Crude oil materials from railway wagons.	100 Cft.	62.50		cu.m	22.10			
	d) Fuel oil from tank into empty drums, including stacking within one chain (30 m).	Per Ton	173.65	Deplati	Per Tonne	170.90			
	e) Petrol (2 gallon tin)	100 Nos.	246.15		100 Nos.	246.15			The rate includes checking and weighing the tins.
16	f) Kerosine oil (4 gallon tin) Removing and stacking within one chain (30 m) lead:	100 Nos.	488.40		100 Nos.	488.40			and weighing the tins.
	a) Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc.	100 Cft.	195.35		cu.m	69.00			
	b) Bricks.	1000 Nos.	520.95		1000 Nos.	520.95			
	c) Broad gauge wooden sleepers.	100 Nos.	312.6		100 Nos.	312.6			
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	186.05		100 Nos.	186.05			
	e) Rails girders, pipes, cement etc.	Per Ton	86.85		Per Tonne	85.45			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description	R	ate (British Sy	rstem)	Ra	te (Metric S	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	f) Bridge and crossing timbers, etc.	100 No.	1041.90		100 No.	1041.90				
17	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	195.35		Per Tonne	192.30				
18	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	111.65		Per Tonne	109.85				
19	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	781.45		100 Nos.	781.45				
20	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	372.10		100 Nos.	372.10				
21	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	390.70		100 Nos.	390.70				
22	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	205.65		100 Nos.	205.65				
23	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	1562.90	0 3	100 Nos.	1562.90				
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	781.45	Departi	100 Nos.	781.45				
25	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	117.20		Per Tonne	115.35				

# 3. EARTHWORK (EXCAVATION & EMBANKMENT)

- Special allowances for the hardness, wetness and slush:-
  - The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.
- 2 Deduction for shrinkage from bank measurements:-
  - The following allowances should be provided for material which is not rammed, or equally consolidated:-
  - a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour........ 10%
  - b) Deduction for settlement from the bank measurement when the earthwork is done by machines................................. 3 to 6%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors

	MRS, BI-ANNUAL PER						RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	stem)		ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
1	Earthwork excavation underessed lead upto a single throw of Kassi, phaorah or shovel:-	1			No.			171 to 17.5	
	<ul><li>a) In ashes, sand, soft soil or silt clearance.</li><li>b) In ordinary soil.</li></ul>	1000 Cft. 1000 Cft.	1,465.20 1,758.25		cu.m cu.m	51.75 62.10			
2	Earthwork excavation in ashes, sand and soft soil or silt clearance, undressed lead upto 50 ft (15 metre).	1000 Cft.	2,148.95		cu.m	75.90		ditto	
3	Bed clearance and dressing slopes of drains to required sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead.  a) Excavated material undressed.  b) Excavated material dressed in the specified manner.	1000 Cft. 1000 Cft.	2,735.05 2,955.75	Departs 	cu.m cu.m	96.60 104.40		ditto	The rate is applicable where the earth of the bed to be removed is of the type of ordinary soil. When it is silt or 1 or 2 above, whichever is applicable. the drains of each category.
4	Borrowpit excavation undressed lead upto 100 ft (30 metre).  a) Ordinary soil b) Hard soil	1000 Cft. 1000 Cft.	2,735.05 3,360.20		cu.m cu.m	96.60 118.70			
5	Earthowrk in ordinary soil for embankments lead upto 100 ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete in all respects:- i) 95% to 100% maximum modified AASHO dry density. ii) 90% maximum modified AASHO dry density. iii) 85% maximum modified AASHO dry density. Regular excavation dressed.	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,982.55 2,982.55 2,982.55 2,007.05	3,767.55 3,646.50 3,525.45	cu.m cu.m cu.m cu.m	105.35 105.35 105.35 70.90	133.05 128.80 124.50	411-13 and 301-1 & 202-3	The rate includes hire charges of machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also includes clearing and grubbing where necessary.
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and	1000 Site	2,007.00		Cum	, 3.50		17.1 to 17.5	

	MRS, BI-ANNUAL PERIO	D (1st FEE	BRUARY, 20	13 TO 31st J	ULY, 20 <sup>2</sup>	13) DISTR	RICT RAWAL	PINDI	
Sr.	Description	, r	Rate (British Sv	stom)	D	ate (Metric S	Evetom)	Spec	Remarks
No.	Description	Unit of	Kate (British Sy	stein)	Unit of	ate (Metric 8	System)	Spec. No.	Kemarks
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 50 ft. (15 m) lead:- i) ordinary ii) hard iii) very hard iv) gravel & shingle	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	3,411.95 4,037.10 4,701.30 7,915.80	3,480.40 4,105.55 4,769.75 7,984.20	cu.m cu.m cu.m cu.m	120.50 142.60 166.05 279.60	122.95 145.00 168.45 282.00		
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to 10.0 ft. (3.0 mm) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 100 ft. (30 m) lead:  i) ordinary  ii) hard  iii) very hard  iv) gravel & shingle	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	3,722.40 4,347.55 5,011.80 8,616.95	3,858.55 4,483.70 5,147.95 8,753.10	cu.m cu.m cu.m cu.m	131.50 153.55 177.00 304.35	136.30 158.35 181.85 309.15	ditto	
9	Excavation in shingle or gravel formation and rock, not requiring blasting, undressed lead upto 100 ft (30 m).  i) Dry  ii) Wet  iii) In flowing water	1000 Cft. 1000 Cft. 1000 Cft.	7,423.70 8,595.85 10,940.15	Depuarte 	cu.m cu.m cu.m	262.20 303.60 386.40	  	17.1 to 17.5	
10	Earthwork excavation in irrigation channels, drains, etc. to designed section, grades and profiles, excavated material disposed off and dressed within 50 ft. (15 m) lead:-							ditto	
11	i) ordinary ii) hard iii) very hard iv) gravel & shingle	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	3,136.30 3,761.45 4,425.70 7,835.50	  	cu.m cu.m cu.m	110.75 132.85 156.30 276.75	  		
	Excavation in rock dressed to designed section, grades and profiles, excavated material disposed off within 100 ft. (30 m) and lift upto 5'-0" (1.5 m).  a) Soft rock, slate, shale, schist laterite work, with pick and crow bar.	1000 Cft.	7,476.50		cu.m	264.05		17.1 to 17.5	Tools and plants shall be the liability of the contractor.
	b) Medium hard rock, requiring occasional blasting.	1000 Cft.	11,794.90	12,370.90	cu.m	416.60	436.95		
12	Excavation in hard rock requiring blasting and disposal of excavated material (blasted material) upto 50 ft. (15 m) lead, (including dressing and levelling to designed section, etc. complete).								Tools and plants required shall be the liability of the Contractor
	i) Grade I	1000 Cft.	7,194.00	7,770.00	cu.m	254.10	274.45		2) Reduce the rate by 8% if the excavated section is not dressed or

	MRS, BI-ANNUAL PERIO	D (1st FEI	BRUARY, 20	13 TO 31st J	ULY, 20 <sup>-</sup>	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sv	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	Bescription	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	Remarks
	ii) Grade II iii) Grade III iv) Grade IV v) Grade V vi) Grade VI  b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50 ft. (15 m) lead (including dressing and levelling to designed section, etc. complete):-  i) Grade I ii) Grade II	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	7,756.30 9,279.60 10,311.85 11,404.80 12,241.70 14,388.00 15,512.65	8,716.30 10,431.60 11,655.85 12,940.80 13,969.70 15,540.00 17,432.65	cu.m cu.m cu.m cu.m	273.95 327.75 364.20 402.80 432.40 508.20 547.90	307.85 368.45 411.70 457.05 493.40 548.85 615.70	17.1 to 17.5	levelled to designed section.  1) Tools and plants required shall be the liability of the contractor.  2) Reduce the rate by 8% if the excavated section is not dressed or levelled to designed section.
13	iii) Grade III iv) Grade IV v) Grade V vi) Grade VI Rehandling of earthwork:	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	18,559.20 20,623.70 22,809.60 24,483.35	20,863.20 23,311.70 25,881.60 27,939.35	cu.m cu.m cu.m cu.m	655.50 728.45 805.65 864.75	736.90 823.35 914.15 986.80		reveiled to designed section.
	<ul><li>a) Lead upto a single throw of Kassi, phaorah or shovel</li><li>b) Upto a lead of 50 ft. (15 m).</li></ul>	1000 Cft. 1000 Cft.	976.80 1,367.50		cu.m cu.m	34.50 48.30	 	ditto	
14	Rehandling of gravel work or excavated rock, lead upto 50 ft.( 15 m)	1000 Cft.	3,907.20	Departs	cu.m	138.00		17.1 to 17.5	
	<ul> <li>Filling, watering and ramming earth under floors:-</li> <li>i) with surplus earth from foundation, etc.</li> <li>ii) with new earth excavated from outside, lead upto one chain (30 m).</li> <li>Extra for every 50 ft. (15 m) additional lead or part thereof:-</li> </ul>	1000 Cft. 1000 Cft.	1,969.45 3,801.20	 	cu.m cu.m	69.55 134.25	 	anto	This rate shall be applicable upto
	<ul> <li>i) for earhtwork soft, ordinary, hard and very hard.</li> <li>ii) for gravel, shingle or rock.</li> </ul>	1000 Cft. 1000 Cft.	34.30 40.15	 	cu.m cu.m	1.20 1.40			1000 ft. total distance, including the lead covered in the item of earthwork
17	Transportation of earth all types when the total distance, including the lead covered in the item of work, is more than 1000 ft. (300 m)	1000 00	1.550.00			55.50			This rate will be paid inaddition to the rate of earthwork, without deducting the lead covered in the item of
	<ul> <li>a) upto ¼ mile (400 m).</li> <li>b) for every 330 ft. (100 m) additional lead or part thereof, beyond ¼ mile (400 m) upto one mile. (1.6 Km.)</li> <li>c) for every ¼ mile (400 m) additional lead or part thereof,</li> </ul>	1000 Cft. 1000 Cft.	1,576.90 85.80		cu.m cu.m	55.70 3.05			earthwork
	beyond one mile (1.6 Km.) upto 5 mile (8 Km). d) for every ½ mile (800 m) additional lead or part thereof, beyond 5 miles (8 Km).	1000 Cft. 1000 Cft.	161.50 143.45		cu.m cu.m	5.70 5.05			
18	Dressing and levelling of earhtwork to designed section, etc. complete:-							17.10 to 17.5	

Chain dressed of	
No.   Unit of   M/ment   Labour   Composite   M/ment   Labour   Composite   No.	
Ashes, sand, silt or soft soil.	Remarks
b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting.  1000 Cft. 247.55 cu.m 8.75 cu.m 21.05 line cu.m 21.05 l	
b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting.  1000 Cft. 247.55 cu.m 8.75 cu.m 21.05 line cu.m 21.05 l	
c) Gravel work or soft rock not requiring blasting.  1000 Cft. 596.65 cu.m 21.05 ditto This rate dressed 6	
blasting.  19 Dowel dressing.  Per 116.15 Metre 3.80 ditto This rate dressed of the control of the contro	
19 Dowel dressing.  Per Chain  Per Chain  116.15 Metre 3.80 ditto This rate dressed of	
Chain dressed of	
Chain dressed of	te is in addition to payment for
	l earhtwork.
	oaid only when exclusively
	g is done and no earthwork is
carried o	out in embankment or cutting.
b) Dressing of earthwork (done by machinery or otherwise 100Sft. 92.40 sq.m 9.95 i) The st	surface area dressed is to be
	or measurement.
	item is applicable where the
dressing	g is done by the contractor
. [V] hame	nan the one who executed the
work.	
21 Excavation in foundation of building, bridges and other	
structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and rammiing lead	
upto one chain (30 m) and lift upto 5 ft. (1.5 m)	
a) in sand, ashes or loose soil  1000 Cft. 3,527.05 cu.m 124.60	
b) in ordinary soil. 1000 Cft. 4,118.40 cu.m 145.45	
c) in hard soil or soft murum. 1000 Cft. 4,609.45 cu.m 162.80	
22 Cutting hard rock such as granite, ballast, hard lime stone or 1000 Cft. 28,976.65 32,990.90 cu.m 1023.45 1165.25 17.1 to 17.5 Tools an	
sand stone, etc. with chisels and hammers, for small	of the contractor.
foundations.	
23 Extra for excavation requiring shoring. 1000 Cft. 525.35 754.50 cu.m 18.55 26.65 17.1 to 17.5 Composi	cita rata includas matarials
i.e. plank	
24 Compaction of earthwork (soft, ordinary or hard soil):-	ik, etc.
a) Mixing, moistening earth to optimum moisture content 1000 Cft. 468.25 cu.m 16.55	
in layers for compaction, etc. complete.	
b) Compaction by rolling with animal driven	
roller/hand rammed:	
i) soft or sandy soil 1000 Cft. 586.10 cu.m 20.70	
1) The r	rate does not include hire
	charges of the roller. 2) Roller to be 'supplied by Government
iii) hard soil 1000 Cft. 781.45 cu.m 27.60 Governm	
iv) admixture of shingle 1000 Cft. 879.10 cu.m 31.05	
iv) admixture of shingle 1000 Cft. 879.10 cu.m 31.05	
c) Ramming earthwork (all types of soil). 1000 Cft. 586.10 cu.m 20.70	

	MRS, BI-ANNUAL PERIO	O (1st FEI	BRUARY, 20	)13 TO 31st J	JULY, 20	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.	<b>F</b>	Unit of			Unit of		,	No.	
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	d) Ramming earhtwork behind retaining walls.	1000 Cft.	781.45		cu.m	27.60			
25	Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture content in layers, etc. complete:							17.1 (a) *411-5 and 202-3	The rate also includes hire charges of machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.
	i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.		785.00	cu.m	-	27.75		of driver and cleaner, etc.
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		663.95	cu.m	-	23.45		
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.	/ ×	542.90	cu.m	-	19.20		
26	Extra for wet earthwork.	1000 Cft.	1,367.50	-	cu.m	48.30	-	17.1 to 17.5	That will support a man's weight.
27	Extra for slush or Daldal including dewatering.	1000 Cft.	3,125.75		cu.m	110.40	-	17.1 to 17.5	That will not support a man's weight.
28	Extra for puddling.	1000 Cft.	2,457.85		cu.m	86.80	-	ditto	
29	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	371.20	- , ;	Metre	12.20	-	ditto	
30	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.( 15 m).	1000 Cft.	3,516.50		cu.m	124.20		17.1 to 17.5	
	II.( 13 m).	Trans	namce 9	DEPORT	nem t				
31	Dag bailing 3" (75 mm) deep.	Per mile	1,483.15		Per Km	921.75		ditto	Dag bailing for layout of borrow pit, to be done by contractors at their own cost.
32	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	651.20		sq.m	70.05		ditto	
33	Berm cutting:-							17.1 to 17.5	
	lead upto a single throw of Kassi, phaora or shovel     (without dressing).	1000 Cft.	1,758.25		cu.m	62.10			
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	3,136.30		cu.m	110.75			
34	Berm trimming both sides of channels:-							17.1 to 17.5	
	a) upto 3½ ft. (1.06 m) depth.	Per Mile	4,576.00		Per Km.	2860.00			
	<ul> <li>b) exceeding 3½ ft. to 5 ft. (1.06 to 1.5 m) depth.</li> <li>c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth</li> </ul>	Per Mile Per Mile	6,384.40 9,974.80		Per Km. Per Km.	3990.25 6234.25			
25		FEI MIIIE	9,974.60		FU KIII.	0234.23		1200	
35	Ploughing and levelling borrowpits.							ditto	Area ploughed to be measured.
	<ul><li>i) upto 3 ft. (0.9 m) depth.</li><li>ii) above 3 ft. (0.9 m) depth.</li></ul>	Per Acre Per Acre	976.80 1,953.60	 	Per Hect. Per Hect.	2413.70 4827.45			

	MRS, BI-ANNUAL PERIO	D (1st FEI	BRUARY, 20	13 TO 31st J	ULY, 20	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	•	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	Ño.	
		Wi/illelit	Labout	Composite	Wi/ment	Labout	Composite		
36	Making boundary or service roads, including dag-belling, levelling and dressing:							ditto	
	i) in unploughed land:								
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	492.80 660.00		Metre Metre	16.15 21.65			
	ii) in ploughed land:								
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	508.20 675.40		Metre Metre	16.65 22.15			
37	Earthwork by boats, including hire of boats:-	. /						17.1 to 17.5	For ordinary soil.
	<ul> <li>i) Digging and loading into boats, upto 50 ft. (15 m) lead.</li> <li>ii) Carriage by boats upto 10 chains (300 m).</li> <li>iii) Extra for every additional one chain (30 m) or part thereof beyond 10 chains (300 m).</li> </ul>	1000 Cft. 1000 Cft. 1000 Cft.	2,930.40 735.15 78.15		cu.m cu.m cu.m	103.50 25.95 2.75	  		
	iv) Unloading earth from boats.	1000 Cft.	1,367.50		cu.m	48.30			
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	1,172.15	Sec. 78	cu.m	41.40		17.1 to 17.5	
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	2,735.05	Dep <u>o</u> urts	cu.m	96.60		17.1 to 17.5	
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	2,197.80		cu.m	77.65		ditto	
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	377.30	399.30	cu.m	133.25	141.05		The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface								The rate does not include back filling after laying of sewer, which is payable separately.
	water, in all types of soil except shingle, gravel and rock:  i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth  ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth  iii) above 15.0 ft. (4.5 m) depth	1000 Cft. 1000 Cft. 1000 Cft.	3,188.75 5,411.20 6,974.10	3,528.30 5,914.55 7,477.45	cu.m cu.m cu.m	112.65 191.10 246.35	124.60 208.90 264.10		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to								The rate does not include back filling after laying of sewer, which is payable

	MRS, BI-ANNUAL PERIO	D (1st FEI	BRUARY, 20	)13 TO 31st J	ULY, 20 <sup>-</sup>	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	stem)		ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:							13.5	separately.
	<ul> <li>i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL.</li> <li>ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL.</li> <li>iii) Exceeding 8 ft. (2.4 m) depth below SSWL.</li> </ul>	1000 Cft. 1000 Cft. 1000 Cft.	4,481.40 5,602.25 8,403.40	6,832.65 8,608.30 11,641.45	cu.m cu.m cu.m	158.30 197.85 296.80	241.35 304.05 411.20		
44	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	2,935.70		cu.m	103.70	-	17.1 to 17.5 **8.1	The rate does not include back filling after laying of pipe line, which is payable separately.
45	Cutting and removing trees within a distance of 100 ft. (30 m)								
	a) upto 2½ ft. (760 mm) girth. b) above 2½ ft. to 6 ft. (760 to 1800 mm) girth.	Each Each	589.40 1,145.10		Each Each	589.40 1145.10			
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	732.60	- , 5	Each	732.60			
47	Jungle clearance and removing within 100 ft. (30 m).	-		S. Carrie					
	a) light b) thick	1000 Sft. 1000 Sft.	97.70 195.35	Dep <u>o</u> rtn	sq.m sq.m	1.05 2.10			
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	46.90		sq.m	5.05			
49	Ploughing 3 times.	Per Acre	396.85		Per Hect.	980.55			
50	Levelling, dressing and making lawns.	100Sft.	195.35		sq.m	21.00			
51	Turfing lawns (excluding cost of turf).	100Sft.	167.20		sq.m	18.00			
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry,wet slush,daldal and under water) including its disposal and prepartion of working pad for operation of machinery.  (Rates includes 100 ft lead)	1000 Cft.		2123.00	cu.m		75.00		

 <sup>\*</sup> Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 \*\* Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

# 4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, BI-ANNUAL PERIO	O (1st FEI	BRUARY, 20	)13 TO 31st J	ULY, 201	13) DISTI	RICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Stone Work								
1	Dismantling dry stone masonry.	100Cft.	332.10		cu.m	117.30		18.1	
2	Dismantling stone masonry in mud mortar.	100Cft.	488.40		cu.m	172.50		ditto	
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	1,172.15		cu.m	414.00		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.
4	a) Dismantling dry stone or spawl pitching.	100Cft.	586.10		cu.m	207.00		ditto	
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	742.35	6	cu.m	262.20		ditto	
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	976.80		cu.m	345.00		ditto	
6	Dismantling stone pitching, cement or lime grouted.	100Cft.	1,562.90	TV man mathin	cu.m	552.00		ditto	
7	Dismantling stone in crates:	54E (\$1.00)	tanas 9	Departn	OLETTE E				
	a) wooden crates	100Cft.	781.45		cu.m	276.00			
	b) wire crates	ditto	976.80		ditto	345.00			
8	Dismantling stone ware drain including base concrete.	100Cft.	547.00		cu.m	193.20		ditto	
	Brick Work								
9	lling.	100Cft.	195.35		cu.m	69		18.1	
10	onry.	100Cft.	488.4		cu.m	172.5		ditto	
11	onry.	100Cft.	332.1		cu.m	117.3		ditto	
12	ortar.	100Cft.	683.75		cu.m	241.5		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th
13	ortar.	100Cft.	1660.55		cu.m	586.5		ditto	and subsequent floors respectively against item No. 12, 13, 14 & 15.

	MRS, BI-ANNUAL PERIO	O (1st FE	BRUARY, 20	13 TO 31st J	ULY, 20	13) DISTI	RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				-			-		
14	Dismantling cement block masonry.	100Cft.	1,465.20		cu.m	517.50		ditto	
15	Dismantling Dhajji walling.	100Cft.	390.70		cu.m	138.00		ditto	
	<u>Concrete</u>								
16	Dismantling mud concrete.	100Cft.	781.45		cu.m	276.00		ditto	
17	Dismantling lime concrete.	100Cft.	1,074.50		cu.m	379.50			Add extra 13%, 32% and 51% on
18	Dismantling lime or cement concrete, under water.	100Cft.	4,102.55		cu.m	1449.00			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 17, 19 & 20.
19	a) Dismantling cement concrete plain 1:4:8.	100Cft.	2,148.95	1	cu.m	759.00		ditto	
	b) Dismantling cement concrete plain 1:3:6.	ditto	3,516.50		ditto	1242.05			
	c) Dismantling cement concrete 1:2:4 plain.	ditto	4,297.90		ditto	1518.00			
	d) Dismantling cement concrete with brick	ditto	1,172.15		ditto	414.00			
	aggregate. e) Dismantling D.P.C. of cement concrete 1½" thick (40 mm) and clearing the site.	ditto	586.10	- 19	ditto	207.00			
20	Dismantling cement concrete reinforced, separating reinforcement from concrete,	100Cft.	7,032.95	35	cu.m	2484.05		ditto	
	cleaning and straightening the same.	Fig.	ramae q	Departs	nem t				
	Roofing								
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or ballies.	100Sft.	234.45		sq.m	25.25		18.1	
22	a) Dismantling 1st class tile roofing.	100Sft.	586.10		sq.m	63.05			Add extra 13%, 32 and 51% on labour rate only for 2nd, 3rd, 4th
	b) Dismantling 2nd class tile roofing.	100Sft.	488.40		sq.m	52.55		ditto	and subsequent floors respectively against items No. 22, 25, 26 and 28.
23	Dismantling from any height, asbestos sheets and ridge coping.	100Sft.	330.00		sq.m	35.50		18.1	
24	a) Dismantling roof of wooden planks and battens, from any height.	100Sft.	264		sq.m	28.4		ditto	
	b) Dismantling wooden ceiling above 20' (6.0 m) height in difficult position, including lifting with care and special scaffolding along live electric wires and with	100Sft.	1,026.45		sq.m	110.45		ditto	

	MRS, BI-ANNUAL PERIO	O (1st FEI	BRUARY, 20	13 TO 31st J	ULY, 20 <sup>-</sup>	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Luboui	Composite	Cint	Labour	composite		
	machines underneath.								
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	781.45		sq.m	84.10		ditto	
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	976.80		sq.m	105.10		ditto	
27	Stripping and stacking slate or tiles from the truss roofing.	100Sft.	488.40		sq.m	52.55			
	b) Stripping and stacking C.I. sheet roof.	ditto	455.35		ditto	49.00			
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	636.25		ditto	68.45			
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	781.45		sq.m	84.10		18.1	
	Flooring	187	1-15	- ,6					
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	332.10	36	sq.m	35.75		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively
30	Dismantling plank or wooden block flooring, etc.	100Sft.	488.40	Departs	sq.m	52.55		ditto	against items No. 29 and 30.
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-								i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.
	a) 6" to 12" (150 to 300 mm) diameter b) 13" to 24" (325 to 600 mm) diameter	Per Lft Per Lft	13.20 21.00		Metre Metre	43.30 68.90			ii) Bends, elbows, sluice valves,
	c) 25" to 36" (625 to 900 mm) diameter	ditto	24.65		ditto	80.85			etc. should not be paid for extra if
	d) Above 36" (Above 900 mm) diameter	ditto	35.00		ditto	114.80			fixed in the length of pipe line that is being dismantled.
	WOOD WORK								
32	a) Removing door with chowkat.	Per No.	174.25		Per No.	174.25		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th
	b) Removing windows and sky lights with chowkat.	No. ditto	136.35		No. ditto	136.35			and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.
33	Removing ventilators and wooden sunshade, etc.	Per No.	71.55		Per No.	71.55		ditto	
34	a) Dismantling wooden beams upto 12' (3.65m)	Per No.	122.10		Per No.	122.10		ditto	

	MRS, BI-ANNUAL PERIO	O (1st FE	BRUARY, 20	13 TO 31st J	JULY, 20 <sup>-</sup>	13) DISTF	RICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	length.								
	b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length.	ditto	195.35		ditto	195.35			
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	235.70		sq.m	25.35		ditto	
	b) Dismantling wooden trusses.	100Kg	696.15		%Kg	696.15			
36	Dismantling wooden palisade fencing.	Per Lft.	19.35		Metre	63.45		ditto	
	<u>Iron work</u>								
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	701.55		%Kg	701.55		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.
38	Dismantling rolled steel beams or iron rails, etc.	100 <b>K</b> g	320.65		%Kg	320.65		ditto	
39	Dismantling iron latrine.	Per Unit/ 2 Seats	757.70	50	Per Unit/ 2 Seats	757.70		ditto	
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per inch bore	16.15	- J. 19	Each per cm bore	6.45		ditto	
41	a) Dismantling B.G. water column.	Each	4,917.00		Each	4917.00		ditto	
	b) Dismantling M.G. or N.G. water column.	Each	3,283.50		Each	3283.50		ditto	
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	332.10		Metre	10.90		18.1	
	<u>Miscellaneous</u>								
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	156.30		sq.m	16.80		18.1	
44	Dismantling cloth ceiling and supporting timber.	100Sft.	293.05		sq.m	31.55		ditto	
45	Dismantling and removing road metalling.	100Cft.	781.45		cu.m	276.00		ditto	
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead (30 metre).	100Cft.	1,043.20		cu.m	368.45		ditto	
47	Removing mud plaster from walls.	100Sft.	81.40		sq.m	8.75		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th
48	Removing cement or lime plaster.	100Sft.	162.80		sq.m	17.50		ditto	and subsequent floors against item No. 47, 48, 49, & 50 respectively

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
49	Scraping:-							18.1			
	a) White wash or colour wash.	100Sft.	97.70		sq.m	10.50					
	b) Ordinary distemper, oil bound distemper, or paint of wall.	ditto	293.05		ditto	31.55					
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	929.30		sq.m	100.00		18.1			
51	Scraping boulders.	100Cft.	1,367.50		cu.m	483.00		18.1			
52	Cleaning lime or cement mortar of old stones to be used in masonry.  Electric Wiring	100Cft.	683.75		cu.m	241.50		18.1			
54	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).  Dismantling plug point and making good damaged surface (building portion).	Per point  Per point	30.60 26.20	31.00 26.55	Per point  Per point	30.60 26.20	31.00 26.55				
55	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-		rance 9	Departs	e seu t						
	i) on surface ii) recessed in wall	Per foot Per foot	5.60 11.80	5.65 11.95	P.Mtr P.Mtr	18.35 38.70	18.55 39.20				

# 5. MORTAR

	MRS, BI-ANNUAL PERIOD (	31st JULY, 2	013) DISTRIC	CT RAWALP	INDI		
		Dry	Material Required	d for	Dry .	Material Required	l for
a	5		ft. Wet (Ready) N	Mortar		um Wet (Ready)	
S. No.	Ratio of Mortar	Cement	Lime	a .	Cement	Lime	Sand
		(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.
- 1	2	Bag 3	Ctt.	Ctt.	Bag.	Cum 7	8
	<u> </u>	3	4	5	6	/	8
1	Cement: Sand						
	1:2	33.48		82	11.83		0.82
	1:3	23.11		85	8.16		0.85
	1:4	18.37		90	6.49		0.90
	1:5	14.70		90	5.19		0.90
	1:6	13.61		100	4.81		1.00
	1:7	11.68		100	4.12		1.00
	1:8	10.21		100	3.61		1.00
2	Cement : Lime : Sand						
	1:1:6	12.25	15.0	90	4.33	0.15	0.90
	1:1:7	10.70	13.1	92	3.78	0.13	0.92
	1:1:8	9.39	11.5	92	3.32	0.12	0.92
	1:1:9	8.52	10.44	94	3.00	0.10	0.94
	1:1:10	7.67	9.4	94	2.71	0.09	0.94
	1:2:8	9.19	22.5	90	3.25	0.23	0.90
	1:2:9	8.16	20.0	90	2.88	0.20	0.90
	1:2:10	7.67	18.8	94	2.71	0.19	0.94
	1:2:12	6.39	15.66	94	2.26	0.16	0.94
	1:3:12	6.26	23.0	92	2.21	0.23	0.92
	1:3:14	5.47	20.1	94	1.93	0.20	0.94
	1:3:16	4.82	17.7	94	1.70	0.18	0.94
	1: 1/4: 3	23.11	7.0	85	8.16	0.07	0.85
3	Lime: Sand	(Thomas and a	rue (II)barrens	<del>nath au</del> n seemat			
	1:2	Jac. Decree-Detector-Al	43	86		0.43	0.86
	1:3		31	93		0.31	0.93

# 5. MORTAR

	MRS, BI-ANNUAL F	PERIOD (19	st FEBRU	ARY, 201	3 TO 31s	t JULY, 2	013) DIS	TRICT RA	WALPIN	DI	
			Dry Material Wet	Required for (Ready) Mor	or 100 Cft. tar				aterial Requi Wet (Ready		
S. No.	Ratio of Mortar	Clay	Lime (Putty)	Sand	Surkhi	Cinder	Clay	Lime (Putty)	Sand	Surkhi	Cinder
		Cft.	Ctt.	Cft.	Cft.	Cft.	M	M	M	M	M
1	<u> </u>	3	4	5	6	1	3	4	5	6	/
4	Mud	135					1.35				
5	Lime : Surkhi										
	2:3		49.00	-	73.5		-	0.49	-	0.74	-
	1:2		40.75	-	81.5		-	0.41	-	0.82	-
	1:3		30.30	-	91.0		-	0.30	-	0.91	-
6	Lime : Sand : Surkhi										
	1:1:1		40.50	40.5	40.5		-	0.41	0.41	0.41	
7	Lime: Cinder			35-							
,	1:1		57.0	-	- `	57.0	-	0.57	-	-	0.57
			1								

Wet material required for 100 Cft.

Wet material required for 1M³ (35.32 Cft)

			masonry (incl	uding wastag	e):	masonry (including wasta	ge):
1	Brick a) b) c) d)	Masonry: Mud Mortar Cement, Sand Cement, Lime (Putty) Lime (Putty) Sand	Sand	35.00 25.00 25.00 25.00	Cft Cft	0.35 0.25 0.25 0.25	M <sup>3</sup> M <sup>3</sup> M <sup>3</sup> M <sup>3</sup>
2	a) ii ii)	Random rubble, uncou Foundation and Plinth Superstructure Coursed	rsed	45.00 40.00 35.00		0.45 0.40 0.35	M³ M³ M°
	b)	Ashlar Block in course	or Scabled masonry	30.00	Cft	0.30	$M^3$
	c)	Ashlar fine masonry		20.00	Cft	0.20	$M^3$
Notes :	(1) (2) (3) (4)	Cement Unslaked lime Slaked lime Quick lime	1 Cft. 1.7 Cft. 2.5 Cft. 40 Kg	= 40.8233 = 37.3242 = 37.3242 Will yie	Kg		

### 6. CONCRETE

Notes 1 Notes (1) Rates for all finished works include the removal of surplus debris, unused material and by products.

2 If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
								_			
1	Mud concrete in foundation including watering and ramming, using brick or stone ballast 1½" (40 mm) gauge.	100Cft	2166.50	4236.50	cu.m	765.20	1496.35		The stone ballast, crushed bajri, round shingle from nallah, or brick		
	and other or stone outlines 1/2 (to time) gauge.		-						ballast may be used according to		
2	Dry rammed brick or stone ballast, 1½" to 2"( 40 mm to 50	100Cft	1465.20	3379.20	cu.m	517.50	1193.55		their comparative cheaper rates in		
	mm) gauge.	1. /							various areas of the Province.		
					78						
		386			7 34						
		663/7	1.6	/ جورت	43						
3	Cement concrete brick or stone ballast 1½ " to 2" (40 mm to	- 0			53			20.1	-do-		
	50 mm) gauge, in foundation and plinth:-			0							
	(a) Ratio 1: 3: 6	100Cft	2861.10	12048.90	cu.m	1010.55	4255.65				
	(b) Ratio 1: 4: 8	ditto	2861.10	10285.75	"	1010.55	3632.95				
	(c) Ratio 1:5:10	ditto	2861.10	9349.60	"	1010.55	3302.30				
	(d) Ratio 1: 6:12	ditto	2861.10	8640.60	"	1010.55	3051.85				
	(e) Ratio 1: 6: 18	ditto	2861.10	7936.50	"	1010.55	2803.15				
	(f) Ratio 1: 7:20	ditto	2861.10	7590.65	"	1010.55	2681.00				
4	Extra on item No. 3 above, for sedimentation tank or filter										
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri,		
									round shingle from nallah, or brick		
	(a) in bed	100Cft	942.50	-	cu.m	332.90	-		ballast may be used according to		
									their comparative cheaper rates in		
	(b) on slope	ditto	1407.10	-	"	497.00	-		various areas of the Province.		
5	Cement concrete plain including placing,							20.1			
	compacting, finishing and curing										
	complete (including screening and										
	washing of stone aggregate):										

Page 41

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	R	ate (British Sys	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	(a) Ratio 1: 1:2 (b) Ratio 1: 1½: 1½ (c) Ratio 1: 1½: 3 (d) Ratio 1: 2: 3 (e) Ratio 1: 3: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 6	100Cft ditto ditto ditto ditto ditto ditto ditto	3904.55 3904.55 3904.55 3904.55 3904.55 3904.55	23590.25 19351.25 18446.75 16354.80 16830.00	cu.m " " cu.m	1379.10 1379.10 1379.10 1379.10 1379.10 1379.10	8488.45 8332.10 6834.85 6515.40 5776.50 5944.35 5315.15					
	(h) Ratio 1: 3: 6	ditto	3904.55	14472.35	"	1379.10	5111.65					
	(i) Ratio 1: 4: 8	ditto	3904.55	12769.20	"	1379.10	4510.10					
6	Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):-  (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-			Depart				20.4	1) The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring.  2) Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid extra.  3) This item shall not be applicable to factory made units.			
	(1) Type A (nominal mix 1:1:2) (2) Type B (nominal mix 1: 1½: 3) (3) (c) Type C (nominal mix 1: 2: 4) (a)(ii) Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 5(a) (i) above not requiring form work (i.e. horizental shuttering) complete in all respects:- (1) Type A (nominal mix 1: 1: 2) (2) Type B (nominal mix 1: 1½: 3) (3) Type C (nominal mix 1: 2: 4)	Per Cft ditto ditto  Per Cft ditto ditto	89.65 89.65 89.65 52.80 52.80 52.80	287.25 262.05 268.25 216.85	cu.m " cu.m " "	3166.45 3166.45 3166.45 1864.90 1864.90	11793.35 10145.65 9255.60 9474.60 7659.15 6769.10		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.			

	MRS, BI-ANNUAL PERIO	OD (1st FE	EBRUARY, 2	013 TO 31s	JULY,	2013) DIS	TRICT RAWA	LPINDI	
Sr.	Description	F	Rate (British Sys	etem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(b) Precast reinforced cement concrete and prestressed reinforced cement concrete in columns, beams, lintels, stair cases, shelves, etc. (1) Type A (nominal mix 1: 1: 2) (2) Type B (nominal mix 1:1½: 3) (3) Type C (nominal mix 1: 2: 4)	Per Cft ditto ditto	67.60 67.60 67.60	300.60 253.60 228.75	cu.m "	2387.65 2387.65 2387.65	10617.20 8957.15 8079.45		
	(c) Erecting and fixing in position, precast cement concrete or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m) including all charges.	Per Cft	31.15	45.20	cu.m	1100.20	1596.45		
	(d) Add extra labour for R.C. concrete in 2nd and subsequent storeys.	Per Cft	14.65		cu.m	517.45	-		
7	Providing and casting in situ bored reinforced concrete piles with type C concrete (nominal mix 1: 2: 4), using 10% extra cement in dry mix, and course sand, including all labour and material (except the cost of steel reinforcement and its		\$ 15°					*851-1 to 851-10	Composite rate shall be reduced by Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.
	labour for bending and laying in position, etc. which will be paid separately, including, screening & washing of shingle and curing:- i) 18 " (450 mm) dia pile	Per Rft	697.35	958.35	Metre	2287.30	3143.40		
	ii) 20" (500 mm) dia pile iii) 22" (550 mm) dia pile iv) 24" (600 mm) dia pile	Per Rft Per Rft Per Rft	788.90 930.3 1105.45	1110.85 1307.35 1569.35	Metre Metre Metre	2587.60 3051.4 3625.90	3643.60 4288.1 5147.5		
8	Fabrication of mild steel reinforcement bar cage for R.C.C. bored piles, including cutting, bending, laying in position, welding and fastening, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from the bars):-							*851-5	The rate includes wastage, overlaps, etc. but does not apply to the laps and spiral reinforcement which are specifically shown in the structural / working drawings of piles as per lapping requirements of design.
	(a) plain bars (b) deformed bars	Per Cwt.	1069.20 1069.20	4489.45 5955.25	100 kg	2104.70 2104.70	8837.50 11722.95		
9	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints							*851.5	The rate includes wastage, overlaps and chairs, etc.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	and fastenings, including cost of binding wire and labour											
	charges for binding of steel reinforcement (also includes											
	removal of rust from bars):-	D G :	200.40	2005.05	1001	571.65	7640.20					
	<ul><li>(a) Plain bars</li><li>(b) Deformed bars (Grade-40)</li></ul>	Per Cwt. ditto	290.40 290.40		100 kg ditto	571.65 571.65	7649.30 10767.40					
	(c) Deformed bars (Grade-40) (c) Deformed bars (Grade-60)	ditto	290.40	5832.85	ditto	571.65	10767.40					
	(C) Deformed bars (Grade-00)	ditto	290.40	3632.63	unto	3/1.03	11462.00					
10	Precast cement concrete solid or face blocks (1:2:4),	Per Cft	36.50	164.75	cu.m	1289.20	5818.95	20.2				
	including cost of templates.											
			/ X	) \								
11	Precast cement concrete hollow blocks (1: 2: 4), including	Per Cft	80.25	164.55	cu.m	2834.45	5811.90	20.2				
	cost of templates and constructing walls thereof.	de l			111							
12	Descriding and fiving amountal computation 2" (50 mm) thick	Per Sft	23.25	44.80	7 8	250.15	482.05	20.1 to				
12	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	Per Sit	23.23	44.80	sq.m	250.15	482.03	20.1 to				
	(1. 2. 4), without seet.	16517	1.65	/ منزرت	49			20.4				
13	Extra labour for laying concrete plain or reinforced:	-0			93							
				Dim								
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	1562.90	T))erevert	cu.m	552.00	-					
	(b) for every additional 10'(3 m) height.	100Cft	976.80	TO STATE SHOW IN	cu.m	345.00	-					
1.4		10006	200.70			120.00						
14	Extra labour for work of weirs, rail or road bridges, syphons, and concreting in superstructure	100Cft	390.70	-	cu.m	138.00	-					
	concreting in superstructure											
15	Making reinforced cement concrete spout, including fixing in	Each	290.40	426.25	Each	290.40	426.25	20.4				
	position (2½' x 6" x5") (760 mmx150 mm x 125 mm)											
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement	Per hole	696.95	-	Each	696.95	-	20.1				
	concrete or stone masonry walls and repairing.											
17	Tutus lakasus for skinning apparets in 500 U-	10000	2402.40		av	040 55		20.1				
1/	Extra labour for skipping concrete in wells.	100Cft	2402.40	-	cu.m	848.55	-	20.1				
18	Nicking concrete surface:											
	(a) Cement concrete surface	100Sft	269.30	-	sq.m	29.00	-					
	(b) Lime concrete surface	ditto	88.85	-	"	9.55	-					

Page 44

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric S	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
		Cint	Labout	Composite	Cilit	Labout	Composite			
19	Preparing, watering and ramming surface for laying concrete									
	(for Headworks only):-									
	(a) Horizontal floor	100Sft	248.50	-	sq.m	26.75	-			
	(b) Glacis and crest	ditto	366.95	-	"	39.50	-			
	(c) Inverted filters	ditto	116.15	-	"	12.50	-			
20	Fabrication of high tensile steel prestressing cables for	100 Kg.	3452.20	31484.50	100 Kg.	3452.20	31484.50	*811-1	The rate includes wastage in	
	prestressed (post tensioned) concrete, including assembling by							to	cutting and breakage in stressing,	
	drawing the H.T. wire through metal spacer plate, inserting in helix							811-11	etc.	
	core and taping or tying, sheathing in longitudinally welded metal		/ ×	)						
	corrugated sheath, positioning, anchorage with male and female		/		\					
	set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule,	-1.6								
	maintaining stressing record and supply the same in the approved	8			日数					
	proforma to the Engineer-in-charge, making loop at blind end,	100			7 82					
	including all materials required for it, grouting the cable ducts with	169/	1	67	13					
	cement, cutting projected ends and making good recesses, etc.,	7			277					
	complete in all respects.	~			200					
21	Fabrication of High Tensile steel reinforcement for prestressed	100kg	2079.00	29097.20	%kg	2079.00	29097.20		1) The rate includes wastage in	
	(pretension) concrete work, including inserting wire in moulds,		vance (	Depart	TROUGHT.	Ė			cutting and breakage in stressing,etc.	
	providing M.S. shear bars, spacers and lift hooks, male and			-						
	female anchorage, tie down, struts, stressing cables, maintaining								2) Quantity of H. T. wire will form	
	stress record and supply the same in approved proforma to the								basis of payment.	
	Engineer-in-charge, cutting wires and projecting ends and making								3) This item shall not be applicable	
	good recesses, etc., complete in all respects.								to factory made units.	
22	Lifting, transporting and placing precast prestressed concrete							*811-1		
	B eam, Girder and other members (excluding battens) etc. in							to		
	Position on the bridge to correct alignment and level, etc.							811-11		
	complete									
	i) Beam upto 50 ft. (15 m) length	100Cft		1330.80	cu.m		470.05			
	ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length	100Cft		1925.52	cu.m		680.10			
	iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length	100Cft		2510.40	cu.m		886.65			
	iv) Beam above 100ft. (30m) upto 150ft.(45m) length	100Cft		3228.70	cu.m		1140.40			
	v) Beam above 150ft. (45m) length	100Cft		3933.45	cu.m		1389.30			

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31s	t JULY, 2	2013) DIS	TRICT RAWA	LPINDI	
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
23	Providing and laying foam concrete 3 inch (75 mm) thick, using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,	Per Sft.	21.45	54.20	sq.m.	230.80	583.20		
24	Providing and fixing 6 in(150 mm), wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-		×						
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	12.30 12.60	86.95 78.65	\	40.35 41.35	285.20 257.95		
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-		557		7				
	a) On interior surface (without mastic strip)	Per Rft.	11.20	85.90	Metre	36.75	281.75		
	b) On exterior surface (with mastic strip)	ditto	11.20	88.90	econocias de la composition della composition de	36.75	291.60		
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on expansion joints complete in all respects.	Per Sft.	11.60	96.80	Sq.m	124.80	1041.55		
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG. stopper to expansion joint.	Per Rft.	4.15	66.75	Metre	13.60	218.95		
28	Providing embeding 10" (250 mm) wide ½" (6 mm) thick rubber water stopper in expansion joints of R.C.C. roof slab complete in all respects.	Per Rft.	16.85	63.65	Metre	55.25	208.70		
29	Filling expansion joints with bitumen. sand & saw dust in ratio 1:2:2.	Per Rft per inch width	2.45	20.50	P.Metre/ Per 25 mm Width	8.05	67.25		
30	Filling expansion joints with bitumen.	Per Rft.	32.60	-	Metre	106.95	-		

Page 46

	MRS, BI-ANNUAL PERIO	TRICT RAWA	ALPINDI						
Sr.	Description	R	Rate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				*******					
31	Laying asphaltic mixture in expansion joints.	Per Rft.	34.20	-	Metre	112.20	-		Material to be paid on actuals.
32	Providing and fixing theremopore (foamed polythene)								
	sheet in horizontal and vertical expansion joints:								
	a) 1" (25 mm) thick thermopore sheet	Per Sft.	4.65	9.55	Sq.m	50.05	102.75		
	b) 1½" (40 mm) thick thermopore sheet	ditto	4.65	13.80	"	50.05	148.50		
33	Providing and laying damp proof course of cement concrete		/ X	) \					
	1:2: 4(using cement, sand and shingle), including bitumen		/ ·						
	coating :-	-116			111				
					72				
	(a) with one coat bitumen and one coat polythene sheet	85%			1 366				
	500gauge	1647	1.6	/(4: ست	43				
	i) 1½" thick (40 mm)	100Sft	1026.50	4006.45	sq.m	110.45	431.10		
	ii) 2" thick (50 mm)	100Sft	1026.50	4490.65	sq.m	110.45	483.20		
	iii) 3" thick (75 mm)	100Sft	1071.40	5589.20	sq.m	115.30	601.40		
	(b) with 2 coats of bitumen:								
	i) 1½" thick (40 mm)	100Sft	1026.50	4487.45	sq.m	110.45	482.85		
	ii) 2" thick (50 mm)	100Sft	1026.50		_	110.45	534.85		
	iii) 3" thick (75 mm)	100Sft	1071.40	6069.50	sq.m	115.30	653.10		
34	Providing and laying damp proof course with cement sand								
34	plaster and bitumen coating:-								
	praster and ortunion countries.								
	(a) with one coat of bitumen and one coat of polythene sheet								
	500 gauge :-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	959.20	2645.80	sq.m	103.20	284.70		
	b) 3/4" thick (20 mm)	100Sft	959.20		sq.m	103.20			
	, , ,				1				

	ALPINDI	TRICT RAWA	2013) DIS	JULY,	013 TO 31st	BRUARY, 2	OD (1st FE	MRS, BI-ANNUAL PERIO
Remarks	Spec.	System)	ate (Metric S	R	tem)	Rate (British Syst	F	r. Description
	No.	Composite	Labour	Unit	Composite	Labour	Unit	0.
								ii) Ratio 1:3
		293.20	103.20	sq.m	2725.00	959.20	100Sft	a) ½ " thick (13 mm)
		321.00	103.20	sq.m		959.20	100Sft	b) 3/4 " thick (20mm)
								iii) Ratio 1:2
		303.25	103.20	sq.m	2818.15	959.20	100Sft	a) ½ " thick (13 mm)
		342.55	103.20	sq.m		959.20	100Sft	b) <sup>3</sup> / <sub>4</sub> " thick (20 mm)
								(b) with 2 coats of bitumen:-
				\		/ 3		i) Ratio 1: 4
		318.75	103.20	sq.m	2962.40	959.20	100Sft	a) ½" thick (13 mm)
		345.00	103.20	sq.m	3206.50	959.20	100 <b>S</b> ft	b) 3/4" thick (20 mm)
				7 Table		-	188	ii) Ratio 1:3
		327.40	103.20	sq.m	3042.60	959.20	100Sft	a) ½ " thick (13 mm)
		355.20	103.20	sq.m		959.20	100Sft	b) <sup>3</sup> / <sub>4</sub> " thick (20 mm)
			į.		These west	elumentenso (	(100)	iii) Ratio 1:2
		348.65	103.20	sq.m	3240.10	959.20	100Sft	a) ½ " thick (13 mm)
		390.30	103.20	sq.m	3627.10	959.20	100Sft	b) 3/4 " thick (20 mm)
								Providing and laying vertical damp proof course with cement sand plaster and bitumen coating:-
								(a) with one coat of bitumen and one coat of polythene sheet 500 gauge:
								i) Ratio 1: 4
		273.40	103.20	sa m	2540.95	959 20	100Sft	
		299.70	103.20	sq.m		959.20	100Sft	b) 3/4" thick (20 mm)
								ii) Ratio 1:3
		282.00	103.20	sq.m	2620.65	959.20	100Sft	a) ½ " thick (13 mm)
		309.80	103.20	sq.m	2879.00	959.20	100Sft	b) 3/4 " thick (20 mm)
		348.65 390.30 273.40 299.70	103.20 103.20 103.20 103.20	sq.m sq.m sq.m sq.m	3240.10 3627.10 2540.95 2785.15	959.20 959.20 959.20 959.20	100Sft 100Sft 100Sft 100Sft	iii) Ratio 1:2 a) ½ " thick (13 mm) b) ¾ " thick (20 mm)  Providing and laying vertical damp proof course with cement sand plaster and bitumen coating:-  (a) with one coat of bitumen and one coat of polythene sheet 500 gauge:  i) Ratio 1: 4 a) ½" thick (13 mm) b) ¾" thick (20 mm)  ii) Ratio 1:3 a) ½ " thick (13 mm)

	MRS, BI-ANNUAL PERIO								
Sr.	Description		Rate (British Sys	tem)	F	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) Ratio 1:2			*****					
	a) ½ " thick (13 mm)	100Sft	959.20		•	103.20	303.25		
	b) ¾ " thick (20 mm)	100Sft	959.20	3205.15	sq.m	103.20	344.85		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	959.20	2962.35	sq.m	103.20	318.75		
	b) 3/4" thick (20 mm)	100Sft	959.20	3206.50	sq.m	103.20	345.00		
			/ X	) \					
	ii) Ratio 1:3		/ ~	1	\				
	a) ½ " thick (13 mm)	100Sft	959.20	3042.00	sq.m	103.20	327.30		
	b) 3/4 " thick (20 mm)	100Sft	959.20	3300.35	sq.m	103.20	355.10		
		. 83			J 88				
	iii) Ratio 1:2	1886	-	67					
	a) ½ " thick (13 mm)	100Sft	959.20	3239.55	sq.m	103.20	348.60		
	b) 3/4 " thick (20 mm)	100Sft	959.20	3626.45	sq.m	103.20	390.20		
36	Grouting concrete between, the grooves of gates, including	100Cft	4626.60	I)epart	cu.m.	1634.10	-		
	shuttering.								
37	Chiesel dressing concrete surface on sides of grooves.	100Sft	148.10	-	sq.m	15.95	-		
38	Laying and ramming dry ballast or kankar.	100Cft	1587.30	-	cu.m	560.65	-		
39	Hoisting and placing in position R.C.C. shelves.	per No.	51.55	-	per No.	51.55	-		
40	Breaking brick ballast, screening and stacking:-								
	(a) 2"(50 mm) ring	100Cft.	1221.00	-	cu.m	431.25	-		
	(b) 1½ "(40 mm) ring	ditto	1367.50	-	"	483.00	-		
	(c) 1" (25 mm) ring	ditto	1587.30		"	560.65	-		
	(d) Jhama ballast ¾"(20 mm) ring	ditto	1831.50		"	646.90	-		
41	Supplying and fixing broken glasses on court yard walls, including 1:3: 6 cement concrete coping.	Per Rft	38.30	76.05	metre	125.60	249.45		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Crushing stone ballast by machine.  Breaking stone ballast screened and stacked:-	100Cft	1221.00	-	cu.m.	431.25	-		This does not include the charges for working of crushers, but includes manual labour for carriageof stone to crusher within three chains (90 m) and also stacking the product after crushing within three chains (90 m).				
	(a) 2" ring (50 mm) (b) 1½" ring (40 mm) (c) 1" ring (25 mm) d) ½" ring (13 mm) (e) 1/8" to ¼" ring (3 mm to 6 mm)  Screening and stacking stone ballast shingle or bajri, etc.  Washing ballast, bajri or shingle.	100Cft. ditto ditto ditto ditto 100Cft.	1367.50 1587.30 1831.50 2442.00 4151.40 390.70		cu.m. " " " cu.m.	483.00 560.65 646.90 862.50 1466.30 138.00							
46	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2½' (1.50 m x 0.76 m)	Each	223.60	Depart	Each	223.60	-						

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

### 7. BRICK WORK

- 1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.
- 2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4"x4" (200x100x100 mm) nominal.

	MRS, BI-ANNUAL PERIO	TRICT RAWA	LPINDI						
Sr. No.	Description	j	Rate (British Sy	stem)	R	Rate (Metric	System)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
1	Pacca brick work in mud mortar in buildings:  i) in foundation and plinth ii) in ground floor	100Cft. ditto	2035.65 2695.65	13444.65 14104.65	cu.m ditto	719.00 952.10	4748.65 4981.75	21.1 to 21.4	Masonry of boundary wall to be considered as masonry other than building.
2	Add extra labour on item No. 1 for brick work in:-		× .						The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) first floor	100Cft.	525.35		cu.m	185.55	-		
	ii) second floor	ditto	1185.35		ditto	418.65	-		
	iii) third floor	ditto	1845.35		ditto	651.80	-		
	iv) fourth & subsequent floors	ditto	2970.00	6/	ditto	1049.00	-		
3	Pacca brick work in mud mortar other than building:-	1						21.1 to 21.4	Same remarks as against item No. 1 above
	i) upto 20 ft. (6.1 m) height	100Cft.	2772.40	14181.40	cu.m	979.20	5008.85		
	ii) extra labour for every 5 ft. (1.5 m) additional height, or part thereof.	ditto	525.35	Disparti	ditto	185.55	-		
4	Pacca brick work in foundation and plinth in:-							ditto	Same remarks as against item No. 1 above.
	i) Cement, sand mortar:-								
	Ratio 1:2	100Cft.	2679.20	18436.40	cu.m	946.25	6511.75		
	Ratio 1:3	ditto	2679.20	17372.60	ditto	946.25	6136.00		
	Ratio 1:4	ditto	2679.20	16734.30	ditto	946.25	5910.55		
	Ratio 1:5	ditto	2679.20	16308.80	ditto	946.25	5760.25		
	Ratio 1:6 Ratio 1:7	ditto ditto	2679.20 2679.20	15989.10 15779.60	ditto ditto	946.25 946.25	5647.35 5573.35		
	Ratio 1:8	ditto	2679.20	15596.00	ditto	946.25	5508.50		
	ii) lime, cement sand mortar:-							21.1	The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	2679.20	16291.65	cu.m	946.25	5754.20		
	Ratio 1:1:7	ditto	2679.20	16060.80	ditto	946.25	5672.70		
	Ratio 1:1:8	ditto	2679.20	15873.90	ditto	946.25	5606.65		
	Ratio 1:1:9	ditto	2679.20	15717.25	ditto	946.25	5551.35		
	Ratio 1:1:10	ditto	2679.20	15599.85	ditto	946.25	5509.85		

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	]	Rate (British Sy	rstem)	R	Rate (Metric	System)	Spec.	Remarks		
No.	_							No.			
	1	Unit	Labour	Composite	Unit	Labour	Composite		<u> </u>		
	iii) lime, sand mortar 1:2	100Cft.	2679.2	15364.1	cu.m	946.25	5426.6	ditto	ditto		
	in inc, said nortal 1.2	Toocit.	2077.2	1330 1.1	Cuilli	710.23	3120.0	ditto	ditto		
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to		
									be reduced by 7% and 14%,		
	i) cement, sand mortar:-								if 2nd or 3rd class bricks are used.		
	Ratio 1:2	100Cft.	3534.55	19291.75	cu.m	1248.40	6813.85		ii) Masonry of boundary wall		
	Ratio 1:3	ditto	3534.55	18227.95	ditto	1248.40	6438.10		to be considered as masonry		
	Ratio 1:4	ditto	3534.55	17589.65	ditto	1248.40	6212.65		other than building.		
	Ratio 1:5	ditto	3534.55	17164.15	ditto	1248.40	6062.35				
	Ratio 1:6	ditto	3534.55	16844.45	ditto	1248.40	5949.45				
	Ratio 1:7 Ratio 1:8	ditto ditto	3534.55 3534.55	16634.95 16450.25	ditto ditto	1248.40 1248.40	5875.45 5810.25				
	Kano 1:8	anto	3334.33	10430.23	anto	1248.40	3810.23				
	ii) lime, cement, sand mortar:-		/ ~						The rate of lime mortar also		
					\				includes grinding of mortar.		
	Ratio 1:1:6	100Cft.	3534.55	17147.00	3 7 7 7 7	1248.40	6056.30				
	Ratio 1:1:7	ditto	3534.55	16918.80	ditto	1248.40	5975.70				
	Ratio 1:1:8 Ratio 1:1:9	ditto ditto	3534.55 3534.55	16729.25 16572.60	ditto ditto	1248.40 1248.40	5908.75 5853.45				
	Ratio 1:1:10	ditto	3534.55	16455.60	ditto	1248.40	5812.10				
	Tamio 1.1.10	unto	3331.33	10133.00	unto	12 10.10	3012.10				
	iii) lime, sand mortar 1:2	100Cft.	3534.55	16219.45	cu.m	1248.40	5728.70		The rate of lime mortar also		
				0					includes grinding of mortar.		
6	Add extra labour on item No. 5 for brickwork	ANT 15		(571)							
	in:-	Q-70	MARILE (	ildegrafti	87/8593 <b>I</b>						
	i) first floor	100Cft.	525.35		cu.m	185.55	-				
	ii) second floor	ditto	1185.35		ditto	418.65	-				
	iii) third floor	ditto	1845.35		ditto	651.80	-				
	iv) fourth & subsequent floors	ditto	2970.00		ditto	1049.00	-				
7	Pacca brick work other than building upto 10ft. (3 m)							21.1	i) The composite rate is to be		
	height.							to	reduced by 7% and 14%, if 2nd or		
								21.5	3rd class bricks are used.		
	i) cement, sand mortar:-								ii) Wadahara adama kin		
	Ratio 1:2	100Cft.	3109.90	18867.10	cu.m	1098.40	6663.85		ii) Workshops, godowns,, bins, house type godowns, reservoirs,		
	Ratio 1:3	ditto	3109.90	17803.30	ditto	1098.40	6288.15		filter beds, storage tanks, wells,		
1	Ratio 1:4	ditto	3109.90	17165.05	ditto	1098.40	6062.70		screening chambers, collecting		
	Ratio 1:5	ditto	3109.90	16739.50	ditto	1098.40	5912.40		tanks, manholes etc. are to be		
1	Ratio 1:6	ditto	3109.90	16419.85	ditto	1098.40	5799.50		treated as masonry other than		
1	Ratio 1:7	ditto	3109.90	16210.30	ditto	1098.40	5725.50		buildings.		
	Ratio 1:8	ditto	3109.90	16026.70	ditto	1098.40	5660.65				
	ii) lime, cement, sand mortar:-								The rate of lime mortar also		
									includes grinding of mortar.		

	MRS, BI-ANNUAL PERI	OD (1st FE	BRUARY, 2	013 TO 31st	JULY, 2	2013) DIS	TRICT RAWA	LPINDI	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Ratio 1:1:6	100Cft.	3109.90	16722.40	cu.m	1098.40	5906.35		
	Ratio 1:1:7	ditto	3109.90	16491.55	ditto	1098.40	5824.80		
	Ratio 1:1:8	ditto	3109.90	16304.65	ditto	1098.40	5758.80		
	Ratio 1:1:9	ditto	3109.90	16147.90	ditto	1098.40	5703.45		
	Ratio 1:1:10	ditto	3109.90	16030.55	ditto	1098.40	5662.00		
	iii) lime, sand mortar 1:2	100Cft.	3109.90	15794.85	cu.m	1098.40	5578.75		ditto
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	525.35		cu.m	185.55	-		
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	1003.20		cu.m	354.35	-	21.5	
10	Extra for pacca brick work in steining of wells or any other	100Cft.	673.20	1352.15	cu.m	237.75	477.60	21.1	The composite rate is to be
	circular masonry.				\			to	reduced by 7% and 14%, if 2nd or
		3.00			4 11.			21.4	3rd class bricks are used.
		-18%			188				
11	Extra labour for profile and flared walls.	100Cft.	231.60	T	cu.m	81.80	-		
12	Extra labour for pacca brick work in piers and abutment:-	1234	1	50					
1-2	2.1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	1,77			201				
	i) from 10ft. to 20ft. (3 m to 6 m) height	100Cft.	260.00	6 20	cu.m	91.85	-		
	ii) above 20 ft. (6 m) height.	100Cft.	525.35	01	cu.m	185.55	-		
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.	wance (	2170.50	cu.m		766.60		This item is to be executed only under the written permission of Superintending Engineer.
14	Reinforced brick work in lintel of openings, laid in 1:3 cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	Per Cft.	88.30	237.30	cu.m	3118.50	8381.45		
15	Extra for dressing or chamfering bricks for:-								
	a) special architectural bricks	100 Nos.	1748.55	_	% Nos.	1748.55	_		
	b) all other purposes	ditto	874.25	-	ditto	874.25	-		
16	Perforated pacca brick walling half brick thick, in ground floors:-	100 54	1245 95	4202.25	Sam	144 00	452.15	21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) mud mortar	100 Sft.	1345.85	4202.25	Sqm.	144.80	452.15		
	ii) cement, sand mortar:-								

	MRS, BI-ANNUAL PER	IOD (1st FE	BRUARY, 2	013 TO 31st	JULY, 2	2013) DIST	TRICT RAWA	LPINDI	
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Ratio 1:2	100 Sft.	1771.25	5714.65	sq.m.	190.60	614.90		
	Ratio 1:3	ditto	1771.25	5448.45	ditto	190.60	586.25		
	Ratio 1:4	ditto	1771.25	5289.15	ditto	190.60	569.10		
	Ratio 1:5	ditto	1771.25	5182.75	ditto	190.60	557.65		
	Ratio 1:6	ditto	1771.25	5108.05	ditto	190.60	549.65		
	Ratio 1:7	ditto	1771.25	5050.00	ditto	190.60	543.40		
	Ratio 1:8	ditto	1771.25	5007.30	ditto	190.60	538.80		
	iii) lime, cement sand mortar								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Sft.	1771.25	5178.50	sq.m	190.60	557.20		
	Ratio 1:1:7	100Sft.	1771.25	5120.10	sq.m	190.60	550.90		
	Ratio 1:1:8	100Sft.	1771.25	5076.75	sq.m	190.60	546.25		
	Ratio 1:1:9	100Sft.	1771.25	5034.30		190.60	541.70		
	Ratio 1:1:10	100Sft.	1771.25	5009.30	sq.m	190.60	539.00		
	iv) lime, sand mortar 1:2	100Sft.	1771.25	4944.55	sq.m	190.60	532.05		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	8			7 🗟				
	i) first floor	100Sft.	265.35	67	sq.m	28.55	-		
	ii) second floor	ditto	590.00	~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	ditto	63.50	-		
	iii) third floor	ditto	925.35	- //6	ditto	99.55	-		
	iv) fourth & subsequent floors	ditto	1431.50	September 1	ditto	154.05	-		
18	Perforated pacca brick walling one brick thick, in ground	Œ.	nance (	Departi				21.1	The composite rate is to be
	floor:	782. 693	MARKEN Y	moustaine es				to 21.4	reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) mud mortar	100Sft.	1888.15	7592.65	sq.m	203.15	816.95		
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	2662.30	10540.90	sq.m	286.45	1134.20		
	Ratio 1:3	ditto	2662.30	10009.00	ditto	286.45	1076.95		
	Ratio 1:4	ditto	2662.30	9689.85	ditto	286.45	1042.65		
	Ratio 1:5	ditto	2662.30	9477.10	ditto	286.45	1019.75		
	Ratio 1:6	ditto	2662.30			286.45	1003.65		
	Ratio 1:7	ditto	2662.30	9211.20		286.45	991.15		
	Ratio 1:8	ditto	2662.30	9120.75	ditto	286.45	981.40		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	2662.30	9468.50	sq.m	286.45	1018.80		includes grinding of mortar
	Ratio 1:1:7	ditto	2662.30	9350.35		286.45	1006.10		
	Ratio 1:1:8	ditto	2662.30	9259.70		286.45	996.35		
	Ratio 1:1:9	ditto	2662.30	9181.30		286.45	987.90		
	Ratio 1:1:10	ditto	2662.30	9124.00	ditto	286.45	981.75		
	iv) lime, sand mortar 1:2	100Sft.	2662.30	9003.50	sq.m	286.45	968.80		ditto

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 2	2013) DIS	TRICT RAWA	ALPINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
19	Add extra labour on item No. 18 for perforated pacca brick work in:-								
	i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors	100Sft. ditto ditto ditto	394.00 889.00 1384.00 2227.50	  	sq.m ditto ditto ditto	139.20 314.00 488.85 786.75	- - -		
20	Fire brick masonry in fireclay mortar:-  i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	22.90	609.50		1193.55	21526.85	21.1 to 21.2	
	<ul> <li>i) upto 20 ft. (6.10 m) height including all charges.</li> <li>ii) Extra for every 5 ft. (1.5 m) additional height, or part thereof.</li> </ul>	100Cft.	33.80 525.35		cu.m ditto	185.55	-	21.2	A&C No.I dated 2.9.1998
21	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-	4						21.19	
	i) 4½" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	100Sft.	1510.10	8144.95	sq.m	162.50	876.40		
	ii) 4½" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	100Sft.	1354.30	7548.10	sq.m	145.70	812.20		
	iii) 3" (75 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	ditto	1194.60	6026.25	ditto	128.55	648.45		
	iv) 3" (75 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	ditto	955.70	5297.40	ditto	102.85	570.00		
22	Ghilafi work (1½ brick thick wall)	100Cft.	2711.70	9199.95	cu.m	957.75	3249.40	21.18	
23	Dry brick pitching	100Cft.	1650.00	12828.00	cu.m	582.80	4530.85	21.1	
24	Sun dried bricks in mud mortar	100Cft.	2275.70	3843.20	cu.m	803.80	1357.40	21.16	
25	Pise wall (mud walling)	100Cft.	1188.00		cu.m	419.60	-	21.17	
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2	
	<ul> <li>i) 3" (75 mm) thick drip course cornice</li> <li>ii) 4½" (113 mm) thick drip course cornice.</li> <li>iii) 4½" (113 mm) thick eave brick with back brick.</li> </ul>	Rft. ditto ditto	17.25 19.60 13.20	44.95 93.05 109.55	Metre ditto ditto	56.60 64.30 43.30	147.45 305.20 359.30		correction vide A&C No.I dated 2.9.98
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2	
	i) 1 brick ii) 2 bricks	Rft. ditto	19.60 28.90	33.95 72.60	Metre ditto	64.30 94.80	111.35 238.15		

	MRS, BI-ANNUAL PEF	RICT RAWA	LPINDI						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) 3 bricks iv) 4 bricks	ditto ditto	38.55 48.45	111.00 155.05	ditto ditto	126.45 158.90	364.10 508.55		
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	683.75		1,000 Nos	683.75	-		
29	Scraping bricks dismantled from pacca masonry	1,000 Nos	1289.40		1,000 Nos	1289.40	-		
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	162.80	1242.80	cu.m	57.50	438.95		
31	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart.	Rft.	72.60	129.40	Metre	238.15	424.45		
32	First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG hoop iron strips bonding placed at 2.0' (600 mm) apart horizontally, and at 1.0' (300 mm) interval vertically.				1				This item is to be executed only under the written permission of the Superintending Engineer.
	i) 1:3 ii) 1:4	100Sft. ditto	1354.30 1354.30	8885.80 8630.50	sq.m ditto	145.70 145.70	956.10 928.65		
33	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	38.70	T)ervarti	sq.m	416.40	-		
34	Replacing kallar eaten bricks	Each No.	30.60	37.55	Each	30.60	37.55		
35	Repairing corners of bridges and other hydraulic masonry works	Each No.	193.60	266.90	Each	193.60	266.90		
36	Extra labour for drains of bath rooms, etc.	Per Lft.	16.85		Metre	55.25			
37	Maroo corners	Each Corner	107.70		Each Corner	107.70			Payable in addition to brick work

#### 8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- 3 Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIO	LPINDI							
Sr.	Description	F	Rate (British Sys	tem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Random, rubble masonry (uncoursed), in foundation and plinth:	1						22.10, 22.11	
	a) dry masonry	100 Cft.	2811.60	3597.60	cu.m	993.05	1270.65		
	b) in mud mortar	100 Cft.	3517.80	4600.80	cu.m	1242.50	1625.00		
	c) in lime, sand mortar 1:2	100 Cft.	5385.60	8108.40	cu.m	1902.20	2863.90		
	d) in cement, sand mortar								
	i) ratio 1:3	100 Cft.	5385.60	11444.70	cu.m	1902.20	4042.25		
	ii) ratio 1:4	100 Cft.	5385.60	10487.30	cu.m	1902.20	3704.10		
	iii) ratio 1:6	100 Cft.	5385.60	9391.50	cu.m	1902.20	3317.10		
	iv) ratio 1:8	100 Cft.	5385.60	8785.20	cu.m	1902.20	3102.95		
2	Coursed rubble masonry hammer dressed, in foundation and plinth:							22.8	
	a) dry masonry	100 Cft.	3484.80	4270.80	cu.m	1230.85	1508.45		
	b) in mud mortar	100 Cft.	4897.20	5980.20	cu.m	1729.70	2112.20		
	c) in lime, sand mortar 1:2	100 Cft.	6015.90	8522.75	cu.m	2124.80	3010.25		
	d) in cement, sand mortar:								
	i) ratio 1:3	100 Cft.	6015.90	11777.10	cu.m	2124.80	4159.65		
	ii) ratio 1:4	100 Cft.	6015.90	10926.05	cu.m	2124.80	3859.10		
	iii) ratio 1:6	100 Cft.	6015.90	9951.75	cu.m	2124.80	3514.95		
	iv) ratio 1:8	100 Cft.	6015.90	9416.00	cu.m	2124.80	3325.75		
3	Random rubble masonry (uncoursed) in ground floor or 20 ft.(6 m) height, building/other than building.							22.10	
	a) dry masonry	100 Cft.	3148.20	3934.20	cu.m	1111.95	1389.55		
	b) in mud mortar	100 Cft.	4224.00	5307.00	cu.m	1491.90	1874.45		

	MRS, BI-ANNUAL PERIO	RICT RAWA	LPINDI						
Sr.	Description	]	Rate (British Sys	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	-							No.	
	I	Unit	Labour	Composite	Unit	Labour	Composite		T
	c) in lime, sand mortar 1:2	100 Cft.	5847.60	8570.40	cu.m	2065.35	3027.05		
	d) in cement, sand mortar:	100 011	2017100	32 / 31 13	•	2000.00	3027.00		
	i) ratio 1:3	100 Cft.	5847.60	11906.70	cu.m	2065.35	4205.45		
	ii) ratio 1:4	100 Cft.	5847.60	10949.30	cu.m	2065.35	3867.30		
	iii) ratio 1:6	100 Cft.	5847.60	9853.50	cu.m	2065.35	3480.25		
	iv) ratio 1:8	100 Cft.	5847.60	9247.20	cu.m	2065.35	3266.10		
4	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8	
	a) dry masonry	100 Cft.	4065.60	4851.60	cu.m	1435.95	1713.60		
	b) in mud mortar	100 Cft.	6058.80	7128.60	cu.m	2139.95	2517.80		
	c) in lime, sand mortar 1:2	100 Cft.	6765.00	9271.85	cu.m	2389.40	3274.80		
	d) in cement, sand mortar: i) ratio 1:3	100 Cft.	6765.00	12526.20	cu.m	2389.40	4424.25		
	ii) ratio 1:4	100 Cft.	6765.00	11675.15	cu.m	2389.40	4123.65		
	iii) ratio 1:6	100 Cft.	6765.00	10700.85	cu.m	2389.40	3779.55		
	iv) ratio 1:8	100 Cft.	6765.00	10165.10	cu.m	2389.40	3590.30		
	,	1881			(88)				
5	Ashlar block in course or scabbled masonry (including	3300	-		3.65%			22.5	
	dressing, etc.,) in ground floor or 20 ft. (6 m) height,	163/7	1:5	- 150/	1/53			&	
	building/other than building.	Y-11	1		77.			22.6	
		100 50	2	6 223					
	a) in lime, sand mortar 1:2	100 Cft.	17991.60	20396.60	cu.m	6354.65	7204.10		
	b) in cement, sand mortar:	100 CG	17991.60	22621.05		6254.65	7090 75		
	i) ratio 1:3 ii) ratio 1:4	100 Cft. 100 Cft.	17991.60	22621.05 21982.75	cu.m	6354.65 6354.65	7989.75 7764.30		
	ii) ratio 1:4 iii) ratio 1:6	100 Cit. 100 Cft.	17991.60	21259.35	cu.m cu.m	6354.65	7508.80		
	m) rado 1.0	100 Cit.	17991.00	21239.33	Cu.III	0334.03	7308.80		
6	Ashlar fine masonry (including dressing, etc.) in ground							22.3	
	floor or 20 ft. 6 m) height, building/other than building.							(A) to	
								(C) &	
	a) in lime, sand mortar 1:2	100 Cft.	33079.20	35273.35	cu.m	11683.55	12458.55	22.4	
	b) in cement, sand mortar:								
	i) ratio 1:3	100 Cft.	33079.20	36385.60	cu.m	11683.55	12851.40		
	ii) ratio 1:4	100 Cft.	33079.20	36065.95	cu.m	11683.55	12738.50		
	iii) ratio 1:6	100 Cft.	33079.20	35711.35	cu.m	11683.55	12613.25		
7	Extra labour on items 3, 4, 5 & 6 above for work in:-								
	i) first floor	100 Cft.	742.90	_	cu.m	262.40	_		
	ii) second floor	100 Cft.	1662.15	-	cu.m	587.05	-		
	iii) third floor	100 Cft.	2600.95	-	cu.m	918.65	-		
	iv) fourth floor	100 Cft.	4126.85	-	cu.m	1457.60	-		
8	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m)	100 Cft.	660.00	-	cu.m	233.10	-		
	additional height, other than building, or part thereof.						<u> </u>		

Sr.	Description	T	Rate (British Sy			Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	1941.20	-	cu.m	685.65	-	22.12	
10	Extra labour for:-							22.7	
	<ul><li>a) coping and caps, etc.</li><li>b) cornice &amp; string course</li></ul>	100 Cft. 100 Rft.	9694.10 9694.10	-	cu.m Rm.	3423.95 317.95	- -		
11	Dressing stones:-							22.2	
	<ul> <li>a) hammer dressed</li> <li>b) rough tooled dressed</li> <li>c) chisel dressed</li> <li>d) fine dressed</li> </ul>	100 Sft. 100 Sft. 100 Sft. 100 Sft.	3669.60 6948.50 8416.30 17571.85		sq.m sq.m sq.m sq.m	394.85 747.65 905.60 1890.75			<ul> <li>i) This rate of dressing shall be paid only when the supply of undressed stone is made.</li> <li>ii) In case of masonry, dressing is already included and this rate shall not be added thereto.</li> <li>iii) Only dressed surface of stone</li> </ul>
12	Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft.	7226.15	12364.65	sq.m	777.55	1330.45	22.13	shall be measured.
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	306.45	334.20	cu.m	10823.80	11803.95		
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	175.95	206.65	cu.m	6214.55	7298.90		

### 9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, BI-ANNUAL PERIO	O (1st FE	BRUARY, 20	013 TO 31st	JULY, 20	013) DIST	RICT RAWA	LPINDI	
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100Sft.	4811.65	10509.75	sq.m	517.75	1130.85	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	3701.30	7907.55	sq.m	398.25	850.85	23.2	ditto
3	Covering mud roof with coal tar, and fine sand.	100Sft.	202.90	1106.90	sq.m	21.85	119.10	23.1 to 23.2	ditto
4	Filling spaces in between:-	P. Berthi	nance (	Larparei	MARKET A				
	<ul> <li>a) Wooden battens over beams, filled with deodar wood pieces (spacers).</li> <li>b) RCC battens, filled with CC block 1:3:6.</li> <li>c) Spaces filled with bricks.</li> </ul>	100Sft. roof area -ditto- -ditto-	387.20 710.15 198.10	2225.35 1034.25 687.90	sq.m	41.65 76.40 21.30	239.45 111.30 74.00		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100Sft.	1184.05	6242.55	sq.m	127.40	671.70	23.1	ditto
6	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm) earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ½" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.  Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	)13) DIST	RICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Labout	Composite	CIII	Labout	Composite		
	<ul><li>a) cement concrete in haunches 1:6:12.</li><li>b) cement concrete in haunches 1:3:6.</li></ul>	100Sft. ditto	5290.55 5290.55	15714.00 16818.75	sq.m ditto	569.25 569.25	1690.85 1809.70		
7	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ½" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.
	and gobri) soffit of arches cement plastered. The rate also includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
		10077	/ ×	)\			4 4 4 0 4 7		
	<ul><li>a) cement concrete in haunches 1:6:12.</li><li>b) cement concrete in haunches 1:3:6.</li></ul>	100Sft. ditto	4300.55 4300.55	15327.55 15552.80	sq.m ditto	462.75 462.75	1649.25 1673.50		
8	Extra for vaulted jack arch roofing.	100Sft.	1077.10		sq.m	115.90	-		ditto
9	Jack arch roofing of shingle and cement concrete 1:3:6, 4½" (113 mm) thick at crown, with ½" (13 mm) cement	100Sft.	5907.00	12857.75	sq.m	635.60	1383.50	23.3	ditto
	plaster including cost of supplying, erecting and dismantling centring.	1	200		14 July 1			to 23.5	
10	Earth filling over roof including watering, ramming with 1" (25 mm) mud plaster finished, with gobri leeping:	F	nance (	Departi	reson t			23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 3" (75 mm) thick earth filling and 1" (25 mm) mud plaster	100Sft.	503.50	821.00	sq.m	54.20	88.35	23.3	& sub- sequent floors, respectively.
	b) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster	100Sft.	659.45	1042.95	sq.m	70.95	112.20		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	73.90	88.25	sq.m	7.95	9.50	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or 1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)	100Sft.	390.70	2135.35	sq.m	42.05	229.75	23.1	
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub-sequent floors, respectively,
	a) 20 BWG	100Sft.	774.4	14471.75	sq.m	83.35	1557.15		on items 13 to 18.
	b) 22 BWG c) 24 BWG	100Sft. 100Sft.	774.4 774.4	12467.05 10074.7	sq.m sq.m	83.35 83.35	1341.45 1084.05		

	MRS, BI-ANNUAL PERIOD	PINDI							
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Labout	Composite	CIII	Labour	Composite		
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300 mm) outside width finished smooth with a floating coat of neat cement.	Rft.	54.90	73.85	Metre	180.05	242.25	23.10	
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	205.90	361.45	Each	Each	361.45	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4 <sup>1</sup> / <sub>2</sub> " (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	205.90	716.85	Each	205.90	716.85	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.		×						
	a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe	Per Rft. Per Rft.	44.05 44.05	151.65 175.00		144.50 144.50	497.40 574.00		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	44.05	123.90	sq.m	474.00	1333.15	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	11.75	75.65	Sq.m	126.45	814.00		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-	OTTO:		Whateres and the	an ann offi				Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	<ul><li>a) 4" dia (100 mm) cast iron down pipe.</li><li>b) 3" (75 mm) cast iron down pipe.</li></ul>	Per Rft. Per Rft.	38.70 38.70	195.65 172.35		126.95 126.95	641.75 565.30		& sub- sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	165.15	458.05	Each	165.15	458.05		
22	Shoes, bends or offsets for cast iron rain water down pipe, including fixing and painting.	Each	58.10	293.00	Each	58.10	293.00		
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	183.50	302.00	Each	183.50	302.00	23.10	
24	Laying ½" (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100Sft.	4158.00	18321.85	sq.m	447.40	1971.45	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	<ul><li>a) 22 BWG sheets roofing</li><li>b) 24 BWG sheets roofing</li></ul>	100Sft. 100Sft.	2451.25 2451.25	15076.30 13500.85	sq.m sq.m	263.75 263.75	1622.20 1452.70	23.60	

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 20	013 TO 31st	JULY, 20	13) DIST	RICT RAWAL	.PINDI	
Sr.	Description		Rate (British Sy	rstem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and ridges, etc).	100Sft.	1650.00	5394.00	sq.m	177.55	580.40	23.8	
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100Sft.	189.75		sq.m	20.40	-	23.6	
28	Fixing asbestos cement sheet ridges and valleys ¼" (6 mm) thick.	Per Rft.	19.85	68.00	Metre	65.10	223.05	23.8	
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-	,	/ ×					23.6	
	a) 6" (150 mm) lap and 18" (450 mm)	Per Rft.	55.05	384.70	Per Metre	180.55	1261.80		
	overall, of 22 gauge G.I sheet ridging. b) 9" (225 mm) lap and 24" (600 mm) overall, of 24 gauge G.I sheet ridging.	Per Rft.	69.70	376.95	Per Metre	228.60	1236.40		
	c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging.	Per Rft.	69.70	444.35	Per Metre	228.60	1457.45		
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	34.85	154.90	Per Metre	114.30	508.05	23.11	
31	Making masonry ventilators in cement, sand mortar 1:4	Each	774.40	1290.60	Each	774.40	1290.60		
32	Fixing water spouts or parnalas.	Each	232.30		Each	232.30	-	23.10	
33	Making drip course 2"x½" (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	9.75	10.90	Metre	32.00	35.75		
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	28.00	339.40	sq.m	301.30	3651.95		
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:-								

	MRS, BI-ANNUAL PERIO	) (1st FE	BRUARY, 20	013 TO 31st	JULY, 20	013) DIST	RICT RAWAI	PINDI	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) Thermopore sheet ½ " (13 mm) thick	100Sft.	1824.90	6935.90	aa m	196.35	746.30		
	ii) Thermopore sheet <sup>3</sup> / <sub>4</sub> " (20 mm) thick	100Sft.	1824.90	7061.90	sq.m sq.m	196.35	759.85		
	iii) Thermopore sheet 1" (25 mm) thick	100Sft.	1828.25	7191.25	-	196.70	773.80		
	in) Thermopore sheet 1 (23 min) thick	100511.	1626.23	/191.23	sq.m	190.70	773.80		
36	Providing and fixing AC rain water down pipe 4" (100 mm) dia, with shoe, T-bend, clamp, etc.	Rft.	11.60	230.00	Metre	38.05	754.40		
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:-								Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.
	i) for slabs upto 6" (150 mm) thick	Rft.	13.45	15.15	Metre	44.10	49.70		concrete.
	ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick.	Rft.	22.65	25.65	Metre	74.30	84.15		
	101 slabs exceeding 0 to 12 (150 to 500 min) tinek.	Kit.	22.03	23.03	Wietre	74.50	04.13		
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-	.46			d sis				Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times
	i) upto 1.0' (300 mm) height of girder or beam.	Each	56.10	61.65	Each	56.10	61.65		for reinforced cement concrete.
	ii) for every 6" (150 mm) additional height or part thereof.	Each	26.95	29.60	Each	26.95	29.60		
39	Hoisting RS. Beams and wooden beams and placing in position.	Each	213.85	<b>S</b>	Each	213.85	-		
40	Hoisting and placing in position sahl ballies, over roof.	Each	33.20	Deviorte	Each	33.20	-		
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.								
	a) 5' to 6' (1.50 to 1.83 m) long	Each	30.55	_	Each	30.55	_		
	b) 6' to 7' (1.83 to 2.13 m) long	Each	42.75	_	Each	42.75	_		
	c) 7' to 8' (2.13 to 2.44 m) long	Each	53.45	-	Each	53.45	-		
	d) 8' to 9' (2.44 to 2.74 m) long	Each	71.30	-	Each	71.30	-		
	e) above 9' (2.74 m) length	Each	85.55	-	Each	85.55	-		
42	Hoisting and placing in position R.C. trough:								Applicable only to roof trough (inverted tees & trough) for height of
	a) upto 10' (3 m) in length	Each	85.55	_	Each	85.55	_		1st storey only.
	b) 10' to 11' (3 to 3.36 m) in length	ditto	106.90	-	ditto	106.90	-		
	c) 11' to 12' (3.36 to 3.66 m) in length	ditto	142.55	-	ditto	142.55	-		
	d) 12' to 13' (3.66 to 3.96 m) in length	ditto	164.50	-	ditto	164.50	-		
	e) 13' to 14' (3.96 to 4.26 m) in length	ditto	178.20	-	ditto	178.20	-		
	f) 14' to 15' (4.26 to 4.57 m) in length	ditto	194.40	-	ditto	194.40	-		
	g) 15' to 16' (4.57 to 4.88 m) in length	ditto	213.85	-	ditto	213.85	-		
	h) 16' to 17' (4.88 to 5.19 m) in length	ditto	237.60	-	ditto	237.60	-		
	i) 17' to 18' (5.19 to 5.49 m) in length	ditto	305.50	-	ditto	305.50	-		
	j) 18' to 19' (5.49 to 5.80 m) in length	ditto	329.00	-	ditto	329.00	-		

	MRS, BI-ANNUAL PERIO	LPINDI							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	k) 19' to 20' (5.80 to 6.10 m) in length	ditto	356.40	-	ditto	356.40	-		
43	Hoisting and placing in position R.C. inverted battens:-								
	i) upto 10' (3.05 m) span	Each	65.65	-	Each	65.65	-		
	ii) from 10' to 12' (3.05 to 3.66 m) span	ditto	145.95	-	ditto	145.95	-		
	iii) from 12' to 13' (3.66 to 3.96 m) span	ditto	175.10	-	ditto	175.10	-		
	iv) from 13' to 14' (3.96 to 4.26 m) span	ditto	218.90	-	ditto	218.90	-		
	v) from 14' to 15' (4.26 to 4.57 m) span	ditto	238.80	-	ditto	238.80	-		
	vi) from 15' to 16' (4.57 to 4.88 m) span	ditto	262.70	-	ditto	262.70	-		
	vii) from 16' to 18' (4.88 to 5.49 m) span	ditto	328.35	-	ditto	328.35	-		
	viii) from 18' to 20' (5.49 to 6.10 m) span	ditto	525.35	-	ditto	525.35	-		
44	Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	Each	309.75	541.70	Each	309.75	541.70		

Fimance Department

### 10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproduct

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description		Rate (British Sy	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	2052.60	3309.50	sq.m	220.85	356.10				
2	Earth flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	697.95	1027.95	sq.m	75.10	110.60	24.1			
3	Providing, laying, watering and ramming brick ballast 1½" to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	1564.20	3574.20	cum.	552.50	1262.40				
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	1270.50	1758.20	sq.m	136.70	189.20	24.2			
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	680.05	3671.65	sq.m	73.15	395.05	24.12			
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by ½ "(13 mm) thick mud plaster.	100 Sft.	1223.75	5675.15	sq.m	131.70	610.65	24.12			
7	Grouting 4½"(113 mm) dry brick work with cement mortal ratio 1: 5	100 Sft.	665.30	1095.65	sq.m	71.60	117.90				
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	1190.65	4905.65	sq.m	128.10	527.85	24.4			
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar 1:6.	100 Sft.	1,520.65	6,951.60	sq.m	163.60	748.00	24.4			
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of ¾" (20 mm) thick cement mortar 1:6.	100 Sft.	1,488.30	3,560.65	sq.m	160.15	383.15	ditto			
11	Brick ties (9"x4½"x1½")(225 mm x 113 mm x 40 mm) laid flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.	100 Sft.	1,656.60	5,111.75	sq.m	178.25	550.00	24.4			
12	Cement tiles (8"x8"x¾")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement	100 Sft.	994.40	5,233.10	sq.m	107.00	563.10	24.7			

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIN									
Sr.	Description		Rate (British Sy	rstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	mortar 1:2.								
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm) (b) 9"x9"x¾" (225 x 225 x 20 mm) (c) 6"x6"x¾"(150 x 150 x 20 mm)	100 Sft. ditto ditto	994.40 994.40 994.40	3,691.85 4,737.70 6,617.85	sq.m ditto ditto	107.00 107.00 107.00	397.25 509.80 712.10		
14	Coloured cement tiles (8"x8"x¾")(200 x 200 x 20 mm) of approved dark shade laid flat in 1:2 cement mortar, over ¾" (20 mm) bedding mortar of 1:2.	100 Sft.	994.40	5,261.90	sq.m	107.00	566.20	24.7	
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-		/ ×	5	\			24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick (b) 1½"(30 mm) thick (c) 1½"(40 mm) thick (d) 1¾"(45 mm) thick (e) 2"(50 mm) thick (f) 2½"(56 mm) thick (g) 2½"(62 mm) thick (h)2¾"(70 mm) thick (i) 3"(75 mm) thick	100 Sft. ditto	1,135.85 1,135.85 1,405.15 1,405.15 1,674.40 1,723.25 1,943.70 1,943.70	2,226.45 2,468.10 2,979.00 3,232.35 3,800.10 4,075.00 4,472.25 4,789.55 5,070.25	sq.m ditto ditto ditto ditto ditto ditto ditto ditto	122.20 122.20 151.20 151.20 180.15 185.40 209.15 209.15 209.15	239.55 265.55 320.55 347.80 408.90 438.45 481.20 515.35 545.55		
16	Providing and laying conglomerate flooring (two coat work) with top layer of ½"(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone chips passing 3/16"(6 mm) sieve, over bottom layer of cement concrete 1:3:6, including surface finishing and dividing in panels:-		T. Q.N.CE	Depart				24.10	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1½"(40 mm) thick (b) 1¾"(45 mm) thick (c) 2"(50 mm) thick	100 Sft. ditto ditto	1,678.40 1,678.40 2,115.95	3,197.80 3,357.80 4,043.40	sq.m ditto ditto	180.60 180.60 227.70	344.10 361.30 435.05		
17	Add extra in cement concrete floor topping, if finished with pigment and polishing.	100 Sft.	387.20	861.90	sq.m	41.65	92.75		
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	293.05	-	sq.m	31.55	-		On items 19-25 & 29-34
19	Flag stone flooring in lime mortar 1:2, over 3/4"(20 mm) bedding mortar, in platforms and floors, etc.							24.5	
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	3,324.55 3,324.55	4,944.85 5,213.35	sq.m ditto	357.70 357.70	532.05 560.95		

	MRS, BI-ANNUAL PERIO	PINDI							
Sr.	Description		Rate (British Sy	vstem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
20	Asphalt flooring , including preparation of proper base remelting, setting out, and finishing complete:-							24.10	
	(a) 1"(25 mm) thick topping (b) ½"(13 mm) thick topping (c) ½"(6 mm) thick topping	100 Sft. ditto ditto	1,313.40 1,035.55 771.15	15,936.35 8,497.30 4,599.60	sq.m ditto ditto	141.30 111.45 83.00	1714.75 914.30 494.90		
21	1 <sup>3</sup> / <sub>8</sub> "(35 mm) thick mosaic flooring, consisting of 3/8"(10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete :-								If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	4,512.30 4,512.30	6,839.05 7,116.00	sq.m ditto	485.50 485.50	735.90 765.70		
22	1½"(40 mm) thick mosaic flooring, consisting of ½ "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing:	-3007/6							If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	4,512.30 4,512.30	7,003.70 7,600.20	sq.m ditto	485.50 485.50	753.60 817.80		
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over ¾"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	2,776.75	6,624.10	sq.m	298.80	712.75	24.8	
24	Laying floor of approved white glazed tile ¼" (6 mm) thick in white cement 1:2 over ¾" (20mm) thick cement mortar 1:2, complete.	100 Sft.	3,550.80	8,901.00	sq.m	382.05	957.75	24.7	
25	Laying floor of approved coloured glazed tiles ½ "(6 mm) thick, laid in white cement and pigment on a bed of ¾" (20 mm) thick cement mortar 1:2.	100 Sft.	3,550.80	9,448.20	sq.m	382.05	1016.65	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	892.30	1,021.85	sq.m	96.00	109.95		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	952.50	1,084.75	sq.m	102.50	116.70		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description		Rate (British Sy	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	152.35	197.30	sq.m	16.40	21.25	24.6		
29	Shisham wood boarding or strip flooring 3/4" (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½ "x2"(40 x 50 mm),size placed at 12"(300 mm) centre to centre, including two coats of bitumen laid hot on the base.	100 Sft.	3,080.00	33,696.30	sq.m	331.40	3625.70	24.13		
30	Deodar wood boarding or strip flooring 3/4" (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½"x2"(40 x 50 mm) size, placed at 12"(300 mm) centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	3,484.80	42,232.15	sq.m	374.95	4544.20	ditto		
31	Teak wood boarding or strip flooring ½" (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens 1½" x2"(40 x 50 mm) size, placed at 12"(300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	3,058.00	45,014.15	sq.m	329.05	4843.50	ditto		
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	3,240.60	37,684.20	sq.m	348.70	4054.80	24.13		
33	Teak wood block 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	3,058.00	74,630.45	sq.m	329.05	8030.25	ditto		
34	Laying wooden paving of hard wood on edge in coal tar and asphalt:-  (a) Shisham wood (b) Kikar wood	100 Sft. Per Inch thickness ditto	1,874.40 1,874.40	23,060.55 13,313.55	sq.m per cm thickness ditto	201.70 201.70	2481.30 1432.55	ditto		
35	Tile skirting laid in 1:2 cement mortar, over ¾"(20 mm) thick cement mortar, 1:2 including cement washing and filling joints complete:-									
	(a) cement tiles (b) mosaic tiles	100 Sft. ditto	1,627.80 2,692.80	6,240.05 8,789.30	sq.m ditto	175.15 289.75	671.45 945.75			
36	Providing grey cement skirting or dado 3/8"(10 mm) thick including rounding of corner and straight ening of top edge and finishing to smooth surface afterplastering:									
	(a) 1:2 cement, sand mortar	100 Sft.	2,068.90	2,619.50	sq.m	222.60	281.85			

Sr.	Description		Rate (British S	vstem)	Ra	te (Metric Sy	Metric System)		Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(b) 1:3 cement, sand mortar	ditto	2,068.90	2,456.40	ditto	222.60	264.30		
	(c) Extra if skirting or dado is finished with pigment of any colour.	ditto	122.10	383.20	ditto	13.15	41.25		
37	White glazed tile (6"x6"x <sup>1</sup> / <sub>4</sub> ") (6 mm) thick dado jointed in white cement and laid over 1:2 cement sand mortar 3/4" (20mm) thick, including finishing.	100 Sft.	4,375.80	9,726.00	sq.m	470.85	1046.50	24.7	
38	Coloured glazed tile dado (6"x6"1/4") (6mm) thick in pigment over 1:2 cement, sand mortar 3/4"(20mm) thick, including finishing.	100 Sft.	4,375.80	10,256.65	sq.m	470.85	1103.60	ditto	
39	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:		/ 3	5					
	(a) using grey cement: i) 3/8"(10 mm) thick ii) ½"(13 mm) thick	100 Sft. ditto	5,332.80 5,332.80	6,548.85 7,295.90	sq.m ditto	573.80 573.80	704.65 785.05		
	(b) using white cement :	18	1.6	- 10	J.F				
	'i) 3/8"(10 mm) thick ii) ½"(13 mm) thick	100 Sft. ditto	5,332.80 5,332.80	7,378.75 7,670.05	sq.m ditto	573.80 573.80	793.95 825.30		
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	14.05	75.40	sq.m	151.20	811.30	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	4.10	Metre	-	13.45		Labour for fixing already included in items No. 15, 16, 21and 22 of this Chapter.
42	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels								
	a) Size 1½" x <sup>3</sup> / <sub>8</sub> " (40 x 10 mm) b) Size 1½" x ¼" (40 x 6 mm)	Per Rft.	-	6.60 4.60	Metre ditto	-	21.65 15.10		

## 11. SURFACE RENDERING

- 1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD	PINDI							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7	
	a) ½" (13 mm) thick b) 1" (25 mm) thick	100 Sft. ditto	307.00 428.85	387.10 589.05	sq.m ditto	33.05 46.15	41.65 63.40		
2	Mud plaster on floor or roof (excluding Gobri leeping):-							ditto	Add extra 13%, 32% and 51% above
	a) ½" (13 mm) thick	100 Sft.	276.65	356.75	sq.m	29.75	38.40		the labour rates only or 6%, 15% & 23% on the composite rates for 2nd, 3rd, 4th and subsequenct floors,
	b) 1" (25 mm) thick	ditto	276.65	436.85	ditto	29.75	47.00		respectively.
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.	188						25.1 to 25.6	
	a) ½" (6 mm) thick	100 Sft.	894.95	1056.05	sq.m	96.30	113.65		
	b) ½" (13 mm) thick	ditto	894.95	1217.00	ditto	96.30	130.95		
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-	Tir	iance (	Deplanti				ditto	
	a) ½" (6 mm) thick b) ½" (13 mm) thick	100 Sft. ditto	894.95 894.95	1293.00 1534.45	sq.m ditto	96.30 96.30	139.15 165.10		
	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand and shingle) upto 20' (6.00 m) height.	100 Sft.	2221.80	4661.70	sq.m	239.05	501.60	ditto	
	Providing and laying machine sprayed plaster ½" (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto	
	i) ratio 1:1 ii) ratio 1:1½ iii) ratio 1:2	100 Sft. ditto ditto	796.65 796.65 796.65	2249.35 2148.50 2090.40	sq.m ditto ditto	85.70 85.70 85.70	242.05 231.20 224.95		
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1 to	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick	100 Sft. ditto ditto	894.95 894.95 1127.30	1445.55 1609.10 2228.45	sq.m ditto ditto	96.30 96.30 121.30	155.55 173.15 239.80	25.6	

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description		Rate (British System)			Rate (Metric System)			Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
0	9 - 1 - 12 - 20/(600 ) 1 - 1								
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto	
	a) 3/8" (10 mm) thick	100 Sft.	894.95	1282.45	sq.m	96.30	138.00		
	b) ½" (13 mm) thick c) ¾" (20 mm) thick	ditto ditto	894.95 1127.30	1411.65 1902.30	ditto ditto	96.30 121.30	151.90 204.70		
	c) 3/4" (20 mm) thick	unto	1127.30	1902.30	unto	121.50	204.70		
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto	
	a) 3/8" (10 mm) thick	100 Sft.	894.95	1238.25	sq.m	96.30	133.25		
	b) ½" (13 mm) thick	ditto	894.95	1332.00	ditto	96.30	143.30		
	c) 3/4" (20 mm) thick	ditto	1127.30	1808.45	ditto	121.30	194.60		
10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C.		/					ditto	i) This item shall be applicable to
	roof slabs only, upto 20' height.		14	) \					buildings meant for human habitation only, such as buildings
		1							like residences, offices,
	a) 1:2	100 Sft.	1029.60	1689.80	sq.m	110.80	181.80		educational institutions and
	b) 1:3	ditto	1029.60	1526.20	ditto	110.80	164.20		hospitals, etc. It shall not be
	c) 1:4	ditto	1029.60	1481.95	ditto	110.80	159.45		admissible on godowns; bins; agriculture, poultry and animal
		100	T	67	180				sheds; cycle stands; garrages; etc.
		Y.	1. 270						ii) The thickness of the plaster will
		450		5 2 18					not be more than 3/8" (10 mm) thick.
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-			0				25.1 to 25.6	tnick.
	a) 3/8" (10 mm) thick	100 Sft.	894.95	1200.05	sa m	96.30	129.15		
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick	ditto	894.95	1265.40	sq.m ditto	96.30	136.15		
	c) 3/4" (20 mm) thick	ditto	1127.30	1737.50	ditto	121.30	186.95		
12	Cement plaster 1:6 upto 20' (6.00 mm)							ditto	
12	height:-							unto	
	a) 3/8" (10 mm) thick	100 Sft.	894.95	1145.50	sq.m	96.30	123.25		
	b) ½" (13 mm) thick	ditto	894.95	1227.20	ditto	96.30	132.05		
	c) <sup>3</sup> / <sub>4</sub> " (20 mm) thick	ditto	1127.30	1628.40	ditto	121.30	175.20		
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	541.75	759.90	sq.m	58.30	81.75	25.4 to 25.6	
14	Lime pointing flush upto 20' (6.00 m) height including	100 Sft.	662.65	778.85	sq.m	71.30	83.80	25.8	
	raking joints, in lime, sand mortar 1:2.								
15	Lime pointing struck joints on walls, upto 20' (6.00 m)	100 Sft.	1029.60	1145.80	sq.m	110.80	123.30	ditto	
	height, including raking joints in lime sand mortar 1:2.								
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2	100 Sft.	894.95	1307.10	sq.m	96.30	140.65		
	b) ratio 1:3	ditto	894.95	1211.10	ditto	96.30	130.30		

	MRS, BI-ANNUAL PERIOD	.PINDI							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Labout	Composite	Cint	Labout	Composite		
17	Cement pointing 1:2 flush on floor.	100 Sft.	662.65	1074.75	sq.m	71.30	115.65	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-								
	a) ratio 1:2 b) ratio 1:3	100 Sft. ditto	1029.60 1029.60	1441.75 1345.70	sq.m ditto	110.80 110.80	155.15 144.80		
19	Pointing flush on stone work, upto 20' (6.00 m) height.							25.8	
	a) in lime mortar 1:2 (lime, sand) b) in cement mortar 1:3 c) on stone work raised:- i) in lime mortar 1:2	100 Sft. ditto	834.25 834.25 1568.15	990.20 1150.35 1724.10	sq.m ditto	89.75 89.75 168.75	106.55 123.80 185.50		
	ii) in cement mortar 1:3	ditto	1568.15	1884.30	sq.m ditto	168.75	202.75		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	401.30		sq.m	43.20	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	200.65		sq.m	21.60	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	92.95	99.50	sq.m	10.00	10.70	25.11	
23	Distempering:-	***		\$ 1.0°				ditto	
	a) new surface:- i) one coat ii) two coats iii) three coats	100 Sft. ditto ditto	102.35 151.25 200.20	181.35 254.25 327.20	ditto	11.00 16.30 21.55	19.50 27.35 35.20		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	93.35 151.25	148.35 206.25	sq.m ditto	10.05 16.30	15.95 22.20		
24	Colour washing:-							25.10	
	a) new surface:- i) one coat ii) two coats	100 Sft. ditto	71.60 107.40	100.10 149.05	sq.m ditto	7.70 11.55	10.75 16.05		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	71.60 107.40	89.25 136.30	sq.m ditto	7.70 11.55	9.60 14.65		
25	White washing:-							25.9	
	a) new surface:- i) one coat ii) two coats	100 Sft. ditto	71.60 107.40	95.05 142.45		7.70 11.55	10.25 15.35		

	MRS, BI-ANNUAL PERIOD	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAW							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) three coats	ditto	139.20	185.90	ditto	15.00	20.00		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	71.60 107.40	89.15 136.60	sq.m ditto	7.70 11.55	9.60 14.70		
26	Gobri leeping:-							25.7	
	a) on walls b) over roofs	100 Sft. ditto	104.85 88.70	109.00 92.85	sq.m ditto	11.30 9.55	11.75 10.00		
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	134.65		sq.m	14.50	-	25.8	Payable with fresh masonry, when the face of the work is not to be
28	Extra for lime, mud or cement plaster and pointing from 20' (6.00 m) and above for each additional 10' (3.00 m) height or part thereof.	100 Sft.	162.30		sq.m	17.45	-		plastered/pointed.
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	396.00	898.50	sq.m	42.60	96.70		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	396.00	426.90	sq.m	42.60	45.95		
31	Extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft.	125.40	222.90	sq.m	13.50	24.00		
32	Providing grooved cement sand plaster 1:3 over existing plastered and roughened surface upto 20' (6.00 m) height.	Fir	ianice (	Departi					
	i) 3/8" (10 mm) thick ii) ½" (13 mm) thick	100 Sft. ditto	1029.60 1029.60	1417.10 1546.25	sq.m ditto	110.80 110.80	152.50 166.40		
33	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	5.95	34.25	Metre	19.50	112.35		
34	Petty repairs to fire place.								
	i) Single ii) Double	Each Each	162.60 325.25	208.15 416.30	Each Each	162.60 325.25	208.15 416.30		Area about 100 Sft (10.76 ag m)
35	Petty repair to main rooms.	Each	334.35	455.85	Each	334.35	455.85		Area above 100 Sft (10.76 sq.m)
36	Petty repair to small rooms.	Each	167.20	227.90	Each	167.20	227.90		Area upto 100 Sft (10.76 sq.m)
37	Petty repair to verandah.	Each	334.35	431.50	Each	334.35	431.50		The height will be taken from the
38	Extra labour for white washing, colour washing, priming coat and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	100 Sft. Per coat	11.95	-	sq.m Per coat	1.30	-		floor, roof or ground uderneath as the case may be on the side towards which the work is to be done.

## 12. WOOD WORK

- 1 No extra rate is to be paid for sawing as the rates are inclusive of these
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 2	013 TO 31st	JULY, 20	13) DISTR	ICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	549.50 616.00	3750.65 2713.60	cu.m ditto	19408.35 21757.10	132472.95 95844.35		
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.	. /	× .		\ :			26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	340.80 340.80	3575.30 2500.10		12037.05 12037.05	126279.60 88303.55		
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-		Sir.					26.1 to 26.3 & 26.7	
	i) 2" (50 mm) thick ii) 1¾" (45 mm) thick iii) 1½" (40 mm) thick	Per Sft. ditto ditto	97.40 97.40 97.40	1254.10		1048.00 1048.00 1048.00	14458.20 13494.10 12553.15		
4	First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cn²) including brass fittings, sash bars, etc. complete:-  a) teak wood framing 1¾" (45 mm) thick with wire gauze fixed in position:-							26.8 to 26.10	<ul> <li>i) This also includes the cost of wood required for extra thickness of chowkat.</li> <li>ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and Rs.50.60 per sq.m.</li> </ul>
	i) without springs or spring hinges.	Per Sft.	17.10	548.00	sq.m	184.00	5896.50		KS.50.00 per sq.m.
	ii) with springs or spring hinges.	ditto	17.10	551.70	ditto	184.00	5936.30		
	b) teak wood framing 1½" (40 mm) thick, with wire gauze fixed in position: i) without springs or spring hinges. ii) with springs or spring hinges.	Per Sft.	17.10 17.10	505.35 509.45	sq.m ditto	184.00 184.00	5437.55 5481.70		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square	Per Sft.	30.80			331.40	1785.10		

	MRS, BI-ANNUAL PERIOD	RICT RAWAL	.PINDI						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	inch, (5x5 meshes per cm²) fixed to chowkat with ¾" (20 mm) teak wood strips and screws.  d) G.I. wire gauze 22 SWG, 12x12 meshes per square	Per Sft.	28.90	525.40	sq.m	310.95	5653.30		
	inch (5x5 meshes per cm²) fixed with ½" (13 mm) strip on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc.								
5	P/F expanded metal ½" to ¾" (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	36.70	267.00	sq.m	394.90	2872.90		
6	Providing and fixing expanded metal ½" (13 mm) to ¾" 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	38.50	396.40	sq.m	414.25	4265.25		
7	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-							26.1 to 26.3 & 26.7	7
	a) 2" thick (50 mm) b) 134" thick (45 mm) c) 11/2" thick (40 mm)	Per Sft. ditto ditto	93.40 93.40 93.40	1057.00 988.20 940.45	ditto	1005.00 1005.00 1005.00	11373.30 10633.15 10119.25		
8	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	a) 2½" (56 mm) thick, with ½" (30 mm) battens and 1" (25 mm) planks.	Per Sft.	104.05	681.85	sq.m	1119.60	7336.70		
	b) 134" (40 mm) thick with 1" (25 mm) battens and 34" (20 mm) planks.	ditto	94.75	588.75	ditto	1019.50	6334.95		
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	122.75	388.75	sq.m	1320.80	4182.95		
10	Deodar battened ledged and braced doors and windows 2½" (56 mm) thick (1½" (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	112.05	665.85	sq.m	1205.65	7164.55	26.1, 26.2 26.4 to 26.6	
11	a) Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the Engineer incharge:-							26.1, 26.2 & 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60 Sq.m) for G.I. facing on one side

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 20	013 TO 31st	JULY, 20	13) DISTR	ICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	<ul> <li>i) G.I. sheet facing on one side.</li> <li>ii) G.I. sheet facing on both sides.</li> <li>b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings,</li> </ul>	Per Sft. ditto	48.55 53.85	544.30 569.95	sq.m ditto	522.40 579.45	5856.65 6132.65		and Rs.9.40 per Sft. (Rs.101.20 per Sq.m) for G.I. sheet facing on both sides.
	hinges and locking arrangements, as directed by the Engineer-in-charge:-  i) G.I. sheet facing on one side.	Per Sft.	48.55	222.75	sq.m	522.40	2396.80		unio
12	ii) G.I. sheet facing on both sides.  First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm²) including iron fittings etc. complete:-	ditto	53.85	248.40	ditto	579.45	2672.80	26.8 to 26.10	i) This also includes the cost of wood required for extra thickness of chowkat.
	a) deodar wood framing 1¾" (45 mm) thick with wire gauze fixed in position:-	- 1			}				ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	<ul><li>i) without springs or spring hinges.</li><li>ii) with springs or spring hinges.</li></ul>	Per Sft. ditto	51.35 51.35	454.25 458.35	sq.m ditto	552.55 552.55	4887.75 4931.85		
	<ul> <li>b) deodar wood framing 1½" (40 mm) thick, with wire gauze fixed in position:-</li> <li>i) without springs or spring hinges</li> <li>ii) with springs or spring hinges</li> </ul>	Per Sft.	51.35 51.35	422.25 424.75	sq.m ditto	552.55 552.55	4543.40 4570.30		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm²) fixed to chowkat, with ¾" ('20 mm) thick deodar wood strip and screws.	Per Sft.	38.50	148.60	sq.m	414.25	1598.95		
	d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to chowkat, with ½" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm).	Per Sft.	57.75	388.95	sq.m	621.40	4185.10		
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	83.95	448.85	sq.m	903.30	4829.65	26.1 26.2	
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-								
	a) M.S. angle iron 1½"x ½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	22.40	144.55	sq.m	241.00	1555.35		
	b) M.S. tee iron 1½"x 1½"x ½" (40x40x6 mm) welded	Per Sft.	22.40	109.85	sq.m	241.00	1182.00		

	MRS, BI-ANNUAL PERIOD	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RA								
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	with M.S. flat 2"x ¼" (50 mm x 6 mm)									
15	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 1 <sup>1</sup> / <sub>4</sub> " x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:									
	<ul><li>a) single rebate</li><li>b) double rebate</li></ul>	Per Sft. ditto	29.70 35.70	119.20 137.80		319.55 384.15	1282.60 1482.75			
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	2.80	30.55	sq.m door area	30.15	328.70	26.2		
17	Providing and fixing brass spring hinges to wire gauzed doors.	Each	58.75	208.75	Each	58.75	208.75			
18	Providing and fixing sliding bolt to doors:-	1	1. 55		30					
	i) iron sliding bolt, 10" (250 mm) long ii) iron sliding bolt, 12" (300 mm) long iii) brass sliding bolt, 10" (250 mm) long iv) brass sliding bolt, 12" (300 mm) long	Each ditto ditto ditto	57.75 57.75 57.75 57.75	117.75 159.75 159.75 315.75	Each ditto ditto ditto	57.75 57.75 57.75 57.75	117.75 159.75 159.75 315.75			
19	Extra for brass fittings to doors and windows, except for hinges, which shall be of iron:-									
	i) deodar wood panelled or panelled and     glazed or fully glazed.	Per Sft.	1.70	11.60	sq.m	18.30	124.80			
	ii) deodar wood wire gauzed shutters.	ditto	1.70	9.25	ditto	18.30	99.55			
20	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	179.65	386.05	Each	179.65	386.05			
21	Providing and fixing, approved quality mortice lock.	Each	251.90	441.50	Each	251.90	441.50			
22	Providing and fixing, expended metal ½" to ¾" (13 mm to 20 mm) mesh 16 gauge.									
	<ul> <li>a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc.</li> <li>b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm)</li> </ul>	Per Sft.	36.70 38.50	228.45 325.45	sq.m ditto	394.90 414.25	2458.10 3501.85			
23	a) Providing and fixing deodar wood almirah 9" to 12"								For hollow frame shutter with	

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 20	013 TO 31st	JULY, 20	)13) DISTR	RICT RAWAL	.PINDI	
Sr.	Description	]	Rate (British Sy	stem)	F	ate (Metric S	ystem)	Spec.	Remarks
No.	_	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. complete.	Per Sft.	128.90	1514.45	sq.m	1387.20	16295.45		commercial ply on one side, the composite rate shall be reduced by Rs.54.00 per Sft; or Rs.580.00 per Sqm and for hollow frame shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per Sft. or Rs.245.00 per Sq. metre.
	<ul> <li>Providing and fixing deodar wood almirah 9" to 12"         (225 mm to 300 mm)depth with shelves, shutters,         brass fittings, etc., without boxing and back,         complete.     </li> </ul>	Per Sft.	95.25	517.15	sq.m	1025.00	5564.45		
24	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ½" (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1½:3) shelves 1½" (40 mm) thick including 3 coats of painting.	Per Sft.	73.75	352.50	Sq.m	793.60	3793.00		
25	Providing and fixing wooden box type wardrobe 22" (550 mm) deep including 34" (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods, etc. including three coats of enamel paint:-				253 35				If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood bracing and deodar wood lipping is used, the composite rate will be
	i) Partal wood boxing and deodar wood shelves and leaves, etc.	Per Sft.	142.15	673.85	sq.m	1529.60	7250.80		reduced by Rs.13.00 per Sft. or Rs.140.00 per Sq. metre.
	ii) Deodar wood boxing, and deodar wood shelves and leaves, etc.	ditto	141.25	873.50	ditto	1519.75	9398.80		
26	Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete.	Per Sft.	54.40	549.60	Sq.m	585.15	5913.85		
27	Providing and fixing chowkat for doors, windows and C. windows, including holdfast, etc.								
	a) Teak wood b) Deodar wood c) Shisham wood	Per Sft. ditto ditto	26.75 17.10 19.90	457.70 349.40 160.65	ditto	287.75 184.10 214.10	4924.60 3759.30 1728.40		

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 20	013 TO 31st	JULY, 20	13) DISTR	ICT RAWAL	PINDI	
Sr.	Description	]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	a) 1" (25 mm) thick b) 34" (20 mm) thick c) ½" (13 mm) thick	Sft. ditto ditto	31.95 31.95 31.95	294.45 228.75 163.35	sq.m ditto ditto	343.70 343.70 343.70	3168.35 2461.55 1757.70		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	i) 1" (25 mm) thick ii) 1½" (40 mm) thick iii) 2" (50 mm) thick	Sft. ditto ditto	31.95 31.95 31.95	294.45 425.55 556.65	sq.m ditto ditto	343.70 343.70 343.70	3168.35 4579.00 5989.60		
30	Making and fixing cleats for doors and windows, including hinges and screws.	Each	36.95	114.10	Each	36.95	114.10	26.1 and 26.2	
	b) Making and fixing cleats with brass hooks for roof ventilators.	Each	47.00	85.80	Each	47.00	85.80		
	c) Providing and fixing door stops of 1½" (40 mm) dia rubber block.	Each	5.60	56.10	Each	5.60	56.10		
31	d) Providing and fixing G.I. hook with clamps for doors.  Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.	Each	1.80	9.50	Each	1.80	9.50	ditto	
	a) Shisham wood b) Teak wood	Per Rft. ditto	136.40 102.45	276.15 626.55	Metre ditto	447.40 336.00	905.75 2055.05		
32	Deodar wood dado or picture rail 3"x1½" (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete.	Per Rft.	51.20	220.30	Metre	168.00	722.50	26.1 26.2	
33	Sawing wood by hand:-								
	<ul><li>a) Soft wood (deodar, kail or chir).</li><li>b) Hard wood (shisham, kikar, teak or sahl).</li></ul>	100Sft. ditto	587.40 783.20		sq.m ditto	63.20 84.25	- -		
34	Sawing wood by machine:								
	a) Soft wood b) Hard wood	100Sft. ditto	353.14 530.55	-	sq.m ditto	38.00 57.10	- -		

	MRS, BI-ANNUAL PERIOD	ICT RAWAL	PINDI						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.	_	Unit	Labour	Composite	Unit	Labour	Composite	No.	
35	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	43.70	357.80	sq.m	470.15	3849.95	26.1	
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	48.95	119.05	sq.m	526.70	1281.00	ditto	
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	184.80	7132.80	Each	184.80	7132.80	ditto	
38	Dismantling and refixing eave boards.	Per Rft.	13.20		Metre	43.30			
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1½" (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	195.80	2232.15	Metre	642.25	7321.50	26.1	
40	Providing and fixing partition, including frame work:-	/	_						
	a) Sheets on one side of framework:-	1 1			144.				
	i) Hard board ii) Ply wood ¼" (6 mm) thick iii) Masonite	100Sft. ditto ditto	917.80 917.80 917.80	11911.05 13171.05 13675.05	sq.m ditto ditto	98.75 98.75 98.75	1281.65 1417.20 1471.45		
	b) Sheets on both sides of frame work:-	-60			35-				
	i) Hard board ii) Ply wood ¼" (6 mm) thick iii) Masonite	100Sft. ditto ditto	1101.40 1101.40 1101.40	13382.65 23637.20 16910.65	sq.m ditto ditto	118.50 118.50 118.50	1439.95 2543.35 1819.60		
41	Providing and fixing ceiling, including frame work:-								
	i) Hard board ii) Chip board iii) Ply wood <sup>1</sup> / <sub>4</sub> " (6 mm) thick iv) Masonite	100Sft. ditto ditto ditto	1828.75 1828.75 1828.75 1828.75	8799.65 10959.65 11079.65 10719.65	sq.m ditto ditto ditto	196.75 196.75 196.75 196.75	946.85 1179.25 1192.15 1153.45		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-								In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	i) ¾" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	2035.00 2035.00	8900.00 8979.35	sq.m ditto	218.95 218.95	957.65 966.20		
	b) Partal wood frame panelling:								
	i) ¾" (20 mm) thick	100Sft.	2035.00	5967.50	sq.m	218.95	642.10		

	MRS, BI-ANNUAL PERIOD	ICT RAWAL	PINDI						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 1" (25 mm) thick	ditto	2035.00	6093.50	ditto	218.95	655.65		
43	a) Fixing door, including chowkats.	Each	290.40	-	Each	290.40	-		
44	<ul> <li>b) Fixing windows, including chowkats.</li> <li>a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty.</li> </ul>	ditto Per Sft.	145.20 21.00	48.50	ditto sq.m	145.20 225.75	521.80	26.12	
	b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty.	Per Sft.	27.25	80.10	sq.m	293.00	862.05		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	39.85	88.50	sq.m	428.55	952.35	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	15.00	16.10	sq.m	161.30	173.30		
	b) Cutting to required size and fixing glass panes with wooden fillets and putty.	Per Sft.	22.05	40.25	sq.m	237.00	433.10		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-	1 30							
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	33.80	97.85	sq.m	363.40	1052.95		
	b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sfi (2.25 sq.m).	Per Sft.	33.80	98.05	sq.m	363.40	1055.00		
48	Providing and fixing 1½" (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with:-	E in	tanar (	Departi	er ere t				
	i) M.S. angle iron 1½"x1½"x¼", welded i) (40 mmx 40 mmx 6mm) with M.S. flat 2"x¼" (50 mm x 6 mm)	Per Sft.	132.45	650.60	sq.m	1424.90	7000.55		
	ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm)	Per Sft.	132.45	604.60	sq.m	1424.90	6505.50		
49	Providing and fixing 1½" (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1¼" (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1½"x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complete in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	i) M.S. angle iron 1½"x1½"x½", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¼" (50 mm x 6 mm)	Per Sft.	93.40	534.95	sq.m	1004.75	5756.25		
	ii) M.S. tee iron 1½"x1½"x¼", welded	Per Sft.	93.40	500.25	sq.m	1004.75	5382.90		

	MRS, BI-ANNUAL PERIOD	(1st FE	BRUARY, 20	013 TO 31st	JULY, 20	13) DISTR	ICT RAWAL	PINDI	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(40 mmx40 mmx 6mm) with M.S. flat 1/2"x1/4" (13 mm x 6 mm)			•			•		
50	Providing and fixing 1½" (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	47.95	334.70	sq.m	515.95	3601.15		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	91.20	350.20	sq.m	981.55	3768.00		
52	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	20.20	33.70	Metre	66.25	110.50		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	8.40	125.60	Metre	27.60	411.95		
54	Providing and fixing M.S. flat ½"x1/8" (13mm x 3mm) grill including ¾" x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	47.80	180.65	sq.m	514.25	1943.95		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cnf) fixed to steel window, complete with flat iron patti ½"x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	15.90	56.00	sq.m	170.95	602.40		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 P.SQM
56	Providing and fixing wooden moulding stopper 2½"x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	<ul><li>a) Teak wood moulding</li><li>b) Deodar wood moulding</li></ul>	Per Sft. ditto	21.05 21.05	102.95 62.25	sq.m ditto	226.35 226.35	1107.60 669.95		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between braces with 1:3:6 PCC fixing ply of approved quality								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))

	MRS, BI-ANNUAL PERIO	ICT RAWAL	PINDI						
Sr.	Description		Rate (British Sy	stem)		Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	including holdfasts complete in all respects.								
	a) Teak wood ply	Per Sft.	45.20	305.65	sa m	486.20	3288.90		
Ī	b) With commercial ply	ditto	45.20		sq.m ditto	486.20	3212.50		
58	Providing and fixing ornamental wooden architrave 3" x (1½" tapered to ¼") all along the door frame complete in all respect.								
	a) Teak wood architrave	Per Sft.	9.00	63.65	sq.m	96.80	685.00		
	b) Deodar wood architrave	ditto	9.00	36.10	ditto	96.80	388.35		
59	Providing and fixing Vin board cabinet 3/4" thick with drawers 3"deep in 'Kitchen including termite proofing and polishing with synthetic enamel as specified, with handles hinges, screws etc., complete in all respects.	,	*						
	i) 1-1/2' deep, without back	Per Sft	101.25	496.00	sq.m	1089.65	5337.00		
	ii) 1-1/2' deep,with back	Per Sft	101.25	544.00	The Control of	1089.65	5853.45		
Í	iii) 2' deep,without back iv) 2' deep,with back	Per Sft Per Sft	101.25 101.25	542.80 590.80		1089.65 1089.65	5840.55 6357.05		

Finance Department

# 13. PAINTING AND VARNISHING

1 The rates include charges for scaffolding and other arrangements.

2 The rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIO	DD (1st FEE	BRUARY, 20	13 TO 31st	JULY, 20	13) DISTR	RICT RAWA	LPINDI	
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	a) Cleaning painted wood work with oil and water.	100 Sft.	97.70	130.25	sq.m	10.50	14.00		
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	65.10	111.90	sq.m	7.00	12.05	27.7	
2	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	195.35		sq.m	21.00	-	27.3	
3	Scraping, brushing and removing old paint from metal surface.	100 Sft.	781.45		sq.m	84.10	-	27.9	
4	Painting old surfaces:-  a) Painting corrugated surfaces, patent roofing, etc. with oil paint.	W E						27.1 27.3 & 27.9	
	i) first coat ii) each subsequent coat	100 Sft. ditto	255.55 193.60	427.15 281.20	sq.m ditto	27.50 20.85	45.95 30.25		
	b) Painting sashes, fanlights, glazed or gauzed doors and windows:-	SF 15 m	ance I	deports					
	i) first coat ii) each subsequent coat	100 Sft. ditto	154.90 131.65	246.10 206.05	sq.m ditto	16.65 14.15	26.50 22.15		
	c) Painting doors and windows, any type:								
	i) first coat ii) each subsequent coat	100 Sft. ditto	255.55 193.60	430.75 326.80	sq.m ditto	27.50 20.85	46.35 35.15		
	d) Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:- i) first coat	100 Sft.	154.90	246.10	sq.m	16.65	26.50		
	ii) each subsequent coat e) Painting fillets, framings, skirtings, pipes, gutters and similar linear work not exceeding 6" in girth:-	ditto	131.65	206.05	ditto	14.15	22.15		
	i) first coat ii) each subsequent coat	100 Lft. ditto	131.65 92.95	222.85 167.35	Metre ditto	4.30 3.05	7.30 5.50		
	f) Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:-								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.		Description	F	Rate (British Sys	stem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks		
No.			Unit	Labour	Composite	Unit	Labour	Composite	No.			
		i) first coat ii) each subsequent coat	100 Nos. ditto	397.65 358.30	569.25 449.50		397.65 358.30	569.25 449.50				
	g)	Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:-										
		<ul><li>i) first coat</li><li>ii) each subsequent coat</li></ul>	100 Nos ditto	908.90 524.25	1420.10 779.85	100 Nos ditto	908.90 524.25	1420.10 779.85				
5	Pain	ting new surface:-							27.1 27.2 &			
	a)	Preparing surface and painting corrugated surface, patent roofing, etc.		×	7				27.9			
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Sft. ditto	395.20 138.25	618.40 351.85	sq.m ditto	42.50 14.90	66.55 37.85				
	b)	Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):-	E E		160							
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Sft. ditto	165.90 111.50	320.10 232.70	sq.m ditto	17.85 12.00	34.45 25.05				
	c)	Preparing surface and painting of doors and windows any type (including edges):-	(Figur	amor A	hegasutti	n.en.t						
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Sft. ditto	395.20 138.25	614.80 351.85		42.50 14.90	66.15 37.85				
	d)	Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:-										
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Sft. ditto	251.35 111.50	384.55 232.70	sq.m ditto	27.05 12.00	41.40 25.05				
	e)	Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-										
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Lft. ditto	197.45 74.35	298.25 173.95		6.50 2.45	9.80 5.70				
	f)	Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-										
		<ul><li>i) priming coat.</li><li>ii) each subsequent coat of paint.</li></ul>	100 Nos. ditto	580.8 286.95	1113 710.55		580.8 286.95	1113 710.55				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	F	Rate (British Sys	tem)	Rat	te (Metric Sy	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	g) Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-											
	i) priming coat. ii) each subsequent coat of paint.	100 Nos. ditto	1666.50 499.40	2537.70 1259.00	100 Nos. ditto	1666.50 499.40	2537.70 1259.00					
	h) Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	26.95	42.05	sq.m	2.90	4.50					
6	Applying Khanki Mixture hot to barrage gates:-							27.10				
	i) first coat ii) second coat	100 Sft. ditto	193.60 153.20	462.35 323.95	sq.m ditto	20.85 16.50	49.75 34.85					
7	French polishing complete:-	* =			14			27.6				
	a) on new work b) on old work	100 Sft. ditto	2010.15 1048.45	2072.55 1082.05	sq.m ditto	216.30 112.80	223.00 116.45					
8	Varnishing wood work, including cleaning and preparing surface.	60			3							
	a) first coat b) second coat c) third coat	100 Sft. ditto ditto	154.90 58.10 58.10	279.10 152.20 132.65	sq.m ditto ditto	16.65 6.25 6.25	30.05 16.40 14.25					
9	Bitumen coating to plastered or cement concrete surface:-											
	i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m) ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m) iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m)	100 Sft. ditto ditto	162.80 156.30 128.95	1197.70 681.10 653.75	sq.m ditto ditto	17.50 16.80 13.85	128.85 73.30 70.35					
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	7.75	8.35	Per No.	7.75	8.35	27.1				
11	Writing letters or figures at any surface with reflective paint of approved quality and colour per letter per inch height.	Per Letter per inch height	7.75	8.10	Per Letter per 25 mm height	7.75	8.10	27.1				
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	9.15	10.00	ditto	9.15	10.00	ditto				
13	Coaltar painting:							27.8 to				
	a) first coat, laid hot b) second coat, laid hot	100 Sft. ditto	132.40 80.25	949.00 594.35		14.25 8.65	102.10 63.95	27.11				

	MRS, BI-ANNUAL PERIOD	LPINDI							
Sr.	Description	F	Rate (British Sys	stem)	Rat	e (Metric Sy	rstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Solignum painting:-							27.8	
	a) one coat, applied hot     b) two coats, applied hot	100 Sft. ditto	148.10 224.40	174.50 266.65	sq.m ditto	15.95 24.15	18.80 28.70		
15	Creosote painting:-							ditto	
	a) one coat, applied hot b) two coats, applied hot	100 Sft. ditto	177.75 269.30	292.95 462.50	sq.m ditto	19.10 29.00	31.50 49.75		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	498.95	514.55	sq.m	53.70	55.35	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	195.35	203.10	sq.m	21.00	21.85	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	38.70	45.30	Each	38.70	45.30	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	77.45	90.15	per Metre	254.00	295.75	ditto	
20	Painting sounding rods and other gauges, reading to 10th of a foot (metre)	Per Lft.	38.70	42.70	per Metre	127.00	140.00	27.1	
21	Painting leveling staves.	Per Lft.	122.30	128.70	per Metre	401.20	422.05		
22	a) Painting and lettering mile/Km stones, on both sides:	11/2/11	ance q	hemouti.	nen.t			ditto	
	i) one coat ii) two coats	Each ditto	82.95 145.20	128.55 218.40	Each ditto	82.95 145.20	128.55 218.40		
	b) Painting and lettering Furlong/½ Km stones, on both sides:-							27.1	
	i) one coat ii) two coats	Each ditto	11.05 19.35	16.45 28.80	Each ditto	11.05 19.35	16.45 28.80		
	c) Painting and lettering Sign posts:-								
	i) one coat ii) two coats	Each ditto	92.95 153.35	122.55 203.75	Each ditto	92.95 153.35	122.55 203.75		
23	Removing paint or varnish from wall.	100 Sft.	390.70	-	sq.m	42.05	-	27.12	
24	Scraping from hydraulic gates:-							27.1	
	a) Khanki paint b) Aluminium paint	100 Sft. ditto	781.45 781.45	-	sq.m ditto	84.10 84.10	- -		

	MRS, BI-ANNUAL PERIOD	(1st FEE	BRUARY, 20	13 TO 31st	JULY, 20	13) DISTF	RICT RAWA	LPINDI	
Sr.	Description	F	Rate (British Sy	stem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
25	Painting letters with shade.	per letter per inch height	12.40	12.40	per letter per 25 mm height	12.40	12.40	27.1	
26	Scraping rust from old rail or girders.	100 Sft.	586.10	625.10	sq.m	63.05	67.25	27.9 27.10	
27	Chiselling old paint from brick work.	100 Sft.	781.45	811.45	sq.m	84.10	87.30	27.12	
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	651.20	665.40	sq.m	70.05	71.60		
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	195.35	242.15	sq.m	21.00	26.05	27.9	
30	Cleaning and painting punkha poles, including fixing hooks.	Each	125.40	133.20	Each	125.40	133.20	27.3	
31	Preparing surface and painting with emulsion paint:-	& E			14			27.12	
	<ul><li>a) first coat</li><li>b) 2nd and each subsequent coat</li></ul>	100 Sft. ditto	201.15 154.20	383.05 296.80	sq.m ditto	21.65 16.60	41.20 31.95		
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.	-		38	3			27.12	
	a) new surface:	W is m	ance G	hepronte	nent				
	i) 1st coat ii) 2nd and subsequent coat	100 Sft. ditto	201.15 154.20	280.35 223.60		21.65 16.60	30.15 24.05		
	b) old surface:								
	<ul><li>i) 1st coat</li><li>ii) 2nd and subsequent coat</li></ul>	100 Sft. ditto	201.15 154.20	234.55 186.90		21.65 16.60	25.25 20.10		
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:								
	a) new surface:								
	i) 1st coat ii) 2nd coat	%sft %sft	660.00 363.65	1117.00 564.65		71.00 39.15	120.20 60.75		
	b) old surface:	%sft	363.65	564.65	sq.m	39.15	60.75		
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	1.15	2.05	Metre	3.80	6.65		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads comlpete in all respect.	Per Rft.	1.25	9.30	Metre	4.15	30.55	AASHTO M248-91 (2000)	Rates shall be reduced by <b>Rs.0.50</b> P.Rft or <b>Rs.1.65</b> P.Mtr. If glass beads are not used.			
35	Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	48.10	80.50	Job	48.10	80.50	(2000)	in glass seads are not used.			
36	Repainting of iron poles with cross arms, with bitumen or other approved paint.	Per Job	112.20	228.60	Job	112.20	228.60					
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:		×									
	i) upto 40 mm (1½") dia	Per Rft.	1.05	3.35	Metre	3.35	7.05					
	ii) above 40 mm (1½") to 50 mm (2") dia	ditto	2.05	4.00	ditto	6.75	13.05					
	iii) above 50 mm (2") to 100 mm (4") dia	ditto	3.40	6.30	ditto	11.20	20.70					
38	Repainting main switches and branch distribution boards of all sizes and types, with approved paint (complete set).	Per Job	22.20	68.80	Job	22.20	68.80					
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	62.50	departi	sq.m	6.75	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.			

## 14. LINING OF CANALS

- Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The rates also include curing for specified period wherever necessary.
- Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description		Rate (British Sy	estem)	I	Rate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3					
	a) in bed b) on slope	100Sft. ditto	433.30 591.35	-	sq.m ditto	46.60 63.65	- -						
2	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	1056.00	1523.10	sq.m	113.65	163.90	ditto					
3	Cement plaster ½" (13 mm) thick ratio 1:10.				)			ditto					
	a) in bed b) on slope	100Sft. ditto	769.10 958.30	999.90 1189.10	sq.m ditto	82.75 103.10	107.60 127.95						
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	16	7/-	مرحكومت وتنح	7 J			ditto					
	a) in bed b) on slope	100Sft. ditto	769.10 958.30	1177.85 1367.10	sq.m ditto	82.75 103.10	126.75 147.10						
5	Cement plaster 1½" (40 mm) thick ratio 1:6.	4	imance	(I)epan		1.t		ditto					
	a) in bed b) on slope	100Sft. ditto	958.30 1190.65	1935.50 2167.80	sq.m ditto	103.10 128.10	208.25 233.25						
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are				
	a) in bed b) on slope	100Cft. ditto	4501.20 5157.90	14574.95 15231.65	cu.m ditto	1589.80 1821.75	5147.85 5379.80		payable separately.				
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are				
	a) in bed	100Cft.	4501.20	15936.60	cu.m	1589.80	5628.80		payable separately.				
	b) on slope	ditto	5157.90	16593.30	ditto	1821.75	5860.75						
8	Brick lining 9"x4½"x3" (225x113x75 mm) in 1:6 cement, sand mortar:-							28.2	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are				
	a) in bed b) on slope	100Cft. ditto	4501.20 5157.90	17832.95 18489.65	cu.m ditto	1589.80 1821.75	6298.60 6530.55		payable separately.				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description		Rate (British Sy	stem)	]	Rate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	Brick lining 9"x4½"x3" (225x113x75 mm), in 1:3 cement, sand mortar:-							ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to				
	a) in bed b) on slope	100Cft. ditto	4501.20 5157.90	19194.60 19851.30	cu.m ditto	1589.80 1821.75	6779.55 7011.50		5 above are payable separately.				
	Cement concrete lining, using washed screened and graded stone aggregate:-							20.1, 28.1 & 28.3					
	a) in bed:-												
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	3904.55 3904.55 3904.55		cu.m ditto ditto	1379.10 1379.10 1379.10	5944.35 5111.65 4510.10						
	b) on slope:-					1377110	1010110						
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	4511.10 4511.10 4511.10	17436.55 15078.90 13375.75	cu.m ditto ditto	1593.30 1593.30 1593.30	6158.60 5325.85 4724.30						
		16	1 / 1	مرحكز مرت يؤنو	100								

Finance Department

## 15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIO	WALPIND	<u> </u>						
Sr.	Description	I	Rate (British Sys	stem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Cutting Ransome and Larson piles.	Per cut	134.65	ı	Per cut	134.65	-	29.1- 29.3	
2	Cutting universal piles.	Per cut	199.25	-	Per cut	199.25	-	ditto	
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	2486.90		sq.m	267.60	-	ditto	1) The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre).  2) The rates are for the tackle gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government.  3) T-piles and adjustable junction piles will be counted as two piles.
4	Driving steel piles,more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	2386.55	Depar	sq.m	256.80	-	ditto	ditto
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	1784.65	-	sq.m	192.05	-	ditto	ditto
6	Dolleying piles.	Each	158.40	-	Each	158.40	-	ditto	Upto 5' (1.5 m) dolleying.
7	Drilling holes in piles by hand.	Each	18.50	-	Each	18.50	-	ditto	
8	Raising and lowering machine.	Per Ft.	2437.60	-	Metre	7995.35	-	ditto	
9	Turning Machine, 90°	Per Job	3696.00	-	Per Job	3696.00	-	29.1 to 29.3	
10	Turning Machine, 135°.	Per Job	4498.55	-	Per Job	4498.55	-	ditto	
11	Turning Machine, 180°.	Per Job	6082.55	-	Per Job	6082.55	-	29.1 to 29.3	
12	Travelling machine (light).	Per Chain	7204.55	-	30 M.	7204.55	-	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit Labour Composite Unit Labour Composite		No.									
13	Loading and unloading piles.	Ton	144.55	-	Tonne	142.30	-	ditto	To be done by hand carts or ramps, including cost of ropes.				
14	Dismantling piling machine.	Each	16398.80	-	Each	16398.80	-	ditto					
15	Erecting piling machine.	Each	18921.70	-	Each	18921.70	-	ditto					
16	Carriage of piling machine under different conditions.	per chain	3006.95	-	30 M	3006.95	-	ditto					



Finance Department

#### 16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
  - the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
  - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
  - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the poin of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	Ra	te (British Syste	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	742.35		cu.m	262.15							
2	Weaving matresses.	100Cft.	1406.60		cu.m	496.75							
3	Supplying and filling jute bags 1.25 (0.035 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	22.00	36.80	Per Baq	22.00	36.8		The rate does not include supply of sand or earth for filling bags, which will be paid extra.				
	b) Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water.	ditto	34.20	49.00	Per Baq	34.20	49		-ditto-				
4.00	a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	52.60	104.15	Per Bag	52.60	104.15		The rate does not include supply of sand or earth for filling bags, which will be paid extra.				
	b) Supply and filling new jute bags 4 to 5 cft (0.11 to	ditto	75.15	126.70	ditto	75.15	126.70		-ditto-				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	Ra	te (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
				-			-					
	0.14 cu.m) capacity, with sand or earth, sewing and laying in position, under water.											
5	Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled with sand or earth:-											
	a) 1st chain (30 m)	100 Nos	195.35		% Nos	195.35						
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	70.35		Per 30 m Per 100 Nos/	70.35						
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	27.35		ditto	27.35						
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-		9.55									
	a) 1st chain (Ist 30 metre)	100 Nos	781.45	3	% Nos	781.45						
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	273.50	eparti	Per 30 m per %Nos	273.50						
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	105.50		ditto	105.50						
7	Rolling matresses to river edge and floating, after unroling:-											
	a) area of matress upto 2,000 Sft. (186 sq.m)	100Sft.	439.55		sq.m	47.30						
	b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m)	100Sft.	732.60		sq.m	78.85						
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	854.70		ditto	91.95						
8	Sewing empty cement bags in sheets.	100 Nos	683.75	717.35	% Nos	683.75	717.35					
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	952.40	1050.40	cu.m	336.40	371		Measured in the shape of compact round bundles and of size specified for the work, before filling at site.			

	MRS, BI-ANNUAL PERIO	D (1st FEB	RUARY, 201	3 TO 31st J	ULY, 201	13) DISTR	ICT RAWA	LPINDI	
Sr.	Description	Ra	nte (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
10	Launching the above and placing in position.	100Cft.	468.85		cu.m	165.60			
11	Supply within 5 chains (150 m):-								
	a) Boulders 9" (225 mm) and above	100Cft.	1414.40		cu.m	499.50			
	b) Over size shingle 3" to 9"(75 to 225 mm)	ditto	945.55		ditto	333.90			
	c) Mixed graded shingle	ditto	1121.35		ditto	396.00			
12	Supplying Munj or Patha Trungers 6" (150 mm) mesh to hold 3 Cft. (0.085 cu.m)	Each	61.05	103.70	Each	61.05	103.7		
13	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to make crate):-	/	*						
	a) 6" (150 mm) mesh				W.				
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	813.10 871.20 871.20	1071.85 1711.20 2188.30	sq.m ditto ditto	87.50 93.75 93.75	115.35 184.15 235.45		
	b) 4" (100 mm) mesh		3,0		3				
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	1045.45 1161.60 1161.60	1462.15 2419.10 3133.10	sq.m ditto ditto	112.50 125.00 125.00	157.35 260.30 337.10		
14	Providing and laying shingle on top of bund, including handling of materials within three chains.	100Cft.	488.40	818.40	cu.m	172.50	289.05		
15	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)								
	a) stone or boulder b) shingle or spawl c) brick bats	100Cft. ditto ditto	854.70 854.70 659.35	1316.70 1184.70 1649.35	cu.m ditto ditto	301.85 301.85 232.90	465 418.4 582.55		The rate includes supply of brick bats to site of work.
16	Supply and dumping by boat, including loading into boal within three chains (90 m) lead, and hire charges of boat and boatman.								The rate includes supply of brick bats to site of work.
	a) stone or boulder	100Cft.	1504.80	1966.80	cu.m	531.50	694.65		
	b) shingle or spawl	ditto	1504.80	1834.80	ditto	531.50	648.05		
	c) brick bats	ditto	1309.45	2299.45	ditto	462.50	812.15		
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	1136.50	2126.50	cu.m	401.40	751.1		The rate includes supply of brick bats to site of work.
18	Supplying and filling bricks in crates and hand packing	100Cft.	1380.70	13800.70	cu.m	487.65	4874.4		The rate includes supply of bricks

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description	Ra	te (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(excluding cost of crates).								to site of work.
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-								
	i) stone or boulder ii) shingle or spawl	100Cft. ditto	1576.10 1576.10	2038.10 1906.10	cu.m ditto	556.65 556.65	719.85 673.25		
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	171.90	-	cu.m	60.70	-		
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	859.60		cu.m	303.60	-		
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	488.40	988.40	sq.m	52.55	106.35	30.1	
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	1221.00	1271.00	sq.m	131.40	136.75	ditto	
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1½ (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	2735.70	3819.40	sq.m	294.35	410.95		The cost of placing earth between rolls shall be paid separately, as earthwork.
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	914.75	1000.35	sq.m	98.45	107.65		Measurement to be made of the area of elevation on one face only.
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	1578.70	1680.80	sq.m	169.85	180.85		
	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	990.00	1719.00	cu.m	349.65	607.15		
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	2979.90	3627.90	cu.m	1052.50	1281.35		
29	Providing and laying stone pitching, for top layer only:-								
	a) one slope b) on level	100Cft. ditto	2475.00 2230.80	3123.00 2878.80	cu.m ditto	874.15 787.90	1103.05 1016.8		
30	Providing and laying stone or spawl filling:-								

	MRS, BI-ANNUAL PERIO	LPINDI							
Sr.	Description	Ra	ate (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
							•		
	a) on level	100Cft.	656.70	956.70	cu.m	231.95	337.90		
	b) on slope	ditto	811.55	1111.55	ditto	286.65	392.6		
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.								
	i) top layer on slope	100Cft.	3291.55	5697.25	cu.m	1162.60	2012.25		
	ii) top layer on level	ditto	3047.35	5453.05	ditto	1076.35	1926.00		
	iii) stone pitching/filling on slope or on level	ditto	1759.70	4246.40	ditto	621.50	1499.85		
	(other than top layer).		/ X						
32	Grouting stone pitching or apron, etc. in:-	/	7	}					
32		40000				12012	40045		
	a) cement, sand mortar 1:3	100Sft.	1116.45	4629.70	sq.m	120.15	498.15		
	b) cement, sand mortar 1:8	ditto	950.40	2708.10	ditto	102.25	291.40		
33	Sand grouting in stone apron, with high	100Sft.	378.85	918.85	sq.m	40.75	98.85		
	pressure hose.	1886			1000				
		6377	150	~ 30 / C	400				
34	Grouting stone filling or pitching, with bajri.	100Cft.	610.50	1186.50	cu.m	215.65	419.05		
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	2312.10	3	cu.m	816.65	-		
26	Callastina and stacking handson from mullah hada an lasar	100Cft.	701 45	KRIPARTEN	97 (\$100) E	276.00			
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cit.	781.45	-	cu.m	276.00	-		
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	656.70	1232.70	cu.m	231.95	435.40		
38	Grouting jharies between blocks with bajri.	100Cft.	656.70	1040.70	cu.m	231.95	367.60		
39	Breaking stone into spawls and stacking	100Cft.	586.10	-	cu.m	207.00	-		
	Canal and Roads								
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-								
	a) upto 2.0' (600 mm) F.S. depth	Each	20.40	-	Each	20.40	-		
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	22.95	-	ditto	22.95	-		
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	30.60	-	ditto	30.60	-		
	d) above 4.0' (1200 mm) F.S. depth	ditto	76.55	-	ditto	76.55	-		

	MRS, BI-ANNUAL PERIO	LPINDI							
Sr.	Description	Ra	nte (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				,			,		
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-								
	a) i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead.	100 Nos	976.80	1008.30	% Nos	976.80	1008.30		
	ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	464.65	-	100 Nos	464.65	-		
	iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	561.80		100 Nos	561.80	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	48.85	78.50	Per 30 Metre of one row	48.85	78.50		
	v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	687.70	856.90	ditto	687.70	856.90		
	b) i) Cutting and supplying unsharpened pegs 4.0' (1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	86.85	122.70	100 Nos	86.85	122.70		
	ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	464.65	-	100 Nos	464.65	-		
	iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	686.50	-	100 Nos	686.50	-		
	<ul><li>iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).</li></ul>	Per Chain of one row	48.85		Per 30 M of one row	48.85			
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1722.60		ditto	1722.60			
	c) i) Cutting and supplying unsharpened pegs 5.0' (1.5	100 Nos	108.60	153.45	100 Nos	108.60	153.45		

	MRS, BI-ANNUAL PER	LPINDI							
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).								
	ii) Sharpening one end of 5' $(1.5 \text{ m})$ long pegs, 3" to 6" $(75 \text{ to } 150 \text{ mm})$ dia.	100 Nos	491.55	-	100 Nos	491.55	-		
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	792.00	-	100 Nos	792.00	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	48.85	78.50	Per 30 M of one row	48.85	78.50		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per chain of one row	752.40	989.10	Per 30 M of one row	752.40	989.10		
•	1) i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	1953.60	2007.40	100 Nos	1953.60	2007.4		
	ii) Sharpening one end of 6' $(1.8 \text{ m})$ long pegs, 3" to 6" $(75 \text{ to } 150 \text{ mm})$ dia.	100 Nos	584.50	oparts	100 Nos	584.50	-		
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	950.40	-	100 Nos	950.40	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	48.85	78.50	Per Chain of one row	48.85	78.50		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1966.80	2254.25	ditto	1966.80	2254.25		
(	e) i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	1465.20	1576.80	100 Nos	1465.20	1576.80		

	MRS, BI-ANNUAL PERI	OD (1st FEB	RUARY, 201	3 TO 31st .	JULY, 201	3) DISTR	RICT RAWA	LPINDI	
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	743.40	-	100 Nos	743.40	-		
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3" to 6" (75 to 150 mm) dia driven 2' (600 mm) below the available bed or ground (average).	100 Nos	1049.15	-	100 Nos	1049.15	-		
	<ul><li>iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).</li></ul>	Per chain of one row	48.85	65.25	Per 30 M of one row	48.85	65.25		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per Chain of one row	2217.60	2555.80	Per 30 M of one row	2217.60	2555.80		
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-	# E	670						
	a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2½" to 5" (63 m to 125 mm) dia.	100 Nos	7200.00	19	100 Nos	7200.00	-		
	ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	650.50	eparts	100 Nos	650.50	-		
	iii) Driving Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long 21/2" to 5" (63 to 125 mm) dia, driven 2.5' (750 mm) below the available bed or ground (average).	100 Nos	1148.40	-	100 Nos	1148.40	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	73.25	119.75	Per 30 M of one Row	73.25	119.75		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	2712.60	3151.80	ditto	2712.60	3151.80		
	b) i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	10800.00	100 Nos	-	10800		
	ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	743.40	-	100 Nos	743.40	-		

	MRS, BI-ANNUAL PERIOD	ICT RAWA	LPINDI						
Sr.	Description	Ra	te (British Syst	em)	Rate	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				•			•		
	iii) Driving Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long 2½" to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average).	100 Nos	1247.15	-	100 Nos	1247.15	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	244.20	854.90	Per 30 M of one Row	244.20	854.90		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	3326.40	3884.40	ditto	3326.40	3884.40		
	c) i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos		11400.00	100 Nos	-	11400.00		
	ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	836.35		100 Nos	836.35	-		
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long 2½" to 5" dia, driven 3.5' (1.07 mm) below the available bed or ground (average).	100 Nos	1425.60		100 Nos	1425.60	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	244.20	854.90	Per 30 M of one row	244.20	854.90		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	3940.20	4582.80	ditto	3940.20	4582.80		
	d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	12600.00	100 Nos	-	12600.00		
	ii) Sharpening one end of 14'-1" to 16.0' (4.30 to 4.90 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	929.30	-	100 Nos	929.30	-		
	iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1584.00	-	100 Nos	1584.00	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one Row	244.20	854.90	Per 30 M of one Row	244.20	854.90		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile	ditto	4532.90	5276.90	ditto	4532.90	5276.90		

	MRS, BI-ANNUAL PERIO	DD (1st FEB	RUARY, 201	3 TO 31st .	JULY, 201	3) DISTR	ICT RAWA	LPINDI	
Sr.	Description	Ra	te (British Syste	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).								
	e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	13200.00	100 Nos	-	13200.00		
	ii) Sharpening one end of 16'-1" to 20' (4.9 to 6.10 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	1115.15	-	100 Nos	1115.15	-		
	iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1900.80		100 Nos	1900.80	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	244.20	854.90	Per 30 M of one row	244.20	854.90		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	5669.40	6616.20	ditto	5669.40	6616.20		
43	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	244.20	311.70	cu.m	86.25	110.10		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.
44	Filling brush wood only, thoroughly packed.	100Cft.	195.35	-	cu.m	69.00	-		Measured in compacted and packed shape before filling.
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	468.85	-	Per 30 M	468.85	-		
46	<ul><li>a) Gachi pitching 1' (300 mm) thick.</li><li>b) Gachi pitching done with silt clearance and berm dressing.</li></ul>	100Sft. 100Sft.	2539.70 2148.95	-	Sq.m Sq.m	273.25 231.25	-		

## 17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.			
	a) channels, discharge upto 50 cusecs.	Job	814.00	-	Job	814.00	-					
	b) channels, discharge from 51 to 100 cusecs.	Job	1074.50		Job	1074.50	-					
	c) channels, discharge from 101 to 200 cusecs.	Job	1628.00		Job	1628.00	-					
	d) channels, discharge from 201 to 350 cusecs.	Job	2197.80	-	Job	2197.80	-					
	e) channels, discharge over 350 cusecs.	Job	3256.00		Job	3256.00	-					
2	Dismantling outlets:-	835						18.1	These rates are for total dismantlement and removal			
	a) old types, such as K.G.O's orifices, etc.	Each	814.00		Each	814.00	-		of material. The rates do not			
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	1221.00	S 33	ditto	1221.00	-		include earth work for which rates are given in item 1, above.			
	c) A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm)	ditto	1628.00	Depart	ditto	1628.00	-		above.			
	d) A.P.M. or O.F., "H" above 3.0'. (900 mm)	ditto	2035.00	-	ditto	2035.00	-					
	e) Tail cluster bifurcation	ditto	1221.00	-	ditto	1221.00	-					
	f) Tail cluster trifurcation	ditto	1628.00	-	ditto	1628.00	-					
	g) Tail cluster quardification	ditto	2035.00	-	ditto	2035.00	-					
3	Making temporary A.P.M. bricks block and fixing at site.	Each	383.35	696.10	Each	383.35	696.10	21.1 & 21.2				
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	794.65	-	Job	794.65	-	18.1, 21.1 & 21.2				
5	Dismantling walls and fitting iron block of O.F. outlet	Each	794.65	-	Each	794.65	-	18.1, 21.1 & 21.2				
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
								17.2				
	a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth	Each ditto	1953.60 2637.35	-	Each ditto	1953.60 2637.35	-					
7	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	423.70	857.35	Each	423.70	857.35	18.1, 21.1 & 21.2				
8	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	825.00	1533.30	Each	825.00	1533.30	ditto				
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-								Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no O.F. iron block.			
	a) for channel depth of 5.0'. (1.5 m) b) for channel depth of 4.0'. (1.2 m) c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) e) for channel depth of less than 2.0'. (600 mm)	Each ditto ditto ditto ditto	929.30 696.95 557.55 464.65 371.70	1049.20 816.85 677.45 557.25 437.05	Each ditto ditto ditto ditto	929.30 696.95 557.55 464.65 371.70	816.85 677.45 557.25					
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	383.35	562.90	Each	383.35	562.90					
11	Laying iron pipes for outlets.	Per Lft.	18.60		Metre	61.00	-	21.1, 21.2 & 17.1 to 17.5				
12	Water allowance for constructing outlets or culverts, when canal water is not flowing.	Each	397.25 to 814.00	Depart	Each	397.25 to 814.00			At the discretion of the Engineer-in-charge depending upon the distance and source of supply.			
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	301.40	-	Each	301.40	-					
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2				
	a) portion under bank.     b) portion under road, beyond bank.	Rft. ditto	76.35 33.40	84.35 41.40	Metre ditto	250.45 109.55	276.7 135.8					
15	Removing pipe outlet, refilling earth and puddling.							17.1				
	a) portion under bank.     b) portion under road, beyond bank.	Rft. ditto	65.10 24.40	-	Metre ditto	213.65 80.10	-	to 17.5				
16	Changing pipe outlets by removing one pipe and replacing it at the same site with another pipe complete with earth and puddling.											
	portion under bank.     portion under road, beyond bank.	Rft. ditto	90.40 45.20	98.35 53.20	Metre ditto	296.50 148.25	322.75 174.5					

#### 18. ROAD & ROAD STRUCTURE

- 1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Sub-base & base construction								
1	Providing and laying sub-base course of brick on edge 4½" (113 mm) thick, including compaction to required camber and grade.	100Cft.	2635.75	14465.35	cu.m	930.95	5109.15	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	2150.70	3324.90	cu.m	759.65	1174.35	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.
3	a) Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and. aggregate.	Tim	S ma O		2004			ditto	
	<ul><li>i) Pit run or bed run gravel.</li><li>ii) Crushed stone aggregate.</li></ul>	100Cft. 100Cft.	2150.7 2150.7	2618.7 3050.7	cu.m cu.m	759.65 759.65	924.95 1077.5		
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
									It shall be payable from the nearest approved quarry.     The quantity of pit run or bed run gravel and crushed stone

	MRS, BI-ANNUAL PERIOD	) (1st FEBF	RUARY, 201	3 TO 31st JI	JLY, 201	3) DISTRI	CT RAWAL	.PINDI	
Sr.	Description	R	ate (British Sys	tem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	a) Providing and laying base course of crushed stone	100Cft.	2401.50	4766.70	cu.m	848.20	1683.60	501-1	aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft.
	aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and. aggregate.		*		Vuini	0.0120	1000.00	to 501-6	
	b) Subsequent carriage of crushed stone aggregate.	100Cft. of console- dated base	74;c		4				1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
		Time	ma O	epartn					2) It shall be payable from the nearest approved quarry.  3) The quantity of crushed stone aggregate for payment of carriage shal be taken as per actual loose volume burnot more than 122 Cft.
5	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	5.85	29.70	Metre	19.25	97.50	552-1 to 552-5	
	Bituminous Work & Resurfacing.								
6	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre.	100Sft.	97.70	1141.50	sq.m	10.50	122.85	601-1 to 601-6	
7	Providing and laying bituminous tack coat, using 10 lbs. of bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.)	100Sft.	97.70	596.30	sq.m	10.50	64.15	611-1 to 611-5	
8	<ul> <li>a) Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rollin</li> </ul>							612-1 to 612-6	

	Description	R	ate (British Sys	tem)	Ra	te (Metric S	vstem)	Spec.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.								
	1) 1st coat:-								
	i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre	100Sft.	94.05	2368.75	Sq.m	10.10	254.90		
	ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size ¾" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre.	100Sft.	94.05	2070.90	Sq.m	10.10	222.85		
	2) 2nd coat:-	7 28		-	100				
	i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size $\frac{1}{2}$ " (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre.	100Sft.	72.35	1482.35	Sq.m	7.80	159.50		
	ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre.	100Sft.	72.35	1088.00	Sq.m	7.80	117.05		
	3) 3rd coat:-								
	14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ½" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	49.50	838.05	sq.m	5.35	90.15		
b)	Subsequent carriage of crushed stone aggregate/bajri,	100Cft.			cu.m				1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or ras the case may be.
									It shal be payable from the nearest approved quarry.

Sr.	Description	Ra	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work.							612-1 to 612-6	
	i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m.	100Sft.	62.70	1304.75	sq.m	6.75	140.40		
	ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre.	100Sft.	62.70	1185.70	sq.m	6.75	127.60		
	b) Subsequent carriage of crushed stone aggregate/bajri.	100Cft.			cu.m				Same remarks as against item 8(b) above.
10	Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density.	per inch thickness per 100Sft.	mae D	epartu	per 25mm thickness per Sq.m			641-1 to 642-6	
	(i) 3% Bitumen	-do-	1056.75	3278.20	-do-	113.75	352.85		
	(ii) 3.5% Bitumen	-do-	1056.75	3584.10	-do-	113.75	385.80		
	(iii) 4% Bitumen	-do-	1056.75	3890.05	-do-	113.75	418.70		
	(iv) 4.5% Bitumen (v) 5% Bitumen	-do- -do-	1056.75 1056.75	4195.95 4501.70	-do- -do-	113.75 113.75	451.65 484.55		
	(vi) 5.5% Bitumen	-do-	1056.75	4807.80	-do-	113.75	517.50		
	(vii) 6% Bitumen	-do-	1056.75	5113.75	-do-	113.75	550.45		
11	Scarifying old road surface including removal of debris within 1 chain (30 m).	100Sft.	162.80	-	Sq.m	17.50	-		
	Incidental Construction								
12	Providing R.C.C. railing on bridges, as per standard drawing.	Per Rft.	92.10	959.10	Metre	302.20	3146.65	901-1 to 901-4	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of binding wire and removal of rust from the bars, etc.
	Providing and fixing G.I. pipe railing, as pe	Per Rft. of	74.95	677.20	Metre	245.85	2221.80	ditto	

	MRS, BI-ANNUAL PERI	OD (1st FEBF	RUARY, 2013	3 TO 31st J	JLY, 2013	3) DISTRI	CT RAWAL	PINDI	
Sr.	Description	R	ate (British Sys	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	standard drawing.	3 rows of Pipes							
14	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end	-	2400.00	Each set of one end	-	2400.00	911-1 to 911-6	
15	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch	-	18.00	cu.cm	-	1.10	ditto	
16	Providing and laying expansion joint of neoprine strip 4"x½" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	50.15	191.40	Metre	164.55	628.00	921-1 to 921-4	
17	Providing and fixing rain water outlet of A.C. pipe.	Each	25.10	253.20	Each	25.10	253.20	931-1 to 933-4	
18	Providing and erection at site of work:-	11 /		7				941-1 to 941-5	The rate is for complete item of work according to Standard design
	i) R.C.C. mile/Km. stone	Each	1774.20	3885.20	Each	1774.20	3885.20		including cement concrete
	ii) R.C.C. furlong/½ Km. stone	Each	84.70	301.70	Each	84.70	301.70		foundation block and painting
	iii) R.C.C. boundary pillar. iv) Sign post of M.S. plate 1/8" thick (3 mm)	Each	158.25	465.80	Each	158.25	465.80		letters etc.
	a) Mandatory.	Each	559.85	4371.50	Each	559.85	4371.50		
	b) Warning/Direction/Informatory.	Each	541.30	4093.30	Each	541.30	4093.30		
19	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	2021.60	13851.20	cu.m	714.00	4892.25		The nominal thickness of bricks (9" x 4-3/8"x 2-11/16") shall be taken for the purpose of measurement and payment.

# 19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- 1 Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, BI-ANNUAL PERI	OD (1st l	FEBRUARY	, 2013 TO 3°	1st JUL	r, 2013) C	DISTRICT R	AWALPIN	DI
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-								
	i) white ii) coloured	Each Each	293.70 293.70	1,985.90 2,165.90	Each Each	293.70 293.70	1,985.90 2,165.90		
2	Providing and fixing, double seat and cover only.	188			그&				
	i) bakelite ii) plastic	Each Each	3.50 3.50	321.50 219.50	Each Each	3.50 3.50	321.50 219.50		
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.	7			100				
	i) white ii) coloured	Each Each	229.35 229.35	1,129.40 1,321.40	Each Each	229.35 229.35	1,129.40 1,321.40		
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	229.35	1,957.35	Each	229.35	1,957.35		
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	229.35	553.40	Each	229.35	553.40		
6	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.								
	i) white, with pedestal	Each	290.40	2,366.40	Each	290.40	2,366.40		
	ii) coloured, with pedestal	Each	290.40	2,558.40	Each	290.40	2,558.40		
	iii) white, without pedestal	Each	259.90	1,621.90	Each	259.90	1,621.90		
	iv) coloured, without pedestal	Each	259.90	1,687.90	Each	259.90	1,687.90		
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	259.90	4,340.20	Each	259.90	4,340.20		
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18") with drain board of mosaic, including bracket set, waste pipe and waste coupling.	Each	259.90	1,025.45	Each	259.90	1,025.45		

	MRS, BI-ANNUAL PERIO	OD (1st l	FEBRUARY	, <b>2013 TO</b> 3	1st JUL	r, 2013) C	ISTRICT R	AWALPIN	DI
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-								
	i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18")	Each Each	259.90 259.90	1,586.35 1,406.35	Each Each	259.90 259.90	1,586.35 1,406.35		
10	Providing and fixing glazed earthen ware flat back urinal.	Each	168.30	856.70	Each	168.30	856.70		
11	Providing and fitting glazed earthen ware low down flushing cistern 13,63 litres (3 gallons) capacity, including bracket set, copper connection, etc.								
	i) white ii) coloured	Each Each	259.90 259.90	1,244.20 1,316.20	Each Each	259.90 259.90	1,244.20 1,316.20		
12	Providing and fitting plastic made low down flushing cistern 1363 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.								
	i) white	Each	259.90	1,076.20	Each	259.90	1,076.20		If rubber connection is used, the
	ii) coloured	Each	259.90	1,076.20	Each	259.90	1,076.20		composite rate will be reduced by Rs. 12.50
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	259.90	1,255.95	Each	259.90	1,255.95		
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.								
	i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity	Each Each	276.70 276.70	2,382.75 1,542.75	Each Each	276.70 276.70	2,382.75 1,542.75		
15	Providing and fixing, chromium plated soap dish.	Each	16.85	185.05	Each	16.85	185.05		
16	Providing and fitting, glazed earthen ware soap dish.								
	i) white ii) coloured	Each Each	16.85 16.85	464.65 212.65	Each Each	16.85 16.85	464.65 212.65		
17	Providing and fixing, chromium plated toilet paper holder.	Each	22.45	394.15	Each	22.45	394.15		
18	Providing and fixing, chromium plated towel rail:-								
	i) 60 cm (24") long, and 2 cm (¾") dia. ii) 50 cm (20") long, and 1.5 cm (½") dia.	Each Each	22.45 22.45	346.05 286.05	Each Each	22.45 22.45	346.05 286.05		

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	vstem)	Spec.	Remarks			
No.								No.				
		Unit	Labour	Composite	Unit	Labour	Composite					
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	42.1	361.7	Each	42.1	361.7					
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-											
	i) with chromium plated brackets and railing.     ii) glass shelf only, without chromium plated brackets     and railing.	Each Each	49.90 33.65	346.00 78.05	Each Each	49.90 33.65	346.00 78.05					
21	Providing and fitting glazed earthen ware shelf 60x13 cm (24"x5"), with chromium plated bracket and railing:-											
	i) White ii) Coloured	Each Each	49.90 49.90	901.60 1,021.60	Each Each	49.90 49.90	901.60 1,021.60					
22	Providing and fitting:-	.du			111							
	<ul> <li>i) plastic soap dish</li> <li>ii) plastic toilet paper holder</li> <li>iii) plastic towel rail</li> <li>iv) plastic shelf 60x13 cm (24"x5") with bracket and railing.</li> </ul>	Each Each Each Each	16.85 22.45 22.45 22.45	149.70 212.55 230.55 414.05	Each Each Each Each	16.85 22.45 22.45 22.45	149.70 212.55 230.55 414.05					
23	Providing and fixing chromium plated pillar-cock, heavy:-			984	350							
	i) 2 cm (3/4") ii) 1.5 cm (1/2")	Each Each	22.45 22.45	526.45 682.45	Each Each	22.45 22.45	526.45 682.45					
24	Providing and fixing chromium plated stop cock, heavy:-											
	i) 2 cm (3/4") ii) 1.5 cm (1/2")	Each Each	22.45 22.45	262.45 174.85	Each Each	22.45 22.45	262.45 174.85					
25	Providing and fixing underground stop cock 13 mm (½"), with chromium plated cover.	Each	32.10	471.70	Each	32.10	471.70					
	Providing and fixing chromium plated bib cock: i) 2 cm (¾") ii) 1.5 cm (½")	Each Each	22.45 22.45	334.45 316.45	Each Each	22.45 22.45	334.45 316.45					
27	Providing and fixing chromium plated tee stop cock 15mm (½").	Each	22.45	442.45	Each	22.45	442.45					
28	Providing and fixing chromium plated shower rose:-											
	i) 1.5x10 cm (½"x4") ii) 2x15 cm (¾"x6")	Each Each	22.45 22.45	322.45 400.45	Each Each	22.45 22.45	322.45 400.45					
29	Providing and fixing, chromium plated mixing valve, for wash	Each	28.05	1,528.05	Each	28.05	1,528.05					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	hand basin, sink or shower.												
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)				
	i) 30 mm (1¼") dia	Each	33.65	423.65	Each	33.65	423.65		will be reduced by Rs. 66, 77, 95, 107				
	ii) 40 mm(1½") dia	Each	33.65	579.65	Each	33.65	579.65		and 120 respectively.				
	iii) 50 mm(2") dia	Each	33.65	795.65	Each	33.65	795.65						
	iv) 65 mm(2½") dia	Each	33.65	1,257.65	Each	33.65	1,257.65						
	v) 80 mm(3") dia	Each	33.65	1,863.65	Each	33.65	1,863.65						
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (½") dia.												
	i) single way	Each	22.45	364.45	Each	22.45	364.45						
	ii) two way	Each	33.65	627.65	Each	33.65	627.65						
	iii) three way	Each	44.90	758.90	Each	44.90	758.90						
32	Providing and fixing, union brass cock.	8				a a							
	i) 13 mm (½") dia	Each	22.45	136.45	Each	22.45	136.45						
	ii) 20 mm (¾") dia	Each	22.45	214.45	Each	22.45	214.45						
		1	1000	8 7 Car 1 1									
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-			200	193								
	i) 10x5 cm (4"x2")	Each	67.30	372.55	Each	67.30	372.55						
	ii) 10x7.5 cm (4"x3")	Each	67.30	366.55	Each	67.30	366.55						
34	Providing and fitting "P" trap:-												
	i) 10 cm (4") of cast iron.	Each	56.10	439.90	Each	56.10	439.90						
	ii) 10 cm (4") glazed.	Each	56.10	119.50	Each	56.10	119.50						
	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	84.15	630.75	Each	84.15	630.75						
36	Providing and fitting, cast iron soil pipe with:-												
	i) lead caulked, yarn joint:-												
	a) 10 cm (4") i/d	Per foot	25.15	218.20	Metre	82.50	715.70						
	b) 5 cm (2") i/d	Per foot	10.05	92.20	Metre	33.00	302.40						
	ii) cement caulked joint:-												
	a) 10 cm (4") i/d	Per foot	6.05	144.85	Metre	19.90	475.15						
	b) 5 cm (2") i/d	Per foot	2.45	79.15	Metre	7.95	259.60						

	Description	F Unit	Rate (British Sys	stem)	Ra	te (Metric S	vatam)	G	Donesiles
37 P		Unit				itt (Mittile B	ystem)	Spec.	Remarks
			Labour	Composite	Unit	Labour	Composite	No.	
	roviding and fitting, A.C. soil pipe with cement caulked bint, including all specials:-								
i)	60 (2½)" mm i/d	Per foot	4.85	28.85	Metre	15.90	94.70		
ii		Per foot	5.40	68.05	Metre	17.65	223.15		
	i) 100 (4") mm i/d	Per foot	6.05	102.80	Metre	19.90	337.15		
iv	v) 150 (6") mm i/d	Per foot	8.10	128.20	Metre	26.50	420.55		
	roviding and fitting cast iron specials, such as tee bend, ollar, cross, etc. plain type:-								In case of plug type, the composite rate shall be increased by Rs.2 per kg.
i)	lead caulked joint	Kg	21.00	145.70	Kg	21.00	145.70		
ii		Kg	12.90	109.55	Kg	12.90	109.55		
	upply and fitting of cast iron manhole cover vith frame, etc. complete.	.11							
i)	30 cm (12") dia	Each	33.65	177.65	Each	33.65	177.65		
ii		Each	33.65	849.65	Each	33.65	849.65		
ii	i) 60 cm (24") dia	Each	53.00	1,433.00	Each	53.00	1,433.00		
	roviding and fitting R.C.C. pipe 10 cm (4") dia, including aying and jointing in trenches.	Per foot	12.60	37.80	Metre	41.25	123.90		
	roviding and fitting chromium plated or oxidised, gas cock 'mm (1/4"):-	Œ	in an ce	(I)epa	r É arriso	N. F			
i)	single way	Each	22.45	190.45	Each	22.45	190.45		
ii	) two way	Each	33.65	285.65	Each	33.65	285.65		
ii	i) three way	Each	44.90	476.90	Each	44.90	476.90		
	roviding and fitting nipple or bush, 6 mm to 0 mm (1/4" to 3/8") i/d.	Each	16.85	46.85	Each	16.85	46.85		
43 P	roviding and fixing, brass gas cock:-								
a b	) 15 mm (½") dia ) 20 mm (¾") dia	Each Each	3.50 127.50	87.50 99.50	Each Each	3.50 127.50	87.50 99.50		
	roviding and fixing brass stop cock/bib cock:-			,,,,,			77.20		
a		Each	5.60	77.60	Each	5.60	77.60		
b	) 20 mm (¾") dia	Each	5.60	116.00	Each	5.60	116.00		
45 H	loisting and placing in position, precast R.C. latrine seats.	Each	272.25	-	Each	272.25	-		
	Replacement								

Sr.	Description		Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and fixing, chromium plated waste coupling:-								
	i) 3 cm (1 <sup>1</sup> / <sub>4</sub> ") ii) 4 cm (1 <sup>1</sup> / <sub>2</sub> ")	Each Each	33.65 33.65	116.45 122.45	Each Each	33.65 33.65	116.45 122.45		
2	Providing and fixing rubber plug with chain:-								
	i) 3 cm (1 <sup>1</sup> / <sub>4</sub> ") ii) 4 cm (1 <sup>1</sup> / <sub>2</sub> ")	Each Each	1.35 1.35	45.75 52.95	Each Each	1.35 1.35	45.75 52.95		
3	Providing and fixing, waste pipe of PVC:-								
	i) 3 cm (1 <sup>1</sup> / <sub>4</sub> ") ii) 4 cm (1 <sup>1</sup> / <sub>2</sub> ")	Each Each	16.85 16.85	42.05 48.05	Each Each	16.85 16.85	42.05 48.05		
4	Providing and fixing, flushing bend of PVC.								
	i) 3 cm (1 <sup>1</sup> / <sub>4</sub> ") ii) 4 cm (1 <sup>1</sup> / <sub>2</sub> ")	Each Each	14.95 14.95	40.15 46.15	Each Each	14.95 14.95	40.15 46.15		
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-	16		ر حکومت پڑت					
	i) 3 cm (1 <sup>1</sup> / <sub>4</sub> ") i/d ii) 4 cm (1 <sup>1</sup> / <sub>2</sub> ")	Each Each	33.65 33.65	537.65 657.65	Each Each	33.65 33.65	537.65 657.65		
6	Providing and fixing, angle iron brackets for:-	12	nman ce	(E)lespen		N.E			
	<ul><li>i) wash hand basin and cistern</li><li>ii) sinks</li></ul>	Each Each	33.65 33.65	156.05 170.45	Each Each	33.65 33.65	156.05 170.45		
7	Providing and fixing 1.5 cm (½") dia connection, including check nuts, etc.:-								
	<ul><li>i) plastic rubber connection</li><li>ii) copper connection</li></ul>	Each Each	13.45 13.45	44.65 81.85	Each Each	13.45 13.45	44.65 81.85		
8	Providing and fixing brass ball float valve:-								
	i) 1.5 cm (½") dia ii) 2.0 cm (¾") dia iii) 2.5 cm (1") dia iv) 3 cm (1½") dia v) 4.0 cm (1½") dia	Each Each Each Each Each	28.05 28.05 28.05 28.05 28.05	220.05 286.05 346.05 376.05 520.05	Each Each Each Each Each	28.05 28.05 28.05 28.05 28.05	220.05 286.05 346.05 376.05 520.05		
	v) 4.0 cm (1½") dia vi) 5 cm (2") dia	Each	28.05	904.05	Each	28.05	904.05		

## 20. SURFACE DRAINAGE

- 1. Specification No. correspond to Book of Specification (B & R Department ) Vol. 11, 1966 (public Health Works).
- 2. Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOR	RICT RAWA	LPINDI						
Sr. No.	Description	]	Rate (British Sy	stem)	Ra	te (Metric Sy	ystem)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
1	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-							17.1	
	a) 3" thick (75 mm)		/ ×	)					
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	851.90 851.90	3,562.80 3,396.95	Metre ditto	27.95 27.95	116.85 111.40		
	B) 4½" thick (113 mm)	13			78				
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,277.15 1,277.15	5,183.30 4,932.35	ditto ditto	41.90 41.90	170.00 161.80		
2	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled and struck flush:-	GF in		San Democrit	en en t			17.1	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,257.05 1,257.05 1,257.05	5,033.65 4,767.95 4,693.25	Sqm. ditto ditto	135.25 135.25 135.25	541.60 513.05 505.00		
3	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,789.90 1,789.90 1,789.90	7,483.70 7,057.60 6,951.55	Sqm. ditto ditto	192.60 192.60 192.60	805.25 759.40 748.00		
4	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,190.65 1190.65 1190.65			128.10 128.1 128.1	534.45 505.9 497.85		

	MRS, BI-ANNUAL PERIO	D (1st FE	BRUARY, 20	013 TO 31st	JULY, 20	13) DISTE	RICT RAWA	LPINDI	
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.	•	Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	Pacca brick on edge, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,833.20 1,833.20 1,833.20	7,527.00 7,100.90 6,994.85	Sqm. ditto ditto	197.25 197.25 197.25	809.90 764.05 752.65		
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ½:5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ¼" (6 mm) thick, as per Engineer's drawing (excluding excavation):-		<u>*</u>					17.1	
	a) Type I b) Type II	Per Rft ditto	28.50 57.00	79.60 147.75	Metre ditto	93.50 187.05	261.05 484.55		
	c) Type III d) Type IV	ditto ditto	73.85 88.05	191.60 228.50	ditto ditto	242.30 288.75	628.45 749.50		
	e) Type V	ditto	116.10	311.90	ditto	380.85	1,023.00		
	f) Type VI	ditto	133.55	357.55	ditto	437.95	1,172.75		
	g) Type VII	ditto	148.00	394.00	ditto	485.45	1,292.35		
	h) Type VIII	ditto	165.30	443.30	ditto	542.15	1,453.95		
	i) Type IX j) Type X	ditto ditto	220.90 242.65	626.75 686.95	ditto ditto	724.55 795.85	2,055.70 2,253.25		
	k) Type XI	ditto	271.20	763.85	ditto	889.55	2,505.50		
	I) Type XII	ditto	289.10	810.60	ditto	948.30	2,658.75		
7	Laying R.C.C hume pipes in position, including jointing:-	Don I ft	52.55	55 50	Matua	172 20	192.10		
	a) 6" to 12" (150 mm to 300 mm) dia b) 12" to 24" (300 mm to 600 mm) dia	Per Lft. ditto	52.55 81.85	55.50 87.80	Metre ditto	172.30 268.45	182.10 288.05		
	c) 24" to 36" (600 mm to 900 mm) dia	ditto	105.05	114.05	ditto	344.65	374.15		
	, , , , ,			-					

# 21. SEWERAGE

- 1 Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works).
- 2 Rate for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD	(1st FEE	BRUARY, 20	13 TO 31st	JULY, 20	)13) DIST	RICT RAW	ALPINDI	
Sr. No.	Description	]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and laying R.C.C. pipe, moulded with cement concrete 1:1½:3, with spigot socket or collar joint, etc. including cost of reinforcement, conforming to B.S. 5911 Part I: 1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes where necessary, finishing and testing, etc., complete							Chapter - 8	
	i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 225 mm (9:) i/d	Rft. Rft. Rft.	14.70 17.80 34.35	67.15 105.65 276.25	Metre Metre Metre	48.20 58.40 112.65	220.25 346.55 906.10		
2	Providing and laying non-reinforced concrete pipe moulded with cement concrete 1:1½:3, conforming to ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipe where necessary, finishing and testing, etc. complete	300	- Gr.					ditto	
	i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 200 mm (8") i/d iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm) v) 250 mm (10") i/d	Rft. Rft. Rft. Rft. Rft.	11.05 13.35 21.40 23.10 23.50	34.25 48.75 67.80 85.50 94.45	Metre Metre Metre Metre Metre	36.25 43.80 70.20 75.75 77.10	112.35 159.90 222.40 280.45 309.80		
3	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc., complete.							ditto	
	i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iii) 460 mm (21":) i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	35.45 44.50 53.70 67.15 77.45 113.40 136.00 169.25 208.20 270.95 506.75 698.05 892.1 1392.25 1725.20	347.00 425.25 460.45 593.00 711.00 994.05 1062.55 1244.00 1684.05 2193.05 2921 3663.25 4186.75 5016.35 5678.80	Metre Metre	116.30 145.95 176.15 220.25 254.05 371.95 446.10 555.15 682.90 888.7 1662.15 2289.6 2926.1 4566.6 5658.65	1138.15 1394.80 1510.30 1945.05 2332.10 3260.50 3485.15 4080.30 5523.70 7193.2 9580.9 12015.45 13732.55 16453.65 18626.45		

	MRS, BI-ANNUAL PERIOD	(1st FEE	BRUARY, 20	13 TO 31st	JULY, 20	13) DIST	RICT RAW	ALPINDI	
Sr.	Description	I	Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class III, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipe where necessary, testing, etc. complete:-							Chapter-8	
5	i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	35.45 44.50 53.70 67.15 77.45 113.40 136.00 169.25 208.20 270.95 513.90 708.05 904.60 1412.20 1750.20	419.20 515.00 647.70 790.75 918.40 1096.20 1327.95 1480.40 1983.75 2574.95 3147.05 4020.05 4965.40 6466.60 8043.00	Metre Metre Metre Metre Metre Metre	116.30 145.95 176.05 220.25 254.10 371.95 446.00 555.05 682.95 888.75 1685.55 2322.40 2967.05 4632.05 5740.55	1375.00 1689.20 2124.45 2593.65 3012.35 3595.55 4355.70 4855.70 6506.70 8445.85 10322.30 13185.75 16286.50 21210.45 26381.05	Chapter - 8	
6	Specification C-76-79, Class IV, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc. complete:  i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii) 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	35.45 44.50 53.70 67.15 77.45 113.40 136.00 169.25 208.20 270.95 513.90 708.05 904.60 1412.20 1750.20	517.15 646.60 776.20 910.10 1040.80 1377.70 1584.95 1763.15 2485.60 3064.55 3706.50 4999.30 6311.80 8302.60 9879.00	Metre	116.30 145.95 176.05 220.25 254.10 371.95 446.00 555.05 682.95 888.75 1685.30 2322.60 2967.05 4632.05 5740.55	1696.20 2120.85 2545.90 2985.10 3413.90 4518.90 5198.75 5783.05 8152.70 10051.75 12157.30 16397.55 20702.65 27232.55 32403.05		1) This rate shall be payable, in
6	Lowering of sub-soil water table, by installation of tubewell: along sewer line and pumping out water, for excavation ir open cutting below sub-soil water level, concreting, curing laying and jointing pipes, filling haunches, etc. till the								This rate shall be payable, in addition to the item of excavation below SSWL for sewers and manholes under Chapter.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr. No.	Description	1	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	NO.				
	completion of sewer line, including disposal of pumped out water:-  1) 0-1 ft. (0 to 310 mm) below SSWL 2) 0-2 ft. (0 to 610 mm) below SSWL 3) 0-3 ft. (0 to 910 mm) below SSWL 4) 0-4 ft. (0 to 1220 mm) below SSWL 5) 0-5 ft. (0 to 1520 mm) below SSWL 6) 0-6 ft. (0 to 1830 mm) below SSWL 7) 0-7 ft. (0 to 2170 mm) below SSWL 8) 0-8 ft. (0 to 2480 mm) below SSWL 9) 0-9 ft. (0 to 2790 mm) below SSWL	Rft of laid sewer ditto	- - - - - -	386.95 660.20 953.85 1329.50 1644.70 1965.00 2256.30 2437.70	ditto ditto ditto ditto ditto ditto	-	667.85 1269.15 2165.50 3128.55 4360.70 5394.55 6445.15 7400.75 7995.75		EARTHWORK 2) The grant of these rates shall be subject to Superintending Engineer's approval.  3) The rate includes cost of providing pumps, POL and all operation charges at the site of work, etc.			
	10) 0-10 ft. (0 to 3100 mm) below SSWL 11) 0-11 ft. (0 to 3410 mm) below SSWL 12) 0-12 ft. (0 to 3720 mm) below SSWL	ditto ditto ditto	X	2809.50 3124.75 3464.25	ditto ditto ditto	- - -	9215.10 10249.25 11362.75					
7	Constructing gully grating chamber, 12"x12", ( 300x300 mm) complete in all respects:	J. (-		3101123	anto		11302.73	16.2	Pipe connection to be paid separately.			
	a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) frame hinged safety type.	Each	591.05	2724.70	Each	591.05	2724.70					
	b) concrete Gully trap.	ditto	591.05	2499.70	ditto	591.05	2499.70					
8	Constructing standard gully grating chamber, 3'x2½' (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects.	Each	1791.55	7632.10	Each	1791.55	7632.10	ditto	Pipe connection to be paid separately.			
9	Extra for making and finishing benching floor work in manhole chamber, with 1/8" (3 mm) thick cement finish	100Sft.	762.15	1214.85	Sq.m	82.00	130.70	14.4				
10	Restoration of brick pavement on edge, over laid service line, with 2" (50 mm) sand cushion under soling	100Sft.	1088.20	2717.55	Sq.m	117.10	292.40	13.1				
11	Restoration of flat brick pavement sand grouted, over 2' (50 mm) thick dry sand cushion, under soling on laic service line.	100Sft.	660.65	1809.80	Sq.m	71.10	194.75	13.1				
12	Restoration of metalled road, on laid service line, including compaction:-							13.1				
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base	100Sft.	2704.90	9112.05	Sq.m	291.05	980.45					
	b) Carpeted road, with 1½" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base	100Sft.	1944.25	6731.25	Sq.m	209.20	724.30					
	c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base.	100Sft.	763.85	4394.20	Sq.m	82.20	472.80					
13	Providing and fixing 11/4"x11/4"x3/16" (31x31x5 mm) angle							14.7				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description	1	Rate (British Sys	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	iron step, in manhole chambers, including carriage and setting the same in work to correct lines and levels	Each	74.30	232.35	Each	74.30	232.35			
14	Fixing manhole frame and cover in R.C.C. slab including carriage to site.	Per set	183.40	-	Per set	183.40	-	ditto		
15	Providing and fixing 3" (75 mm) thick R.C.C. manhole cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20" (500 mm) clear i/d (frame weighing 37.324 Kg. or one maund) as per Standard Drawing STD/PD No. 5, of 1977, complete in all respects.	Per set	125.05	2823.25	Per set	125.05	2823.25	ditto		
15-A	Providing and fixing 6" thick R.C.C. manhole cover with tee shaped C.I. frame of 22" I/d (frame weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect.	Per set	251.60	4080.20	Per set	251.60	4080.20			
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects.	Per set	225.35	2485.00	Per set	225.35	2485.00	ditto		
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover with 3"x3"x½" (75x75x6mm) angle iron frame, 22' (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects.	Per set	194.30	3962.15	Per set	194.30	3962.15	ditto		
18	Desilting of disposal work collecting tank, including removal of sludge within 3 chains (90 metre)	100Cft.	558.15	612.45	cum	197.15	216.30	16.2		
19	Providing and installing, C.I. ventilating shaft painted with bituminous paint with foundation bolts, as per PHEC Standard Drawing STD/PD No. 4 of 1977, complete in all respects (except concrete foundation block):  a) 6" (150 mm) i/d shaft							14.6		
	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long	Per Cwt ditto ditto ditto	164.20 182.40 197.00 206.15	2318.95 2343.50 2356.75 2366.25	%kg ditto ditto ditto	323.20 359.10 387.80 405.80	4564.90 4613.25 4639.25 4657.95			
	b) 9" (225 mm) i/d shaft									
	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long	Per Cwt ditto ditto ditto	144.15 155.35 166.30 200.20	2295.15 2305.85 2317.15 2350.90	%kg ditto ditto ditto	283.75 305.75 327.40 394.10	4518.00 4539.05 4561.30 4627.75			
	c) 12" (300 mm) i/d shaft									

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI												
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
20	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long  Silt clearing 10' (3.00 m) dia wells, and removal of slush outside the compound:  a) upto 10' (3.00 m) depth of slush b) beyond 10' (3.00 m) depth of slush	Per Cwt ditto ditto	127.25 163.60 190.85 4705.80 9226.80	2279.25 2312.80 2339.35	ditto	250.45 322.00 375.70 4705.80 9226.80	4486.70 4552.70 4605.05						



Timance Department

# 22. SINKING OF WELLS

- Rates for all finished works include the removal of surplus debris, unused material and byproducts. Well curbs to be laid at spring level or as deep as possible.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Excavation of well in dry upto 20'(6 metre) below ground level, and disposal of soil within one chain (30 metre)											
	a) in ordinary soil or sand :-	1000 Cft.			cu.m							
	<ul> <li>i) from 0' to 5' (o to 1.5 m) depth</li> <li>ii) from 5.1' to 10' (1.5 to 3.0 metre) depth</li> <li>iii) from 10.1' to 15' (3.0 to 4.5 metre) depth</li> <li>iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth</li> <li>b) in hard soil</li> <li>i) from 0' to 5'(0 to 1.5 metre) depth</li> </ul>	ditto ditto ditto ditto	2903.05 3032.00 3411.00 3915.00		ditto ditto ditto ditto	102.55 107.10 120.50 138.30						
	ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth	ditto ditto ditto	3696.20 4040.05 4544.05	ر اعرب	ditto ditto ditto	130.55 142.70 160.50	- - -					
	c) in hard strata, such as shingle, gravel, etc.  i) from 0' to 5'(0 to 1.5 metre) depth  ii) from 5.1' to 10'(1.5 to 3.0 metre) depth  iii) from 10.1' to 15'(3.0 to 4.5 metre) depth  iv) from 15.1' to 20'(4.5 to 6.0 metre) depth	1000 Cft. ditto ditto ditto	7626.85 7900.35 8236.40 8842.00	Depari	cu.m ditto ditto ditto	269.40 279.05 290.90 312.30						
2	Dry sinking of well, including loading, and removing excavated material within one chain (30 m):-											
	a) in ordinary soil:-  i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth iv) from 25.1' to 30'(7.5 to 9.0 m) depth v) from 30.1' to 35'(9.0 to 10.5 m) depth vi) from 35.1' to 40'(10.5 to 12.0 m) depth	1000 Cft. ditto ditto ditto ditto	15628.80 19536.00 23443.20 27350.40 31257.60 35164.80	- - - - -	cu.m ditto ditto ditto ditto	552.00 690.00 828.00 966.00 1104.00 1242.00						
	vii) from 40.1'to 45'(12.0 to 13.5 m) depth viii) from 45'(13.5 Sm) to any depth b) in hard soil:-	ditto ditto	39072.00 42979.20	-	ditto ditto	1380.00 1518.05						
	i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth	1000 Cft. ditto ditto	21489.60 25396.80 29304.00	- - -	cu.m ditto ditto	759.00 897.00 1035.00	- - -					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	33211.20		ditto	1173.00						
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	37118.40	-	ditto	1311.00	-					
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	41025.60	-	ditto	1449.00	-					
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	44932.80	-	ditto	1587.05	-					
	viii) from 45'(13.5 m) to any depth	ditto	48840.00	-	ditto	1725.05	-					
	c) in hard strata, such as shingle, gravel, etc.											
	i) from 10! to 15!/2 0 to 4.5 m) doubth	1000 Cft.	29304.00			1035.00						
	i) from 10' to 15'(3.0 to 4.5 m) depth			_	cu.m		-					
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	33211.20	-	ditto	1173.00	-					
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	37118.40	- ) - /	ditto	1311.00	-					
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	37606.80		ditto	1328.25	-					
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	44932.80	-	ditto	1587.05	-					
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	48840.00	-	ditto	1725.05	-					
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	52747.20		ditto	1863.05	-					
	viii) from 45'-1" (13.5 m) to any depth	ditto	56654.40		ditto	2001.05	-					
3	Wet sinking of well in ordinary soil (value of C upto 5), for	1136	-	6)				*841-1	The outer dimensions of the curb			
	depths below spring level, including charges of machinery,	100		ر ۱۳۰۸	-41			to	shall form basis of payment.			
	shoring, kentledge and removal of excavated spoil within	-6		-//	633			841-9				
	one chain (30 m):-		20	4								
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	25157.65	(T)) e spacet	cu.m	£ 888.55	-					
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	53460.00	areas francis	ditto	1888.20	-					
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	65796.90	-	ditto	2323.95	-					
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	85536.00	-	ditto	3021.15	-					
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	95040.00	-	ditto	3356.80	-					
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	106920.00	-	ditto	3776.40	-					
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	109661.55	-	ditto	3873.25	-					
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	112547.35	-	ditto	3975.15	-					
	ix) above 80'(24.0 m) to any depth	ditto	122194.30	-	ditto	4315.90	-					
								#O.45				
4	Wet sinking of well in cohesive soil (value of Cmore than							*841-1	The outer dimensions of the curb			
	5), for depths below spring level, including charges of							to	shall form basis of payment.			
	machinery shoring, kentledge and removal of excavated							841-9				
	spoil within one chain (30 m):-											
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	-	38311.70	cu.m	-	1353.15					
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	-	47889.60	ditto	-	1691.45					
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	57467.50	ditto	-	2029.75					
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	76623.35	ditto	-	2706.35					
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	-	88411.55	ditto	-	3122.70					
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	-	95779.20	ditto	-	3382.90					
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	-	104486.40		-	3690.45					
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	-	108429.30	ditto	-	3829.70					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI											
Sr.	Description	]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ix) above 80'(24.0 m) to any depth	ditto	-	114935.05	ditto	-	4059.50					
5	Wet sinking of well in shingle, or gravel, etc, for depths below spring level, including charges of machinery, shoring, kentledge and removal of excavated spoil within one chain (30 m):-							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.			
	i) from o' to 10'(0 to 3.0 m) depth ii) above 10' to 20'(3.0 to 6.0 m) depth iii) above 20' to 30'(6.0 to 9.0 m) depth	1000 Cft. ditto ditto	- - -	52243.20 63852.80 76623.35	cu.m ditto ditto	-	1845.25 2255.30 2706.35					
	iv) above 30' to 40'(9.0 to 12.0 m) depth v) above 40' to 50'(12.0 to 15.0 m) depth vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto ditto ditto	/ ×	104486.40 114935.05 127705.60	ditto ditto ditto	-	3690.45 4059.50 4510.55					
	vii) above 60' to 70'(18.0 to 21.0 m) depth viii) above 70' to 80'(21.0 to 24.0 m) depth ix) above 80'(24.0 m) to any depth	ditto ditto ditto		133645.40 136827.45 151230.35	ditto ditto ditto	-	4720.35 4832.75 5341.45					
6	Making and fixing in position, kiker wood well curb.	Per Cft.	741.10	2134.05	cu.m	26175.70	75373.80					
7	Laying well curb in position only.	Each	269.30		Each	269.30	-					
8	Providing, making and laying R.C.C. well curb in position, using coarse sand, including all kinds of form, moulds, curing, shuttering, rendering and finishing the exposed surface, (including screening and washing of aggregate:-	T	vance	Depart		7		*841-1 to 841-9	I) If concrete mixer is supplied by Government, all charges including depreciation will be recovered from the contractor.      The rate does not include cost of			
	a) Ratio 1:1½:3 b) ratio 1:2:4	Per Cft. ditto	159.30 159.30	348.25 323.25	cu.m ditto	5627.30 5627.30	12299.60 11417.55		steel reinforcement and its labour for bending, which is payable, separately.			
9	Providing and fixing structural steel for cutting edge.	100Kg	580.80	10757.10	100Kg	580.80	10757.10	841-1 to 841-9				
10	Making and removing false masonry on well.	100Cft.	4919.65	16962.70	cu.m	1737.60	5991.20	21.1 to 21.5 & 18.1	The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.			

<sup>\*</sup> Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

## 23. TUBEWELL AND WATER SUPPLY

- Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)" Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY,	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAL	.PIND	
Sr.	Description	R	ate (British S	System)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Boring for tubewell in all types of soil except shingle and rock, from ground level to 100 ft. (30 m) depth, including sinking and withdrawing of casing pipe, complete:-							Chap. 2	
2	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 100.1 ft. to 200 ft. (30 to 60 m) below ground level, including sinking and withdrawing of casing pipe, complete:-	Per Rft. of bore ditto ditto ditto ditto ditto ditto ditto ditto		42.30 58.20 104.25 159.15 205.45 260.35 283.10 420.45 446.35	Per Metre of bore ditto ditto ditto ditto ditto ditto		138.80 190.80 341.90 522.05 673.95 854.00 928.55 1379.05 1464.05	ditto	
	a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d	Per Rft. of bore ditto ditto ditto ditto ditto	ONCE !	176.00 248.15 277.95 318.55 349.10 492.95 518.85	Per Metre of bore ditto ditto ditto ditto		577.20 813.90 911.60 1044.90 1145.05 1616.90 1701.90		
3	Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 200.1 ft. to 300 ft. (60 to 90 m) below ground level, including sinking and withdrawing of casing pipe, complete:-							ditto	
4	a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 300.1 ft. to 400 ft. (90 to 120 m) below ground level, including sinking and withdrawing of casing pipe, complete:-	Per Rft. of bore ditto ditto ditto ditto ditto		245.75 317.30 349.80 395.30 419.25 541.35 568.50	Per Metre of bore ditto ditto ditto ditto ditto		806.00 1040.70 1147.30 1296.60 1375.15 1775.70 1864.60	Chap. 2	
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d	Rft of bore ditto		422.25 472.65	Per Metre of bore		1385.00 1550.30		

	MRS, BI-ANNUAL PERIOD	(1st FEB	BRUARY, 2	2013 TO 31st	JULY, 20	)13) DIST	RICT RAWAL	PIND	
Sr.	Description	R	ate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	ditto ditto ditto		498.40 661.50 665.10	ditto ditto ditto		1634.75 2169.80 2181.60		
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells in all types of soil except shingle, gravel and rock:							ditto	
	a) from ground level to 250 ft. (75 m) below ground level:								
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto		408.15 587.00	Per Metre of bore ditto		1338.75 1925.35		Upto 2 cusec discharge Above 2 cusec discharge
	b) exceeding 250 ft. (75 m) depth below ground level:-	Rft	×		Per Metre				
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	of bore ditto		408.15 587.00	of bore ditto		1338.75 1925.35		Upto 2 cusec discharge Above 2 cusec discharge
6	Boring for tubewell in shingle, gravel and rock, including sinking and withdrawing of casing pipe:-	E E			7 🚳			ditto	Location and depth of shingle, gravel or rock is to be determined from the bore log.
	a) from ground level to 200 ft. (60 m) below ground level:	7.00			2				
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto	ance (	920.50 1244.95	Per Metre of bore ditto		3019.30 4083.50		Upto 2 cusec discharge Above 2 cusec discharge
	b) exceeding 200 ft. (60 m) depth below ground level:-								
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	ditto ditto		920.50 1244.95	ditto ditto		3019.30 4083.50		Upto 2 cusec discharge Above 2 cusec discharge
7	Providing strong substantially built box of deodar wood 4'x2½'x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	619.15	11306.35	Job for compl- ete bore	619.15	11306.35	ditto	
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	118.80	169.20	Per Set of 2 bottles	118.80	169.20	Chap. 2	
9	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc complete:-							ditto	Cost/labour of jointing both ends is included in the rate.
	a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick	Per Rft. Per Rft. Per Rft. Per Rft.	21.35 21.35 28.45 32.10	1018.85 1277.95	Per Metre Per Metre Per Metre Per Metre	70.05 70.05 93.40 105.35	2274.20 3341.85 4191.75 4926.95		

	MRS, BI-ANNUAL PERIOD	(1st FEE	BRUARY, 2	2013 TO 31st	JULY, 20	13) DIST	RICT RAWAL	.PIND	
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick	Per Rft. Per Rft.	35.60 41.50	1921.00	Per Metre Per Metre	116.75 136.15	5282.75 6300.90		
	g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick	Per Rft. Per Rft.	50.40 50.40		Per Metre Per Metre	165.25 165.25	7983.15 8155.35		
	i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick	Per Rft.	56.75	2555.75	Per Metre	186.05	8382.80		
	j) 10" i/d, ¹/4" (250 mm i/d 6 mm) thick k) 12" i/d, ¹/4" (300 mm i/d 6 mm) thick	Per Rft.	56.75 57.95		Per Metre	186.05 190.00	10621.40 12071.80		
	1) 15" i/d, <sup>1</sup> / <sub>4</sub> " (375 mm i/d 6 mm) thick m) 18" i/d, <sup>1</sup> / <sub>4</sub> " (450 mm i/d 6 mm) thick	Per Rft. Per Rft.	66.40 66.40		Per Metre Per Metre	217.75 217.75	15026.95 16921.15		
	n) 20" i/d, <sup>1</sup> / <sub>4</sub> " (500 mm i/d 6 mm) thick o) 22" i/d, <sup>1</sup> / <sub>4</sub> " (550 mm i/d 6 mm) thick	Per Rft. Per Rft.	78.20 79.40	5695.70	Per Metre Per Metre	256.55 260.50	18681.95 21441.10		
10	Providing and installing M.S. Bail plug in tubewell bore	TOTALL.	77.40	0330.70	1 ci wicuc	200.30	21441.10		In the case of increase or decrease
10	hole:		×	)					in the case of increase of decrease in the length of Bail plug, the rates will be increased or decreased as
	a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long.	Each	93.20	532.55	Each	93.20	532.55		per rates given in serial No. 14 of
	b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long.	Each	93.20	714.25	Each	93.20	714.25		this chapter for the respective
	c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long.	Each	155.55	1381.65	Each	155.55	1381.65		diameter.
	d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long. e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long.	Each Each	155.55 209.95	1747.60 2210.45	Each Each	155.55 209.95	1747.60 2210.45		
	e) 6" 1/d, 2 ft. (150 mm 1/d 600 mm) long. f) 7" 1/d, 2 ft. (175 mm 1/d 600 mm) long.	Each	209.95	2567.90	Each	209.95	2567.90		
	g) 8" i/d, 2 ft. (200 mm i/d 600 mm) long	Each	258.85	2843.10	Each	258.85	2843.10		
	h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long	Each	258.85	3167.20	Each	258.85	3167.20		
	i) 10" i/d, 2 ft. (250 mm i/d 600 mm) long	Each	258.85	4069.65	Each	258.85	4069.65		
	j) 12" i/d, 2 ft. (300 mm i/d 600 mm) long	Each	310.65	4885.55	Each	310.65	4885.55		
	k) 15" i/d, 2 ft. (375 mm i/d 600 mm) long	Each	310.65	6031.65	Each	310.65	6031.65		
	1) 18" i/d, 2 ft. (450 mm i/d 600 mm) long	Each	373.55	6878.65	Each	373.55	6878.65		
	m) 20" i/d, 2 ft. (500 mm i/d 600 mm) long	Each	406.30	7621.65	Each	406.30	7621.65		
	n) 22" i/d, 2 ft. (550 mm i/d 600 mm) long	Each	406.30	8387.30	Each	406.30	8387.30		
11	Providing and installing, P.V.C. strainer B.S.S. Class 'B', in tubewell bore hole, including sockets and solvents, etc complete:-							Chap. 2	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Per Rft. Per Rft.	16.20 18.40		Per Metre Per Metre	53.15 60.40	360.15 528.80		
	c) 5" i/d (125 mm)	Per Rft.	19.50		Per Metre	63.90	729.10		
	d) 6" i/d (150 mm)	Per Rft.	22.75		Per Metre	74.65	960.25		
	e) 8" i/d (200 mm)	Per Rft.	31.05		Per Metre	101.80	2305.95		
	f) 10" i/d (250 mm)	Per Rft.	31.75		Per Metre	104.10	3449.70		
	g) 12" i/d (300 mm)	Per Rft.	31.75		Per Metre	104.10	4591.15		
12	Providing and installing P.V.C. strainer B.S.S. Class `D', in tubewell bore hole, including sockets and solvent, etc complete:-								
	a) 1½" i/d (30 mm)	Per Rft.	11.20		Per Metre	36.80	154.9		
	b) 1½" i/d (40 mm)	Per Rft.	11.50		Per Metre	37.65	175.4		
	c) 2" i/d (50 mm)	Per Rft.	11.60		Per Metre	38.00	270.2		
	d) 3" i/d (75 mm)	Per Rft.	16.20	169.80	Per Metre	53.15	557		

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND										
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft.	18.35 19.50 35.15	391.50	Per Metre Per Metre Per Metre	60.25 63.90 115.20	875 1284.05 1847.05			
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:-									
	i) B.S.S. Class `B'									
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) ii) B.S.S. Class `D'  a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each Each	8.30 9.30 10.10 13.30 15.65 16.50 19.35 19.35 5.80 6.10 6.30 8.30 9.30 10.10 13.3	59.90 78.90 118.10 172.90 339.65 472.50 637.35 661.35 32.20 45.70 65.10 86.30 112.50 158.90 207.7	Each Each Each Each Each Each Each	8.30 9.30 10.10 13.30 15.65 16.50 19.35 19.35 5.80 6.10 6.30 8.30 9.30 10.10 13.3	59.90 78.90 118.10 172.90 339.65 472.50 637.35 661.35 32.20 45.70 65.10 86.30 112.50 158.90 207.7			
14	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:-  a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, ¼" (250 mm i/d 6 mm) thick j) 12" i/d, ¼" (300 mm i/d 6 mm) thick k) 15" i/d, ¼" (375 mm i/d 6 mm) thick l) 18" i/d, ¼" (450 mm i/d 6 mm) thick m) 20" i/d, ¼" (500 mm i/d 6 mm) thick n) 22" i/d, ¼" (550 mm i/d 6 mm) thick	Per Rft.	56.30 56.30 70.45 70.45 100.50 117.25 117.25 140.75 140.75 172.15 185.65 185.65	316.10 415.80 758.65 914.10 1049.70 1294.65 1468.45 1889.65 2225.75 2747.00 3412.50 3786.05	Per Metre Per Metre	184.65 184.65 231.10 231.10 329.65 329.65 384.60 384.60 461.65 461.65 564.65 608.95	778.05 1036.80 1363.80 2488.40 2998.25 3443.00 4246.50 4816.50 6198.05 7300.45 9010.15 11192.95 12418.15 13599.10			
15	Providing and installing P.V.C. blind pipe, B.S.S. Class `B', in tubewell bore hole, including sockets and solvent and jointing with strainer, etc. complete.							ditto		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND										
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
16	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)  Providing and installing P.V.C. blind pipe, B.S.S. Class	Per Rft.	20.60 23.25 24.35 29.25 38.80 40.50 48.20	173.25 230.75 320.85 487.60 755.70 1046.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	67.50 76.30 79.85 94.55 127.35 132.85 158.10 148.30	390.25 568.30 756.85 1051.00 1599.40 2478.70 3432.85 4084.30				
17	'D', in tubewell bore hole, including sockets and solvent: and jointing with strainer, etc. complete.  a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)  Testing and developing of tubewell of size 6" (150 mm)	Per Rft.	13.30 13.55 14.35 18.10 23.25 24.35 30.00	59.65 85.40 171.70 281.30 407.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	43.70 44.45 47.10 59.30 76.30 79.85 98.45	160.20 195.60 280.15 563.10 922.70 1335.90 1926.05				
18	i/d and above continuously.  i) upto 1.5 cs. discharge  ii) above 1.5 cs. discharge  Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3	Per Hour ditto Per Cft.	21.50	1095.25 1317.30 71.90	CONTRACTOR IN	759.35	1095.25 1317.30 2539.50		The rate includes wastage, etc.		
19	mm), around tubewell in bore hole.  Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc complete in all respects:	ref cit.	21.30	71.50	cu.m	737.33	2337.30	Chap. 2	1) Pipes to be supplied by Government. 2) Providing and installing specials and valves is not included in the rate, which is payable separately.		
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft.		54.05 67.70 80.15 97.45 146.25 171.55 221.80	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		142.75 177.25 222.05 262.85 319.70 479.65 562.65 727.55 960.95				
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:-							ditto	<ol> <li>Pipes to be supplied by Government.</li> <li>Providing and installing specials</li> </ol>		

	MRS, BI-ANNUAL PERIO	D (1st FEE	BRUARY, 2	.013 TO 31st	JULY, 20	)13) DIST	RICT RAWAL	.PIND	
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft.		22.35 32.55 35.85 42.05 58.75 68.80 94.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		66.05 73.25 106.85 117.50 137.90 192.75 225.65 310.20 391.80		and valves is not included in the rate, which is payable separately.
21	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches with Tyton joints, complete in all respects:-  a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	*	9.80 11.25 14.40 16.20 22.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		32.10 36.95 47.30 53.15 72.45 91.30	Chap. 2	Pipes to be supplied by Government.     Providing and installing specials and valves is not included in the rate, which is payable separately.
22	g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d  Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves.	Per Rft. Per Rft. Per Rft.	Suce !	33.15 48.65	Per Metre Per Metre Per Metre		108.75 159.60 191.15	Chap. 2	Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) Light Quality  a) ½" i/d (15 mm) 2mm thick b) ¾" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1¼" i/d (32 mm) 2.65mm thick e) 1½" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"½ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick	Per Rft.	8.45 9.10 10.20 10.30 10.45 11.80 12.35 14.30 15.40	75.90 103.80 133.15 168.05 209.45 283.80 332.55	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	27.65 29.90 33.50 33.85 34.20 38.65 40.55 46.95 50.55	180.45 248.95 340.50 436.75 551.15 686.90 930.90 1090.80 1524.90		
	ii) Medium Quality  a) ½" i/d (15 mm) 2.65mm thick b) ¾" i/d (20 mm) 2.65mm thick c) 1" i/d (25 mm) 3.25mm thick d) 1½" i/d (32 mm) 3.25mm thick e) 1½" i/d (40 mm) 3.25mm thick f) 2" i/d (50 mm) 3.65mm thick g) 2"½ i/d (65 mm) 3.65mm thick	Per Rft.	8.45 9.10 10.20 10.30 10.65 11.80 12.35	81.45 119.50 151.90 174.70 240.15	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	27.65 29.90 33.50 33.85 34.85 38.65 40.55	211.90 267.10 391.90 498.30 573.05 787.70 1002.20		i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia, 3/4"dia & 1/2"dia) for Bath rooms/ Levorotary. ii. For internal G.I piping (1"dia, 3/4"dia & 1/2"dia) Bath room(s)/ Levorotary of rate (composite) shall be

=	MRS, BI-ANNUAL PERIOL	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND									
Sr.	Description	R	ate (British S	System)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
i :	h) 3" i/d (75 mm) 4.05mm thick i) 4" i/d (100 mm) 4.5mm thick j) 5" i/d (150 mm) 4.85mm thick k) 6" i/d (200 mm) 4.85mm thick iii) Heavy Quality	Per Rft. Per Rft. Per Rft. Per Rft.	14.30 15.40 17.90 18.20	546.90 749.70	Per Metre Per Metre Per Metre Per Metre	46.95 50.55 58.65 59.65	1261.15 1793.80 2459.05 2865.80		reduced by 8% and specials mentioned above may be paid at the rates placed on Website as per actual quantity used.		
23	a) ½" i/d (15 mm) 3.25mm thick b) ¾" i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick d) 1½" i/d (32 mm) 4.05mm thick e) 1½" i/d (40 mm) 4.05mm thick f) 2" i/d (50 mm) 4.5mm thick g) 2"½ i/d (65 mm) 4.5mm thick h) 3" i/d (75 mm) 4.85mm thick i) 4" i/d (100 mm) 5.4mm thick j) 5" i/d (125 mm) 5.4mm thick k) 6" i/d (150 mm) 5.4mm thick Providing, laying, cutting, jointing, testing and disinfecting Asbestos cement/Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:	Per Rft.	8.45 9.10 10.20 10.30 10.65 11.80 12.35 14.30 15.40 17.90 18.20	118.55 174.60 227.05 254.75 349.25 437.40 562.20 764.90 946.05		27.65 29.90 33.50 33.85 34.85 38.65 40.55 46.95 50.55 58.65 59.65	300 388.8 572.65 744.7 835.65 1145.5 1434.75 1844 2508.95 3102.95 3664.25	PS 428 & ISO 160	Providing and installing specials and valves is not included in the rate, which is payable separately.		
24	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)  C Class Working Pressure a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (300 mm) g) 14" i/d (300 mm) h) 16" i/d (400 mm) i) 18" i/d (500 mm) h) 16" i/d (400 mm) i) 18" i/d (500 mm) k) 24" i/d (600 mm) C Class Working Pressure	Per Rft.	10.40 11.00 15.15 20.90 27.20 34.60 40.05 45.20 53.35 62.75 75.00 10.40 11.00 15.15 20.90 27.20 34.60 40.05 45.20 53.35 62.75 76.05	259.40 410.30 687.05 936.05 1237.00 1588.20 2018.15 2511.75 3089.80 4263.25 189.40 272.15 468.75 742.35 1034.00 1438.40 2208.25 2819.05 3457.05 4115.10	Per Metre	34.05 36.15 49.70 68.60 89.25 113.55 131.35 148.30 174.95 205.75 245.95 34.05 36.15 49.70 68.60 89.25 113.55 131.35 148.30 174.95 205.75 249.50	892.65 1537.45 2434.90 3391.45 4718.00 7243.05 9246.50 11339.20 13497.50 19001.15	PS 428 & ISO 160			

	MRS, BI-ANNUAL PERIOD	PIND							
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Per Rft. Per Rft. Per Rft. Per Rft.	11.00 15.15 20.90 27.20	589.50 1039.75 1534.25	Per Metre Per Metre Per Metre Per Metre	36.15 49.70 68.60 89.25	1063.75 1933.50 3410.40 5032.40		
	f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	34.60 40.05 45.20 53.35 62.75	3332.05 4302.35 5181.15	Per Metre Per Metre Per Metre Per Metre Per Metre	113.55 131.35 148.30 174.95 205.75	7343.05 10929.05 14111.70 16994.10 20727.20		
26	Providing, laying, cutting, jointing, testing and disinfecting P.V.C. pipe line of B.S.S. with `B' Class working pressure pipe, in trenches, complete in all respects:		×					Chap 2	Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) h) 12" i/d (300 mm) g) 14" i/d (350 mm)	Per Rft.	3.10 3.90 4.80 5.15 7.25 9.45 11.70 14.95		Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	10.20 12.85 15.80 16.80 23.80 31.05 38.35 49.05	339.40 514.70 706.30 992.40 1525.30 2423.85 3378.60 4063.80		
27	Providing, laying, cutting, jointing, testing and disinfecting pipe line in trenches with P.V.C. pipes of B.S.S. with `D' Class working pressure complete in all respects:  a) 2" i/d (50 mm)  b) 3" i/d (75 mm)  c) 4" i/d (100 mm)  d) 5" i/d (125 mm)  e) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.55 3.05 3.85 4.75 5.05	159.75 267.05 395.35	Per Metre Per Metre Per Metre Per Metre Per Metre	8.30 10.00 12.65 15.50 16.50	245.95 523.90 876.00 1296.70 1880.60	ditto	Providing and installing specials and valves is not included in the rate, which is payable separately.
28	Providing and fixing cast iron special of B.S.S. Class `B' (such as bend, tee cross collar, reducer, tail piece flanged spigot, cap, flanged socket, taper, angle branch plug etc.) for cast iron pipe line, complete:-							9.1	i) Labour rates include the cost of jointing material & labour.  ii) The internal dia of the pipe, from which the orange is taken out will
	a) C.I.S.S. Specials, with spigot. and socket joint:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d b) C.I. flanged specials, with flanged and	Per Kg. Per Kg. Per Kg.	19.20 11.00 7.85	101.90 93.65 90.50	Per Kg	19.20 11.00 7.85	101.90 93.65 90.50		be considered the internal dia for the purpose of payments of specials.
	flanged joints:-  i) 3" to 6" (75 to 150 mm) i/d  ii) 8" to 12" (200 to 300 mm) i/d  iii) 15" to 18" (375 to 450 mm) i/d	Per Kg Per Kg Per Kg	8.25 2.30 3.65	90.90 84.95 84.95	Per Kg	8.25 2.30 3.65	90.90 84.95 84.95		

	MRS, BI-ANNUAL PERIO	D (1st FEE	BRUARY, 2	2013 TO 31st	JULY, 20	013) DIST	RICT RAWAL	PIND	
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) C.I. Specials, with tyton joints:-								
	i) 3" to 6" (75 to 150 mm) i/d	Per Kg	10.55	93.25	Per Kg	10.55	93.25		
	ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d	Per Kg Per Kg	10.55 10.55	93.25 93.25	Per Kg Per Kg	10.55 10.55	93.25 93.25		
29	Providing and fixing cast iron specials of B.S.S. Class 'B							9.1	Labour rates include the cost of
2)	(such as bend, tee, cross collar, reducer, tail piece flanged socket, flanged spigot, cap, taper, angle branch.							7.1	jointing material and labour.
	plug, etc) for Asbestos cement pipe line, with comet join								2) The internal dia of the pipe, from
	and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d	Per Kg	11.60	94.30	Per Kg	11.60	94.30		which the branch is taken out, will be considered the internal dia for
	ii) 8" to 18" (200 to 450 mm) i/d	Per Kg Per Kg	6.05	88.75	Per Kg	6.05 4.85	88.75 87.50		the purpose of payment.
		rei Kg	4.85	87.50	Per Kg	4.63	87.30		
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class `B', for cast iron pipe line, and Asbestos	/	,		\			9.1	Labour rates include cost of jointing material and labour.
	cement pipe line (including cost of jointing material):-	. J. L	550.00	5000.00	100	<b>55</b> 0.00	5020.00		
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	570.00 620.25	6030.00 7100.25	Each Each	570.00 620.25	6030.00 7100.25		
	c) 5" i/d (125 mm)	Each	1116.50	8676.50	Each	1116.50	8676.50		
	d) 6" i/d (150 mm)	Each	1190.25	11750.25	Each	1190.25	11750.25		
	e) 8" i/d (200 mm)	Each	1389.75	20709.75	Each	1389.75	20709.75		
	f) 10" i/d (250 mm)	Each	2358.70	26598.70	Each	2358.70	26598.70		
	g) 12" i/d (300 mm)	Each	2650.55	34450.55	Each	2650.55	34450.55		
	h) 16" i/d (400 mm)	Each	3515.50	62915.50	Each	3515.50	62915.50		
	i) 18" i/d (450 mm)	Each	4046.15	110246.15	Each	4046.15	110246.15		
31	Providing and fixing, sluice valve of B.S.S. quality and	780, 190000	DESTRUCTED A	monthean e					Labour rates include cost of jointing
	weight, for Asbestos cement pipe line, with comet join							9.1	material and labour.
	and rubber ring, complete (including cost of jointing								
	materials):-								
	a) 3" i/d (75 mm)	Each	371.30	5051.30	Each	371.30	5051.30		
	b) 4" i/d (100 mm)	Each	457.05	5881.05	Each	457.05	5881.05		
	c) 6" i/d (150 mm)	Each	576.95	9876.95	Each	576.95	9876.95		
	d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Each Each	946.55 1210.30	17986.55 22210.30	Each Each	946.55 1210.30	17986.55 22210.30		
	e) 10" i/d (250 mm) f) 12" i/d (300 mm)	Each	1422.85	27582.85	Each	1422.85	27582.85		
	g) 16" i/d (400 mm)	Each	1684.95	52924.95	Each	1684.95	52924.95		
	h) 18" i/d (450 mm)	Each	2009.05	94409.05	Each	2009.05	94409.05		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2½" (65 mm) dia (including cost of jointing	Each	54.95	4374.95	Each	54.95	4374.95	9.1	Labour rates include cost of jointing material and labour.
	material).								2) Connecting pipes and specials, if used, will be paid extra.
33	Providing and fixing, air valve 2½ (65mm) dia of B.S.S. quality and weight (complete with jointing material)							ditto	
	a) single	Each	116.90	3176.90	Each	116.90	3176.90		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND										
Sr.	Description	R	ate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	b) double	Each	116.90	7076.90	Each	116.90	7076.90				
34	Providing and fitting C.I. flanges on pipes, including turning, threading, facing and fitting, etc. complete in all respects:-							ditto			
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	27.95	102.75	Per Kg	27.95	102.75				
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	17.75	92.55	Per Kg	17.75	92.55				
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	14.90	89.70	Per Kg	14.90	89.70				
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:	Per Inch	×		Per cm i/d						
	a) 3" to 6" (75 to 150 mm) i/d b) 8" to 12" (200 to 300 mm) i/d c) 15" to 18" (375 to 450 mm) i/d	i/d of pipe ditto ditto		50.70 62.90 58.05	of pipe		20.30 25.15 23.20				
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I pipe of B.S.S. 1387-1967 complete in all respects, including specials and valves:-	200	35.7	- ,					Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.		
	i) G.I. flanged joints (Heavy Quality)			0							
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	14.80 14.80 15.95 16.00 18.40 20.70 20.75	256.15 348.35 434.95 557.05 757.40 936.00 1105.55	Per Metre Per Metre Per Metre Per Metre	48.50 48.50 52.25 52.55 60.30 67.90 68.05	840.20 1142.65 1426.60 1827.15 2484.30 3070.10 3626.15				
	ii) C.I. flanged joints (Medium Quality)										
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	16.65 15.70 17.75 17.85 20.35 22.85 22.95	268.20 342.85 427.60 610.05 834.80	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	54.65 51.55 58.30 58.50 66.80 74.90 75.30	649.75 879.75 1124.55 1402.45 2000.95 2738.10 3184.85				
37	Providing and installing P.V.C. bends, of B.S.S.										
	i) Class 'B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm)	Each Each Each	80.45 92.90 116.15	204.05 356.90 632.15	Each	80.45 92.90 116.15	204.05 356.90 632.15				

	MRS, BI-ANNUAL PERIO	) (1st FEE	BRUARY, 2	2013 TO 31st	JULY, 20	013) DIST	RICT RAWAL	.PIND	
Sr.	Description	R	ate (British S	System)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	d) 6" i/d (150 mm)	Each	120.15	882.15	Each	120.15	882.15		
	ii) Class `D' working pressure:-								
	a) 11/4" i/d (30 mm)	Each	52.40	84.80	Each	52.40	84.80		
	b) 1½" i/d (40 mm)	Each	56.60	91.40	Each	56.60	91.40		
	c) 2" i/d (50 mm)	Each	61.40	131.00	Each	61.40	131.00		
	d) 3" i/d (75 mm)	Each	80.45	265.25	Each	80.45	265.25		
	e) 4" i/d (100 mm)	Each	92.90	527.30	Each	92.90	527.30		
	f) 5" i/d (125 mm)	Each	116.15	1112.15	Each	116.15	1112.15		
	g) 6" i/d (150 mm)	Each	120.15	1524.15	Each	120.15	1524.15		
38	Providing and installing P.V.C. tees, of B.S.S.								
	i) Class `B' working pressure:-		/ ×	)					
	a) 3" i/d (80 mm)	Each	120.70	576.70	Each	120.70	576.70		
	b) 4" i/d (100 mm)	Each	141.20	1065.20	Each	141.20	1065.20		
	c) 5" i/d (125 mm)	Each	171.45	2031.45	Each	171.45	2031.45		
	d) 6" i/d (150 mm)	Each	180.20	2100.20	Each	180.20	2100.20		
	ii) Class `D' working pressure:-	1 300							
	a) 11/4" i/d (30 mm)	Each	80.15	206.15	Each	80.15	206.15		
	b) 1½" i/d (40 mm)	Each	85.20	240.00	Each	85.20	240.00		
	c) 2" i/d (50 mm)	Each	91.70	295.70	Each	91.70	295.70		
	d) 3" i/d (75 mm)	Each	120.70	570.70	Each	120.70	570.70		
	e) 4" i/d (100 mm)	Each	141.20	1065.20	Each	141.20	1065.20		
	f) 5" i/d (125 mm)	Each	171.45	2019.45	Each	171.45	2019.45		
	g) 6" i/d (150 mm)	Each	180.20	2088.20	Each	180.20	2088.20		
39	Providing and installing P.V.C. sockets, B.S.S.								
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm)	Each	58.00	139.60	Each	58.00	139.60		
	b) 4" i/d (100 mm)	Each	70.45	214.45	Each	70.45	214.45		
	c) 5" i/d (125 mm)	Each	88.05	286.05	Each	88.05	286.05		
	d) 6" i/d (150 mm)	Each	92.05	368.05	Each	92.05	368.05		
	e) 8" i/d (200 mm)	Each	133.40	769.40	Each	133.40	769.40		
	f) 10" i/d (250 mm)	Each	157.40	1885.40		157.40	1885.40		
	g) 12" i/d (300 mm)	Each	182.05	4142.05	Each	182.05	4142.05		
	h) 14" i/d (350 mm)	Each	204.90	3324.90	Each	204.90	3324.90		
	ii) Class `D' working pressure:-								
	a) 1 <sup>1</sup> / <sub>4</sub> " i/d (30 mm)	Each	33.70	55.30	Each	33.70	55.30		
	b) 1½" i/d (40 mm)	Each	37.90	67.90	Each	37.90	67.90		
	c) 2" i/d (50 mm)	Each	42.70	90.70	Each	42.70	90.70		
	d) 3" i/d (75 mm)	Each	58.00	210.40	Each	58.00	210.40		
	e) 4" i/d (100 mm)	Each	70.45	352.45	Each	70.45	352.45		
	f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each	88.05 92.05	604.05 1004.05	Each Each	88.05 92.05	604.05 1004.05		
	g) 0 1/0 (130 mm)	Eacii	92.03	1004.03	Lacii	92.03	1004.03		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPIND										
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
40	Providing and installing P.V.C. Tapered core, B.S.S.										
	i) Class `B' working pressure:-										
	201:/1/75	Г 1	90.45	120.05	Г 1	00.45	120.05				
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	80.45 92.90	120.05 145.70	Each Each	80.45 92.90	120.05 145.70		1		
	c) 5" i/d (125 mm)	Each	116.15	182.15	Each	116.15	182.15		1		
	d) 6" i/d (150 mm)	Each	120.15	199.35	Each	120.15	199.35				
	e) 8" i/d (200 mm)	Each	170.85	302.85	Each	170.85	302.85				
	f) 10" i/d (250 mm)	Each	194.85	366.45	Each	194.85	366.45				
	g) 12" i/d (300 mm)	Each	226.95	438.15	Each	226.95	438.15				
	h) 14" i/d (350 mm)	Each	249.80	513.80	Each	249.80	513.80				
	ii) Class `D' working pressure:-	/	29	) /							
	a) 1 <sup>1</sup> / <sub>4</sub> " i/d (30 mm)	Each	52.40	71.60	Each	52.40	71.60				
	b) 1½" i/d (40 mm)	Each	56.60	83.00	Each	56.60	83.00				
	c) 2" i/d (50 mm)	Each	61.40	93.80	Each	61.40	93.80				
41	M-1:	1887			7 887				The mate in all decides the common of the		
41	Making connection for new watersupply lines with the running main, including excavation of trench and refilling.	1 300			3.66				The rate includes the component of bailing out water from the trench		
	complete, but excluding cost of pipe and specials, etc	184/	1.15	60 /	1636				and cutting of existing pipe line.		
		N. T.									
	Diameter of running main:	ACT.		500	Day.						
		Per		2	Per						
	i) upto 6" i/d (150 mm)	Connection	1145.10	. Aller S.	Connection	1145.10					
	ii) upto 8" i/d (200 mm)	ditto	1438.15	Dirinart.	ditto	1438.15					
	iii) upto 10" i/d (250 mm) iv) upto 12" i/d (300 mm)	ction ditto	2046.00 2778.60	100	ction ditto	2046.00 2778.60					
	v) upto 16" i/d (400 mm)	ditto	3423.10		ditto	3423.10					
	vi) upto 20" i/d (500 mm)	ditto	4412.10		ditto	4412.10					
	vii) upto 24" i/d (600 mm)	ditto	5313.00		ditto	5313.00					

# 24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Supply and erection of G.I. pipes for wiring purposes, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.										
	a) on surface, including clamps, etc.							38.4			
	i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d vii) 80 mm i/d b) recessed in walls, including hooks, cutting jharries and repairing surface:  i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iii) 25 mm i/d v) 40 mm i/d v) 40 mm i/d vi) 50 mm i/d vi) 50 mm i/d vi) 50 mm i/d vii) 80 mm i/d vii) 80 mm i/d	Per Rft.	14.35 14.35 17.40 17.40 20.70 26.35 20.45 20.45 21.30 21.30 23.25 31.95 51.10	59.65 74.05 96.95 123.15 151.35 187.65 293.85 63.60 78.90 103.00 126.25 155.70 197.95 318.50	Per Metre	47.00 47.00 47.00 57.00 57.00 67.90 86.40 67.05 67.05 69.85 69.85 76.20 104.80 167.65	195.70 242.85 317.90 403.95 496.40 615.45 963.80 208.55 258.75 337.85 414.10 510.60 649.25 1,044.65	38.3			
2	Supply and erection of M.S. conduit pipes for wiring, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.							38.4 & 38.6			
	a) on surface, including clamps, etc.  i) 16 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d b) recessed in walls, including cutting jharries, cost of hooks and repairing surface etc.  i) 16 mm i/d ii) 20 mm i/d	Per Rft.	9.95 9.95 9.95 9.95 11.20 13.80	30.45 35.70 40.90 45.35 57.60 70.35	Per Metre	32.65 32.65 32.65 32.65 36.70 45.20	99.80 117.15 134.10 148.75 188.90 230.80	38.3 & 38.7			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks		
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.			
	iv) 32 mm i/d	Per Rft.	21.30	56.65	Per Metre	69.85	185.80				
	v) 40 mm i/d	Per Rft.	22.20	67.55	Per Metre	72.90	221.55				
	vi) 50 mm i/d	Per Rft.	23.25	80.30	Per Metre	76.20	263.40				
	VI) 50 mm //d	T CI TKIT.	23.23	00.50	T CI TVICUC	70.20	203.40				
3	Supply and erection of PVC pipe for wiring recessed in walls,							38.3 &			
	including inspection boxes, pull boxes, hooks, cutting jharries,							38.5			
	and repairing surface, etc., complete with all specials.										
	i) 12 mm i/d	Per Rft.	16.50	26.85	Per Metre	54.10	88.05				
	ii) 20 mm i/d	Per Rft.	17.05	31.00	Per Metre	55.90	101.70				
	iii) 25 mm i/d	Per Rft.	18.95	36.95	Per Metre	62.10	121.20				
	iv) 32 mm i/d	Per Rft.	20.45	44.95	Per Metre	67.05	147.50				
	v) 40 mm i/d	Per Rft.	21.30	55.05	Per Metre	69.85	180.60				
	vi) 50 mm i/d	Per Rft.	22.20	66.20	Per Metre	72.90	217.20				
	a to the spring to a second				를 냈다.						
4	Supply and erection of PVC pipe for wiring on surface	188 T			J 23						
	including clamps inspection boxes, pull boxes, bends, tees,	300	and the same of th		7 885						
	repairing surface, etc., complete with all specials:-	355	1	(-)	1 2138						
	i) 12 mm i/d	Per Rft.	4.50	15.55	Per Metre	14.70	51.05				
	ii) 20 mm i/d	Per Rft.	4.50	19.10	Per Metre	14.70	62.70				
	iii) 25 mm i/d	Per Rft.	4.50	24.40	Per Metre	14.70	80.00				
	iv) 32 mm i/d	Per Rft.	5.10	32.70	Per Metre	16.80	107.30				
	v) 40 mm i/d	Per Rft.	5.10	43.30	Per Metre	16.80	142.10				
	vi) 50 mm i/d	Per Rft.	6.20	58.25	Per Metre	20.25	191.05				
5	Supply and erection of G.I. flexible pipe for wiring, including welding of sockets, nipples and check nuts, etc. complete:-							38.4			
	i) 12 mm i/d	Don Dft	11.00	55.70	Dan Matua	29.70	192.70				
	i) 12 mm i/d ii) 20 mm i/d	Per Rft. Per Rft.	11.80 12.60	55.70 71.85	Per Metre Per Metre	38.70 41.25	182.70 235.65				
	iii) 25 mm i/d	Per Rft.	13.00	96.05	Per Metre	42.70	315.10				
	iv) 32 mm i/d	Per Rft.	15.75	117.45	Per Metre	51.60	385.20				
	v) 40 mm i/d	Per Rft.	17.15	132.75	Per Metre	56.30	435.50				
	vi) 50 mm i/d	Per Rft.	18.85	172.90	Per Metre	61.90	567.10				
	vii) 80 mm i/d	Per Rft.	25.15	333.75	Per Metre	82.55	1,094.75				
6	Supply and erection PVC pipe for recessed wiring (main and							38.2 &			
	sub-main) purpose, including bends, specials, etc. in floor,							38.3			
	wall or trenches:-										
	50	D 50	22.22		D 14	<b>53</b> 00	222 22				
	i) 50 mm i/d	Per Rft.	22.20	67.85	Per Metre	72.90	222.55				
	ii) 80 mm i/d	Per Rft.	25.55	88.20	Per Metre	83.80	289.30				
	iii) 100 mm i/d	Per Rft.	25.55	113.30	Per Metre	83.80	371.65				
7	Supply and erection of PVC pipe for surface wiring (main and										
′	sub-main) including clamps, inspection boxes, pull boxes										
	bends etc., complete with all specials:-										

	MRS, BI-ANNUAL PERIOD (	(1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DISTI	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	6.20 8.95 10.25	53.15 88.00 110.90	Per Metre Per Metre Per Metre	20.25 29.35 33.55	174.30 288.65 363.80		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	1.80	4.00	Per Metre	5.85	13.15	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	1.80	13.00	Per Metre	5.85	42.65	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):-  a) 250/440 volts, PVC insulated:  i) 3/0.74 mm (3/0.029")  ii) 3/0.91 mm (3/0.036")  iii) 7/0.74 mm (7/0.029")  iv) 7/0.91 mm (7/0.036")  v) 7/1.12 mm (7/0.044")  vi) 7/1.63 mm (19/0.052")  viii) 19/1.63 mm (19/0.064")  b) 250/440 volts, PVC insulated cotton braided and compounded cables:-  i) 3/0.74 mm (3/0.029")  ii) 3/0.91 mm (3/0.036")  iii) 7/0.74 mm (7/0.029")  iv) 7/0.91 mm (7/0.036")  v) 7/1.12 mm (7/0.036")  v) 7/1.12 mm (7/0.044")	Per Rft.	3.60 3.60 3.60 4.00 4.50 5.50 12.40 14.50 4.00 4.00 4.20 4.70	9.80 10.25 13.95 20.60 29.40 71.15 114.85 157.25 10.20 10.65 14.35 20.85 29.65	Per Metre	11.75 11.75 11.75 13.05 14.70 18.05 40.75 47.50 13.05 13.05 13.05 13.80 15.45	32.20 33.55 45.80 67.55 96.45 233.40 376.75 515.80 33.50 34.85 47.10 68.35 97.20	38.1	
11	vi) 7/1.63 mm (7/0.064")  Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):-  i) 3/0.74 mm (3/0.029")  ii) 3/0.91 mm (3/0.036")  iii) 7/0.74 mm (7/0.029")  iv) 7/0.91 mm (7/0.036")  v) 7/1.12 mm (7/0.044")	Per Rft.  Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.60 3.60 3.60 4.00 4.50	9.40 12.30 16.45 23.50 33.15	Per Metre	17.80 11.75 11.75 11.75 13.05 14.70	30.85 40.35 54.00 77.10 108.70		

	MRS, BI-ANNUAL PERIOD (	1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DISTI	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.50	64.90	Per Metre	18.05	212.95		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in							38.1 to	
	prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-							38.7	
	i) 7/1.63 mm (7/0.064")	Per Rft.	5.45	73.30	Per Metre	17.80	240.45		
	ii) 19/1.32 mm (19/0.052")	Per Rft.	5.95	123.20	Per Metre	19.60	404.20		
	iii) 19/1.63 mm (19/0.064")	Per Rft.	6.50	166.55	Per Metre	21.35	546.30		
	iv) 19/2.11 mm (19/0.083")	Per Rft.	7.15	317.80	Per Metre	23.50	1,042.35		
	v) 37//1.83 mm (37/0.072")	Per Rft.	12.35	441.45	Per Metre	40.50	1,448.00		
	vi) 37/2.11 mm (37/0.083")	Per Rft.	14.90	553.90	Per Metre	48.95	1,816.75		
	vii) 37/2.62 mm (37/0.103")	Per Rft.	21.05	849.65	Per Metre	69.10	2,786.90		
13	Supply and erection of copper conductor cables for service	. J. L			Hw.			ditto	
	connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for	188 F			7 887				
	cable only):-	7 34	10000		1 700				
	a) PVC insulated, PVC sheathed twin core, 250/440 volts.	1997	1-6	- 190/	19				
	i) 3/0.74 mm (3/0.029")	Per Rft.	4.00	16.85	Per Metre	13.05	55.30		
	ii) 3/0.91 mm (3/0.036")	Per Rft.	4.00	23.50	Per Metre	13.05	77.10		
	iii) 7/0.74 mm (7/0.029")	Per Rft.	4.00	31.80	Per Metre	13.05	104.35		
	iv) 7/0.91 mm (7/0.036")	Per Rft.	4.20	46.20	Per Metre	13.80	151.45		
	v) 7/1.12 mm (7/0.044")	Per Rft.	4.70	65.35	Per Metre	15.45	214.40		
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.45	129.70	Per Metre	17.80	425.35		
	b) PVC insulated, PVC sheathed 3 core,								
	660/1100 volt cable:-								
	i) 3/0.74 mm (3/0.029")	Per Rft.	4.20	25.00	Per Metre	13.80	81.95		
	ii) 3/0.91 mm (3/0.036")	Per Rft.	4.20	35.35	Per Metre	13.80	116.00		
	iii) 7/0.74 mm (7/0.029")	Per Rft.	4.20	47.85	Per Metre	13.80	156.90		
	iv) 7/0.91 mm (7/0.036")	Per Rft.	4.70	69.70	Per Metre	15.45	228.65		
	v) 7/1.12 mm (7/0.044")	Per Rft.	5.00	99.20	Per Metre	16.30	325.35		
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.70	200.30	Per Metre	18.65	656.95		
	c) PVC insulated, PVC sheathed 4 core,								
	660/1100 volt non armoured cable:-								
	i) 3/0.74 mm (3/0.029")	Per Rft.	4.50	31.90	Per Metre	14.70	104.60		
	ii) 3/0.91 mm (3/0.036")	Per Rft.	4.50	44.35	Per Metre	14.70	145.50		
	iii) 7/0.74 mm (7/0.029")	Per Rft.	4.70	60.65	Per Metre	15.45	199.00		
	iv) 7/0.91 mm (7/0.036")	Per Rft.	4.70	89.45	Per Metre	15.45	293.45		
	v) 7/1.12 mm (7/0.044")	Per Rft.	5.00	128.40	Per Metre	16.30	421.15		
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.70	260.75	Per Metre	18.65	855.30		
	vii) 19/1.32 mm (19/0.052")	Per Rft.	7.95	486.45	Per Metre	26.10	1,595.55		
	d) PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable.								Cost of trenches where necessary

Second		MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DISTI	RICT RAWA	LPINDI	
A support with G.I. wire 16 SWG,   194 SZ mm (190.052")   194 SZ m		Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
19   19   13 mm (1900.052")   Per Rf.   7.95   542.40   Per Metre   26.10   1,779.05   Per Rf.   19   19   18 mm (1900.072")   Per Rf.   8.95   794.80   Per Metre   29.35   3,219.50   Per Metre   20.35   P	No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
iii) 191.63 mm (190.054*)		armoured with G.I. wire 16 SWG.								is included in the rates.
iii) 191.63 mm (190.054*)		i) 19/1 32 mm (19/0 052")	Per Rft	7 95	542 40	Per Metre	26 10	1 779 05		
iii) 19/183 mm (190/072*)								· ·		
vi y   92-11 mm (190.083')										
v) 377/183 mm (370,072")   Per Rft   9.95   1,870.80   Per Mere   20.5   6,136.25     vi								· ·		
vi) 372.41 mm (370.0887)										
vii) 37/2.62 mm (370,093")   Per Rft.   14.35   2.882.35   Per Metre   47.00   9.454.05     viii) 37/2.62 mm (370,093")   Per Rft.   17.90   3.587.40   Per Metre   58.75   11.766.65     38.1   deep, with 4.75 mm thick (316") bakelites sheet top, for recessed wirting, including making holes for regulators, switches, plugs, etc.     0   10 x 10 cm (4"x4")   Each   73.45   166.60   Each   73.45   166.60     iii) 72.5 x 10 cm (7"x4")   Each   47.90   32.75   Each   11.750   31.275     vi > 20 x 25 cm (8"x10")   Fach   146.85   144.15     vi > 30 x 55 cm (12"x14")   Each   17.50   31.275   Each   146.85   144.15     vi > 30 x 55 cm (12"x14")   Each   15.80     vi > 30 x 55 cm (12"x14")   Each   16.80   29.60     vi > 20 x 25 cm (8"x10")   Vi = 1.80     vi > 20 x 25 cm										
Viii)   372,62 mm (370,103")   Per Rft.   17,90   3,587,40   Per Metre   58,75   11,766,65   38,1     48   Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")   deep, with 475 mm thick, (570) shadelite sheet top, for recessed wiring, including making holes for regulators, switches, plugs, etc.   i) 10 x 10 cm (4"x4")   Each   73,45   166,60   18ch   73,45   166,60   17,45   166,60   17,47   18ch   73,45   166,60   17,47   18ch   73,45   166,60   17,47   18ch   73,45   166,60   17,47   18ch   73,45   166,60   18ch   73,45   166,60   18ch   73,45   166,60   17,50   12,20   18ch   79,90   21,220   18ch   17,50   312,75   18ch   117,50   312,75   18ch   117								· ·		
deep, with 4.75 mm thick (316°) backelite sheet top, for recessed writing, including making holes for regulators, switches, plugs, etc.   i) 10 x 10 cm (4°x4°)   Each   73.45   166.60   Each   73.45   Each   17.50   312.75   Supply and receion of round block of Sahl wood, 10x4 cm   Each   105.80   538.10   Each   105.80   538.10   Each   105.80								· · · · · · · · · · · · · · · · · · ·		
recessed writing, including making holes for regulators, switches, plags, etc.	14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")							38.1	
Switches, plugs, etc.				11					to	
Fach   58.75   125.05   Each   73.45   166.60   Each   117.50   312.75   Each   146.85   414.15   Each   146.85   414.15   Each   146.85   414.15   Each   16.80   Each   195.80   538.10   Each   195.80   538.10   Each   195.80   Each   195				~	100	\			38.7	
ii) 17.5 x 10 cm (7"x4")   Each   97.90   212.20   Each   97.90   212.20   Each   97.90   212.20     iv) 20 x 25 cm (8"x10")   Each   17.5 v   312.75   Each   146.85   414.15     iv) 20 x 25 cm (10"x12")   Each   16.80   29.60   Each   117.50   312.75     iv) 30 x 35 cm (12"x14")   Each   16.80   29.60   Each   16.80   29.60     iv) 20 x 25 cm (8"x10")   Each   16.80   29.60   Each   16.80   29.60     iv) 20 x 25 cm (8"x10")   Each   23.50   78.90     iv) 20 x 25 cm (8"x10")   Each   23.50   90.90     iv) 25 x 30 cm (10"x12")   Each   23.50   199.55     iv) 25 x 30 cm (10"x12")   Each   23.50   79.95     iv) 25 x 30 cm (10"x12")   Each   23.50   77.10     iv) 25 x 30 cm (10"x12")   E		switches, plugs, etc.	. /			1				
ii) 17.5 x 10 cm (7"x4")   Each   97.90   212.20   Each   97.90   212.20   Each   97.90   212.20     iv) 20 x 25 cm (8"x10")   Each   17.5 v   312.75   Each   146.85   414.15     iv) 20 x 25 cm (10"x12")   Each   16.80   29.60   Each   117.50   312.75     iv) 30 x 35 cm (12"x14")   Each   16.80   29.60   Each   16.80   29.60     iv) 20 x 25 cm (8"x10")   Each   16.80   29.60   Each   16.80   29.60     iv) 20 x 25 cm (8"x10")   Each   23.50   78.90     iv) 20 x 25 cm (8"x10")   Each   23.50   90.90     iv) 25 x 30 cm (10"x12")   Each   23.50   199.55     iv) 25 x 30 cm (10"x12")   Each   23.50   79.95     iv) 25 x 30 cm (10"x12")   Each   23.50   77.10     iv) 25 x 30 cm (10"x12")   E		:) 10 (4"4")	To de	50.75	125.05	- Hii.	50.75	125.05		
iii) 22.5 x 10 cm (9"x4")										
Fach   117.50   312.75   Fach   117.50   312.75   Fach   117.50   312.75   Fach   144.15   Fach   146.85   414.15   Fach   146.15   Fach   146.					The second secon	7 300.4				
V  25 x 30 cm (10"x12")   Each   146.85   414.15   Each   195.80   538.10   Each   195.80   Each   235.0			A REST OF THE REST			V 100 HE				
Supply and erection of round block of Sahl wood, 10x4 cm (4"x1½") thick.   Each   16.80   29.60   Each   23.50			All the second	The second second		77143				
15   Supply and erection of round block of Sahl wood, 10x4 cm						and the second second				
(4"x1½") thick.		(VI) 50 X 55 CIII (12 X14 )	Eacii	193.80	338.10	Eacii	193.80	336.10		
(4"x1½") thick.	15	Supply and erection of round block of Sahl wood, 10x4 cm	Each	16.80	29.60	Each	16.80	29.60	38.1	
16   Supply and erection of teak wood board, 4.5 cm (1¾") thick.			ARTES		1070 Commercial according	landa and a second				
i) 17.5 x 10 cm (7"x4") ii) 22.5 x 10 cm (0"x4") iii) 20 x 25 cm (8"x10") iii) 22.5 x 10 cm (0"x12") iii) 22.5 x 10 cm (0"x4") iii) 20 x 25 cm (8"x10") iii) 20 x 25 cm			78, 12,112	TOTAL CAS	alog goals i					
ii) 22.5 x 10 cm (9"x4")	16	Supply and erection of teak wood board, 4.5 cm (1¾") thick.							38.1	
Fach   26.10   106.70   Each   29.35   146.15   Each   29.35   199.55   Each   29.35   199.55   Each   20.35   Each		i) 17.5 x 10 cm (7"x4")	Each	23.50	78.90	Each	23.50	78.90		
iv) 25 x 30 cm (10"x12")		ii) 22.5 x 10 cm (9"x4")	Each	23.50	90.90	Each	23.50	90.90		
Supply and erection of Sahl wood board, 4.5 cm (134") thick.   Each   33.55   199.55   Each   33.55   199.55   Each   33.55   199.55		iii) 20 x 25 cm (8"x10")	Each	26.10	106.70	Each	26.10	106.70		
Supply and erection of Sahl wood board, 4.5 cm (1¾") thick.   Each   23.50   59.10   Each   23.50   59.10   Each   23.50   77.10   Each   23.50   Each   29.35   Each		iv) 25 x 30 cm (10"x12")	Each	29.35	146.15	Each	29.35	146.15		
i) 17.5 x 10 cm (7"x4") ii) 22.5 x 10 cm (9"x4") iii) 20 x 25 cm (8"x10") iii) 20 x 25 cm (8"x10") iii) 20 x 25 cm (8"x10") Each 23.50 77.10 Each 23.50 77.10 Each 23.50 77.10 Each 23.50 77.10 Each 26.10 91.10 Each 29.35 109.95 v) 30 x 35 cm (12"x14") Each 33.55 130.35  Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.  a) double pole:  Each 23.50 77.10 Each 25.50 For 0.09.95 Each 29.35 130.35  When the base frame is already installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 350.80.		v) 30 x 35 cm (12"x14")	Each	33.55	199.55	Each	33.55	199.55		
ii)   22.5 x 10 cm (9"x4")   Each   23.50   77.10   Each   23.50   77.10     iii)   20 x 25 cm (8"x10")   Each   26.10   91.10     iv)   25 x 30 cm (10"x12")   Each   29.35   109.95     v)   30 x 35 cm (12"x14")   Each   33.55   130.35      18   Supply and erection of iron/aluminum clad, 500 volts main   switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth   with necessary flexible pipe and thimbles, etc.   38.1   When the base frame is already   installed, the labour and composite   rates will be reduced as follows:- For   with necessary flexible pipe and thimbles, etc.   15 to 35 Amps. by Rs. 21.20 and Rs.     a)   double pole:   38.80 and Rs. 252.60. For 100 Amps.   by Rs. 38.80 and Rs. 350.80.	17	Supply and erection of Sahl wood board, 4.5 cm (1¾") thick.								
ii)   22.5 x 10 cm (9"x4")   Each   23.50   77.10   Each   23.50   77.10     iii)   20 x 25 cm (8"x10")   Each   26.10   91.10     iv)   25 x 30 cm (10"x12")   Each   29.35   109.95     v)   30 x 35 cm (12"x14")   Each   33.55   130.35      18   Supply and erection of iron/aluminum clad, 500 volts main   switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth   with necessary flexible pipe and thimbles, etc.   38.1   When the base frame is already   installed, the labour and composite   rates will be reduced as follows:- For   with necessary flexible pipe and thimbles, etc.   15 to 35 Amps. by Rs. 21.20 and Rs.     a)   double pole:   38.80 and Rs. 252.60. For 100 Amps.   by Rs. 38.80 and Rs. 350.80.		i) 17.5 x 10 cm (7"x4")	Each	23.50	59.10	Each	23.50	59.10		
Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.   Supply and composite rates will be reduced as follows: For with necessary flexible pipe:   Supply and composite rates will be reduced as follows: For double pole:   Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.   Supply and erection of iron/aluminum clad, 500 volts main salready installed, the labour and composite rates will be reduced as follows: For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.										
iv) 25 x 30 cm (10"x12") v) 30 x 35 cm (12"x14")  Each 29.35 v) 30 x 35 cm (12"x14")  Each 29.35 Ea		, , ,								
v) 30 x 35 cm (12"x14")  Each 33.55 130.35 Each 33.55 130.35  Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.  a) double pole:  Bach 33.55 130.35 Each 33.55 130.35  When the base frame is already installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.										
switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.  a) double pole:  switches with kitkat fuses, on angle iron board with 3 mm installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.		, , ,								
(1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc.  a) double pole:  a) double pole:  rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.	18								38.1	
with necessary flexible pipe and thimbles, etc.  15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.										
145.50. For 60 to 65 Amps. by Rs. a) double pole: 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.										
a) double pole:  38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.		with necessary flexible pipe and thimbles, etc.								
		a) double pole:								38.80 and Rs. 252.60. For 100 Amps.
		i) 15/20 Amp.	Each	391.60	1,411.90	Each	391.60	1,411.90		by Ks. 30.00 and Ks. 330.00.

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	)13) DISTI	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 30/35 Amp. iii) 60/65 Amp. iv) 100 Amp.	Each Each Each	391.60 587.40 587.40	1,693.90 2,199.90 2,739.90	Each Each Each	391.60 587.40 587.40	1,693.90 2,199.90 2,739.90		
	b) triple pole: i) 15/20 Amp. ii) 30/35 Amp.	Each Each	587.40 391.60	1,925.70 2,149.90	Each Each	587.40 391.60	1,925.70 2,149.90		
	c) triple pole with neutral link:  i) 30/35 Amp.  ii) 60/65 Amp.  iii) 100 Amp.	Each Each Each	391.60 587.40 742.90	2,317.90 2,921.10 3,574.60	Each Each Each	391.60 587.40 742.90	2,317.90 2,921.10 3,574.60		
19	Supply and erection of iron/aluminum clad, 500 volts main switches with triple pole and neutral link and HRC fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles.	F						38.1	When the base frame is already installed, the labour & composite rates will be reduced as follows:-  i) For 60/65 Amp. by Rs. 21.20 and
	60/65 Amp 100 Amp 150 Amp 200 Amp 300 Amp 400 Amp 500 Amp	Each Each Each Each Each Each	587.40 742.90 742.90 1,676.40 1,676.40 2,346.30 2,514.60	2,968.80 4,132.30 5,651.50 9,069.00 10,437.00 14,023.50 17,870.00	Each Each Each Each Each Each Each	587.40 742.90 742.90 1,676.40 1,676.40 2,346.30 2,514.60	2,968.80 4,132.30 5,651.50 9,069.00 10,437.00 14,023.50 17,870.00		Rs. 145.50. ii) For 100 to 300 Amp. by Rs. 21.20 and Rs. 350.80 iii) For 400 to 500 Amp. by Rs. 42.20 and Rs. 526.20
20	Supply and erection of iron/aluminum clad, branch distribution board, 250 volt, on angle iron frame of suitable size with 3 mm (1/8") M.S. sheet covering:							ditto	When the base frame is already installed the labour and composite rates will be reduced by Rs. 19.50 & Rs. 152.20 respectively.
	i) 2 way, 15 Amp per way ii) 3 way, 15 Amp per way iii) 4 way, 15 Amp per way iv) 5 way, 15 Amp per way v) 6 way, 15 Amp per way vi) 7 way, 15 Amp per way vii) 8 way, 15 Amp per way viii) 9 way, 15 Amp per way viii) 9 way, 15 Amp per way ix) 10 way, 15 Amp per way x) 11 way, 15 Amp per way x) 11 way, 15 Amp per way xi) 12 way, 15 Amp per way xii) 2 way, 30 Amp per way xiii) 3 way, 30 Amp per way xiv) 4 way, 30 Amp per way xv) 5 way, 30 Amp per way xvi) 6 way, 30 Amp per way	Each Each Each Each Each Each Each Each	195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 293.70 293.70 293.70 293.70	591.20 591.20 663.20 723.20 765.20 819.20 867.20 921.20 999.20 1,059.20 1,113.20 689.10 695.10 755.10 821.10 863.10	Each Each Each Each Each Each Each Each	195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 195.80 293.70 293.70 293.70 293.70	591.20 591.20 663.20 723.20 765.20 819.20 867.20 921.20 999.20 1,059.20 1,113.20 689.10 695.10 755.10 821.10 863.10		RS. 152.20 respectively.

	MRS, BI-ANNUAL PERIOD (	1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DIST	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	xviii 8 way, 30 Amp per way	Each	293.70	983.10	Each	293.70	983.10		
	xix) 9 way, 30 Amp per way	Each	293.70	1,031.10	Each	293.70	1,031.10		
	xx) 10 way, 30 Amp per way	Each	293.70	1,115.10	Each	293.70	1,115.10		
21	Supply and erection of bus bars, for 500 volts 3 phase A.C. supply with four copper bars, including glazed porcelain							38.1	When the base frame is already installed the labour and composite
	bridges, on angle iron board, fixed with rag bolts and M.S. sheet box 1.5 mm thick, etc. complete:-							3311	rates will be reduced by Rs. 21.20 and Rs. 145.50 respectively.
	i) 60 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm)	Each	749.10	2,789.40	Each	749.10	2,789.40		
	ii) 100 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm)	Each	749.10	2,789.40	Each	749.10	2,789.40		
	iii) 200 Amp with 4 copper bars size 2"x1/8" (50x 3 mm)	Each	1,161.60	3,297.90	Each	1,161.60	3,297.90		
	iv) 300 Amp with 4 copper bars	Each	1,343.10	3,479.40	Each	1,343.10	3,479.40		
	size 2"x3/16" (50x 5 mm) v) 500 Amp with 4 copper	Each	917.40	3,641.80	Each	917.40	3,641.80		
	size 2"x1/4" (50x 6 mm)	647	1.6	/ جزمت	45				
22	i) Supply and erection of plain pendent lamp holder, complete with bakelite lamp holder and flexible twin wire 23/0.0076" upto 2 metre length (without bulb and shade).	Each	14.05	103.45	Each	14.05	103.45	38.1	
	ii) Extra for additional length of flexible wire, beyond 2 metres.	Per Rft.	antar (	1.65	Per Metre		5.45		
23	Supply and erection of counter weight pedent with porcelain counter weight, and fitting on bakelite lamp holder, with flexible twin wire 23/0.0076" complete (without bulb and shade).	Each	28.05	231.20	Each	28.05	231.20	38.1	
24	Supply and erection of stiff pedent with brass/metal pipe 6.3 cm (2.5") long, and 15 mm (½") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm (3/0.029").	Each	38.70	379.50	Each	38.70	379.50	ditto	
25	Supply and erection of 22.5 cm (9") long swan neck plain brass/steel brass oxidised bracket lamp holder, complete.	Each	40.05	103.05	Each	40.05	103.05	ditto	
26	Supply and erection of wall type/pole type bracket, with double cover water tight reflector, flexible wire and brass bolder.	Each	55.30	407.65	Each	55.30	407.65	ditto	
27	Supply and erection of bakelite button holder shade, large size.	Each	9.15	45.85	Each	9.15	45.85	ditto	
28	Supply and erection of call bell 220/250 volts, fixed on teak wood board 17.5x10 cm (7"x4").	Each	38.70	217.10	Each	38.70	217.10	38.1	

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DIST	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	8.40	205.00	Each	8.40	205.00	38.1	
30	Supply and erection of ceiling rose, bakelite.	Each	14.05	33.40	Each	14.05	33.40	ditto	
31	Supply and erection of switches 5 Amp.								
	i) open type ii) piano type iii) ring type, recessed iv) plate type, recessed v) double control, open type vi) double control, ring type recessed vii) double control, piano type	Each Each Each Each Each Each	13.45 13.45 13.45 13.45 18.10 18.10	30.40 30.40 25.45 47.20 46.30 40.30 41.50	Each Each Each Each Each Each Each	13.45 13.45 13.45 13.45 18.10 18.10	30.40 30.40 25.45 47.20 46.30 40.30 41.50	ditto	
32	Supply and erection of switches 10/15 Amp.	& E			14			ditto	
	i) open type ii) recessed type	Each Each	13.45 13.45	39.25 48.85	Each Each	13.45 13.45	39.25 48.85		
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	13.45	75.25	Each	13.45	75.25	ditto	
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	13.45	51.25	Each	13.45	51.25	ditto	
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.	· Ir man	ance (	I))epocri				ditto	
	i) open type ii) recessed type	Each Each	13.45 13.45	45.25 81.25	Each Each	13.45 13.45	45.25 81.25		
36	Supply and erection of 3 pin switch and plug combined, recessed type.							ditto	
	i) 5 Amp ii) 10/15 Amp	Each Each	13.45 13.45	65.05 89.95	Each Each	13.45 13.45	65.05 89.95		
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe, open type.	Each	13.45	141.25	Each	13.45	141.25	ditto	
38	Supply and erection of cut out, bakelite.							ditto	
	i) open type ii) recessed type	Each Each	7.50 7.50	33.30 39.30	Each Each	7.50 7.50	33.30 39.30		
39	Supply and erection of button holder.							38.1	
	i) bakelite large size ii) brass	Each Each	8.40 8.40	27.00 39.00	Each Each	8.40 8.40	27.00 39.00		
40	Supply and erection of brass bracket with holder.	Each	11.20	41.80	Each	11.20	41.80	ditto	

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	013 TO 31st	t JULY, 20	013) DISTI	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	7.50	27.30	Each	7.50	27.30	ditto	
42	Supply and erection of kitkat, 500 volt:							ditto	
43	i) 15/20 Amp ii) 30/35 Amp iii) 60/65 Amp iv) 100 Amp v) 200 Amp vi) 300 Amp vii) 400 Amp viii) 500 Amp Supply and erection of tube light, including rod, choke, starter	Each Each Each Each Each Each Each Each	13.25 14.45 22.10 24.85 28.40 28.40 36.70 36.70	44.75 45.95 67.10 111.85 151.40 307.40 381.70 552.70	Each Each Each Each Each Each Each Each	13.25 14.45 22.10 24.85 28.40 28.40 36.70 36.70	44.75 45.95 67.10 111.85 151.40 307.40 381.70 552.70	38.1	
	with frame, flexible wire, including connection from ceiling rose, etc., complete.	8 F		50	7 8				
	i) double rod (80 watts) with two chokes and 2 starters.	Per set	229.35	1,159.65	Per set	229.35	1,159.65		
	ii) single rod (40 watts) with one choke and one starter.	ditto	183.50	609.75	ditto	183.50	609.75		
	iii) round tube, 32 watt, with one choke and one starter, without cover.	Each	183.50	666.15	Each	183.50	666.15		
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	152.90	755.60	ditto	152.90	755.60		
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking arrangement, including painting:- i) 60x35x15 cm (24"x14"x6")	Each	479.75	2,238.90	Each	479.75	2,238.90	ditto	
	ii) 95x40x20 cm (38"x16"x8") iii) 105x52.5x22.5 cm (42"x21"x9") iv) 135x70x27.5 cm (54"x28"x11")	Each Each Each	695.75 1,058.75 1,169.85	2,800.15 3,868.95 5,575.45	Each Each Each	695.75 1,058.75 1,169.85	2,800.15 3,868.95 5,575.45		
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate 25x6 mm (1"x1/4"), with bolts and nuts for hanging ceiling fans.	Each	30.60	142.20	Each	30.60	142.20	38.1 & 38.10	
46	Supply and erection of girder strut, of M.S. tee section 40x40x6 mm (1½"1½"x ½"), complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	38.70	850.25	Each	38.70	850.25	ditto	
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with 75x40x3 mm (3"x1½"x1/8") M.S. steel channel, with clamp, bolts and nuts, etc., including fixing with cement	Each	41.50	1,184.15	Each	41.50	1,184.15	38.1	

	MRS, BI-ANNUAL PERIOD (	1st FEB	RUARY, 2	013 TO 31s	t JULY, 20	13) DIST	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	concrete 1:3:6.								
48	Supply and erection of roof suspension hook of M.S plate 75x40x12.7mm (3"x1½"x½") with 16 mm (5/8") hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Each	55.30	482.90	Each	55.30	482.90		
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	17.25	34.05	Each	17.25	34.05	ditto	
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	466.20	2,129.70	Each	466.20	2,129.70	38.12	
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x¼") section:-	# =			144				
	i) 0.60 metre (2') long for 2 lines. ii) 1.200 metre (4') long for 4 lines.	Each Each	120.20 140.25	553.85 1,146.50	Each Each	120.20 140.25	553.85 1,146.50		
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.	Per Rft.	7.20	20.25	Per Metre	23.55	66.50	38.14	
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	10.25	31.50	Per Metre	33.55	103.35	ditto	
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line,include shackle insulator for holding insulated wire and straining devices for bearer wire and other accessories etc., complete.	Per Rft.	42.60	241.95	Per Metre	139.70	793.60		
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	41.90	239.85	Per Metre	137.50	786.75		
56	Supply and erection of lightning arrestor horn type, complete.	Each	232.30	2,392.30	Each	232.30	2,392.30		
57	Supply and erection of shackle insulator, medium size.	Each	31.75	193.75	Each	31.75	193.75	38.12	
58	Supply and erection of pin insulator, green medium size.	Each	31.75	79.75	Each	31.75	79.75	ditto	
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	16.50	1,040.10	Per Kg	16.50	1,040.10	38.1	
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire.	Per Kg	16.50	104.10	Per Kg	16.50	104.10	ditto	

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DIST	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
61	pole to pole etc.  Wiring overhead line in 2 single core, PVC/weather proof cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.							38.12	
62	i) 3/0.74 mm (3/0.029") ii) 7/0.74 mm (7/0.029") iii) 7/0.91 mm (7/0.036") iv) 7/1.12 mm (7/0.044")  Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft. ditto ditto ditto Per Rft.	3.95 3.95 3.95 3.95 7.90	11.40 19.55 26.00 34.85 20.80	Per Metre ditto ditto ditto	12.90 12.90 12.90 12.90 25.90	37.45 64.10 85.25 114.35	38.1	
63 64	Supply and erection of street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp.  Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):	Each	193.60	933.50	Each	193.60	933.50		
	i) G.E.C. design ii) Philips design	Each ditto	387.20 387.20	2,739.20 3,111.20	Each ditto	387.20 387.20	2,739.20 3,111.20		
65	Supply and fitting of mercury vapour lamp, complete with choke set.  i) 125 watt lamp  ii) 250 watt lamp	Each ditto	152.90 183.50	1,052.90 1,923.50	Each ditto	152.90 183.50	1,052.90 1,923.50		
66	Manufacture and erection of angle iron lattice steel structure pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1½"x1½"x3/16" (30x30x5 mm) angle iron legs and ¾"x¾"1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1¾"x1¾"x3/16"(45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x½" (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.	Each	6,672.55	22,546.65	Each	6,672.55	22,546.65	38.13	The composite rate will be reduced or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per	Each	6,256.85	34,423.15	Each	6,256.85	34,423.15	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.

	MRS, BI-ANNUAL PERIOD	1st FEB	RUARY, 2	2013 TO 31s	t JULY, 20	13) DIST	RICT RAWA	LPINDI	
Sr.	Description	R	ate (British S	System)	Rate	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3½'x3½' (2400x1050x1050 mm), etc. complete in all respects.								
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (½") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	825.00	3,614.70	Job	825.00	3,614.70		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in 15 mm (½") dia G.I. pipe, best quality:- i) on surface, including clamps, etc. ii) recessed in wall, including hooks,	Per Rft.	8.85 20.10	52.95 65.10	Per Metre	29.05 66.00	173.70 213.60	38.11	
70	jharries and making good surface.  Bonding to earth with wire on surface, including cost of wire,	# F			7	30.00	210100	ditto	
	clamps, thimbles, etc. a) G.I. wire:	60 m	\$ 5	- 1° /	1030				
	i) 8 SWG ii) 16 SWG	Per Rft. ditto	4.10 4.10	9.70 5.65	Per Metre ditto	13.45 13.45	31.75 18.60		
	b) Copper wire:	'Ar William	ance (	IDEPART	ing and T				
	i) 16 SWG ii) 20 SWG	Per Rft. ditto	4.10 4.10	11.15 6.80	Per Metre ditto	13.45 13.45	36.60 22.35		
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	14.15	18.60	Per Metre	46.45	61.00	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	550.00	4,317.15	Each	550.00	4,317.15	ditto	
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.								
	i) tape 40x3 mm (1½"x1/8") ii) tape 50x3 mm (2"x1/8")	Per Rft. ditto	20.10 20.10	254.55 303.45	Per Metre ditto	66.00 66.00	835.00 995.30		
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	387.20	2,655.20	Job	387.20	2,655.20		
75	Supply and erection of electric energy meter, including meter testing fee, etc.							38.1	

Sr.	Description	R	ate (British S	System)	Ra	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) single phase:								
	i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts	Each ditto	168.30 168.30	2,246.70 2,246.70	Each ditto	168.30 168.30	2,246.70 2,246.70		
	b) three phase, 4 wires:								
	i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts	Each ditto ditto	336.60 458.70 458.70	5,933.40 6,055.50 6,055.50	Each ditto ditto	336.60 458.70 458.70	5,933.40 6,055.50 6,055.50		
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.	1.							The credit of out turn of dismantled material has been accounted for in the rate.
	<ul><li>i) 1200 mm (48") sweep, 275-300 RPM.</li><li>ii) 1400 mm (56") sweep, 250-275 RPM.</li></ul>	Each ditto	313.50 344.05	913.50 1,046.65	Each ditto	313.50 344.05	913.50 1,046.65		
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.	B.	14	(عاد ت					The credit of out turn of dismantled material has been accounted for in the rate.
	i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM	Each ditto	224.40 224.40	640.80 719.40	Each ditto	224.40 224.40	640.80 719.40		
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	269.30	836.30	Each	269.30	836.30		The credit of out turn of dismantled material has been accounted for in the rate.
79	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	42.10	102.10	Each	42.10	102.10	38.1	me rate.
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	33.65	57.65	Each	33.65	57.65	ditto	
81	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	42.10	162.10	Each	42.10	162.10	ditto	
82	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	84.15	194.55	Each	84.15	194.55		The credit out turn of dismantled material has been accounted for in the rate.
83	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	149.00	186.05	Each	149.00	186.05		me ide.

## 25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31st	JULY, 2	013) DIS	TRICT RAW	ALPINDI	
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Railway Track, etc.								
1	Laying, linking and packing tramway line.	100Lft.	1263.45		Metre	41.45			
2	Dismantling tramway track.	100Lft.	420.50		Metre	13.80			
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	3278.00		Metre	107.50			
4	Linking points and crossings, complete with fastenings.	Each	3187.80		Each	3187.80			
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	378.85		Each Point	378.85			
6	Fixing street lamp posts.	Each	415.15	0	Each	415.15			
7	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	4068.90	Depart	100 Nos	4068.90			
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	489.30		100 Nos	489.30			
	IRON WORK								
9	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	2230.80	7658.35	100 Kg	4391.35	15075.45		
10	Fabrication of heavy steel work, with angle, tees, flat iror round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling assembling and fixing, but excluding erection in position	Per Cwt	788.05	5949.10	100 Kg	1551.25	11710.80		
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	258.15		100 Kg	508.15			
12	Fixing corrugated iron sheet, including revitting, etc	100 Sft.	929.30		sq.m	100.00			
13	Erecting corrugated iron sheet tanks, upto 20 (6 m) height.	Per Cwt	420.10		100 Kg	826.95			

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY,	2013 TO 31st	JULY, 2	013) DIS	TRICT RAW	ALPINDI	
Sr.	Description	Ra	ate (British S	System)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Erecting rolled steel beams or old rails, in roofs, etc. erection and fixing in position.	Per Cwt	247.30		100 Kg	486.75			
15	Erecting rolled steel beams or rails, erection for posts etc (other than in roofs).	Per Cwt	121.10		100 Kg	238.40			
16	Making bolts and nuts of iron rods.	Per Cwt	1752.30	7790.75	100 Kg	3449.40	15336.10		
17	Cutting rails, rolled steel joists and beams, with hacksaw:-	,	/ ×	( )					
	a) upto 6" size (150 mm) b) above 6" size (150 mm)	Per Cut Per Cut	174.25 259.25		Per Cut Per Cut	174.25 259.25			
18	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	82.95		Per Cwt Cut	82.95			
19	Bending rolled steel beams or rails.	Per Bend	88.10	340.00	Per Bend	88.10	340.00		
20	Drilling holes, in plates upto ½" (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	32.85	t Wanners en still	Per Hole	32.85			
21	Extra for drilling holes in plates over ½" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	17.70	Too fame e	Per Hole	17.70			
22	Rivetting 1/8" dia (3 mm).	100 Nos	412.50		100 Nos	412.50			
23	Cutting out Rivets, all sizes.	100 Nos	1468.50		100 Nos	1468.50			
24	Fitting and erection of gutters of sheet iron.	Per Lft.	54.20		Metre	177.70			
25	Cutting and fixing iron bars, for barred windows.	Per bar	33.20		Per bar	33.20			
26	Cutting G.I. sheets.	Each Cut	18.05		Each Cut	18.05			
27	Notching web or foot of rail posts, for housing rail beams.	Per Notch	391.60	559.60	Per Notch	391.60	559.60		
28	Hoop iron netted trellis work fixed with nails.	Per Sft.	23.25		sq.m	250.00			
29	Fixing zinc iron or G.I. sheet on table tops	Per Sft.	13.65		sq.m	147.05			
30	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	136.70	696.45		1471.05	7494.00		
31	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm)	Per Sft.	142.75	822.55	sq.m	1535.70	8850.50		

	MRS, BI-ANNUAL PERIO	D (1st FEB	RUARY,	2013 TO 31st	JULY, 2	2013) DIS	TRICT RAW	ALPINDI	
Sr.	Description	R	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	centre to centre, with locking arrangement.	1							
32	Making and fixing grating in opening, including fixing at site with flat iron 2"x3/8" (50x10 mm) and 3/4" (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	55.05	342.10	sq.m	592.10	3681.05		
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed tc 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete	Per Rft.	293.85	780.25	Metre	964.05	2559.95		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8' punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	156.65	549.00	Metre	513.95	1801.20		
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	113.25	571.90	Metre	371.56	1876.31		-do-
		785. (8.8)88	<b>STACK</b>	THESPORE					
36	Providing and fixing collapsible gate made of 2"x2"x" <sup>1</sup> / <sub>4</sub> ' (50x50x6 mm) tee iron at top and bottom, channel iron verticals <sup>3</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>8</sub> " (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of <sup>3</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>4</sub> "x <sup>1</sup> / <sub>4</sub> " (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	190.40	615.90	sq.m	2048.75	6627.30		
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1½"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	45.30	221.00	sq.m	487.25	2378.10		
38	Providing and fixing M.S. angle iron 1½"x1½"x½" (40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.	Per Rft.	23.75	141.20	Metre	77.95	463.25		

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY,	2013 TO 31st	JULY, 2	013) DIS	TRICT RAW	ALPIND	
Sr.	Description	R	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Providing and fixing stair railing of 2½" (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.	Per Rft.	126.15	645.50	Metre	413.80	2117.80		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square
40	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	22.45	60.55	sq.m	241.45	651.60		bars.
41	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1½"x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ¾"x1"x¾"x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the Engineer-in-charge:-								For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	a) without wire gauze:  i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick b) fixed with wire gauze, 22 SWG	Per Sft. ditto ditto ditto ditto	58.10 58.10 58.10 58.10 58.10	303.15 307.95 315.15 322.35 327.15	sq.m ditto ditto ditto ditto	624.90 624.90 624.90 624.90 624.90	3262.05 3313.70 3391.15 3468.65 3520.30		
	<ul> <li>i) glass pane 2 mm thick</li> <li>ii) glass pane 2.5 mm thick</li> <li>iii) glass pane 3 mm thick</li> <li>iv) glass pane 4 mm thick</li> <li>v) glass pane 5 mm thick</li> </ul>	Per Sft. ditto ditto ditto ditto	81.55 81.55 81.55 81.55 81.55	360.10 364.90 372.10 379.30 384.10	sq.m ditto ditto ditto ditto	877.30 877.30 877.30 877.30 877.30	3874.60 3926.25 4003.75 4081.20 4132.85		
42	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1½"x1½" (30x30mm) for leaves including M.S. square bars ½"x½" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG) beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects.								
	<ul> <li>a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass panes <sup>1</sup>/<sub>4</sub>" (6 mm) thick.</li> <li>b) For fixed panels without wire gauze.</li> </ul>	Per Sft.	55.40 53.70	298.20 181.15	Sq.m ditto	595.90 577.80	3208.70 1948.95		

	MRS, BI-ANNUAL PERIOD	(1st FEB	RUARY, 2	2013 TO 31st	JULY, 2	013) DIS	TRICT RAW	ALPINDI	
Sr.	Description	Ra	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
43	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	58.45	370.90	Sq.m	628.85	3990.65		
44	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	72.40	430.75	Per Sft.	779.15	4634.75		
45	Flapping G.I. pipes for bath room drains.	Each	504.90	543.30	Each	504.90	543.30		
46	Supply and fixing iron grating for fire place.	Per Sft.	91.75	193.75	sq.m	987.10	2084.65		
47	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	38.70		Metre	127.00			
48	Providing and fixing angle iron railing, using 2½"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x½" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long ¾" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	60.85	782.05	Metre	199.55	2565.70		
	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5 mm), angle iron post 3½ ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" (225x225x300 mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	1402.95	9707.70		46.05	318.50		
50	Providing and fixing barbed wire fencing on compound	100Rft.	2345.50	12367.30	Metre	76.95	405.75		

Sr.	MRS, BI-ANNUAL PERIO	Rate (British System)				ate (Metric S		Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	Kellarks
51	wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects.  Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium								(1) Increase rate by Rs. 40.00 per Sft or Rs.430.50 per Sq-metre if
	doors, using delux section of M/s Al-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	67.00	481.30	sq. m	720.90	5178.80		sections thickness is 2 mm.  (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade.  (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used.
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan Cables having frame size of 100 x 20 mm (4"x¾") and leaf frame sections of 50 x 20 mm (2"x¾"), all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Sft	95.40	371.25	sq. m	1026.50	3994.65		(1) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if section thickness is 1.2 mm.  (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminium shade.  (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per sq-metre if local

## 26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description		Rate (British System)			te (Metric Sy	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	49.65	58.50	Per sq.m	534.40	629.40		The board is to be of cement plaster ½" (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.	
2	Fixing handles to iron hammers.	Each	70.15	_	Each	70.15	-			
3	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete.	100Lft.	5,041.35	22,519.60	L.m.	165.40	738.85		Vertical bars in straining and stiffening posts to be 4 No. each by ½" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be ¼" (6 mm) dia. at 12" (300 mm) centre to centre.	
	<u>Surveying</u>	4		MS 22	33.					
4	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	36.15	162.15	Each	36.15	162.15			
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	112.20	129.35	100Nos.	112.20	129.35			
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	269.30	467.30	100Nos.	269.30	467.30			
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	58.10	66.70	Per L.M.	190.55	218.90			
8	Placing boundary pillars in position, including digging pits.	Each	38.70	-	Each	38.70	-			
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	165.00	314.20	Each	165.00	314.20		Composite rate does not include cost of iron distance marks.	
	Hand Pumps & Pressure Pipes									
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	38.70	-	Per cut	38.70	-			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description		Rate (British Sy	estem)	Rat	te (Metric S	ystem)	Spec. No.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	71.55	0	Per cut	71.55	0				
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	49.95	-	Each End	49.95	-				
13	Assembling 11/2" (40 mm) dia pressure pipe.	100Lft.	175.75	-	Per Metre	5.75	-				
14	Boring and fixing 1½" (40 mm) dia pressure pipe:										
	a) in ordinary soil	Per Lft.	59.55	_	Per Metre	195.40	-				
	b) in clay c) in shingle	Per Lft. Per Lft.	114.50 169.46	( )	Per Metre Per Metre	375.70 555.95	-				
	c) in sinigle	rei Lit.	109.40		rei Mene	333.93	-				
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	26.25		Per Metre	86.20	-				
16	Fixing hand pump (Machine only)	Each	134.65		Each	134.65	-				
	Rest House Furniture & Fuel, etc.	EST.	1								
17	Washing Niwar of bed.	Per bed	366.30	396.55	Per bed	366.30	396.55				
18	Washing Durries.	100Sft.	488.40	560.40	sq.m	52.55	60.30				
19	Recaning chairs:		nance	Depart	mesmit						
	i) office chairs, single caning seat only.	Each	235.60	270.30	Each	235.60	270.30				
	ii) office chairs, double canning seat only.	Each	302.95	351.90	Each	302.95	351.90				
	iii) office chairs, single caning back only.	Each	168.30	170.50	Each	168.30	170.50				
	iv) office chairs, double caning back only.	Each	269.30	288.05	Each	269.30	288.05				
	v) easy chairs, single caning seat only.	Each	168.30	214.80	Each	168.30	214.80				
	vi) easy chairs, double caning seat only.	Each	471.25	540.60	Each	471.25	540.60				
	vii) easy chairs, single caning only, back and seat in one piece.	Each	673.20	958.80	Each	673.20	958.80				
	viii) easy chairs, double caning back & seat in one piece or couches with caned area about 16 Sft (1.5 Sqm).	Each	1,009.80	1,703.40	Each	1,009.80	1,703.40				
20	Making and fixing Hat pegs ordinary.	Each	121.20	442.80	Each	121.20	442.80				
21	Weaving charpoy.	Each	326.05	-	Each	326.05	-				
22	Sweeping chimney.	Each	81.40	82.70	Each	81.40	82.70				
23	Picture railing, including making, fixing and painting.	Per Lft.	34.65	105.55	Per LM	113.75	346.30				
24	Cutting fuel wood, from plantation.	100Kg	109.00	-	100Kg	109.00	-				
25	Splitting fuel wood.	100Kg	228.35	-	100Kg	228.35	-				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI									
Sr.	Description	Rate (British System)		ystem)	Rat	e (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	361.15	-	100Kg of Char- coal	361.15	-			
27	Filling cement bags with coal and sewing (including cosof strings).	100Cft.	1,001.20	1,004.35	cu.m	353.65	354.75			
28	Supplying manure.	Cart Load	122.10	254.10	Cart Load	122.10	254.10		Capacity of cart, 20 Cft. (0.57 cu.m).	
29	Washing punkha frills.	Each	100.30	-	Each	100.30	-			
30	Washing:-		/ >	( )						
	a) table cloth b) napkins, dusters, etc.	Each Each	25.10 16.70		Each Each	25.10 16.70	-			
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	45.05		Each No.	45.05	-			
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	49.00	( دارست	Each No.	49.00	-			
33	Dredging Sumps.	Per Shift	1,831.50	<b>S</b> 4.1	Per Shift	1,831.50	-		Not less than five gangmen to be employed for each shift to ensure effective dredging.	
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each	152.90	Lucpart	Each	152.90	-			
35	Bailing out water:-									
	a) by hand b) by pump	1000 Cft. 1000 Cft.	1,465.20 181.50	329.00	cu.m ditto	51.75 6.40	11.60		Rate includes cost of providing pump, POL and operation charges, etc.	
36	Drilling holes in R.C. Trough	Per Nos.	96.80	-	Per Nos.	96.80	-			
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.								The rate includes overlaps.	
	i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick)	Per Sft. Per Sft.	0.75 1.50	2.30 2.80	sq.m sq.m	8.10 16.20	24.75 30.15			
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100Sft.	1,021.60	6,718.45	sq.m	109.95	722.90			
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	165.95	-	Per Hole	165.95	-		Same rate to be paid for other type of masonry and R.C.C. work.	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) DISTRICT RAWALPINDI										
Sr.	Description	Rate (British System)			Rat	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
40	Making 1½"x1½" (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	145.20	-	Per Plank	145.20	-				
	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	48.85		Per hole per c.m depth	19.55					
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	67.30	205.70	sq.m of each spray	7.25	22.15				
43	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.	-300									
	<ul> <li>i) without cement concrete base.</li> <li>ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm).</li> </ul>	100Rft. 100Rft.	5,893.40 6,462.65	22,153.70 24,200.10	Per Metre Per Metre	193.30 212.00	726.65 793.75				