MARKET RATES SYSTEM (MRS)

BI-ANNUAL PERIOD

(1ST FEBRUARY, 2013 TO 31ST JULY, 2013)

GOVERNMENT OF THE PUNJAB

FINANCE DEPARTMENT

TABLE OF CONTENTS

Sr No.	Chapter	Pa	ıge N	<i>(os</i>
01.	Carriage	3	to	23
02.	Loading, Unloading & Stacking	24	to	26
03.	Earthwork (Excavation & Embankment)	27	to	33
04.	Dismentling (Demolition).	34	to	38
05.	Mortar	39	to	40
06.	Concrete	41	to	50
07.	Brickwork	51	to	56
08.	Stone Masonary	57	to	59
09.	Roofing	60	to	65
10.	Flooring	66	to	70
11.	Surface Rendering	71	to	74
12.	Wood Work	75	to	84
13.	Painting L Varnishing	85	to	90
14.	Lining of Canals	91	to	92
15.	Sheet Piling	93	to	94
16.	Protection & Diversion Work	95	to	104
17.	Outlets	105	to	106
18.	Road & Road Structure	107	to	111
19.	Plumbing, Sanitary Installation & Gas Fittings	112	to	117
20.	Surface Drainage	118	to	119
21.	Sewerage	120	to	124
22.	Sinking of Wells	125	to	127
23.	Tubewell & Water Supply	128	to	139
24.	Electric Installation	140	to	152
25.	Iron Work	153	to	158
26.	Miscellaneous	159	to	162

1. CARRIAGE

Note: 1 The rates are applicable to carriage of material on pacca roads only.

For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.

Note: 2 For hilly areas 25% above the rates in the plain areas shall be allowed for total mileage (Km) covered.

Note: 3 In case of articles longer than 15 ft. (4.6 m) carried in trucks, the following rates shall be allowed:-

- i) Above 15 ft. to 25 ft. (4.6 to 7.6 m): Total rates to be paid for 15 ft. to 25 ft. (4.6 to 7.6 m) length will be 1.5 times of the rate given in the Composite Schedule of Rates.
- ii) Above 25 ft. (7.6 m):- The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.

The length measured shall not be the actual length, but the length of the form of consignment as actually received.

Note: 4 The term 'mile' (Km) whenever used is to mean statute mile (Km).

Note: 5 The rates include loading and unloading of material from the conveyance and stacking as directed.

Note: 6 The rates for carriage by boat or steamer shall be the same as by any other mechanical means on land.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	t JULY, 2013	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr. No.	Description	100		Rate (Metric System) Unit of M/ment Labour Composite		Spec. No.	Remarks			
1	Carriage of 100 Cft. (2.83 cu.m) of all materials like stone aggregate, spawl, kankar lime (unslaked), surkhi, etc. or 150 Cft. (4.25 cu.m) of timber, by truck or by any other means owned by the contractor.	Ti)	Maring Carris	Departi	Marine II			16.1		
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30M 30M 30M 300 Metre	104.50 19.25 11.95 117.55				
	1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km				Km Km Km Km Km Km	163.30 76.95 58.85 40.90 37.90 37.25 34.55				
	8th Km 9th Km 10th Km 11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms				Km Km Km Km Km	34.15 31.95 29.65 22.00 3.25 2.00				

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY, 2	2013 TO 31s	t JULY, 2013)	TEH: NO	OWSHER	A, SOAN VA	LLEY, KI	IUSHAB
Sr.	Description		1			ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
2	Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastenings, points and crossing, Bridge Girders, pipes, sheets, Rail, M.S. bars, etc. etc. by truck or any other means owned by the contractor.							16.1	Cement carried in containers other than bags will be paid according to this item. The word "pipes" covers G.I,C.I,R.C.C. and P.C.C.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km		37.		30M 30M 30M 300M Km Km Km	104.50 19.25 11.95 117.55 163.30 76.95 58.85 40.90			
1	5th Km 6th Km	, ,	-		Km	37.90 37.25			
	7th Km	1			Km	34.55			
	8th Km	18			Km	34.15			
	9th Km	16/17	1	-16/	Km	31.95			
	10th Km	- 0		- 1 B	Km	29.65			
3	11th Kms to 200Kms 201 Kms to 250 Kms 251 Kms & susequent Kms Carriage of 100 maunds of fuel wood by truck or any other means owned by the contractor:	Ti	nameer (Departi	Km Km Km	22.00 3.25 2.00		16.1	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 30 M 30 M 300 M Km Km Km	104.50 19.25 11.95 117.55 163.30 76.95 58.85 40.90			
	5th Km				Km	37.90			
	6th Km				Km	37.25			
	7th Km				Km	34.55			
	8th Km				Km	34.15			
	9th Km				Km	31.95			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 20	13 TO 31st	JULY, 2013)	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	IUSHAB
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	10th Km				Km	29.65			
4	11th & subsequent Kms Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm) or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or any other means owned by the contractor:-				Km	22.00		ditto	Reduce the rate by 33% in case of carriage of 1000 Nos. tiles size 12"x6"x1 ¹ / ₄ " (300 x 150 x 30 mm).
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	104.50 19.25 11.95			12 AO AT /4 (300 A 130 A 30 mm).
	1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				300 M Km Km Km	117.55 163.30 76.95 58.85			
	4th Km	/	570		Km	40.90			
	5th Km	.46	0.5		Km	37.90			
	6th Km 7th Km	\$ E	Sixon		Km Km	37.25 34.55			
	8th Km	1617	1	-,6/	Km	34.15			
	9th Km	-02	20	\$ C 18	Km	31.95			
	10th Km	Tin.	amer (Departi	Km	29.65			
5	11th & subsequent Kms Carriage of 100 cft. (2.83 cu.m) of all material like stone, aggregate, spawl, kankar lime(unslaked), surkhi, etc. or 150 cft. (4.25 cu.m) of timber, by means of material trolly.				Km	22.00		16.1	Material trolly to be supplied by the Government and maintained and run by the contractor.
	1st chain (1st 30 m) 2nd chain to 10th chain (2nd 30 m to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 300 M Km	104.50 19.25 117.55 133.95			
	2nd Km 3rd Km 4th Km				Km Km Km	102.05 54.35 42.45			
	5th Km				Km	37.30			
	6th Km 7th Km				Km Km	35.85 30.25			
	8th Km				Km	29.90			
	9th Km				Km	27.95			
	10th Km				Km	25.95			
	11th Kms to 200Kms 201 Kms to 250 Kms				Km Km	20.95 3.25			

	MRS, BI-ANNUAL PERIOD (1st FEE	BRUARY, 2	2013 TO 31:	st JULY, 2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KI	HUSHAB
Sr.	Description		_			Rate (Metric System)		Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
6	251 Kms & susequent Kms Carriage of 5 tons of all material like coal, stone lime (unslaked), etc. B.G. Rail fastening, points and crossing, Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by means of material trolly.				Km	2.00		16.1	Material trolly to be supplied by the Government and maintained and run by the contractor.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 30 M 300 M Km Km Km	104.50 19.25 117.55 133.95 102.05 54.35 42.45			
	5th Km 6th Km				Km Km	37.30 35.85			
	7th Km		/ "		Km	30.25			
	8th Km			1	Km	29.90			
	9th Km	11.6			Km	27.95			
	10th Km	8			Km	25.95			
	11th Kms to 200Kms	1,59			Km	20.95			
	201 Kms to 250 Kms 251 Kms & susequent Kms	1834	1	6 7	Km Km	3.25 2.00			
7	2.21 Kins & suscite Kins Carriage of 100 maunds of fuel wood, by means of material trolly. 1st chain (1st 30 m) 2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km	(Fig.		Departs	30 M 30 M 300 M Km Km Km	104.50 19.25 117.55 133.95 102.05 54.35 42.45		ditto	Material trolly to be supplied by the Government and maintained and run by the contractor.
	5th Km				Km	37.30			
	6th Km				Km	35.85			
	7th Km				Km	30.25			
	8th Km				Km	29.90			
	9th Km				Km	27.95			
	10th Km				Km	25.95			
	11th & subsequent Kms				Km	20.95			
8	Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm),							ditto	Material trolly to be supplied by the
	by means of material trolly.								Government and maintained and run
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	104.50 19.25			by the contractor.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	RA, SOAN VA	LLEY, KH	USHAB
Sr.	Description				R	Rate (Metric System)			Remarks
No.	-				Unit of M/ment	Labour	Composite	Spec. No.	
	1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				300 M Km Km Km Km	117.55 133.95 102.05 54.35 42.45		16.1	
	5th Km				Km	37.30			
	6th Km				Km	35.85			
	7th Km				Km	30.25			
	8th.		35	,	Km	29.90			
	9th Km	,			Km	27.95			
	10th Km	116	2/1		Km	25.95			
	11th & subsequent Kms Carriage of 1000 No. bricks, 9"x4½"x3" (225x113x75 mm) or 8"x4"x4" (200x100x100 mm) (nominal) 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km			Departs	30 M 30 M 30 M 300 M Km Km Km	20.95 85.62 17.80 9.81 96.24 133.90 62.95 48.20 33.75 32.00		ditto	
	6th Km				Km	31.25			
	7th Km				Km	28.30			
	8th Km				Km	27.95			
	9th Km				Km	26.15			
	10th Km				Km	24.30			
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½" (225x113x38 mm). 1st chain (1st 30 m)				Km 30 M	17.90 51.67		16.1	
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	51.67 9.51		16.1	

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description				R	ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 300 M Km Km Km	5.86 58.14 80.80 38.10 29.15 20.20	-		
	5th Km				Km	18.65			
	6th Km				Km	18.30			
	7th Km				Km	17.10			
	8th Km		30	1	Km	16.90			
	9th Km	,			Km	15.80			
	10th Km	116	15		Km	14.75			
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.	8			Km	10.85		ditto	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	100			30 M 30 M 30 M	1.97 0.24 0.11			
	1000 to 3000 ft. (300 to 900 m)	arces II			300 M	1.16			
	1st Km	Tin	namen (Departs	Km	2.00			
	2nd Km				Km	1.40			
	3rd Km				Km	0.60			
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including bundling.				Km	0.35		16.1	
	1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft.				300 M 300 M	28.84 3.59			
	1st Km				Km	4.90			
	2nd Km				Km	4.70			
	3rd Km				Km	2.30			
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash				Km	2.05		ditto	Previous lead of collection not

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description					ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	or brushwood, by boat or road :-								to be deducted from the next lead of carriage.
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	42.75 19.25 5.86			
	1000 to 3000 ft. (300 to 900 m)				300 M	48.29			
	1st Km				Km	74.80			
	2nd Km				Km	38.10			
	3rd Km		/ ×)	Km	29.15			
	4th Km	/			Km	20.20			
	5th Km				Km	18.65			
	6th Km	835			Km	18.30			
	7th Km		100		Km	17.10			
	8th Km 9th Km 10th Km 11th Km & subsequent	Œ	namer (Departi	Km Km Km Km	16.90 15.80 14.75 10.85			
14	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre) Execeeding 1000 to 5000 ft (300 to 1500metre)				Tonne 300 M	349.41 84.66		ditto	
	1st Km				Km	160.65			
	2nd Km				Km	75.05			
	3rd Km				Km	51.00			
	4th Km				Km	33.15			
	5th Km				Km	31.30			
	6th Km				Km	30.10			
	7th Km				Km	26.05			
	8th Km				Km	25.70			

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 2	2013 TO 31s	t JULY, 2013) TEH: N	OWSHER	RA, SOAN VA	LLEY, KI	HUSHAB
Sr.	Description				Rate (Metric System)		System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km 10th Km 11th Km & susequent				Km Km Km	25.15 19.90 16.40			
15	Carriage of small consignments weighing upto 5 maunds (job rates):							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%; and for consignments weighing 10
	Upto 1000 ft. (300 metre)				Consign- ment/	28.37			to 20 maunds, rate be increased by 100%.
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				300 M	19.46			
	1st Km		/ ×		Consign- ment/ Km	25.15			
	2nd Km	1.6	05			15.70			
16	3rd Km & subsequent Carriage of consignments job.					5.25			
	i) Cooly load for distance:-	18/7	100	-190	Each				
	a) Upto 5 Km b) Above 5 to 13 Km	nge.			Consignmen "	51.45 121.00			
	ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ½ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km	T		Depart	Each Consignmen """ """""""""""""""""""""""""""""""	10.85 16.45 20.80 26.00 45.95 82.25			
	iii) Cart load for a distance :-				Each Consig- nment				
	a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to 10 Miles(16 Km)				"	89.85 163.55			
	iv) Camel load for a distance:-								
	a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km)				"	66.45 100.75			
17	Hire charges of:-								1. This item will be allowed with
	i) truck (10 Ton Capacity)				Per	3000.00			prior concurrence of Superintending Engineer.

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KI	IUSHAB	
Sr.	Description				Rate (Metric System)		System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	ii) tractor with trolly iii) tractor without trolly				day "	1000.00	•		2. The rate includes pay of driver and cleaner only. The repairs shall be the responsibility of the owner and the cost of lubrication, fuel, loading and unloading shall be paid by the borrower.
18	Carriage of bitumen, tar or other lubricants, in drums:							16.1	
	1st Km 2nd Km				Per Tonne	26.80 18.50			
				,	,,				
	3rd & subsequent Km	,	/ %		"	7.55			
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-	*							
	i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Ti		Z/s Departs	30 M 30 M 30 M 300 M Km Km	4.10 0.75 0.45 4.65 6.45 3.00 2.30			
	4th Km				Km	1.60			
	5th Km				Km	1.50			
	6th Km				Km	1.40			
	7th Km				Km	1.30			
	8th Km				Km	1.25			
	9th Km				Km	1.25			
	10th Km				Km	1.15			
	11th Km & Susequent				Km	1.10			
	ii) 4" (100 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	5.40			

	MRS, BI-ANNUAL PERIOD (1st F	EBRUARY, 2	2013 TO 31s	t JULY, 2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.	^				Unit of M/ment	Labour	Composite	No.	
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	1.00 0.60	, , , , , , , , , , , , , , , , , , ,		
	1000 to 9000 ft. (300 to 900 m)				300 M	6.10			
	1st Km				Km	8.45			
	2nd Km				Km	3.95			
	3rd Km				Km	3.00			
	4th Km				Km	2.10			
	5th Km		/ ×)	Km	1.95			
	6th Km	. /			Km	1.85			
	7th Km		/43b		Km	1.75			
	8th Km 9th Km 10th Km 11th Km & subsequent Km		1967		Km Km Km Km	1.70 1.60 1.50 1.45			
ii	ii) 6" (150 mm) i/d pipes:-			G. Paris					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 9000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Pi	energe (Departs	30 M 30 M 30 M 300 M Km Km	8.10 1.50 0.95 9.10 12.70 5.95 4.55			
	4th Km				Km	3.15			
	5th Km				Km	2.90			
	6th Km				Km	2.85			
	7th Km				Km	2.65			
	8th Km				Km	2.55			
	9th Km				Km	2.45			
i	10th Km 11th Km & subsequent Km v) 8" (200 mm) i/d pipes:				Km Km	2.25 1.95			

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	JSHAB
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	13.70 2.55 1.55 15.45 21.45 10.40 7.85			
	4th Km				Km	5.40			
	5th Km		and E-min		Km	5.05			
	6th Km		/ ×	1	Km	4.95			
	7th Km	/	_		Km	4.55			
	8th Km	16	Yes		Km	4.40			
	9th Km				Km	4.00			
	10th Km 11th Km & subsequent Km	16/7	19.65	(عارب	Km Km	2.45 1.80			
v)	10" (250 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Œ		Separts	30 M 30 M 30 M 300 M Km Km	18.45 3.40 2.10 20.75 28.80 13.45 10.25			
	4th Km				Km	7.10			
	5th Km				Km	6.55			
	6th Km				Km	6.45			
	7th Km				Km	6.25			
	8th Km				Km	6.15			
	9th Km				Km	5.75			
	10th Km 11th Km & subsequent Kms				Km Km	5.35 3.95			
vi)	12" (300 mm) i/d pipes:								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013)) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB					
Sr.	Description				R	ate (Metric :	System)	Spec.	Remarks		
No.	-				Unit of M/ment	Labour	Composite	No.			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M 30 M 30 M 300 M Km Km Km	23.95 4.40 2.75 26.95 37.45 18.50 13.75 9.25	•				
	5th Km				Km	8.55					
	6th Km				Km	8.40					
	7th Km		/ ×)	Km	7.80					
	8th Km	/			Km	7.70					
	9th Km				Km	7.15					
	10th Km	850	100		Km	6.65					
	11th Km & subsequent Kms	617	100	٠٠٠٠	Km	5.00					
	vii) 16" (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Tin		Departs	30 M 30 M 30 M 300 M Km Km	39.30 7.25 4.50 44.20 61.40 29.15 22.10					
	4th Km				Km	15.35					
	5th Km				Km	14.20					
	6th Km				Km	13.95					
	7th Km				Km	12.95					
	8th Km				Km	12.80					
	9th Km				Km	11.95					
	10th Km 11th Km & subsequent Kms viii) 18" (450 mm) i/d pipes:-				Km Km	11.10 8.25					

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013)					3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB					
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks		
No.					Unit of M/ment	Labour	Composite	No.			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	50.50 9.30 5.80 56.80 78.90 37.20 28.45					
	4th Km				Km	19.80					
	5th Km				Km	18.30					
	6th Km		Me		Km	18.00					
	7th Km	,			Km	16.70					
	8th Km	116	22.3		Km	16.50					
	9th Km	8 1	174		Km	15.45					
ix	10th Km 11th Km & subsequent Kms 20" (500 mm) i/d pipes:-	10/1	150		Km Km	14.35 10.55					
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Ti	1.0000 (27 (Departs	30 M 30 M 30 M 300 M Km Km	53.60 9.85 6.15 60.30 83.75 39.45 30.15					
	4th Km				Km	20.95					
	5th Km				Km	19.40					
	6th Km				Km	19.05					
	7th Km				Km	17.70					
	8th Km				Km	17.50					
	9th Km				Km	16.35					
x	10th Km 11th Km & subsequent Kms 24" (600 mm) i/d pipes:-				Km Km	15.20 11.40					

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	JSHAB
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 5000 ft. (300 to 1500 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	59.40 10.95 6.80 66.80 92.80 43.70 33.40	•		
	4th Km				Km	23.70			
	5th Km				Km	21.50			
	6th Km		35		Km	21.10			
	7th Km	,	(~		Km	19.55			
	8th Km	116	200		Km	19.35			
	9th Km	8			Km	18.10			
20	10th Km 11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading, unloading and stacking (Rate per 1000 ft.) (300 metre):-		\$ 5 to	- 19	Km Km	16.80 12.40			
	i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km	Ti		Departs	30 M 30 M 30 M 300 M Km Km	8.10 1.50 0.95 9.10 12.65 5.95 4.55			
	4th Km				Km	3.15			
	5th Km				Km	2.90			
	6th Km				Km.	2.85			
	7th Km				Km	2.65			
	8th Km				Km	2.60			
	9th Km				Km	2.45			

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2013 TO 31st JULY, 20	13) TEH: N	IOWSHER <i>A</i>	A, SOAN VA	LLEY, KHU	SHAB
Sr.	Description			Rate (Metric Sy	ystem)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	10th Km 11th Km & subsequent Kms ii) 4" (100 mm) i/d pipes:-		Km Km	2.30 1.90			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		30 M 30 M 30 M 300 M Km Km	12.45 2.30 1.45 14.00 19.50 9.35 7.05			
	4th Km	76	Km	4.80			
	5th Km		Km	4.45			
	6th Km	July Comments	Km	4.35			
	7th Km		Km	4.05			
	8th Km	Will the second	Km	4.00			
	9th Km	10 Sept.	Km	3.75			
	10th Km 11th Km & subsequent Kms iii) 5" (125 mm) i/d pipes:-	Finance Depar	Km Km	3.45 3.00			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		30 M " 300 M Km	17.00 3.15 1.95 19.10 26.55 12.65 9.70			
	4th Km		"	6.80			
	5th Km		Km.	6.10			
	6th Km		"	6.00			
	7th Km		"	5.55			
	8th Km			5.50			
	9th Km			5.15			

	MRS, BI-ANNUAL PERIOD (1st	FEBRUARY, 2013 TO 31st JULY, 2	2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KHU	ISHAB
Sr.	Description			ate (Metric S	System)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	10th Km			4.75			
	11th Km & subsequent Kms			4.75 3.60			
	iv) 6" (150 mm) i/d pipes:						
	1st chain (1st 30 m) 2nd chain (2nd 30 m)		30 M 30 M	23.45 4.30			
	3rd to 10th chain (60 to 300 m)		30 M	2.70			
	1000 to 3000 ft. (300 to 300 m)		300 M	26.35			
	1st Km.		Km.	36.60			
	2nd Km		Km.	17.25			
	3rd Km		Km.	13.20			
	4th Km	(*)	Km.	9.15			
	5th Km		Km.	8.50			
	6th Km		Km.	8.35			
	7th Km		Km.	7.75			
	8th Km		Km.	7.65			
	9th Km	******	Km.	7.15			
	10th Km	April 1	Km.	6.65			
	11th Km & subsequent Kms	95 татем Отра	Km.	4.95			
	v) 8" (200 mm) i/d pipes:-						
	1st chain (1st 30 m)		30 M	41.10			
	2nd chain (2nd 30 m)		30 M	7.55			
	3rd to 10th chain (60 to 300 m)		30 M	4.70			
	1000 to 3000 ft. (300 to 900 m)		300 M	46.25			
	1st Km		Km	64.20			
	2nd Km 3rd Km		Km Km	30.30 23.15			
	4th Km		Km	16.10			
	5th Km		Km	14.90			
	6th Km		Km	14.65			
	7th Km		Km	13.60			
	8th Km		Km	13.45			

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KHU	JSHAB
Sr.	Description				R	ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	12.55			
	10th Km 11th Km & subsequent Kms vi) 10" (250 mm) i/d pipes:-				Km Km	11.65 8.60			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	63.75 11.75 7.30 71.70 99.60 46.95 35.90			
	4th Km		*		Km	24.95			
	5th Km	11.6			Km	23.10			
	6th Km	8	22		Km	22.70			
	7th Km	856		-67	Km	21.05			
	8th Km		10.00	- 77	Km	20.80			
	9th Km			G. Fireman	Km	19.50			
	10th Km 11th Km & subsequent Kms	Ti	namer (Departs	Km Km	18.10 13.50			
	vii) 12" (300 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	89.70 16.50 10.25 100.90 140.20 66.10 50.50			
	4th Km				Km	35.10			
	5th Km				Km	32.55			
	6th Km				Km	31.95			
	7th Km				Km	29.65			
	8th Km				Km	29.30			

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description					ate (Metric	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	27.40			
	10th Km 11th Km & subsequent Kms				Km Km	25.45 18.95			
	viii) 14" (350 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	116.75 21.50 13.35 131.35 182.50 86.00 65.75			
	4th Km		.55		Km	45.70			
	5th Km	11/			Km	42.35			
	6th Km	81	00		Km	41.60			
	7th Km	188/	5.4	- 16	Km	38.55			
	8th Km		3		Km	38.10			
	9th Km		0	0	Km	35.65			
	10th Km 11th Km & subsequent Kms	970	MARINI CIE (Departi	Km Km	33.15 24.70			
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-								
	i) 2" (50 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	5.90 1.10 0.70 6.65 9.25 4.35 3.35			
	5th Km				Km	2.15			
	6th Km				Km	2.10			
	7th Km				Km	1.95			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) T				TEH: N	OWSHER	A, SOAN VA	LLEY, KH	JSHAB
Sr.	Description		,			ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	1.90			
	9th Km				Km	1.80			
	10Km 11th Km & subsequent Kms				Km Km	1.65 1.25			
Ī	ii) 2½" (63 mm) i/d pipes:-				Kili	1.23			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km		<u> </u>		30 M 30 M 30 M 300 M Km Km	9.20 1.70 1.05 10.35 14.40 6.80 5.20			
	4th Km	116	-		Km	3.65			
	5th Km		~ 1AUA		Km	3.40			
	6th Km	16/7	1-6	-16/	Km	3.35			
	7th Km	-65			Km	3.10			
	8th Km		AL ATTENDED OF SALE OF	Therene madelle	Km	2.85			
	9th Km		Latin Car	Departi	Km	2.75			
	10Km 11th Km & subsequent Kms				Km Km	2.55 1.95			
	iii) 3" (75 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km				30 M 30 M 30 M 300 M Km	12.75 2.35 1.45 14.35 19.90			
	2nd Km 3rd Km				Km Km	9.40 7.20			
	4th Km				Km	5.00			
	5th Km				Km	4.65			
	6th Km				Km	4.55			
	7th Km				Km	4.20			

	MRS, BI-ANNUAL PERIOD (1st	FEBRUARY, 2013 TO 31s	t JULY, 2013) TEH: N	IOWSHERA, SOAN	VALLEY, KHUS	HAB
Sr.				Rate (Metric System)	Spec.	Remarks
No.			Unit of M/ment	Labour Composite	No.	
	8th Km		Km	4.15		
	9th Km		Km	3.80		
	10th Km 11th Km & subsequent Kms		Km Km	3.55 2.70		
	iv) 4" (100 mm) i/d pipes:-		Kili	2.70		
	1st chain (1st 30 m)		30 M	21.10		
	2nd chain (2nd 30 m)		30 M	3.90		
	3rd to 10th chain (60 to 300 m)		30 M	2.40		
	1000 to 3000 ft. (300 to 900 m)		300 M	23.75		
	1st Km		Km	32.95		
	2nd Km 3rd Km	/ ×	Km Km	15.55 11.85		
		76				
	4th Km		Km	8.25		
	5th Km		Km	7.65		
	6th Km		Km	7.50		
	7th Km	1	Km	7.05		
	8th Km		Km	6.85		
	9th Km	Tinance (Km	6.40		
	10th Km		Km	5.90		
	11th Km & subsequent Kms		Km	4.55		
	v) 5" (125 mm) i/d pipes:-					
	1st chain (1st 30 m)		30 M	31.55		
	2nd chain (2nd 30 m)		30 M	5.80		
	3rd to 10th chain (60 to 300 m)		30 M	3.60		
	1000 to 3000 ft. (300 to 900 m)		300 M	35.50		
	1st Km		Km	49.30		
	2nd Km		Km	23.25 17.75		
	3rd Km		Km	17.73		
	4th Km		Km	12.35		
	5th Km		Km	11.45		
	6th Km		Km	11.25		
	7th Km		Km	10.45		

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY, 2	013 TO 31s	t JULY, 2013	TEH: N	OWSHER	A, SOAN VA	LLEY, KHUS	HAB
Sr.	Description					ate (Metric S	System)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	10.30			
	9th Km				Km	9.65			
	10th Km				Km	8.85			
	11th Km & subsequent Kms				Km	6.75			
	vi) 6" (150 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M 30 M	45.45 8.35			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M	5.20			
	1000 to 3000 ft. (300 to 900 m)				300 M	51.10			
	1st Km				Km	71.00			
	2nd Km		/ ×4	1	Km	33.45			
	3rd Km				Km	25.60			
	4th Km	. /			Km	17.80			
	5th Km				Km	16.45			
	6th Km	8			Km	16.15			
	7th Km	386			Km	15.00			
	8th Km	1647	1.6	- 150/	Km	14.85			
	9th Km	100			Km	13.90			
	10th Km			F 12-78	Km	12.90			
	11th Km & subsequent Kms				Km	9.70			
	Hand shunting loaded Railway wagons or trucks:-	Tin	MARINE CAN (Departs	数据加其				
	a) upto ½ mile / ¼ Km				Each	150.05			
	b) upto ½ mile / ½ Km				No	271.65			
	c) upto ³ / ₄ mile / ³ / ₄ Km				"	366.70			
	d) upto 1 (1.6 Km) mile				"	436.40			
	e) 2nd mile and subsequent miles/				Each				
	2nd and subsequent kilometres				No/Km	271.15			
23	Hand shunting empty Railway wagons or trucks.								
	a) upto ¼ mile / ¼ Km				Each	87.05			
	b) upto ½ mile /½ Km				No.	144.20			
	c) upto 3/4 mile / 3/4 Km				"	190.20			
	d) upto 1 mile / 1 Km				"	228.30			
	e) 2nd mile and subsequent miles/				Each	122.15			
	2nd and subsequent kilometres				No/Km	133.15			

2. LOADING, UNLOADING & STACKING

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB									
Sr.	Description	R	ate (British Sy	rstem)	Ra	te (Metric S	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
1	Laoding or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	401.30		cu.m	141.75				
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-		×							
	a) Bricks 10" (250 mm) size.	1000 Nos.	501.60		1000 Nos.	501.60				
	b) Bricks 9" (225 mm) or smaller size.	ditto	401.30		ditto	401.30				
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	501.60	- 10	100 Bags	501.60				
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	48.15		100 Nos.	48.15				
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	300.95	Deploye	100 Kg	8.05				
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	240.75		Per Tonne	236.95				
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	30.10		Each	30.10				
8	Loading or unloading packages of all sorts, upto one Cwt (50 Kg). Loading or unloading sleepers other than wooden, including stacking lead within one chain:-	Each	15.05		Each	15.05			Except cement in jute or paper bags.	
	a) Broad gauge sleepers	100 Nos.	1003.20		100 Nos.	1003.20				
	b) Metre gauge and narrow gauge sleepers.	ditto	501.60		ditto	501.60				
10	Loading or unloading timber logs or timber for shuttering,	Per	125.4		Per	123.4				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	R	ate (British Sy	stem)	Ra	te (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Ton			Tonne							
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	1203.85		100 Kg	32.25						
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	200.65		Per Tonne	197.45						
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	148.45		cu.m	52.45						
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	192.60		cu.m	68.05						
15	Unloading oil, bitumen tar, etc.	116			Di.							
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	501.60		100 litres	11.05						
	b) Crude oil (drained by gravity).	1000 Gallon	501.60		100 litres	11.05						
	c) Crude oil materials from railway wagons.	100 Cft.	64.20		cu.m	22.70						
	d) Fuel oil from tank into empty drums, including stacking within one chain (30 m).	Per Ton	178.35	Departs	Per Tonne	175.55						
	e) Petrol (2 gallon tin)	100 Nos.	252.80		100 Nos.	252.80			The rate includes checking and weighing the tins.			
16	f) Kerosine oil (4 gallon tin) Removing and stacking within one chain (30 m) lead:	100 Nos.	501.60		100 Nos.	501.60			and weighing the tins.			
	Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc.	100 Cft.	200.65		cu.m	70.85						
	b) Bricks.	1000 Nos.	535.05		1000 Nos.	535.05						
	c) Broad gauge wooden sleepers.	100 Nos.	321		100 Nos.	321						
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	191.10		100 Nos.	191.10						
	e) Rails girders, pipes, cement etc.	Per Ton	89.15		Per Tonne	87.75						

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAI	LEY, KHU	ISHAB
Sr.	Description	R	ate (British Sy	rstem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	f) Bridge and crossing timbers, etc.	100 No.	1070.10		100 No.	1070.10			
17	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	200.65		Per Tonne	197.45			
18	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	114.65		Per Tonne	112.85			
19	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	802.55		100 Nos.	802.55			
20	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	382.15		100 Nos.	382.15			
21	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	401.30		100 Nos.	401.30			
22	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	211.20		100 Nos.	211.20			
23	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	1605.10		100 Nos.	1605.10			
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	802.55		100 Nos.	802.55			
25	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	120.40		Per Tonne	118.50			

3. EARTHWORK (EXCAVATION & EMBANKMENT)

- Special allowances for the hardness, wetness and slush:-
 - The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.
- 2 Deduction for shrinkage from bank measurements:-
 - The following allowances should be provided for material which is not rammed, or equally consolidated:-
 - a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour........ 10%
 - b) Deduction for settlement from the bank measurement when the earthwork is done by machines................................. 3 to 6%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors

	MRS, BI-ANNUAL PERIOD (1st F						A, SOAN VAI	LEY, KHU	JSHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
1	Earthwork excavation underessed lead upto a single throw of Kassi, phaorah or shovel:-	4			No.			171 to 17.5	
	a) In ashes, sand, soft soil or silt clearance.b) In ordinary soil.	1000 Cft. 1000 Cft.	1,504.80 1,805.75	-	cu.m cu.m	53.15 63.80			
2	Earthwork excavation in ashes, sand and soft soil or silt clearance, undressed lead upto 50 ft (15 metre).	1000 Cft.	2,207.05		cu.m	77.95		ditto	
3	Bed clearance and dressing slopes of drains to required sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead. a) Excavated material undressed. b) Excavated material dressed in the specified manner.	1000 Cft. 1000 Cft.	2,808.95 3,035.45	Departs <u>:</u>	cu.m cu.m	99.20 107.20	 	ditto	The rate is applicable where the earth of the bed to be removed is of the type of ordinary soil. When it is silt or 1 or 2 above, whichever is applicable. the drains of each category.
4	Borrowpit excavation undressed lead upto 100 ft (30 metre). a) Ordinary soil b) Hard soil	1000 Cft. 1000 Cft.	2,808.95 3,451.00		cu.m cu.m	99.20 121.90	 		
5	Earthowrk in ordinary soil for embankments lead upto 100 ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete in all respects: i) 95% to 100% maximum modified AASHO dry density. ii) 90% maximum modified AASHO dry density.	1000 Cft. 1000 Cft.	3,063.05 3,063.05	3,848.05 3,727.00	cu.m cu.m	108.20 108.20	135.90 131.65	411-13 and 301-1 & 202-3	The rate includes hire charges of machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also includes clearing and grubbing where necessary.
6	iii) 85% maximum modified AASHO dry density. Regular excavation dressed.	1000 Cft. 1000 Cft.	3,063.05 2,061.10	3,605.95	cu.m cu.m	108.20 72.80	127.35	*411-2	
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and							17.1 to 17.5	

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY, 2	013 TO 31st	JULY, 2013)	TEH: NO	OWSHER	A, SOAN VAL	LEY, KHU	SHAB
Sr.	Description		Rate (British Sy	stom)	p	ate (Metric	Syctom)	Spec.	Remarks
No.	Description	Unit of	Rate (British Sy	stem)	Unit of	ate (Metric)	•	No.	Kemarks
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	timbering the trenches, dressed to designed level and								
	dimensions, trimming, removal of surface water from								
	trenches, back filling and surplus excavated material								
	disposed of and dressed within 50 ft. (15 m) lead:-								
	i) ordinary	1000 Cft.	3,503.80	3,576.65	cu.m	123.75	126.35		
	ii) hard	1000 Cft.	4,145.85	4,218.70	cu.m	146.45	149.00		
	iii) very hard	1000 Cft.	4,828.05	4,900.90	cu.m	170.55	173.10		
	iv) gravel & shingle	1000 Cft.	8,129.10	8,201.95	cu.m	287.10	289.70		
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to							ditto	
	10.0 ft. (3.0 mm) depth for storm water channels, drains,								
	sullage drains in open areas, roads, streets, lanes, including								
	under pinning of walls and shoring to protect existing works,		/ ×-)					
	shuttering and timbering the trenches, dressed to designed		_						
	level and dimensions, trimming, removal of surface water	/							
	from trenches, back filling and surplus excavated material	11.6	41-11		11:				
	disposed of and dressed within 100 ft. (30 m) lead:-	188			333				
	i) ordinary	1000 Cft.	3,822.70	3,967.65	cu.m	135.00	140.15		
	ii) hard	1000 Cft.	4,464.75	4,609.70	cu.m	157.70	162.80		
	iii) very hard	1000 Cft.	5,146.95	5,291.90	cu.m	181.80	186.90		
	iv) gravel & shingle	1000 Cft.	8,849.30	8,994.20	cu.m	312.55	317.70		
9	Excavation in shingle or gravel formation and rock, not	-		September 1				17.1 to 17.5	
	requiring blasting, undressed lead upto 100 ft (30 m).								
	i) Dry	1000 Cft.	7,624.30	Thereactions the	cu.m	269.30			
	ii) Wet	1000 Cft.	8,828.15	reconstruction and	cu.m	311.80			
	iii) In flowing water	1000 Cft.	11,235.85		cu.m	396.85			
10	Earthwork excavation in irrigation channels, drains, etc. to								
	designed section, grades and profiles, excavated material							ditto	
	disposed off and dressed within 50 ft. (15 m) lead:-								
	i) ordinary	1000 Cft.	3,220.80		cu.m	113.75			
	ii) hard	1000 Cft.	3,862.85		cu.m	136.45			
	iii) very hard	1000 Cft.	4,545.00		cu.m	160.55			
	iv) gravel & shingle	1000 Cft.	8,046.70		cu.m	284.20			
11	Excavation in rock dressed to designed section, grades and								
	profiles, excavated material disposed off within 100 ft. (30 m)							17.1 to 17.5	Tools and plants shall be the liability
	and lift upto 5'-0" (1.5 m).								of the contractor.
	a) Soft rock, slate, shale, schist laterite work, with pick and	1000 Cft.	7,677.10		cu.m	271.15			
	crow bar. b) Medium hard rock, requiring occasional blasting.	1000 Cft.	12,118.35	12,694.35	cu.m	428.00	448.35		
12	a) Excavation in hard rock requiring blasting and disposal								
	of excavated material (blasted material) upto 50 ft. (15	1						17.1 to 17.5	1) Tools and plants required shall be
	m) lead, (including dressing and levelling to designed	1							the liability of the Contractor
	section,e tc. complete).								
	i) Crede I	1000 Cf	7 206 70	7.062.70	an	260.00	201.25		2) Reduce the rate by 8% if the excavated section is not dressed or
	i) Grade I	1000 Cft.	7,386.70	7,962.70	cu.m	260.90	281.25		excavated section is not dressed of

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAL	LEY, KHU	SHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	ii) Grade II iii) Grade III iv) Grade IV v) Grade V vi) Grade VI	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	7,967.50 9,533.05 10,594.30 11,716.30 12,576.95	8,927.50 10,685.05 11,938.30 13,252.30 14,304.95	cu.m cu.m cu.m cu.m	281.40 336.70 374.20 413.80 444.20	315.30 377.40 421.65 468.05 505.25		levelled to designed section.
	b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50 ft. (15 m) lead (including dressing and levelling to designed section, etc. complete):-		,	,					Tools and plants required shall be the liability of the contractor. Reduce the rate by 8% if the
	i) Grade I ii) Grade II iii) Grade III iv) Grade IV v) Grade V vi) Grade V	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	14,773.45 15,935.05 19,066.10 21,188.65 23,432.65 25,153.90	15,925.45 17,855.05 21,370.10 23,876.65 26,504.65 28,609.90	cu.m cu.m cu.m cu.m cu.m	521.80 562.85 673.40 748.40 827.65 888.45	562.50 630.65 754.80 843.30 936.15 1010.50		excavated section is not dressed or levelled to designed section.
13	Rehandling of earthwork:		1	- July 1					
	a) Lead upto a single throw of Kassi, phaorah or shovelb) Upto a lead of 50 ft. (15 m).	1000 Cft. 1000 Cft.	1,003.20 1,404.50		cu.m cu.m	35.45 49.60		ditto	
14	Rehandling of gravel work or excavated rock, lead upto 50 ft.(15 m)	1000 Cft.	4,012.80	- Deports	cu.m	141.75		17.1 to 17.5	
15	Filling, watering and ramming earth under floors:-							ditto	
	i) with surplus earth from foundation, etc. ii) with new earth excavated from outside, lead upto one chain (30 m).	1000 Cft. 1000 Cft.	2,022.25 3,902.35		cu.m cu.m	71.45 137.85			
16	Extra for every 50 ft. (15 m) additional lead or part thereof: i) for earhtwork soft, ordinary, hard and very hard. ii) for gravel, shingle or rock.	1000 Cft. 1000 Cft.	36.45 42.75	 	cu.m cu.m	1.30 1.50			This rate shall be applicable upto 1000 ft. total distance, including the lead covered in the item of earthwork
17	Transportation of earth all types when the total distance, including the lead covered in the item of work, is more than 1000 ft. (300 m)								This rate will be paid inaddition to the rate of earthwork, without deducting the lead covered in the item of
	 a) upto ¼ mile (400 m). b) for every 330 ft. (100 m) additional lead or part thereof, beyond ¼ mile (400 m) upto one mile. (1.6 Km.) 	1000 Cft.	1,618.70 84.10		cu.m	57.15 2.95			earthwork
	 for every ¼ mile (400 m) additional lead or part thereof, beyond one mile (1.6 Km.) upto 5 mile (8 Km). d) for every ½ mile (800 m) additional lead 	1000 Cft.	162.40		cu.m	5.75			
18	or part thereof, beyond 5 miles (8 Km). Dressing and levelling of earhtwork to designed section, etc. complete:-	1000 Cft.	144.35	1	cu.m	5.10		17.10 to 17.5	

No. Unit of M/ment Labour Composite Unit of M/ment Labour Composite No. No.	
No. Unit of M/ment Labour Composite M/ment Labour Composite No. No. No.	D 1
a) Ashes, sand, silt or soft soil. b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting. Per Chain M/ment Labour Composite M/ment Labour Composite Labour Composite Cu.m 4.60 cu.m 8.95 cu.m 21.65 cu.m 21.65 ditto This rate is in addressed earhtwo	Remarks
a) Ashes, sand, silt or soft soil. b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting. 1000 Cft. 130.50 cu.m 4.60 cu.m 8.95 cu.m 8.95 cu.m 21.65 1000 Cft. 612.50 cu.m 21.65 ditto This rate is in addressed earhtwo	
b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting. 1000 Cft. 254.05 cu.m 8.95 cu.m 21.65 cu.m 21.65 ditto This rate is in addressed earhtwo	
c) Gravel work or soft rock not requiring blasting. 1000 Cft. 612.50 cu.m 21.65 ditto This rate is in active Chain 119.25 Metre 3.90 ditto This rate is in active Gressed earhtwo	
blasting. 19 Dowel dressing. Per 119.25 Metre 3.90 ditto This rate is in addressed earhtwo	
19 Dowel dressing. Per 119.25 Metre 3.90 ditto This rate is in addressed earhtwo	
Chain dressed earhtwo	
Chain dressed earhtwo	ddition to payment for
	when exclusively
	and no earthwork is
carried out in en	mbankment or cutting.
b) Dressing of earthwork (done by machinery or otherwise 100Sft. 94.90 sq.m 10.20 i) The surface a	area dressed is to be
and left undressed) to designed section.	
	pplicable where the
	by the contractor ne who executed the
work.	le who executed the
21 Excavation in foundation of building, bridges and other	
structures, including dagbelling, dressing, refilling around	
structure with excavated earth, watering and rammiing lead	
upto one chain (30 m) and lift upto 5 ft. (1.5 m)	
a) in sand, ashes or loose soil 1000 Cft. 3,622.10 cu.m 127.95	
b) in ordinary soil. 1000 Cft. 4,229.30 cu.m 149.40	
c) in hard soil or soft murum.	raquired shall be the
22 Cutting hard rock such as granite, ballast, hard lime stone or sand stone, etc. with chisels and hammers, for small 1000 Cft. 29,789.75 33,803.60 cu.m 1052.15 1193.95 17.1 to 17.5 Tools and plants liability of the company of the	
foundations.	sinactor.
23 Extra for excavation requiring shoring. 1000 Cft. 541.20 785.15 cu.m 19.10 27.75 17.1 to 17.5 Composite rate in	includes materials,
i.e. plank, etc.	
24 Compaction of earthwork (soft, ordinary or hard soil):-	
a) Mixing, moistening earth to optimum moisture content 1000 Cft. 480.60 cu.m 17.00	
in layers for compaction, etc. complete.	
b) Compaction by rolling with animal driven	
roller/hand rammed:	
i) soft or sandy soil 1000 Cft. 601.90 cu.m 21.25	
	s not include hire
ii) ordinary soil 1000 Cft. 702.25 cu.m 24.80 charges of the re-	oller.
2) Roller to be '	supplied by
iii) hard soil 1000 Cft. 802.55 cu.m 28.35 Government	
iv) admireture of akingle	
iv) admixture of shingle 1000 Cft. 902.90 cu.m 31.90	
c) Ramming earthwork (all types of soil). 1000 Cft. 601.90 cu.m 21.25	

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAL	LEY, KHU	JSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit of		·	Unit of		•	No.	
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	d) Ramming earhtwork behind retaining walls.	1000 Cft.	802.55		cu.m	28.35			
25	Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture content in layers, etc. complete:							17.1 (a) *411-5 and 202-3	The rate also includes hire charges of machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.
	i) 95% to 100% maximum modified AASHO dry density.	1000 Cft.		785.00	cu.m	-	27.75		or driver and electricity, etc.
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		663.95	cu.m	-	23.45		
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.	/ ×	542.90	cu.m	-	19.20		
26	Extra for wet earthwork.	1000 Cft.	1,404.50	-	cu.m	49.60	-	17.1 to 17.5	That will support a man's weight.
27	Extra for slush or Daldal including dewatering.	1000 Cft.	3,210.25		cu.m	113.40	-	17.1 to 17.5	That will not support a man's weight.
28	Extra for puddling.	1000 Cft.	2,523.85		cu.m	89.15	-	ditto	
29	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	381.20		Metre	12.50	-	ditto	
	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.(15 m).	1000 Cft.	3,611.50		cu.m	127.55		17.1 to 17.5	
	1.(13 11).	Fun	wanter 9	DEPART	20年7月末				
31	Dag bailing 3" (75 mm) deep.	Per mile	1,522.15		Per Km	946.05		ditto	Dag bailing for layout of borrow pit, to be done by contractors at their own cost.
32	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	668.80		sq.m	71.95		ditto	
33	Berm cutting:-							17.1 to 17.5	
	lead upto a single throw of Kassi, phaora or shovel (without dressing).	1000 Cft.	1,805.75		cu.m	63.80			
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	3,220.80		cu.m	113.75			
34	Berm trimming both sides of channels:-							17.1 to 17.5	
	a) upto 3½ ft. (1.06 m) depth.	Per Mile	4,699.20		Per Km.	2937.00			
	 b) exceeding 3½ ft. to 5 ft. (1.06 to 1.5 m) depth. c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth 	Per Mile Per Mile	6,554.25		Per Km. Per Km.	4096.40 6400.90			
25	c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth Ploughing and levelling borrowpits.	FCI WITE	10,241.45		FCI KIII.	0400.90		ditto	Area plaughed to be managed
35	r loughing and levering borrowpits.							aitto	Area ploughed to be measured.
	i) upto 3 ft. (0.9 m) depth.ii) above 3 ft. (0.9 m) depth.	Per Acre Per Acre	1,003.20 2,006.40		Per Hect. Per Hect.	2478.95 4957.90			

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAI	LEY, KHU	SHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	•	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	Ño.	
		NI/IIIeiit	Labour	Composite	M/ment	Labour	Composite		
36	Making boundary or service roads, including dag-belling, levelling and dressing:							ditto	
	i) in unploughed land:								
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	506.00 677.60		Metre Metre	16.60 22.25			
	ii) in ploughed land:								
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide. b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	521.80 693.40		Metre Metre	17.10 22.75			
37	Earthwork by boats, including hire of boats:-	. /						17.1 to 17.5	For ordinary soil.
	 i) Digging and loading into boats, upto 50 ft. (15 m) lead. ii) Carriage by boats upto 10 chains (300 m). iii) Extra for every additional one chain (30 m) or part thereof beyond 10 chains (300 m). 	1000 Cft. 1000 Cft. 1000 Cft.	3,009.60 754.80 80.25		cu.m cu.m cu.m	106.30 26.65 2.85	 		
	iv) Unloading earth from boats.	1000 Cft.	1,404.50		cu.m	49.60			
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	1,203.85	Sec. 78	cu.m	42.50		17.1 to 17.5	
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	2,808.95	Dep <u>o</u> crts	cu.m	99.20		17.1 to 17.5	
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	2,257.20		cu.m	79.70		ditto	
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	386.75	408.75	cu.m	136.60	144.35		The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface								The rate does not include back filling after laying of sewer, which is payable separately.
	water, in all types of soil except shingle, gravel and rock: i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth iii) above 15.0 ft. (4.5 m) depth	1000 Cft. 1000 Cft. 1000 Cft.	3,275.10 5,558.00 7,163.10	3,635.90 6,093.15 7,698.25	cu.m cu.m cu.m	115.70 196.30 253.00	128.40 215.20 271.90		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to								The rate does not include back filling after laying of sewer, which is payable

	MRS, BI-ANNUAL PERIOD (1st FEBR	RUARY, 20	013 TO 31st	JULY, 2013)	TEH: NC	WSHER	A, SOAN VAL	LEY, KHU	SHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of			Unit of			No.	
		M/ment	Labour	Composite	M/ment	Labour	Composite		
	correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:							13.5	separately.
	 i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL. ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL. iii) Exceeding 8 ft. (2.4 m) depth below SSWL. 	1000 Cft. 1000 Cft. 1000 Cft.	4,613.40 5,767.25 8,650.90	7,071.35 8,889.70 12,005.35	cu.m cu.m cu.m	162.95 203.70 305.55	249.75 314.00 424.05		
44	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	3,014.90		cu.m	106.50	-	**8.1	The rate does not include back filling after laying of pipe line, which is payable separately.
45	Cutting and removing trees within a distance of 100 ft. (30 m)								
	a) upto 2½ ft. (760 mm) girth. b) above 2½ ft. to 6 ft. (760 to 1800 mm) girth.	Each Each	606.55 1,178.10		Each Each	606.55 1178.10			
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	752.40		Each	752.40			
47	Jungle clearance and removing within 100 ft. (30 m).	-		G. G. Co					
	a) light b) thick	1000 Sft. 1000 Sft.	100.30 200.65	Departs	sq.m sq.m	1.10 2.15			
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	48.15		sq.m	5.20			
49	Ploughing 3 times.	Per Acre	407.55		Per Hect.	1007.10			
50	Levelling, dressing and making lawns.	100Sft.	200.65		sq.m	21.60			
51	Turfing lawns (excluding cost of turf).	100Sft.	171.60		sq.m	18.45			
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry,wet slush,daldal and under water) including its disposal and prepartion of working pad for operation of machinery. (Rates includes 100 ft lead)	1000 Cft.		2123.00	cu.m		75.00		

 ^{*} Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 ** Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER.	A, SOAN VAI	LLEY, KHUSHAB		
Sr.	Description]	Rate (British Sy	stem)	Ra	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	Stone Work									
1	Dismantling dry stone masonry.	100Cft.	341.10		cu.m	120.50		18.1		
2	Dismantling stone masonry in mud mortar.	100Cft.	501.60		cu.m	177.15		ditto		
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	1,203.85		cu.m	425.20		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.	
4	a) Dismantling dry stone or spawl pitching.	100Cft.	601.90		cu.m	212.60		ditto		
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	762.45	5	cu.m	269.30		ditto		
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	1,003.20		cu.m	354.35		ditto		
	Dismantling stone pitching, cement or lime grouted. Dismantling stone in crates:	100Cft.	1,605.10	Departs	cu.m	566.90		ditto		
	a) wooden crates	100Cft.	802.55		cu.m	283.45				
	b) wire crates	ditto	1,003.20		ditto	354.35				
8	Dismantling stone ware drain including base concrete.	100Cft.	561.80		cu.m	198.45		ditto		
	<u>Brick Work</u>									
9	lling.	100Cft.	200.65		cu.m	70.85		18.1		
10	onry.	100Cft.	501.6		cu.m	177.15		ditto		
11	onry.	100Cft.	341.1		cu.m	120.5		ditto		
12	ortar.	100Cft.	702.25		cu.m	248.05		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th	
13	ortar.	100Cft.	1705.45		cu.m	602.35		ditto	and subsequent floors respectively against item No. 12, 13, 14 & 15.	

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAL	LLEY, KHUSHAB		
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
14	Dismantling cement block masonry.	100Cft.	1,504.80		cu.m	531.50		ditto		
15	Dismantling Dhajji walling.	100Cft.	401.30		cu.m	141.75		ditto		
	<u>Concrete</u>									
16	Dismantling mud concrete.	100Cft.	802.55		cu.m	283.45		ditto		
17	Dismantling lime concrete.	100Cft.	1,103.50		cu.m	389.75			Add extra 13%, 32% and 51% on	
18	Dismantling lime or cement concrete, under water.	100Cft.	4,213.45		cu.m	1488.20			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 17, 19 & 20.	
19	a) Dismantling cement concrete plain 1:4:8.	100Cft.	2,207.05	,	cu.m	779.55		ditto		
	b) Dismantling cement concrete plain 1:3:6.	ditto	3,611.50		ditto	1275.60				
	c) Dismantling cement concrete 1:2:4	ditto	4,414.10		ditto	1559.05				
	plain. d) Dismantling cement concrete with brick	ditto	1,203.85		ditto	425.20				
	aggregate. e) Dismantling D.P.C. of cement concrete 1½" thick (40 mm) and clearing the site.	ditto	601.90	- 19	ditto	212.60				
20	Dismantling cement concrete reinforced, separating reinforcement from concrete,	100Cft.	7,223.05	S = 18	cu.m	2551.20		ditto		
	cleaning and straightening the same.	The second	rantos 9	Departs	nem t					
	Roofing			9						
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or ballies.	100Sft.	240.75		sq.m	25.90		18.1		
22	a) Dismantling 1st class tile roofing.	100Sft.	601.90		sq.m	64.75			Add extra 13%, 32 and 51% on labour rate only for 2nd, 3rd, 4th	
	b) Dismantling 2nd class tile roofing.	100Sft.	501.60		sq.m	53.95		ditto	and subsequent floors respectively against items No. 22, 25, 26 and 28.	
23	Dismantling from any height, asbestos sheets and ridge coping.	100Sft.	340.55		sq.m	36.65		18.1		
24	a) Dismantling roof of wooden planks and battens, from any height.	100Sft.	272.45		sq.m	29.3		ditto		
	b) Dismantling wooden ceiling above 20' (6.0 m) height in difficult position, including lifting with care and special scaffolding along live electric wires and with	100Sft.	1,058.10		sq.m	113.85		ditto		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	JARY, 2013 TO 31st JULY, 2013) 1)WSHER	A, SOAN VAL	LEY, KHU	SHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
		CIIIt	Labour	Composite	CIII	Labour	Composite		
	machines underneath.								
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	802.55		sq.m	86.35		ditto	
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	1,003.20		sq.m	107.95		ditto	
27	Stripping and stacking slate or tiles from the truss roofing.	100Sft.	501.60		sq.m	53.95			
	b) Stripping and stacking C.I. sheet roof.	ditto	468.45		ditto	50.40			
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	660.00		ditto	71.00			
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	802.55		sq.m	86.35		18.1	
	Flooring	18/	1-65	- 16/					
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	341.10	S 4 5 6	sq.m	36.70		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively
30	Dismantling plank or wooden block flooring, etc.	100Sft.	501.60	Departs	sq.m	53.95		ditto	against items No. 29 and 30.
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-								i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.
	a) 6" to 12" (150 to 300 mm) diameter	Per Lft	13.60		Metre	44.60 71.00			ii) Danda albayya aluisa yalyas
	b) 13" to 24" (325 to 600 mm) diameter c) 25" to 36" (625 to 900 mm) diameter	Per Lft ditto	21.65 25.40		Metre ditto	83.30			ii) Bends, elbows, sluice valves, etc. should not be paid for extra if
	d) Above 36" (Above 900 mm) diameter	ditto	36.10		ditto	118.40			fixed in the length of pipe line that is being dismantled.
	WOOD WORK								
32	a) Removing door with chowkat.	Per	180.20		Per	180.20		18.1	Add extra 13%, 32% and 51% on
	b) Removing windows and sky lights with chowkat.	No. ditto	141.10		No. ditto	141.10			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.
33	Removing ventilators and wooden sunshade, etc.	Per No.	74.05		Per No.	74.05		ditto	20.
34	a) Dismantling wooden beams upto 12' (3.65m)	Per No.	125.40		Per No.	125.40		ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	WSHER	A, SOAN VAI	LEY, KHU	ISHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	length.								
	b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length.	ditto	200.65		ditto	200.65			
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	243.25		sq.m	26.15		ditto	
	b) Dismantling wooden trusses.	100Kg	715.65		%Kg	715.65			
36	Dismantling wooden palisade fencing.	Per Lft.	20.00		Metre	65.60		ditto	
	<u>Iron work</u>								
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	723.20		%Kg	723.20		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.
38	Dismantling rolled steel beams or iron rails, etc.	100Kg	329.30		%Kg	329.30		ditto	
39	Dismantling iron latrine.	Per Unit/ 2 Seats	781.45	6	Per Unit/ 2 Seats	781.45		ditto	
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per inch bore	16.70	3	Each per cm bore	6.70		ditto	
41	a) Dismantling B.G. water column.	Each	5,062.20		Each	5062.20		ditto	
	b) Dismantling M.G. or N.G. water column.	Each	3,382.50		Each	3382.50		ditto	
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	341.10		Metre	11.20		18.1	
	Miscellaneous								
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	160.50		sq.m	17.25		18.1	
44	Dismantling cloth ceiling and supporting timber.	100Sft.	300.95		sq.m	32.40		ditto	
45	Dismantling and removing road metalling.	100Cft.	802.55		cu.m	283.45		ditto	
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead (30 metre).	100Cft.	1,071.40		cu.m	378.40		ditto	
47	Removing mud plaster from walls.	100Sft.	83.60		sq.m	9.00		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th
48	Removing cement or lime plaster.	100Sft.	167.20		sq.m	18.00		ditto	and subsequent floors against item No. 47, 48, 49, & 50 respectively

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	OWSHER.	A, SOAN VAL	LEY, KHU	ISHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
49	Scraping:-							18.1	
	a) White wash or colour wash.	100Sft.	100.30		sq.m	10.80			
	b) Ordinary distemper, oil bound distemper, or paint of wall.	ditto	300.95		ditto	32.40			
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	960.95		sq.m	103.40		18.1	
51	Scraping boulders.	100Cft.	1,404.50		cu.m	496.05		18.1	
	Cleaning lime or cement mortar of old stones to be used in masonry.	100Cft.	702.25		cu.m	248.05		18.1	
	Electric Wiring	/	()						
	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).	Per point	31.70	32.10	Per point	31.70	32.10		
	Dismantling plug point and making good damaged surface (building portion).	Per point	27.15	27.50	Per point	27.15	27.50		
	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-		rance (Departs	eent				
	i) on surface ii) recessed in wall	Per foot Per foot	5.80 12.20	5.85 12.35	P.Mtr P.Mtr	19.00 40.00	19.20 40.50		

5. MORTAR

S, BI-A	NNUAL PERIOD (1st FEBRUA						
		Dry 100 C	Material Required Ift. Wet (Ready) M	i for Mortar	Dry One C	Material Required um Wet (Ready)	d for Mortar
S. No.	Ratio of Mortar	Cement	Lime	Tortur	Cement	Lime	Sand
		(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.
		Bag	Ctt.	Ctt.	Bag.	Cum	
1	2	3	4	5	6	7	8
1	Cement: Sand						
	1:2	33.48		82	11.83		0.82
	1:3	23.11		85	8.16		0.85
	1:4	18.37		90	6.49		0.90
	1:5	14.70		90	5.19		0.90
	1:6	13.61		100	4.81		1.00
	1:7	11.68		100	4.12		1.00
	1:8	10.21		100	3.61		1.00
2							
2	Cement: Lime: Sand	10.05	17.0	0.0	4.22	0.45	0.00
	1:1:6	12.25	15.0	90	4.33	0.15	0.90
	1:1:7	10.70	13.1	92	3.78	0.13	0.92
	1:1:8	9.39	11.5	92	3.32	0.12	0.92
	1:1:9	8.52	10.44	94	3.00	0.10	0.94
	1:1:10	7.67	9.4	94	2.71	0.09	0.94
	1:2:8	9.19	22.5	90	3.25	0.23	0.90
	1:2:9	8.16	20.0	90	2.88	0.20	0.90
	1:2:10	7.67	18.8	94	2.71	0.19	0.94
	1:2:12	6.39	15.66	94	2.26	0.16	0.94
	1:3:12	6.26	23.0	92	2.21	0.23	0.92
	1:3:14	5.47	20.1	94	1.93	0.20	0.94
	1:3:16	4.82	17.7	94	1.70	0.18	0.94
	1: 1/4: 3	23.11	7.0	85	8.16	0.07	0.85
3	Lime: Sand	(Companies	ne (II))urens	rathamourant			
	1:2	THE RECOGNISHED A	43	86		0.43	0.86
	1:3		31	93		0.31	0.93

5. MORTAR

MR	RS, BI-ANNUAL PERIOD (1st	FEBRUAR	•			3) TEH: N	IOWSHE	RA, SOAI	VALLE	Y, KHUSI	HAB		
			Dry Material Wet	Required for (Ready) Mor			Dry Material Required for one M' Wet (Ready) Mortar						
S. No.	Ratio of Mortar	Clay	Lime (Putty)	Sand	Surkhi	Cinder	Clay	Lime (Putty)	Sand	Surkhi	Cinder		
	<u> </u>	Cft.	Cft.	Cft.	Cft.	Cft.	M	M	M	M	M		
1	<u> </u>	3	4	5	6	/	3	4	5	6	/		
4	Mud	135					1.35						
5	Lime : Surkhi												
	2:3		49.00	-	73.5		-	0.49	-	0.74	-		
	1:2		40.75	-	81.5		-	0.41	-	0.82	-		
	1:3		30.30	-	91.0		-	0.30	-	0.91	-		
6	Lime: Sand: Surkhi												
	1:1:1		40.50	40.5	40.5		-	0.41	0.41	0.41			
7	Lime: Cinder)xf= \									
	1:1		57.0	-	- `	57.0	-	0.57	-	-	0.57		

Wet material required for 100 Cft. Wet material required for 1M³ (35.32 Cft)

			masonry (inc	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The same	The second secon	masonry (including wasta	,
1	Brick a) b) c) d)	Masonry: Mud Mortar Cement, Sand Cement, Lime (Putty) Sand Lime (Putty) Sand	4	8	35.00 25.00 25.00 25.00	Cft Cft	0.35 0.25 0.25 0.25	M ³ M ³ M ⁵ M ⁵
2	Stone a)	e Masonry: Random rubble, uncoursed Foundation and Plinth			45.00	CE Department	0.45	M ⁵
) Superstructure) CoursedAshlar Block in course or Sc	rahled masonry		40.00 35.00 30.00	Cft Cft	0.40 0.35 0.30	M ³ M ³ M ³
	c)	Ashlar fine masonry	abled masomy		20.00		0.20	M^3
Notes:	(1) (2) (3) (4)	Cement Unslaked lime Slaked lime Quick lime	1 Cft. 1.7 Cft. 2.5 Cft. 40 Kg	=	40.8233 37.3242 37.3242 Will yie	Kg		

6. CONCRETE

Notes 1 Notes (1) Rates for all finished works include the removal of surplus debris, unused material and by products.

2 If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
								_				
1	Mud concrete in foundation including watering and ramming,	100Cft	2226.05	3786.05	cu.m	786.25	1337.25		The stone ballast, crushed bajri,			
	using brick or stone ballast 1½" (40 mm) gauge.								round shingle from nallah, or brick			
		100.00	150100	2022.00		524.50	10.57.55		ballast may be used according to			
2	Dry rammed brick or stone ballast, 1½" to 2"(40 mm to 50	100Cft	1504.80	3022.80	cu.m	531.50	1067.65		their comparative cheaper rates in			
	mm) gauge.	.1.6)				various areas of the Province.			
		8			무셨							
					7 82							
		1634	1:30	- ,60)	23							
3	Cement concrete brick or stone ballast 1½ " to 2" (40 mm to	Y-10			63			20.1	-do-			
	50 mm) gauge, in foundation and plinth:-			ST. Comments				_	<u>'</u>			
		2070		07715		-E.						
	(a) Ratio 1: 3: 6	100Cft	2940.30	19	cu.m	1038.50	4230.65					
	(b) Ratio 1: 4: 8	ditto	2940.30		"	1038.50	3603.95					
	(c) Ratio 1:5:10	ditto	2940.30		"	1038.50	3271.25					
	(d) Ratio 1: 6:12	ditto	2940.30	8551.20	"	1038.50	3020.30					
	(e) Ratio 1: 6: 18	ditto	2940.30		"	1038.50	2737.90					
	(f) Ratio 1: 7:20	ditto	2940.30	7417.75	"	1038.50	2619.95					
4	Extra on item No. 3 above, for sedimentation tank or filter											
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri,			
									round shingle from nallah, or brick			
	(a) in bed	100Cft	972.85	-	cu.m	343.60	-		ballast may be used according to			
									their comparative cheaper rates in			
	(b) on slope	ditto	1453.30	-	"	513.30	-		various areas of the Province.			
5	Cement concrete plain including placing,							20.1				
	compacting, finishing and curing											
	complete (including screening and											
1	washing of stone aggregate):											

Page 41

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	R	ate (British Sys	stem)	R	Rate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(a) Ratio 1: 1:2 (b) Ratio 1: 1½: 1½ (c) Ratio 1: 1½: 3 (d) Ratio 1: 2: 3	100Cft ditto ditto ditto	4018.10 4018.10 4018.10 4018.10	24699.20 24228.80 20046.20 19147.10	"	1419.20 1419.20 1419.20 1419.20	8723.75 8557.60 7080.30 6762.75						
	(e) Ratio 1: 3: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 6 (h) Ratio 1: 3: 6 (i) Ratio 1: 4: 8	ditto 100Cft ditto ditto ditto	4018.10 4018.10 4018.10 4018.10 4018.10			1419.20 1419.20 1419.20 1419.20 1419.20	6019.90 6197.05 5577.20 5371.70 4778.05						
6	Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):- (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-			Depart				20.4	1) The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring. 2) Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid extra. 3) This item shall not be applicable to factory made units.				
	(1) Type A (nominal mix 1:1:2) (2) Type B (nominal mix 1: 1½: 3) (3) (c) Type C (nominal mix 1: 2: 4) (a)(ii) Reinforced cement concrete in slab of rafts / strip foundation, base slab of column and retaining walls; etc and other structural members other than those mentioned in 5(a) (i) above not requiring form work (i.e. horizental shuttering) complete in all respects:- (1) Type A (nominal mix 1: 1: 2) (2) Type B (nominal mix 1: 1½: 3) (3) Type C (nominal mix 1: 2: 4)	Per Cft ditto ditto Per Cft ditto ditto	92.20 92.20 92.20 54.40 54.40 54.40	228.00		3256.50 3256.50 3256.5 1921.40 1921.40 1921.40	12264.85 10633.10 9758.90 9849.00 8052.95 7175.25		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab sand and local sand respectively is used.				

Chap-6 (Concrete) Page 42

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks			
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.				
				•			•					
	(b) Precast reinforced cement concrete and prestressed											
	reinforced cement concrete in columns, beams, lintels, stair											
	cases, shelves, etc.											
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	69.55	312.85	cu.m	2456.50	11049.85					
	(2) Type B (nominal mix 1:1½: 3)	ditto	69.55	266.40	"	2456.50	9409.25					
	(3) Type C (nominal mix 1: 2: 4)	ditto	69.55	241.90	"	2456.50	8543.90					
	(c) Erecting and fixing in position, precast cement concrete											
	or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m)	Per Cft	32.10	45.95	cu.m	1133.75	1622.95					
	including all charges.		/ ×									
	(d) Add extra labour for R.C. concrete in	Per Cft	15.05		cu.m	531.55	-					
	2nd and subsequent storeys.				그셨.							
		. 39			7 E.							
7	Providing and casting in situ bored reinforced concrete piles	1834	1	67	13			*851-1	Composite rate shall be reduced by			
	with type C concrete (nominal mix 1: 2: 4), using 10% extra	7.3	100		200			to	Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab			
	cement in dry mix, and course sand, including all labour and	~			Spar			851-10	sand and local sand respectively is used.			
	material (except the cost of steel reinforcement and its			0								
	labour for bending and laying in position, etc. which will be	Œ.	vance (I)epart	nen ener							
	paid separately, including, screening & washing of shingle	. Lin. 1999	The street of the same same same same same same same sam	and the first sector is	CONTRACTOR I							
	and curing:- i) 18 " (450 mm) dia pile	Per Rft	702.95	981.15	Metre	2305.70	3218.15					
	ii) 20" (500 mm) dia pile	Per Rft	797.20	1140.40	Metre	2614.80	3740.50					
	iii) 22" (550 mm) dia pile	Per Rft	943.7	1344.55	Metre	3095.35	4410.1					
	iv) 24" (600 mm) dia pile	Per Rft	1122.55	1617.05	Metre	3681.95	5303.95					
8	Fabrication of mild steel reinforcement bar cage for R.C.C.	T CI KIT	1122.33	1017.03	wieue	3001.73	5505.75	*851-5	The rate includes wastage, overlaps,			
Ü	bored piles, including cutting, bending, laying in position,								etc. but does not apply to the laps and			
	welding and fastening, including cost of binding wire and								spiral reinforcement which are specifically			
	labour charges for binding of steel reinforcement (also								shown in the structural / working drawings			
	includes removal of rust from the bars):-								of piles as per lapping requirements			
	iniciades removal of fust from the vars):-								of design.			
	(a) plain bars	Per Cwt.	1102.20	4521.25	100 kg	2169.70	8900.10		or design.			
	(b) deformed bars	ditto	1102.20	5987.05	U	2169.70	11785.55					
9	Fabrication of mild steel reinforcement for cement concrete,							*851.5	The rate includes wastage, overlaps			
	including cutting, bending, laying in position, making joints								and chairs, etc.			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
			240041	Сотролес	- CIIIV	240041	Composite						
	and fastenings, including cost of binding wire and labour												
	charges for binding of steel reinforcement (also includes												
	removal of rust from bars):-												
	(a) Plain bars	Per Cwt.	300.30		_	591.15	7666.25						
	(b) Deformed bars (Grade-40)	ditto	300.30		ditto	591.15	10784.35						
	('c) Deformed bars (Grade-60)	ditto	300.30	5841.45	ditto	591.15	11498.90						
10	Precast cement concrete solid or face blocks (1:2:4),	Per Cft	37.70	168.20	cu.m	1331.55	5940.80	20.2					
	including cost of templates.												
			/ ×) \									
11	Precast cement concrete hollow blocks (1: 2: 4), including	Per Cft	82.85	168.75	cu.m	2926.25	5960.25	20.2					
	cost of templates and constructing walls thereof.	- de 6			111								
12	Danidia d Sain	D 06	24.00	46.05	78	259.25	105 50	20.1.4-					
12	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	Per Sft	24.00	46.05	sq.m	258.25	495.50	20.1 to 20.4					
	(1. 2. 4), without steet.	163/7	1.50	/ جورت	43			20.4					
13	Extra labour for laying concrete plain or reinforced:	- 0			33								
				0									
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	1605.10	II))eersoort	cu.m	566.90	-						
	(b) for every additional 10'(3 m) height.	100Cft	1003.20	and the second of	cu.m	354.35	-						
14	Extra labour for work of weirs, rail or road bridges, syphons, and	100Cft	401.30		cu.m	141.75							
14	concreting in superstructure	100Cit	401.30	-	Cu.III	141.75	-						
	conversing in superstance												
15	Making reinforced cement concrete spout, including fixing in	Each	300.30	442.10	Each	300.30	442.10	20.4					
	position (2½' x 6" x5") (760 mmx150 mm x 125 mm)												
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement	Per hole	720.70	-	Each	720.70	-	20.1					
	concrete or stone masonry walls and repairing.												
17	Extra labour for skipping concrete in wells.	100Cft	2472.80	_	cu.m	873.40	-	20.1					
18	Nicking concrete surface:												
	(a) Cement concrete surface	100Sft	279.85		sq.m	30.10	-						
	(b) Lime concrete surface	ditto	92.35	-	"	9.95	-						
<u></u>													

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 2	2013 TO 31s	t JULY, 201	3) TEH: I	NOWSHE	RA, SOAN V	ALLEY,	KHUSHAB
Sr.	Description	R	Rate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
19	Preparing, watering and ramming surface for laying concrete (for Headworks only):- (a) Horizontal floor (b) Glacis and crest (c) Inverted filters	100Sft ditto ditto	257.05 380.15 120.10		sq.m "	27.65 40.90 12.90			
20	Fabrication of high tensile steel prestressing cables for prestressed (post tensioned) concrete, including assembling by drawing the H.T. wire through metal spacer plate, inserting in helix core and taping or tying, sheathing in longitudinally welded metal corrugated sheath, positioning, anchorage with male and female set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule, maintaining stressing record and supply the same in the approved proforma to the Engineer-in-charge, making loop at blind end, including all materials required for it, grouting the cable ducts with cement, cutting projected ends and making good recesses, etc., complete in all respects.	100 Kg.	3550.80	31595.30	100 Kg.	3550.80	31595.30	*811-1 to 811-11	The rate includes wastage in cutting and breakage in stressing, etc.
21	Fabrication of High Tensile steel reinforcement for prestressed (pretension) concrete work, including inserting wire in moulds, providing M.S. shear bars, spacers and lift hooks, male and female anchorage, tie down, struts, stressing cables, maintaining stress record and supply the same in approved proforma to the Engineer-in-charge, cutting wires and projecting ends and making good recesses, etc., complete in all respects. Lifting, transporting and placing precast prestressed concrete	100kg	2134.45	29149.55	%kg	2134.45	29149.55	*811-1	1) The rate includes wastage in cutting and breakage in stressing,etc. 2) Quantity of H. T. wire will form basis of payment. 3) This item shall not be applicable to factory made units.
	B eam, Girder and other members (excluding battens) etc. in Position on the bridge to correct alignment and level, etc. complete i) Beam upto 50 ft. (15 m) length ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length iv) Beam above 100ft. (30m) upto 150ft.(45m) length v) Beam above 150ft. (45m) length	100Cft 100Cft 100Cft 100Cft		1352.60 1954.62 2554.05 3286.90 4008.25	cu.m cu.m cu.m cu.m		477.75 690.35 902.10 1160.95 1415.70		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
23	Providing and laying foam concrete 3 inch (75 mm) thick, using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,	Per Sft.	22.10	55.40		237.80	596.10				
24	Providing and fixing 6 in(150 mm). wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-										
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	12.75 13.05	87.45 79.15	\	41.80 42.80	286.85 259.60				
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-		557		7						
	a) On interior surface (without mastic strip)	Per Rft.	11.65	86.35	January St. Phys. Lett. B 1985 1985 1985 1985 1985 1985 1985 1985	38.20	283.25				
	b) On exterior surface (with mastic strip)	ditto	11.65	89.35	"	38.20	293.05				
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on expansion joints complete in all respects.	Per Sft.	12.00	97.20	Sq.m	129.10	1045.85				
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG. stopper to expansion joint.	Per Rft.	4.30	66.90	Metre	14.10	219.45				
28	Providing embeding 10" (250 mm) wide ¼" (6 mm) thick rubber water stopper in expansion joints of R.C.C. roof slab complete in all respects.	Per Rft.	17.50	64.30	Metre	57.40	210.85				
29	Filling expansion joints with bitumen. sand & saw dust in ratio 1:2:2.	Per Rft per inch width	2.50	20.35	P.Metre/ Per 25 mm Width	8.20	66.75				
30	Filling expansion joints with bitumen.	Per Rft.	33.45	-	Metre	109.70	-				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	R	Rate (British Sys	tem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				

31	Laying asphaltic mixture in expansion joints.	Per Rft.	35.10	-	Metre	115.15	-		Material to be paid on actuals.			
32	Providing and fixing theremopore (foamed polythene)											
	sheet in horizontal and vertical expansion joints:											
	11.07	D GC	4.00	0.70	q	51.65	104.25					
	 a) 1" (25 mm) thick thermopore sheet b) 1½" (40 mm) thick thermopore sheet 	Per Sft. ditto	4.80 4.80	9.70 13.95	Sq.m	51.65 51.65	104.35 150.10					
	b) 1/2 (40 mm) thek thermopore sheet	ditto	4.80	13.93		31.03	130.10					
33	Providing and laying damp proof course of cement concrete		/ ×)								
	1:2: 4(using cement, sand and shingle), including bitumen		/	1	\							
	coating :-	.1.6	-)							
					무셨							
	(a) with one coat bitumen and one coat polythene sheet				7 182							
	500gauge	18/7	1.6	-150)	13							
	i) 1½" thick (40 mm)	100Sft	1057.75	4064.05	sq.m	113.80	437.30					
	ii) 2" thick (50 mm)	100Sft	1057.75	4556.25	sq.m	113.80	490.25					
	iii) 3" thick (75 mm)	100Sft	1104.40	5671.05	sq.m	118.85	610.20					
	(b) with 2 coats of bitumen:											
	i) 1½" thick (40 mm)	100Sft	1057.75	4534.25	sq.m	113.80	487.90					
	ii) 2" thick (50 mm)	100Sft	1057.75		_	113.80						
	iii) 3" thick (75 mm)	100Sft	1104.40		sq.m	118.85	660.70					
34	Providing and laying damp proof course with cement sand											
	plaster and bitumen coating:-											
	(a) with one coat of bitumen and one coat of polythene sheet											
	500 gauge:-											
	i) Ratio 1: 4	10096	007.00	2670.75		106.20	200.25					
	a) ½" thick (13 mm)	100Sft	987.80		-	106.30						
	b) 3/4" thick (20 mm)	100Sft	987.80	2930.80	sq.m	106.30	315.35					
ь			l			I						

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	F	Rate (British Sys	tem)	F	Rate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ii) Ratio 1:3	10000	007.00	2550 45		10520	20.5.00					
	a) ½" thick (13 mm)	100Sft	987.80		_	106.30	296.80					
	b) 3/4 " thick (20mm)	100Sft	987.80	3023.40	sq.m	106.30	325.30					
	iii) Ratio 1:2											
	a) ½ " thick (13 mm)	100Sft	987.80	2849.30	sq.m	106.30	306.60					
	b) ¾ " thick (20 mm)	100Sft	987.80	3215.50	sq.m	106.30	346.00					
	(b) with 2 coats of bitumen:-											
	i) Ratio 1: 4		/ "									
	a) ½" thick (13 mm)	100Sft	987.80	2985.30	sq.m	106.30	321.20					
	b) 3/4" thick (20 mm)	100Sft	987.80		sq.m	106.30	348.25					
		. 1887			7 🕸 .							
	ii) Ratio 1:3	838	-	-	7 3/5	-						
	a) ½ " thick (13 mm)	100Sft	987.80	3065.00	sq.m	106.30	329.80					
	b) 3/4 " thick (20 mm)	100Sft	987.80		A 17 T. C.	106.30	358.30					
	iii) Ratio 1:2	002	an service server of	W. and a south	facus anaes	46						
	a) ½ " thick (13 mm)	100Sft	987.80	3261.50	sq.m	106.30	350.95					
	b) 34 " thick (20 mm)	100Sft	987.80		_	106.30	393.45					
35	Providing and laying vertical damp proof course with cement											
	sand plaster and bitumen coating:-											
	(a) with one coat of bitumen and one coat of polythene sheet											
	500 gauge:											
	i) Ratio 1: 4											
	a) ½" thick (13 mm)	100Sft	987.80	2573.60	sq.m	106.30	276.90					
	b) 3/4" thick (20 mm)	100Sft	987.80		_	106.30	304.00					
	ii) Ratio 1:3											
	a) ½ " thick (13 mm)	100Sft	987.80	2652.80	sq.m	106.30	285.45					
	b) 3/4 " thick (20 mm)	100Sft	987.80		_	106.30	313.95					
					•							

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	I	Rate (British Sys	stem)	F	Rate (Metric S	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	iii) Ratio 1:2												
	a) ½ " thick (13 mm)	100Sft	987.80	2849.30	sq.m	106.30	306.60						
	b) ¾ " thick (20 mm)	100Sft	987.80	3244.30	sq.m	106.30	349.10						
	(b) with 2 coats of bitumen:-												
	i) Ratio 1: 4												
	a) ½" thick (13 mm)	100Sft	987.80	2985.20	sq.m	106.30	321.20						
	b) 3/4" thick (20 mm)	100Sft	987.80	3236.65	sq.m	106.30	348.25						
			/ ×4) \									
	ii) Ratio 1:3		/ ~	1	\								
	a) ½ " thick (13 mm)	100Sft	987.80	3064.30	sq.m	106.30	329.70						
	b) 3/4 " thick (20 mm)	100Sft	987.80	3329.25	sq.m	106.30	358.25						
		. 183			J 887.								
	iii) Ratio 1:2	188	-	67									
	a) ½ " thick (13 mm)	100Sft	987.80	3260.95	sq.m	106.30	350.90						
	b) ³ / ₄ " thick (20 mm)	100Sft	987.80	3655.75	sq.m	106.30	393.35						
36	Grouting concrete between, the grooves of gates, including	100Cft	4771.80	E)epart	cu.m.	1685.40	-						
	shuttering.												
37	Chiesel dressing concrete surface on sides of grooves.	100Sft	153.90	-	sq.m	16.55	-						
38	Laying and ramming dry ballast or kankar.	100Cft	1630.20	-	cu.m	575.80	-						
39	Hoisting and placing in position R.C.C. shelves.	per No.	53.20	-	per No.	53.20	-						
40	Breaking brick ballast, screening and stacking:-												
	(a) 2"(50 mm) ring	100Cft.	1254.00	-	cu.m	442.90	-						
	(b) 1½ "(40 mm) ring	ditto	1404.50	-	"	496.05	-						
	(c) 1" (25 mm) ring	ditto	1630.20	-	"	575.80	-						
	(d) Jhama ballast ¾"(20 mm) ring	ditto	1881.00		"	664.35	-						
41	Supplying and fixing broken glasses on court yard walls, including 1:3: 6 cement concrete coping.	Per Rft	39.40	79.30	metre	129.25	260.10						

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	2013 TO 31s	t JULY, 201	3) TEH:	NOWSHE	RA, SOAN V	ALLEY,	KHUSHAB
Sr.	Description	R	ate (British Sys	tem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Crushing stone ballast by machine. Breaking stone ballast screened and stacked:-	100Cft	1254.00	-	cu.m.	442.90	-		This does not include the charges for working of crushers, but includes manual labour for carriageof stone to crusher within three chains (90 m) and also stacking the product after crushing within three chains (90 m).
44	(a) 2" ring (50 mm) (b) 1½" ring (40 mm) (c) 1" ring (25 mm) d) ½" ring (13 mm) (e) 1/8" to ¼" ring (3 mm to 6 mm) Screening and stacking stone ballast shingle or bajri, etc.	100Cft. ditto ditto ditto ditto	1404.50 1630.20 1881.00 2508.00 4263.60		cu.m.	496.05 575.80 664.35 885.85 1505.90	- - - -		
45	Washing ballast, bajri or shingle.	100Cft.	401.30		cu.m.	141.75	-		
46	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2½' (1.50 m x 0.76 m)	Each	230.45	Depart	Each	230.45	-		

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

7. BRICK WORK

- 1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.
- 2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4"x4" (200x100x100 mm) nominal.

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	2013 TO 31s	t JULY, 2013	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB				
Sr. No.	Description		Rate (British Sy	estem)	R	Rate (Metric S	System)	Spec. No.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
1	Pacca brick work in mud mortar in buildings: i) in foundation and plinth ii) in ground floor	100Cft. ditto	2100.40 2781.50	12432.40 13113.50	cu.m ditto	741.85 982.45	4391.10 4631.70	21.1 to 21.4	Masonry of boundary wall to be considered as masonry other than building. The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
2	Add extra labour on item No. 1 for brick work in:- i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors	100Cft. ditto ditto ditto	541.20 1222.30 1903.45 3065.05		cu.m ditto ditto ditto	191.15 431.70 672.30 1082.60	- - - -		
3	Pacca brick work in mud mortar other than building:- i) upto 20 ft. (6.1 m) height ii) extra labour for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	2860.40 541.20	13192.40	cu.m ditto	1010.30 191.15	4659.55 -	21.1 to 21.4	Same remarks as against item No. 1 above
4	Pacca brick work in foundation and plinth in:- i) Cement, sand mortar:-							ditto	Same remarks as against item No. 1 above.
	Ratio 1:2 Ratio 1:3 Ratio 1:4 Ratio 1:5 Ratio 1:6 Ratio 1:7 Ratio 1:8 ii) lime, cement sand mortar:- Ratio 1:1:6 Ratio 1:1:7 Ratio 1:1:8 Ratio 1:1:9 Ratio 1:1:10	100Cft. ditto	2764.50 2764.50 2764.50 2764.50 2764.50 2764.50 2764.50 2764.50 2764.50 2764.50 2764.50	17631.30 16574.10 15939.80 15516.90 15199.00 14991.90 14808.50 15351.90 15139.55 14967.80 14823.75 14715.85	cu.m ditto	976.35 976.35 976.35 976.35 976.35 976.35 976.35 976.35 976.35 976.35	6227.40 5853.95 5629.95 5480.55 5368.30 5295.15 5230.35 5422.30 5347.30 5286.65 5235.75 5197.65	21.1	The rate of lime mortar also includes grinding of mortar.

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	.013 TO 31s	t JULY, 2013)) TEH: I	NOWSHE	RA, SOAN VA	ALLEY, KHUSHAB		
Sr.	Description]	Rate (British Sy	stem)	F	Rate (Metric	System)	Spec.	Remarks	
No.		TT *4	T -1	G	TI*4	T -1	G	No.		
-	<u> </u>	Unit	Labour	Composite	Unit	Labour	Composite			
	iii) lime, sand mortar 1:2	100Cft.	2764.5	14143.1	cu.m	976.35	4995.35	ditto	ditto	
	mic, said morai 1.2	100011.	2704.3	14143.1	cu.m	770.55	4773.33	ditto	unto	
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to	
									be reduced by 7% and 14%,	
	i) cement, sand mortar:-								if 2nd or 3rd class bricks are	
	D : 12	100.00	2646.25	10512.05		1007.05	6520.00		used.	
	Ratio 1:2 Ratio 1:3	100Cft. ditto	3646.25 3646.25	18513.05 17455.85	cu.m ditto	1287.85 1287.85	6538.80 6165.40		ii) Masonry of boundary wall to be considered as masonry	
	Ratio 1:4	ditto	3646.25	16821.55	ditto	1287.85	5941.35		other than building.	
	Ratio 1:5	ditto	3646.25	16398.65		1287.85	5792.00		oner than building.	
	Ratio 1:6	ditto	3646.25	16080.80		1287.85	5679.75			
	Ratio 1:7	ditto	3646.25	15873.65	ditto	1287.85	5606.55			
	Ratio 1:8	ditto	3646.25	15688.85	ditto	1287.85	5541.30			
			/ ") /						
	ii) lime, cement, sand mortar:-		/	- ·					The rate of lime mortar also	
	Ratio 1:1:6	100Cft.	3646.25	16233.65	au m	1287.85	5733.75		includes grinding of mortar.	
	Ratio 1:1:7	ditto	3646.25	16023.10		1287.85	5659.35			
	Ratio 1:1:8	ditto	3646.25	15849.55	ditto	1287.85	5598.05			
	Ratio 1:1:9	ditto	3646.25	15705.50	ditto	1287.85	5547.20			
	Ratio 1:1:10	ditto	3646.25	15597.90		1287.85	5509.20			
		7.33	1		err.					
	iii) lime, sand mortar 1:2	100Cft.	3646.25	15024.85	cu.m	1287.85	5306.80		The rate of lime mortar also	
				9					includes grinding of mortar.	
6	Add extra labour on item No. 5 for brickwork	W. 18	an order areas of	TV comment and the	and the second					
	in:-	Den.	namer (Engrare	STATE OF STATE					
	i) first floor	100Cft.	541.20		cu.m	191.15	-			
	ii) second floor	ditto	1222.30		ditto	431.70	-			
	iii) third floor	ditto	1903.45		ditto	672.30	-			
	iv) fourth & subsequent floors	ditto	3065.05		ditto	1082.60	-			
7	Pacca brick work other than building upto 10ft. (3 m)							21.1	i) The composite rate is to be	
,	height.							to	reduced by 7% and 14%, if 2nd or	
								21.5	3rd class bricks are used.	
	i) cement, sand mortar:-									
							l		ii) Workshops, godowns,, bins,	
	Ratio 1:2	100Cft.	3210.25	18077.05		1133.85	6384.80		house type godowns, reservoirs,	
	Ratio 1:3	ditto	3210.25	17019.85		1133.85	6011.40		filter beds, storage tanks, wells,	
	Ratio 1:4 Ratio 1:5	ditto	3210.25	16385.50		1133.85	5787.35		screening chambers, collecting tanks, manholes etc. are to be	
	Ratio 1:5 Ratio 1:6	ditto ditto	3210.25 3210.25	15962.65 15644.75		1133.85 1133.85	5638.00 5525.75		tanks, manholes etc. are to be treated as masonry other than	
	Ratio 1:7	ditto	3210.25	15437.65	ditto	1133.85	5452.60		buildings.	
	Ratio 1:7	ditto	3210.25	15254.25		1133.85	5387.80		- Carraingo.	
	ii) lime, cement, sand mortar:-								The rate of lime mortar also	
									includes grinding of mortar.	

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	t JULY, 2013) TEH: N	NOWSHE	RA, SOAN V	VALLEY, KHUSHAB		
Sr.	Description]	Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				_					
	Ratio 1:1:6	100Cft.	3210.25	15797.60	cu.m	1133.85	5579.70		
	Ratio 1:1:7	ditto	3210.25	15585.30	ditto	1133.85	5504.75		
	Ratio 1:1:8	ditto	3210.25	15413.50		1133.85	5444.05		
	Ratio 1:1:9	ditto	3210.25	15269.40		1133.85	5393.15		
	Ratio 1:1:10	ditto	3210.25	15161.60	ditto	1133.85	5355.10		
	iii) lime, sand mortar 1:2	100Cft.	3210.25	14588.85	cu.m	1133.85	5152.80		ditto
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	541.20		cu.m	191.15	-		
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	1040.15		cu.m	367.40	-	21.5	
10	Extra for pacca brick work in steining of wells or any other circular masonry.	100Cft.	699.60	1319.50	cu.m	247.10	466.05	21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
		1995			3.666			21.4	of class offers are used.
11	Extra labour for profile and flared walls.	100Cft.	240.65		cu.m	85.00	-		
12	Extra labour for pacca brick work in piers and abutment:-	16	100	- 19	43				
	i) from 10ft. to 20ft. (3 m to 6 m) height ii) above 20 ft. (6 m) height.	100Cft. 100Cft.	267.80 541.20		cu.m cu.m	94.60 191.15	-		
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.	vance (2762.40	cu.m		975.70		This item is to be executed only under the written permission of Superintending Engineer.
14	Reinforced brick work in lintel of openings, laid in 1:3 cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	Per Cft.	91.10	234.55	cu.m	3218.05	8284.30		
15	Extra for dressing or chamfering bricks for:-								
	special architectural bricks all other purposes	100 Nos. ditto	1815.50 907.75	- -	% Nos. ditto	1815.50 907.75	- -		
16	Perforated pacca brick walling half brick thick, in ground floors:-							21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) mud mortar	100 Sft.	1388.75	3975.55	Sqm.	149.45	427.75		
	ii) cement, sand mortar:-								

	MRS, BI-ANNUAL PERIOD (1st FEBI	RA, SOAN V	ALLEY, K	HUSHAB					
Sr.	Description]	Rate (British Sy	rstem)	R	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Unit	Labout	Composite	Cint	Labout	Composite		
	Ratio 1:2	100 Sft.	1827.20	5547.70	sq.m.	196.60	596.95		
	Ratio 1:3	ditto	1827.20	5283.00	ditto	196.60	568.45		
	Ratio 1:4	ditto	1827.20	5124.80	ditto	196.60	551.45		
	Ratio 1:5	ditto	1827.20	5019.10	ditto	196.60	540.05		
	Ratio 1:6	ditto	1827.20	4944.70	ditto	196.60	532.05		
	Ratio 1:7	ditto	1827.20	4887.20	ditto	196.60	525.85		
	Ratio 1:8	ditto	1827.20	4844.75	ditto	196.60	521.30		
	iii) lime, cement sand mortar								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Sft.	1827.20	4977.80	sq.m	196.60	535.60		
	Ratio 1:1:7	100Sft.	1827.20	4923.35	sq.m	196.60	529.75		
	Ratio 1:1:8	100Sft.	1827.20	4883.60	sq.m	196.60	525.50		
	Ratio 1:1:9	100Sft.	1827.20	4845.05	sq.m	196.60	521.35		
	Ratio 1:1:10	100Sft.	1827.20	4822.50	sq.m	196.60	518.90		
	iv) lime, sand mortar 1:2	100Sft.	1827.20	4672.45	sq.m	196.60	502.75		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	18			18				
	i) first floor	100Sft.	273.40	67	sq.m	29.40	-		
	ii) second floor	ditto	608.35		ditto	65.45	-		
	iii) third floor	ditto	954.50	- ///	ditto	102.70	-		
	iv) fourth & subsequent floors	ditto	1477.55	Service Control	ditto	159.00	-		
18	Perforated pacca brick walling one brick thick, in ground floor:	(Fa)	vanae (Depart	eristes i	1		21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
	i) mud mortar	100Sft.	1947.25	7113.25	sq.m	209.50	765.40		
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	2746.55	10179.95	sq.m	295.55	1095.35		
	Ratio 1:3	ditto	2746.55	9651.35	ditto	295.55	1038.50		
	Ratio 1:4	ditto	2746.55	9334.20	ditto	295.55	1004.35		
	Ratio 1:5	ditto	2746.55	9122.75	ditto	295.55	981.60		
	Ratio 1:6	ditto	2746.55	8974.00	ditto	295.55	965.60		
	Ratio 1:7	ditto	2746.55	8858.50	ditto	295.55	953.20		
	Ratio 1:8	ditto	2746.55	8768.60	ditto	295.55	943.50		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	2746.55	9040.25	sq.m	295.55	972.75		includes grinding of mortar
	Ratio 1:1:7	ditto	2746.55	8931.35	ditto	295.55	961.00		
	Ratio 1:1:8	ditto	2746.55	8848.25	ditto	295.55	952.05		
	Ratio 1:1:9	ditto	2746.55	8776.15	ditto	295.55	944.30		
	Ratio 1:1:10	ditto	2746.55	8723.15	ditto	295.55	938.60		
	iv) lime, sand mortar 1:2	100Sft.	2746.55	8435.05	sq.m	295.55	907.60		ditto

	MRS, BI-ANNUAL PERIOD (1st FEBR	RUARY, 2	013 TO 31s	t JULY, 2013	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB				
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
19	Add extra labour on item No. 18 for perforated pacca brick work in:-								
	i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors	100Sft. ditto ditto ditto	405.90 916.75 1427.60 2298.80	 	sq.m ditto ditto ditto	143.35 323.80 504.20 811.90	- - -		
20	Fire brick masonry in fireclay mortar:- i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	34.90	610.60	cu.m	1232.70	21566.00	21.1 to 21.2	
	ii) Extra for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	541.20		ditto	191.15	-		A&C No.I dated 2.9.1998
21	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-	1			1			21.19	
	i) 4½" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	100Sft.	1560.25	7852.40	sq.m	167.90	844.90		
	ii) 4½" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	100Sft.	1399.85	7250.95	sq.m	150.60	780.20		
	iii) 3" (75 mm) thick walling with hoop iron, bonding 6" (150 mm) apart.	ditto	1234.20	5839.40	ditto	132.80	628.30		
	iv) 3" (75 mm) thick walling with hoop iron, bonding 12" (300 mm) apart.	ditto	987.35	5102.65	ditto	106.25	549.05		
22	Ghilafi work (1½ brick thick wall)	100Cft.	2798.00	8452.25	cu.m	988.25	2985.35	21.18	
23	Dry brick pitching	100Cft.	1702.80	11908.80	cu.m	601.45	4206.20	21.1	
24	Sun dried bricks in mud mortar	100Cft.	2346.95	3323.45	cu.m	828.95	1173.85	21.16	
25	Pise wall (mud walling)	100Cft.	1219.70		cu.m	430.80	-	21.17	
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2	
	 i) 3" (75 mm) thick drip course cornice ii) 4½" (113 mm) thick drip course cornice. iii) 4½" (113 mm) thick eave brick with back brick. 	Rft. ditto ditto	17.85 20.25 13.60	46.75 92.40 106.85	Metre ditto ditto	58.55 66.40 44.60	153.35 303.05 350.45		correction vide A&C No.I dated 2.9.98
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2	
	i) 1 brick ii) 2 bricks	Rft. ditto	20.25 29.85	34.40 73.00	Metre ditto	66.40 97.90	112.85 239.45		

	MRS, BI-ANNUAL PERIOD (1st F	LLEY, K	HUSHAB						
Sr. No.	Description	-	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec. No.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) 3 bricks iv) 4 bricks	ditto ditto	39.85 50.10	112.60 153.95	ditto ditto	130.70 164.35	369.35 504.95		
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	702.25		1,000 Nos	702.25	-		
29	Scraping bricks dismantled from pacca masonry	1,000 Nos	1324.20		1,000 Nos	1324.20	-		
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	167.20	1607.20	cu.m	59.05	567.65		
31	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart.	Rft.	75.10	129.40	Metre	246.35	424.45		
2	First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG hoop iron strips bonding placed at 2.0' (600 mm) apart horizontally, and at 1.0' (300 mm) interval vertically.								This item is to be executed only under the written permission of the Superintending Engineer.
	i) 1:3 ii) 1:4	100Sft. ditto	1399.85 1399.85	8577.85 8324.10	sq.m ditto	150.60 150.60	923.00 895.65		
3	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	40.05	Themarts	sq.m	430.95	-		
34	Replacing kallar eaten bricks	Each No.	31.70	38.05	Each	31.70	38.05		
5	Repairing corners of bridges and other hydraulic masonry works	Each No.	200.20	270.95	Each	200.20	270.95		
36	Extra labour for drains of bath rooms, etc.	Per Lft.	17.50		Metre	57.40			
7	Maroo corners	Each Corner	111.95		Each Corner	111.95			Payable in addition to brick work

8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- 3 Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBI	LLEY, K	HUSHAB						
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Random, rubble masonry (uncoursed), in foundation and plinth:							22.10, 22.11	
	a) dry masonryb) in mud mortarc) in lime, sand mortar 1:2	100 Cft. 100 Cft. 100 Cft.	2904.00 3633.30 5563.80	3690.00 4581.30 7857.00	cu.m cu.m cu.m	1025.70 1283.30 1965.15	1303.30 1618.10 2775.10		
	d) in cement, sand mortar i) ratio 1:3 ii) ratio 1:4 iii) ratio 1:6	100 Cft. 100 Cft. 100 Cft.	5563.80 5563.80 5563.80	11755.20 10803.70 9714.75	cu.m cu.m	1965.15 1965.15 1965.15	4151.95 3815.85 3431.25		
2	iv) ratio 1:8 Coursed rubble masonry hammer dressed, in foundation and plinth:	100 Cft.	5563.80	9112.20	cu.m	1965.15	3218.45	22.8	
	a) dry masonry b) in mud mortar c) in lime, sand mortar 1:2	100 Cft. 100 Cft. 100 Cft.	3603.60 5062.20 6217.20	4389.60 6010.20 8342.45	cu.m cu.m cu.m	1272.80 1787.95 2195.90	1550.40 2122.80 2946.55		
	d) in cement, sand mortar: i) ratio 1:3 ii) ratio 1:4 iii) ratio 1:6 iv) ratio 1:8	100 Cft. 100 Cft. 100 Cft. 100 Cft.	6217.20 6217.20 6217.20 6217.20	12096.00 11250.25 10281.65 9749.75	cu.m cu.m cu.m cu.m	2195.90 2195.90 2195.90 2195.90	4272.30 3973.60 3631.50 3443.60		
3	Random rubble masonry (uncoursed) in ground floor or 20 ft.(6 m) height, building/other than building.							22.10	
	a) dry masonry b) in mud mortar	100 Cft. 100 Cft.	3253.80 4362.60	4039.80 5310.60	cu.m cu.m	1149.25 1540.85	1426.85 1875.70		

	MRS, BI-ANNUAL PERIOD (1st FEB	RA, SOAN VA	LLEY, K	HUSHAB					
Sr.	Description]	Rate (British Sys	stem)	R	ate (Metric	System)	Spec.	Remarks
No.	-							No.	
		Unit	Labour	Composite	Unit	Labour	Composite		I
	c) in lime, sand mortar 1:2	100 Cft.	6042.30	8335.50	cu.m	2134.15	2944.10		<u> </u>
	d) in cement, sand mortar:				2 3.1.22		_,		
	i) ratio 1:3	100 Cft.	6042.30	12233.70	cu.m	2134.15	4320.95		
	ii) ratio 1:4	100 Cft.	6042.30	11282.20	cu.m	2134.15	3984.85		
	iii) ratio 1:6	100 Cft.	6042.30	10193.25	cu.m	2134.15	3600.25		
	iv) ratio 1:8	100 Cft.	6042.30	9590.70	cu.m	2134.15	3387.45		
4	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8	
	a) dry masonry	100 Cft.	4204.20	4990.20	cu.m	1484.90	1762.55		
	b) in mud mortar c) in lime, sand mortar 1:2	100 Cft. 100 Cft.	6263.40 6992.70	7204.20 9117.95	cu.m	2212.25 2469.80	2544.50 3220.45		
	c) in lime, sand mortar 1:2 d) in cement, sand mortar:	100 Cit.	0992.70	9117.93	cu.m	2409.80	3220.43		
	i) ratio 1:3	100 Cft.	6992.70	12871.50	cu.m	2469.80	4546.20		
	ii) ratio 1:4	100 Cft.	6992.70	12025.75	cu.m	2469.80	4247.50		
	iii) ratio 1:6	100 Cft.	6992.70	11057.15	cu.m	2469.80	3905.40		
	iv) ratio 1:8	100 Cft.	6992.70	10525.25	cu.m	2469.80	3717.50		
5	Ashlar block in course or scabbled masonry (including	200			1000			22.5	
	dressing, etc.,) in ground floor or 20 ft. (6 m) height,	1834	1	. 50 7	183			&	
	building/other than building.	7.3	1. 27		200			22.6	
		100		62.3					
	a) in lime, sand mortar 1:2	100 Cft.	18625.20	20743.85	cu.m	6578.40	7326.75		
	b) in cement, sand mortar:	100 00	40.55.50			4.550.40	0244.70		
	i) ratio 1:3	100 Cft.	18625.20	23342.80	cu.m	6578.40	8244.70		
	ii) ratio 1:4	100 Cft.	18625.20	22708.50	cu.m	6578.40	8020.65		
	iii) ratio 1:6	100 Cft.	18625.20	21989.60	cu.m	6578.40	7766.75		
6	Ashlar fine masonry (including dressing, etc.) in ground							22.3	
	floor or 20 ft. 6 m) height, building/other than building.							(A) to	
	a) in line and marks 1.2	100.00	24212 40	26264.25		10110.50	12042.00	(C) &	
	a) in lime, sand mortar 1:2	100 Cft.	34313.40	36364.35	cu.m	12119.50	12843.90	22.4	
	b) in cement, sand mortar: i) ratio 1:3	100 Cft.	34313.40	37663.85	cu.m	12119.50	13302.85		
	ii) ratio 1:4	100 Cft.	34313.40	37346.20	cu.m	12119.50	13190.70		
	iii) ratio 1:6	100 Cft.	34313.40	36994.40	cu.m	12119.50	13066.40		
7	Extra labour on items 3, 4, 5 & 6 above for work in:-								
	i) first floor	100 Cft.	765.60	-	cu.m	270.40	-		
	ii) second floor	100 Cft.	1714.95	-	cu.m	605.70	-		
	iii) third floor	100 Cft.	2684.35	-	cu.m	948.10	-		
	iv) fourth floor	100 Cft.	4262.00	-	cu.m	1505.35	-		
_		100 ==]						
8	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m) additional height, other than building, or part thereof.	100 Cft.	681.10	-	cu.m	240.55	-		
	additional neight, other than building, or part thereof.								
Ь		I				1			1

Sr.	Description	1	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	1982.85	-	cu.m	700.35	-	22.12	
10	Extra labour for:-							22.7	
	a) coping and caps, etc.b) cornice & string course	100 Cft. 100 Rft.	10074.25 10074.25	-	cu.m Rm.	3558.25 330.45	- -		
11	Dressing stones:-							22.2	
	a) hammer dressed b) rough tooled dressed c) chisel dressed d) fine dressed	100 Sft. 100 Sft. 100 Sft. 100 Sft.	3801.60 7201.90 8722.55 18237.10		sq.m sq.m sq.m sq.m	409.05 774.90 938.55 1962.30			 i) This rate of dressing shall be paid only when the supply of undressed stone is made. ii) In case of masonry, dressing is already included and this rate shall not be added thereto. iii) Only dressed surface of stone shall be measured.
12	Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft.	7482.80	12880.95	sq.m	805.15	1386.00	22.13	snail be measured.
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	315.50	343.55	cu.m	11143.45	12134.20		
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	181.35	212.40	cu.m	6405.30	7501.95		

9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	t JULY, 2013)	TEH: N	OWSHER	RA, SOAN VA	LLEY, KH	IUSHAB
Sr.	Description		Rate (British Sy	ystem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100Sft.	4965.30	10372.40	sq.m	534.25	1116.05	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	3817.45	7812.20	sq.m	410.75	840.60	23.2	ditto
3	Covering mud roof with coal tar, and fine sand.	100Sft.	209.35	1103.50	sq.m	22.55	118.75	23.1 to 23.2	ditto
4	Filling spaces in between:-	F. J. 1911	namer.	etweethere e	7/15/19/A				
	 a) Wooden battens over beams, filled with deodar wood pieces (spacers). b) RCC battens, filled with CC block 1:3:6. c) Spaces filled with bricks. 	100Sft. roof area -ditto- -ditto-	400.40 732.60 204.55	2238.55 1073.05 664.85	sq.m	43.10 78.85 22.00	240.85 115.45 71.55		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100Sft.	1222.75	5967.00	sq.m	131.55	642.05	23.1	ditto
6	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm) earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ½" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred. Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 2	.013 TO 31st	t JULY, 2013)) TEH: N	OWSHER	RA, SOAN VA	LLEY, KH	IUSHAB
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.				Í	Unit			No.	
	<u> </u>	Unit	Labour	Composite	Unit	Labour	Composite		
	a) cement concrete in haunches 1:6:12.b) cement concrete in haunches 1:3:6.	100Sft. ditto	5459.50 5459.50	15838.00 16937.50	sq.m ditto	587.45 587.45	1704.15 1822.50		
7	Jack arch roofing 4½" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ½" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.
	and gobri) soffit of arches cement plastered. The rate also includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
			/ ×) \					
	a) cement concrete in haunches 1:6:12.b) cement concrete in haunches 1:3:6.	100Sft. ditto	4437.85 4437.85	15486.10 15754.95	sq.m ditto	477.50 477.50	1666.30 1695.25		
8	Extra for vaulted jack arch roofing.	100Sft.	1119.35		sq.m	120.45	-		ditto
9	Jack arch roofing of shingle and cement concrete 1:3:6,	100Sft.	6078.60	13457.30	sq.m	654.05	1448.00	23.3	ditto
	4½" (113 mm) thick at crown, with ½" (13 mm) cement plaster including cost of supplying, erecting and dismantling centring.	4			40.9F			to 23.5	
10	Earth filling over roof including watering, ramming with 1" (25 mm) mud plaster finished, with gobri leeping:	En.	nance (Dop ar ti	reestra E			23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 3" (75 mm) thick earth filling and 1" (25 mm) mud plaster	100Sft.	517.85	734.10	sq.m	55.70	79.00	23.3	& sub- sequent floors, respectively.
	b) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster	100Sft.	678.20	930.45	sq.m	72.95	100.10		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	76.55	88.60	sq.m	8.25	9.55	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or 1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)	100Sft.	401.30	2128.00	sq.m	43.20	228.95	23.1	
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively,
	a) 20 BWG b) 22 BWG	100Sft. 100Sft.	800.8 800.8	14498.15 12493.45	sq.m	86.15 86.15	1560 1344.3		on items 13 to 18.
	c) 24 BWG	100Sft.	800.8	10101.1	sq.m sq.m	86.15	1086.9		

	MRS, BI-ANNUAL PERIOD (1st FEBR	LLEY, KH	USHAB						
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Labout	Composite	CIII	Labout	Composite		
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300 mm) outside width finished smooth with a floating coat of neat cement.	Rft.	56.75	76.00	Metre	186.15	249.30	23.10	
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	212.80	376.50	Each	Each	376.50	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4 ¹ / ₂ " (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	212.80	707.60	Each	212.80	707.60	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.		×						
	a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe	Per Rft. Per Rft.	45.60 45.60	153.25 176.60	Metre Metre	149.55 149.55	502.65 579.25		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	45.60	125.50	sq.m	490.65	1350.40	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	12.15	76.05	Sq.m	130.75	818.30		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-	ANTES.		Whateres and the	on one of				Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 4" dia (100 mm) cast iron down pipe.b) 3" (75 mm) cast iron down pipe.	Per Rft. Per Rft.	40.05 40.05	197.35 173.90		131.35 131.35	647.30 570.40		& sub- sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	171.05	465.10	Each	171.05	465.10		
22	Shoes, bends or offsets for cast iron rain water down pipe, including fixing and painting.	Each	60.05	294.95	Each	60.05	294.95		
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	190.10	310.05	Each	190.10	310.05	23.10	
24	Laying ½" (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100Sft.	4303.20	18467.05	sq.m	463.00	1987.05	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	a) 22 BWG sheets roofingb) 24 BWG sheets roofing	100Sft. 100Sft.	2533.10 2533.10	15158.15 13582.65	sq.m sq.m	272.55 272.55	1631.00 1461.50	23.60	

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 2	013 TO 31st	: JULY, 2013)	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB				
Sr.	Description		Rate (British Sy	rstem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26		10000	1702.00	5446.00		102.20	506.10	22.0	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and ridges, etc).	100Sft.	1702.80	5446.80	sq.m	183.20	586.10	23.8	
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100Sft.	195.20		sq.m	21.00	-	23.6	
28	Fixing asbestos cement sheet ridges and valleys ¼" (6 mm) thick.	Per Rft.	20.55	68.65	Metre	67.40	225.15	23.8	
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-		/ ×					23.6	
	a) 6" (150 mm) lap and 18" (450 mm)	Per Rft.	57.00	386.70	Per Metre	186.95	1268.40		
	overall, of 22 gauge G.I sheet ridging. b) 9" (225 mm) lap and 24" (600 mm)	Per Rft.	72.05	379.30	Per Metre	236.30	1244.10		
	overall, of 24 gauge G.I sheet ridging. c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging.	Per Rft.	72.05	446.70	Per Metre	236.30	1465.20		
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	36.05	156.10	Per Metre	118.25	512.00	23.11	
31	Making masonry ventilators in cement, sand mortar 1:4	Each	800.80	1284.40	Each	800.80	1284.40		
32	Fixing water spouts or parnalas.	Each	240.25		Each	240.25	-	23.10	
33	Making drip course 2"x½" (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	10.05	11.20	Metre	32.95	36.75		
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	28.90	338.15	sq.m	310.95	3638.50		
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:-								

	MRS, BI-ANNUAL PERIOD (1st FEBR	JULY, 2013)	13) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	D. T	10006	1004.20	6749.20		202.75	726.10		
	i) Thermopore sheet ½ " (13 mm) thick	100Sft.	1884.30	6748.20	sq.m	202.75	726.10		
	ii) Thermopore sheet ³ / ₄ " (20 mm) thick	100Sft.	1884.30	6874.20	sq.m	202.75	739.65		
	iii) Thermopore sheet 1" (25 mm) thick	100Sft.	1887.80	7003.70	sq.m	203.15	753.60		
36	Providing and fixing AC rain water down pipe 4" (100 mm) dia, with shoe, T-bend, clamp, etc.	Rft.	12.00	230.40	Metre	39.35	755.70		
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:-								Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.
	i) for slabs upto 6" (150 mm) thick	Rft.	14.00	15.70	Metre	45.90	51.50		concrete.
	ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick.	Rft.	23.50	26.65	Metre	77.10	87.40		
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-	.4.6	*		J. S.				Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times for reinforced cement concrete.
	i) upto 1.0' (300 mm) height of girder or beam.	Each	58.30	64.05	Each	58.30	64.05		
	ii) for every 6" (150 mm) additional height or part thereof.	Each	28.00	30.75	Each	28.00	30.75		
39	Hoisting RS. Beams and wooden beams and placing in position.	Each	220.45	\$ \disp\disp\disp\disp\disp\disp\disp\disp	Each	220.45	-		
40	Hoisting and placing in position sahl ballies, over roof.	Each	34.30	Theriaeti	Each	34.30	-		
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.								
	a) 5' to 6' (1.50 to 1.83 m) long	Each	31.50	_	Each	31.50	_		
	b) 6' to 7' (1.83 to 2.13 m) long	Each	44.10	_	Each	44.10	_		
	c) 7' to 8' (2.13 to 2.44 m) long	Each	55.10	_	Each	55.10	_		
	d) 8' to 9' (2.44 to 2.74 m) long	Each	73.50	_	Each	73.50	-		
	e) above 9' (2.74 m) length	Each	88.20	-	Each	88.20	-		
42	Hoisting and placing in position R.C. trough:								Applicable only to roof trough (inverted tees & trough) for height of
	a) upto 10' (3 m) in length	Each	88.20	_	Each	88.20	_		1st storey only.
	b) 10' to 11' (3 to 3.36 m) in length	ditto	110.20	-	ditto	110.20	-		, . , .
	c) 11' to 12' (3.36 to 3.66 m) in length	ditto	146.95	-	ditto	146.95	-		
	d) 12' to 13' (3.66 to 3.96 m) in length	ditto	169.55	-	ditto	169.55	-		
	e) 13' to 14' (3.96 to 4.26 m) in length	ditto	183.70	-	ditto	183.70	-		
	f) 14' to 15' (4.26 to 4.57 m) in length	ditto	200.40	-	ditto	200.40	-		
	g) 15' to 16' (4.57 to 4.88 m) in length	ditto	220.45	-	ditto	220.45	-		
	h) 16' to 17' (4.88 to 5.19 m) in length	ditto	244.95	-	ditto	244.95	-		
	i) 17' to 18' (5.19 to 5.49 m) in length	ditto	314.90	-	ditto	314.90	-		
	j) 18' to 19' (5.49 to 5.80 m) in length	ditto	339.15	-	ditto	339.15	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	k) 19' to 20' (5.80 to 6.10 m) in length	ditto	367.40	-	ditto	367.40	-				
43	Hoisting and placing in position R.C. inverted battens:-										
	i) upto 10' (3.05 m) span	Each	67.65	-	Each	67.65	-				
	ii) from 10' to 12' (3.05 to 3.66 m) span	ditto	150.35	-	ditto	150.35	-				
	iii) from 12' to 13' (3.66 to 3.96 m) span	ditto	180.40	-	ditto	180.40	-				
	iv) from 13' to 14' (3.96 to 4.26 m) span	ditto	225.50	-	ditto	225.50	-				
	v) from 14' to 15' (4.26 to 4.57 m) span	ditto	246.00	-	ditto	246.00	-				
	vi) from 15' to 16' (4.57 to 4.88 m) span	ditto	270.60	-	ditto	270.60	-				
	vii) from 16' to 18' (4.88 to 5.49 m) span	ditto	338.25	-	ditto	338.25	-				
	viii) from 18' to 20' (5.49 to 6.10 m) span	ditto	541.20	-	ditto	541.20	-				
44	Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	Each	320.30	569.25	Each	320.30	569.25				

Finance Department

10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproduct

	MRS, BI-ANNUAL PERIOD (1st FEE	- 71		t JULY, 2013) TEH: NO	OWSHER	A, SOAN VA	LLEY, KH	IUSHAB
Sr.	Description		Rate (British Sy	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	2112.00	3368.90	sq.m	227.25	362.50		
2	Earth flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	717.75	897.75	sq.m	77.25	96.60	24.1	
3	Providing, laying, watering and ramming brick ballast 1½" to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	1606.45	3346.45	cum.	567.40	1181.95		
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	1306.80	1612.25	sq.m	140.60	173.50	24.2	
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	701.70	3441.30	sq.m	75.50	370.30	24.12	
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by ½ "(13 mm) thick mud plaster.	100 Sft.	1262.30	5339.30	sq.m	135.80	574.50	24.12	
7	Grouting 4½"(113 mm) dry brick work with cement mortal ratio 1:5	100 Sft.	686.40	1133.80	sq.m	73.85	122.00		
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	1227.60	4728.20	sq.m	132.10	508.75	24.4	
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of ¾" (20 mm) thick cement mortar 1:6.	100 Sft.	1,568.15	6,670.00	sq.m	168.75	717.70	24.4	
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of ¾" (20 mm) thick cement mortar 1:6.	100 Sft.	1,534.50	3,536.15	sq.m	165.10	380.50	ditto	
11	Brick ties (9"x4½"x1½")(225 mm x 113 mm x 40 mm) laid flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.	100 Sft.	1,709.40	5,041.45	sq.m	183.95	542.45	24.4	
12	Cement tiles (8"x8"x¾")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement	100 Sft.	1,026.35	5,284.20	sq.m	110.45	568.60	24.7	

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2013 TO 31s	t JULY, 2013	3) TEH: NOWSHERA, SOAN VALLEY, K				IUSHAB
Sr.	Description		Rate (British Sy	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	mortar 1:2.								
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm) (b) 9"x9"x¾" (225 x 225 x 20 mm) (c) 6"x6"x¾" (150 x 150 x 20 mm)	100 Sft. ditto ditto	1,026.35 1,026.35 1,026.35	3,742.80 4,788.70 6,669.15	sq.m ditto ditto	110.45 110.45 110.45	402.75 515.25 717.60		
14	Coloured cement tiles (8"x8"x¾")(200 x 200 x 20 mm) of approved dark shade laid flat in 1:2 cement mortar, over ¾" (20 mm) bedding mortar of 1:2.	100 Sft.	1,026.35	5,313.00	sq.m	110.45	571.70	24.7	
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-		(*	5	\			24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick (b) 1½"(30 mm) thick (c) 1½"(40 mm) thick (d) 1¾"(45 mm) thick (e) 2"(50 mm) thick (f) 2½"(56 mm) thick (g) 2½"(62 mm) thick (h)2¾"(70 mm) thick (i) 3"(75 mm) thick	100 Sft. ditto	1,176.80 1,176.80 1,453.30 1,453.30 1,729.85 1,780.00 2,006.40 2,006.40 2,006.40	2,286.60 2,531.90 3,053.75 3,311.80 3,890.60 4,171.45 4,553.40 4,899.20 5,184.70	sq.m ditto ditto ditto ditto ditto ditto ditto ditto	126.60 126.60 156.40 156.40 186.15 191.55 215.90 215.90 215.90	246.05 272.45 328.60 356.35 418.65 448.85 489.95 527.15 557.85		
16	Providing and laying conglomerate flooring (two coat work) with top layer of ½"(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone chips passing 3/16"(6 mm) sieve, over bottom layer of cement concrete 1:3:6, including surface finishing and dividing in panels:-		TANCE	Depart				24.10	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1½"(40 mm) thick (b) 1¾"(45 mm) thick (c) 2"(50 mm) thick	100 Sft. ditto ditto	1,738.45 1,738.45 2,189.90	3,285.25 3,446.40 4,152.30	sq.m ditto ditto	187.05 187.05 235.65	353.50 370.85 446.80		
17	Add extra in cement concrete floor topping, if finished with pigment and polishing.	100 Sft.	400.40	875.60	sq.m	43.10	94.20		
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	300.95	-	sq.m	32.40	-		On items 19-25 & 29-34
19	Flag stone flooring in lime mortar 1:2, over ¾"(20 mm) bedding mortar, in platforms and floors, etc.							24.5	
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	3,435.70 3,435.70	4,957.60 5,197.30	sq.m ditto	369.70 369.70	533.45 559.25		

	MRS, BI-ANNUAL PERIOD (1st FEBI	LEY, KI	HUSHAB						
Sr.	Description		Rate (British Sy	vstem)	Ra	ite (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
20	Asphalt flooring , including preparation of proper base remelting, setting out, and finishing complete:-			-				24.10	
	(a) 1"(25 mm) thick topping (b) ½"(13 mm) thick topping (c) ½"(6 mm) thick topping	100 Sft. ditto ditto	1,353.00 1,067.20 795.45	15,802.40 8,442.50 4,583.60	sq.m ditto ditto	145.60 114.85 85.60	1700.35 908.40 493.20		
21	1 ³ / ₈ "(35 mm) thick mosaic flooring, consisting of 3/8"(10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete :-								If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	4,650.60 4,650.60	6,997.75 7,273.60	sq.m ditto	500.40 500.40	752.95 782.65		
22	1½"(40 mm) thick mosaic flooring, consisting of ½ "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing:	300 /6							If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement (b) using white cement	100 Sft. ditto	4,650.60 4,650.60	7,162.80 7,757.80	sq.m ditto	500.40 500.40	770.70 834.75		
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over ¾"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	2,866.80	6,730.55	sq.m	308.45	724.20	24.8	
24	Laying floor of approved white glazed tile ¼" (6 mm) thick in white cement 1:2 over ¾" (20mm) thick cement mortar 1:2, complete.	100 Sft.	3,663.00	9,034.55	sq.m	394.15	972.10	24.7	
25	Laying floor of approved coloured glazed tiles ½ "(6 mm) thick, laid in white cement and pigment on a bed of ¾" (20 mm) thick cement mortar 1:2.	100 Sft.	3,663.00	9,581.75	sq.m	394.15	1031.00	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	916.10	1,045.65	sq.m	98.55	112.50		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	977.85	1,110.10	sq.m	105.20	119.45		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.

	MRS, BI-ANNUAL PERIOD (1st FEB	LLEY, KH	IUSHAB						
Sr.	Description		Rate (British Sy	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		Cint	Labour	Composite	Cint	Labour	Composite		
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	157.80	202.75	sq.m	17.00	21.80	24.6	
29	Shisham wood boarding or strip flooring 3/4" (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½ "x2"(40 x 50 mm),size placed at 12"(300 mm) centre to centre, including two coats of bitumen laid hot on the base.	100 Sft.	3,190.00	35,044.20	sq.m	343.25	3770.75	24.13	
30	Deodar wood boarding or strip flooring 3/4" (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens 1½"x2"(40 x 50 mm) size, placed at 12"(300 mm) centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	3,603.60	42,329.65	sq.m	387.75	4554.65	ditto	
31	Teak wood boarding or strip flooring ½" (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens 1½ " x2"(40 x 50 mm) size, placed at 12"(300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	3,168.00	45,102.85	sq.m	340.90	4853.05	ditto	
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	3,352.80	39,743.50	sq.m	360.75	4276.40	24.13	
33	Teak wood block 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	3,168.00	74,682.75	sq.m	340.90	8035.85	ditto	
34	Laying wooden paving of hard wood on edge in coal tar and asphalt: (a) Shisham wood (b) Kikar wood	100 Sft. Per Inch thickness ditto	1,936.00 1,936.00	24,394.85 13,348.25	sq.m per cm thickness ditto	208.30 208.30	2624.90 1436.25	ditto	
35	Tile skirting laid in 1:2 cement mortar, over ¾"(20 mm) thick cement mortar, 1:2 including cement washing and filling joints complete:-								
	(a) cement tiles (b) mosaic tiles	100 Sft. ditto	1,680.25 2,781.90	6,317.05 8,903.05	sq.m ditto	180.80 299.35	679.70 957.95		
36	Providing grey cement skirting or dado 3/8"(10 mm) thick including rounding of corner and straight ening of top edge and finishing to smooth surface afterplastering:								
	(a) 1:2 cement, sand mortar	100 Sft.	2,141.15	2,701.90	sq.m	230.40	290.70		

Sr.	Description		Rate (British S	vstem)	Ra	te (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(b) 1:3 cement, sand mortar	ditto	2,141.15	2,538.60	ditto	230.40	273.15		
	(c) Extra if skirting or dado is finished with pigment of any colour.	ditto	125.40	386.50	ditto	13.50	41.60		
37	White glazed tile (6"x6"x ¹ / ₄ ") (6 mm) thick dado jointed in white cement and laid over 1:2 cement sand mortar 3/4" (20mm) thick, including finishing.	100 Sft.	4,514.40	9,885.95	sq.m	485.75	1063.75	24.7	
38	Coloured glazed tile dado (6"x6"1/4") (6mm) thick in pigment over 1:2 cement, sand mortar 3/4"(20mm) thick, including finishing.	100 Sft.	4,514.40	10,415.85	sq.m	485.75	1120.75	ditto	
39	Mosaic dado or skirting with one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over ½"(13 mm) thick cement plaster 1:3, including rubbing and polishing, complete with finishing:		/ 3	5					
	(a) using grey cement: i) 3/8"(10 mm) thick ii) ½"(13 mm) thick	100 Sft. ditto	5,491.20 5,491.20	6,708.40 7,469.10	sq.m ditto	590.85 590.85	721.80 803.70		
	(b) using white cement :	18	1.6	10,50) F				
	'i) 3/8"(10 mm) thick ii) ½"(13 mm) thick	100 Sft. ditto	5,491.20 5,491.20	7,550.45 7,841.75	sq.m ditto	590.85 590.85	812.45 843.75		
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	14.50	75.85	sq.m	156.00	816.15	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	4.10	Metre	-	13.45		Labour for fixing already included in items No. 15, 16, 21and 22 of this Chapter.
42	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels								
	a) Size 1½" x ³ / ₈ " (40 x 10 mm) b) Size 1½" x ¼" (40 x 6 mm)	Per Rft.	-	6.60 4.60	Metre ditto	-	21.65 15.10		

11. SURFACE RENDERING

- 1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBR	RUARY, 2013 TO 31st JULY, 2013)			TEH: NO	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7	
	a) ½" (13 mm) thick b) 1" (25 mm) thick	100 Sft. ditto	316.40 441.75	378.50 565.95		34.05 47.55	40.75 60.90		
2	Mud plaster on floor or roof (excluding Gobri leeping):-							ditto	Add extra 13%, 32% and 51% above the labour rates only or 6%, 15% &
	a) ½" (13 mm) thick	100 Sft.	285.10	347.20	sq.m	30.70	37.35		23% on the composite rates for 2nd, 3rd, 4th and subsequenct floors,
	b) 1" (25 mm) thick	ditto	285.10	409.30	ditto	30.70	44.05		respectively.
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.	18			1			25.1 to 25.6	
	a) ½" (6 mm) thick	100 Sft.	924.00	1059.80	sq.m	99.40	114.05		
	b) ½" (13 mm) thick	ditto	924.00	1195.45	ditto	99.40	128.65		
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-	Fir	iamor (Deplanti	gg (gasa jel) Pak (ke) (l) de			ditto	
	a) ½" (6 mm) thick b) ½" (13 mm) thick	100 Sft. ditto	924.00 924.00	1328.30 1575.65	sq.m ditto	99.40 99.40	142.95 169.55		
	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand and shingle) upto 20' (6.00 m) height.	100 Sft.	2288.35	4759.35	sq.m	246.25	512.10	ditto	
	Providing and laying machine sprayed plaster ½" (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto	
	i) ratio 1:1 ii) ratio 1:1½ iii) ratio 1:2	100 Sft. ditto ditto	824.40 824.40 824.40	2279.30 2178.00 2119.65	sq.m ditto ditto	88.70 88.70 88.70	245.25 234.35 228.05		
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1 to	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick	100 Sft. ditto ditto	924.00 924.00 1164.25	1484.75 1650.45 2285.70	sq.m ditto ditto	99.40 99.40 125.25	159.75 177.60 245.95	25.6	

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB									
Sr.	Description		Rate (British System)			Rate (Metric System)			Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto	
U	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	924.00 924.00 1164.25	1321.50 1453.95 1959.20	sq.m ditto ditto	99.40 99.40 125.25	142.20 156.45 210.80	ditto	
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto	
10	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick Cement plaster 3/8" (10 mm) thick under soffit of R.C.C.	100 Sft. ditto ditto	924.00 924.00 1164.25	1278.75 1374.85 1866.55	sq.m ditto ditto	99.40 99.40 125.25	137.60 147.95 200.85	ditto	i) This item shall be applicable to
	roof slabs only, upto 20' height. a) 1:2 b) 1:3 c) 1:4	100 Sft. ditto ditto	1063.90 1063.90 1063.90	1734.70 1570.70 1528.00	sq.m ditto ditto	114.50 114.50 114.50	186.65 169.00 164.40		buildings meant for human habitation only, such as buildings like residences, offices, educational institutions and hospitals, etc. It shall not be admissible on godowns; bins; agriculture, poultry and animal sheds; cycle stands; garrages; etc. ii) The thickness of the plaster will not be more than 3/8" (10 mm) thick.
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-			0				25.1 to 25.6	unck.
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ³ 4" (20 mm) thick	100 Sft. ditto ditto	924.00 924.00 1164.25	1240.50 1309.55 1797.25	sq.m ditto ditto	99.40 99.40 125.25	133.50 140.90 193.40		
12	Cement plaster 1:6 upto 20' (6.00 mm)							ditto	
	height:- a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	924.00 924.00 1164.25	1185.85 1271.30 1687.90	sq.m ditto ditto	99.40 99.40 125.25	127.60 136.80 181.60		
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	561.25	779.90	sq.m	60.40	83.90	25.4 to 25.6	
14	Lime pointing flush upto 20' (6.00 m) height including raking joints, in lime, sand mortar 1:2.	100 Sft.	683.75	774.20	sq.m	73.55	83.30	25.8	
15	Lime pointing struck joints on walls, upto 20' (6.00 m) height, including raking joints in lime sand mortar 1:2.	100 Sft.	1063.90	1154.35	sq.m	114.50	124.20	ditto	
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2 b) ratio 1:3	100 Sft. ditto	924.00 924.00	1343.45 1247.95	sq.m ditto	99.40 99.40	144.55 134.30		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: N	OWSHER	A, SOAN VAI	LLEY, KHU	USHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		CILL	Zusour	Composite	01110	240041	Composite		
17	Cement pointing 1:2 flush on floor.	100 Sft.	683.75	1103.25	sq.m	73.55	118.70	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-								
	a) ratio 1:2 b) ratio 1:3	100 Sft. ditto	1063.90 1063.90	1483.40 1387.90		114.50 114.50	159.60 149.35		
19	Pointing flush on stone work, upto 20' (6.00 m) height.							25.8	
	a) in lime mortar 1:2 (lime, sand) b) in cement mortar 1:3 c) on stone work raised:- i) in lime mortar 1:2	100 Sft. ditto	863.30 863.30	981.65 1187.25	sq.m ditto	92.90 92.90	105.65 127.75		
	i) in lime mortar 1:2 ii) in cement mortar 1:3	100 Sft. ditto	1623.60 1623.60	1741.95 1947.55	sq.m ditto	174.70 174.70	187.45 209.55		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	411.85		sq.m	44.30	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	205.90		sq.m	22.15	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	96.10	102.65	sq.m	10.35	11.05	25.11	
23	Distempering:-	***		S - 38				ditto	
	a) new surface:- i) one coat ii) two coats iii) three coats	100 Sft. ditto ditto	106.05 156.75 207.40	185.00 259.70 334.40	ditto	11.40 16.85 22.30	19.90 27.95 36.00		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	96.70 156.75	151.70 211.70		10.40 16.85	16.30 22.80		
24	Colour washing:-							25.10	
	a) new surface:- i) one coat ii) two coats	100 Sft. ditto	73.50 110.25	97.50 145.20		7.90 11.85	10.50 15.60		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	73.50 110.25	87.75 133.55		7.90 11.85	9.45 14.35		
25	White washing:-							25.9	
	a) new surface:- i) one coat ii) two coats	100 Sft. ditto	73.50 110.25	92.45 138.60		7.90 11.85	9.95 14.90		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iii) three coats	ditto	142.90	180.65	ditto	15.40	19.45		
	b) old surface:- i) one coat ii) two coats	100 Sft. ditto	73.50 110.25	87.70 133.85	sq.m ditto	7.90 11.85	9.45 14.40		
26	Gobri leeping:-							25.7	
	a) on walls b) over roofs	100 Sft. ditto	108.65 91.85	112.05 95.25	sq.m ditto	11.70 9.90	12.05 10.25		
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	139.90		sq.m	15.05	-	25.8	Payable with fresh masonry, when the face of the work is not to be plastered/pointed.
28	Extra for lime, mud or cement plaster and pointing from 20' (6.00 m) and above for each additional 10' (3.00 m) height or part thereof.	100 Sft.	167.50		sq.m	18.00	-		prastered/pointed.
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	406.55	919.10	sq.m	43.75	98.90		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	406.55	425.45	sq.m	43.75	45.80		
31	Extra cost of labour and material for red oxide pigment in cement pointing to match with the colour of bricks.	100 Sft.	128.70	226.20	sq.m	13.85	24.35		
32	Providing grooved cement sand plaster 1:3 over existing plastered and roughened surface upto 20' (6.00 m) height.	Fir	ianice (Deploati					
	i) 3/8" (10 mm) thick ii) ½" (13 mm) thick	100 Sft. ditto	1063.90 1063.90	1461.40 1593.90	sq.m ditto	114.50 114.50	157.25 171.50		
33	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	6.15	34.40	Metre	20.15	112.85		
34	Petty repairs to fire place.								
	i) Single ii) Double	Each Each	168.15 336.35	215.15 430.30	Each Each	168.15 336.35	215.15 430.30		Area chaus 100 Sft (10.76 ca.m.)
35	Petty repair to main rooms.	Each	345.45	471.30	Each	345.45	471.30		Area above 100 Sft (10.76 sq.m)
36	Petty repair to small rooms.	Each	172.70	235.60	Each	172.70	235.60		Area upto 100 Sft (10.76 sq.m)
37	Petty repair to verandah.	Each	345.45	446.05	Each	345.45	446.05		The height will be taken from the
38	Extra labour for white washing, colour washing, priming coat and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	100 Sft. Per coat	12.25	-	sq.m Per coat	1.30	-		floor, roof or ground uderneath as the case may be on the side towards which the work is to be done.

12. WOOD WORK

- 1 No extra rate is to be paid for sawing as the rates are inclusive of these
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 2	013 TO 31st	: JULY, 2013)	TEH: N	OWSHER A	A, SOAN VAL	LEY, KI	HUSHAB
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	ystem)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	569.45 638.00	3770.55 2873.60	cu.m ditto	20112.95 22534.15	133175.85 101495.55		
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.	. /	× .		\ :			26.1	
	a) Deodar wood b) Shisham wood	Per Cft. ditto	352.55 352.55	3587.05 2646.25	cu.m ditto	12452.05 12452.05	126694.60 93465.55		
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-		Sir.		## **			26.1 to 26.3 & 26.7	
	i) 2" (50 mm) thick ii) 1 ³ / ₄ " (45 mm) thick iii) 1 ¹ / ₂ " (40 mm) thick	Per Sft. ditto ditto	100.95 100.95 100.95	1347.25 1257.65 1170.15	sq.m ditto ditto	1086.20 1086.20 1086.20	14496.40 13532.30 12590.80		
4	First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cm²) including brass fittings, sash bars, etc. complete:- a) teak wood framing 1¾" (45 mm) thick with wire gauze fixed in position:-							26.8 to 26.10	 i) This also includes the cost of wood required for extra thickness of chowkat. ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and Rs.50.60 per sq.m.
	i) without springs or spring hinges.	Per Sft.	17.70	548.65	sq.m	190.45	5903.45		
	ii) with springs or spring hinges.	ditto	17.70	552.30	ditto	190.45	5942.75		
	 b) teak wood framing 1½" (40 mm) thick, with wire gauze fixed in position:- i) without springs or spring hinges. ii) with springs or spring hinges. 	Per Sft.	17.70 17.70		sq.m ditto	190.45 190.45	5444.00 5488.15		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square	Per Sft.	31.90	167.00	sq.m	343.25	1796.90		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHER/	A, SOAN VA	LLEY, KF	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.	·	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	inch, (5x5 meshes per cm²) fixed to chowkat with ¾" (20 mm) teak wood strips and screws. d) G.I. wire gauze 22 SWG, 12x12 meshes per square inch (5x5 meshes per cm²) fixed with ½" (13 mm) strip	Per Sft.	29.90	526.40		321.70	5664.05		
	on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc.								
5	P/F expanded metal ½" to ¾" (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	37.95	268.25	sq.m	408.35	2886.35		
6	Providing and fixing expanded metal ½" (13 mm) to ¾" 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	39.90	397.75	sq.m	429.30	4279.80		
7	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-		567					26.1 to 26.3 & 26.7	,
	a) 2" thick (50 mm) b) 13/4" thick (45 mm) c) 11/2" thick (40 mm)	Per Sft. ditto ditto	96.80 96.80 96.80	1060.40 991.60 943.90	ditto	1041.55 1041.55 1041.55	11409.90 10669.70 10156.35		
8	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	a) 2½" (56 mm) thick, with ½" (30 mm) battens and 1" (25 mm) planks.	Per Sft.	107.80	685.60	sq.m	1159.95	7377.05		
	b) 134" (40 mm) thick with 1" (25 mm) battens and 34" (20 mm) planks.	ditto	98.15	592.15	ditto	1056.10	6371.55		
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	127.40	393.40	sq.m	1370.80	4233.00		
10	Deodar battened ledged and braced doors and windows 2½" (56 mm) thick (1½" (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	116.10	669.95	sq.m	1249.25	7208.65	26.1, 26.2 26.4 to 26.6	
11	a) Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the Engineer incharge:-							26.1, 26.2 & 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60 Sq.m) for G.I. facing on one side

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHERA	A, SOAN VAI	LEY, KI	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.	·	Unit	Labour	Composite	Unit	Labour	Composite	Ño.	
	 i) G.I. sheet facing on one side. ii) G.I. sheet facing on both sides. b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, 	Per Sft. ditto	50.35 55.80	546.05 571.90	sq.m ditto	541.75 600.40	5875.50 6153.65		and Rs.9.40 per Sft. (Rs.101.20 per Sq.m) for G.I. sheet facing on both sides.
	hinges and locking arrangements, as directed by the Engineer-in-charge: i) G.I. sheet facing on one side. ii) G.I. sheet facing on both sides.	Per Sft.	50.35 55.80	211.40 237.25	sq.m ditto	541.75 600.40	2274.65 2552.80		
12	First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm²) including iron fittings etc. complete:-	. /	/ *		\			26.8 to 26.10	i) This also includes the cost of wood required for extra thickness of chowkat.
	a) deodar wood framing 1¾" (45 mm) thick with wire gauze fixed in position:-								ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	i) without springs or spring hinges.ii) with springs or spring hinges.	Per Sft. ditto	53.15 53.15	456.05 460.15	sq.m ditto	571.90 571.90	4907.10 4951.20		
	 b) deodar wood framing 1½" (40 mm) thick, with wire gauze fixed in position: i) without springs or spring hinges ii) with springs or spring hinges 	Per Sft.	53.15 53.15	424.05 426.55	sq.m ditto	571.90 571.90	4562.80 4589.70		
	c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm ²) fixed to chowkat, with ³ / ₄ " ('20 mm) thick deodar wood strip and screws.	Per Sft.	39.90	149.95	sq.m	429.30	1613.45		
	d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to chowkat, with ½" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm).	Per Sft.	59.80	391.00	sq.m	643.45	4207.15		
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	86.90	451.75	sq.m	935.05	4860.85	26.1 26.2	
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-								
	a) M.S. angle iron 1½"x ½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	23.30	145.40	sq.m	250.70	1564.50		
	b) M.S. tee iron 1½"x 1½"x ½" (40x40x6 mm) welded	Per Sft.	23.30	110.70	sq.m	250.70	1191.15		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	013 TO 31st	JULY, 2013)	TEH: NO	OWSHER/	A, SOAN VAL	LEY, KH	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	with M.S. flat 2"x ¼" (50 mm x 6 mm)								
	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 1'4" x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:								
	a) single rebate b) double rebate	Per Sft. ditto	30.65 36.90	120.80 139.85	sq.m ditto	329.80 397.05	1299.80 1504.80		
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	2.90	30.65	sq.m door area	31.20	329.80	26.2	
	Providing and fixing brass spring hinges to wire gauzed doors.	Each	60.70	210.70	Each	60.70	210.70		
	Providing and fixing sliding bolt to doors:- i) iron sliding bolt, 10" (250 mm) long ii) iron sliding bolt, 12" (300 mm) long iii) brass sliding bolt, 10" (250 mm) long iv) brass sliding bolt, 12" (300 mm) long Extra for brass fittings to doors and windows, except for	Each ditto ditto ditto	59.80 59.80 59.80 59.80	119.80 161.80 161.80 317.80	Each ditto ditto ditto	59.80 59.80 59.80 59.80	119.80 161.80 161.80 317.80		
	hinges, which shall be of iron:-	Per Sft.	1.75	11 65		18.85	125.25		
	i) deodar wood panelled or panelled and glazed or fully glazed. ii) deodar wood wire gauzed shutters.	ditto	1.75	9.30	sq.m ditto	18.85	125.35 100.05		
	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	185.85	392.25	Each	185.85	392.25		
21	Providing and fixing, approved quality mortice lock.	Each	260.70	450.30	Each	260.70	450.30		
	Providing and fixing, expended metal ½" to ¾" (13 mm to 20 mm) mesh 16 gauge.								
	 a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc. b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm) 	Per Sft.	37.95 39.90	229.70 326.85	sq.m ditto	408.35 429.30	2471.55 3516.90		
23	a) Providing and fixing deodar wood almirah 9" to 12"								For hollow frame shutter with

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHER/	A, SOAN VA	LLEY, KI	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	F	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. complete.	Per Sft.	133.75	1519.10	sq.m	1439.25	16345.75		commercial ply on one side, the composite rate shall be reduced by Rs.54.00 per Sft; or Rs.580.00 per Sqm and for hollow frame shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per Sft. or Rs.245.00 per Sq. metre.
	 b) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm)depth with shelves, shutters, brass fittings, etc., without boxing and back, complete. 	Per Sft.	98.80	520.65	sq.m	1062.85	5602.30		
24	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ½" (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1½:3) shelves 1½" (40 mm) thick including 3 coats of painting.	Per Sft.	76.25	355.65	Sq.m	820.65	3826.75		
25	Providing and fixing wooden box type wardrobe 22" (550 mm) deep including 3/4" (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods, etc. including three coats of enamel paint:-		Signal Control of Cont		2000 G				If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood bracing and deodar wood lipping is used, the composite rate will be
	i) Partal wood boxing and deodar wood shelves and leaves, etc.	Per Sft.	147.25	658.65	sq.m	1584.20	7086.90		reduced by Rs.13.00 per Sft. or Rs.140.00 per Sq. metre.
	ii) Deodar wood boxing, and deodar wood shelves and leaves, etc.	ditto	146.10	878.35	ditto	1572.30	9451.00		
26	Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete.	Per Sft.	56.30	552.80	Sq.m	605.75	5947.90		
27	Providing and fixing chowkat for doors, windows and C. windows, including holdfast, etc.								
	a) Teak wood b) Deodar wood c) Shisham wood	Per Sft. ditto ditto	27.65 17.70 20.60	458.60 350.00 170.40	ditto	297.75 190.70 221.45	4934.60 3765.90 1833.65		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHERA	A, SOAN VAI	LEY, KH	USHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	a) 1" (25 mm) thick b) 34" (20 mm) thick c) ½" (13 mm) thick	Sft. ditto ditto	33.15 33.15 33.15	295.65 229.95 164.55	sq.m ditto ditto	356.50 356.50 356.50	3181.15 2474.35 1770.50		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	i) 1" (25 mm) thick ii) 1½" (40 mm) thick iii) 2" (50 mm) thick	Sft. ditto ditto	33.15 33.15 33.15	295.65 426.75 557.85	sq.m ditto ditto	356.50 356.50 356.50	3181.15 4591.75 6002.40		
30	Making and fixing cleats for doors and windows, including hinges and screws.	Each	38.30	115.45	Each	38.30	115.45	26.1 and 26.2	
	b) Making and fixing cleats with brass hooks for roof ventilators.	Each	48.60	87.40	Each	48.60	87.40		
	c) Providing and fixing door stops of 1½" (40 mm) dia rubber block.	Each	5.85	56.35	Each	5.85	56.35		
31	d) Providing and fixing G.I. hook with clamps for doors. Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.	Each	1.85	9.55	Each	1.85	9.55	ditto	
	a) Shisham wood b) Teak wood	Per Rft. ditto	140.95 105.95	289.70 630.05	Metre ditto	462.35 347.50	950.25 2066.55		
32	Deodar wood dado or picture rail 3"x1½" (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete.	Per Rft.	52.95	222.05	Metre	173.75	728.25	26.1 26.2	
33	Sawing wood by hand:-								
	a) Soft wood (deodar, kail or chir). b) Hard wood (shisham, kikar, teak or sahl).	100Sft. ditto	607.20 809.60		sq.m ditto	65.35 87.10	-		
34	Sawing wood by machine:								
	a) Soft wood b) Hard wood	100Sft. ditto	365.33 548.85	- -	sq.m ditto	39.30 59.05	- -		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHER A	A, SOAN VAI	LEY, KH	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	F	ate (Metric S	ystem)	Spec.	Remarks
No.	_	Unit	Labour	Composite	Unit	Labour	Composite	No.	
35	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	45.30	359.40	sq.m	487.15	3867.00	26.1	
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	50.60	120.70	sq.m	544.45	1298.75	ditto	
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	191.40	7139.40	Each	191.40	7139.40	ditto	
38	Dismantling and refixing eave boards.	Per Rft.	13.65		Metre	44.85			
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1½" (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	202.40	2238.75	Metre	663.90	7343.10	26.1	
40	Providing and fixing partition, including frame work:-	/	_						
	a) Sheets on one side of framework:-	*			144.				
	i) Hard board ii) Ply wood ¼" (6 mm) thick iii) Masonite	100Sft. ditto ditto	948.75 948.75 948.75	11941.95 13201.95 13705.95	sq.m ditto ditto	102.10 102.10 102.10	1284.95 1420.55 1474.75		
	b) Sheets on both sides of frame work:-	100			25-				
	i) Hard board ii) Ply wood ¼" (6 mm) thick iii) Masonite	100Sft. ditto ditto	1138.50 1138.50 1138.50	13419.75 23674.30 16947.75	sq.m ditto ditto	122.50 122.50 122.50	1443.95 2547.35 1823.60		
41	Providing and fixing ceiling, including frame work:-								
	i) Hard board ii) Chip board iii) Ply wood ¼" (6 mm) thick iv) Masonite	100Sft. ditto ditto ditto	1890.65 1890.65 1890.65 1890.65	8388.50 10548.50 10668.50 10308.50	sq.m ditto ditto ditto	203.45 203.45 203.45 203.45	902.60 1135.00 1147.95 1109.20		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-								In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	i) ³ / ₄ " (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	2103.75 2103.75	8974.80 9050.40		226.35 226.35	965.70 973.80		
	b) Partal wood frame panelling:								
	i) ¾" (20 mm) thick	100Sft.	2103.75	5787.30	sq.m	226.35	622.70		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHER A	A, SOAN VAI	LEY, KH	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 1" (25 mm) thick	ditto	2103.75	5913.30	ditto	226.35	636.25		
43	a) Fixing door, including chowkats.	Each	300.30	-	Each	300.30	-		
44	b) Fixing windows, including chowkats.a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty.	ditto Per Sft.	150.15 21.70	49.20	ditto sq.m	150.15 233.35	529.40	26.12	
	b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty.	Per Sft.	28.20	81.05	sq.m	303.25	872.30		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	41.20	89.85	sq.m	443.05	966.85	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	15.50	16.60	sq.m	166.90	178.90		
	b) Cutting to required size and fixing glass panes with wooden fillets and putty.	Per Sft.	22.75	41.00	sq.m	245.00	441.10		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-	18							
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	34.90	99.00	sq.m	375.70	1065.20		
	b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sfi (2.25 sq.m).	Per Sft.	34.90	99.20	sq.m	375.70	1067.25		
48	Providing and fixing 1½" (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with:-	Fin	rance (Depart	er een t				
	i) M.S. angle iron 1½"x1½"x½", welded i) (40 mmx 40 mmx 6mm) with M.S. flat 2"x½" (50 mm x 6 mm)	Per Sft.	137.20	655.35	sq.m	1476.15	7051.45		
	ii) M.S. tee iron 1½"x1½"x¾", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¾" (13 mm x 6 mm)	Per Sft.	137.20	609.35	sq.m	1476.15	6556.50		
49	Providing and fixing 1½" (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1¼" (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1½"x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complete in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	i) M.S. angle iron 1½"x1½"x½", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¼" (50 mm x 6 mm)	Per Sft.	96.80	538.35	sq.m	1041.55	5792.75		
	ii) M.S. tee iron 1½"x1½"x¼", welded	Per Sft.	96.80	503.65	sq.m	1041.55	5419.45		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013)	TEH: N	OWSHER/	A, SOAN VAI	LEY, KI	IUSHAB
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(40 mmx40 mmx 6mm) with M.S. flat ½"x½" (13 mm x 6 mm)			•			•		
50	Providing and fixing 1½" (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1½"x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	49.55	336.30	sq.m	533.35	3618.50		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	94.65	353.95	sq.m	1018.30	3808.70		
52	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	21.00	34.50	Metre	68.85	113.10		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	8.75	125.95	Metre	28.70	413.15		
54	Providing and fixing M.S. flat ½"x1/8" (13mm x 3mm) grill including ¾" x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	49.55	182.40	sq.m	532.95	1962.40		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cnf) fixed to steel window, complete with flat iron patti ½"x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	16.45	56.55	sq.m	177.15	608.55		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 P.SQM
56	Providing and fixing wooden moulding stopper 2½"x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	a) Teak wood moulding b) Deodar wood moulding	Per Sft. ditto	21.85 21.85	103.75 63.10	-	235.25 235.25	1116.45 678.85		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between braces with 1:3:6 PCC fixing ply of approved quality								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))

Description	1	Rate (British System)			Rate (Metric S	ystem)	Spec.	Remarks
	Unit	Labour	Composite	Unit	Labour	Composite	No.	
including holdfasts complete in all respects.								
a) Teak wood ply	Per Sft.	46.70	307.60	sq.m	502.60	3309.95		
b) With commercial ply	ditto	46.70	300.50	ditto	502.60	3233.55		
Providing and fixing ornamental wooden architrave (1½" tapered to ¼") all along the door frame complerespect.								
a) Teak wood architrave	Per Sft.	9.30	64.00	sq.m	100.30	688.50		
b) Deodar wood architrave	ditto	9.30	36.40	ditto	100.30	391.85		
Providing and fixing Vin board cabinet 3/4" thick w drawers 3"deep in 'Kitchen including termite proofin polishing with synthetic enamel as specified, with h hinges, screws etc., complete in all respects.	ng and	/ *						
i) 1-1/2' deep, without back	Per Sft	104.80	499.90	sq.m	1127.40	5378.95		
ii) 1-1/2' deep,with back	Per Sft	104.80	547.90	sq.m	1127.40	5895.40		
iii) 2' deep,without back iv) 2' deep,with back	Per Sft Per Sft	104.80 104.80	546.70 594.70	sq.m sq.m	1127.40 1127.40	5882.50 6399.00		

Finance Department

13. PAINTING AND VARNISHING

1 The rates include charges for scaffolding and other arrangements.

2 The rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBRU			JULY, 2013)	TEH: NO	OWSHER/	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description]	Rate (British Sys	stem)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	a) Cleaning painted wood work with oil and water.	100 Sft.	100.30	132.90	sq.m	10.80	14.30		
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	66.90	113.70	sq.m	7.20	12.25	27.7	
2	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	200.65		sq.m	21.60	-	27.3	
3	Scraping, brushing and removing old paint from metal surface.	100 Sft.	802.55		sq.m	86.35	-	27.9	
4	Painting old surfaces:- a) Painting corrugated surfaces, patent roofing, etc. with	E						27.1 27.3 & 27.9	
	oil paint.	BI	16		43			21.9	
	i) first coatii) each subsequent coat	100 Sft. ditto	264.25 200.20	435.85 287.80	sq.m ditto	28.45 21.55	46.90 30.95		
	 Painting sashes, fanlights, glazed or gauzed doors and windows:- 	(Figur	ance G	depositi					
	i) first coatii) each subsequent coat	100 Sft. ditto	160.15 136.15	251.35 210.55	sq.m ditto	17.25 14.65	27.05 22.65		
	c) Painting doors and windows, any type:								
	i) first coatii) each subsequent coat	100 Sft. ditto	264.25 200.20	439.45 333.40	sq.m ditto	28.45 21.55	47.30 35.85		
	d) Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:-								
	 i) first coat ii) each subsequent coat e) Painting fillets, framings, skirtings, pipes, gutters and similar linear work not exceeding 6" in girth:- 	100 Sft. ditto	160.15 136.15	251.35 210.55	sq.m ditto	17.25 14.65	27.05 22.65		
	i) first coatii) each subsequent coat	100 Lft. ditto	136.15 96.10	227.35 170.50	Metre ditto	4.45 3.15	7.45 5.60		
	f) Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:-								

		MRS, BI-ANNUAL PERIOD (1st FEBRI) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB							
Sr.		Description	F	Rate (British Sys	stem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.			Unit	Labour	Composite	Unit	Labour	Composite	No.	
		i) first coat ii) each subsequent coat	100 Nos. ditto	412.50 371.50	584.10 462.70		412.50 371.50	584.10 462.70		
		Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:-								
		i) first coat ii) each subsequent coat	100 Nos ditto	942.85 543.10	1454.05 798.70		942.85 543.10	1454.05 798.70		
5	Paint	ing new surface:-							27.1 27.2 &	
		Preparing surface and painting corrugated surface, patent roofing, etc.		×					27.9	
		i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	410.00 143.35	633.20 356.95	sq.m ditto	44.10 15.45	68.15 38.40		
		Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):-	E E		(a)					
		i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	172.00 115.30	326.20 236.50	sq.m ditto	18.50 12.40	35.10 25.45		
		Preparing surface and painting of doors and windows any type (including edges):-	Fin	ance C	herenanti.	nent				
		priming coat. each subsequent coat of paint.	100 Sft. ditto	410.00 143.35	629.60 356.95		44.10 15.45	67.75 38.40		
		Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:-								
		i) priming coat. ii) each subsequent coat of paint.	100 Sft. ditto	260.15 115.30	393.35 236.50		28.00 12.40	42.35 25.45		
		Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-								
		i) priming coat. ii) each subsequent coat of paint.	100 Lft. ditto	204.20 76.90	305.00 176.50		6.70 2.50	10.00 5.80		
		Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-								
		i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	600.6 296.90	1132.8 720.50		600.6 296.90	1132.8 720.50		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	F	Rate (British Sys	tem)	Rat	te (Metric Sy	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	g) Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-											
	i) priming coat. ii) each subsequent coat of paint.	100 Nos. ditto	1725.90 517.00	2597.10 1276.60	100 Nos. ditto	1725.90 517.00	2597.10 1276.60					
	h) Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	28.00	43.10	sq.m	3.00	4.65					
6	Applying Khanki Mixture hot to barrage gates:-							27.10				
	i) first coat ii) second coat	100 Sft. ditto	200.20 158.20	467.10 327.80	sq.m ditto	21.55 17.05	50.25 35.25					
7	French polishing complete:-	*			14.			27.6				
	a) on new work b) on old work	100 Sft. ditto	2085.60 1086.15	2148.00 1119.75	sq.m ditto	224.40 116.85	231.15 120.50					
8	Varnishing wood work, including cleaning and preparing surface.				3							
	a) first coat b) second coat c) third coat	100 Sft. ditto ditto	160.15 60.05 60.05	284.35 154.20 134.65	sq.m ditto ditto	17.25 6.45 6.45	30.60 16.60 14.50					
9	Bitumen coating to plastered or cement concrete surface:-											
	i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m) ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m) iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m)	100 Sft. ditto ditto	167.20 160.50 132.40	1191.40 680.85 652.75	sq.m ditto ditto	18.00 17.25 14.25	128.20 73.25 70.25					
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	8.00	8.60	Per No.	8.00	8.60	27.1				
11	Writing letters or figures at any surface with reflective paint of approved quality and colour per letter per inch height.	Per Letter per inch height	8.00	8.35	Per Letter per 25 mm height	8.00	8.35	27.1				
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	9.50	10.35	ditto	9.50	10.35	ditto				
13	Coaltar painting:							27.8 to				
	a) first coat, laid hot b) second coat, laid hot	100 Sft. ditto	135.90 82.35	942.45 591.25	sq.m ditto	14.60 8.85	101.40 63.60	27.11				

	MRS, BI-ANNUAL PERIOD (1st FEBR	LLEY, KH	IUSHAB						
Sr.	Description	F	Rate (British Sys	stem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Solignum painting:-							27.8	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	153.90 233.20	180.30 275.45	sq.m ditto	16.55 25.10	19.40 29.65		
15	Creosote painting:-							ditto	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	184.70 279.85	299.90 473.05		19.85 30.10	32.25 50.90		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	512.15	527.75	sq.m	55.10	56.80	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	200.65	208.35	sq.m	21.60	22.40	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	40.05	46.65	Each	40.05	46.65	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	80.10	92.80	per Metre	262.65	304.40	ditto	
20	Painting sounding rods and other gauges, reading to 10th of a foot (metre)	Per Lft.	40.05	44.00	per Metre	131.35	144.30	27.1	
21	Painting leveling staves.	Per Lft.	126.70	133.10	per Metre	415.65	436.50		
22	a) Painting and lettering mile/Km stones, on both sides:	134-157	ance 9	hegysort i	nemt			ditto	
	i) one coat ii) two coats	Each ditto	85.80 150.15	131.40 223.35	Each ditto	85.80 150.15	131.40 223.35		
	b) Painting and lettering Furlong/½ Km stones, on both sides:-							27.1	
	i) one coat ii) two coats	Each ditto	11.45 20.00	16.85 29.45	Each ditto	11.45 20.00	16.85 29.45		
	c) Painting and lettering Sign posts:-								
	i) one coat ii) two coats	Each ditto	96.10 158.55	125.70 208.95	Each ditto	96.10 158.55	125.70 208.95		
23	Removing paint or varnish from wall.	100 Sft.	401.30	-	sq.m	43.20	-	27.12	
24	Scraping from hydraulic gates:-							27.1	
	a) Khanki paint b) Aluminium paint	100 Sft. ditto	802.55 802.55	-	sq.m ditto	86.35 86.35	- -		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	F	Rate (British Sy	stem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
25	Painting letters with shade.	per letter per inch height	12.80	12.80	per letter per 25 mm height	12.80	12.80	27.1				
26	Scraping rust from old rail or girders.	100 Sft.	601.90	640.90	sq.m	64.75	68.95	27.9 27.10				
27	Chiselling old paint from brick work.	100 Sft.	802.55	832.55	sq.m	86.35	89.60	27.12				
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	668.80	683.00	sq.m	71.95	73.50					
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	200.65	247.45	sq.m	21.60	26.65	27.9				
30	Cleaning and painting punkha poles, including fixing hooks.	Each	128.70	136.50	Each	128.70	136.50	27.3				
31	Preparing surface and painting with emulsion paint:-	& E						27.12				
	a) first coatb) 2nd and each subsequent coat	100 Sft. ditto	208.75 160.00	390.65 302.60	sq.m ditto	22.45 17.20	42.05 32.55					
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.	6 0		3	35-			27.12				
	a) new surface:	IF is m	amos A	depuseti	nent							
	i) 1st coat ii) 2nd and subsequent coat	100 Sft. ditto	208.75 160.00	287.95 229.40		22.45 17.20	31.00 24.70					
	b) old surface:											
	i) 1st coat ii) 2nd and subsequent coat	100 Sft. ditto	208.75 160.00	242.15 192.70		22.45 17.20	26.05 20.75					
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:											
	a) new surface:											
	i) 1st coat ii) 2nd coat	%sft %sft	681.10 375.55	1138.10 576.55		73.30 40.40	122.45 62.05					
	b) old surface:	%sft	375.55	576.55	sq.m	40.40	62.05					
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	1.20	2.05	Metre	3.95	6.80					

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	13 TO 31st	JULY, 2013) TEH: NO	OWSHER	A, SOAN VA	ALLEY, KI	IUSHAB
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads comlpete in all respect.	Per Rft.	1.30	9.35	Metre	4.30	30.65	AASHTO M248-91 (2000)	Rates shall be reduced by Rs.0.50 P.Rft or Rs.1.65 P.Mtr. If glass beads are not used.
35	Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	49.95	82.35	Job	49.95	82.35	(2000)	ii giass beaus are not used.
36	Repainting of iron poles with cross arms, with bitumen or other approved paint.	Per Job	116.60	233.00	Job	116.60	233.00		
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:		×						
	i) upto 40 mm (1½") dia	Per Rft.	1.05	3.50	Metre	3.50	7.15		
	ii) above 40 mm (1½") to 50 mm (2") dia	ditto	2.15	4.05	ditto	7.00	13.30		
	iii) above 50 mm (2") to 100 mm (4") dia	ditto	3.55	6.45	ditto	11.65	21.10		
38	Repainting main switches and branch distribution boards of all sizes and types, with approved paint (complete set).	Per Job	23.10	69.65	Job	23.10	69.65		
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	64.20) eparti	sq.m	6.90	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.

14. LINING OF CANALS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The rates also include curing for specified period wherever necessary.
- Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

	MRS, BI-ANNUAL PERIOD (1st FE	BRUARY	1st JULY, 20	2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB					
Sr.	Description		Rate (British Sy	vstem)]	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3	
	a) in bed b) on slope	100Sft. ditto	444.90 607.20	-	sq.m ditto	47.85 65.35	-		
2	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	1087.70	1620.20	sq.m	117.05	174.35	ditto	
3	Cement plaster ½" (13 mm) thick ratio 1:10.		1					ditto	
	a) in bed b) on slope	100Sft. ditto	791.90 987.35	1038.20 1233.70	sq.m ditto	85.20 106.25	111.70 132.75		
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	16	1 / 5	/ حکومت پنی				ditto	
	a) in bed b) on slope	100Sft. ditto	791.90 987.35	1210.50 1406.00	sq.m ditto	85.20 106.25	130.25 151.30		
5	Cement plaster 1½" (40 mm) thick ratio 1:6.	9	Pantan ce	(I)epan		1t		ditto	
	a) in bed b) on slope	100Sft. ditto	987.35 1227.60	2008.55 2248.80	sq.m ditto	106.25 132.10	216.10 241.95		
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:- a) in bed	100Cft.	4643.10	14237.50	cu.m	1639.95	5028.70	28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are payable separately.
	b) on slope	ditto	5319.60	14914.00	ditto	1878.90	5267.60		payable separately.
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are
	a) in bed	100Cft.	4643.10	15590.70	cu.m	1639.95	5506.65		payable separately.
	b) on slope	ditto	5319.60	16267.20	ditto	1878.90	5745.60		
8	Brick lining 9"x4½"x3" (225x113x75 mm) in 1:6 cement, sand mortar:-							28.2	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bed b) on slope	100Cft. ditto	4643.10 5319.60	17099.50 17776.00	cu.m ditto	1639.95 1878.90	6039.55 6278.50		payable separately.

Sr.	Description	ļ	Rate (British Sy	stem)]	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	Brick lining 9"x4½"x3" (225x113x75 mm), in 1:3 cement, sand mortar:-							ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to
	a) in bed b) on slope	100Cft. ditto	4643.10 5319.60	18452.70 19129.20	cu.m ditto	1639.95 1878.90	6517.50 6756.45		5 above are payable separately.
10	Cement concrete lining, using washed screened and graded stone aggregate:-							20.1, 28.1 & 28.3	
	a) in bed:-								
	i) ratio 1:2:4	100Cft.	4018.10	17545.45	cu.m	1419.20	6197.05		
	ii) ratio 1:3:6 iii) ratio 1:4:8	ditto ditto	4018.10 4018.10	15208.70 13527.85	ditto ditto	1419.20 1419.20	5371.70 4778.05		
	b) on slope:-								
	i) ratio 1:2:4	100Cft.	4643.10 4643.10	18170.45	cu.m ditto	1639.95 1639.95	6417.80 5592.45		
	ii) ratio 1:3:6 iii) ratio 1:4:8	ditto ditto	4643.10	15833.70 14152.85	ditto	1639.95	5592.45 4998.80		

Finance Department

15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEB	ERA, SOAN	VALLEY,	, KHUSHAB					
Sr.	Description	ŀ	Rate (British Sys	stem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Cutting Ransome and Larson piles.	Per cut	139.90	-	Per cut	139.90	-	29.1- 29.3	
2	Cutting universal piles.	Per cut	207.10	-	Per cut	207.10	-	ditto	
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	2552.90		sq.m	274.70		ditto	1) The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre). 2) The rates are for the tackle gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government. 3) T-piles and adjustable junction
4	Driving steel piles,more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	2449.90	Depar	sq.m	263.60	-	ditto	piles will be counted as two piles. ditto
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	1832.15	-	sq.m	197.15	-	ditto	ditto
6	Dolleying piles.	Each	162.60	-	Each	162.60	-	ditto	Upto 5' (1.5 m) dolleying.
7	Drilling holes in piles by hand.	Each	19.25	-	Each	19.25	-	ditto	
8	Raising and lowering machine.	Per Ft.	2508.00	-	Metre	8226.25	-	ditto	
9	Turning Machine, 90°	Per Job	3801.60	-	Per Job	3801.60	-	29.1 to 29.3	
10	Turning Machine, 135°.	Per Job	4625.30	-	Per Job	4625.30	-	ditto	
11	Turning Machine, 180°.	Per Job	6251.50	-	Per Job	6251.50	-	29.1 to 29.3	
12	Travelling machine (light).	Per Chain	7405.20	-	30 M.	7405.20	-	ditto	

Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
13	Loading and unloading piles.	Ton	148.45	-	Tonne	146.15	-	ditto	To be done by hand carts or ramps, including cost of ropes.
14	Dismantling piling machine.	Each	16925.90	-	Each	16925.90	-	ditto	
15	Erecting piling machine.	Each	19529.90	-	Each	19529.90	-	ditto	
16	Carriage of piling machine under different conditions.	per chain	3094.10	-	30 M	3094.10	-	ditto	



Finance Department

16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
 - the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
 - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
 - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the poin of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description	Ra	te (British Syste	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	762.45		cu.m	269.25					
2	Weaving matresses.	100Cft.	1444.60		cu.m	510.15					
3	Supplying and filling jute bags 1.25 (0.035 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	22.55	37.40	Per Baq	22.55	37.4		The rate does not include supply of sand or earth for filling bags, which will be paid extra.		
	b) Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water.	ditto	35.10	49.95	Per Baq	35.10	49.95		-ditto-		
4.00	a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry.	Per Bag	54.00	105.55	Per Bag	54.00	105.55		The rate does not include supply of sand or earth for filling bags, which will be paid extra.		
	b) Supply and filling new jute bags 4 to 5 cft (0.11 to	ditto	77.15	128.70	ditto	77.15	128.70		-ditto-		

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 20 ⁻	13 TO 31st .	JULY, 2013)	TEH: NO	WSHERA	A, SOAN VA	LLEY, K	HUSHAB
Sr.	Description	Ra	nte (British Syst	em)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				-			-		
	0.14 cu.m) capacity, with sand or earth, sewing and laying in position, under water.								
5	Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled with sand or earth:-								
	a) 1st chain (30 m)	100 Nos	200.65		% Nos	200.65			
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	72.25		Per 30 m Per 100 Nos/	72.25			
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	28.10		ditto	28.10			
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-		9.5%						
	a) 1st chain (Ist 30 metre)	100 Nos	802.55	3/2-	% Nos	802.55			
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	280.90	departs	Per 30 m per %Nos	280.90			
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	108.35		ditto	108.35			
7	Rolling matresses to river edge and floating, after unroling:-								
	a) area of matress upto 2,000 Sft. (186 sq.m)	100Sft.	451.45		sq.m	48.60			
	b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m)	100Sft.	752.40		sq.m	80.95			
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	877.80		ditto	94.45			
8	Sewing empty cement bags in sheets.	100 Nos	702.25	735.85	% Nos	702.25	735.85		
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	978.10	1076.15	cu.m	345.45	380.1		Measured in the shape of compact round bundles and of size specified for the work, before filling at site.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 20	13 TO 31st J	IULY, 2013)	TEH: NO	WSHERA	A, SOAN VA	LLEY, K	HUSHAB
Sr.	Description	Ra	ate (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
10	Launching the above and placing in position.	100Cft.	481.55		cu.m	170.05			
11	Supply within 5 chains (150 m):-								
	a) Boulders 9" (225 mm) and above	100Cft.	1452.65		cu.m	513.00			
	b) Over size shingle 3" to 9"(75 to 225 mm)	ditto	971.10		ditto	342.95			
	c) Mixed graded shingle	ditto	1151.65		ditto	406.70			
12	Supplying Munj or Patha Trungers 6" (150 mm) mesh to hold 3 Cft. (0.085 cu.m)	Each	62.70	105.35	Each	62.70	105.35		
13	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to make crate):-	/	*						
	a) 6" (150 mm) mesh	1			W.				
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	840.85 900.90 900.90	1099.55 1740.90 2218.00	sq.m ditto ditto	90.45 96.95 96.95	118.30 187.30 238.65		
	b) 4" (100 mm) mesh	600	5,0						
	i) 15 SWG wire ii) 10 SWG wire iii) 8 SWG wire	100Sft. ditto ditto	1081.10 1201.20 1201.20	1497.80 2458.70 3172.70	sq.m ditto ditto	116.30 129.25 129.25	161.15 264.55 341.40		
14	Providing and laying shingle on top of bund, including handling of materials within three chains.	100Cft.	501.60	831.60	cu.m	177.15	293.70		
15	Supply and dumping at site, without boat, including handling of materials within three chains (90 m)								
	a) stone or boulderb) shingle or spawlc) brick bats	100Cft. ditto ditto	877.80 877.80 677.15	1339.80 1207.80 1535.15	cu.m ditto ditto	310.00 310.00 239.15	473.15 426.55 542.20		The rate includes supply of brick bats to site of work.
16	Supply and dumping by boat, including loading into boal within three chains (90 m) lead, and hire charges of boat and boatman.								The rate includes supply of brick bats to site of work.
	a) stone or boulder	100Cft.	1544.40	2006.40	cu.m	545.50	708.65		
	b) shingle or spawl	ditto	1544.40	1874.40	ditto	545.50	662.05		
	c) brick bats	ditto	1343.75	2201.75	ditto	474.60	777.65		
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	1166.90	2024.90	cu.m	412.15	715.2		The rate includes supply of brick bats to site of work.
18	Supplying and filling bricks in crates and hand packing	100Cft.	1417.70	12757.70	cu.m	500.75	4506		The rate includes supply of bricks

	MRS, BI-ANNUAL PERIOD (1st FEBF	IULY, 2013)	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description	Ra	te (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(excluding cost of crates).								to site of work.
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-								
	i) stone or boulder ii) shingle or spawl	100Cft. ditto	1618.30 1618.30	2080.30 1948.30	cu.m ditto	571.60 571.60	734.75 688.15		
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	176.55	-	cu.m	62.35	-		
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	882.80	_	cu.m	311.80	-		
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	501.60	1001.60	sq.m	53.95	107.75	30.1	
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	1254.00	1304.00	sq.m	134.95	140.30	ditto	
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1½' (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	2809.15	3892.80	sq.m	302.25	418.85		The cost of placing earth between rolls shall be paid separately, as earthwork.
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	939.20	1024.80	sq.m	101.05	110.25		Measurement to be made of the area of elevation on one face only.
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	1620.95	1723.05	sq.m	174.40	185.4		
27	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	1016.40	1745.40	cu.m	359.00	616.5		
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	3078.90	3726.90	cu.m	1087.45	1316.35		
29	Providing and laying stone pitching, for top layer only:-								
	a) one slope b) on level	100Cft. ditto	2554.20 2303.40	3202.20 2951.40	cu.m ditto	902.15 813.55	1131 1042.45		
30	Providing and laying stone or spawl filling:-								

	MRS, BI-ANNUAL PERIOD (1st FEBF	ULY, 2013)	13) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description	Ra	te (British Syste	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
		10006	676.50	076.50		229.05	244.00		
	a) on level	100Cft.	676.50	976.50	cu.m	238.95	344.90		
	b) on slope	ditto	837.40	1137.40	ditto	295.75	401.75		
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.								
	i) top layer on slope	100Cft.	3400.85	5904.85	cu.m	1201.20	2085.60		
	ii) top layer on level	ditto	3150.05	5654.05	ditto	1112.60	1997.00		
	iii) stone pitching/filling on slope or on level	ditto	1817.40	4402.35	ditto	641.90	1554.9		
	(other than top layer).		/ ×						
32	Grouting stone pitching or apron, etc. in:-		_	/					
	a) cement, sand mortar 1:3	100Sft.	1150.65	4751.35	sq.m	123.80	511.25		
	b) cement, sand mortar 1:8	ditto	980.10	2836.10	ditto	105.45	305.15		
33	Sand grouting in stone apron, with high	100Sft.	390.70	1110.70	sq.m	42.05	119.50		
	pressure hose.	B. I	(J. J. J.	.60) (B)				
34	Grouting stone filling or pitching, with bajri.	100Cft.	627.00	1311.00	cu.m	221.45	463.05		
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	2384.45	Samuel wavel® a	cu.m	842.20	-		
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cft.	802.55	ar gr <u>u</u> er e n	cu.m	283.45	-		
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	676.50	1360.50	cu.m	238.95	480.55		
38	Grouting jharies between blocks with bajri.	100Cft.	676.50	1132.50	cu.m	238.95	400.00		
39	Breaking stone into spawls and stacking	100Cft.	601.90	-	cu.m	212.60	-		
	Canal and Roads								
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-								
	a) upto 2.0' (600 mm) F.S. depth	Each	21.00	-	Each	21.00	-		
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	23.60	-	ditto	23.60	-		
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	31.50	-	ditto	31.50	-		
	d) above 4.0' (1200 mm) F.S. depth	ditto	78.70	-	ditto	78.70	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description	Ra	nte (British Syst	em)	Rat	te (Metric Sy	vstem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
				,							
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-										
	a) i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead.	100 Nos	1003.20	1034.70	% Nos	1003.20	1034.70				
	ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	480.50	-	100 Nos	480.50	-				
	iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	576.60		100 Nos	576.60	-				
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	50.15	79.80	Per 30 Metre of one row	50.15	79.80				
	v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	700.90	870.10	ditto	700.90	870.10				
	b) i) Cutting and supplying unsharpened pegs 4.0' (1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	86.85	122.70	100 Nos	86.85	122.70				
	ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	480.50	-	100 Nos	480.50	-				
	iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average).	100 Nos	704.75	-	100 Nos	704.75	-				
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	50.15		Per 30 M of one row	50.15					
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1768.80		ditto	1768.80					
	c) i) Cutting and supplying unsharpened pegs 5.0' (1.5	100 Nos	108.60	153.45	100 Nos	108.60	153.45				

	MRS, BI-ANNUAL PERIOD (1st FEE	BRUARY, 20	RUARY, 2013 TO 31st JULY, 2013) TEH: NOWS					EH: NOWSHERA, SOAN VALLEY, KHUSHAB				
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).											
	ii) Sharpening one end of 5' (1.5 m) long pegs, 3" to 6" $(75 \text{ to } 150 \text{ mm})$ dia.	100 Nos	508.45	-	100 Nos	508.45	-					
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	813.10	-	100 Nos	813.10	-					
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	50.15	79.80	Per 30 M of one row	50.15	79.80					
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per chain of one row	772.20	1008.90	Per 30 M of one row	772.20	1008.90					
d	i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	2006.40	2060.20	100 Nos	2006.40	2060.2					
	ii) Sharpening one end of $6'$ (1.8 m) long pegs, $3"$ to $6"$ (75 to 150 mm) dia.	100 Nos	604.55	eparts	100 Nos	604.55	-					
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	975.75	-	100 Nos	975.75	-					
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	50.15	79.80	Per Chain of one row	50.15	79.80					
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	2019.60	2307.05	ditto	2019.60	2307.05					
е	i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km).	100 Nos	1504.80	1616.40	100 Nos	1504.80	1616.40					

	MRS, BI-ANNUAL PERIOD (1st FEB	JULY, 2013)	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description	Ra	ate (British Syst	em)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	768.75	-	100 Nos	768.75	-		
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3" to 6" (75 to 150 mm) dia driven 2' (600 mm) below the available bed or ground (average).	100 Nos	1077.10	-	100 Nos	1077.10	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per chain of one row	50.15	66.55	Per 30 M of one row	50.15	66.55		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per Chain of one row	2277.00	2615.20	Per 30 M of one row	2277.00	2615.20		
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-	# E	670						
	a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2½" to 5" (63 m to 125 mm) dia.	100 Nos	7200.00	- B	100 Nos	7200.00	-		
	ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	672.65)eparts	100 Nos	672.65	-		
	iii) Driving Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long 2½" to 5" (63 to 125 mm) dia, driven 2.5' (750 mm) below the available bed or ground (average).	100 Nos	1179.00	-	100 Nos	1179.00	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	75.25	121.75	Per 30 M of one Row	75.25	121.75		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	2785.20	3224.40	ditto	2785.20	3224.40		
	b) i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	10800.00	100 Nos	-	10800		
	ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	768.75	-	100 Nos	768.75	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSH.										
Sr.	Description	Ra	te (British Syst	em)	Rate	e (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	iii) Driving Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long 2½" to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average).	100 Nos	1280.40	-	100 Nos	1280.40	-				
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	250.80	861.50	Per 30 M of one Row	250.80	861.50				
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	3415.50	3973.50	ditto	3415.50	3973.50				
	c) i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos		11400.00	100 Nos	-	11400.00				
	ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	864.85		100 Nos	864.85	-				
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long 2½" to 5" dia, driven 3.5' (1.07 mm) below the available bed or ground (average).	100 Nos	1463.60		100 Nos	1463.60	-				
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	250.80	861.50	Per 30 M of one row	250.80	861.50				
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	4045.80	4688.40	ditto	4045.80	4688.40				
	d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	12600.00	100 Nos	-	12600.00				
	ii) Sharpening one end of 14'-1" to 16.0' (4.30 to 4.90 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	960.95	-	100 Nos	960.95	-				
	iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1626.25	-	100 Nos	1626.25	-				
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one Row	250.80	861.50	Per 30 M of one Row	250.80	861.50				
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile	ditto	4654.30	5398.30	ditto	4654.30	5398.30				

	MRS, BI-ANNUAL PERIOD (1st FEBI	LLEY, K	HUSHAB						
Sr.	Description	Ra	te (British Syste	em)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).								
	e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2½" to 5" (63 to 125 mm) dia.	100 Nos	-	13200.00	100 Nos	-	13200.00		
	ii) Sharpening one end of 16'-1" to 20' (4.9 to 6.10 m) long Bamboos, 2½" to 5" (63 to 125 mm) dia.	100 Nos	1153.15	-	100 Nos	1153.15	-		
	iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) 2½" to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1951.50		100 Nos	1951.50	-		
	iv) Tying Bamboos 2½" to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	250.80	861.50	Per 30 M of one row	250.80	861.50		
	v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	5821.20	6768.00	ditto	5821.20	6768.00		
43	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	250.80	318.30	cu.m	88.60	112.40		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.
44	Filling brush wood only, thoroughly packed.	100Cft.	200.65	-	cu.m	70.85	-		Measured in compacted and packed shape before filling.
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	481.55	-	Per 30 M	481.55	-		
46	 a) Gachi pitching 1' (300 mm) thick. b) Gachi pitching done with silt clearance and berm dressing. 	100Sft. 100Sft.	2608.30 2207.05	-	Sq.m Sq.m	280.65 237.50	- -		

17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013) TEH: N	IOWSHE	RA, SOAN	VALLEY,	KHUSHAB
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.
	a) channels, discharge upto 50 cusecs.	Job	836.00	-	Job	836.00	-	17.3	
	b) channels, discharge from 51 to 100 cusecs.	Job	1103.50	_	Job	1103.50	-		
	c) channels, discharge from 101 to 200 cusecs.	Job	1672.00)	Job	1672.00	-		
	d) channels, discharge from 201 to 350 cusecs.	Job	2257.20		Job	2257.20	-		
	e) channels, discharge over 350 cusecs.	Job	3344.00		Job	3344.00	-		
2	Dismantling outlets:-	835						18.1	These rates are for total dismantlement and removal
	a) old types, such as K.G.O's orifices, etc.	Each	836.00		Each	836.00	-		of material. The rates do not include earth work for which
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	1254.00	\$ 150 m	ditto	1254.00	-		rates are given in item 1, above.
	c) A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm)	ditto	1672.00	Depart	ditto	1672.00	-		above.
	d) A.P.M. or O.F., "H" above 3.0'. (900 mm)	ditto	2090.00	-	ditto	2090.00	-		
	e) Tail cluster bifurcation	ditto	1254.00	-	ditto	1254.00	-		
	f) Tail cluster trifurcation	ditto	1672.00	-	ditto	1672.00	-		
	g) Tail cluster quardification	ditto	2090.00	-	ditto	2090.00	-		
3	Making temporary A.P.M. bricks block and fixing at site.	Each	396.40	698.65	Each	396.40	698.65	21.1 & 21.2	
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	821.05	-	Job	821.05	-	18.1, 21.1 & 21.2	
5	Dismantling walls and fitting iron block of O.F. outlet	Each	821.05	-	Each	821.05	-	18.1, 21.1 & 21.2	
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to	

	MRS, BI-ANNUAL PERIOD (1st FEE	BRUARY, 2	013 TO 31st	JULY, 2013) TEH: N	IOWSHE	RA, SOAN '	VALLEY,	KHUSHAB
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
								17.2	
	a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth	Each ditto	2006.40 2708.65	-	Each ditto	2006.40 2708.65	-		
7	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	437.35	856.95	Each	437.35	856.95	18.1, 21.1 & 21.2	
8	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	851.40	1531.50	Each	851.40	1531.50	ditto	
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-								Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no O.F. iron block.
	a) for channel depth of 5.0'. (1.5 m) b) for channel depth of 4.0'. (1.2 m) c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) e) for channel depth of less than 2.0'. (600 mm)	Each ditto ditto ditto ditto	960.95 720.70 576.60 480.50 384.40	1084.65 844.45 700.30 576.90 453.45	Each ditto ditto ditto ditto	960.95 720.70 576.60 480.50 384.40	576.90		
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	396.40	584.65	Each	396.40	584.65		
11	Laying iron pipes for outlets.	Per Lft.	19.20		Metre	63.05	-	21.1, 21.2 & 17.1 to 17.5	
12	Water allowance for constructing outlets or culverts, when canal water is not flowing.	Each	407.95 to 836.00	Depart	Each	407.95 to 836.00			At the discretion of the Engineer-in-charge depending upon the distance and source of supply.
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	310.65	-	Each	310.65	-		
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	78.55 34.40	86.80 42.65	Metre ditto	257.70 112.90	284.75 139.95		
15	Removing pipe outlet, refilling earth and puddling.							17.1	
	a) portion under bank. b) portion under road, beyond bank.	Rft. ditto	66.90 25.10	-	Metre ditto	219.40 82.30		to 17.5	
16	Changing pipe outlets by removing one pipe and replacing it at the same site with another pipe complete with earth and puddling.								
	portion under bank. portion under road, beyond bank.	Rft. ditto	92.95 46.45	101.20 54.70		304.90 152.45	331.95 179.5		

18. ROAD & ROAD STRUCTURE

- 1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".
- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 3 The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	•							
Sr.	Description	R	ate (British Sys	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Sub-base & base construction								
1	Providing and laying sub-base course of brick on edge 4½" (113 mm) thick, including compaction to required camber and grade.	100Cft.	2707.70	13608.50	cu.m	956.35	4806.50	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	2177.10	3254.70	cu.m	768.95	1149.55	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.
3	Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and aggregate.	Time	SZ ma D		25.79.2			ditto	
	i) Pit run or bed run gravel.ii) Crushed stone aggregate.	100Cft. 100Cft.	2177.1 2177.1	2645.1 2897.1	cu.m cu.m	768.95 768.95	934.25 1023.25		
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail as the case may be.
									2) It shall be payable from the nearest approved quarry.3) The quantity of pit run or bed run gravel and crushed stone

	MRS, BI-ANNUAL PERIOD (1st FEBR	JARY, 201	3 TO 31st J	ULY, 2013)	TEH: NO	WSHERA	, SOAN VA	LLEY, K	HUSHAB
Sr.	Description	R	ate (British Sys	tem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	 a) Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to 	100Cft.	2434.50	4799.70	cu.m	859.85	1695.25	501-1 to 501-6	aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft.
	required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and aggregate.	/	Ť						
	b) Subsequent carriage of crushed stone aggregate.	100Cft. of console- dated base							1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
		Time.	mae D	epartu					2) It shall be payable from the nearest approved quarry.3) The quantity of crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 122 Cft.
	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	6.05	27.85	Metre	19.90	91.35	552-1 to 552-5	
	Bituminous Work & Resurfacing.								
	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre.	100Sft.	100.30	1136.30	sq.m	10.80	122.25	601-1 to 601-6	
7	Providing and laying bituminous tack coat, using 10 lbs. of bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.)	100Sft.	100.30	591.15	sq.m	10.80	63.60	611-1 to 611-5	
8	 a) Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rollin 							612-1 to 612-6	

	Description	R	ate (British Sys	tem)	Ra	te (Metric Sy	ystem)	Spec.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.								
	1) 1st coat:-								
	i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre	100Sft.	95.90	2341.60	Sq.m	10.30	251.95		
	ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size ¾" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre.	100Sft.	95.90	2047.25	Sq.m	10.30	220.30		
	2) 2nd coat:-	7 28		-	115				
	i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size ½" (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre.	100Sft.	73.75	1465.60	Sq.m	7.95	157.70		
	ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre.	100Sft.	73.75	1076.35	Sq.m	7.95	115.80		
	3) 3rd coat:-								
	14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ½" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	50.45	828.85	sq.m	5.45	89.20		
b)	Subsequent carriage of crushed stone aggregate/bajri,	100Cft.			cu.m				1) The carriage for the whole distance to the site of work shall calculated on the basis of the rate of the actual means of transport used in carriage, i.e. road and/or ras the case may be.
									It shal be payable from the nearest approved quarry.

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 201	3 TO 31st J	ULY, 2013)	TEH: NOV	WSHERA	, SOAN VA	LLEY, K	HUSHAB
Sr. No.	Description	Ra	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec. No.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	110.	
9	a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work.							612-1 to 612-6	
	 i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m. 	100Sft.	63.90	1290.00	sq.m	6.90	138.80		
	ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre.	100Sft.	63.90	1172.40	sq.m	6.90	126.15		
	b) Subsequent carriage of crushed stone aggregate/bajri.	100Cft.			cu.m				Same remarks as against item 8(b) above.
10	Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density.	per inch thickness per 100Sft.	moe D	epartn	per 25mm thickness per Sq.m			641-1 to 642-6	
	(i) 3% Bitumen	-do-	1056.75	3288.35	-do-	113.75	353.95		
	(ii) 3.5% Bitumen	-do-	1056.75	3589.40	-do-	113.75	386.35		
	(iii) 4% Bitumen (iv) 4.5% Bitumen	-do- -do-	1056.75 1056.75	3890.45 4191.45	-do- -do-	113.75 113.75	418.75 451.15		
	(v) 5% Bitumen	-do-	1056.75	4492.30	-do-	113.75	483.55		
	(vi) 5.5% Bitumen	-do-	1056.75	4793.55	-do-	113.75	515.95		
	(vii) 6% Bitumen	-do-	1056.75	5094.60	-do-	113.75	548.40		
11	Scarifying old road surface including removal of debris within 1 chain (30 m).	100Sft.	167.20	-	Sq.m	18.00	-		
	Incidental Construction								
12	Providing R.C.C. railing on bridges, as per standard drawing.	Per Rft.	95.10	971.80	Metre	311.95	3188.30	901-1 to 901-4	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of binding wire and removal of rust from the bars, etc.
13	Providing and fixing G.I. pipe railing, as pe	Per Rft. of	77.50	679.75	Metre	254.25	2230.20	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEI	LLEY, K	KHUSHAB						
Sr.	Description	R	ate (British Sys	tem)	Rat	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	standard drawing.	3 rows of Pipes							
14	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end	-	2400.00	Each set of one end	-	2400.00	911-1 to 911-6	
15	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch		18.00	cu.cm	-	1.10	ditto	
16	Providing and laying expansion joint of neoprine strip 4"x½" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	51.50	190.75	Metre	168.90	625.80	921-1 to 921-4	
17	Providing and fixing rain water outlet of A.C. pipe.	Each	25.75	253.85	Each	25.75	253.85	931-1 to 933-4	
18	Providing and erection at site of work:-	1000		3				941-1 to 941-5	The rate is for complete item of work according to Standard design
	i) R.C.C. mile/Km. stone	Each	1829.35	3957.55	Each	1829.35	3957.55		including cement concrete
	ii) R.C.C. furlong/½ Km. stone	Each	87.30	304.95	Each	87.30	304.95		foundation block and painting
	iii) R.C.C. boundary pillar. iv) Sign post of M.S. plate 1/8" thick (3 mm)	Each	162.80	489.35	Each	162.80	489.35		letters etc.
	a) Mandatory.	Each	575.95	4375.70	Each	575.95	4375.70		
	b) Warning/Direction/Informatory.	Each	556.75	4096.90	Each	556.75	4096.90		
19	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	2075.70	12976.50	cu.m	733.15	4583.30		The nominal thickness of bricks (9" x 4-3/8"x 2-11/16") shall be taken for the purpose of measurement and payment.

19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, BI-ANNUAL PERIOD (1st FEE	BRUARY	, 2013 TO 3	1st JULY, 2	013) TEI	H: NOWS	HERA, SOA	N VALLE	Y, KHUSHAB
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-								
	i) white ii) coloured	Each Each	303.60 303.60	2,001.30 2,181.30	Each Each	303.60 303.60	2,001.30 2,181.30		
2	Providing and fixing, double seat and cover only.	388			그&).			
	i) bakelite ii) plastic	Each Each	3.65 3.65	321.65 219.65	Each Each	3.65 3.65	321.65 219.65		
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.	Š			180				
	i) white ii) coloured	Each Each	237.60 237.60	1,137.90 1,329.90	Each Each	237.60 237.60	1,137.90 1,329.90		
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	237.60	1,965.60	Each	237.60	1,965.60		
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	237.60	561.90	Each	237.60	561.90		
6	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.								
	i) white, with pedestal	Each	300.30	2,376.30	Each	300.30	2,376.30		
	ii) coloured, with pedestal iii) white, without pedestal	Each Each	300.30 268.95	2,568.30 1,630.95	Each Each	300.30 268.95	2,568.30 1,630.95		
	iv) coloured, without pedestal	Each	268.95	1,696.95	Each	268.95	1,696.95		
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	268.95	4,349.80	Each	268.95	4,349.80		
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18") with drain board of mosaic, including bracket set, waste pipe and waste coupling.	Each	268.95	1,035.60	Each	268.95	1,035.60		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB													
Sr.	Description	F	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-													
	i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18")	Each Each	268.95 268.95	1,596.00 1,416.00	Each Each	268.95 268.95	1,596.00 1,416.00							
10	Providing and fixing glazed earthen ware flat back urinal.	Each	174.90	863.30	Each	174.90	863.30							
11	Providing and fitting glazed earthen ware low down flushing cistern 13,63 litres (3 gallons) capacity, including bracket set, copper connection, etc.													
	i) white ii) coloured	Each Each	268.95 268.95	1,254.15 1,326.15	Each Each	268.95 268.95	1,254.15 1,326.15							
12	Providing and fitting plastic made low down flushing cistern 1363 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.													
	i) white ii) coloured	Each Each	268.95 268.95	1,086.15 1,086.15	Each Each	268.95 268.95	1,086.15 1,086.15		If rubber connection is used, the composite rate will be reduced by					
				36	133		·		Rs. 12.50					
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	268.95	1,265.25	Each	268.95	1,265.25							
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.													
	i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity	Each Each	286.45 286.45	2,392.75 1,552.75	Each Each	286.45 286.45	2,392.75 1,552.75							
15	Providing and fixing, chromium plated soap dish.	Each	17.50	185.70	Each	17.50	185.70							
16	Providing and fitting, glazed earthen ware soap dish.													
	i) white ii) coloured	Each Each	17.50 17.50	465.30 213.30	Each Each	17.50 17.50	465.30 213.30							
17	Providing and fixing, chromium plated toilet paper holder.	Each	23.30	395.25	Each	23.30	395.25							
18	Providing and fixing, chromium plated towel rail:-													
	i) 60 cm (24") long, and 2 cm (¾") dia. ii) 50 cm (20") long, and 1.5 cm (½") dia.	Each Each	23.30 23.30	346.90 286.90	Each Each	23.30 23.30	346.90 286.90							

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	vstem)	Spec.	Remarks				
No.	•							No.					
-		Unit	Labour	Composite	Unit	Labour	Composite						
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	43.75	363.35	Each	43.75	363.35						
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-												
	i) with chromium plated brackets and railing. ii) glass shelf only, without chromium plated brackets and railing.	Each Each	51.75 35.00	348.10 79.40	Each Each	51.75 35.00	348.10 79.40						
21	Providing and fitting glazed earthen ware shelf 60x13 cm (24"x5"), with chromium plated bracket and railing:-												
	i) White ii) Coloured	Each Each	51.75 51.75	903.70 1,023.70	Each Each	51.75 51.75	903.70 1,023.70						
22	Providing and fitting:-				- JU								
	 i) plastic soap dish ii) plastic toilet paper holder iii) plastic towel rail iv) plastic shelf 60x13 cm (24"x5") with bracket and railing. 	Each Each Each Each	17.50 23.30 23.30 23.30	150.45 213.65 231.65 415.00	Each Each Each Each	17.50 23.30 23.30 23.30	150.45 213.65 231.65 415.00						
23	Providing and fixing chromium plated pillar-cock, heavy:-		A. S. C.		13300								
	i) 2 cm (3/4") ii) 1.5 cm (1/2")	Each Each	23.30 23.30	527.30 683.30	Each Each	23.30 23.30	527.30 683.30						
24	Providing and fixing chromium plated stop cock, heavy:-												
	i) 2 cm (3/4") ii) 1.5 cm (1/2")	Each Each	23.30 23.30	263.30 175.70	Each Each	23.30 23.30	263.30 175.70						
25	Providing and fixing underground stop cock 13 mm (½"), with chromium plated cover.	Each	33.35	472.95	Each	33.35	472.95						
	Providing and fixing chromium plated bib cock: i) 2 cm (¾") ii) 1.5 cm (½")	Each Each	23.30 23.30	335.30 317.30	Each Each	23.30 23.30	335.30 317.30						
27	Providing and fixing chromium plated tee stop cock 15mm (½").	Each	23.30	443.30	Each	23.30	443.30						
28	Providing and fixing chromium plated shower rose:-												
	i) 1.5x10 cm (½"x4") ii) 2x15 cm (¾"x6")	Each Each	23.30 23.30	323.30 401.30	Each Each	23.30 23.30	323.30 401.30						
29	Providing and fixing, chromium plated mixing valve, for wash	Each	29.15	1,529.15	Each	29.15	1,529.15						

MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHA											
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	hand basin, sink or shower.										
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)		
	i) 30 mm (1¼") dia	Each	35.00	425.00	Each	35.00	425.00		will be reduced by Rs. 66, 77, 95, 107		
	ii) 40 mm(1½") dia	Each	35.00	581.00	Each	35.00	581.00		and 120 respectively.		
	iii) 50 mm(2") dia	Each	35.00	797.00	Each	35.00	797.00				
	iv) 65 mm(2½") dia	Each	35.00	1,259.00	Each	35.00	1,259.00				
	v) 80 mm(3") dia	Each	35.00	1,865.00	Each	35.00	1,865.00				
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (1/2") dia.										
	i) single way	Each	23.30	365.30	Each	23.30	365.30				
	ii) two way	Each	35.00	629.00	Each	35.00	629.00				
	iii) three way	Each	46.65	760.65	Each	46.65	760.65				
32	Providing and fixing, union brass cock.	88									
	i) 13 mm (½") dia	Each	23.30	137.30	Each	23.30	137.30				
	ii) 20 mm (³ 4") dia	Each	23.30	215.30	Each	23.30	215.30				
		3	1000	8 7 mm	15.00						
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-			988	353						
	i) 10x5 cm (4"x2")	Each	69.95	377.35	Each	69.95	377.35				
	ii) 10x7.5 cm (4"x3")	Each	69.95	371.35	Each	69.95	371.35				
34	Providing and fitting "P" trap:-										
	i) 10 cm (4") of cast iron.	Each	58.30	442.65	Each	58.30	442.65				
	ii) 10 cm (4") glazed.	Each	58.30	122.25	Each	58.30	122.25				
35	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	87.45	622.05	Each	87.45	622.05				
36	Providing and fitting, cast iron soil pipe with:-										
	i) lead caulked, yarn joint:-										
	a) 10 cm (4") i/d	Per foot	25.95	219.25	Metre	85.15	719.20				
	b) 5 cm (2") i/d	Per foot	10.40	92.65	Metre	34.05	303.85				
	ii) cement caulked joint:-										
	a) 10 cm (4") i/d	Per foot	6.30	145.10	Metre	20.65	475.90				
	b) 5 cm (2") i/d	Per foot	2.50	79.25	Metre	8.25	259.90				

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	1	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
		l Omt	Labour	Composite	UIII	Labour	Composite		1				
37	Providing and fitting, A.C. soil pipe with cement caulked joint, including all specials:-												
	i) 60 (2 ¹ / ₄)" mm i/d ii) 80 (3") mm i/d iii) 100 (4") mm i/d iv) 150 (6") mm i/d	Per foot Per foot Per foot Per foot	5.05 5.60 6.30 8.40	29.05 68.25 103.00 128.55	Metre Metre Metre Metre	16.50 18.35 20.65 27.50	95.30 223.85 337.90 421.55						
38	Providing and fitting cast iron specials, such as tee bend, collar, cross, etc. plain type:-								In case of plug type, the composite rate shall be increased by Rs.2 per kg.				
	i) lead caulked joint ii) cement caulked joint	Kg Kg	21.70 13.35	147.10 110.20	Kg Kg	21.70 13.35	147.10 110.20						
39	Supply and fitting of cast iron manhole cover with frame, etc. complete.												
	i) 30 cm (12") dia ii) 45 cm (18") dia iii) 60 cm (24") dia	Each Each Each	35.00 35.00 55.00	179.00 851.00 1,435.00	Each Each Each	35.00 35.00 55.00	179.00 851.00 1,435.00						
40	Providing and fitting R.C.C. pipe 10 cm (4") dia, including laying and jointing in trenches.	Per foot	13.00	38.20	Metre	42.55	125.25						
41	Providing and fitting chromium plated or oxidised, gas cock 6'mm (¼"):-	Q	im an ce	(I)epa	TË HYASO	nt.							
	i) single way ii) two way iii) three way	Each Each Each	23.30 35.00 46.65	191.30 287.00 478.65	Each Each Each	23.30 35.00 46.65	191.30 287.00 478.65						
42	Providing and fitting nipple or bush, 6 mm to 10 mm (1/4" to 3/8") i/d.	Each	17.50	47.50	Each	17.50	47.50						
43	Providing and fixing, brass gas cock:-												
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	3.65 132.50	87.65 99.65	Each Each	3.65 132.50	87.65 99.65						
44	Providing and fixing brass stop cock/bib cock:-												
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	5.85 5.85	77.85 116.25	Each Each	5.85 5.85	77.85 116.25						
45	Hoisting and placing in position, precast R.C. latrine seats.	Each	280.50	-	Each	280.50	-						
	Replacement												

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	I	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Providing and fixing, chromium plated waste coupling:-												
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	35.00 35.00	117.80 123.80	Each Each	35.00 35.00	117.80 123.80						
2	Providing and fixing rubber plug with chain:-												
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	1.40 1.40	45.80 53.00	Each Each	1.40 1.40	45.80 53.00						
3	Providing and fixing, waste pipe of PVC:-												
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	17.50 17.50	42.70 48.70	Each Each	17.50 17.50	42.70 48.70						
4	Providing and fixing, flushing bend of PVC.												
	i) 3 cm (1½") ii) 4 cm (1½")	Each Each	15.55 15.55	40.75 46.75	Each Each	15.55 15.55	40.75 46.75						
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-	10		وين وين		Š.							
	i) 3 cm (1½") i/d ii) 4 cm (1½")	Each Each	35.00 35.00	539.00 659.00	Each Each	35.00 35.00	539.00 659.00						
6	Providing and fixing, angle iron brackets for:-	垫	nnance	(ii))epa		N.E							
	i) wash hand basin and cistern ii) sinks	Each Each	35.00 35.00	157.40 171.80	Each Each	35.00 35.00	157.40 171.80						
7	Providing and fixing 1.5 cm (½") dia connection, including check nuts, etc.:-												
	i) plastic rubber connection ii) copper connection	Each Each	14.00 14.00	45.20 82.40	Each Each	14.00 14.00	45.20 82.40						
8	Providing and fixing brass ball float valve:-												
	i) 1.5 cm (½") dia ii) 2.0 cm (¾") dia iii) 2.5 cm (1") dia iv) 3 cm (1½") dia v) 4.0 cm (1½") dia vi) 5 cm (2") dia	Each Each Each Each Each Each	29.15 29.15 29.15 29.15 29.15 29.15	221.15 287.15 347.15 377.15 521.15 905.15	Each Each Each Each Each Each	29.15 29.15 29.15 29.15 29.15 29.15 29.15	221.15 287.15 347.15 377.15 521.15 905.15						

20. SURFACE DRAINAGE

- 1. Specification No. correspond to Book of Specification (B & R Department) Vol. 11, 1966 (public Health Works).
- 2. Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31s	t JULY, 2013	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KH	HUSHAB
Sr. No.	Description]	Rate (British Sy	stem)	Ra	te (Metric Sy	ystem)	Spec. No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-							17.1	
	a) 3" thick (75 mm)		/ ×)					
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	879.25 879.25	3,415.65 3,252.25	Metre ditto	28.85 28.85	112.05 106.65		
	B) 4½" thick (113 mm)	13			78				
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,318.10 1,318.10	4,969.15 4,719.45	ditto ditto	43.25 43.25	163.00 154.80		
2	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled and struck flush:-	Œŝi	Vanior (SA Devart	en enet			17.1	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,297.50 1,297.50 1,297.50	4,844.05 4,580.10 4,505.75	Sqm. ditto ditto	139.60 139.60 139.60	521.20 492.80 484.80		
3	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,848.00 1,848.00 1,848.00	7,197.30 6,773.70 6,668.40	Sqm. ditto ditto	198.85 198.85 198.85	774.45 728.85 717.50		
4	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,227.60 1227.6 1227.6		Sqm. ditto ditto	132.10 132.1 132.1	513.70 485.3 477.3		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2	013 TO 31st	JULY, 2013) TEH: N	OWSHER.	A, SOAN VA	LLEY, KH	IUSHAB
Sr.	Description	F	Rate (British Sys	etem)	Ra	te (Metric Sy	rstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	Pacca brick on edge, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,889.20 1,889.20 1,889.20	7,238.50 6,814.90 6,709.60	Sqm. ditto ditto	203.30 203.30 203.30	778.85 733.30 721.95		
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ½:5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ¼" (6 mm) thick, as per Engineer's drawing (excluding excavation):-							17.1	
	a) Type I b) Type II	Per Rft ditto	29.40 58.80	82.35 151.05	Metre ditto	96.45 192.90	270.05 495.40		
	c) Type III	ditto	76.10	195.45	ditto	249.60	641.00		
	d) Type IV	ditto	90.65	233.00	ditto	297.40	764.20		
	e) Type V	ditto	119.55	317.70	ditto	392.20	1,042.05		
	f) Type VI	ditto	137.50	363.95	ditto	451.00	1,193.80		
	g) Type VII	ditto	152.40	400.75	ditto	499.85	1,314.50		
	h) Type VIII	ditto	170.20	449.85	ditto	558.30	1,475.45		
	i) Type IX	ditto	227.40	638.20	ditto	745.85	2,093.30		
	j) Type X	ditto	249.80	699.45	ditto	819.30	2,294.15		
	k) Type XI	ditto	279.20	777.85	ditto	915.80	2,551.35		
	l) Type XII	ditto	297.65	825.00	ditto	976.25	2,705.95		
7	Laying R.C.C hume pipes in position, including jointing:-								
	a) 6" to 12" (150 mm to 300 mm) dia	Per Lft.	54.10	57.20	Metre	177.50	187.60		
	b) 12" to 24" (300 mm to 600 mm) dia	ditto	84.20	90.35	ditto	276.25	296.40		
	c) 24" to 36" (600 mm to 900 mm) dia	ditto	108.25	117.50	ditto	355.05	385.45		

21. SEWERAGE

- 1 Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works).
- 2 Rate for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	JARY, 20	13 TO 31st	JULY, 2013)) TEH: N	OWSHER	A, SOAN V	ALLEY, KI	HUSHAB
Sr. No.	Description	1	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Providing and laying R.C.C. pipe, moulded with cement concrete 1:1½:3, with spigot socket or collar joint, etc. including cost of reinforcement, conforming to B.S. 5911 Part I: 1981, Class "L" including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipes where necessary, finishing and testing, etc., complete							Chapter - 8	
	i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 225 mm (9:) i/d	Rft. Rft. Rft.	15.15 18.35 35.40	67.60 106.20 277.30	Metre Metre Metre	49.70 60.20 116.10	221.75 348.35 909.55		
2	Providing and laying non-reinforced concrete pipe moulded with cement concrete 1:1½:3, conforming to ASTM Specification C-14-73, Class 2, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing, cutting pipe where necessary, finishing and testing, etc. complete	THE STATE OF THE S	64					ditto	
	i) 100 mm (4") i/d ii) 150 mm (6") i/d iii) 200 mm (8") i/d iv) 225 mm (9:) i/d wall thickness 1 inch (25 mm) v) 250 mm (10") i/d	Rft. Rft. Rft. Rft. Rft.	11.35 13.75 22.05 23.80 24.20	34.55 49.15 68.45 86.20 95.15	Metre Metre Metre Metre Metre	37.25 45.10 72.30 78.05 79.40	113.30 161.20 224.50 282.75 312.10		
3	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class II. Wall B, including carriage of pipe from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc., complete.							ditto	
	i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iii) 460 mm (21":) i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	36.50 45.80 55.25 69.15 79.70 116.75 139.95 174.20 214.35 278.95 521.95 719.3 918.65 1434.7	348.05 426.55 462.00 595.00 713.25 997.40 1066.50 1248.95 1690.20 2201.05 2936.2 3684.5 4213.3 5058.8	Metre	119.70 150.20 181.20 226.80 261.40 382.95 459.05 571.40 703.05 914.95 1712 2359.3 3013.15 4705.8 5832.80	1141.60 1399.10 1515.35 1951.60 2339.45 3271.45 3498.10 4096.55 5543.85 7219.45 9630.75 12085.15 13819.6 16592.85 18800.65		

	MRS, BI-ANNUAL PERIOD (1st FEBRU	JARY, 20)13 TO 31st	JULY, 2013) TEH: N	OWSHER	RA, SOAN V	ALLEY, K	HUSHAB
Sr.	Description	1	Rate (British Sy	stem)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
4	Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class III, Wall B, including carriage of pipes from factory to site of work, lowering in trenches to correct alignment and grade, jointing with rubber ring, cutting pipe							Chapter-8	
5	where necessary, testing, etc. complete: i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d Providing and laying R.C.C. pipe sewers, moulded with cement concrete 1:1½:3 conforming to ASTM Specification C-76-79, Class IV, Wall B, including carriage of pipes from factory to site of work, lowering in trenches	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	36.50 45.80 55.25 69.15 79.70 116.75 139.95 174.20 214.35 278.95 529.25 729.55 931.50 1455.25 1803.95	420.25 516.35 649.25 792.75 920.65 1099.55 1331.95 1485.35 1989.90 2582.95 3162.40 4041.55 4992.30 6509.65 8096.75	Metre	119,70 150,25 181,20 226,75 261,45 382,85 459,10 571,40 914,90 1735,95 2392,95 3055,25 4773,15 5916,95	1693.65 2129.55 2600.20 3019.75 3606.50 4368.80 4871.95 6526.85	Chapter - 8	
6	to correct alignment and grade, jointing with rubber ring cutting pipes where necessary, testing, etc. complete: i) 310 mm (12") i/d ii) 380 mm (15") i/d iii) 460 mm (18") i/d iv) 530 mm (21":) i/d v) 610 mm (24") i/d vi) 690 mm (27") i/d vii) 760 mm (30") i/d viii) 840 mm (33") i/d ix) 910 mm (36") i/d x) 1070 mm (42") i/d xi) 1220 mm (48") i/d xii) 1370 mm (54") i/d xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d xv) 1830 mm (72") i/d Lowering of sub-soil water table, by installation of tubewell: along sewer line and pumping out water, for excavation ir open cutting below sub-soil water level, concreting, curing laying and jointing pipes, filling haunches, etc. till the	Rft. Rft. Rft. Rft. Rft. Rft. Rft. Rft.	36.50 45.80 55.25 69.15 79.70 116.75 139.95 174.20 214.35 278.95 529.25 729.55 931.50 1455.25 1803.95	518.20 647.90 777.75 912.05 1043.05 1381.05 1588.90 1768.10 2491.70 3072.55 3721.85 5020.80 6338.70 8345.65 9932.75	Metre	119.70 150.25 181.20 226.75 261.45 382.85 459.10 571.40 703.10 914.90 1735.70 2393.15 3055.25 4773.15 5916.95	2125.15 2551.10 2991.55 3421.30 4529.85 5211.80 5799.40 8172.85 10077.95 12207.70 16468.15 20790.85 27373.65		1) This rate shall be payable, in addition to the item of excavation below SSWL for sewers and manholes under Chapter.

	MRS, BI-ANNUAL PERIOD (1st FEBR	OWSHER	RA, SOAN V	ALLEY, K	(HUSHAB				
Sr.	Description]	Rate (British Sys	tem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	completion of sewer line, including disposal of pumped outwater:- 1) 0-1 ft. (0 to 310 mm) below SSWL 2) 0-2 ft. (0 to 610 mm) below SSWL	Rft of laid sewer ditto	-	208.50 395.55	Metre of laid sewer ditto	- -	683.80 1297.45		EARTHWORK 2) The grant of these rates shall be subject to Superintending Engineer's approval.
	3) 0-3 ft. (0 to 910 mm) below SSWL 4) 0-4 ft. (0 to 1220 mm) below SSWL 5) 0-5 ft. (0 to 1520 mm) below SSWL 6) 0-6 ft. (0 to 1830 mm) below SSWL 7) 0-7 ft. (0 to 2170 mm) below SSWL 8) 0-8 ft. (0 to 2480 mm) below SSWL 9) 0-9 ft. (0 to 2790 mm) below SSWL 10) 0-10 ft. (0 to 3100 mm) below SSWL	ditto		675.60 976.50 1361.95 1684.80 2013.05 2311.50 2496.60 2877.75 3201.05	ditto ditto ditto ditto	-	2216.05 3202.95 4467.25 5526.15 6602.90 7581.75 8188.85 9439.00 10499.50		3) The rate includes cost of providing pumps, POL and all operation charges at the site of work, etc.
7	12) 0-12 ft. (0 to 3720 mm) below SSWL Constructing gully grating chamber, 12"x12", (300x300 mm) complete in all respects:	ditto	- ×	3549.15	ditto	-	11641.15	16.2	Pipe connection to be paid separately.
	a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) frame hinged safety type.	Each	609.25	2655.60	Each	609.25	2655.60		
	b) concrete Gully trap.	ditto	609.25	2430.60	ditto	609.25	2430.60		
8	Constructing standard gully grating chamber, 3'x2½' (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects.	Each	1847.85	7544.30	Each	1847.85	7544.30	ditto	Pipe connection to be paid separately.
9	Extra for making and finishing benching floor work in manhole chamber, with 1/8" (3 mm) thick cement finish	100Sft.	787.65	1241.30	Sq.m	84.75	133.55	14.4	
10	Restoration of brick pavement on edge, over laid service line, with 2" (50 mm) sand cushion under soling	100Sft.	1122.90	2686.40	Sq.m	120.85	289.05	13.1	
11	Restoration of flat brick pavement sand grouted, over 2' (50 mm) thick dry sand cushion, under soling on laic service line.	100Sft.	681.80	1806.80	Sq.m	73.35	194.40	13.1	
12	Restoration of metalled road, on laid service line, including compaction:-							13.1	
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base	100Sft.	2712.15	9110.35	Sq.m	291.85	980.25		
	b) Carpeted road, with 1½" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base	100Sft.	1948.65	6728.95	Sq.m	209.70	724.05		
	c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base.	100Sft.	774.40	4392.95	Sq.m	83.35	472.70		
13	Providing and fixing 11/4"x11/4"x3/16" (31x31x5 mm) angle							14.7	

	MRS, BI-ANNUAL PERIOD (1st FEBRU	JULY, 2013)	3) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr. No.	Description	1	Rate (British Sys	stem)	Ra	nte (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iron step, in manhole chambers, including carriage and setting the same in work to correct lines and levels	Each	76.05	234.05	Each	76.05	234.05		
14	Fixing manhole frame and cover in R.C.C. slab including carriage to site.	Per set	188.15	-	Per set	188.15	-	ditto	
15	Providing and fixing 3" (75 mm) thick R.C.C. manhole cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20" (500 mm) clear i/d (frame weighing 37.324 Kg. or one maund) as per Standard Drawing STD/PD No. 5, of 1977, complete in all respects.	Per set	127.95	2830.30	Per set	127.95	2830.30	ditto	
15-A	Providing and fixing 6" thick R.C.C. manhole cover with tee shaped C.I. frame of 22" I/d (frame weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect.	Per set	258.55	4098.10	Per set	258.55	4098.10		
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects.	Per set	231.35	2501.95	Per set	231.35	2501.95	ditto	
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhole cover with 3"x3"x ¹ / ₄ " (75x75x6mm) angle iron frame, 22' (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects.	Per set	199.55	3976.15	Per set	199.55	3976.15	ditto	
18	Desilting of disposal work collecting tank, including removal of sludge within 3 chains (90 metre)	100Cft.	573.25	627.55	cum	202.45	221.65	16.2	
19	Providing and installing, C.I. ventilating shaft painted with bituminous paint with foundation bolts, as per PHEC Standard Drawing STD/PD No. 4 of 1977, complete in all respects (except concrete foundation block):							14.6	
	 a) 6" (150 mm) i/d shaft i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long 	Per Cwt ditto ditto ditto	169.15 187.90 202.95 212.35	2323.90 2349.00 2362.70 2372.45	ditto	332.90 369.90 399.50 418.00	4574.65 4624.05 4650.95 4670.20		
	b) 9" (225 mm) i/d shaft								
	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long iv) 36 ft. (11 metre) long	Per Cwt ditto ditto ditto	148.35 159.90 171.20 206.05	2299.35 2310.40 2322.00 2356.75	ditto	292.05 314.70 337.00 405.65	4526.30 4548.00 4570.90 4639.30		
	c) 12" (300 mm) i/d shaft								

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB												
Sr.	Description	F	Rate (British Sys	tem)	Ra	te (Metric S	system)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
20	i) 18 ft. (5.5 metre) long ii) 24 ft. (7.30 metre) long iii) 30 ft. (9.15 metre) long Silt clearing 10' (3.00 m) dia wells, and removal of slush outside the compound: a) upto 10' (3.00 m) depth of slush b) beyond 10' (3.00 m) depth of slush	Per Cwt ditto ditto	130.90 168.30 196.35 4857.60 9517.20	2282.90 2317.50 2344.85		257.70 331.30 386.50 4857.60 9517.20	4493.95 4562.00 4615.90 - -						



Timance Department

22. SINKING OF WELLS

- Rates for all finished works include the removal of surplus debris, unused material and byproducts. Well curbs to be laid at spring level or as deep as possible.

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB											
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Excavation of well in dry upto 20'(6 metre) below ground level, and disposal of soil within one chain (30 metre)											
	a) in ordinary soil or sand :-	1000 Cft.			cu.m							
	 i) from 0' to 5' (o to 1.5 m) depth ii) from 5.1' to 10' (1.5 to 3.0 metre) depth iii) from 10.1' to 15' (3.0 to 4.5 metre) depth iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth b) in hard soil i) from 0' to 5'(0 to 1.5 metre) depth ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth or in hard strata, such as shingle, gravel, etc. 	ditto ditto ditto ditto ditto 1000 Cft. ditto ditto ditto	2981.50 3113.95 3503.15 4020.85 3631.60 3796.10 4149.25 4666.90		ditto	105.30 110.00 123.75 142.00 128.25 134.10 146.55 164.85						
2	i) from 0' to 5'(0 to 1.5 metre) depth ii) from 5.1' to 10'(1.5 to 3.0 metre) depth iii) from 10.1' to 15'(3.0 to 4.5 metre) depth iv) from 15.1' to 20'(4.5 to 6.0 metre) depth Dry sinking of well, including loading, and removing excavated material within one chain (30 m):-	1000 Cft. ditto ditto ditto	7833.00 8113.90 8459.00 9080.95	Depart :	cu.m ditto ditto ditto	276.65 286.60 298.75 320.75	-					
	a) in ordinary soil:- i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth iv) from 25.1' to 30'(7.5 to 9.0 m) depth v) from 30.1' to 35'(9.0 to 10.5 m) depth vi) from 35.1' to 40'(10.5 to 12.0 m) depth vii) from 40.1'to 45'(12.0 to 13.5 m) depth viii) from 45'(13.5 Sm) to any depth	1000 Cft. ditto ditto ditto ditto ditto ditto ditto	16051.20 20064.00 24076.80 28089.60 32102.40 36115.20 40128.00 44140.80		cu.m ditto ditto ditto ditto ditto ditto ditto	566.95 708.65 850.40 992.15 1133.85 1275.60 1417.30 1559.05						
	 i) in hard soil:- i) from 10' to 15'(3.0 to 4.5 m) depth ii) from 15.1' to 20'(4.5 to 6.0 m) depth iii) from 20.1' to 25'(6.0 to 7.5 m) depth 	1000 Cft. ditto ditto	22070.40 26083.20 30096.00	- - -	cu.m ditto ditto	779.55 921.25 1063.00	- - -					

	MRS, BI-ANNUAL PERIOD (1st FEB	RA, SOAN	VALLEY,	KHUSHAB					
Sr.	Description	1	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	34108.80	_	ditto	1204.70	_		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	38121.60	_	ditto	1346.45	_		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	42134.40	_	ditto	1488.20	_		
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	46147.20	_	ditto	1629.90	_		
	viii) from 45'(13.5 m) to any depth	ditto	50160.00	-	ditto	1771.65	-		
	c) in hard strata, such as shingle, gravel, etc.								
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	30096.00	-	cu.m	1063.00	-		
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	34108.80	-	ditto	1204.70	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	38121.60	- 1 - /	ditto	1346.45	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	38623.20	J = -	ditto	1364.15	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	46147.20	-	ditto	1629.90	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	50160.00		ditto	1771.65	-		
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	54172.80		ditto	1913.40	-		
	viii) from 45'-1" (13.5 m) to any depth	ditto	58185.60		ditto	2055.10	-		
3	Wet sinking of well in ordinary soil (value of C upto 5), for	1884	1	.60)				*841-1	The outer dimensions of the curb
	depths below spring level, including charges of machinery,	You						to	shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within	- 4		- 10	833			841-9	
	one chain (30 m):-		20	2					
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	25934.10	(II) ne source	cu.m	916.00	-		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	55110.00	The second of	ditto	1946.50	-		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	67827.70	-	ditto	2395.65	-		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	88176.00	-	ditto	3114.40	-		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	97973.35	-	ditto	3460.40	-		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	110220.00	-	ditto	3892.95	-		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	113046.15	-	ditto	3992.80	-		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	116021.05	-	ditto	4097.85	-		
	ix) above 80'(24.0 m) to any depth	ditto	125965.70	-	ditto	4449.10	-		
4	Wet sinking of well in cohesive soil (value of Cmore than							*841-1	The outer dimensions of the curb
•	5), for depths below spring level, including charges of							to	shall form basis of payment.
	machinery shoring, kentledge and removal of excavated							841-9	Pujmenu
	spoil within one chain (30 m):-							0.17	
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	-	39191.95	cu.m	-	1384.25		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	-	48989.95	ditto	-	1730.30		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	-	58787.90	ditto	-	2076.40		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	-	78383.90	ditto	-	2768.50		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	-	90442.95	ditto	-	3194.45		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	-	97979.85	ditto	-	3460.65		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	-	106887.10	ditto	-	3775.25		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	-	110920.60	ditto	-	3917.70		

	MRS, BI-ANNUAL PERIOD (1st FEI	VALLEY,	KHUSHAB						
Sr.	Description	1	Rate (British Sy	stem)	Ra	ite (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ix) above 80'(24.0 m) to any depth	ditto	-	117575.80	ditto	-	4152.80		
5	Wet sinking of well in shingle, or gravel, etc, for depths below spring level, including charges of machinery, shoring, kentledge and removal of excavated spoil within one chain (30 m):-							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.
	i) from o' to 10'(0 to 3.0 m) depth ii) above 10' to 20'(3.0 to 6.0 m) depth iii) above 20' to 30'(6.0 to 9.0 m) depth	1000 Cft. ditto ditto	- - -	53443.55 65319.90 78383.90	cu.m ditto ditto	- - -	1887.60 2307.10 2768.50		
	iv) above 30' to 40'(9.0 to 12.0 m) depth v) above 40' to 50'(12.0 to 15.0 m) depth vi) above 50' to 60'(15.0 to 18.0 m) depth vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto ditto ditto ditto	()	106887.10 117575.80 130639.80 136716.05	ditto ditto ditto ditto	- - -	3775.25 4152.80 4614.20 4828.80		
_	viii) above 70' to 80'(21.0 to 24.0 m) depth ix) above 80'(24.0 m) to any depth	ditto ditto		139971.20 154705.05	ditto ditto		4943.80 5464.20		
6 7	Making and fixing in position, kiker wood well curb. Laying well curb in position only.	Per Cft.	766.25 279.85	2159.05	cu.m Each	27064.70 279.85	76257.80		
8	Providing, making and laying R.C.C. well curb in position, using coarse sand, including all kinds of form, moulds, curing, shuttering, rendering and finishing the exposed surface, (including screening and washing of aggregate :-	Œ,	nance	Depart				*841-1 to 841-9	I) If concrete mixer is supplied by Government, all charges including depreciation will be recovered from the contractor. The rate does not include cost of
	a) Ratio 1:1½:3 b) ratio 1:2:4	Per Cft. ditto	164.60 164.60	361.25 336.65	cu.m ditto	5813.80 5813.80	12759.60 11890.75		steel reinforcement and its labour for bending, which is payable, separately.
9	Providing and fixing structural steel for cutting edge.	100Kg	600.60	10774.30	100Kg	600.60	10774.30	841-1 to 841-9	
10	Making and removing false masonry on well.	100Cft.	5066.15	16533.40	cu.m	1789.35	5839.60	21.1 to 21.5 & 18.1	The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.

^{*} Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

23. TUBEWELL AND WATER SUPPLY

- Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)" Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 2013 TO 31st JULY, 2013)			13) TEH: NOWSHERA, SOAN VA			LLEY, KHU	JSHAB
Sr.	Description	R	ate (British S	System)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Boring for tubewell in all types of soil except shingle and rock, from ground level to 100 ft. (30 m) depth, including sinking and withdrawing of casing pipe, complete:-							Chap. 2	
2	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 100.1 ft. to 200 ft.	Per Rft. of bore ditto ditto ditto ditto ditto ditto ditto ditto	*	43.25 59.45 106.55 162.60 209.85 266.00 289.15 429.75 456.20	Per Metre of bore ditto ditto ditto ditto ditto ditto ditto ditto		141.95 194.95 349.45 533.35 688.35 872.40 948.40 1409.60 1496.35	ditto	
	(30 to 60 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d	Per Rft. of bore ditto ditto ditto ditto ditto	ance (179.80 253.50 283.90 325.50 356.45 503.90 530.40	Per Metre of bore ditto ditto ditto ditto		589.75 831.45 931.25 1067.60 1169.15 1652.85 1739.65		
3	Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 200.1 ft. to 300 ft. (60 to 90 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d	Per Rft.			Per Metre		823.60	ditto	
4	b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle gravel & rock, from a depth of 300.1 ft. to 400 ft. (90 to 120 m) below ground level, including sinking and withdrawing of casing pipe, complete:-	of bore ditto ditto ditto ditto ditto		324.20 357.40 403.95 428.35 553.40 581.10	of bore ditto ditto ditto ditto ditto		1063.30 1172.20 1325.00 1404.90 1815.20 1905.95	Chap. 2	
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d	Rft of bore ditto		431.45 483.05	Per Metre of bore		1415.10 1584.35		

	MRS, BI-ANNUAL PERIOD (1st FEBR	st JULY, 2013	13) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description	R	ate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	ditto ditto ditto		509.20 676.30 679.90	ditto ditto ditto		1670.20 2218.30 2230.10		
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells in all types of soil except shingle, gravel and rock:							ditto	
	a) from ground level to 250 ft. (75 m) below ground level:								
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto		411.40 591.65	Per Metre of bore ditto		1349.35 1940.60		Upto 2 cusec discharge Above 2 cusec discharge
	b) exceeding 250 ft. (75 m) depth below ground level:-	Rft	×		Per Metre		1040.05		
	i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	of bore ditto		411.40 591.65	of bore ditto		1349.35 1940.60		Upto 2 cusec discharge Above 2 cusec discharge
6	Boring for tubewell in shingle, gravel and rock, including sinking and withdrawing of casing pipe:-	E E			7 🚳			ditto	Location and depth of shingle, gravel or rock is to be determined from the bore log.
	a) from ground level to 200 ft. (60 m) below ground level:	(E)			3				
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	Per Rft. of bore ditto	ance (927.80 1254.80	Per Metre of bore ditto		3043.20 4115.80		Upto 2 cusec discharge Above 2 cusec discharge
	b) exceeding 200 ft. (60 m) depth below ground level:-			9					
	i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d	ditto ditto		927.80 1254.80	ditto ditto		3043.20 4115.80		Upto 2 cusec discharge Above 2 cusec discharge
7	Providing strong substantially built box of deodar wood 4'x2½'x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	637.15	11324.35	Job for complete bore	637.15	11324.35	ditto	
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	118.80	169.20	Per Set of 2 bottles	118.80	169.20	Chap. 2	
9	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc complete:-							ditto	Cost/labour of jointing both ends is included in the rate.
	a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick	Per Rft. Per Rft. Per Rft. Per Rft.	21.80 21.80 29.05 32.80	1019.30 1278.55	Per Metre Per Metre Per Metre Per Metre	71.50 71.50 95.35 107.60	2275.65 3343.30 4193.70 4929.20		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VA								USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	36.35 42.40 51.50 51.50 58.00	1921.90 2435.00 2487.50	Per Metre Per Metre Per Metre Per Metre Per Metre	119.20 139.10 168.95 168.95 190.25	5285.20 6303.85 7986.80 8159.00 8387.00		
	j) 10" i/d, ¹/4" (250 mm i/d 6 mm) thick k) 12" i/d, ¹/4" (300 mm i/d 6 mm) thick l) 15" i/d, ¹/4" (375 mm i/d 6 mm) thick m) 18" i/d, ¹/4" (450 mm i/d 6 mm) thick n) 20" i/d, ¹/4" (500 mm i/d 6 mm) thick o) 22" i/d, ¹/4" (550 mm i/d 6 mm) thick	Per Rft.	58.00 59.20 67.90 67.90 80.00 81.20	3681.70 4582.90 5160.40 5697.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	190.25 194.20 222.65 222.65 262.45 266.35	10625.60 12076.00 15031.85 16926.05 18687.85 21446.95		
10	Providing and installing M.S. Bail plug in tubewell bore hole:	n 1 /	05.60	54150	F 1	05.60	541.50		In the case of increase or decrease in the length of Bail plug, the rates will be increased or decreased as
	a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long. b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long. c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long. d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long. e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long.	Each Each Each Each Each	95.60 95.60 159.60 159.60 215.35	541.50 725.35 1397.00 1765.65 2232.90		95.60 95.60 159.60 159.60 215.35	541.50 725.35 1397.00 1765.65 2232.90		per rates given in serial No. 14 of this chapter for the respective diameter.
	f) 7" i/d, 2 ft. (175 mm i/d 600 mm) long. g) 8" i/d, 2 ft. (200 mm i/d 600 mm) long h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long i) 10" i/d, 2 ft. (250 mm i/d 600 mm) long	Each Each Each Each	215.35 265.55 265.55 265.55	2592.95 2872.10 3198.85 4104.45		215.35 265.55 265.55 265.55	2592.95 2872.10 3198.85 4104.45		
	j) 12" i/d, 2 ft. (300 mm i/d 600 mm) long k) 15" i/d, 2 ft. (375 mm i/d 600 mm) long l) 18" i/d, 2 ft. (450 mm i/d 600 mm) long m) 20" i/d, 2 ft. (500 mm i/d 600 mm) long n) 22" i/d, 2 ft. (550 mm i/d 600 mm) long	Each Each Each Each Each	318.75 318.75 383.20 416.85 416.85	4926.90 6081.00 6937.60 7686.75 8457.65	Each Each Each Each Each	318.75 318.75 383.20 416.85 416.85	4926.90 6081.00 6937.60 7686.75 8457.65		
11	Providing and installing, P.V.C. strainer B.S.S. Class 'B', in tubewell bore hole, including sockets and solvents, etc complete:-							Chap. 2	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm)	Per Rft.	16.55 18.80 19.90 23.25 31.70 32.45 32.45	161.60 222.70 293.25 703.70 1052.45	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	54.30 61.75 65.30 76.25 104.00 106.35 106.35	361.30 530.10 730.50 961.85 2308.15 3451.95 4593.40		
12	Providing and installing P.V.C. strainer B.S.S. Class `D', in tubewell bore hole, including sockets and solvent, etc complete:-								
	a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm)	Per Rft. Per Rft. Per Rft. Per Rft.	11.45 11.70 11.80 16.55	53.70 82.60	Per Metre Per Metre Per Metre Per Metre	37.55 38.40 38.75 54.35	155.65 176.15 270.95 558.15		

	MRS, BI-ANNUAL PERIOD (1st FEBR	LLEY, KHU	JSHAB						
Sr.	Description	R	ate (British S	System)	R	ate (Metric S	System)	Spec.	Remarks
No.	•	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft.	18.75 19.90 35.80	391.90	Per Metre Per Metre Per Metre	61.55 65.30 117.35	876.3 1285.45 1849.2		
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:-								
	i) B.S.S. Class `B'								
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) ii) B.S.S. Class `D' a) 11/4" i/d (30 mm) b) 11/2" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each Each	8.40 9.40 10.20 13.45 15.85 16.70 19.60 19.60 5.85 6.15 6.35 8.40 9.40 10.20 13.45	60.00 79.00 118.20 173.05 339.85 472.70 637.60 661.60 32.25 45.75 65.15 86.40 112.60 159.00 207.85	Each Each Each Each Each Each Each Each	8.40 9.40 10.20 13.45 15.85 16.70 19.60 19.60 5.85 6.15 6.35 8.40 9.40 10.20 13.45	60.00 79.00 118.20 173.05 339.85 472.70 637.60 661.60 32.25 45.75 65.15 86.40 112.60 159.00 207.85		
	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:- a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (125 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 1/4" (250 mm i/d 6 mm) thick j) 12" i/d, 1/4" (300 mm i/d 6 mm) thick k) 15" i/d, 1/4" (375 mm i/d 6 mm) thick l) 18" i/d, 1/4" (450 mm i/d 6 mm) thick m) 20" i/d, 1/4" (500 mm i/d 6 mm) thick n) 22" i/d, 1/4" (550 mm i/d 6 mm) thick	Per Rft.	57.65 57.65 72.15 72.15 102.95 102.95 120.15 120.15 144.20 176.40 190.20	317.45 417.50 760.35 916.55 1052.15 1297.55 1471.35 1892.55 2229.20 2750.45 3416.75 3790.60	Per Metre Per Metre	189.10 189.10 236.65 236.65 337.70 394.10 394.10 473.00 473.00 578.60 623.85 623.85	782.50 1041.25 1369.40 2494.00 3006.30 3451.05 4256.00 4826.05 6207.55 7311.75 9021.45 11206.90 12433.10 13614.00	Chap. 2	
15	Providing and installing P.V.C. blind pipe, B.S.S. Class `B', in tubewell bore hole, including sockets and solvent: and jointing with strainer, etc. complete.							ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20)13 TO 31s	st JULY, 2013) TEH: N	OWSHER	A, SOAN VAI	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
16	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) Providing and installing P.V.C. blind pipe, B.S.S. Class	Per Rft.	21.05 23.80 24.90 29.90 39.70 41.40 49.30 46.30	173.80 231.30 321.50 488.50 756.60 1047.70	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	69.10 78.05 81.65 96.65 130.25 135.80 161.75 151.90	391.85 570.05 758.65 1053.10 1602.30 2481.70 3436.50 4087.90		
17	'D', in tubewell bore hole, including sockets and solvent and jointing with strainer, etc. complete. a) 1½" i/d (30 mm) b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) Testing and developing of tubewell of size 6" (150 mm) i/d and above continuously. i) upto 1.5 cs. discharge	Per Rft. Per Hour	13.60 13.85 14.70 18.50 23.80 24.90 30.65	59.95 85.75 172.10 281.85 407.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	44.65 45.45 48.20 60.65 78.05 81.65 100.60	161.15 196.60 281.20 564.45 924.45 1337.70 1928.15		
18	ii) above 1.5 cs. discharge Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3 mm), around tubewell in bore hole.	ditto Per Cft.	22.00	1317.30 73.65	CONTRACTOR RE	777.05	1317.30 2601.30		The rate includes wastage, etc.
19	Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc complete in all respects:- a) 3" (75 mm) i/d	Per Rft.		44.50	Per Metre		145.90	Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
	b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft.		55.20 69.20 81.85 99.45 149.35 175.20 226.35	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		181.10 226.95 268.50 326.25 489.85 574.60 742.40 980.45		
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:-							ditto	 Pipes to be supplied by Government. Providing and installing specials

	MRS, BI-ANNUAL PERIOD (1st FEBR	RUARY, 20	ARY, 2013 TO 31st JULY, 2013) TEH				A, SOAN VAI	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d	Per Rft.		22.90 33.25 36.55 42.90	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		67.70 75.05 109.00 119.90 140.65 196.40		and valves is not included in the rate, which is payable separately.
21	g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d Laying, cutting, jointing, testing and disinfecting cast iron	Per Rft. Per Rft. Per Rft.		96.50	Per Metre Per Metre Per Metre		229.95 316.35 400.25	Chap. 2	Pipes to be supplied by
	pipe line in trenches with Tyton joints, complete in all respects: a) 3" (75 mm) i/d	Per Rft.	×		Per Metre		32.75		Government. 2) Providing and installing specials and valves is not included in the rate, which is payable separately.
	b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d	Per Rft.		14.70 16.55 22.55 28.40	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		37.65 48.25 54.20 73.90 93.15 110.90		
22	h) 15" (375 mm) i/d i) 18" (450 mm) i/d Providing, laying, cutting, jointing, testing and disinfecting	Per Rft. Per Rft.) 55 ; (2)	49.45	Per Metre Per Metre		162.15 194.15	Chap.	Cost of sockets, tees, elbows
	G.I. pipeline in trenches, with socket joints, using G.I pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves.i) Light Quality	Tin	ance		en een t			2	bends, valves, crosses, unions and plugs, etc. is included in the rates.
	a) ½" i/d (15 mm) 2mm thick b) ¾" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1½" i/d (32 mm) 2.65mm thick e) 1½" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"½ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick	Per Rft.	8.55 9.25 10.40 10.50 10.60 11.95 12.55 14.55	76.05 104.00 133.30 168.20 209.60 284.00 332.80	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	28.05 30.40 34.10 34.45 34.80 39.25 41.15 47.65 51.30	180.90 249.45 341.05 437.30 551.75 687.55 931.50 1091.50 1525.65		
	ii) Medium Quality a) ½" i/d (15 mm) 2.65mm thick b) ¾" i/d (20 mm) 2.65mm thick c) 1" i/d (25 mm) 3.25mm thick d) 1½" i/d (32 mm) 3.25mm thick e) 1½" i/d (40 mm) 3.25mm thick f) 2" i/d (50 mm) 3.65mm thick g) 2"½ i/d (65 mm) 3.65mm thick	Per Rft.	8.55 9.25 10.40 10.50 10.80 11.95 12.55	81.60 119.65 152.10 174.90 240.35	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	28.05 30.40 34.10 34.45 35.45 39.25 41.15	212.35 267.60 392.45 498.85 573.65 788.30 1002.85		i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia, 3/4"dia & 1/2"dia) for Bath rooms/ Levorotary. ii. For internal G.I piping (1"dia, 3/4"dia & 1/2"dia) Bath room(s)/ Levorotary of rate (composite) shall be

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	13 TO 31	st JULY, 2013) TEH: N	OWSHER	RA, SOAN VA	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	System)	R	ate (Metric S	System)	Spec.	Remarks
No.	•	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	h) 3" i/d (75 mm) 4.05mm thick i) 4" i/d (100 mm) 4.5mm thick j) 5" i/d (150 mm) 4.85mm thick k) 6" i/d (200 mm) 4.85mm thick iii) Heavy Quality	Per Rft. Per Rft. Per Rft. Per Rft.	14.55 15.65 18.15 18.45	547.10 749.95	Per Metre Per Metre Per Metre Per Metre	47.65 51.30 59.50 60.55	1261.80 1794.55 2459.90 2866.65		reduced by 8% and specials mentioned above may be paid at the rates placed on Website as per actual quantity used.
23	a) ½" i/d (15 mm) 3.25mm thick b) ¾" i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick d) 1½" i/d (32 mm) 4.05mm thick e) 1½" i/d (40 mm) 4.05mm thick f) 2" i/d (50 mm) 4.5mm thick g) 2"½ i/d (65 mm) 4.5mm thick h) 3" i/d (75 mm) 4.85mm thick i) 4" i/d (100 mm) 5.4mm thick j) 5" i/d (125 mm) 5.4mm thick k) 6" i/d (150 mm) 5.4mm thick Providing, laying, cutting, jointing, testing and disinfecting Asbestos cement/Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:	Per Rft.	8.55 9.25 10.40 10.50 10.80 11.95 12.55 14.55 15.65 18.15	118.70 174.75 227.20 254.95 349.45 437.60 562.40 765.15 946.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	28.10 30.40 34.10 34.45 35.45 39.25 41.15 47.65 51.30 59.50 60.55	300.45 389.3 573.25 745.3 836.2 1146.15 1435.35 1844.7 2509.7 3103.85 3665.15	PS 428 & ISO 160	Providing and installing specials and valves is not included in the rate, which is payable separately.
24	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (450 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm) C Class Working Pressure a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm) Class Working Pressure	Per Rft.	10.70 11.40 15.65 21.60 28.05 35.70 41.25 46.60 54.95 64.65 77.15 10.70 11.40 15.65 21.60 28.05 35.70 41.25 46.60 54.95 64.65 78.30	259.75 410.80 687.70 936.95 1238.10 1589.45 2019.55 2513.40 3091.70 4265.45 189.75 272.50 469.20 743.05 1034.85 1439.50 2209.50 2820.45 3458.70 4117.00	Per Metre	35.15 37.30 51.30 70.80 92.05 117.15 135.35 152.80 180.25 212.00 253.10 35.15 37.30 51.30 70.80 92.05 117.15 135.35 152.80 180.25 212.00 253.80	893.80 1539.05 2437.10 3394.30 4721.60 7247.15 9251.05 11344.55 13503.80 19008.50		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VAL							LLEY, KHUSHAB	
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	11.40 15.65 21.60 28.05 35.70 41.25	589.95 1040.45 1535.15 2239.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	37.30 51.30 70.80 92.05 117.15 135.35	1064.90 1935.10 3412.60 5035.25 7346.65 10933.15		
	g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)	Per Rft. Per Rft. Per Rft. Per Rft.	41.23 46.60 54.95 64.65	4303.75 5182.75	Per Metre Per Metre Per Metre	152.80 180.25 212.00	10933.13 14116.25 16999.45 20733.50		
26	Providing, laying, cutting, jointing, testing and disinfecting P.V.C. pipe line of B.S.S. with 'B' Class working pressure pipe, in trenches, complete in all respects:		×					Chap 2	Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) h) 12" i/d (300 mm) g) 14" i/d (350 mm)	Per Rft.	3.15 4.00 4.90 5.25 7.40 9.70 11.95 15.30		Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	10.40 13.15 16.10 17.15 24.30 31.75 39.25 50.20	339.60 515.00 706.65 992.75 1525.80 2424.50 3379.50 4064.95		
27	Providing, laying, cutting, jointing, testing and disinfecting pipe line in trenches with P.V.C. pipes of B.S.S. with `D' Class working pressure complete in all respects: a) 2" i/d (50 mm) b) 3" i/d (75 mm) c) 4" i/d (100 mm) d) 5" i/d (125 mm) e) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	2.60 3.10 3.95 4.85 5.15	159.80 267.15 395.45	Per Metre Per Metre Per Metre Per Metre Per Metre	8.45 10.25 12.95 15.85 16.85	246.15 524.10 876.25 1297.05 1880.95	ditto	Providing and installing specials and valves is not included in the rate, which is payable separately.
28	Providing and fixing cast iron special of B.S.S. Class `B' (such as bend, tee cross collar, reducer, tail piece flanged spigot, cap, flanged socket, taper, angle branch plug etc.) for cast iron pipe line, complete:-							9.1	i) Labour rates include the cost of jointing material & labour. ii) The internal dia of the pipe, from which the branch is taken out will
	a) C.I.S.S. Specials, with spigot. and socket joint:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d	Per Kg. Per Kg. Per Kg.	19.75 11.30 8.10	102.40 93.95 90.75	Per Kg	19.75 11.30 8.10	102.40 93.95 90.75		be considered the internal dia for the purpose of payments of specials.
	 b) C.I. flanged specials, with flanged and flanged joints:- 3" to 6" (75 to 150 mm) i/d 8" to 12" (200 to 300 mm) i/d 15" to 18" (375 to 450 mm) i/d 	Per Kg Per Kg Per Kg	8.40 2.30 3.70	91.10 84.95 84.95	Per Kg	8.40 2.30 3.70	91.10 84.95 84.95		

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY, 20)13 TO 31s	st JULY, 2013) TEH: N	IOWSHER	A, SOAN VAI	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	c) C.I. Specials, with tyton joints:-								
	i) 3" to 6" (75 to 150 mm) i/d	Per Kg	10.95	93.65	Per Kg	10.95	93.65		
	ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d	Per Kg Per Kg	10.95 10.95	93.65 93.65	Per Kg Per Kg	10.95 10.95	93.65 93.65		
29	Providing and fixing cast iron specials of B.S.S. Class 'B (such as bend, tee, cross collar, reducer, tail piece							9.1	Labour rates include the cost of jointing material and labour.
	flanged socket, flanged spigot, cap, taper, angle branch, plug, etc) for Asbestos cement pipe line, with comet join								2) The internal dia of the pipe, from
	and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d	Per Kg	11.70	94.40	Per Kg	11.70	94.40		which the branch is taken out, will be considered the internal dia for
	ii) 8" to 18" (200 to 450 mm) i/d iii) 20" to 24" (500 to 600 mm) i/d	Per Kg Per Kg	6.10 4.85	88.75 87.55	Per Kg Per Kg	6.10 4.85	88.75 87.55		the purpose of payment.
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class `B', for cast iron pipe line, and Asbestos	. (\			9.1	Labour rates include cost of jointing material and labour.
	cement pipe line (including cost of jointing material): a) 3" i/d (75 mm)	Each	587.95	6047.95	Each	587.95	6047.95		
	b) 4" i/d (100 mm)	Each	639.80	7119.80	Each	639.80	7119.80		
	c) 5" i/d (125 mm)	Each	1151.65	8711.65	Each	1151.65	8711.65		
	d) 6" i/d (150 mm)	Each Each	1227.75	11787.75	Each	1227.75 1433.50	11787.75 20753.50		
	e) 8" i/d (200 mm) f) 10" i/d (250 mm)	Each	1433.50 2429.10	20753.50 26669.10	Each Each	2429.10	26669.10		
	g) 12" i/d (300 mm)	Each	2729.65	34529.65	Each	2729.65	34529.65		
	h) 16" i/d (400 mm)	Each	3620.45	63020.45	Each	3620.45	63020.45		
	i) 18" i/d (450 mm)	Each	4166.90	110366.90	Each	4166.90	110366.90		
31	Providing and fixing, sluice valve of B.S.S. quality and	TE 12/00	CHICK !	AMERICAN E.					Labour rates include cost of jointing
31	weight, for Asbestos cement pipe line, with comet join and rubber ring, complete (including cost of jointing materials):-							9.1	material and labour.
	a) 3" i/d (75 mm)	Each	375.60	5055.60	Each	375.60	5055.60		
	b) 4" i/d (100 mm)	Each	461.70	5885.70	Each	461.70	5885.70		
	c) 6" i/d (150 mm)	Each	582.05	9882.05	Each	582.05	9882.05		
	d) 8" i/d (200 mm)	Each	953.70	17993.70	Each	953.70	17993.70		
	e) 10" i/d (250 mm)	Each	1218.80	22218.80	Each	1218.80	22218.80		
	f) 12" i/d (300 mm)	Each Each	1434.30 1697.95	27594.30 52937.95	Each Each	1434.30 1697.95	27594.30 52937.95		
	g) 16" i/d (400 mm) h) 18" i/d (450 mm)	Each	2022.75	94422.75	Each	2022.75	94422.75		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2½" (65 mm) dia (including cost of jointing material).	Each	55.60	4375.60	Each	55.60	4375.60	9.1	Labour rates include cost of jointing material and labour.
	,								2) Connecting pipes and specials, if used, will be paid extra.
33	Providing and fixing, air valve 2½ (65mm) dia of B.S.S. quality and weight (complete with jointing material)							ditto	
	a) single	Each	118.15	3178.15	Each	118.15	3178.15		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	13 TO 31s	st JULY, 2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
				•					
	b) double	Each	118.15	7078.15	Each	118.15	7078.15		
34	Providing and fitting C.I. flanges on pipes, including turning, threading, facing and fitting, etc. complete in all respects:-							ditto	
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	28.95	103.75	Per Kg	28.95	103.75		
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	18.40	93.20	Per Kg	18.40	93.20		
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	15.45	90.25	Per Kg	15.45	90.25		
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:	Per Inch	×		Per cm i/d				
	a) 3" to 6" (75 to 150 mm) i/d b) 8" to 12" (200 to 300 mm) i/d	i/d of pipe ditto		51.95 64.65	of pipe ditto		20.80 25.85		
	c) 15" to 18" (375 to 450 mm) i/d	ditto		59.60	ditto		23.85		
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I pipe of B.S.S. 1387-1967 complete in all respects, including specials and valves:-		357						Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) G.I. flanged joints (Heavy Quality)			10 0					
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	15.10 15.10 16.25 16.30 18.75 21.15 21.20	256.45 348.65 435.25 557.35 757.80 936.45 1106.00	Per Metre Per Metre Per Metre Per Metre	49.50 49.50 53.25 53.50 61.50 69.35 69.50	841.15 1143.60 1427.60 1828.15 2485.50 3071.55 3627.60		
	ii) C.I. flanged joints (Medium Quality)								
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft.	17.00 16.05 18.15 18.20 20.80 23.35 23.50	268.55 343.20 427.95 610.50 835.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	55.85 52.60 59.45 59.65 68.20 76.60 77.05	650.95 880.85 1125.75 1403.65 2002.35 2739.80 3186.55		
37	Providing and installing P.V.C. bends, of B.S.S.								
	i) Class `B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm)	Each Each Each	82.00 94.45 118.05	205.60 358.45 634.05	Each Each Each	82.00 94.45 118.05	205.60 358.45 634.05		

	MRS, BI-ANNUAL PERIOD (1st FEBRU	JARY, 20	13 TO 31s	st JULY, 2013) TEH: N	OWSHER	A, SOAN VAI	LLEY, KHU	JSHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	d) 6" i/d (150 mm)	Each	122.05	884.05	Each	122.05	884.05		
		24011	122.00	00.100		122.00	00 1.00		
	ii) Class `D' working pressure:-	F1-	52.70	96.10	F1-	52.70	96.10		
	a) 1½" i/d (30 mm) b) 1½" i/d (40 mm)	Each Each	53.70 57.90	86.10 92.70	Each Each	53.70 57.90	86.10 92.70		
	c) 2" i/d (50 mm)	Each	62.70	132.30	Each	62.70	132.30		
	d) 3" i/d (75 mm)	Each	82.00	266.80	Each	82.00	266.80		
	e) 4" i/d (100 mm)	Each	94.45	528.85	Each	94.45	528.85		
	f) 5" i/d (125 mm)	Each	118.05	1114.05	Each	118.05	1114.05		
	g) 6" i/d (150 mm)	Each	122.05	1526.05	Each	122.05	1526.05		
38	Providing and installing P.V.C. tees, of B.S.S.								
	i) Class `B' working pressure:-		×						
	a) 3" i/d (80 mm)	Each	123.00	579.00	Each	123.00	579.00		
	b) 4" i/d (100 mm)	Each	143.50	1067.50	Each	143.50	1067.50		
	c) 5" i/d (125 mm)	Each	174.35	2034.35	Each	174.35	2034.35		
	d) 6" i/d (150 mm)	Each	183.10	2103.10	Each	183.10	2103.10		
		187	and the same of the same of		/ 83/ ,				
	ii) Class `D' working pressure:-	886 1		-	2,650				
	a) 1 ¹ / ₄ " i/d (30 mm)	Each	82.05	208.05	Each	82.05	208.05		
	b) 1½" i/d (40 mm)	Each	87.15	241.95	Each	87.15	241.95		
	c) 2" i/d (50 mm)	Each	93.60	297.60	Each	93.60	297.60		
	d) 3" i/d (75 mm)	Each	123.00	573.00	Each	123.00	573.00		
	e) 4" i/d (100 mm)	Each	143.50	1067.50	Each	143.50	1067.50		
	f) 5" i/d (125 mm)	Each	174.35	2022.35	Each	174.35	2022.35		
	g) 6" i/d (150 mm)	Each	183.10	2091.10	Each	183.10	2091.10		
39	Providing and installing P.V.C. sockets, B.S.S.								
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm)	Each	58.80	140.40	Each	58.80	140.40		
	b) 4" i/d (100 mm)	Each	71.20	215.20	Each	71.20	215.20		
	c) 5" i/d (125 mm)	Each	89.05	287.05	Each	89.05	287.05		
	d) 6" i/d (150 mm)	Each	93.05	369.05	Each	93.05	369.05		
	e) 8" i/d (200 mm)	Each	134.70	770.70	Each	134.70	770.70		
	f) 10" i/d (250 mm)	Each	158.70	1886.70	Each	158.70	1886.70		
	g) 12" i/d (300 mm)	Each	183.60	4143.60	Each	183.60	4143.60		
	h) 14" i/d (350 mm)	Each	206.45	3326.45	Each	206.45	3326.45		
	ii) Class `D' working pressure:-								
	a) 1¼" i/d (30 mm)	Each	34.35	55.95	Each	34.35	55.95		
	b) 1½" i/d (40 mm)	Each	38.55	68.55	Each	38.55	68.55		
	c) 2" i/d (50 mm)	Each	43.35	91.35	Each	43.35	91.35		
	d) 3" i/d (75 mm)	Each	58.80	211.20	Each	58.80	211.20		
	e) 4" i/d (100 mm)	Each	71.20	353.20	Each	71.20	353.20		
	f) 5" i/d (125 mm)	Each	89.05	605.05	Each	89.05	605.05		
	g) 6" i/d (150 mm)	Each	93.05	1005.05	Each	93.05	1005.05		

	MRS, BI-ANNUAL PERIOD (1st FEBF	RUARY, 20	13 TO 31s	t JULY, 2013) TEH: N	OWSHER	A, SOAN VA	LLEY, KH	USHAB
Sr.	Description	R	ate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
40	Providing and installing P.V.C. Tapered core, B.S.S.								
	i) Class `B' working pressure:-								
	iy Chass B working pressure.								
	a) 3" i/d (75 mm)	Each	82.00	121.60	Each	82.00	121.60		
	b) 4" i/d (100 mm)	Each	94.45	147.25	Each	94.45	147.25		
	c) 5" i/d (125 mm) d) 6" i/d (150 mm)	Each Each	118.05 122.05	184.05 201.25	Each Each	118.05 122.05	184.05 201.25		
	e) 8" i/d (200 mm)	Each	173.40	305.40	Each	173.40	305.40		
	f) 10" i/d (250 mm)	Each	197.40	369.00	Each	197.40	369.00		
	g) 12" i/d (300 mm)	Each	230.05	441.25	Each	230.05	441.25		
	h) 14" i/d (350 mm)	Each	252.90	516.90	Each	252.90	516.90		
			/ ×						
	ii) Class `D' working pressure:-	/		}					
	a) 1 ¹ / ₄ " i/d (30 mm)	Each	53.70	72.90	Each	53.70	72.90		
	b) 1½" i/d (40 mm)	Each	57.90	84.30		57.90	84.30		
	c) 2" i/d (50 mm)	Each	62.70	95.10	Each	62.70	95.10		
41	Making connection for new watersupply lines with the	188 -			7 887				The rate includes the component of
41	running main, including excavation of trench and refilling,	7 300	10.000		3,666				bailing out water from the trench
	complete, but excluding cost of pipe and specials, etc	1834	1.10	60 /	1636				and cutting of existing pipe line.
		N. S.							
	Diameter of running main:	7503		5-23	Children of the Control of the Contr				
		Per	-	al same	Per				
	i) upto 6" i/d (150 mm)	Connection	1178.10		Connection	1178.10			
	ii) upto 8" i/d (200 mm)	ditto	1479.05	II) ENGLEFT	ditto	1479.05			
	iii) upto 10" i/d (250 mm)	ction ditto	2105.40 2857.80		ction	2105.40 2857.80			
	iv) upto 12" i/d (300 mm) v) upto 16" i/d (400 mm)	ditto	2857.80 3521.75		ditto ditto	2857.80 3521.75			
	vi) upto 20" i/d (400 mm)	ditto	4537.50		ditto	4537.50			
	vii) upto 24" i/d (600 mm)	ditto	5464.80		ditto	5464.80			
	, , , , , , , , , , , , , , , , , , ,								

24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

Sr.	Description	R	ate (British S	System)	Rate	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Supply and erection of G.I. pipes for wiring purposes, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.								
	a) on surface, including clamps, etc.							38.4	
	i) 15 mm i/d	Per Rft.	14.80	60.15	Per Metre	48.60	197.30		
	ii) 20 mm i/d	Per Rft.	14.80	74.55	Per Metre	48.60	244.45		
	iii) 25 mm i/d	Per Rft.	14.80	97.40	Per Metre	48.60	319.55		
	iv) 32 mm i/d	Per Rft.	17.95	123.75	Per Metre	58.85	405.85		
	v) 40 mm i/d	Per Rft.	17.95	151.90	Per Metre	58.85	498.30		
	vi) 50 mm i/d	Per Rft.	21.35	188.30	Per Metre	70.10	617.70		
	vii) 80 mm i/d	Per Rft.	27.20	294.70	Per Metre	89.20	966.65		
	b) recessed in walls, including hooks, cutting jharries and	1			537			20.2	
	repairing surface:		24	La Carrie				38.3	
	i) 15 mm i/d	Per Rft.	21.10	64.25	Per Metre	69.15	210.70		
	ii) 20 mm i/d	Per Rft.	21.10	79.55	Per Metre	69.15	260.95		
	iii) 25 mm i/d	Per Rft.	21.95	103.70	Per Metre	72.05	340.15		
	iv) 32 mm i/d	Per Rft.	21.95	126.95	Per Metre	72.05	416.45		
	v) 40 mm i/d	Per Rft.	23.95	156.45	Per Metre	78.60	513.15		
	vi) 50 mm i/d vii) 80 mm i/d	Per Rft. Per Rft.	32.95 52.70	199.00 320.15	Per Metre Per Metre	108.10 172.90	652.65 1,050.10		
2	Supply and erection of M.S. conduit pipes for wiring, including						·	38.4 & 38.6	
_	pull boxes, inspection boxes, bends, tees, etc. complete with							36.4 & 36.0	
	all specials.								
	a) on surface, including clamps, etc.								
	i) 16 mm i/d	Per Rft.	10.30	30.75	Per Metre	33.75	100.90		
	ii) 20 mm i/d	Per Rft.	10.30	36.05	Per Metre	33.75	118.25		
	iii) 25 mm i/d	Per Rft.	10.30	41.25	Per Metre	33.75	135.30		
	iv) 32 mm i/d	Per Rft.	10.30	45.70	Per Metre	33.75	149.90		
	v) 40 mm i/d	Per Rft.	11.55	58.00	Per Metre	37.95	190.20		
	vi) 50 mm i/d	Per Rft.	14.25	70.85	Per Metre	46.70	232.35		
	b) recessed in walls, including cutting jharries, cost of hooks and repairing surface etc.							38.3 & 38.7	
	i) 16 mm i/d	Per Rft.	18.85	40.35	Per Metre	61.75	132.30		
	ii) 20 mm i/d	Per Rft.	18.85	45.10	Per Metre	61.75	147.90		
	iii) 25 mm i/d	Per Rft.	21.10	51.75	Per Metre	69.15	169.75		

	MRS, BI-ANNUAL PERIOD (1st FEBRUA	ARY, 20	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KH	IUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sv	stem)	Spec.	Remarks
No.	Bestription	Unit	Labour	Composite	Unit	Labour	Composite	No.	Remarks
	iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d	Per Rft. Per Rft. Per Rft.	21.95 22.90 23.95	57.35 68.30 81.10	Per Metre Per Metre Per Metre	72.05 75.20 78.60	188.15 223.95 265.95		
3	Supply and erection of PVC pipe for wiring recessed in walls, including inspection boxes, pull boxes, hooks, cutting jharries, and repairing surface, etc., complete with all specials.							38.3 & 38.5	
	i) 12 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	17.00 17.55 19.55 21.10 21.95 22.90	27.40 31.55 37.55 45.65 55.80 66.95	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	55.80 57.65 64.05 69.15 72.05 75.20	89.80 103.55 123.25 149.75 182.95 219.55		
4	Supply and erection of PVC pipe for wiring on surface including clamps inspection boxes, pull boxes, bends, tees, repairing surface, etc., complete with all specials:-	E		1100		15 20	51.60		
	i) 12 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d	Per Rft.	4.65 4.65 4.65 5.30 5.30 6.40	15.75 19.25 24.55 32.90 43.50 58.45	Per Metre	15.20 15.20 15.20 17.35 17.35 20.95	51.60 63.20 80.50 107.85 142.70 191.75		
5	Supply and erection of G.I. flexible pipe for wiring, including welding of sockets, nipples and check nuts, etc. complete:-							38.4	
	i) 12 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d vii) 80 mm i/d	Per Rft.	12.20 13.00 13.45 16.25 17.75 19.50 26.00	56.10 72.30 96.50 117.95 133.35 173.55 334.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	40.00 42.70 44.15 53.35 58.20 64.00 85.35	184.00 237.10 316.55 386.95 437.40 569.20 1,097.55		
6	Supply and erection PVC pipe for recessed wiring (main and sub-main) purpose, including bends, specials, etc. in floor, wall or trenches:-							38.2 & 38.3	
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	22.90 26.35 26.35	68.60 89.05 114.15	Per Metre Per Metre Per Metre	75.20 86.45 86.45	224.95 292.05 374.40		
7	Supply and erection of PVC pipe for surface wiring (main and sub-main) including clamps, inspection boxes, pull boxes bends etc., complete with all specials:-								

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20°	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, K	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.	·	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	6.40 9.25 10.60	53.35 88.30 111.30	Per Metre Per Metre Per Metre	20.95 30.35 34.70	175.00 289.65 365.05		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	1.85	4.05	Per Metre	6.05	13.35	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	1.85	13.05	Per Metre	6.05	42.85	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):- a) 250/440 volts, PVC insulated: i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (19/0.052") viii) 19/1.32 mm (19/0.064") b) 250/440 volts, PVC insulated cotton braided and compounded cables:- i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.036") v) 7/1.12 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft.	3.70 3.70 4.10 4.65 5.70 12.80 14.95 4.10 4.10 4.35 4.85 5.60	9.95 10.35 14.10 20.75 29.55 71.35 115.25 157.70 10.35 10.75 14.50 20.95 29.80 71.25	Per Metre	12.15 12.15 12.15 13.50 15.20 18.70 42.05 49.05 13.50 13.50 14.30 16.00 18.40	32.60 33.95 46.20 68.00 96.95 234.00 378.05 517.30 33.95 35.30 47.55 68.80 97.75 233.70	38.1	
11	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):- i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044")	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.70 3.70 3.70 4.10 4.65	9.50 12.45 16.60 23.65 33.30	Per Metre Per Metre Per Metre Per Metre Per Metre	12.15 12.15 12.15 13.50 15.20	31.20 40.75 54.40 77.55 109.20		

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KI	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.70	65.10	Per Metre	18.70	213.55		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-							38.1 to 38.7	
	i) 7/1.63 mm (7/0.064") ii) 19/1.32 mm (19/0.052") iii) 19/1.63 mm (19/0.064") iv) 19/2.11 mm (19/0.083") v) 37//1.83 mm (37/0.072") vi) 37/2.11 mm (37/0.083") vii) 37/2.62 mm (37/0.103")	Per Rft.	5.60 6.15 6.75 7.40 12.75 15.45 21.80	73.50 123.45 166.75 318.05 441.90 554.40 850.40	Per Metre	18.40 20.25 22.10 24.30 41.90 50.60 71.45	241.05 404.85 547.00 1,043.15 1,449.35 1,818.40 2,789.25		
13	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):-	E						ditto	
	a) PVC insulated, PVC sheathed twin core, 250/440 volts. i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	4.10 4.10 4.10 4.35 4.85 5.60	17.00 23.65 31.95 46.30 65.55 129.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	13.50 13.50 13.50 14.30 16.00 18.40	55.75 77.55 104.80 151.90 214.95 425.95		
	b) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:-								
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064")	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	4.35 4.35 4.35 4.85 5.15 5.90	25.15 35.50 48.00 69.90 99.35 200.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	14.30 14.30 14.30 16.00 16.85 19.30	82.40 116.50 157.35 229.20 325.90 657.55		
	c) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:-								
	i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052")	Per Rft.	4.65 4.65 4.85 4.85 5.15 5.90 8.25	32.05 44.50 60.85 89.60 128.55 260.95 486.70	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	15.20 15.20 16.00 16.00 16.85 19.30 27.00	105.10 146.00 199.50 293.95 421.70 855.95 1,596.40		
	d) PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable.								Cost of trenches where necessary

	MRS, BI-ANNUAL PERIOD (1st FEBRUA	ARY, 20	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, K	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sv	stem)	Spec.	Remarks
No.	Description	Unit	Labour	Composite	Unit	Labour	Composite	No.	XOMUZ RS
	armoured with G.I. wire 16 SWG.								is included in the rates.
		Per Rft.	8.25	542.65	Per Metre	27.00	1,779.95		as meraded in the rates.
	i) 19/1.32 mm (19/0.052") ii) 19/1.63 mm (19/0.064")	Per Rft.	8.80	725.10	Per Metre	28.90	2,378.30		
	iii) 19/1.83 mm (19/0.072")	Per Rft.	9.25	981.85	Per Metre	30.35	3,220.50		
	iv) 19/2.11 mm (19/0.083")	Per Rft.	10.00	1,373.85	Per Metre	32.80	4,506.30		
	v) 37//1.83 mm (37/0.072")	Per Rft.	10.30	1,871.15	Per Metre	33.75	6,137.35		
	vi) 37/2.11 mm (37/0.083")	Per Rft.	12.35	2,365.25	Per Metre	40.50	7,758.05		
	vii) 37/2.36 mm (37/0.093")	Per Rft.	14.80	2,882.80	Per Metre	48.60	9,455.65		
	viii) 37/2.62 mm (37/0.103")	Per Rft.	18.50	3,588.00	Per Metre	60.70	11,768.65		
14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")							38.1	
	deep, with 4.75 mm thick (3/16") bakelite sheet top, for	/	~)				to	
	recessed wiring, including making holes for regulators, switches, plugs, etc.	/	,					38.7	
	i) 10 x 10 cm (4"x4")	Each	60.70	127.35	Each	60.70	127.35		
	ii) 17.5 x 10 cm (7"x4")	Each	75.90	169.40	Each	75.90	169.40		
	iii) 22.5 x 10 cm (9"x4")	Each	101.20	215.85	Each	101.20	215.85		
	iv) 20 x 25 cm (8"x10")	Each	121.45	317.30	Each	121.45	317.30		
	v) 25 x 30 cm (10"x12")	Each	151.80	419.70	Each	151.80	419.70		
	vi) 30 x 35 cm (12"x14")	Each	202.40	545.40	Each	202.40	545.40		
15	Supply and erection of round block of Sahl wood, 10x4 cm	Each	17.35	30.15	Each	17.35	30.15	38.1	
	$(4"x1\frac{1}{2}")$ thick.	Finn	antar (I)egari	nervenn t				
16	Supply and erection of teak wood board, 4.5 cm (1 ³ / ₄ ") thick.	200. (00.000)	PRODUCTING.	area da mara a	- SECULORATE IN-			38.1	
	i) 17.5 x 10 cm (7"x4")	Each	24.30	79.70	Each	24.30	79.70		
	ii) 22.5 x 10 cm (9"x4")	Each	24.30	91.70	Each	24.30	91.70		
	iii) 20 x 25 cm (8"x10")	Each	27.00	107.60	Each	27.00	107.60		
	iv) 25 x 30 cm (10"x12")	Each	30.35	147.15	Each	30.35	147.15		
	v) 30 x 35 cm (12"x14")	Each	34.70	200.70	Each	34.70	200.70		
17	Supply and erection of Sahl wood board, 4.5 cm (1 ³ / ₄ ") thick.								
	i) 17.5 x 10 cm (7"x4")	Each	24.30	59.90	Each	24.30	59.90		
	ii) 22.5 x 10 cm (9"x4")	Each	24.30	77.90	Each	24.30	77.90		
	iii) 20 x 25 cm (8"x10")	Each	27.00	92.00	Each	27.00	92.00		
	iv) 25 x 30 cm (10"x12")	Each	30.35	110.95	Each	30.35	110.95		
	v) 30 x 35 cm (12"x14")	Each	34.70	131.50	Each	34.70	131.50		
18	Supply and erection of iron/aluminum clad, 500 volts main							38.1	When the base frame is already
	switches with kitkat fuses, on angle iron board with 3 mm								installed, the labour and composite
	(1/8") thick M.S. sheet covering, including bonding to earth								rates will be reduced as follows:- For
	with necessary flexible pipe and thimbles, etc.								15 to 35 Amps. by Rs. 21.20 and Rs.
	a) double pole:								145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps.
	i) 15/20 Amp.	Each	404.80	1,425.45	Each	404.80	1,425.45		by Rs. 38.80 and Rs. 350.80.
	1 /			-, .20.10		. 5	-, .200		1

	MRS, BI-ANNUAL PERIOD (1st FEBRI	JARY, 20	13 TO 31s	st JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, K	HUSHAB
Sr.	Description	R	ate (British	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 30/35 Amp. iii) 60/65 Amp. iv) 100 Amp.	Each Each Each	404.80 607.20 607.20	1,707.45 2,220.05 2,760.05	Each Each Each	404.80 607.20 607.20	1,707.45 2,220.05 2,760.05		
	b) triple pole: i) 15/20 Amp. ii) 30/35 Amp.	Each Each	607.20 404.80	1,945.85 2,163.45	Each Each	607.20 404.80	1,945.85 2,163.45		
	c) triple pole with neutral link: i) 30/35 Amp. ii) 60/65 Amp. iii) 100 Amp.	Each Each Each	404.80 607.20 766.80	2,331.45 2,941.60 3,599.20	Each Each Each	404.80 607.20 766.80	2,331.45 2,941.60 3,599.20		
19	Supply and erection of iron/aluminum clad, 500 volts main switches with triple pole and neutral link and HRC fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles.	F						38.1	When the base frame is already installed, the labour & composite rates will be reduced as follows:- i) For 60/65 Amp. by Rs. 21.20 and
	60/65 Amp 100 Amp 150 Amp 200 Amp 300 Amp 400 Amp 500 Amp	Each Each Each Each Each Each	607.20 766.80 766.80 1,729.20 1,729.20 2,418.90 2,593.80	2,988.60 4,156.20 5,675.40 9,121.80 10,489.80 14,096.10 17,953.00	Each Each Each Each Each Each Each	607.20 766.80 766.80 1,729.20 1,729.20 2,418.90 2,593.80	2,988.60 4,156.20 5,675.40 9,121.80 10,489.80 14,096.10 17,953.00		Rs. 145.50. ii) For 100 to 300 Amp. by Rs. 21.20 and Rs. 350.80 iii) For 400 to 500 Amp. by Rs. 42.20 and Rs. 526.20
20	Supply and erection of iron/aluminum clad, branch distribution board, 250 volt, on angle iron frame of suitable size with 3 mm (1/8") M.S. sheet covering:							ditto	When the base frame is already installed the labour and composite rates will be reduced by Rs. 19.50 & Rs. 152.20 respectively.
	i) 2 way, 15 Amp per way ii) 3 way, 15 Amp per way iii) 4 way, 15 Amp per way iv) 5 way, 15 Amp per way v) 6 way, 15 Amp per way vi) 7 way, 15 Amp per way vii) 8 way, 15 Amp per way viii) 9 way, 15 Amp per way viii) 9 way, 15 Amp per way ix) 10 way, 15 Amp per way x) 11 way, 15 Amp per way xi) 12 way, 15 Amp per way xii) 2 way, 30 Amp per way xiii) 3 way, 30 Amp per way xiv) 4 way, 30 Amp per way xv) 5 way, 30 Amp per way xvi) 6 way, 30 Amp per way xvii) 7 way, 30 Amp per way	Each Each Each Each Each Each Each Each	202.40 202.40 202.40 202.40 202.40 202.40 202.40 202.40 202.40 303.60 303.60 303.60 303.60 303.60 303.60	597.80 597.80 669.80 729.80 771.80 825.80 873.80 927.80 1,005.80 1,119.80 699.00 705.00 831.00 873.00 939.00	Each Each Each Each Each Each Each Each	202.40 202.40 202.40 202.40 202.40 202.40 202.40 202.40 202.40 202.40 303.60 303.60 303.60 303.60 303.60	597.80 597.80 669.80 729.80 771.80 825.80 873.80 927.80 1,005.80 1,119.80 699.00 705.00 765.00 831.00 873.00 939.00		Rs. 152.20 respectively.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20 ⁻	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KI	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	rstem)	Spec.	Remarks
No.	•	Unit	Labour	Composite	Unit	Labour	Composite	No.	
				•					
	xviii; 8 way, 30 Amp per way xix) 9 way, 30 Amp per way	Each Each	303.60 303.60	993.00 1,041.00	Each Each	303.60 303.60	993.00 1,041.00		
	(xx) 9 way, 30 Amp per way (xx) 10 way, 30 Amp per way	Each	303.60	1,125.00	Each	303.60	1,125.00		
	any so may, so samp per may			-,			-,		
21	Supply and erection of bus bars, for 500 volts 3 phase A.C.							20.1	When the base frame is already
	supply with four copper bars, including glazed porcelain bridges, on angle iron board, fixed with rag bolts and M.S.							38.1	installed the labour and composite rates will be reduced by Rs. 21.20 and
	sheet box 1.5 mm thick, etc. complete:-								Rs. 145.50 respectively.
	i) 60 Amp. with 4 copper bars	Each	775.50	2,816.55	Each	775.50	2,816.55		
	size 1½"x1/8" (40 x 3 mm)	Lucii	773.30		Euch	773.30	2,010.33		
	ii) 100 Amp. with 4 copper bars	Each	775.50	2,816.55	Each	775.50	2,816.55		
	size 1½"x1/8" (40 x 3 mm) iii) 200 Amp with 4 copper bars	Each	1,201.20	3,338.25	Each	1,201.20	3,338.25		
	size 2"x1/8" (50x 3 mm)	11/	and the same of th		111				
	iv) 300 Amp with 4 copper bars	Each	1,389.30	3,526.35	Each	1,389.30	3,526.35		
	size 2"x3/16" (50x 5 mm) v) 500 Amp with 4 copper	Each	950.40	3,675.75	Each	950.40	3,675.75		
	size 2"x1/4" (50x 6 mm)	1897 J	12:3	- 16/	189		,		
22	Supply and erection of plain pendent lamp holder,	Each	14.60	104.00	Each	14.60	104.00	38.1	
	complete with bakelite lamp holder and flexible twin wire	Lucii		10 1100	Zuen	1.100	10.1.00	20.1	
	23/0.0076" upto 2 metre length (without bulb and shade).	- control (
	ii) Extra for additional length of flexible wire, beyond	Per Rft.	ance o	1.65	Per Metre		5.45		
	2 metres.								
23	Supply and erection of counter weight pedent with porcelain	Each	29.15	232.30	Each	29.15	232.30	38.1	
	counter weight, and fitting on bakelite lamp holder, with	Zuen	27.10	202.00	2	2,110	202.00	30.1	
	flexible twin wire 23/0.0076" complete (without bulb and								
	shade).								
24	Supply and erection of stiff pedent with brass/metal pipe 6.3	Each	40.05	380.85	Each	40.05	380.85	ditto	
	cm (2.5") long, and 15 mm (½") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm								
	(3/0.029").								
25	Supply and erection of 22.5 cm (9") long swan neck plain	Each	41.40	104.40	Each	41.40	104.40	ditto	
23	brass/steel brass oxidised bracket lamp holder, complete.	Lacii	41.40	104.40	Lacii	41.40	104.40	unto	
26	Supply and erection of wall type/pole type bracket, with double	Each	57.20	400.55	Each	57.20	409.55	ditto	
20	cover water tight reflector, flexible wire and brass bolder.	Eacn	37.20	409.55	Each	37.20	409.55	anto	
27	Supply and erection of bakelite button holder shade, large size.	Each	9.50	46.20	Each	9.50	46.20	ditto	
	3120.								
28	Supply and erection of call bell 220/250 volts, fixed on teak	Each	40.05	218.40	Each	40.05	218.40	38.1	
	wood board 17.5x10 cm (7"x4").								
			ı			l .	l		ı

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KI	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	8.75	205.35	Each	8.75	205.35	38.1	
30	Supply and erection of ceiling rose, bakelite.	Each	14.60	33.95	Each	14.60	33.95	ditto	
31	Supply and erection of switches 5 Amp.								
	i) open type ii) piano type iii) ring type, recessed iv) plate type, recessed v) double control, open type vi) double control, ring type recessed vii) double control, piano type	Each Each Each Each Each Each	14.00 14.00 14.00 14.00 18.75 18.75	30.95 30.95 26.00 47.75 46.95 40.95 42.15	Each Each Each Each Each Each Each	14.00 14.00 14.00 14.00 18.75 18.75	30.95 30.95 26.00 47.75 46.95 40.95 42.15	ditto	
32	Supply and erection of switches 10/15 Amp.	# E			1			ditto	
	i) open type ii) recessed type	Each Each	14.00 14.00	39.80 49.40	Each Each	14.00 14.00	39.80 49.40		
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	14.00	75.80	Each	14.00	75.80	ditto	
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	14.00	51.80	Each	14.00	51.80	ditto	
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.	Market St.	ance (IDEPART				ditto	
	i) open type ii) recessed type	Each Each	14.00 14.00	45.80 81.80	Each Each	14.00 14.00	45.80 81.80		
36	Supply and erection of 3 pin switch and plug combined, recessed type.							ditto	
	i) 5 Amp ii) 10/15 Amp	Each Each	14.00 14.00	65.60 90.50	Each Each	14.00 14.00	65.60 90.50		
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe, open type.	Each	14.00	141.80	Each	14.00	141.80	ditto	
38	Supply and erection of cut out, bakelite.							ditto	
	i) open type ii) recessed type	Each Each	7.75 7.75	33.55 39.55	Each Each	7.75 7.75	33.55 39.55		
39	Supply and erection of button holder.							38.1	
	i) bakelite large size ii) brass	Each Each	8.75 8.75	27.35 39.35	Each Each	8.75 8.75	27.35 39.35		
40	Supply and erection of brass bracket with holder.	Each	11.65	42.25	Each	11.65	42.25	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	7.75	27.55	Each	7.75	27.55	ditto			
42	Supply and erection of kitkat, 500 volt:							ditto			
43	i) 15/20 Amp ii) 30/35 Amp iii) 60/65 Amp iv) 100 Amp v) 200 Amp vi) 300 Amp vii) 400 Amp viii) 500 Amp Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete. i) double rod (80 watts) with two chokes and 2 starters.	Each Each Each Each Each Each Each Per set	13.75 15.00 22.90 25.80 29.45 29.45 38.00 38.00	45.25 46.50 67.90 112.80 152.45 308.45 383.00 554.00	Each Each Each Each Each Each Each Pach	13.75 15.00 22.90 25.80 29.45 29.45 38.00 38.00	45.25 46.50 67.90 112.80 152.45 308.45 383.00 554.00	38.1			
	ii) single rod (40 watts) with one choke and one starter.iii) round tube, 32 watt, with one choke and one starter, without cover.	ditto	190.10 190.10	616.35 672.75	ditto Each	190.10 190.10	616.35 672.75				
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	158.40	761.10	ditto	158.40	761.10				
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking arrangement, including painting:- i) 60x35x15 cm (24"x14"x6") ii) 95x40x20 cm (38"x16"x8") iii) 105x52.5x22.5 cm (42"x21"x9") iv) 135x70x27.5 cm (54"x28"x11")	Each Each Each Each	497.05 721.05 1,097.30 1,212.75	2,256.20 2,825.40 3,907.45 5,618.30	Each Each Each Each	497.05 721.05 1,097.30 1,212.75	2,256.20 2,825.40 3,907.45 5,618.30	ditto			
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate 25x6 mm (1"x ¹ /4"), with bolts and nuts for hanging ceiling fans.	Each	31.70	143.30	Each	31.70	143.30	38.1 & 38.10			
46	Supply and erection of girder strut, of M.S. tee section 40x40x6 mm (1½"1½"x ¼"), complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	40.05	857.85	Each	40.05	857.85	ditto			
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with 75x40x3 mm (3"x1½"x1/8") M.S. steel channel, with clamp, bolts and nuts, etc., including fixing with cement	Each	42.90	1,186.05	Each	42.90	1,186.05	38.1			

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 20 ⁻	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KH	IUSHAB
Sr.	Description	R	ate (British S	ystem)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	concrete 1:3:6.			•			•		
48	Supply and erection of roof suspension hook of M.S plate 75x40x12.7mm (3"x1½"x½") with 16 mm (5/8") hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Each	57.20	485.50	Each	57.20	485.50		
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	17.95	34.75	Each	17.95	34.75	ditto	
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	479.95	2,241.50	Each	479.95	2,241.50	38.12	
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x¼") section:-	* =			18.				
	i) 0.60 metre (2') long for 2 lines. ii) 1.200 metre (4') long for 4 lines.	Each Each	124.95 145.75	558.55 1,158.40	Each Each	124.95 145.75	558.55 1,158.40		
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.	Per Rft.	7.40	20.55	Per Metre	24.35	67.45	38.14	
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	10.60	31.95	Per Metre	34.70	104.85	ditto	
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line,include shackle insulator for holding insulated wire and straining devices for bearer wire and other accessories etc., complete.	Per Rft.	43.95	243.45	Per Metre	144.10	798.45		
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	43.25	241.25	Per Metre	141.90	791.25		
56	Supply and erection of lightning arrestor horn type, complete.	Each	240.25	2,400.25	Each	240.25	2,400.25		
57	Supply and erection of shackle insulator, medium size.	Each	33.00	195.00	Each	33.00	195.00	38.12	
58	Supply and erection of pin insulator, green medium size.	Each	33.00	81.00	Each	33.00	81.00	ditto	
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	17.15	1,040.75	Per Kg	17.15	1,040.75	38.1	
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire.	Per Kg	17.15	104.75	Per Kg	17.15	104.75	ditto	

	MRS, BI-ANNUAL PERIOD (1st FEBRI	JARY, 20	13 TO 31s	st JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, K	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
61	pole to pole etc. Wiring overhead line in 2 single core, PVC/weather proof							38.12	
	cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.							30.12	
	i) 3/0.74 mm (3/0.029") ii) 7/0.74 mm (7/0.029")	Per Rft.	4.05 4.05	11.55 19.70	Per Metre ditto	13.35 13.35	37.90 64.55		
	iii) 7/0.91 mm (7/0.036") iv) 7/1.12 mm (7/0.044")	ditto ditto	4.05 4.05	26.15 35.00	ditto ditto	13.35 13.35	85.70 114.80		
62	Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft.	8.20	21.10	Per Metre	26.90	69.25	38.1	
63	Supply and erection of street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp.	Each	200.20	940.10	Each	200.20	940.10		
64	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):	1	64	- , , fer					
	i) G.E.C. design ii) Philips design	Each ditto	400.40 400.40	2,752.40 3,124.40	Each ditto	400.40 400.40	2,752.40 3,124.40		
65	Supply and fitting of mercury vapour lamp, complete with choke set.	T_{mn}	am.ce (Depart	maem t	1.50 (0			
	i) 125 watt lamp ii) 250 watt lamp	Each ditto	158.40 190.10	1,058.40 1,930.10	Each ditto	158.40 190.10	1,058.40 1,930.10		
66	Manufacture and erection of angle iron lattice steel structure pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1½"x1½"x3/16" (30x30x5 mm) angle iron legs and ¾"x¾"1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1¾"x1¾"x3/16"(45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x½" (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.	Each	6,910.10	22,871.50	Each	6,910.10	22,871.50	38.13	The composite rate will be reduced or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per	Each	6,467.40	34,569.65	Each	6,467.40	34,569.65	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.

	MRS, BI-ANNUAL PERIOD (1st FEBRU	ARY, 201	13 TO 31s	t JULY, 201	3) TEH: N	OWSHER	A, SOAN V	ALLEY, KI	HUSHAB
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3½'x3½' (2400x1050x1050 mm), etc. complete in all respects.								
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (½") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	851.40	3,661.00	Job	851.40	3,661.00		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in 15 mm (½") dia G.I. pipe, best quality:- i) on surface, including clamps, etc. ii) recessed in wall, including hooks,	Per Rft.	9.15 20.75	53.25 65.80	Per Metre	30.05 68.10	174.70 215.80	38.11	
70	jharries and making good surface. Bonding to earth with wire on surface, including cost of wire, clamps, thimbles, etc.	# E			7			ditto	
	a) G.I. wire: i) 8 SWG ii) 16 SWG	Per Rft.	4.25 4.25	9.85 5.85	Per Metre	14.00 14.00	32.35 19.15		
	b) Copper wire:	Final	anice (I)epart		14.00	17.13		
	i) 16 SWG ii) 20 SWG	Per Rft. ditto	4.25 4.25	11.35 7.00	Per Metre ditto	14.00 14.00	37.15 22.90		
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	14.65	19.10	Per Metre	48.05	62.60	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	567.60	4,334.75	Each	567.60	4,334.75	ditto	
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.								
	i) tape 40x3 mm (1½"x1/8") ii) tape 50x3 mm (2"x1/8")	Per Rft. ditto	20.75 20.75	255.20 304.10	Per Metre ditto	68.10 68.10	837.10 997.45		
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	400.40	2,668.40	Job	400.40	2,668.40		
75	Supply and erection of electric energy meter, including meter testing fee, etc.							38.1	

	MRS, BI-ANNUAL PERIOD (1st FEBR	A, SOAN VA	LLEY, K	HUSHAB					
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) single phase:								
	i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts	Each ditto	174.90 174.90	2,253.30 2,253.30	Each ditto	174.90 174.90	2,253.30 2,253.30		
	b) three phase, 4 wires:								
	i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts	Each ditto ditto	349.80 475.20 475.20	5,946.60 6,072.00 6,072.00	Each ditto ditto	349.80 475.20 475.20	5,946.60 6,072.00 6,072.00		
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.	1)				The credit of out turn of dismantled material has been accounted for in the rate.
	i) 1200 mm (48") sweep, 275-300 RPM.ii) 1400 mm (56") sweep, 250-275 RPM.	Each ditto	325.05 356.40	925.05 1,059.00	Each ditto	325.05 356.40	925.05 1,059.00		
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.		15.	(عادت					The credit of out turn of dismantled material has been accounted for in the rate.
	i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM	Each ditto	233.20 233.20	649.60 728.20	Each ditto	233.20 233.20	649.60 728.20		
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	279.85	846.85	Each	279.85	846.85		The credit of out turn of dismantled material has been accounted for in the rate.
79	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	43.75	103.75	Each	43.75	103.75	38.1	inc rac.
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	35.00	59.00	Each	35.00	59.00	ditto	
81	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	43.75	163.75	Each	43.75	163.75	ditto	
82	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	87.45	197.85	Each	87.45	197.85		The credit out turn of dismantled material has been accounted for in
83	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	153.55	190.60	Each	153.55	190.60		the rate.

25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEBRU	B) TEH: N	OWSHE	RA, SOAN V	ALLEY,	KHUSHAB			
Sr.	Description	R	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Railway Track, etc.								
1	Laying, linking and packing tramway line.	100Lft.	1296.60		Metre	42.55			
2	Dismantling tramway track.	100Lft.	431.65		Metre	14.15			
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	3363.80		Metre	110.35			
4	Linking points and crossings, complete with fastenings.	Each	3272.30		Each	3272.30			
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	390.70	- 1.50 - 1.50 - 1.50	Each Point	390.70			
6	Fixing street lamp posts.	Each	426.35	0	Each	426.35			
7	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	4189.70	Depart	100 Nos	4189.70			
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	502.30		100 Nos	502.30			
	IRON WORK								
9	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	2303.40	7729.60	100 Kg	4534.25	15215.75		
10	Fabrication of heavy steel work, with angle, tees, flat iror round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling assembling and fixing, but excluding erection in position	Per Cwt	813.10	5972.90	100 Kg	1600.65	11757.65		
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	266.95		100 Kg	525.45			
12	Fixing corrugated iron sheet, including revitting, etc	100 Sft.	960.95		sq.m	103.40			
13	Erecting corrugated iron sheet tanks, upto 20 (6 m) height.	Per Cwt	432.60		100 Kg	851.55			

	MRS, BI-ANNUAL PERIOD (1st FEBR	JARY, 20	13 TO 31s	st JULY, 2013	B) TEH: N	NOWSHE	RA, SOAN V	ALLEY,	KHUSHAB
Sr.	Description	Ra	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
14	Erecting rolled steel beams or old rails, in roofs, etc. erection and fixing in position.	Per Cwt	254.10		100 Kg	500.20			
15	Erecting rolled steel beams or rails, erection for posts etc (other than in roofs).	Per Cwt	124.50		100 Kg	245.10			
16	Making bolts and nuts of iron rods.	Per Cwt	1811.70	7848.80	100 Kg	3566.35	15450.40		
17	Cutting rails, rolled steel joists and beams, with hacksaw:-	,	/ ×	()					
	a) upto 6" size (150 mm) b) above 6" size (150 mm)	Per Cut Per Cut	180.20 268.20		Per Cut Per Cut	180.20 268.20			
18	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	85.80		Per Cwt Cut	85.80			
19	Bending rolled steel beams or rails.	Per Bend	91.10	343.00	Per Bend	91.10	343.00		
20	Drilling holes, in plates upto ½" (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	33.85	t Wanasa matik	Per Hole	33.85			
21	Extra for drilling holes in plates over ½" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	18.20	montanes e	Per Hole	18.20			
22	Rivetting 1/8" dia (3 mm).	100 Nos	423.50		100 Nos	423.50			
23	Cutting out Rivets, all sizes.	100 Nos	1518.00		100 Nos	1518.00			
24	Fitting and erection of gutters of sheet iron.	Per Lft.	55.80		Metre	182.95			
25	Cutting and fixing iron bars, for barred windows.	Per bar	34.30		Per bar	34.30			
26	Cutting G.I. sheets.	Each Cut	18.70		Each Cut	18.70			
27	Notching web or foot of rail posts, for housing rail beams.	Per Notch	404.80	572.80	Per Notch	404.80	572.80		
28	Hoop iron netted trellis work fixed with nails.	Per Sft.	24.00		sq.m	258.50			
29	Fixing zinc iron or G.I. sheet on table tops	Per Sft.	14.15		sq.m	152.05			
30	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	140.95	700.55	sq.m	1516.70	7538.15		
31	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and 3/4" (20 mm) square bars 4" (100 mm)	Per Sft.	147.20	826.90	sq.m	1583.90	8897.20		

	MRS, BI-ANNUAL PERIOD (1st FEBI	RUARY, 20	13 TO 31	st JULY, 2013	B) TEH: N	NOWSHE	RA, SOAN V	ALLEY,	KHUSHAB
Sr.	Description	R	ate (British S	System)	Ra	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	centre to centre, with locking arrangement.								
32	Making and fixing grating in opening, including fixing at site with flat iron 2"x3/8" (50x10 mm) and ¾" (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	56.75	343.75	sq.m	610.75	3698.90		
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed tc 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete	Per Rft.	304.75	791.10	Metre	999.90	2595.45		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8' punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	162.80	546.05	Metre	534.10	1791.45		
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	117.70	576.25	Metre	386.15	1890.58		-do-
		Print.	MILL CE	THE PHONE		5			
36	Providing and fixing collapsible gate made of 2"x2"x" ¹ /4" (50x50x6 mm) tee iron at top and bottom, channel iron verticals ³ / ₄ "x ¹ / ₄ "x ¹ / ₈ " (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts. handles 12" (300 mm) long of ³ / ₄ "x ¹ / ₄ "x ¹ / ₄ "x ¹ / ₄ "x ¹ / ₈ " (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	196.25	621.85	sq.m	2111.50	6691.30		
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1½"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	46.85	222.65	sq.m	504.00	2395.60		
38	Providing and fixing M.S. angle iron 1½"x1½"x¼" (40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.	Per Rft.	24.70	142.10	Metre	81.00	466.25		

	MRS, BI-ANNUAL PERIOD (1st FEBRI	ALLEY,	KHUSHAB						
Sr.	Description	Ra	ate (British S	System)	Ra	te (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Providing and fixing stair railing of 2½" (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.	Per Rft.	130.65	649.95	Metre	428.55	2132.35		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square
40	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	23.30	61.45	sq.m	250.90	661.05		bars.
41	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1½"x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ¾"x1"x¾"x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the Engineer-in-charge:-				7				For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	a) without wire gauze: i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iii) glass pane 4 mm thick v) glass pane 5 mm thick b) fixed with wire gauze, 22 SWG	Per Sft. ditto ditto ditto ditto	60.30 60.30 60.30 60.30	305.35 310.15 317.35 324.55 329.35	sq.m ditto ditto ditto ditto	648.75 648.75 648.75 648.75	3285.40 3337.05 3414.55 3492.00 3543.65		
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick 	Per Sft. ditto ditto ditto ditto	84.70 84.70 84.70 84.70 84.70	363.20 368.00 375.20 382.40 387.20	sq.m ditto ditto ditto ditto	911.20 911.20 911.20 911.20 911.20	3908.00 3959.65 4037.10 4114.60 4166.25		
42	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1½"x1½" (30x30mm) for leaves including M.S. square bars ½"x½" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG) beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects.								
	 a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass panes 1/4" (6 mm) thick. b) For fixed panels without wire gauze. 	Per Sft.	56.75 55.00	299.55 182.40	Sq.m ditto	610.40 591.60	3223.15 1962.70		

	MRS, BI-ANNUAL PERIOD (1st FEBR	UARY, 20 ⁻	13 TO 31s	t JULY, 2013	B) TEH: N	OWSHE	RA, SOAN V	ALLEY,	KHUSHAB
Sr.	_	Ra	ate (British S	ystem)	Ra	nte (Metric S	System)	Spec. Remarks No.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite		
43	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	60.30	372.75	Sq.m	649.00	4010.95		
44	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	74.80	433.35	Per Sft.	804.60	4663.10		
45	Flapping G.I. pipes for bath room drains.	Each	524.70	563.10	Each	524.70	563.10		
46	Supply and fixing iron grating for fire place.	Per Sft.	95.05	197.05	sq.m	1022.65	2120.15		
47	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	40.05		Metre	131.35			
48	Providing and fixing angle iron railing, using 2½"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x½" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long ¾" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	62.65	783.65	Metre	205.55	2571.10		
	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5 mm), angle iron post 3½ ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" (225x225x300 mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	1449.55	9734.40		47.55	319.35		
50	Providing and fixing barbed wire fencing on compound	100Rft.	2425.95	12437.80	Metre	79.60	408.05		

	MRS, BI-ANNUAL PERIOD (1st FEE	KHUSHAB							
Sr. No.	Description	R	Rate (British System)			ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
51	wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects. Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s Al-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	68.65	482.95	sq. m	738.65	5196.55		(1) Increase rate by Rs. 40.00 per Sft or Rs.430.50 per Sq-metre if sections thickness is 2 mm. (2) Reduce rate by Rs.20.00 per Sf or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade. (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used.
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan Cables having frame size of 100 x 20 mm (4"x¾") and leaf frame sections of 50 x 20 mm (2"x¾"), all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Sft	97.85	373.70	sq. m	1052.85	4021.00		(1) Reduce rate by Rs.20.00 per Sf or Rs.215.20 per Sq-metre if section thickness is 1.2 mm. (2) Reduce rate by Rs.20.00 per Sf or Rs.215.20 per Sq-metre if sections are of dull aluminium shade. (3) Reduce rate by Rs.20.00 per Sf or Rs.215.20 per sq-metre if local

26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PERIOD (1st FEB	RUARY,	2013 TO 31s	st JULY, 201	3) TEH: N	OWSHER	A, SOAN VA	LLEY, I	KHUSHAB
Sr.	Description		Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	51.30	60.40	Per sq.m	552.15	649.65		The board is to be of cement plaster ½" (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.
2	Fixing handles to iron hammers.	Each	72.90		Each	72.90	-		beauing.
3	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete.	100Lft.	5,199.15	22,900.00	L.m.	170.60	751.30		Vertical bars in straining and stiffening posts to be 4 No. each by ½" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be ½" (6 mm) dia. at 12" (300 mm) centre to centre.
	<u>Surveying</u>	4		100	33.				
4	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	37.20	163.20	Each	37.20	163.20		
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	116.60	133.75	100Nos.	116.60	133.75		
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	279.85	477.85	100Nos.	279.85	477.85		
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	60.05	68.70	Per L.M.	197.05	225.40		
8	Placing boundary pillars in position, including digging pits.	Each	40.05	-	Each	40.05	-		
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	170.30	328.60	Each	170.30	328.60		Composite rate does not include cost of iron distance marks.
	Hand Pumps & Pressure Pipes								
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	40.05	-	Per cut	40.05	-		

	MRS, BI-ANNUAL PERIOD (1st FEBI	3) TEH: NO	B) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB						
Sr.	Description		Rate (British System)		Rat	te (Metric S	ystem)	Spec. Remai	rks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	74.05	0	Per cut	74.05	0		
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	51.70	-	Each End	51.70	-		
13	Assembling 1½" (40 mm) dia pressure pipe.	100Lft.	181.50	-	Per Metre	5.95	-		
14	Boring and fixing 11/2" (40 mm) dia pressure pipe:								
	a) in ordinary soil	Per Lft.	61.40		Per Metre	201.40	-		
	b) in clay c) in shingle	Per Lft. Per Lft.	117.80 174.24	') \	Per Metre Per Metre	386.50 571.65	-		
	c) in sinigle	T CI LIL.	174.24		1 CI WICHC	371.03	_		
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	27.05		Per Metre	88.80	-		
16	Fixing hand pump (Machine only)	Each	139.90		Each	139.90	-		
	Rest House Furniture & Fuel, etc.	SEN.	1						
17	Washing Niwar of bed.	Per bed	376.20	406.45	Per bed	376.20	406.45		
18	Washing Durries.	100Sft.	501.60	573.60	sq.m	54.00	61.75		
19	Recaning chairs:	9	mance	Depart	musin t				
	i) office chairs, single caning seat only.	Each	244.85	279.55	Each	244.85	279.55		
	ii) office chairs, double canning seat only.	Each	314.80	363.80	Each	314.80	363.80		
	iii) office chairs, single caning back only.	Each	174.90	177.10	Each	174.90	177.10		
	iv) office chairs, double caning back only.	Each	279.85	298.60	Each	279.85	298.60		
	v) easy chairs, single caning seat only.	Each	174.90	221.40	Each	174.90	221.40		
	vi) easy chairs, double caning seat only.	Each	489.70	559.10	Each	489.70	559.10		
	vii) easy chairs, single caning only, back and seat in one	Each	699.60	985.20	Each	699.60	985.20		
	piece. viii) easy chairs, double caning back & seat in one piece or couches with caned area about 16 Sft (1.5 Sqm).	Each	1,049.40	1,743.00	Each	1,049.40	1,743.00		
20	Making and fixing Hat pegs ordinary.	Each	125.95	468.40	Each	125.95	468.40		
21	Weaving charpoy.	Each	334.60	-	Each	334.60	-		
22	Sweeping chimney.	Each	83.60	84.90	Each	83.60	84.90		
23	Picture railing, including making, fixing and painting.	Per Lft.	36.05	106.90	Per LM	118.20	350.75		
24	Cutting fuel wood, from plantation.	100Kg	111.95	-	100Kg	111.95	-		
25	Splitting fuel wood.	100Kg	234.50	-	100Kg	234.50	-		

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description		Rate (British Sy	ystem)	Rat	te (Metric S	ystem)	Spec. Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	371.05	-	100Kg of Char- coal	371.05	-				
27	Filling cement bags with coal and sewing (including cos of strings).	100Cft.	1,028.30	1,031.40	cu.m	363.20	364.30				
28	Supplying manure.	Cart Load	125.40	257.40	Cart Load	125.40	257.40	Capacity of cart, 20 Cft. (0.57 cu.m).			
29	Washing punkha frills.	Each	102.95	-	Each	102.95	-				
30	Washing:-		/ >	()							
	a) table cloth b) napkins, dusters, etc.	Each Each	25.75 17.15		Each Each	25.75 17.15	- -				
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	46.35		Each No.	46.35	-				
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	50.35	(جارت	Each No.	50.35	-				
33	Dredging Sumps.	Per Shift	1,881.00	S 4.1	Per Shift	1,881.00	-	Not less than five gangmen to be employed for each shift to ensure effective dredging.			
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each	158.40	Lucpart	Each	158.40	-				
35	Bailing out water:-										
	a) by hand b) by pump	1000 Cft. 1000 Cft.	1,504.80 187.70	335.15	cu.m ditto	53.15 6.65	11.85	Rate includes cost of providing pump, POL and operation charges, etc.			
36	Drilling holes in R.C. Trough	Per Nos.	100.10	-	Per Nos.	100.10	-				
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.							The rate includes overlaps.			
	i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick)	Per Sft. Per Sft.	0.75 1.55	2.30 2.85	sq.m sq.m	8.30 16.60	24.95 30.55				
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100Sft.	1,053.20	6,725.80	sq.m	113.35	723.70				
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	171.60	-	Per Hole	171.60	-	Same rate to be paid for other type of masonry and R.C.C. work.			

	MRS, BI-ANNUAL PERIOD (1st FEBRUARY, 2013 TO 31st JULY, 2013) TEH: NOWSHERA, SOAN VALLEY, KHUSHAB										
Sr.	Description	Rate (British System)			Rat	e (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
40	Making 1½"x1½" (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	150.15	-	Per Plank	150.15	-				
41	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	50.15		Per hole per c.m depth	20.05					
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	69.95	208.30	sq.m of each spray	7.55	22.40				
43	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.	-300									
	 i) without cement concrete base. ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm). 	100Rft. 100Rft.	6,071.20 6,656.20	22,655.60 24,685.70	Per Metre Per Metre	199.15 218.30	743.10 809.70				