Market Rates System (MRS)

Bí-annual Períod

(1st August, 2012 to 31st January, 2013)

Government of the Punjab

Fínance Department

haroon_01@hotmail.com

TABLE OF CONTENTS

Sr No.	Chapter	Pa	ge N	<i>los</i>
01.	Carriage	03	to	22
02.	Loading, Unloading & Stacking	23	to	25
03.	Earthwork (Excavation & Embankment)	26	to	32
04.	Dismentling (Demolition)	33	to	37
05.	Mortar	38	to	39
06.	Concrete	40	to	50
07.	Brickwork	51	to	56
08.	Stone Masonary	57	to	59
09.	Roofing	60	to	65
10.	Flooring	66	to	71
11.	Surface Rendering	72	to	76
12.	Wood Work	77	to	87
13.	Painting & Varnishing	88	to	94
14.	Lining of Canals	<i>95</i>	to	96
15.	Sheet Piling	97	to	<i>98</i>
16.	Protection & Diversion Work	99	to	109
17.	Outlets	110	to	112
18.	Road & Road Structure	113	to	117
19.	Plumbing, Sanitary Installation & Gas Fittings	118	to	124
20.	Surface Drainage	125	to	126
21.	Sewerage	127	to	131
22.	Sinking of Wells	132	to	134
23.	Tubewell & Water Supply	135	to	147
24.	Electric Installation	148	to	161
	Iron Work	162	to	167
26.	Miscellaneous	168	to	171

1. CARRIAGE

	1. CARAGE											
Note:		The rates are applicable to carriage of material on pacca roads only. For kacha roads an allowance of 25% extra shall be allowed for 2nd and subsequent mileage (Km) rates. Rate upto 1st mile (1st Km) is however common to both kacha and pacca roads.										
Note:	2	For hilly areas 25% above the rates in the plain areas shall be allow	ved for total mile	eage (Km) cover	red.							
Note:	3	In case of articles longer than 15 ft. (4.6 m) carried in trucks, the for	llowing rates sh	all be allowed:-								
		i) Above 15 ft. to 25 ft. (4.6 to 7.6 m) :- Total rates to be paid for rate given in the Composite Schedule of Rates.	15 ft. to 25 ft. (4	4.6 to 7.6 m) len	ngth will be 1.5 ti	mes of the						
		ii) Above 25 ft. (7.6 m) :- The total rate to be paid for above 25 ft. (7.6 m) length will be 2 times of the rate given in the Composite Schedule of Rates.										
		The length measured shall not be the actual length, but the length of the form of consignment as actually received.										
Note:	4	The term 'mile' (Km) whenever used is to mean statute mile (Km).		1	()							
Note:	5	The rates include loading and unloading of material from the conve	eyance and stack	ting as directed.		1.						
Note:	6	The rates for carriage by boat or steamer shall be the same as by an	v other mechani	ical means on la	nd	JUN.						
	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
-			33	K		1 - 24%			_			
Sr. No.		Description	100	State The	- 10	Rate Unit of	e (Metric Sy	stem)	Spec. No.	Remarks		
110.			10		Consultant les	M/ment	Labour	Composite	110.			
1 (Carri	iage of 100 Cft. (2.83 cu.m) of all materials like stone		00	00				16.1			
		egate, spawl, kankar lime (unslaked), surkhi, etc. or	100000		-1277.	a						
		Cft. (4.25 cu.m) of timber, by truck or by any other	12:12		ELMS CHORNER	State and the						
r	mear	ns owned by the contractor.			17							
		1st chain (1st 30 m)				30M	94.90					
		2nd chain (2nd 30 m)				30M	17.45					
		3rd to 10th chain (60 to 300 m)				30M	10.85					
		1000 to 3000 ft. (300 to 900 m)				300 Metre	106.75					
		1st Km				Km	157.59					
		2nd Km				Km	74.11					
		3rd Km				Km	56.45					
		4th Km				Km	39.07					
		5th Km				Km	36.16					
		6th Km				Km	35.51					
		7th Km				Km	32.92					
		8th Km				Km Km	32.54					
		9th Km 10th Km				Km Km	30.42 28.21					
		10th Km 11th Kms to 200Kms				Km Km	28.21 20.56					
2 1						KIII	2.00		16.1	Cement carried in containers other		
									10.1	than bags will be paid according to		
										this item. The word "pipes" covers		
(Carri (unsl	201 Kms to 250 Kms 251 Kms & susequent Kms iage of 5 tons of all material like coal, stone lime laked), etc. B.G. Rail fastenings, points and crossing, ge Girders, pipes, sheets, Rail, M.S. bars, etc. etc.				Km Km	3.25		16.1	than bags will be paid acc		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks	
No.	2 compron				Unit of M/ment	Labour	Composite	No.		
	by truck or any other means owned by the contractor.				wi/ment	Labour	Composite		G.I,C.I,R.C.C. and P.C.C.	
	1st chain (1st 30 m)				30M	94.90				
	2nd chain (2nd 30 m)				30M 30M	94.90 17.45				
	3rd to 10th chain (60 to 300 m)				30M	10.85				
	1000 to 3000 ft. (300 to 900 m)				300M	106.75				
	1st Km				Km	157.59				
	2nd Km				Km	74.11				
	3rd Km				Km Km	56.45				
	4th Km				Km	39.07				
	5th Km				Km	36.16				
	6th Km		-AD - PART		Km	35.51				
	7th Km		1 3	\sim	Km	32.92				
	8th Km	/	· · ·	1	Km	32.54				
	9th Km	de la	100		Km	30.42				
	10th Km	- 18 E			Km	28.21				
	11th Kms to 200Kms	3867			Km	20.56				
	201 Kms to 250 Kms 251 Kms & susequent Kms	1839	No.	6 /	Km Km	3.25 2.00				
3	Carriage of 100 maunds of fuel wood by truck	100			KIII	2.00		16.1		
5	or any other means owned by the contractor:	1000		6	and a second			10.1		
	1st chain (1st 30 m)		50	0-2	30 M	94.90				
	2nd chain (2nd 30 m)	ALC: 1		- 1777 A.	30 M	17.45				
	3rd to 10th chain (60 to 300 m)	(Film	16811162	Dine the second	30 M	10.85				
	1000 to 3000 ft. (300 to 900 m)				300 M	106.75				
	1st Km				Km	157.59				
	2nd Km				Km	74.11				
	3rd Km 4th Km				Km Km	56.45 39.07				
	401 Kili				KIII	39.07				
	5th Km				Km	36.16				
	6th Km				Km	35.51				
	7th Km				Km	32.92				
	8th Km				Km	32.54				
	9th Km				Km	30.42				
	10th Km				Km	28.21				
					IZ.	20.55				
4	11th & subsequent Kms Carriage of 1000 Nos. bricks 10"x5"x3" (250x125x75 mm)				Km	20.56		ditto	Reduce the rate by 33% in case of	
+	or 1000 Nos. tiles 12"x6"x2" (300x150x50 mm) by truck or							unto	carriage of 1000 Nos. tiles size	
	any other means owned by the contractor :-								12"x6"x1'4" (300 x 150 x 30 mm).	

	MRS, BI-ANNUAL	PERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY	, 2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	1st chain (1st 30 m)				30 M	94.90	•		
	2nd chain (2nd 30 m)				30 M	17.45			
	3rd to 10th chain (60 to 300 m)				30 M	10.85			
	1000 to 3000 ft. (300 to 900 m)				300 M	106.75			
	1st Km				Km	157.59			
	2nd Km				Km	74.11			
	3rd Km				Km	56.45			
	4th Km				Km	39.07			
	5th Km				Km	36.16			
	6th Km				Km	35.51			
	7th Km				Km	32.92			
	8th Km			\sim	Km	32.54			
	9th Km	-1.1			Km	30.42			
	10th Km	8	0011		Km	28.21			
	11th & subsequent Kms	Ster L			Km	20.56			
5	Carriage of 100 cft. (2.83 cu.m) of all material like stone,	1,639	No.	. 50 /	ixin	20.50		16.1	Material trolly to be supplied by the
5	aggregate, spawl, kankar lime(unslaked), surkhi, etc. or	No.							Government and maintained and run
	150 cft. (4.25 cu.m) of timber, by means of material trolly	1		5/1	53-				by the contractor.
	1st chain (1st 30 m)			2.5-	30 M	94.90			
	2nd chain to 10th chain (2nd 30 m to 300 m)			-	30 M	17.45			
	1000 to 3000 ft. (300 to 900 m)	(Fi	951.6779831.07.983	ชีสีในเหลือเกณะจ	300 M	106.75			
	1st Km	181-16	AN BRANKING PROCESSION	arua lasses i	Km	129.25			
	2nd Km				Km	98.22			
	3rd Km 4th Km				Km Km	51.99			
						40.50			
	5th Km				Km	35.54			
	6th Km				Km	34.12			
	7th Km				Km	28.76			
	8th Km				Km	28.43			
	9th Km				Km	26.56			
	10th Km				Km	24.62			
	11th Kms to 200Kms				Km	19.66			
	201 Kms to 250 Kms				Km	3.25			
	251 Kms & susequent Kms				Km	2.00			
6	Carriage of 5 tons of all material like coal, stone lime							16.1	Material trolly to be supplied by the
	(unslaked), etc. B.G. Rail fastening, points and crossing,								Government and maintained and run
	Bridge girders, pipes, sheets, Rail, M.S. bars, etc. etc. by								by the contractor.
	means of material trolly.				20.14	01.00			
	1st chain (1st 30 m)				30 M	94.90			
	2nd chain (2nd 30 m) 1000 to 3000 ft. (300 to 900 m)				30 M 300 M	17.45 106.75			
	1500 10 5000 ft. (500 10 900 ft) 1st Km				S00 M Km	129.25			
	2nd Km				Km	98.22			
	2nd Km				Km	98.22			<u> </u>

	MRS, BI-ANNUAL F	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	, 2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	3rd Km				Km	51.99	•		
	4th Km				Km	40.50			
	5th Km				Km	35.54			
	6th Km				Km	34.12			
	7th Km				Km	28.76			
	8th Km				Km	28.43			
	9th Km 10th Km				Km Km	26.56 24.62			
	11th Kms to 200Kms				Km	19.66			
	201 Kms to 250 Kms				Km	3.25			
_	251 Kms & susequent Kms				Km	2.00			
7	Carriage of 100 maunds of fuel wood, by means of material trolly.							ditto	Material trolly to be supplied by the Government and
	1st chain (1st 30 m)				30 M	94.90			maintained and run by the
	2nd chain (2nd 30 m)		1		30 M	17.45			contractor.
	1000 to 3000 ft. (300 to 900 m) 1st Km		/ ~	1	300 M Km	106.75 129.25			
	2nd Km				Km	98.22			
	3rd Km				Km	51.99			
	4th Km	8			Km	40.50			
	5th Km	S.	For	6	Km	35.54			
	6th Km	1			Km	34.12			
	7th Km		- SA	200	Km	28.76			
	8th Km	(Fi		Deport	Km	28.43			
	9th Km				Km	26.56			
	10th Km				Km	24.62			
8	11th & subsequent Kms Carriage of 1000 Nos. tiles 12"x6"x2" (300x150x50 mm),				Km	19.66		ditto	Material trolly to be supplied by the
Ű	by means of material trolly.							unto	Government and maintained and run
	1st chain (1st 30 m)				30 M	94.90			by the contractor.
	2nd chain (2nd 30 m)				30 M	17.45			
	1000 to 3000 ft. (300 to 900 m)				300 M	106.75			
	1st Km 2nd Km				Km Km	129.25 98.22		16.1	
	3rd Km				Km	51.99		10.1	
	4th Km				Km	40.50			
	5th Km				Km	35.54			
	6th Km				Km	34.12			
	7th Km				Km	28.76			
	8th.				Km	28.43			

	MRS, BI-ANNUAL P	012 TO 31st	st JANUARY, 2013) DISTRICT JHANG						
Sr.	Description				Rate	e (Metric Sy	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
					M/ment	Labour	Composite		
	9th Km				Km	26.56			
	10th Km				Km	24.62			
	11th & subsequent Kms				Km	19.66			
9	Carriage of 1000 No. bricks, 9"x41/2"x3"							ditto	
	(225x113x75 mm) or 8"x4"x4" (200x100x100 mm) (nominal)								
	1st chain (1st 30 m)				30 M	77.76			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	16.00 8.91			
	1000 to 3000 ft. (300 to 900 m)				300 M	87.40			
	1st Km				Km	129.19			
	2nd Km		× ×		Km	60.63			
	3rd Km 4th Km		/ .		Km Km	46.25 32.24			
					1.				
	5th Km	1	510 mg/m		Km	30.53			
	6th Km		-		Km	29.81			
	7th Km	E.	1.5	/عبرت	Km	26.97			
	8th Km	10			Km	26.66			
	9th Km	201717-0	0	-570	Km	24.92			
	10th Km	(Fi	telestin (18	Discheral	Km	23.11			
10	11th & subsequent Kms Carriage of 1000 No. tiles 9"x4½"x1½"				Km	16.75		16.1	
10	(225x113x38 mm).							10.1	
	1st chain (1st 30 m)				30 M	46.93			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	8.62 5.32		16.1	
	1000 to 3000 ft. (300 to 900 m)				300 M	52.80			
	1st Km				Km	77.99			
	2nd Km				Km	36.68			
	3rd Km 4th Km				Km Km	27.94 19.30			
	5th Km				Km	17.76			
	6th Km				Km	17.47			
	7th Km				Km	16.28			
	8th Km				Km	16.09			
	9th Km				Km	15.03			

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks	
No.					Unit of M/ment	Labour	Composite	No.		
	10th Km				Km	14.00	composite			
11	11th & subsequent Kms Carriage of 1 Cwt. (50 Kg) cement in bags.				Km	10.15		ditto		
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M 30 M	1.79 0.21 0.10				
	1000 to 3000 ft. (300 to 900 m)				300 M	1.05				
	1st Km				Km	1.96				
	2nd Km				Km	1.34				
	3rd Km		A STATE		Km	0.57				
12	4th Km and subsequent kilometers. Carriage of 100 Nos. empty cement bags including				Km	0.34		16.1		
	bundling. 1st 1000 (300 m) ft. 1000 to 3000 (300 to 900 m) ft.	100-	2-91a		300 M 300 M	26.19 3.26				
	1st Km				Km	4.75				
	2nd Km		n - Sel	R. P	Km	4.82				
	3rd Km	(Fi	niamicis -	Dennari	Km	2.23				
13	4th Km & subsequent Kms Carriage of 100 (2.83 cu.m) cft. of Sarkanda or pilchi, frash or brushwood, by boat or road :-			19	Km	1.97		ditto	Previous lead of collection not to be deducted from the next lead of carriage.	
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	38.83 17.45				
	3rd to 10th chain (60 to 300 m)				30 M	5.32				
	1000 to 3000 ft. (300 to 900 m)				300 M	43.86				
	1st Km				Km	71.99				
	2nd Km				Km	36.68				
	3rd Km				Km	27.94				
	4th Km				Km	19.30				
	5th Km				Km	17.76				

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks	
No.					Unit of M/ment	Labour	Composite	No.		
	6th Km				Km	17.47	Composite			
	7th Km				Km	16.28				
	8th Km 9th Km 10th Km				Km Km Km	16.09 15.03 14.00				
	11th Km & subsequent				Km	10.15				
	Carriage of light machinery weighing upto 3 tonne upto 1000 ft. (300 metre) Execceeding 1000 to 5000 ft (300 to 1500metre)				Tonne 300 M	317.30 76.88		ditto		
	1st Km				Km	155.04				
	2nd Km)	Km	72.28				
	3rd Km	.1.1			Km	48.95				
	4th Km	18			Km	31.67				
	5th Km	5	F	5	Km	29.86				
	6th Km				Km	28.67				
	7th Km			S.S.	Km	24.84				
	8th Km 9th Km	Pi	riam car	Derpart	Km Km	24.47 23.91				
	10th Km 11th Km & susequent				Km Km	18.91 15.44				
15	Carriage of small consignments weighing upto 5 maunds (job rates) :							16.1	For consignment weighing 5 to 10 maunds, rate be increased by 25%; and for consignments weighing 10	
	Upto 1000 ft. (300 metre)				Consign-	25.77			to 20 maunds, rate be increased by 100%.	
	Exceeding 1000 to 3000 ft. (300 to 900 metre)				ment/ 300 M	17.67				
	1st Km				Consign-	24.27				
	2nd Km				ment/ Km	15.13				
16	3rd Km & subsequent Carriage of consignments job.				"	5.03				
	i) Cooly load for distance:-				Each					

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description		Rate	e (Metric Sy	stem)	Spec.	Remarks			
No.			Unit of M/ment	Labour	Composite	No.				
	a) Upto 5 Km b) Above 5 to 13 Km		Consignment	49.50 114.80						
	 ii) Carriage of consignments odd jobs. a) Donkey load for distance upto 500 feet. b) Upto 1000 feet. c) Upto ¹/₂ Mile/ 0.8 Km d) Upto one Mile/ 1.6 Km e) Upto three Miles/ 4.8 Km f) Exceeding 3 Miles/ 16 km 		Each Consignment " " "	10.85 16.45 20.80 26.00 45.95 82.25						
	 iii) Cart load for a distance :- a) upto 4 Miles/ 6.4 Km b) Exceeding 4 Miles(6.4 Km) to10 Miles(16 Km) 	0	Each Consig- nment "	89.85 163.55						
	 iv) Camel load for a distance:- a) upto 4 Miles/ 6.4 Km.) b) exceeding 4 to 12 mills (6.4 Km to 19.2 Km) 			66.45 100.75						
17	Hire charges of:-i) truck (10 Ton Capacity)ii) tractor with trolly		Per day "	3000.00 1000.00			 This item will be allowed with prior concurrence of Superintending Engineer. The rate includes pay of driver and cleaner only. The repairs shall be the responsibility of the owner 			
18	iii) tractor without trollyCarriage of bitumen, tar or other lubricants, in drums:	en 12 leases leaves - Energy March 12	n contraction and	800.00		16.1	and the cost of lubrication, fuel, loading and unloading shall be paid by the borrower.			
	1st Km		Per	25.85						
	2nd Km		Tonne "	17.76						
	3rd & subsequent Km		"	7.19						
19	Carriage of Asbestos cement pipes BSS Class 'B" with comet joint and rubber ring, including loading, unloading and stacking (rate per 100 Rft. (30 m pipes):-									
	 i) 3" (75 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 		30 M 30 M 30 M 300 M Km	3.75 0.70 0.45 4.20 6.21						

	MRS, BI-AN	NUAL PERIOD (1st AUGUST, 2012 TO 31s	JANUARY	, 2013) DI	STRICT JH	NG	
Sr.	Description		Rate	e (Metric Sy	stem)	Spec.	Remarks
No.			Unit of M/ment	Labour	Composite	No.	
	2nd Km		Km	2.90			
	3rd Km		Km	2.20			
	4th Km		Km	1.51			
	5th Km		Km	1.39			
	6th Km		Km	1.36			
	7th Km		Km	1.26			
	8th Km		Km	1.24			
	9th Km		Km	1.16			
	10th Km		Km	1.10			
	11th Km & Susequent		Km	1.06			
i	ii) 4'' (100 mm) i/d pipes:-		日後				
	1st chain (1st 30 m)	alter and a second	30 M	4.90			
	2nd chain (2nd 30 m)	Con the second	30 M	0.90			
	3rd to 10th chain (60 to 300 m)		30 M	0.55			
	1000 to 9000 ft. (300 to 900 m)		300 M	5.50			
	lst Km	Finance Depart	Km	8.14			
	2nd Km	19	Km	3.79			
	3rd Km		Km	2.88			
	4th Km		Km	1.98			
	5th Km		Km	1.83			
	6th Km		Km	1.80			
	7th Km		Km	1.67			
	8th Km		Km	1.65			
	9th Km		Km	1.54			
	10th Km		Km	1.44			
	11th Km & subsequent Km		Km	1.39			
i	iii) 6'' (150 mm) i/d pipes:-						
	1st chain (1st 30 m)		30 M	7.35			
	2nd chain (2nd 30 m)		30 M	1.35			
	3rd to 10th chain (60 to 300 m)		30 M	0.85			

	MRS, BI-ANNUAL P	ERIOD (1st Al	012 TO 31st	st JANUARY, 2013) DISTRICT JHANG						
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks	
No.					Unit of M/ment	Labour	Composite	No.		
	1000 to 9000 ft. (300 to 900 m)				300 M	8.30				
	1st Km				Km	12.21				
	2nd Km				Km	5.72				
	3rd Km				Km	4.35				
	4th Km				Km	3.00				
	5th Km				Km	2.78				
	6th Km				Km	2.73				
	7th Km				Km	2.54				
	8th Km		_		Km	2.51				
	9th Km	/		\sim	Km	2.32				
	10th Km	1			Km	2.14				
	11th Km & subsequent Km iv) 8" (200 mm) i/d pipes:	de la			Km	1.80				
		- SEE			12					
	1st chain (1st 30 m)	19	10.15		30 M	12.45				
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)	1697	5.	67	30 M 30 M	2.30 1.45				
	1000 to 3000 ft. (300 to 900 m)	100	1.23		300 M	1.43				
	1st Km	100		5/2	Km	20.69				
	2nd Km		-SA	22.	Km	9.98				
	3rd Km				Km	7.52				
	4th Km	Fin	ØM-CE	I))eqpipe?	Km	5.17				
	5th Km				Km	4.80				
	6th Km				Km	4.72				
	7th Km				Km	4.37				
	8th Km				Km	4.20				
	9th Km				Km	3.79				
	10th Km 11th Km & subsequent Km				Km Km	2.46 1.75				
	v) 10" (250 mm) i/d pipes:-									
	1st chain (1st 30 m)				30 M	16.75				
	2nd chain (2nd 30 m)				30 M	3.10				
	3rd to 10th chain (60 to 300 m)				30 M	1.90				
	1000 to 3000 ft. (300 to 900 m)				300 M	18.85				
	1st Km 2nd Km				Km Km	27.81 12.97				
	3rd Km				Km	9.85				

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description				Rate	(Metric Sys	tem)	Spec.	Remarks	
No.	Zeerpion				Unit of M/ment	Labour	Composite	No.		
	4th Km				Km	6.78	•			
	5th Km				Km	6.25				
	6th Km				Km	6.14				
	7th Km				Km	5.95				
	8th Km				Km	5.88				
	9th Km				Km	5.50				
	10th Km				Km	5.10				
	 11th Km & subsequent Kms vi) 12'' (300 mm) i/d pipes: 				Km	3.68				
	 vi) 12" (300 mm) i/d pipes: 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 	.stel			30 M 30 M 30 M 300 M	21.75 4.00 2.50 24.50				
	1st Km	1			Km	36.13				
	2nd Km 3rd Km	328	F		Km Km	17.85 13.21				
	4th Km	EN 1	1.5	- 190	Km	8.82				
	5th Km	4		R.C.	Km	8.15				
	6th Km	(Fi	r:/5mL(/5	Deeport	Km	8.00				
	7th Km	101-19	eren ander der der serveren en der serveren en Generaliset en der serveren en d	estrate fortexis e	Km	7.40				
	8th Km				Km	7.31				
	9th Km				Km	6.82				
	10th Km				Km	6.32				
	11th Km & subsequent Kms				Km	4.70				
	vii) 16'' (400 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 2si (c. 10h chain (200 m)				30 M 30 M	35.65 6.55				
	3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m)				30 M 300 M	4.10 40.15				
	1st Km				Km	59.25				
	2nd Km 3rd Km				Km Km	28.11 21.18				
	4th Km				Km	14.65				
	5th Km				Km	13.58				

	MRS, BI-ANNUAL F	PERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	Description				Unit of			No.	itemat K5
					M/ment	Labour	Composite		
	6th Km				Km	13.33			
	7th Km				Km	12.34			
	8th Km				Km	12.19			
	9th Km				Km	11.40			
	10th Km				Km	10.58			
	11th Km & subsequent Kms viii) 18'' (450 mm) i/d pipes:-				Km	7.74			
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	45.85 8.45			
	3rd to 10th chain (60 to 300 m)		3		30 M	5.25			
	1000 to 3000 ft. (300 to 900 m)		/	1	300 M	51.60			
	1st Km		(Km	76.12			
	2nd Km				Km	35.81			
	3rd Km	192			Km	27.27			
		- 65			- Star (1997)	10.07			
	4th Km	1358	-		Km	18.87			
	5th Km	109	1.6	- 10/	Km	17.48			
		1			100	17.10			
	6th Km		n Sta	R. C.	Km	17.16			
	7th Km	(Fi	NARM CAL	Deresori	Km	15.90			
	8th Km			07	Km	15.72			
	9th Km				Km	14.69			
	10th Km				Km	13.63			
	11th Km & subsequent Kms				Km	9.86			
	ix) 20'' (500 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	48.65			
	2nd chain (2nd 30 m)				30 M	8.95			
	3rd to 10th chain (60 to 300 m)				30 M	5.55			
	1000 to 3000 ft. (300 to 900 m)				300 M	54.75			
	1st Km				Km	80.81			
	2nd Km				Km	38.00			
	3rd Km				Km	28.93			
	4th Km				Km	20.02			
	5th Km				Km	18.55			
	6th Km				Km	18.22			

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
							•		
	7th Km				Km	16.88			
	8th Km				Km	16.68			
	9th Km				Km	15.57			
	10th Km 11th Km & subsequent Kms x) 24" (600 mm) i/d pipes:-				Km Km	14.45 10.65			
	1st chain (1st 30 m) 2nd chain (2nd 30 m)				30 M 30 M	53.90 9.90			
	3rd to 10th chain (60 to 300 m)				30 M	6.15			
	1000 to 5000 ft. (300 to 1500 m) 1st Km		(1) A		300 M Km	60.65 89.54			
	2nd Km		/ 3)	Km	42.07			
	3rd Km				Km	32.03			
	4th Km		077-01-0		Km	22.69			
	5th Km		E		Km	20.51			
	6th Km	E.	1.5	/عبرت	Km	20.13			
	7th Km	1			Km	18.65			
	8th Km	11753	941 2712 10 10 10 10 10 10 10 10 10 10 10 10 10	110. and south	Km	18.43			
	9th Km	(Fi	niami (20	anelbrait i	Km	17.23			
20	10th Km 11th Km & subsequent Kms Carriage of PVC pipes B.S.S. Class 'B' including loading, unloading and stacking (Rate per 1000 ft.) (300 metre) :-				Km Km	15.98 11.59			
	i) 3'' (75 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	7.35 1.35 0.85 8.25 12.21 5.73 4.36			
	4th Km				Km	3.01			
	5th Km				Km	2.79			

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.	Description				Unit of M/ment	Labour	Composite	No.	
	6th Km				Km.	2.73			
	7th Km				Km	2.53			
	8th Km				Km	2.48			
	9th Km				Km	2.31			
	10th Km 11th Km & subsequent Kms ii) 4'' (100 mm) i/d pipes:-				Km Km	2.15 1.75			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km	State-			30 M 30 M 30 M 300 M Km Km Km Km	11.30 2.10 1.30 12.75 18.80 9.01 6.75 4.58 4.23 4.15			
	7th Km				Km	3.84			
	8th Km		nismicie -	Disposit	Km	3.79			
	9th Km				Km	3.55			
	10th Km 11th Km & subsequent Kms iii) 5'' (125 mm) i/d pipes:-				Km Km	3.28 2.82			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km				30 M " 300 M Km " "	15.45 2.85 1.75 17.35 25.63 12.20 9.33 6.50			
	5th Km				Km.	5.82			
	6th Km				"	5.71			

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	7th Km				"	5.29			
	8th Km					5.23			
	9th Km					4.88			
	10th Km 11th Km & subsequent Kms					4.52 3.33			
	iv) 6" (150 mm) i/d pipes:								
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 300 m) 1st Km. 2nd Km 3rd Km		X		30 M 30 M 30 M 300 M Km. Km. Km.	21.30 3.90 2.45 23.95 35.33 16.62 12.65			
	4th Km	.ile	20		Km.	8.76			
	5th Km	8			Km.	8.11			
	6th Km	1EN	1. is	- 1/0/	Km.	7.96			
	7th Km	1			Km.	7.39			
	8th Km		0		Km.	7.30			
	9th Km	(Pin	NARMA (AC)	Dispon	Km.	6.81			
	10th Km 11th Km & subsequent Kms				Km. Km.	6.32 4.60			
	 v) 8" (200 mm) i/d pipes:- 1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 				30 M 30 M 30 M 300 M Km Km Km	37.30 6.85 4.25 42.00 61.98 29.16 22.21 15.37			
	5th Km				Km	14.23			
	6th Km				Km	13.97			
	7th Km				Km	12.95			

	MRS, BI-ANNUAL I	PERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	, 2013) DI	STRICT JH	ANG	
Sr.	Description				Rate	e (Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	8th Km				Km	12.80			
	9th Km				Km	11.96			
	10th Km 11th Km & subsequent Kms vi) 10'' (250 mm) i/d pipes:-				Km Km	11.07 8.04			
	Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km				30 M 30 M 30 M 300 M Km Km	57.85 10.65 6.60 65.10 96.10 45.19			
	3rd Km				Km	34.43			
	4th Km				Km	23.83			
	5th Km	-1.1			Km	22.06			
	6th Km	ŝ	125.04		Km	21.66			
	7th Km		Sela		Km	20.06			
	8th Km				Km	19.83			
	9th Km			22	Km	18.53			
	10th Km 11th Km & subsequent Kms	(Fi	eussin (22	Deeport	Km Km	17.20 12.61			
	vii) 12" (300 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km	81.45 15.00 9.35 91.65 135.28 63.63 48.46			
	4th Km				Km	33.54			
	5th Km				Km	31.04			
	6th Km				Km	30.49			
	7th Km				Km	28.26			
	8th Km				Km	27.92			

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	(Metric Sys	stem)	Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
	9th Km				Km	26.08			
	10th Km				Km	24.17			
	11th Km & subsequent Kms				Km	17.69			
	viii) 14" (350 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	106.00			
	2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m)				30 M 30 M	19.50 12.15			
	1000 to 3000 ft. (300 to 900 m)				300 M	119.30			
	1st Km				Km	176.07			
	2nd Km				Km	82.79			
	3rd Km				Km	63.05			
	4th Km				Km	43.63			
	5th Km			\mathcal{O}	Km	40.39			
	6th Km	ile	25		Km	39.66			
	7th Km	S.			Km	36.76			
	8th Km	1 Star	14	- 10	Km	36.33			
	9th Km	1			Km	33.96			
	10th Km 11th Km & subsequent Kms	(Fi	841.2124681.07.030	an a	Km Km	31.52 23.07			
21	Carriage of PVC pipes B.S.S. Class 'D' including loading, unloading and stacking (Rates per 1000 ft.):-	2018	n ain cai	arus kasas i					
	i) 2'' (50 mm) i/d pipes:-								
	1st chain (1st 30 m)				30 M	5.35			
	2nd chain (2nd 30 m)				30 M	1.00			
	3rd to 10th chain (60 to 300 m)				30 M	0.60			
	1000 to 3000 ft. (300 to 900 m)				300 M	6.05			
	1st Km				Km	8.92			
	2nd Km 3rd Km				Km Km	4.20 3.19			
					KIII	5.19			
	4th Km				Km	2.20			
	5th Km				Km	2.05			
	6th Km				Km	2.01			
	7th Km				Km	1.88			
	8th Km				Km	1.84			

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUARY,	2013) DI	STRICT JHA	NG	
Sr.	Description				Rate	Rate (Metric System)		Spec.	Remarks
No.					Unit of M/ment	Labour	Composite	No.	
					M/ment	Labour	Composite		
	9th Km				Km	1.73			
	10Km 11th Km & subsequent Kms				Km Km	1.59 1.20			
	ii) 2 ¹ /2" (63 mm) i/d pipes:-								
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	8.35 1.55 0.95 9.40 13.86 6.56 5.00			
	4th Km		/ ×	2	Km	3.48			
	5th Km		(1	Km	3.23			
	6th Km	100			Km	3.17			
	7th Km	125	F		Km	2.93			
	8th Km	EV.	1.5	- 1 ⁹ /	Km	2.70			
	9th Km	10		R. C.	Km	2.61			
	10Km 11th Km & subsequent Kms iii) 3'' (75 mm) i/d pipes:-	(Fi	elamaz	Deeport	Km Km	2.41 1.82			
	1st chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km				30 M 30 M 30 M 300 M Km Km Km	11.55 2.15 1.35 13.00 19.23 9.06 6.90			
	4th Km				Km	4.78			
	5th Km				Km	4.43			
	6th Km				Km	4.35			
	7th Km				Km	4.03			
	8th Km				Km	3.98			
	9th Km				Km	3.61			
	10th Km				Km	3.35			

Sr. Description Remain Remain Spec. Spec. No. 1110 Km & subsequent Kms. Image: Small of the subsequent Kms. Km 2.33 Image: Small of the subsequent Kms. Small of the subseque	
No. Inthem & subsequent Kms Low of Mune and Mune a	arks
11h Km & subsequent Kms Km 2.33 11) 4" (100 mm) (1d pipes:- 30 M 19.15 13 cd chain (243 0 m) 30 M 3.01 30 M 3.01 20d chain (243 0 m) 30 M 3.01 30 M 3.01 30 d to 10b chain (00 to 300 m) 30 M 2.20 300 M 2.15 1000 to 3000 ft, 300 to 900 m) 8 Km 30 M 2.15 14 Km Km Km 14.47 4b Km Km 7.00 Km 11.41 4b Km Km 7.30 Km 6.17 5b Km 66 Km Km 7.17 Km 6.10 10h Km 11th Km & subsequent Kms Km 6.10 Km 4.27 7b Km 5" (125 mm) i/d pipes:- 30 M 2.20 30 M 3.2.3 11th Km & subsequent Kms 70 M 70 M 28.65 30 M 3.2.3 12 of Linhi (145 0 m) 30 m 30 M 3.2.3 30 M 3.2.3 13 of M 3.2.30 30 M 3.2.3 30 M 3.2.3 30 M 3.2.3 <th></th>	
iv) 4" (100 mm) id pipes:- 1st chain (1st 30 m) 30 M 3.50 30 M 3.50 30 M 2.20 30 M 2.20 30 M 3.51 30 M 3.52 30 M 3.182 4 M Km 4 M Km 6 M Km 6 M Km 7 M Km 9 M Km 9 M Km 9 M Km 100 to 300 m) Km 9 M Km 10 M Km 9 M Km 10 M Km 10 M Km 20 M Station (1st 30 m) 20 M Statin (2st 30 m) 30 M S.22 30 M S.23 30 M S.23 30 M S.24 30 M S.2	
1 st chain (1st 30 m) 2nd chain (201 30 m) 30 dt no 10th chain (601 0300 m) 1000 to 3000 ft, 300 no 900 m) 131 st Km 2nd Km 30 M 30 M 32.03 30 MM 22.03 300 MM 31.82 Km 41.497 Km 4h Km Km 7.00 6h Km Km 7.17 7h Km Km 6.71 8h Km Km 6.53 9h Km Km 6.10 10h Km 10h Km 20 th 30 m) 20 chain (1st 30 m) 20 chain (2ad 30 m) 30 th 100 hobmin (0to 300 m) 1000 to 3000 m) 1000 to 300	
2nd chain (2ad 30 m) 30 M 3.50 3rd to 100 chain (60 to 300 m) 30 M 2.20 1000 to 3000 ft (300 to 900 m) Km 31.82 2nd Km 31.82 Km 3rd K m 14.97 Km 4th Km Km 7.90 5th Km Km 7.30 6th Km Km 7.30 7th Km Km 7.30 7th Km Km 6.73 9th Km Km 6.73 9th Km Km 6.53 9th Km Km 5.27 10th Km Kth Km 5.28 10th Km Sth Km 5.27 10th Km Sth Km 5.28 10th Km Sth Km 5.28 10th Km Sth Km 3.00	
3rd to 10th chain (60 to 3000 m) 300 M 2.20 1000 to 3000 fr, (300 to 900 m) 300 M 21.55 1st Km 300 M 7.00 3rd Km 11.41 Km 4th Km Km 7.30 5th Km 6h Km 7.30 6h Km Km 7.17 7th Km Km 6.71 8th Km Km 6.53 9th Km Km 6.10 10th Km Km 4.20 11th Km & subsequent Kms Km 4.21 v) 5" (125 mm) idd pipes:- Km 4.22 1st chain (1st 30 m) 300 M 328.65 300 M 300 M 5.25 300 M 32.80 300 M 1st chain (1st 30 m) 300 M 3.20 300 M 3.20 1st Km Kh Km Km 4.23 300 M 3.220 1st Km Km 3.00 3.00 3.00 3.00 3rd to 100-chain (2d 10 so 0m) 300 M 3.220 Km 3.00 100 to 3000 ft, 3000 to 900 m) Km 3	
1000 to 3000 ft, (300 to 900 m) 300 M 21.55 2nd Km 31.82 2nd Km 11.41 4th Km Km 3rd Km 11.41 5th Km 600 6th Km Km 6th Km Km 7th Km 7.17 7th Km 6.10 8th Km Km 9th Km 6.10 111th Km & subsequent Kms Km 9th Km 6.10 111th Km & subsequent Kms 300 M 9th Km 5.62 100th chain (1st 30 m) 300 M 2nd chain (2nd 30 m) 300 M 300 M 3.22.00 300 M 3.22.00 300 M 3.20 300 M	
1 st Km 31.82 2 4h Kn Km 3 th Kn Km 6 h Kn 7.00 5 th Kn Km 6 h Kn 7.17 7 h Kn 6.71 8 h Kn Km 9 h Kn 6.63 10 h Km Km 10 h Km Km 11 h Kn & subsequent Kms Km 1 st chain (143 0 m) 30 M 3 rd to 10 h chain (60 to 300 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (60 to 300 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (60 to 300 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (60 to 300 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (60 to 300 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (700 to 900 m) 300 M 1 st chain (143 0 m) 300 M 3 rd to 100 chain (700 to 900 m) 300 M 1 st chain (143 0 m) 11.11 1 st chain (143 0 m) 11.11 </td <td></td>	
3rd Km Km 11.41 4th Km Km 7.90 5th Km Km 7.00 6th Km Km 7.17 7th Km 6.71 Km 8th Km Km 6.53 9th Km Km 6.10 10th Km Km 6.22 10th Km Km 5.62 11th Km & subsequent Kms Km 5.62 10th chain (60 to 300 m) 30 M 32.865 3rd to 10th chain (60 to 300 m) 300 M 32.20 15t chain (163 30 m) 300 M 32.20 3rd to 10th chain (60 to 300 m) 32.20 300 M 32.20 15t Km 4th Km 22.36 Km 17.02 4th Km Km 17.02 17.02 17.02 4th Km Km 17.02 17.02 17.02	
4th Km 5th Km 7.00 5th Km 6th Km 7.00 6th Km 7.17 Km 6.71 7th Km Km 6.73 8th Km Km 6.73 9th Km Km 6.73 10th Km Km 6.73 10th Km Km 6.10 10th Km Km 5.62 11th Km & subsequent Kms N 30 M 11st chain (1st 30 m) 30 M 3.20 37dt to 10th chain (60 to 300 m) 300 M 3.20 1st Km Xm 2.23 2nd Km Km 17.02 4th Km Km 11.78 5th Km Km 11.78	
Sh Km 7.0 6th Km 7.0 7th Km 7.1 7th Km 6.1 8th Km 6.1 9th Km 6.10 10th Km 11th Km & subsequent Kms v) 5" (125 mm) i/d pipes:- 500 M 1st chain (1st 30 m) 200 M 2ad chain (2ad 30 m) 300 M 330 to 10th chain (60 to 300 m) 300 M 1st Km 20.3 2ad Km 70 Km 4th Km 11.7 4th Km Km 5th Km Km	
6h Km 7.17 7h Km 6.71 8h Km 6.73 9h Km 6.10 10th Km Km 10th Km 5.62 11th Km & subsequent Kms Km v) 5" (125 nm) i/d pipes:- 1st chain (1st 30 m) 30 M 2nd chain (2nd 30 m) 30 M 2nd chain (2nd 30 m) 300 M 2nd km 2.36 3t Km 17.20 4th Km Km 4th Km Km 5th Km Hong 5th Km Km 5th Km Km	
7th Km 6.71 8th Km 6.53 9th Km 6.610 10th Km 1.610 10th Km 6.10 10th Km 6.22 11th Km & subsequent Kms 6.20 v) 5" (125 mm) i/d pipes- 1st chain (1st 30 m) 30 M 28.65 30 d chain (2nd 30 m) 300 M 32.20 1st Km 70.00 to 300 m) 300 M 32.20 1st Km Km 17.02 4th Km 17.02 Km 11.78 5th Km Km 10.79	
8th Km 6.53 9th Km 6.10 10th Km 11th Km & subsequent Kms 11th Km & subsequent Kms 5.62 v) 5" (125 mm) i/d pipes:- 1st chain (1st 30 m) 30 M 2nd chain (2nd 30 m) 30 M 2nd Km 47.54 2nd Km 7.02 4th Km Km 4th Km Km 5th Km 11.78	
9th Km Km 6.10 10th Km 11th Km & subsequent Kms Km 5.62 v) 5" (125 mm) i/d pipes:- Xm 4.27 1st chain (1st 30 m) 30 M 28.65 30 M 2nd chain (2nd 30 m) 300 M 5.22 30 M 3rd to 10th chain (60 to 300 m) 300 M 52.20 30 M 1st Km 2.20 Km 47.54 2nd Km 37d Km 11.78 4th Km Km 11.78 5th Km Km 10.91	
10th Km 10th Km 6.10 11th Km & subsequent Kms Km 5.62 v) 5" (125 mm) i/d pipes:- Km 4.27 1st chain (1st 30 m) 30 M 28.65 2nd chain (2nd 30 m) 300 M 3.30 3to to 10th chain (60 to 300 m) 300 M 3.30 1000 to 3000 ft. (300 to 900 m) 300 M 32.20 1st Km Km 47.54 2nd Km Km 17.02 4th Km Km 11.78 5th Km Km 10.91	
11th Km & subsequent Kms Km 4.27 v) 5" (125 mm) i/d pipes:- 30 M 28.65 1st chain (1st 30 m) 30 M 5.25 2nd chain (2nd 30 m) 300 M 5.25 3rd to 10th chain (60 to 300 m) 300 M 32.20 1st Km Km 47.54 2nd Km Km 17.02 1st Km Km 17.02 4th Km Km 11.78 5th Km Km 10.91	
v) 5" (125 mm) i/d pipes:- 1st chain (1st 30 m) 30 M 28.65 2nd chain (2nd 30 m) 30 M 5.25 3rd to 10th chain (60 to 300 m) 300 M 32.20 1st Km 300 M 32.20 1st Km Km 44n Km 2nd Km Km 11.78 5th Km Km 10.91	
1st chain (1st 30 m) 30 M 28.65 2nd chain (2nd 30 m) 30 M 5.25 3rd to 10th chain (60 to 300 m) 300 M 3.30 1000 to 3000 ft. (300 to 900 m) 300 M 32.20 1st Km Km 47.54 2nd Km Km 17.02 4th Km Km 11.78 5th Km Km 10.91	
2nd chain (2nd 30 m) 30 M 5.25 3rd to 10th chain (60 to 300 m) 300 M 3.30 1000 to 3000 ft. (300 to 900 m) 300 M 32.20 1st Km 2.36 Km 47.54 2nd Km 17.02 Km 11.78 4th Km Km 10.91 10.91	
2nd chain (2nd 30 m) 30 M 5.25 3rd to 10th chain (60 to 300 m) 300 M 3.30 1000 to 3000 ft. (300 to 900 m) 300 M 32.20 1st Km 2.36 Km 47.54 2nd Km 17.02 Km 17.02 4th Km Km 11.78 Km 10.91	
3rd to 10th chain (60 to 300 m) 30 M 3.30 1000 to 3000 ft. (300 to 900 m) 300 M 32.20 1st Km Km 44.54 2nd Km 17.02 4th Km 11.78 5th Km M	
1st KmKm47.542nd Km22.363rd Km17.024th Km11.785th Km10.91	
2nd Km 22.36 3rd Km 17.02 4th Km Km 5th Km 10.91	
3rd Km Km 17.02 4th Km Km 11.78 5th Km Km 10.91	
4th Km Km 11.78 5th Km Km 10.91	
5th Km 10.91	
6th Km 10.71	
7th Km 9.93	
8th Km 9.81	
9th Km 9.19	
10th Km 8.43	
11th Km & subsequent KmsKm6.33	
vi) 6'' (150 mm) i/d pipes:-	

Sr. Description			Rate (Metric System)				Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	No.			
Ist chain (1st 30 m) 2nd chain (2nd 30 m) 3rd to 10th chain (60 to 300 m) 1000 to 3000 ft. (300 to 900 m) 1st Km 2nd Km 3rd Km 4th Km 5th Km 6th Km 7th Km 8th Km 9th Km 10th Km & subsequent Kms 22 Hand shunting loaded Railway wagons or trucks:- a) upto ¼ mile / ¼ Km b) upto ½ mile / ½ Km c) upto ¾ mile / ½ Km d) upto 1 (1.6 Km) mile e) 2nd mile and subsequent miles/		30 M 30 M 30 M 300 M Km Km Km Km Km Km Km Km Km Km Km Km Km	41.25 7.60 4.70 46.40 68.51 32.21 24.52 16.97 15.72 15.44 14.31 14.15 13.22 12.25 9.06 144.80 262.15 353.90 421.15					
2nd and subsequent kilometres 23 Hand shunting empty Railway wagons or trucks.		No/Km	259.05					
 a) upto ¼ mile / ¼ Km b) upto ½ mile / ½ Km c) upto ¾ mile / ¾ Km d) upto 1 mile / 1 Km e) 2nd mile and subsequent miles/ 2nd and subsequent kilometres 	(Finance Depar	Each No. " Each No/Km	84.00 139.15 183.55 220.30 127.20					

1 The rate for loading into and unloading from mobile trucks, trollies and boats, etc. will be the same as for Railway wagons.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	R	ate (British Sy	/stem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
1	Laoding or unloading into or from Railway wagons, lead within one chain, (30m) shingle, sand, ballast, surkhi, ashes, kankar, brick bats, coal, lime or 1,000 Nos. tiles size 12"x6"x2" (300x150x50 mm) or 9"x4½"x1½" (225x113x37mm) properly laid & stacked.	100 Cft.	364.30		cu.m	128.70					
2	Loading or unloading bricks into or from Railway wagons laid and stacked, lead within one chain:-			*							
	a) Bricks 10" (250 mm) size.	1000 Nos.	455.40	0	1000 Nos.	455.40					
	b) Bricks 9" (225 mm) or smaller size.	ditto	364.30		ditto	364.30					
3	Loading or unloading into or from Railway wagons cement in bags (from inside or outside the godown) and stacking within one chain (30 m)	100 Bags	455.40		100 Bags	455.40					
4	Loading or unloading into or from Railway wagons empty cement bags (from inside or outside the godown) and stacking.	100 Nos.	43.70	×	100 Nos.	43.70					
5	Loading or unloading into or from Railway wagons (from inside or outside the godown) and stacking, white lime in bags.	100 Mds.	273.25		100 Kg	7.30					
6	Loading or unloading into or from Railway wagons Structural Steel, R.S. joists, broad, narrow or meter gauge rail and rail fastenings, etc.	Per Tonne	218.60		Per Tonne	215.15					
7	Loading or unloading 45 gallon (204.57 Litres) drums full into or from Railway wagons, lead upto one chain.	Each	27.30		Each	27.30					
8 9	Loading or unloading packages of all sorts, upto one Cwt (50 Kg). Loading or unloading sleepers other than wooden, including stacking lead within one chain:-	Each	13.65		Each	13.65			Except cement in jute or paper bags.		
	a) Broad gauge sleepers	100 Nos.	910.80		100 Nos.	910.80					
	b) Metre gauge and narrow gauge sleepers.	ditto	455.40		ditto	455.40					
10	Loading or unloading timber logs or timber for shuttering	Per	113.85		Per	112.05					

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	R	ate (British Sy	/stem)	Ra	te (Metric S	/stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	into or from Railway wagons of any gauge, including stacking lead within one chain (30 m)	Ton			Tonne							
11	Loading or unloading bhoosa in Railway wagons lead upto 150 ft. (45 m)	100 Mds.	1092.95		100 Kg	29.3						
12	Loading or unloading timber scrap or wooden plugs, into or from Railway wagons, and stacking within one chain lead.	Per Ton	182.15		Per Tonne	179.30						
13	Loading or unloading pitching stone or spawl from Railway wagons of any gauge (including clearing 5 ft. (1500 mm) away from the rail).	100 Cft.	134.80		cu.m	47.60						
14	Loading or unloading building stone (including clearing 5 ft. (1.5 m) away from rails).	100 Cft.	174.85	5	cu.m	61.75						
15	Unloading oil, bitumen tar, etc.	de	-		Jui.							
	a) Crude oil (to be pumped from tank wagon into tank).	1000 Gallon	455.40		100 litres	10.00						
	b) Crude oil (drained by gravity).	1000 Gallon	455.40		100 litres	10.00						
	c) Crude oil materials from railway wagons.	100 Cft.	58.30		cu.m	20.60						
	 Fuel oil from tank into empty drums, including stacking within one chain (30 m). 	Per Ton	161.90		Per Tonne	159.35						
	e) Petrol (2 gallon tin)	100 Nos.	229.50		100 Nos.	229.50			The rate includes checking			
16	 f) Kerosine oil (4 gallon tin) Removing and stacking within one chain (30 m) lead: 	100 Nos.	455.40		100 Nos.	455.40			and weighing the tins.			
	 Stone, spawl, brick bats, shingle, sand, lime, surkhi, ashes, kankar and coat, etc. 	100 Cft.	182.15		cu.m	64.35						
	b) Bricks.	1000 Nos.	485.75		1000 Nos.	485.75						
	c) Broad gauge wooden sleepers.	100 Nos.	291.45		100 Nos.	291.45						
	d) Metre gauge or narrow gauge wooden sleepers.	100 Nos.	173.50		100 Nos.	173.50						
	e) Rails girders, pipes, cement etc.	Per Ton	80.95		Per Tonne	79.70						

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	R	ate (British Sy	/stem)	Ra	ate (Metric Sy	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	f) Bridge and crossing timbers, etc.	100 No.	971.50		100 No.	971.50					
17	Loading into wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. including lead one chain (30 M) and stacking inside wagons.	Per Ton	182.15		Per Tonne	179.30					
18	Unloading from wagons girders, rails, permanent way material (except wooden sleepers) iron work, M.S. bars, pipes, etc. lead upto one chain (30 m) but excluding stacking.	Per Ton	104.10		Per Tonne	102.45					
19	Loading into wagons wooden broad gauge sleepers, including one chain (30 m) lead and stacking,.	100 Nos.	728.65		100 Nos.	728.65					
20	Unloading wooden broad gauge sleepers from wagons, including one chain (30 m) lead and stacking.	100 Nos.	346.95	0	100 Nos.	346.95					
21	Loading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead and stacking inside wagons.	100 Nos.	364.30		100 Nos.	364.30					
22	Unloading metre gauge or narrow gauge wooden sleepers, including one chain (30 m) lead but excluding stacking.	100 Nos.	191.75	;	100 Nos.	191.75					
23	Loading bridge and crossing timbers, including one chain (30 m) lead and stacking.	100 Nos.	1457.30	10-3	100 Nos.	1457.30					
24	Unloading bridge and crossing timbers, including one chain (30 m) lead but excluding stacking.	100 Nos.	728.65		100 Nos.	728.65					
25	Loading or unloading bitumen, asphalt or tar in drums, into or from railway wagons, lead upto one chain (30 m).	Per Ton	109.30		Per Tonne	107.55					

3. EARTHWORK (EXCAVATION & EMBANKMENT)

1 Special allowances for the hardness, wetness and slush:-

The grant of allowances for hard, very hard, wet and slush will be subject to Superinteding Engineer's approval. Specific instructions regarding grant of such allowances may be issued by the various Administrative Departments and Statutory Bodies. The earth requiring repeated blows of Kassi to break it and of which dry bulk density is not less than 1.5, will be treated as hard.

- 2 Deduction for shrinkage from bank measurements:-
 - The following allowances should be provided for material which is not rammed, or equally consolidated:-
 - a) Deduction for shrinkage from the bank measurements when the earthwork is done by manual labour....... 10%

Before the work is let out to be done by tractors, scrapers, etc. deduction ranging between 3% to 6% should be agreed to with the contractors

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.	-	Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
1	Earthwork excavation underessed lead upto a single throw of Kassi, phaorah or shovel:-	ik F			<u>y.</u>			171 to 17.5			
	a) In ashes, sand, soft soil or silt clearance.b) In ordinary soil.	1000 Cft. 1000 Cft.	1,366.20 1,639.45	To the second se	cu.m cu.m	48.25 57.90					
2	Earthwork excavation in ashes, sand and soft soil or silt clearance, undressed lead upto 50 ft (15 metre).	1000 Cft.	2,003.75		cu.m	70.75		ditto			
3	 Bed clearance and dressing slopes of drains to required sections including the removal of weeds, roots, etc. disposal of excavated materials within 50 ft. (15 metre) lead. a) Excavated material undressed. b) Excavated material dressed in the specified manner. 	1000 Cft. 1000 Cft.	2,550.25 2,753.50	Departs 	cu.m cu.m	90.10 97.25		ditto	The rate is applicable where the earth of the bed to be removed is of the type of ordinary soil. When it is silt or 1 or 2 above, whichever is applicable. the drains of each category.		
4	Borrowpit excavation undressed lead upto 100 ft (30 metre).a) Ordinary soilb) Hard soil	1000 Cft. 1000 Cft.	2,550.25 3,133.15		cu.m cu.m	90.10 110.65					
5	Earthowrk in ordinary soil for embankments lead upto 100 ft. (30 m), including ploughing and mixing with blade grade or disc harrow or other suitable equipment, and compaction by mechanical means at optimum moisture content and dressing to designed section, complete in all respects:-							*411-1 to 411-13 and 301-1 & 202-3	The rate includes hire charges of machinery, cost of fuel, lubricants, pay of driver and cleaner. The rate also includes clearing and grubbing where necessary.		
6	 i) 95% to 100% maximum modified AASHO dry density. ii) 90% maximum modified AASHO dry density. iii) 85% maximum modified AASHO dry density. Regular excavation dressed. 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,778.75 2,778.75 2,778.75 1,868.60	3,673.75 3,559.45 3,445.15 	cu.m cu.m cu.m cu.m	98.15 98.15 98.15 66.00	129.75 125.70 121.70 	*411-2			
7	Earthwork excavation in open cutting upto 5'-0" (1.5 m) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and							17.1 to 17.5			

	MRS, BI-ANNUAL PER	IOD (1st A	UGUST, 201	2 TO 31st J	ANUARY	, 2013) DI	ISTRICT JHA	NG	
Sr.	Description		Rate (British Sys	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	 timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 50 ft. (15 m) lead:- i) ordinary ii) hard iii) very hard iv) gravel & shingle 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	3,175.90 3,758.85 4,378.20 7,370.90	3,248.80 3,831.70 4,451.05 7,443.75	cu.m cu.m cu.m	112.15 132.75 154.65 260.35	114.75 135.35 157.20 262.90		
8	Earthwork excavation in open cutting 5.01 ft. (1.5 m) to 10.0 ft. (3.0 mm) depth for storm water channels, drains, sullage drains in open areas, roads, streets, lanes, including under pinning of walls and shoring to protect existing works, shuttering and timbering the trenches, dressed to designed level and dimensions, trimming, removal of surface water from trenches, back filling and surplus excavated material disposed of and dressed within 100 ft. (30 m) lead:- i) ordinary ii) hard iii) very hard iv) gravel & shingle	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	3,466.30 4,049.25 4,668.60 8,025.60	3,611.25 4,194.15 4,813.50 8,170.55	cu.m cu.m cu.m cu.m	122.45 143.00 164.90 283.45	127.55 148.15 170.00 288.60	ditto	
9	Excavation in shingle or gravel formation and rock, not	100	- P		<i>¥</i>			17.1 to 17.5	
10	requiring blasting, undressed lead upto 100 ft (30 m). i) Dry ii) Wet iii) In flowing water Earthwork excavation in irrigation channels, drains, etc. to	1000 Cft. 1000 Cft. 1000 Cft.	6,922.10 8,015.05 10,200.95	Dep <u>p</u> artn	cu.m cu.m cu.m	244.50 283.10 360.30	 	1	
	designed section, grades and profiles, excavated material disposed off and dressed within 50 ft. (15 m) lead:-							ditto	
11	 i) ordinary ii) hard iii) very hard iv) gravel & shingle 	1000 Cft. 1000 Cft. 1000 Cft. 1000 Cft.	2,919.85 3,502.75 4,122.10 7,296.95	 	cu.m cu.m cu.m	103.15 123.70 145.60 257.75	 		
11	 Excavation in rock dressed to designed section, grades and profiles, excavated material disposed off within 100 ft. (30 m) and lift upto 5'-0" (1.5 m). a) Soft rock, slate, shale, schist laterite work, with pick and 	1000 Cft.	6,948.50		cu.m	245.40		17.1 to 17.5	Tools and plants shall be the liability of the contractor.
	crow bar.b) Medium hard rock, requiring occasional blasting.	1000 Cft.	10,935.40	11,511.40	cu.m	386.25	406.60		
12								17.1 to 17.5	1) Tools and plants required shall be the liability of the Contractor
	i) Grade I	1000 Cft.	6,646.20	7,222.20	cu.m	234.75	255.10		2) Reduce the rate by 8% if the excavated section is not dressed or

	MRS, BI-ANNUAL PEF	RIOD (1st A	UGUST, 201	12 TO 31st J	ANUARY	, 2013) D	ISTRICT JHA	NG	
Sr.	Description		Rate (British Sys	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	ii) Grade II	1000 Cft.	7,188.70	8,148.70	cu.m	253.90	287.80		levelled to designed section.
	iii) Grade III	1000 Cft.	8,591.90	9,743.90	cu.m	303.45	344.15		_
	iv) Grade IV	1000 Cft.	9,538.30	10,882.30	cu.m	336.90	384.35		
	v) Grade V	1000 Cft.	10,549.45	12,085.45	cu.m	372.60	426.85		
	vi) Grade VI	1000 Cft.	11,313.70	13,041.70	cu.m	399.60	460.65		
	 b) Excavation in hard rock requiring blasting, but blasting prohibited, and disposal of excavated material within 50 ft. (15 m) lead (including dressing and levelling to designed section, etc. complete):- 							17.1 to 17.5	1) Tools and plants required shall be the liability of the contractor.
	designed section, etc. complete).								2) Reduce the rate by 8% if the
	i) Grade I	1000 Cft.	13,292.40	14,444.40	cu.m	469.50	510.20		excavated section is not dressed or
	ii) Grade II	1000 Cft.	14,377.45	16,297.45	cu.m	507.80	575.65		levelled to designed section.
	iii) Grade III	1000 Cft.	17,183.75	19,487.75	cu.m	606.95	688.30		
	iv) Grade IV	1000 Cft.	19,076.65	21,764.65	cu.m	673.80	768.75		
	v) Grade V	1000 Cft.	21,098.90	24,170.90	cu.m	745.20	853.70		
	vi) Grade VI	1000 Cft.	22,627.45	26,083.45	cu.m	799.20	921.25		
13	Rehandling of earthwork:	S.							
	a) Lead upto a single throw of Kassi, phaorah or shovel	1000 Cft.	910.80		cu.m	32.15		ditto	
	b) Upto a lead of 50 ft. (15 m).	1000 Cft.	1,275.10	5 - C. B	cu.m	45.05			
14	Rehandling of gravel work or excavated rock,	1000 Cft.	3,643.20		cu.m	128.70		17.1 to 17.5	
	lead upto 50 ft.(15 m)	Fan	n anice (Departs	nem t				
15	Filling, watering and ramming earth under floors:-	alle. Debutt		an constant and an early	CALCERCOLOGY BY			ditto	
	i) with surplus earth from foundation, etc.	1000 Cft.	1,829.50		cu.m	64.60			
	ii) with new earth excavated from outside,	1000 Cft.	3,519.25		cu.m	124.30			
	lead upto one chain (30 m).	1000 Cit.	5,517.25		cu.m	124.50			
16	Extra for every 50 ft. (15 m) additional lead or part thereof :-								This rate shall be applicable upto
									1000 ft. total distance, including the
	i) for earhtwork soft, ordinary, hard and very hard.	1000 Cft.	32.40		cu.m	1.15			lead covered in the item of earthwork
	ii) for gravel, shingle or rock.	1000 Cft.	37.85		cu.m	1.35			
17	Transportation of earth all types when the total distance,								This rate will be paid inaddition to the
	including the lead covered in the item of work, is more than								rate of earthwork, without deducting
	1000 ft. (300 m)								the lead covered in the item of
	a) upto ¼ mile (400 m).	1000 Cft.	1,469.50		cu.m	51.90			earthwork
	b) for every 330 ft. (100 m) additional lead or part thereof,								
	beyond ¼ mile (400 m) upto one mile. (1.6 Km.)	1000 Cft.	88.90		cu.m	3.15			
	c) for every $\frac{1}{4}$ mile (400 m) additional lead or part thereof,	1000 50							
	beyond one mile (1.6 Km.) upto 5 mile (8 Km).	1000 Cft.	155.15		cu.m	5.50			
	d) for every ½ mile (800 m) additional lead	1000 CF	127 10			105			
	or part thereof, beyond 5 miles (8 Km).	1000 Cft.	137.10		cu.m	4.85			
18	Dressing and levelling of earhtwork to designed section, etc. complete:-							17.10 to 17.5	
	learning the second s	1							l

	MRS, BI-ANNUAL PERI	OD (1st A	UGUST, 20 ⁻	12 TO 31st J	ANUARY	', 2013) D	ISTRICT JHA	NG	
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
	 a) Ashes, sand, silt or soft soil. b) Ordinary or hard soil. c) Gravel work or soft rock not requiring blasting. 	1000 Cft. 1000 Cft. 1000 Cft.	117.65 228.50 551.75		cu.m cu.m cu.m	4.15 8.05 19.50	 		
19	Dowel dressing.	Per Chain	107.35		Metre	3.50		ditto	This rate is in addition to payment for dressed earhtwork.
20	a) Dressing slopes of banks or ground surface.	100Sft.	47.90		sq.m	5.15		ditto	To be paid only when exclusively dressing is done and no earthwork is carried out in embankment or cutting.
	 b) Dressing of earthwork (done by machinery or otherwise and left undressed) to designed section. 	100Sft.	85.80		sq.m	9.25			i) The surface area dressed is to be taken for measurement.
21	Excavation in foundation of building, bridges and other	Same-						15.1.15.5	ii) The item is applicable where the dressing is done by the contractor other than the one who executed the work.
	 structures, including dagbelling, dressing, refilling around structure with excavated earth, watering and rammiing lead upto one chain (30 m) and lift upto 5 ft. (1.5 m) a) in sand, ashes or loose soil b) in ordinary soil. 	1000 Cft. 1000 Cft.	3,284.15 3,833.30	San	cu.m cu.m	116.00 135.40	 	17.1 to 17.5	
22	 c) in hard soil or soft murum. Cutting hard rock such as granite, ballast, hard lime stone or sand stone, etc. with chisels and hammers, for small foundations. 	1000 Cft. 1000 Cft.	4,290.00 26,537.30	30,548.80	cu.m cu.m	151.50 937.30	 1079.00	17.1 to 17.5	Tools and plants required shall be the liability of the contractor.
23 24	Extra for excavation requiring shoring. Compaction of earthwork (soft, ordinary or hard soil) :-	1000 Cft.	481.80	725.75	cu.m	17.00	25.65	17.1 to 17.5 ditto	Composite rate includes materials, i.e. plank, etc.
	a) Mixing, moistening earth to optimum moisture content in layers for compaction, etc. complete.	1000 Cft.	431.80		cu.m	15.25			
	 b) Compaction by rolling with animal driven roller/hand rammed: 								
	i) soft or sandy soil	1000 Cft.	546.50		cu.m	19.30			1) The rate does not include him
	ii) ordinary soil	1000 Cft.	637.55		cu.m	22.50			 The rate does not include hire charges of the roller. Roller to be 'supplied by Government
	iii) hard soil	1000 Cft.	728.65		cu.m	25.75			
	iv) admixture of shingle	1000 Cft.	819.70		cu.m	28.95			
	c) Ramming earthwork (all types of soil).	1000 Cft.	546.50		cu.m	19.30			

	MRS, BI-ANNUAL PERI	OD (1st A	UGUST, 20	12 TO 31st J	ANUARY	, 2013) D	ISTRICT JHA	NG	
Sr.	Description		Rate (British Sy	stem)		ate (Metric S	System)	Spec.	Remarks
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.	
25	 Ramming earhtwork behind retaining walls. Compaction of earthwork with power road roller, including ploughing, mixing, moistening earth to optimum moisture 	1000 Cft.	728.65		cu.m	25.75		17.1 (a)	
	 i) 95% to 100% maximum modified AASHO dry density. 	1000 Cft.		895.00	cu.m	-	31.60	202-3	The rate also includes hire charges of machinery, cost of fuel, lubricant, pay of driver and cleaner, etc.
	ii) 90% maximum modified AASHO dry density.	1000 Cft.		780.70	cu.m	-	27.55		
	iiii) 85% maximum modified AASHO dry density.	1000 Cft.	×	666.40	cu.m	-	23.55		
26	Extra for wet earthwork.	1000 Cft.	1,275.10	/ - \	cu.m	45.05	-	17.1 to 17.5	That will support a man's weight.
27	Extra for slush or Daldal including dewatering.	1000 Cft.	2,914.55		cu.m	102.95	-	17.1 to 17.5	That will not support a man's weight.
28	Extra for puddling.	1000 Cft.	2,284.90		cu.m	80.70	-	ditto	
29	Earthwork on small rain water drains, along canal banks, roads and plantation drains, dressed, etc. complete.	100 Rft.	346.10		Metre	11.35	-	ditto	
30	Filling and compacting soil, earth and boulders behind retaining walls (including excavation of soil and lead upto 50 ft.(15 m).	1000 Cft.	3,278.90		cu.m	115.80		17.1 to 17.5	
31	Dag bailing 3" (75 mm) deep.	Per mile	1,366.05	0.5 9441 11 	Per Km	849.00		ditto	Dag bailing for layout of borrow pit, to be done by contractors at their own cost.
32	Turfing slopes of banks or lawns with grass sods including ploughing, laying, setting and watering (Turf got from within a distance of 5 miles (8 Km.) and maintenance for 15 days).	100Sft.	607.20		sq.m	65.35		ditto	
33	Berm cutting:-							17.1 to 17.5	
	 a) lead upto a single throw of Kassi, phaora or shovel (without dressing). 	1000 Cft.	1,639.45		cu.m	57.90			
	b) upto 50 ft(15 m)lead (including dressing).	1000 Cft.	2,919.85		cu.m	103.15			
34	Berm trimming both sides of channels:-							17.1 to 17.5	
	a) upto $3\frac{1}{2}$ ft. (1.06 m) depth.	Per Mile	4,259.20		Per Km.	2662.00			
	 b) exceeding 3½ ft. to 5 ft. (1.06 to 1.5 m) depth. c) exceeding 5 ft. to 8 ft. (1.5 to 2.4 m) depth 	Per Mile Per Mile	5,934.30 9,278.30		Per Km. Per Km.	3708.95 5798.95			
35	Ploughing and levelling borrowpits.							ditto	Area ploughed to be measured.
	 i) upto 3 ft. (0.9 m) depth. ii) above 3 ft. (0.9 m) depth. 	Per Acre Per Acre	910.80 1,821.60		Per Hect. Per Hect.	2250.65 4501.25			

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit of M/ment	Labour	Composite	Unit of M/ment	Labour	Composite	No.			
36	Making boundary or service roads, including dag-belling, levelling and dressing:							ditto			
	i) in unploughed land:										
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide.b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	457.60 611.60		Metre Metre	15.00 20.05					
	ii) in ploughed land:										
	a) from 10.0 ft. to 20.0 ft. (3 to 6 m) wide.b) from 20.1 ft. to 40.0 ft. (6.10 to 12 m) wide.	Per Chain Per Chain	471.95 625.95		Metre Metre	15.50 20.55					
37	Earthwork by boats, including hire of boats:-	/						17.1 to 17.5	For ordinary soil.		
	 i) Digging and loading into boats, upto 50 ft. (15 m) lead. ii) Carriage by boats upto 10 chains (300 m). iii) Extra for every additional one chain (30 m) or part thereof beyond 10 chains (300 m). 	1000 Cft. 1000 Cft. 1000 Cft.	2,732.40 682.60 72.85		cu.m cu.m cu.m	96.50 24.10 2.55	 				
	iv) Unloading earth from boats.	1000 Cft.	1,275.10	1/10	cu.m	45.05					
38	Unloading earth from B.G. trucks and clearing 5 ft. (1.5 m) from rail.	1000 Cft.	1,092.95	9.735-04	cu.m	38.60		17.1 to 17.5			
39	Earthwork by tramway, digging and loading in trucks, upto 50 ft. (15 m) lead.	1000 Cft.	2,550.25	loep <u>a</u> rts	cu.m	90.10		17.1 to 17.5			
40	Unloading earth from B.G. trucks and spreading upto 15 ft. (4.5 m) from rail.	1000 Cft.	2,049.30		cu.m	72.40		ditto			
41	Supplying clean and screened river or pit sand within 5 chains (150 m).	100Cft.	353.55	375.55	cu.m	124.85	132.65	ditto	The rate incudes:- i) removal of top crust of earth over burden ii) royalty to the government or cost to the private owner.		
42	Earthwork excavation in open cutting for sewers and manholes as shown in drawings including shuttering and timbering, dressing to correct section and dimensions according to templates and levels, and removing surface								The rate does not include back filling after laying of sewer, which is payable separately.		
	 water, in all types of soil except shingle, gravel and rock:- i) 0 ft. to 7.0 ft. (0 to 2.10 m) depth ii) 7-01 ft. to 15.0 ft. (2.15 to 4.5 m) depth iii) above 15.0 ft. (4.5 m) depth 	1000 Cft. 1000 Cft. 1000 Cft.	2,966.40 5,037.00 6,494.25	3,327.20 5,572.15 7,029.40	cu.m cu.m cu.m	104.75 177.90 229.40	117.50 196.80 248.30		If the timbering and shuttering is not actually done at site, the composite rate may be reduced by Rs. 368.20, 579.60 and 579.60 respectively.		
43	Earthwork excavation of trenches in open cutting for sewers and manhole chambers, etc. below sub-soil water level to							17.1 to 17.5 **13.3 &	The rate does not include back filling after laying of sewer, which is payable		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description]	Rate (British Sys	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.	•	Unit of		· · · · · · · · · · · · · · · · · · ·	Unit of		•	No.				
		M/ment	Labour	Composite	M/ment	Labour	Composite					
	correct section and dimensions according to templates and levels, including shoring, timbering and shuttering of M.S. sheets on both sides of the trenches:							13.5	separately.			
	i) 0 ft. to 4.0 ft. (0 to 1.20 m) depth below SSWL.	1000 Cft.	4,095.30	6,635.70	cu.m	144.65	234.35					
	ii) 4.01 ft. to 8.0 ft. (1.22 to 2.4 m) depth below SSWL.	1000 Cft.	5,119.65	8,416.65	cu.m	180.85	297.30					
	iii) Exceeding 8 ft. (2.4 m) depth below SSWL.	1000 Cft.	7,679.50	11,257.80	cu.m	271.25	397.65					
44	Excavation of trenches in all kinds of soil, except cutting rock, for watersupply pipelines upto 5 ft. (1.5 m) depth from ground level, including trimming, dressing sides, levelling the beds of trenches to correct grade and cutting pits for joints, etc. complete in all respects.	1000 Cft.	2,735.05	-	cu.m	96.60		17.1 to 17.5 **8.1	The rate does not include back filling after laying of pipe line, which is payable separately.			
45	Cutting and removing trees within a distance of 100 ft. (30 m)											
	 a) upto 2¹/₂ ft. (760 mm) girth. b) above 2¹/₂ ft. to 6 ft. (760 to 1800 mm) girth. 	Each Each	543.50 1,057.65		Each Each	543.50 1057.65						
46	Uprooting stump and removing within 100 ft. (30 m) from 2 ft. to 6 ft. (600 to 1800 mm) girth.	Each	683.10		Each	683.10						
47	Jungle clearance and removing within 100 ft. (30 m).		S.P.	I Carol								
	a) light b) thick	1000 Sft. 1000 Sft.	91.10 182.15	Dep <u>t</u> arts	sq.m sq.m	1.00 1.95						
48	Uprooting Sarkanda growth and disposal within 100 ft. (30 m)	100Sft.	43.70		sq.m	4.70						
49	Ploughing 3 times.	Per Acre	370.00		Per Hect.	914.30						
50	Levelling, dressing and making lawns.	100Sft.	182.15		sq.m	19.60						
51	Turfing lawns (excluding cost of turf).	100Sft.	154.00		sq.m	16.55						
52	Earthwork in excavation of drains, irrigation channels through excavator / drag lines in all kind of soil and conditions(dry,wet slush,daldal and under water) including its disposal and prepartion of working pad for operation of machinery. (Rates includes 100 ft lead)	1000 Cft.		2000.00	cu.m		70.65					
	(Kates includes 100 ft lead)			2000.00	cu.iii		70.05					

* Specification number correspond to Book of "Specification for Road & Bridge Construction, 1971".
 ** Specification number correspond to Book of "Building & Roads Department Specification Vol. II, 1966 (Public Health Works).

4. DISMANTLING (DEMOLITION)

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 2 The rates for dismantling roofs or upper storey floor, include the dismantling of all materials, except roof supports such as beams and trusses.

	MRS, BI-ANNUAL P	13) DISTRICT	JHANG						
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Stone Work								
1	Dismantling dry stone masonry.	100Cft.	309.65		cu.m	109.35		18.1	
2	Dismantling stone masonry in mud mortar.	100Cft.	455.40		cu.m	160.85		ditto	
3	Dismantling stone masonry in lime or cement mortar.	100Cft.	1,092.95	*)	cu.m	386.05		ditto	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively.
4	a) Dismantling dry stone or spawl pitching.	100Cft.	546.50		cu.m	193.00		ditto	
	b) Dismantling stone or spawl pitching (mud grouted).	100Cft.	692.20		cu.m	244.50		ditto	
5	Dismantling stone or spawl pitching and apron in silted condition.	100Cft.	910.80	S. I. S. Deside	cu.m	321.70		ditto	
6	Dismantling stone pitching, cement or lime grouted.	100Cft.	1,457.30		cu.m	514.70		ditto	
7	Dismantling stone in crates:		enmante.	e senerpha	TE MILLES	U.I.			
	a) wooden crates	100Cft.	728.65		cu.m	257.35			
	b) wire crates	ditto	910.80		ditto	321.70			
8	Dismantling stone ware drain including base concrete.	100Cft.	510.05		cu.m	180.15		ditto	
	Brick Work								
9	Dismantling mud/pise walling.	100Cft.	182.15		cu.m	64.35		18.1	
10	Dismantling sun dried brick masonry.	100Cft.	455.40		cu.m	160.85		ditto	
11	Dismantling dry brick masonry.	100Cft.	309.65		cu.m	109.35		ditto	
12	Dismantling brick work in mud mortar.	100Cft.	637.55		cu.m	225.20		18.1	Add extra 13%, 32% and 51% on
13	Dismantling brick work in lime or cement mortar.	100Cft.	1,548.35		cu.m	546.90		ditto	labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 12, 13, 14 & 15.

	MRS, BI-ANNUAL P	ERIOD (1st AUGUST	Γ, 2012 TO 3 [·]	1st JANU	JARY, 20 1	13) DISTRIC	F JHANG	
Sr.	Description]	Rate (British Sy	rstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Dismantling cement block masonry.	100Cft.	1,366.20		cu.m	482.55		ditto	
15	Dismantling Dhajji walling.	100Cft.	364.30		cu.m	128.65		ditto	
	Concrete								
16	Dismantling mud concrete.	100Cft.	728.65		cu.m	257.35		ditto	
17	Dismantling lime concrete.	100Cft.	1,001.90		cu.m	353.85			Add extra 13%, 32% and 51% on
18	Dismantling lime or cement concrete, under water.	100Cft.	3,825.35		cu.m	1351.10			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against item No. 17, 19 & 20.
19	a) Dismantling cement concrete plain	100Cft.	2,003.75	*)	cu.m	707.75		ditto	
	1:4:8.b) Dismantling cement concrete plain	ditto	3,278.90		ditto	1158.10			
	1:3:6.c) Dismantling cement concrete 1:2:4	ditto	4,007.50		ditto	1415.45			
	plain.d) Dismantling cement concrete with brick	ditto	1,092.95		ditto	386.05			
	 aggregate. e) Dismantling D.P.C. of cement concrete 1¹/₂" thick (40 mm) and clearing the site. 	ditto	546.50	مجرمت ب ^ر یکا ا	ditto	193.00			
20	Dismantling cement concrete reinforced, separating reinforcement from concrete, cleaning and straightening the same.	100Cft.	6,557.75		cu.m	2316.20		ditto	
	Roofing								
21	Dismantling sirki sarkanda or thatched roofing, supported on battens or ballies.	100Sft.	218.60		sq.m	23.50		18.1	
22	a) Dismantling 1st class tile roofing.	100Sft.	546.50		sq.m	58.80			Add extra 13%, 32 and 51% on
	b) Dismantling 2nd class tile roofing.	100Sft.	455.40		sq.m	49.00		ditto	labour rate only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 22, 25, 26 and 28.
	Dismantling from any height, asbestos sheets and ridge coping.	100Sft.	299.65		sq.m	32.25		18.1	
24	 a) Dismantling roof of wooden planks and battens, from any height. 	100Sft.	239.7		sq.m	25.8		ditto	
	b) Dismantling wooden ceiling above 20' (6.0 m) height	100Sft.	937.75		sq.m	100.90		ditto	

	MRS, BI-ANNUAL	PERIOD (1st AUGUS	Г, 2012 ТО З [.]	1st JANI	JARY, 20 ⁻	13) DISTRICT	JHANG	-
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in difficult position, including lifting with care and special scaffolding along live electric wires and with machines underneath.								
25	Dismantling jack arch roofing, including removal of joists.	100Sft.	728.65		sq.m	78.40		ditto	
26	Dismantling R.B. roof complete with mud and plaster, including separating reinforcement, cleaning and straightening the same.	100Sft.	910.80		sq.m	98.00		ditto	
27	 a) Stripping and stacking slate or tiles from the truss roofing. 	100Sft.	455.40		sq.m	49.00			
	b) Stripping and stacking C.I. sheet roof.	ditto	420.70	×	ditto	45.25			
	c) Extra for dismantling C.I. sheet roof above 20 ft. (6m) in difficult position, including lifting with special scaffolding along live electric wire with machine underneath.	ditto	561.00	0	ditto	60.35			
28	Dismantling slates or tiles including battens, purlins and planking.	100Sft.	728.65	حکومہ سے بیتھا	sq.m	78.40		18.1	
	Flooring		No.		53				
29	Dismantling brick or flagged flooring without concrete foundation.	100Sft.	309.65	e Otema	sq.m	33.30		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively
30	Dismantling plank or wooden block flooring, etc.	100Sft.	455.40	an ann Brann	sq.m	49.00		ditto	against items No. 29 and 30.
31	Disjoining R.C.C. pipes inside the trench and dismantling and removing the pipes from the trench and stacking them outside:-								i) The rate does not include the cost of excavation and refilling of trench, or the demolition of any masonry or brick work.
	 a) 6" to 12" (150 to 300 mm) diameter b) 13" to 24" (325 to 600 mm) diameter c) 25" to 36" (625 to 900 mm) diameter d) Above 36" (Above 900 mm) diameter 	Per Lft Per Lft ditto ditto	12.00 19.25 22.55 32.10		Metre Metre ditto ditto	39.35 63.15 73.95 105.30			ii) Bends, elbows, sluice valves,etc. should not be paid for extra iffixed in the length of pipe line thatis being dismantled.
32	a) Removing door with chowkat.	Per	156.40		Per	156.40		18.1	Add extra 13%, 32% and 51% on
	b) Removing windows and sky lights with chowkat.	No. ditto	121.90		No. ditto	121.90			labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 32, 33, 34, 35 & 36.

	MRS, BI-ANNUAL F	ERIOD (1st AUGUS	Γ, 2012 TO 3 [·]	Ist JANU	JARY, 20 ⁻	13) DISTRICT	JHANG	
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
33	Removing ventilators and wooden sunshade, etc.	Per No.	63.90		Per No.	63.90		ditto	
34	a) Dismantling wooden beams upto 12' (3.65m) length.	Per No.	113.85		Per No.	113.85		ditto	
	 b) Dismantling wooden beams from 12.1' to 23' (3.65 to 7.0 m) length. 	ditto	182.15		ditto	182.15			
35	a) Dismantling wooden partition Jaffry work etc.	100Sft.	214.05		sq.m	23.05		ditto	
	b) Dismantling wooden trusses.	100Kg	645.80		%Kg	645.80			
36	Dismantling wooden palisade fencing.	Per Lft.	17.40	×	Metre	57.05		ditto	
	<u>Iron work</u>			\bigcirc					
37	Dismantling iron work of trusses, sheds, water tanks, etc. excluding cutting of rivets.	100Kg	640.90		%Kg	640.90		18.1	Add extra 13%, 32% and 51% on labour rates only for 2nd, 3rd, 4th and subsequent floors respectively against items No. 37 and 38.
38	Dismantling rolled steel beams or iron rails, etc.	100Kg	298.95	طومت پ نجا	%Kg	298.95		ditto	against tients 100. 57 and 58.
39	Dismantling iron latrine.	Per Unit/ 2 Seats	690.35	PS &	Per Unit/ 2 Seats	690.35		ditto	
40	Dismantling tees, bends or sluice valves upto 12" (300 mm) bore.	Each per inch bore	14.50		Each per cm bore	5.80		ditto	
41	a) Dismantling B.G. water column.	Each	4,524.30		Each	4524.30		ditto	
	b) Dismantling M.G. or N.G. water column.	Each	3,011.25		Each	3011.25		ditto	
42	Dismantling all type of wire fencing, including rolling wire into bundles and collecting material.	100Lft.	309.65		Metre	10.15		18.1	
	Miscellaneous								
43	Dismantling wire netting of tennis courts and frame work.	100Sft.	145.75		sq.m	15.70		18.1	
44	Dismantling cloth ceiling and supporting timber.	100Sft.	273.25		sq.m	29.40		ditto	
45	Dismantling and removing road metalling.	100Cft.	728.65		cu.m	257.35		ditto	
46	Dismantling and removing road pavement, etc., including screening and stacking of byproducts upto one chain lead	100Cft.	972.75		cu.m	343.60		ditto	

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	(30 metre).												
47	Removing mud plaster from walls.	100Sft.	75.90		sq.m	8.15		ditto	Add extra 13%, 32% and 51% on				
48	Removing cement or lime plaster.	100Sft.	151.80		sq.m	16.35		ditto	labour rates only for 2nd, 3rd, 4th and subsequent floors against item No. 47, 48, 49, & 50 respectively				
49	Scraping:-							18.1					
	a) White wash or colour wash.	100Sft.	91.10		sq.m	9.80							
	 Ordinary distemper, oil bound distemper, or paint of wall. 	ditto	273.25		ditto	29.40							
50	Dismantling glazed or encaustic tiles, etc.	100Sft.	834.25	*)	sq.m	89.75		18.1					
51	Scraping boulders.	100Cft.	1,275.10		cu.m	450.35		18.1					
52	Cleaning lime or cement mortar of old stones to be used in masonry.	100Cft.	637.55		cu.m	225.20		18.1					
	Electric Wiring	100	14	(حکومہ سے بنایا	7_Ľ	dina.							
	Dismantling light, fan and call bell point including casing and capping/strip open type, and making good damaged surface (building portion).	Per point	27.15	27.55	Per point	27.15	27.55						
	Dismantling plug point and making good	Per	23.30	23.60	Per	23.30	23.60						
54	damaged surface (building portion).	point	23.50	23.00	point	25.50	23.00						
55	Dismantling G.I./M.S. conduit/G.I. flexible/PVC pipes or conduit wiring, etc. of all sizes including making good damaged surface (building portion):-												
	i) on surfaceii) recessed in wall	Per foot Per foot	4.95 10.60	5.05 10.70	P.Mtr P.Mtr	16.25 34.75	16.55 35.10						

5. MORTAR

	MRS, BI-ANNUAL PERIOD						
			Material Require (St. Wet (Ready) M			Material Required am Wet (Ready)	
S. No.	Ratio of Mortar	Cement	Lime	viortal	Cement	Lime	Sand
5.110.	Ratio of Wortan	(50 Kg)	Putty	Sand	(50 Kg.)	Putty	Cum.
		Bag	Cft.	Ctt.	Bag.	Cum	Cuill.
1	2	3	4	5	6 6	7	8
1	Cement : Sand						
	1:2	33.48		82	11.83		0.82
	1:3	23.11		85	8.16		0.85
	1:4	18.37		90	6.49		0.90
	1 : 5	14.70		90	5.19		0.90
	1:6	13.61		100	4.81		1.00
	1:7	11.68		100	4.12		1.00
	1 : 8	10.21		100	3.61		1.00
2	Cement : Lime : Sand						
2	1:1:6	12.25	15.0	90	4.33	0.15	0.90
	1 : 1 : 0 1 : 1 : 7	10.70	13.0	92	3.78	0.13	0.90
	1 : 1 : 7 1 : 1 : 8	9.39	11.5	92	3.32	0.12	0.92
	1 : 1 : 9	8.52	10.44	94	3.00	0.10	0.92
	1 : 1 : 10	7.67	9.4	94	2.71	0.09	0.94
	1 : 2 : 8	9.19	22.5	90	3.25	0.23	0.90
	1:2:9	8.16	20.0	90	2.88	0.20	0.90
	1:2:10	7.67	18.8	94	2.71	0.19	0.94
	1:2:12	6.39	15.66	94	2.26	0.16	0.94
	1:3:12	6.26	23.0	92	2.21	0.23	0.92
	1 : 3 : 14	5.47	20.1	94	1.93	0.20	0.94
	1 : 3 : 16	4.82	17.7	94	1.70	0.18	0.94
	$1 : \frac{1}{4} : 3$	23.11	7.0	85	8.16	0.07	0.85
3	Lime : Sand	(Fim) anna	ue (I)termé	and the second second			
5	1 : 2	THE BERTHOMSBURG	43	86		0.43	0.86
	1 : 2 1 : 3		31	93		0.31	0.00
			~ 1	20		0.01	5.75

5. MORTAR

MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG													
	MRS, BI-ANNUA					JANUAR	Y, 2013)	DISTRIC	JHANG				
			Dry Material	Required fo	r 100 Cft.			Dry Ma	aterial Requi	red for			
S.	Ratio of Mortar	Clay	Lime	(Ready) Mor Sand	tar Surkhi	Cinder	Clay	Lime	Wet (Ready Sand) Mortar Surkhi	Cinder		
No.		Chuy	(Putty)	Sund	Summ	Ciliadi	Ciuy	(Putty)	Sulla	buikin	emater		
		Cft.	Cft.	Cft.	Cft.	Cft.	M	M	M	M	M		
1	2	3	4	5	6	/	3	4	5	6	/		
4		125					1.25						
4	Mud	135					1.35						
5	Lime : Surkhi												
	2:3		49.00	-	73.5		-	0.49	-	0.74	-		
	1:2		40.75	-	81.5		-	0.41	-	0.82	-		
	1 : 3		30.30	-	91.0		-	0.30	-	0.91	-		
6	Lime : Sand : Surkhi												
	1:1:1		40.50	40.5	40.5		-	0.41	0.41	0.41			
_				34 Y									
7	Lime : Cinder 1 : 1		57.0			57.0		0.57			0.57		
	1 : 1		57.0		-	57.0	-	0.37	-	-	0.37		
1	Brick Masonry : a) Mud Mortar	Wet material masonry (inclu	uding wastage 35.00	e): Cft		78		al required f including wash 0.35	tage) : M ³	32 Cft)			
	b) Cement, Sandc) Cement, Lime (Putty) Sand		25.00	Cft Cft	5/2	93°		0.25 0.25	M ³ M ³				
	d) Lime (Putty) Sand		25.00 25.00					0.25	M ³				
2	Stone Masonry : a) Random rubble, uncoursed												
	i) Foundation and Plinth		45.00	Cft				0.45	M ³ M ³				
	ii) Superstructure iii) Coursed		40.00 35.00	Cft Cft				0.40 0.35	M M				
	b) Ashlar Block in course or Sc	abled masonry	30.00					0.30	M^3				
	c) Ashlar fine masonry		20.00					0.20	M^3				
	· · · · · · · · · · · · · · · · · · ·		20100					0.20					
	(1) Cement	1 Cft.	= 40.8233	-									
Notes :	(2) Unslaked lime	1.7 Cft.	= 37.3242	-									
	(3) Slaked lime	2.5 Cft.	= 37.3242	-									
	(4) Quick lime	40 Kg	Will yie	ld 2.6 Cft. lii	ne putty.								

6. CONCRETE

Notes 1 Notes (1) Rates for all finished works include the removal of surplus debris, unused material and by products.

2 If concrete mixer or high frequency vibrator, etc. is supplied by the Government, all charges including depreciation will be recovered from the contractor.

	MRS, BI-ANNUAL PERIOE) (1st Al	JGUST, 201	12 TO 31st J	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	F	Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud concrete in foundation including watering and ramming, using brick or stone ballast 1 ¹ /2" (40 mm) gauge.	100Cft	2013.45	3483.45	cu.m	711.15	1230.35		The stone ballast, crushed bajri, round shingle from nallah, or brick ballast may be used according to
2	Dry rammed brick or stone ballast, 1 ¹ / ₂ " to 2"(40 mm to 50 mm) gauge.	100Cft	1366.20	2752.20	cu.m	482.55	972.10		their comparative cheaper rates in various areas of the Province.
					道海				
3	Cement concrete brick or stone ballast 1 ¹ / ₂ " to 2" (40 mm to 50 mm) gauge, in foundation and plinth:-		S.		2			20.1	-do-
	(a) Ratio 1: 3: 6	100Cft	2654.85	11050.05	cu.m	937.70	3902.90		
	(b) Ratio 1: 4: 8	ditto	2654.85	9359.50	"	937.70	3305.80		
	(c) Ratio 1:5:10	ditto	2654.85	8462.35	"	937.70	2988.90		
	(d) Ratio 1: 6:12	ditto	2654.85	7788.45	"	937.70	2750.90		
	(e) Ratio 1: 6: 18	ditto	2654.85	7057.65	"	937.70	2492.75		
	(f) Ratio 1: 7:20	ditto	2654.85	6737.60	"	937.70	2379.70		
4	Extra on item No. 3 above, for sedimentation tank or filter								
	beds of Public Health Engineering Works:								The stone ballast, crushed bajri,
									round shingle from nallah, or brick
	(a) in bed	100Cft	854.05	-	cu.m	301.65	-		ballast may be used according to
									their comparative cheaper rates in
	(b) on slope	ditto	1271.15	-	"	448.95	-		various areas of the Province.
5	Cement concrete plain including placing,							20.1	

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description	R	ate (British Sy	ystem)	Rat	te (Metric S	ystem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	compacting, finishing and curing complete (including screening and washing of stone aggregate): (a) Ratio 1: 1:2 (b) Ratio 1: 11/2: 11/2 (c) Ratio 1: 11/2: 3 (d) Ratio 1: 2: 3 (e) Ratio 1: 2: 3 (e) Ratio 1: 3: 3 (f) Ratio 1: 2: 4 (g) Ratio 1: 2: 6 (h) Ratio 1: 3: 6 (i) Ratio 1: 4: 8 Providing and laying reinforced cement concrete (including prestressed concrete), using coarse sand and screened graded and washed aggregate, in required shape and design, including forms, moulds, shuttering, lifting, compacting, curing, rendering and finishing exposed surface, complete (but excluding the cost of steel reinforcement, its fabrication and placing in position, etc.):- (a) (i) Reinforced cement concrete in roof slab, beams, columns lintels, girders and other structural members laid in situ or precast laid in position, or prestressed members cast in situ, complete in all respects:-	100Cft ditto ditto ditto 100Cft ditto ditto	3597.00 3597.00 3597.00 3597.00 3597.00 3597.00 3597.00	23811.00 23128.20 19444.20 18508.20 16364.05 17103.25 15595.10 14917.80 13354.45	cu.m " " cu.m " "	1270.45 1270.45 1270.45 1270.45 1270.45 1270.45 1270.45 1270.45	8410.05 8168.90 6867.70 6537.10 5779.80 6040.85 5508.20 5268.95 4716.80	20.4	 The rate includes rendering floor surface smooth, and the plastering done for making up all surfaces after removing centring. Plastering done under soffit of R.C.C. roof slab meant for human habitation buildings shall be paid extra. This item shall not be applicable to factory made units. 	
	(1) Type A (nominal mix 1:1:2)(2) Type B (nominal mix 1: 1¹/₂: 3)	Per Cft ditto	82.55 82.55	334.55 291.35	cu.m	2915.65 2915.65	11816.30 10290.50		4) Composite rate shall be reduced by Rs: 5/50- P.Cft & Rs:12/- P.Cft if chenab	
	(3) (c) Type C (nominal mix 1: 1:2: 4)	ditto	82.55	291.33		2915.65	9476.35		sand and local sand respectively is used.	
	(a)(ii) Reinforced cement concrete in slab of rafts / strip	uno	02.33	200.5		2713.03	7470.55		sand and rocar sand respectively is used.	
	foundation, base slab of column and retaining walls; etc and									
	other structural members other than those mentioned in									

	MRS, BI-ANNUAL PERIO	D (1st Al	JGUST, 201	12 TO 31st J	IANUAR	Y, 2013) I	DISTRICT J	HANG	
Sr.	Description	F	Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	5(a) (i) above not requiring form work (i.e. horizental								
	shuttering) complete in all respects:-								
		Der Cft	49.20	260.75		1705.05	0527.55		
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	48.30	269.75	cu.m	1705.95	9527.55		
	(2) Type B (nominal mix 1: 1½: 3)	ditto	48.30	221.85		1705.95	7835.75		
	(3) Type C (nominal mix 1: 2: 4)	ditto	48.30	198.70	"	1705.95	7018.10		
	(b) Precast reinforced cement concrete and prestressed								
	reinforced cement concrete in columns, beams, lintels, stair								
	cases, shelves, etc.								
	(1) Type A (nominal mix 1: 1: 2)	Per Cft	62.05	302.30	cu.m	2191.60	10677.25		
	(2) Type B (nominal mix 1:1 ¹ / ₂ : 3)	ditto	62.05	258.85	"	2191.60	9142.60		
	(3) Type C (nominal mix 1: 2: 4)	ditto	62.05	236.05		2191.60	8337.30		
		J.S.			114				
	(c) Erecting and fixing in position, precast cement concrete	188			18				
	or stone slab in roofs or lintels, etc. lift unto 20 ft., (6m)	Per Cft	28.65	41.95	cu.m	1011.90	1481.65		
		reren	28.05		cu.m	1011.90	1401.05		
	including all charges.	1000		- 11/2	3				
	(d) Add extra labour for R.C. concrete in	Per Cft	13.65	4 Frence	cu.m	482.10	-		
	2nd and subsequent storeys.					102110			
	and and subsequent storeys.	(L'ann	ance (1	insparts					
7	Providing and casting in situ bored reinforced concrete piles							*851-1	Composite rate shall be reduced by
	with type C concrete (nominal mix 1: 2: 4), using 10% extra							to	Rs: 5/50 P.Cft & Rs:12/- P.Cft if chenab
	cement in dry mix, and course sand, including all labour and							851-10	sand and local sand respectively is used.
	material (except the cost of steel reinforcement and its								
	labour for bending and laying in position, etc. which will be								
	paid separately, including, screening & washing of shingle								
	and curing:-								
	i) 18 " (450 mm) dia pile	Per Rft	681.50	961.70	Metre	2235.30	3154.40		
	ii) 20" (500 mm) dia pile	Per Rft	765.60	1111.30	Metre	2511.15	3645.05		
	iii) 22" (550 mm) dia pile	Per Rft	902.85	1303.8	Metre	2961.35	4276.45		
	iv) 24" (600 mm) dia pile	Per Rft	1059.60	1557.70	Metre	3475.50	5109.3		
8	Fabrication of mild steel reinforcement bar cage for R.C.C.							*851-5	The rate includes wastage, overlaps,
	bored piles, including cutting, bending, laying in position,								etc. but does not apply to the laps and

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	F	Rate (British Sy	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	welding and fastening, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from the bars):-								spiral reinforcement which are specifically shown in the structural / working drawings of piles as per lapping requirements of design.		
	(a) plain bars	Per Cwt.	976.80	4389.30	100 kg	1922.85	8640.35				
	(b) deformed bars	ditto	976.80	5946.70	"	1922.85	11706.10				
9	Fabrication of mild steel reinforcement for cement concrete, including cutting, bending, laying in position, making joints and fastenings, including cost of binding wire and labour charges for binding of steel reinforcement (also includes removal of rust from bars):-		*					*851.5	The rate includes wastage, overlaps and chairs, etc.		
	(a) Plain bars	Per Cwt.	260.70	3847.75	100 kg	513.20	7574.30				
	(b) Deformed bars (Grade-40)	ditto	260.70	5530.75	ditto	513.20	10887.30				
	('c) Deformed bars (Grade-60)	ditto	260.70	5827.75	ditto	513.20	11472.00				
10	Precast cement concrete solid or face blocks (1:2:4), including cost of templates.	Per Cft	32.95	156.95	cu.m	1163.80	5543.45	20.2			
11	Precast cement concrete hollow blocks (1: 2: 4), including cost of templates and constructing walls thereof.	Per Cft	72.75	154.50	cu.m	2569.55	5456.95	20.2			
12	Providing and fixing ornamental cement jali 2" (50 mm) thick (1: 2: 4), without steel.	Per Sft	20.85	41.80	sq.m	224.35	449.75	20.1 to 20.4			
13	Extra labour for laying concrete plain or reinforced:										
	(a) above 20' (6 m) upto 40'(12 m) height	100Cft	1457.30	-	cu.m	514.70	-				
	(b) for every additional 10'(3 m) height.	100Cft	910.80	-	cu.m	321.70	-				
14	Extra labour for work of weirs, rail or road bridges, syphons, and concreting in superstructure	100Cft	364.30	-	cu.m	128.65	-				

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr. No.	Description	F	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks		
INO.		Unit	Labour	Composite	Unit	Labour	Composite	INO.			
15	Making reinforced cement concrete spout, including fixing in position (2 ¹ / ₂ ' x 6" x5") (760 mmx150 mm x 125 mm)	Each	260.70	405.55	Each	260.70	405.55	20.4			
16	Making holes upto 3"(75 mm) dia 18"(450 mm) depth in cement concrete or stone masonry walls and repairing.	Per hole	625.70	-	Each	625.70	-	20.1			
17	Extra labour for skipping concrete in wells.	100Cft	2213.20	-	cu.m	781.70	-	20.1			
18	Nicking concrete surface: (a) Cement concrete surface (b) Lime concrete surface	100Sft ditto	234.95 77.55		sq.m "	25.30 8.35	-				
19	Preparing, watering and ramming surface for laying concrete (for Headworks only):- (a) Horizontal floor (b) Glacis and crest (c) Inverted filters	100Sft ditto ditto	222.65 326.05 104.30		sq.m "	23.95 35.10 11.20	- - -				
20	Fabrication of high tensile steel prestressing cables for prestressed (post tensioned) concrete, including assembling by drawing the H.T. wire through metal spacer plate, inserting in helix core and taping or tying, sheathing in longitudinally welded metal corrugated sheath, positioning , anchorage with male and female set of anchorage cone, forming ducts for transverse cable, stressing cables with jack at both ends as per stressing schedule, maintaining stressing record and supply the same in the approved proforma to the Engineer-in-charge, making loop at blind end, including all materials required for it, grouting the cable ducts with cement, cutting projected ends and making good recesses, etc., complete in all respects.	100 Kg.	3134.70	30821.00	100 Kg.	3134.70	30821.00	*811-1 to 811-11	The rate includes wastage in cutting and breakage in stressing, etc.		
21	Fabrication of High Tensile steel reinforcement for prestressed (pretension) concrete work, including inserting wire in moulds, providing M.S. shear bars, spacers and lift hooks, male and	100kg	1901.80	28576.45	%kg	1901.80	28576.45		 The rate includes wastage in cutting and breakage in stressing,etc. 		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	R	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	female anchorage, tie down, struts, stressing cables, maintaining stress record and supply the same in approved proforma to the Engineer-in-charge, cutting wires and projecting ends and making good recesses, etc., complete in all respects.								 Quantity of H. T. wire will form basis of payment. This item shall not be applicable to factory made units. 		
22	Lifting, transporting and placing precast prestressed concrete B eam, Girder and other members (excluding battens) etc. in Position on the bridge to correct alignment and level, etc. complete		*					*811-1 to 811-11			
23	 i) Beam upto 50 ft. (15 m) length ii) Beam above 50 ft. (15m) upto 75 ft. (22.5m) length iii) Beam above 75ft. (22.5m) upto 100ft. (30m) length iv) Beam above 100ft. (30m) upto 150ft.(45m) length v) Beam above 150ft. (45m) length Providing and laying foam concrete 3 inch (75 mm) thick, 	100Cft 100Cft 100Cft 100Cft 100Cft Per Sft.	19.55	1259.70 1830.71 2368.20 3039.10 3689.65 51.00	cu.m cu.m cu.m cu.m cu.m	210.35	444.95 646.60 836.45 1073.40 1303.20 548.75				
	using cement sand in the ratio of 1:2 and aluminium powder at the rate of 0.2% of the cement, sand mix,	Fina	ance (Departi	ment						
24	Providing and fixing 6 in(150 mm). wide curved sheet of required shape fixed on face of the construction joint with G.I. screw,1.5 in (40 mm) long to cover construction joints vertically:-										
	i) aluminium sheet 1/16 in(1.5 mm) thick ii) G.I. sheet, 18 SWG	Per Rft. Per Rft.	10.70 11.00			35.10 36.10	280.10 252.70				
25	Providing and fixing 1/8" (3 mm) thick 3" (75 mm) wide aluminium strip on horizontal and vertical expansion joints in walls, columns, ceilings and floors etc., including cost of clips/screws etc., complete in all respects:-										

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	F	Rate (British S	ystem)	Rat	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	a) On interior surface (without mastic strip)	Per Rft.	9.80	84.45	Metre	32.15	277.00					
	b) On exterior surface (with mastic strip)	ditto	9.80	87.45		32.15	286.85					
26	Providing and fixing 1/16" (1.5 mm) thick copper flashing on expansion joints complete in all respects.	Per Sft.	10.45	95.60	Sq.m	112.45	1028.65					
27	Providing and fixing 6 in (150 mm). wideG.I. sheet 18SWG. stopper to expansion joint.	Per Rft.	3.65	66.25	Metre	11.95	217.30					
28	Providing embeding 10" (250 mm) wide ¹ / ₄ " (6 mm) thick rubber water stopper in expansion joints of R.C.C. roof	Per Rft.	14.70	61.50	Metre	48.20	201.65					
	slab complete in all respects.				W.							
29	Filling expansion joints with bitumen. sand & saw dust in	Per Rft			P.Metre/							
	ratio 1:2:2.	per inch width	2.30	19.40	Per 25 mm Width	7.55	63.65					
30	Filling expansion joints with bitumen.	Per Rft.	30.05		Metre	98.55	-					
31	Laying asphaltic mixture in expansion joints.	Per Rft.	31.90	Depart.	Metre	104.65	-		Material to be paid on actuals.			
32	Providing and fixing theremopore (foamed polythene) sheet in horizontal and vertical expansion joints:											
	a) 1" (25 mm) thick thermopore sheet	Per Sft.	4.15	9.10	Sq.m	44.65	97.90					
	b) 1 ¹ / ₂ " (40 mm) thick thermopore sheet	ditto	4.15	13.30	"	44.65	143.10					
33	Providing and laying damp proof course of cement concrete 1:2: 4(using cement, sand and shingle), including bitumen coating :-											
	(a) with one coat bitumen and one coat polythene sheet 500gauge											

	MRS, BI-ANNUAL PERIO	D (1st Al	JGUST, 20 ⁻	12 TO 31st .	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	I	Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	i) 1½" thick (40 mm)	100Sft	938.75		sq.m	101.00	409.40		
	ii) 2" thick (50 mm)	100Sft	938.75		sq.m	101.00	459.50		
	iii) 3" thick (75 mm)	100Sft	977.90	5320.90	sq.m	105.20	572.55		
	(b) with 2 coats of bitumen:								
	i) 1 ¹ /2" thick (40 mm)	100Sft	938.75	4249.60	sq.m	101.00	457.25		
	ii) 2" thick (50 mm)	100Sft	938.75	4714.70	sq.m	101.00	507.30		
	iii) 3" thick (75 mm)	100Sft	977.90	5765.15	sq.m	105.20	620.35		
			·		\				
34	Providing and laying damp proof course with cement sand	di h			dui:				
	plaster and bitumen coating:-	しる			12				
	(a) with one coat of bitumen and one coat of polythene sheet	7 28		-7	144				
	500 gauge :-	617 -	- 570	- 19/ 2	10,99				
		100		643	24				
	i) Ratio 1: 4		-00	0.2					
	a) ¹ / ₂ " thick (13 mm)	100Sft	880.00	2481.30	sq.m	94.70	267.00		
	b) ³ / ₄ " thick (20 mm)	100Sft	880.00	2713.95	sq.m	94.70	292.00		
	ii) Ratio 1:3								
	a) ½ " thick (13 mm)	100Sft	880.00	2556.50	sq.m	94.70	275.10		
	b) ³ / ₄ " thick (20mm)	100Sft	880.00	2802.95	sq.m	94.70	301.60		
	iii) Ratio 1:2								
	a) ¹ / ₂ " thick (13 mm)	100Sft	880.00			94.70	285.05		
	b) ³ / ₄ " thick (20 mm)	100Sft	880.00	2996.65	sq.m	94.70	322.45		
	(b) with 2 coats of bitumen:-								
	i) Ratio 1: 4								
	a) ½" thick (13 mm)	100Sft	880.00	2774.70	sq.m	94.70	298.55		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	ŀ	Rate (British Sy	/stem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	b) ¾" thick (20 mm)	100Sft	880.00	3007.75	sq.m	94.70	323.65					
	ii) Ratio 1:3											
	a) ½ " thick (13 mm)	100Sft	880.00	2850.65	sq.m	94.70	306.75					
	b) ¾ " thick (20 mm)	100Sft	880.00	3097.10	sq.m	94.70	333.25					
	iii) Ratio 1:2											
	a) ½ " thick (13 mm)	100Sft	880.00	3038.15	sq.m	94.70	326.90					
	b) ¾ " thick (20 mm)	100Sft	880.00	3407.05	sq.m	94.70	366.60					
35	Providing and laying vertical damp proof course with cement	1	*									
	sand plaster and bitumen coating:-	de f-			his							
	(a) with one coat of bitumen and one coat of polythene sheet	18 E			18							
	500 gauge:	E.	-6-	- 10	XII -							
	i) Ratio 1: 4	100			3							
	a) ½" thick (13 mm)	100Sft	880.00	2386.20	sq.m	94.70	256.75					
	b) ¾" thick (20 mm)	100Sft	880.00	2619.30	sq.m	94.70	281.85					
	ii) Ratio 1:3			a.								
	a) ½ " thick (13 mm)	100Sft	880.00	2461.85	sq.m	94.70	264.90					
	b) ¾ " thick (20 mm)	100Sft	880.00	2708.30	sq.m	94.70	291.40					
	iii) Ratio 1:2											
	a) ½ " thick (13 mm)	100Sft	880.00	2649.35	sq.m	94.70	285.05					
	b) ¾ " thick (20 mm)	100Sft	880.00	3018.25	sq.m	94.70	324.75					
	(b) with 2 coats of bitumen:-											
	i) Ratio 1: 4											
	a) ½" thick (13 mm)	100Sft	880.00	2774.70	sq.m	94.70	298.55					
	b) ¾" thick (20 mm)	100Sft	880.00	3007.75	sq.m	94.70	323.65					

	MRS, BI-ANNUAL PER	RIOD (1st Al	JGUST, 201	12 TO 31st .	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	ŀ	Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) Ratio 1:3	10056	000.00	2950.20		04.70	207.70		
	a) ¹ / ₂ " thick (13 mm) b) ³ / ₄ " thick (20 mm)	100Sft 100Sft	880.00 880.00	2850.30 3096.75	sq.m	94.70 94.70	306.70 333.20		
	0) % unck (20 mm)	100511	880.00	3090.75	sq.m	94.70	555.20		
	iii) Ratio 1:2								
	a) ½ " thick (13 mm)	100Sft	880.00	3037.90	sq.m	94.70	326.90		
	b) ¾ " thick (20 mm)	100Sft	880.00	3406.70	sq.m	94.70	366.55		
36	Grouting concrete between, the grooves of gates, including	100Cft	4207.50) - \	cu.m.	1486.10	-		
	shuttering.		<u></u>						
25		10000	100.05		Aut:	12.00			
37	Chiesel dressing concrete surface on sides of grooves.	100Sft	129.25		sq.m	13.90	-		
38	Laying and ramming dry ballast or kankar.	100Cft	1480.05		cu.m	522.75			
50		rooen	1400.05	- 19/ 1	cu.m	522.15	-		
39	Hoisting and placing in position R.C.C. shelves.	per No.	46.80		per No.	46.80	-		
		-	SP	012	-				
40	Breaking brick ballast, screening and stacking:-	(Thing)	ana ina di	Departi	an sea f				
	(a) 2"(50 mm) ring	100Cft.	1138.50	uningin tata ter	cu.m	402.10	-		
	(b) 1 ¹ / ₂ "(40 mm) ring	ditto	1275.10	-	"	450.35	-		
	(c) 1" (25 mm) ring	ditto	1480.05	-	"	522.75	-		
	(d) Jhama ballast ¾"(20 mm) ring	ditto	1707.75	-	"	603.20	-		
41	Supplying and fixing broken glasses on court yard walls,	Per Rft	35.50	75.90	metre	116.45	248.95		
41	including 1:3: 6 cement concrete coping.	r ci Kit	55.50	75.90	metre	110.45	240.93		
	including 1.5. 6 content concrete coping.								
42	Crushing stone ballast by machine.	100Cft	1138.50	-	cu.m.	402.10	-		This does not include the charges
									for working of crushers, but includes
									manual labour for carriageof stone to
									crusher within three chains (90 m)
									and also stacking the product after
									crushing within three chains (90 m).

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	F	ate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
43	Breaking stone ballast screened and stacked:-											
	(a) 2" ring (50 mm)	100Cft.	1275.10	-	cu.m.	450.35	-					
	(b) 1½ " ring (40 mm)	ditto	1480.05	-		522.75	-					
	(c) 1" ring (25 mm)	ditto	1707.75	-		603.20	-					
	d) ½ " ring (13 mm)	ditto	2277.00	-		804.25	-					
	(e)1/8" to ¼" ring (3 mm to 6 mm)	ditto	3870.90	-	"	1367.20	-					
44	Screening and stacking stone ballast shingle or bajri, etc.	100Cft.	364.30		cu.m.	128.65	-					
45	Washing ballast, bajri or shingle.	100Cft.	364.30		cu.m.	128.65	-					
	Erecting and carting sun shades of precast R.C. concrete upto 5' x 2 ¹ / ₂ ' (1.50 m x 0.76 m)	Each	204.45		Each	204.45	-					

Specification numbers correspond to book of standard specification of Road and Bridge Construction, "1971"

Fimance Department

7. BRICK WORK

1 Rates for all finsihed works include the removal of surplus debris, unused material and byproducts.

2 The rates apply to all sizes of bricks, including the modular bricks of size 8"x4" x4" (200x100x100 mm) nominal.

	MRS, BI-ANNUAL PE	RIOD (1s	t AUGUST, 2	2012 TO 31st	JANUA	RY, 2013)) DISTRICT JH	IANG	
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec. No.	Remarks
INO.		Unit	Labour	Composite	Unit	Labour	Composite	NO.	
	Pacca brick work in mud mortar in buildings:							21.1 to	Masonry of boundary wall to be considered as masonry other than
	i) in foundation and plinthii) in ground floor	100Cft. ditto	1847.65 2446.90	11714.65 12313.90	cu.m ditto	652.60 864.25	4137.60 4349.25	21.4	building.
				*					The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.
2	Add extra labour on item No. 1 for brick work in:-		/ 1	9					
	i) first floor	100Cft.	481.80		cu.m	170.15	-		
	ii) second floor	ditto	1081.10		ditto	381.85	-		
	iii) third floor	ditto	1680.35		ditto	593.50	-		
	iv) fourth & subsequent floors	ditto	2696.75		ditto	952.50	-		
3	Pacca brick work in mud mortar other than building:-	1 1			53			21.1 to 21.4	Same remarks as against item No. 1 above
	i) upto 20 ft. (6.1 m) height	100Cft.	2519.10	12386.10	cu.m	889.75	4374.75		
	ii) extra labour for every 5 ft. (1.5 m)	ditto	481.80	Demont	ditto	170.15	-		
	additional height, or part thereof.	1211	1017-0000 000000	sanadharan p					
4	Pacca brick work in foundation and plinth in:-							ditto	Same remarks as against item No. 1 above.
	i) Cement, sand mortar:-								
	Ratio 1:2	100Cft.	2430.25	16513.45	cu.m	858.30	5832.55		
	Ratio 1:3	ditto	2430.25	15503.65	ditto	858.30	5475.90		
	Ratio 1:4 Ratio 1:5	ditto	2430.25 2430.25	14897.75 14493.85	ditto	858.30	5261.90 5119.25		
	Ratio 1:5 Ratio 1:6	ditto ditto	2430.25 2430.25	14493.85 14190.35	ditto ditto	858.30 858.30	5012.05		
	Ratio 1:0	ditto	2430.25	13991.65	ditto	858.30	4941.85		
	Ratio 1:8	ditto	2430.25	13817.20	ditto	858.30	4880.25		
	ii) lime, cement sand mortar:-							21.1	The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Cft.	2430.25	14498.30	cu.m	858.30	5120.80		
	Ratio 1:1:7	ditto	2430.25	14276.90	ditto	858.30	5042.60		
	Ratio 1:1:8	ditto	2430.25	14097.85	ditto	858.30	4979.35		
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	2430.25	13947.65 13835.10	ditto	858.30	4926.30		
	Kaulo 1:1:10	utto	2430.25	13833.10	ditto	858.30	4886.55		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	iii) lime, sand mortar 1:2	100Cft.	2430.25	13657.15	cu.m	858.30	4823.70	ditto	ditto			
5	Pacca brick work in ground floor:-							ditto	i) The composite rate is to			
	i) cement, sand mortar:-								be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.			
	Ratio 1:2	100Cft.	3211.65	17294.85	cu.m	1134.35	6108.55		ii) Masonry of boundary wall			
	Ratio 1:3	ditto	3211.65	16285.05	ditto	1134.35	5751.90		to be considered as masonry			
	Ratio 1:4	ditto	3211.65	15679.20	ditto	1134.35	5537.90		other than building.			
	Ratio 1:5	ditto	3211.65	15275.25	ditto	1134.35	5395.20					
	Ratio 1:6 Ratio 1:7	ditto	3211.65 3211.65	14971.80	ditto	1134.35	5288.05					
	Ratio 1:7 Ratio 1:8	ditto ditto	3211.65	14773.05 14597.55	ditto ditto	1134.35 1134.35	5217.85 5155.85					
	Kauo 1.8	uno	5211.05	14597.55	unto	1154.55	5155.65					
	ii) lime, cement, sand mortar:-		1						The rate of lime mortar also			
					111				includes grinding of mortar.			
	Ratio 1:1:6	100Cft.	3211.65	15279.75	cu.m	1134.35	5396.80					
	Ratio 1:1:7	ditto	3211.65	15061.00	ditto	1134.35	5319.55					
	Ratio 1:1:8	ditto	3211.65	14879.25	ditto	1134.35	5255.35					
	Ratio 1:1:9	ditto	3211.65	14729.05	ditto	1134.35	5202.30					
	Ratio 1:1:10	ditto	3211.65	14616.95	ditto	1134.35	5162.70					
	iii) lime, sand mortar 1:2	100Cft.	3211.65	14438.60	cu.m	1134.35	5099.70		The rate of lime mortar also includes grinding of mortar.			
		98	MARIN CE	Dangaanti	THE CAN							
6	Add extra labour on item No. 5 for brickwork			Berne 11	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1							
	in:-											
	i) first floor	100Cft.	481.80		cu.m	170.15	_					
	ii) second floor	ditto	1081.10		ditto	381.85	-					
	iii) third floor	ditto	1680.35		ditto	593.50	-					
	iv) fourth & subsequent floors	ditto	2696.75		ditto	952.50	-					
7	Pacca brick work other than building upto 10ft. (3 m)							21.1	i) The composite rate is to be			
	height.							to 21.5	reduced by 7% and 14%, if 2nd or 3rd class bricks are used.			
	i) cement, sand mortar:-								ii) Workshops, godowns,, bins,			
	Ratio 1:2	100Cft.	2816.90	16900.10	cu.m	994.95	5969.10		house type godowns, reservoirs,			
	Ratio 1:2	ditto	2816.90	15890.30	ditto	994.95	5612.45		filter beds, storage tanks, wells,			
	Ratio 1:4	ditto	2816.90	15284.40	ditto	994.95	5398.45		screening chambers, collecting			
	Ratio 1:5	ditto	2816.90	14880.50	ditto	994.95	5255.80		tanks, manholes etc. are to be			
	Ratio 1:6	ditto	2816.90	14577.00	ditto	994.95	5148.60		treated as masonry other than			
	Ratio 1:7	ditto	2816.90	14378.30	ditto	994.95	5078.40		buildings.			
	Ratio 1:8	ditto	2816.90	14203.85	ditto	994.95	5016.80		-			

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	ii) lime, cement, sand mortar:-								The rate of lime mortar also includes grinding of mortar.			
	Ratio 1:1:6	100Cft.	2816.90	14884.95	cu.m	994.95	5257.35					
	Ratio 1:1:7 Ratio 1:1:8	ditto ditto	2816.90 2816.90	14663.55 14484.50	ditto ditto	994.95 994.95	5179.15 5115.95					
	Ratio 1:1:9	ditto	2816.90	14334.20	ditto	994.95	5062.85					
	Ratio 1:1:10	ditto	2816.90	14221.75	ditto	994.95	5023.10					
	iii) lime, sand mortar 1:2	100Cft.	2816.90	14043.80	cu.m	994.95	4960.25		ditto			
8	Add extra labour on item No. 7, for every 10ft.(3 m) additional height, or part thereof.	100Cft.	481.80		cu.m	170.15	-					
9	Extra labour for arch work in brick masonry, including labour for centring and decentring.	100Cft.	887.05	9-1	cu.m	313.30	-	21.5				
10	Extra for pacca brick work in steining of wells or any other	100Cft.	587.40	1177.80	cu.m	207.45	416.00	21.1	The composite rate is to be			
	circular masonry.	- 85			720			to 21.4	reduced by 7% and 14%, if 2nd or 3rd class bricks are used.			
		100			1 566			21.4	Sid class blicks are used.			
11	Extra labour for profile and flared walls.	100Cft.	202.05	; ;	cu.m	71.35	-					
12	Extra labour for pacca brick work in piers and abutment:-				23							
	i) from 10ft. to 20ft. (3 m to 6 m) height	100Cft.	238.55		cu.m	84.25	-					
	ii) above 20 ft. (6 m) height.	100Cft.	481.80	Daquant.	cu.m	170.15	-					
13	Extra for face work (half brick thick) using special bricks instead of first class bricks.	100Cft.		3058.40	cu.m		1080.25		This item is to be executed only under the written permission of Superintending Engineer.			
14	Reinforced brick work in lintel of openings, laid in 1:3	Per Cft.	80.05	215.30		2827.75	7604.40					
14	cement mortar, including all labour, material, forms, moulds, lifting & shuttering, etc, (but excluding cost and labour of steel reinforcement which shall be paid for separately).	Fer Cit.	80.03	215.50	cu.m	2821.15	7604.40					
15	Extra for dressing or chamfering bricks for:-											
	a) special architectural bricksb) all other purposes	100 Nos. ditto	1533.65 766.80	-	% Nos. ditto	1533.65 766.80	-					
16	Perforated pacca brick walling half brick thick, in ground floors:-							21.1 to 21.4	The composite rate is to be reduced by 7% and 14%, if 2nd or 3rd class bricks are used.			
	i) mud mortar	100 Sft.	1221.65	3692.00	Sqm.	131.45	397.25	21.4	Sid class offers are used.			

	MRS, BI-ANNUAL P	IANG							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	1609.50	5133.90	sq.m.	173.20	552.40		
	Ratio 1:3	ditto	1609.50	4881.20	ditto	173.20	525.20		
	Ratio 1:4	ditto	1609.50	4730.00	ditto	173.20	508.95		
	Ratio 1:5	ditto	1609.50	4629.00	ditto	173.20	498.10		
	Ratio 1:6	ditto	1609.50	4558.05	ditto	173.20	490.45		
	Ratio 1:7	ditto	1609.50	4502.95	ditto	173.20	484.50		
	Ratio 1:8	ditto	1609.50	4462.45	ditto	173.20	480.15		
	iii) lime, cement sand mortar								The rate of lime mortar also includes grinding of mortar.
	Ratio 1:1:6	100Sft.	1609.50	4630.10	sq.m	173.20	498.20		includes grinning of mortain
	Ratio 1:1:7	100Sft.	1609.50	4574.15	sq.m	173.20	492.20		
	Ratio 1:1:8	100Sft.	1609.50	4532.70	sq.m	173.20	487.70		
	Ratio 1:1:9	100Sft.	1609.50	4491.90	sq.m	173.20	483.35		
	Ratio 1:1:10	100Sft.	1609.50	4467.95	sq.m	173.20	480.75		
		182			7 82				
	iv) lime, sand mortar 1:2	100Sft.	1609.50	4417.80	sq.m	173.20	475.35		ditto
17	Add extra labour on item No. 16 for pacca brick work in:-	1997		/عزمت:	-49°				
17	ride onlie mood on nom two. To for paced offer work m.	3	Ab		63				
	i) first floor	100Sft.	243.25		sq.m	26.15	-		
	ii) second floor	ditto	538.20		ditto	57.90	-		
	iii) third floor	ditto	842.55		ditto	90.65	-		
	iv) fourth & subsequent floors	ditto	1298.65	MANET FRANK	ditto	139.75	-		
18	Perforated pacca brick walling one brick thick, in ground							21.1	The composite rate is to be
	floor:							to	reduced by 7% and 14%, if 2nd or
								21.4	3rd class bricks are used.
	i) mud mortar	100Sft.	1718.65	6652.15	sq.m	184.95	715.75		
	ii) cement, sand mortar:-								
	Ratio 1:2	100 Sft.	2418.60	9460.20	sq.m	260.25	1017.90		
	Ratio 1:2	ditto	2418.60	8955.30	ditto	260.25	963.60		
	Ratio 1:5	ditto	2418.60	8652.35	ditto	260.25	931.00		
	Ratio 1:5	ditto	2418.60	8450.40	ditto	260.25	909.25		
	Ratio 1:5	ditto	2418.60	8308.50	ditto	260.25	894.00		
	Ratio 1:0	ditto	2418.60	8198.00	ditto	260.25	882.10		
	Ratio 1:8	ditto	2418.60	8112.15	ditto	260.25	872.85		
	iii) lime, cement, sand mortar:-								The rate of lime mortar also
	Ratio 1:1:6	100Sft.	2418.60	8452.65	sq.m	260.25	909.50		includes grinding of mortar
	Ratio 1:1:7	ditto	2418.60	8339.35	ditto	260.25	897.30		
	Ratio 1:1:8	ditto	2418.60	8252.50	ditto	260.25	887.95		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	Ratio 1:1:9 Ratio 1:1:10	ditto ditto	2418.60 2418.60	8177.30 8122.40	ditto ditto	260.25 260.25	879.90 873.95					
	iv) lime, sand mortar 1:2	100Sft.	2418.60	8030.85	sq.m	260.25	864.10		ditto			
19	Add extra labour on item No. 18 for perforated pacca brick work in:-											
	 i) first floor ii) second floor iii) third floor iv) fourth & subsequent floors 	100Sft. ditto ditto ditto	361.35 810.80 1260.25 2022.55		sq.m ditto ditto ditto	127.65 286.40 445.15 714.40	- - -					
20	Fire brick masonry in fireclay mortar:-i) upto 20 ft. (6.10 m) height including all charges.	Per Cft.	30.50	606.20	cu.m	1077.90	21411.20	21.1 to 21.2				
	ii) Extra for every 5 ft. (1.5 m) additional height, or part thereof.	100Cft.	481.80		ditto	170.15	-		A&C No.I dated 2.9.1998			
21	First class brick walling laid in 1:3 cement sand mortar, reinforced with 1" (25 mm) wide 18 gauge hoop iron:-			(کارت	L.S.			21.19				
	 4¹/₂" (113 mm) thick walling with hoop iron, bonding 6" (150 mm) apart. 	100Sft.	1360.25	7363.35	sq.m	146.35	792.30					
	 ii) 4¹/₂" (113 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	100Sft.	1217.05	6779.05	sq.m	130.95	729.45					
	 iii) 3" (75 mm) thick walling with hoop iron, bonding 6" (150 mm) apart. 	ditto	1076.45	5481.50	ditto	115.85	589.80					
	 (150 mm) upart. iv) 3" (75 mm) thick walling with hoop iron, bonding 12" (300 mm) apart. 	ditto	861.15	4776.30	ditto	92.65	513.95					
22	Ghilafi work (1 ¹ /2 brick thick wall)	100Cft.	2461.70	7812.95	cu.m	869.45	2759.55	21.18				
23	Dry brick pitching	100Cft.	1498.20	11218.20	cu.m	529.15	3962.25	21.1				
24	Sun dried bricks in mud mortar	100Cft.	2072.40	2907.90	cu.m	731.95	1027.05	21.16				
25	Pise wall (mud walling)	100Cft.	1100.90		cu.m	388.85	-	21.17				
26	Eave brick moulded, weathered and throated with back brick or drip course cornice, in 1:3 cement mortar:-							21.1 to 21.2				
	 i) 3" (75 mm) thick drip course cornice ii) 4¹/₂" (113 mm) thick drip course cornice. iii) 4¹/₂" (113 mm) thick eave brick with back brick. 	Rft. ditto ditto	15.50 17.60 12.00	44.35 88.30 103.00	Metre ditto ditto	50.85 57.75 39.35	145.45 289.60 337.85		correction vide A&C No.I dated 2.9.98			

	MRS, BI-ANNUAL PE) DISTRICT J	HANG						
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
27	Laying dressed or moulded brick cornices in 1:6 cement mortar, plastering or painting complete:-							21.1 to 21.2	
	 i) 1 brick ii) 2 bricks iii) 3 bricks iv) 4 bricks 	Rft. ditto ditto ditto	17.60 25.95 34.65 43.55	30.85 66.40 102.00 141.15	Metre ditto ditto ditto	57.75 85.10 113.65 142.85	101.20 217.80 334.55 462.95		
28	Cleaning bricks dismantled from kacha pacca masonry	1,000 Nos	637.55		1,000 Nos	637.55	-		
29	Scraping bricks dismantled from pacca masonry	1,000 Nos	1202.25	*	1,000 Nos	1202.25	-		
30	Supplying and filling sand under floor; or plugging in wells.	100Cft.	151.80	1231.80	cu.m	53.60	435.05		
	Providing and laying 2" (50 mm) thick and 15" (375 mm) projected tile band, laid in 1:2 cement sand mortar, with hoop iron 1" (25 mm) wide 18 gauge flat iron sheet 9" apart. First class brick tiles clad by laying tiles in stretcher course in cement sand mortar reinforced with 18 SWG	Rft.	65.20	118.45	Metre	213.85	388.50		This item is to be executed only under the written permission of the
	hoop iron strips bonding placed at 2.0' (600 mm) apart horizontally, and at 1.0' (300 mm) interval vertically.			X. G.					Superintending Engineer.
	i) 1:3 ii) 1:4	100Sft. ditto	1217.05 1217.05	8100.55 7858.20	sq.m ditto	130.95 130.95	871.60 845.55		
33	Chamfering sides of head regulators and masonry walls to increase width.	Per Sft.	34.75		sq.m	373.90	-		
34	Replacing kallar eaten bricks	Each No.	27.15	33.20	Each	27.15	33.20		
35	Repairing corners of bridges and other hydraulic masonry works	Each No.	173.80	241.65	Each	173.80	241.65		
36	Extra labour for drains of bath rooms, etc.	Per Lft.	14.70		Metre	48.20			
37	Maroo corners	Each Corner	94.00		Each Corner	94.00			Payable in addition to brick work

8. STONE MASONRY

- 1 The composite rates do not include the carriage of stone or spawl which will be paid separately by road and/or rail whichever means of transport is adopted. The supply and carriage to site of work of all other materials is included in the composite rates.
- 2 The payment of carriage of stone or spawl will be made on the basis of the actual stack measurement (without any reduction factor) of the stone or spawl carried.
- 3 Where the stone or spawl is issued from stock and the contractor is paid for its carriage and/or labour only; or where the stone or spawl is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall form the basis of the payment of supply or carriage of stone or spawl. The quantity of finished and completed item of work shall form the basis of laying.
- 4 Rates for all finished work include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Random, rubble masonry (uncoursed), in foundation and plinth:				調			22.10, 22.11				
	a) dry masonry	100 Cft.	2541.00	3327.00	cu.m	897.50	1175.10					
	b) in mud mortar	100 Cft.	3177.90	4152.90	cu.m	1122.45	1466.80					
	c) in lime, sand mortar 1:2	100 Cft.	4857.60	7580.40	cu.m	1715.70	2677.40					
	d) in cement, sand mortar		~~~~	1000								
	i) ratio 1:3	100 Cft.	4857.60	10673.70	cu.m	1715.70	3769.95					
	ii) ratio 1:4	100 Cft.	4857.60	9764.90	cu.m	1715.70	3448.95					
	iii) ratio 1:6	100 Cft.	4857.60	8724.75	cu.m	1715.70	3081.60					
	iv) ratio 1:8	100 Cft.	4857.60	8149.20	cu.m	1715.70	2878.30					
2	Coursed rubble masonry hammer dressed, in foundation and plinth:							22.8				
	a) dry masonry	100 Cft.	3128.40	3914.40	cu.m	1104.95	1382.55					
	b) in mud mortar	100 Cft.	4402.20	5377.20	cu.m	1554.85	1899.25					
	c) in lime, sand mortar 1:2	100 Cft.	5413.65	7920.50	cu.m	1912.10	2797.50					
	d) in cement, sand mortar:											
	i) ratio 1:3	100 Cft.	5413.65	10958.85	cu.m	1912.10	3870.65					
	ii) ratio 1:4	100 Cft.	5413.65	10151.00	cu.m	1912.10	3585.35					
	iii) ratio 1:6	100 Cft.	5413.65	9226.10	cu.m	1912.10	3258.65					
	iv) ratio 1:8	100 Cft.	5413.65	8717.65	cu.m	1912.10	3079.05					
3	Random rubble masonry (uncoursed) in ground floor or 20 ft.(6 m) height, building/other than building.							22.10				
	a) dry masonry	100 Cft.	2834.70	3620.70	cu.m	1001.20	1278.85					
	b) in mud mortar	100 Cft.	3814.80	4789.80	cu.m	1347.40	1691.75					

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	 c) in lime, sand mortar 1:2 d) in cement, sand mortar: 	100 Cft.	5266.80	7989.60	cu.m	1860.25	2821.95						
	i) ratio 1:3	100 Cft.	5266.80	11082.90	cu.m	1860.25	3914.50						
	ii) ratio 1:4	100 Cft.	5266.80	10174.10	cu.m	1860.25	3593.50						
	iii) ratio 1:6 iv) ratio 1:8	100 Cft. 100 Cft.	5266.80 5266.80	9133.95 8558.40	cu.m cu.m	1860.25 1860.25	3226.10 3022.85						
4	Coursed rubble masonry hammer dressed, in ground floor or 20 ft. (6 m) height, building/other than building.							22.8					
	a) dry masonry	100 Cft.	3649.80	4435.80	cu.m	1289.10	1566.75						
	b) in mud mortar	100 Cft.	5445.00	6411.60	cu.m	1923.15	2264.60						
	c) in lime, sand mortar 1:2	100 Cft.	6081.90	8588.75	cu.m	2148.15	3033.55						
	d) in cement, sand mortar:			*)									
	i) ratio 1:3	100 Cft.	6081.90	11627.10	cu.m	2148.15	4106.70						
	ii) ratio 1:4	100 Cft.	6081.90	10819.25	cu.m	2148.15	3821.35						
	iii) ratio 1:6	100 Cft.	6081.90	9894.35	cu.m	2148.15	3494.70						
	iv) ratio 1:8	100 Cft.	6081.90	9385.90	cu.m	2148.15	3315.10						
5	Ashlar block in course or scabbled masonry (including	100			I Sin	2		22.5					
-	dressing, etc.,) in ground floor or 20 ft. (6 m) height,	100	1	in 60 /	- 183			&					
	building/other than building.	3	2000	1000				22.6					
			263 V	and L	SS.								
	a) in lime, sand mortar 1:2	100 Cft.	16044.60	18449.35	cu.m	5666.95	6516.30						
	b) in cement, sand mortar:												
	i) ratio 1:3	100 Cft.	16044.60	20511.80	cu.m	5666.95	7244.75						
	ii) ratio 1:4	100 Cft.	16044.60	19905.95	cu.m	5666.95	7030.80						
	iii) ratio 1:6	100 Cft.	16044.60	19219.25	cu.m	5666.95	6788.25						
6	Ashlar fine masonry (including dressing, etc.) in ground floor or 20 ft. 6 m) height, building/other than building.							22.3 (A) to (C) &					
	a) in lime, sand mortar 1:2	100 Cft.	29165.40	31359.25	cu.m	10301.20	11076.10	22.4					
	b) in cement, sand mortar:	100 Cft	20165 40	22200 50		10201 20	11440.25						
	i) ratio 1:3 ii) ratio 1:4	100 Cft. 100 Cft.	29165.40 29165.40	32390.50 32087.10	cu.m	10301.20 10301.20	11440.35 11333.15						
	iii) ratio 1:6	100 Cft. 100 Cft.	29165.40	31750.55	cu.m cu.m	10301.20	11214.30						
7	Extra labour on items 3, 4, 5 & 6 above for work in:-												
	i) first floor	100 Cft.	679.80	-	cu.m	240.10	-						
	ii) second floor	100 Cft.	1511.15	-	cu.m	533.75	-						
	iii) third floor	100 Cft.	2360.70	-	cu.m	833.80	-						
	iv) fourth floor	100 Cft.	3731.90	-	cu.m	1318.10	-						
8	Extra labour on items 3,4,5 & 6 above for every 5 ft.(1.5 m) additional height, other than building, or part thereof.	100 Cft.	599.30	-	cu.m	211.65	-						

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
9	Extra labour for arch work in stone masonry, including centering and decentring, etc.	100 Cft.	1748.80	-	cu.m	617.70	-	22.12				
10	Extra labour for:-							22.7				
	a) coping and caps, etc.b) cornice & string course	100 Cft. 100 Rft.	8458.55 8458.55	- -	cu.m Rm.	2987.55 277.45	-					
11	Dressing stones:- a) hammer dressed b) rough tooled dressed c) chisel dressed d) fine dressed	100 Sft. 100 Sft. 100 Sft. 100 Sft.	3260.40 6156.50 7460.65 15449.30		sq.m sq.m sq.m sq.m	350.80 662.45 802.75 1662.35		22.2	 i) This rate of dressing shall be paid only when the supply of undressed stone is made. ii) In case of masonry, dressing is already included and this rate shall not be added thereto. iii) Only dressed surface of stone shall be measured. 			
12	Dhajji walling 5"x5" (125 mmx125 mm) thick deodar framing with stone laid in 1:6 cement sand mortar, and 1:4 cement sand plaster on both sides.	100 Sft.	6436.40	11682.50	sq.m	692.55	1257.05	22.13				
13	Providing and fixing stone blocks from 2 Cft. (0.6 cu.m) to 6 Cft (0.17 cu.m). each including lift upto 20 ft. (6 m)	Per Cft.	282.05	309.35	cu.m	9962.00	10926.25					
14	Providing and fixing stone blocks, under 2 Cft. (06 cu.m) each including lift upto 20 ft. (6 m)	Per Cft.	160.85	191.15	cu.m	5681.20	6751.40					

9. ROOFING

Rates for all finished works include the removal of surplus debris unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	First class tile roofing, consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m hot bitumen coating sand blinded, provided over 2 layers of tiles 12"x6"x1¼" (300x150x30 mm) laid in 1:6 cement mortar with ½" (13 mm) thick sand wiched layer of 1:6 cement mortar, including 1:2 cement pointing underside of tiles, complete, including curing, etc.	100Sft.	4363.15	9561.05	sq.m	469.50	1028.75	23.1	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
2	Second class tile roofing consisting of 4" (100 mm) earth and 1" (25 mm) mud plaster with Gobri leeping over ½" (13 mm) thick cement plaster 1:6 with 34 lbs. per %Sft or 1.72 Kg/sq.m of hot bitumen coating sand blinded, provided over one layer of 12"x6"x2" (300x150x50 mm) tiles laid in 1:6 cement mortar, including 1:2 cement pointing underneath of tiles complete including curing, etc.	100Sft.	3366.00	7207.75	sq.m	362.20	775.55	23.2	ditto			
3	Covering mud roof with coal tar, and fine sand.	100Sft.	184.35	1043.40	sq.m	19.85	112.25	23.1 to 23.2	ditto			
4	 Filling spaces in between:- a) Wooden battens over beams, filled with deodar wood pieces (spacers). b) RCC battens, filled with CC block 1:3:6. c) Spaces filled with bricks. 	100Sft. roof area -ditto- -ditto-	347.60 645.50 178.80	2003.25 982.20 614.55	sq.m	37.40 69.45 19.25	215.55 105.70 66.15		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.			
5	Single layer of tiles 9"x4½"x1½" (225x113x40 mm) laid over 4"(100 mm) earth and 1" (25 mm) mud plaster without Bhoosa, grouted with cement sand 1:3 on top of RCC roof slab, provided with 34 lbs. per %Sft. or 1.72 Kg/Sq.m bitumen coating sand blinded.	100Sft.	1068.55	5654.65	sq.m	115.00	608.45	23.1	ditto			
6	Jack arch roofing 4 ¹ / ₂ " (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with 3" (75 mm)							23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred.			

	MRS, BI-ANNUAL PERI	NG							
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 earth and 1" (25 mm) plaster, soffits of arches cement plaster 1:6 and ¹/₂" (13 mm) thick. The rate also includes bitumen coating, centring, laying skew bricks in cement mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:- a) cement concrete in haunches 1:6:12. 	100Sft.	4799.50	15045.05	sq.m	516.45	1618.85		Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
7	 b) cement concrete in haunches 1:3:6. Jack arch roofing 4¹/₂" (113 mm) thick laid in 1:5 cement mortar, including an average depth of 4" (100 mm) cement concrete in haunches and over crown, with ¹/₂" (13 mm) cement plaster 1:6 on top (except earth filling mud plaster and gobri) soffit of arches cement plastered. The rate also 	ditto	4799.50	16080.95	ditto	516.45	1730.30	23.3 to 23.5	For steel part and its erection etc. items 10 & 14 under Chapter IRON WORK be referred. Add extra 13%, 32% & 51% on
	includes bitumen coating, centring, laying skew bricks in cement sand mortar (1:3), and encasing exposed flanges of the joints with fine cement concrete 1:2:4 using stone aggregate:-								labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively.
	a) cement concrete in haunches 1:6:12.b) cement concrete in haunches 1:3:6.	100Sft. ditto	3900.60 3900.60	14648.60 14987.05	sq.m ditto	419.70 419.70	1576.20 1612.60		
8	Extra for vaulted jack arch roofing.	100Sft.	939.85		sq.m	101.15	-		ditto
9	Jack arch roofing of shingle and cement concrete 1:3:6, 4½" (113 mm) thick at crown, with ½" (13 mm) cement plaster including cost of supplying, erecting and dismantling centring.	100Sft.	5441.70	12912.40	sq.m	585.55	1389.35	23.3 to 23.5	ditto
10	Earth filling over roof including watering, ramming with 1" (25 mm) mud plaster finished, with gobri leeping:							23.1 to 23.3	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th
	a) 3" (75 mm) thick earth filling and 1" (25 mm) mud plaster	100Sft.	465.05	701.55	sq.m	50.05	75.50		& sub- sequent floors, respectively.
	b) 4" (100 mm) thick earth filling and 1" (25mm) mud plaster	100Sft.	609.05	887.55	sq.m	65.55	95.50		
11	1/8" (3 mm) thick gobri leeping on roofs or floors.	100Sft.	65.45	78.00	sq.m	7.05	8.40	ditto	ditto
12	Two coats of bitumen laid hot using 34 lbs. per %Sft, or	100Sft.	364.30	2008.45	sq.m	39.20	216.10	23.1	

	MRS, BI-ANNUAL PER	NG							
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	1.72 Kg per square metre over roof and blinded with sand at one Cft. per %Sft. (0.003 cu.m per sq.m)								
13	Providing & Fixing corrugated galvanized iron sheets with G.I. bolts, nuts, limpet and bitumen washers, wind ties, complete in all respects without valleys and ridges:-							23.7	Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23% on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively,
	a) 20 BWG b) 22 BWG c) 24 BWG	100Sft. 100Sft. 100Sft.	695.20 695.20 695.20	14392.55 12387.85 9995.50	sq.m sq.m sq.m	74.80 74.80 74.80	1548.65 1332.95 1075.50		on items 13 to 18.
14	Khassi parnalas in cement, sand mortar 1:2, 12" (300 mm) outside width finished smooth with a floating coat of neat cement.	Rft.	49.35	67.40	Metre	161.85	221.05	23.10	
15	Khuras on roof 2'x2'x6" (600 x 600 x 150 mm)	Each	185.35	350.45	Each	Each	350.45	23.10	
16	Bottom Khuras of brick masonry in cement mortar 1:6, 4'x2'x4½" (1200x600x113 mm) over 3" (75 mm) cement concrete 1:4:8.	Each	185.35	657.45	Each	185.35	657.45	23.10	
17	Plain galvanized iron sheets 22 SWG rain water down pipe including clamp and fixing in position.				LGP Br				
	 a) 4" (100 mm) diameter down pipe b) 5" (125 mm) diameter down pipe 	Per Rft. Per Rft.	39.15 39.15	146.75 170.10	Metre Metre	128.40 128.40	481.35 557.95		
18	Plain galvanized iron sheet flashing, 22 gauge.	Per Sft.	39.15	119.00	sq.m	421.25	1280.45	23.11	
19	Providing and fixing 1/16" (1.5 mm) thick lead flashing over roof expansion joint complete in all respects.	Per Sft.	10.50	74.40	Sq.m	113.00	800.55		
20	Cast iron rain water downpipe fixed in position, excluding heads and shoes, but including painting and clamps, etc:-								Add extra 13%, 32% & 51% on labour rates only or 6%, 15% & 23%
	 a) 4" dia (100 mm) cast iron down pipe. b) 3" (75 mm) cast iron down pipe. 	Per Rft. Per Rft.	34.75 34.75	191.40 168.15	Metre Metre	114.00 114.00	627.80 551.55		on composite rates for 2nd, 3rd, 4th & sub- sequent floors, respectively, on items 19 to 24
21	Rain water down pipe cast iron head fixed in place, including cost of clamp holdfast and painting.	Each	146.70	438.25	Each	146.70	438.25		
22	Shoes, bends or offsets for cast iron rain water down pipe,	Each	52.15	287.05	Each	52.15	287.05		

	MRS, BI-ANNUAL PERI	NG							
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	including fixing and painting.								
23	Plain GI sheet iron spouts fixed in position, including painting.	Each	163.00	280.25	Each	163.00	280.25	23.10	
24	Laying ¹ / ₂ " (13 mm) thick deodar ceiling complete, including sawing, planing and fixing.	100Sft.	3715.80	16679.65	sq.m	399.80	1794.75	26.1	
25	Flat sheet roof with galvanized iron plain sheets, including battens, rolls, screws, clips etc. (Planking to be paid for separately):-								
	a) 22 BWG sheets roofingb) 24 BWG sheets roofing	100Sft. 100Sft.	2209.00 2209.00	14659.50 13084.60	sq.m sq.m	237.70 237.70	1577.35 1407.90	23.60	
26	Asbestos cement corrugated sheet roofing including necessary overlaps, and GI hook bolts, nuts, screws, washers and bitumen washers, etc. (excluding valleys and ridges, etc).	100Sft.	1498.20	5242.20	sq.m	161.20	564.05	23.8	
27	Extra labour for erection of GI sheets, flat sheet or asbestos sheet roofing, above 20' (6.10 m) height in difficult position, including lifting with care and special scaffolding along live electric wires.	100Sft.	175.30		sq.m	18.85	-	23.6	
28	Fixing asbestos cement sheet ridges and valleys ¼" (6 mm) thick.	Per Rft.	17.90	66.05	Metre	58.70	216.65	23.8	
29	Plain galvanized iron sheet ridging, including fixture, timber for ridge roll and ridge sheeting:-							23.6	
	a) 6" (150 mm) lap and 18" (450 mm)	Per Rft.	48.90	359.35	Per Metre	160.40	1178.65		
	 overall, of 22 gauge G.I sheet ridging. b) 9" (225 mm) lap and 24" (600 mm) 	Per Rft.	62.55	353.00	Per Metre	205.15	1157.85		
	 overall, of 24 gauge G.I sheet ridging. c) 12" (300 mm) lap and 30" (750 mm) overall, of 22 gauge G.I sheet ridging. 	Per Rft.	62.55	420.40	Per Metre	205.15	1378.90		
30	Plain 22 gauge G.I sheet gutter semi circular 8" (200 mm) dia meter.	Per Rft.	31.30	151.35	Per Metre	102.65	496.45	23.11	
31	Making masonry ventilators in cement, sand mortar 1:4	Each	695.20	1152.85	Each	695.20	1152.85		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	vstem)	R	Rate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
32	Fixing water spouts or parnalas.	Each	208.55		Each	208.55	-	23.10				
33	Making drip course 2"x ¹ /2" (50x13 mm) under RCC slab edges in outer opening, in cement, sand mortar 1:2.	Per Rft.	8.80	9.90	Metre	28.85	32.45					
34	Supplying and laying of twin G.I sheet 20 SWG duly painted with bitumen, with polythene film in between 300 gauge, to provide a sliding joint under the bearing of the beams, including 3" (75 mm) long, 3/8" (10 mm) dia bar to act as holdfast on wall and beam.	Per Sft.	25.50	329.75	sq.m	274.40	3548.10					
35	Providing and laying roof insulation, comprising of single layer of tiles 9"x4½"x1½" (225x113x40 mm) grouted with cement sand mortar 1:3 laid over 2" (50 mm) thick earth (including mud plaster) over thermopore sheet, over polythene sheet 300 gauge over a layer of bitumen, complete in all respects:- i) Thermopore sheet ½" (13 mm) thick ii) Thermopore sheet ½ " (20 mm) thick iii) Thermopore sheet 1" (25 mm) thick	100Sft. 100Sft. 100Sft.	1648.35 1648.35 1651.30	6356.00 6482.00 6610.95	sq.m sq.m sq.m	177.35 177.35 177.70	683.90 697.45 711.35					
36	Providing and fixing AC rain water down pipe 4" (100 mm) dia, with shoe, T-bend, clamp, etc.	Rft.	10.45	228.85	Metre	34.30	750.65					
37	Making jharries in existing brick masonry for providing recesses for bearing of RCC roof slab, including repairing the damaged face:-			3					Rate will be increased by 1.5 time for stone masonry or plain; concrete; and 2 times for reinforced cement concrete.			
	 i) for slabs upto 6" (150 mm) thick ii) for slabs exceeding 6" to 12" (150 to 300 mm) thick. 	Rft. Rft.	11.75 19.90	13.35 22.80		38.55 65.25	43.80 74.80					
38	Making recess in existing brick masonry for bearing of beam, girder, R.S. Joist, etc. including repairing damaged face:-								Rates will be increased by 1.5 times for stone masonry and plain cement concrete and two times for reinforced cement concrete.			
	i) upto 1.0' (300 mm) height of girder or beam.	Each	48.95	54.25	Each	48.95	54.25		is remoted concit concrete.			
	ii) for every 6" (150 mm) additional height or part thereof.	Each	23.50	26.05	Each	23.50	26.05					
39	Hoisting RS. Beams and wooden beams and placing in	Each	195.35		Each	195.35						

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr. No.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec. No.	Remarks			
INO.		Unit	Labour	Composite	Unit	Labour	Composite	N0.				
	position.											
40	Hoisting and placing in position sahl ballies, over roof.	Each	29.80	-	Each	29.80	-					
41	Hoisting precast R.C.C/prestressed concrete battens and placing in position.											
	a) 5' to 6' (1.50 to 1.83 m) long	Each	27.90	-	Each	27.90	-					
	b) 6' to 7' (1.83 to 2.13 m) long	Each	39.05	-	Each	39.05	-					
	c) 7' to 8' (2.13 to 2.44 m) long	Each	48.85	-	Each	48.85	-					
	d) 8' to 9' (2.44 to 2.74 m) long	Each	65.10	-	Each	65.10	-					
	e) above 9' (2.74 m) length	Each	78.15	-	Each	78.15	-					
42	Hoisting and placing in position R.C. trough:		×						Applicable only to roof trough (inverted tees & trough) for height of			
	a) upto 10' (3 m) in length	Each	78.15		Each	78.15	-		1st storey only.			
	b) $10'$ to $11'$ (3 to 3.36 m) in length	ditto	97.70		ditto	97.70	-		5 5			
	c) 11' to 12' (3.36 to 3.66 m) in length	ditto	130.25		ditto	130.25	-					
	d) 12' to 13' (3.66 to 3.96 m) in length	ditto	150.30	-	ditto	150.30	-					
	e) 13' to 14' (3.96 to 4.26 m) in length	ditto	162.80		ditto	162.80	-					
	f) 14' to 15' (4.26 to 4.57 m) in length	ditto	177.60	67	ditto	177.60	-					
	g) 15' to 16' (4.57 to 4.88 m) in length	ditto	195.35	21/10	ditto	195.35	-					
	h) 16' to 17' (4.88 to 5.19 m) in length	ditto	217.05	- 110	ditto	217.05	-					
	i) 17' to 18' (5.19 to 5.49 m) in length	ditto	279.10	and the second	ditto	279.10	-					
	j) 18' to 19' (5.49 to 5.80 m) in length	ditto	300.55	-	ditto	300.55	-					
	k) 19' to 20' (5.80 to 6.10 m) in length	ditto	325.60	There are a second second second second	ditto	325.60	-					
		- M. M.S.	MARCAR S.	LINE ZHUN NI	A CARLE							
43	Hoisting and placing in position R.C. inverted battens:-											
	i) upto 10' (3.05 m) span	Each	60.25	-	Each	60.25	-					
	ii) from 10' to 12' (3.05 to 3.66 m) span	ditto	133.85	-	ditto	133.85	-					
	iii) from 12' to 13' (3.66 to 3.96 m) span	ditto	160.60	-	ditto	160.60	-					
	iv) from 13' to 14' (3.96 to 4.26 m) span	ditto	200.75	-	ditto	200.75	-					
	v) from 14' to 15' (4.26 to 4.57 m) span	ditto	219.00	-	ditto	219.00	-					
	vi) from 15' to 16' (4.57 to 4.88 m) span	ditto	240.90	-	ditto	240.90	-					
	vii) from 16' to 18' (4.88 to 5.49 m) span	ditto	301.15	-	ditto	301.15	-					
	viii) from 18' to 20' (5.49 to 6.10 m) span	ditto	481.80	-	ditto	481.80	-					
44	Reinforced cement concrete spout, including fixing in position, with top and bottom Khurras.	Each	278.10	533.60	Each	278.10	533.60					

10. FLOORING

Rates for all finished works include the removal of surplus debris, unused material and byproduct:

	MRS, BI-ANNUAL PE			2012 TO 31st	JANUAR	Y, 2013) E	DISTRICT JHA	NG	
Sr.	Description		Rate (British Sy	rstem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Laying Murum flooring, consisting of 1"(25 mm) layer of fine powdery or flakey variety of Murum, laid over 6"(150 mm) good hard layer of Murum spreaded over 9"(225 mm) thick sub-base comprising of hand packed rubble or broken bricks properly watered and rammed, provided over well rammed earth.	100 Sft.	1890.90	3147.80	sq.m	203.45	338.70		
2	Earth flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth, including ramming.	100 Sft.	644.35	854.35	sq.m	69.35	91.95	24.1	
3	Providing, laying, watering and ramming brick ballast 1 ¹ / ₂ " to 2"(40 mm to 50 mm) gauge mixed with 25% sand, for floor foundation, complete in all respects.	100 Cft.	1457.95	2987.95	cum.	514.95	1055.35		
4	Mud flooring, consisting of 6"(150 mm) thick consolidated layer of moistened earth and finished off with 1"(25 mm) mud plaster and gobri leeping.	100 Sft.	1173.15	1515.05	sq.m	126.25	163.00	24.2	
5	Dry brick paving laid flat, sand grouted, including preparation of bed by watering, ramming and bringing the same to proper camber, by ½"(13 mm) thick mud plaster.	100 Sft.	617.75	3216.95	sq.m	66.45	346.15	24.12	
6	Dry brick on edge paving, sand grouted, including preparation of bed by watering, ramming & bringing the same to proper camber, by $\frac{1}{2}$ "(13 mm) thick mud plaster	100 Sft.	1113.60	4983.60	sq.m	119.80	536.25	24.12	
7	Grouting 4½"(113 mm) dry brick work with cement mortar ratio 1: 5	100 Sft.	601.90	1013.40	sq.m	64.75	109.05		
8	Flat brick flooring laid in 1:6 cement mortar, over a bed of 3/4" (20 mm) thick cement mortar, 1:6.	100 Sft.	1083.70	4385.65	sq.m	116.60	471.90	24.4	
9	Brick on edge flooring, laid in 1:6 cement mortar, over a bed of ¾" (20 mm) thick cement mortar 1:6.	100 Sft.	1,383.35	6,200.60	sq.m	148.85	667.20	24.4	
10	Brick tiles (12"x6"x2") (300x150x50mm) laid in 1:6 cement mortar, over a bed of ³ / ₄ " (20 mm) thick cement mortar 1:6.	100 Sft.	1,354.65	3,271.30	sq.m	145.75	352.00	ditto	
11	Brick ties (9"x4½"x1½")(225 mm x 113 mm x 40 mm) laid	100 Sft.	1,501.50	4,666.85	sq.m	161.55	502.15	24.4	

	MRS, BI-ANNUAL PE	NG							
Sr.	Description		Rate (British Sy	vstem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	flat in 1:3 cement mortar, over a bed of 3/4"(20 mm) thick cement mortar 1:6.								
12	Cement tiles (8"x8"x¾")(200 x 200 x 20 mm) laid flat in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2.	100 Sft.	901.05	5,089.25	sq.m	96.95	547.60	24.7	
13	Cement concrete tiles laid in 1:2 cement mortar, over 3/4" (20 mm) thick bed of cement mortar 1:2:-							24.8	
	(a) 12"x12"x1" (300 x 300 x 25 mm)	100 Sft.	901.05	3,548.55	sq.m	96.95	381.80		
	(b) 9"x9"x¾" (225 x 225 x 20 mm) (c) 6"x6"x¾"(150 x 150 x 20 mm)	ditto ditto	901.05 901.05	4,594.15 6,473.20	ditto ditto	96.95 96.95	494.35 696.50		
14	Coloured cement tiles (8"x8"x¾")(200 x 200 x 20 mm) of approved dark shade laid flat in 1:2 cement mortar, over ¾" (20 mm) bedding mortar of 1:2.	100 Sft.	901.05	5,118.05	sq.m	96.95	550.70	24.7	
15	Providing and laying topping of cement concrete 1:2:4, including surface finishing and dividing in panels:-	20 KB	F		78			24.9	If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) 1"(25 mm) thick (b) $11(1'/(20 mm))$ thick	100 Sft.	1,008.15	2,062.35	sq.m	108.50	221.90		_
	(b) 1 ¹ / ₄ "(30 mm) thick (c) 1 ¹ / ₂ "(40 mm) thick	ditto ditto	1,008.15 1,258.95	2,294.55 2,777.55	ditto ditto	108.50 135.45	246.90 298.85		
	(d) $1\frac{3}{4}$ (45 mm) thick	ditto	1,258.95	3,022.10	ditto	135.45	325.20		
	(e) 2"(50 mm) thick	ditto	1,509.75	3,559.25	ditto	162.45	383.00		
	(f) 2 ¹ / ₄ "(56 mm) thick	ditto	1,555.30	3,823.40	ditto	167.35	411.40		
	(g) $2\frac{1}{2}$ "(62 mm) thick (b) $2\frac{3}{10}$ "(70 mm) thick	ditto	1,760.55	4,196.70	ditto	189.45 189.45	451.55		
	(h)2¾"(70 mm) thick (i) 3"(75 mm) thick	ditto ditto	1,760.55 1,760.55	4,504.55 4,775.15	ditto ditto	189.45	484.70 513.80		
16	Providing and laying conglomerate flooring (two coat work)		,	,				24.10	If glass or marble strips are used
	with top layer of ½"(13mm) thick wearing surface, consisting of one part of cement and 2 parts of stone								for panelling, it will be paid extra as per item No. 41 or 42.
	chips passing 3/16"(6 mm) sieve, over bottom layer of								per nem No. 41 of 42.
	cement concrete 1:3:6, including surface finishing and dividing in panels:-								
	(a) 1 ¹ / ₂ "(40 mm) thick	100 Sft.	1,491.25	2,947.80	sq.m	160.45	317.20		
	(b) $1\frac{3}{4}$ "(45 mm) thick	ditto	1,491.25	3,100.50	ditto	160.45	333.60		
	(c) 2"(50 mm) thick	ditto	1,888.90	3,738.60	ditto	203.25	402.25		
17	Add extra in cement concrete floor topping, if finished with pigment and polishing.	100 Sft.	347.60	811.50	sq.m	37.40	87.30		

	MRS, BI-ANNUAL F	PERIOD (1s	t AUGUST, 2	2012 TO 31st	JANUAR	Y, 2013) D	ISTRICT JHA	NG	
Sr.	Description		Rate (British Sy	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
18	Extra labour for each storey above ground, for mosaic, conglomerate, tiles, stone and wooden floor.	100 Sft	273.25	-	sq.m	29.40	-		On items 19-25 & 29-34
19	Flag stone flooring in lime mortar 1:2, over ³ /4"(20 mm) bedding mortar, in platforms and floors, etc.							24.5	
	(a) 2"(50 mm) thick (b) 3"(75 mm) thick	100 Sft. ditto	2,994.40 2,994.40	4,614.60 4,883.10	sq.m ditto	322.20 322.20	496.55 525.40		
20	Asphalt flooring , including preparation of proper base remelting, setting out, and finishing complete:-							24.10	
	 (a) 1"(25 mm) thick topping (b) ¹/₂"(13 mm) thick topping (c) ¹/₄"(6 mm) thick topping 	100 Sft. ditto ditto	1,204.50 947.45 702.10	15,365.25 8,176.05 4,416.60	sq.m ditto ditto	129.60 101.95 75.55	1653.30 879.75 475.25		
21	$1^{3}/_{8}$ "(35 mm) thick mosaic flooring, consisting of 3/8"(10 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick flooring of 1:2:4 cement concrete including rubbing and polishing complete :-	State-							If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement(b) using white cement	100 Sft. ditto	4,092.00 4,092.00	6,357.00 6,636.80	sq.m ditto	440.30 440.30	684.00 714.10		
22	1 ¹ / ₂ "(40 mm) thick mosaic flooring, consisting of ¹ / ₂ "(13 mm) mosaic topping of one part of cement and marble powder in the ratio of 3:1 and two parts of marble chips, laid over 1"(25 mm) thick floor of 1:2:4 cement concrete, including rubbing and polishing complete with finishing :-	924	111.011.05	Depan	in en l				If glass or marble strips are used for panelling, it will be paid extra as per item No. 41 or 42.
	(a) using grey cement(b) using white cement	100 Sft. ditto	4,092.00 4,092.00	6,512.75 7,113.05	sq.m ditto	440.30 440.30	700.75 765.35		
23	Providing and laying floor of mosaic marble chips tiles 1"(25 mm) thick of approved quality and shade, laid in white cement and pigment, over ¾"(20 mm) thick bedding of cement sand mortar 1:2, including finishing and polishing, complete.	100 Sft.	2,513.00	6,312.80	sq.m	270.40	679.25	24.8	
24	Laying floor of approved white glazed tile ¹ /4" (6 mm) thick	100 Sft.	3,227.40	8,516.90	sq.m	347.25	916.40	24.7	

	MRS, BI-ANNUAL I	NG							
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	in white cement 1:2 over ³ / ₄ " (20mm) thick cement mortar 1:2, complete.								
25	Laying floor of approved coloured glazed tiles $\frac{1}{4}$ "(6 mm) thick, laid in white cement and pigment on a bed of $\frac{3}{4}$ " (20 mm) thick cement mortar 1:2.	100 Sft.	3,227.40	9,064.10	sq.m	347.25	975.30	ditto	
26	Rubbing and polishing old grit/ mosaic floor, including repairing voids, uneven surface, complete in all respects.	100 Sft.	826.30	955.85	sq.m	88.90	102.85		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
27	Rubbing and polishing grit floor, including repairing voids, uneven surface, complete in all respects	100 Sft.	881.75	1,014.00	sq.m	94.90	109.10		The composite rate will be reduced by Rs. 150.00 per % Sft or Rs.13.95 per Sq. metre respectively, if no polishing is done.
28	Cleaning and washing mosaic or marble floor with caustic soda mixture.	100 Sft.	134.85	179.85	sq.m	14.50	19.35	24.6	
29	Shisham wood boarding or strip flooring $3/4"$ (20mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens $1\frac{1}{2}"x2"(40 \times 50 \text{ mm})$,size placed at $12"(300 \text{ mm})$ centre to centre, including two coats of bitumen laid hot on the	100 Sft.	2,728.00	33,675.00	sq.m	293.55	3623.45	24.13	
	base.	Æ1	imance	Depart					
30	Deodar wood boarding or strip flooring $3/4"$ (20 mm) thick (sawn to required size) tongued and grooved or splayed rebated fixed with brass screws on deodar wood battens $1\frac{1}{2}"x2"(40 \text{ x } 50 \text{ mm})$ size , placed at $12"(300 \text{ mm})$ centre, to centre including two coats of bitumen laid hot on the base.	100 Sft.	3,128.40	38,587.50	sq.m	336.60	4152.00	ditto	
31	Teak wood boarding or strip flooring ½" (13 mm) "thick (sawn to required size) to tongued and grooved screwed on deodar wood battens 1½ " x2"(40 x 50 mm) size, placed at 12"(300 mm) centre to centre, including 2 coats of bitumen laid hot on base.	100 Sft.	2,717.00	43,746.50	sq.m	292.35	4707.10	ditto	
32	Shisham wood block flooring 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	2,900.70	39,109.70	sq.m	312.10	4208.20	24.13	

	MRS, BI-ANNUAL PE	ISTRICT JHA	NG						
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
33	Teak wood block 1"(25 mm) thick cut to required size, fixed on a layer of asphalt bitumen laid on base.	100 Sft.	2,717.00	74,066.85	sq.m	292.35	7969.60	ditto	
34	Laying wooden paving of hard wood on edge in coal tar							ditto	
5.	and asphalt:-	100 Sft.			sq.m			unito	
		Per Inch			per cm				
	(a) Shisham wood	thickness	1,694.00	24,089.85	thickness	182.25	2592.05		
	(b) Kikar wood	ditto	1,694.00	13,043.25	ditto	182.25	1403.45		
35	Tile skirting laid in 1:2 cement mortar, over ³ / ₄ "(20 mm)								
55	thick cement mortar, 1:2 including cement washing and								
	filling joints complete:-								
	ining joints complete.								
	(a) cement tiles	100 Sft.	1,474.60	6,020.70	sq.m	158.65	647.85		
	(b) mosaic tiles	ditto	2,428.80	8,454.80	ditto	261.35	909.75		
			/ /	.,	\ · · · ·				
36	Providing grey cement skirting or dado 3/8"(10 mm) thick				1				
	including rounding of corner and straight ening of top edge	- Server			I 44.				
	and finishing to smooth surface afterplastering :-	1995			7 82				
		Server 1			1 Niel				
	(a) 1:2 cement, sand mortar	100 Sft.	1,846.95	2,371.60	sq.m	198.75	255.20		
	(b) 1:3 cement, sand mortar	ditto	1,846.95	2,216.65	ditto	198.75	238.50		
	(c) Extra if skirting or dado is finished	ditto	113.85	374.95	ditto	12.25	40.35		
	with pigment of any colour.			18 - Same					
37	White glazed tile (6"x6"x ¹ /4") (6 mm) thick dado jointed in white	100 Sft.	3,976.50	9,266.00	sq.m	427.85	997.00	24.7	
	cement and laid over 1:2 cement sand mortar 3/4" (20mm)	120	un an ce	CEDE DOM	ter en e				
	thick, including finishing.								
38	Coloured glazed tile dado (6"x6" ¹ / ₄ ") (6mm) thick in pigment over 1:2	100 Sft.	3,976.50	9,796.65	sq.m	427.85	1054.10	ditto	
	cement, sand mortar 3/4"(20mm) thick, including finishing.				-				
39	Mosaic dado or skirting with one part of cement and								
	marble powder in the ratio of 3:1 and two parts of marble								
	chips, laid over ¹ /2"(13 mm) thick cement plaster 1:3,								
	including rubbing and polishing, complete with finishing:								
	(a) using grey cement:								
	i) 3/8"(10 mm) thick	100 Sft.	4,857.60	6,048.30	sq.m	522.70	650.80		
	ii) ½"(13 mm) thick	ditto	4,857.60	6,762.65	ditto	522.70	727.65		
	(b) using white cement :								
	'i) 3/8"(10 mm) thick	100 Sft.	4,857.60	6,857.25	sq.m	522.70	737.85		

	MRS, BI-ANNUAL PE	RIOD (1s	t AUGUST, 2	2012 TO 31st	JANUAR	Y, 2013) D	DISTRICT JHA	NG	
Sr.	Description		Rate (British S	ystem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) ½"(13 mm) thick	ditto	4,857.60	7,140.60	ditto	522.70	768.35		
40	Rubber flooring, consisting of 12"x12"x1/8" (300x300x3mm) rubber tiles, laid on firm foundation.	Per Sft.	12.70	74.05	sq.m	136.65	796.80	24.14	The cost of base for rubber flooring is not included in the rate and is payable separately.
41	Providing and fixing glass strip 5mm thick and 1½" (40 mm) wide, for dividing the mosaic flooring into panels.	Per Rft.	-	4.10	Metre	-	13.45		Labour for fixing already included in items No. 15, 16, 21and 22 of this Chapter.
	Providing and fixing marble strip of any shade for dividing the mosaic flooring into panels								
	a) Size 1½" x ³ / ₈ " (40 x 10 mm) b) Size 1½" x ¼" (40 x 6 mm)	Per Rft. ditto		6.60 4.60	Metre ditto	-	21.65 15.10		
		2000-			揚				
		S.	19	المريب بر	1. Starten and the second seco				
				X G B	5×				

Finance Department

11. SURFACE RENDERING

1 PLASTERING, POINTING, WHITE WASHING, COLOUR WASHING AND DISTEMPERING, ETC.

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	Rates for all finished works include the removal of surplus debris, unused n MRS, BI-ANNUAL PER	DISTRICT JI	HANG						
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Mud plaster on walls (excluding Gobri leeping) upto 20' (6.00 m) height:-							25.7	
	a) ¹ / ₂ " (13 mm) thick b) 1" (25 mm) thick	100 Sft. ditto	280.55 393.10	346.25 524.50	sq.m ditto	30.20 42.30	37.25 56.45		
2	Mud plaster on floor or roof (excluding Gobri leeping):-							ditto	Add extra 13%, 32% and 51% above the labour rates only or 6%, 15% &
	a) ¹ /2" (13 mm) thick	100 Sft.	252.90	318.60	sq.m	27.20	34.30		23% on the composite rates for 2nd, 3rd, 4th and subsequenct floors,
	b) 1" (25 mm) thick	ditto	252.90	384.30	ditto	27.20	41.35		respectively.
3	Cement lime plaster 1:7:12 (cement, lime and sand) upto 20' (6.00 m) height.				7			25.1 to 25.6	
	a) ¹ /4" (6 mm) thick	100 Sft.	809.15	967.55	sq.m	87.05	104.10		
	b) 1/2" (13 mm) thick	ditto	809.15	1125.80	ditto	87.05	121.15		
4	Cement Neru plaster 1:2 (cement and sand) upto 20' (6.00 m) height:-		namos	Deptart				ditto	
	 a) ¼" (6 mm) thick b) ½" (13 mm) thick 	100 Sft. ditto	809.15 809.15	1191.00 1423.80	sq.m ditto	87.05 87.05	128.15 153.20		
5	2" (50 mm) stucco cement plaster 1:2:4 (cement, sand and shingle) upto 20' (6.00 m) height.	100 Sft.	2038.10	4378.10	sq.m	219.30	471.10	ditto	
6	Providing and laying machine sprayed plaster ¹ / ₂ " (13 mm) thick, using cement and chips zero gauge, over the existing plastered and roughened surface, upto 20' (6.00 m) height:-							ditto	
	 i) ratio 1:1 ii) ratio 1:1¹/₂ iii) ratio 1:2 	100 Sft. ditto ditto	710.70 710.70 710.70	2114.80 2023.35 1970.70	sq.m ditto ditto	76.45 76.45 76.45	227.55 217.70 212.05		
7	Cement plaster 1:2 upto 20' (6.00 m) height:-							25.1	

	MRS, BI-ANNUAL PEF	RIOD (1st	AUGUST, 2	012 TO 31st	JANUA	RY, 2013)	DISTRICT JI	HANG	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) ¾" (20 mm) thick	100 Sft. ditto ditto	809.15 809.15 1017.70	1333.85 1489.55 2067.05	sq.m ditto ditto	87.05 87.05 109.50	143.50 160.30 222.40		
8	Cement plaster 1:3 upto 20' (6.00 m) height:-							ditto	
	 a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	809.15 809.15 1017.70	1178.85 1302.05 1757.10	sq.m ditto ditto	87.05 87.05 109.50	126.85 140.10 189.05		
9	Cement plaster 1:4 upto 20' (6.00 m) height:-							ditto	
	 a) 3/8" (10 mm) thick b) 1/2" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	809.15 809.15 1017.70	1137.05 1226.45 1668.10	sq.m ditto ditto	87.05 87.05 109.50	122.35 131.95 179.50		
10	Cement plaster 3/8" (10 mm) thick under soffit of R.C.C. roof slabs only, upto 20' height.	Grane-							 i) This item shall be applicable to buildings meant for human habitation only, such as buildings like residences, offices,
	a) 1:2 b) 1:3 c) 1:4	100 Sft. ditto ditto	926.65 926.65 926.65		sq.m ditto ditto	99.70 99.70 99.70	167.35 150.65 146.15		educational institutions and hospitals, etc. It shall not be admissible on godowns; bins; agriculture, poultry and animal sheds; cycle stands; garrages; etc. ii) The thickness of the plaster will not be more than 3/8" (10 mm)
11	Cement plaster 1:5 upto 20' (6.00 mm) height:-							25.1 to 25.6	thick.
	 a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick 	100 Sft. ditto ditto	809.15 809.15 1017.70	1100.75 1163.40 1600.90	sq.m ditto ditto	87.05 87.05 109.50	118.45 125.20 172.25		
12	Cement plaster 1:6 upto 20' (6.00 mm)							ditto	
	height:- a) 3/8" (10 mm) thick b) ½" (13 mm) thick c) 3/4" (20 mm) thick	100 Sft. ditto ditto	809.15 809.15 1017.70	1048.90 1127.10 1497.25	sq.m ditto ditto	87.05 87.05 109.50	112.85 121.30 161.10		
13	Applying floating coat of cement 1/32" (0.8 mm) thick.	100 Sft.	480.50	687.85	sq.m	51.70	74.00	25.4 to 25.6	
14	Lime pointing flush upto 20' (6.00 m) height including	100 Sft.	600.60	716.80	sq.m	64.65	77.15	25.8	

	MRS, BI-ANNUAL F	PERIOD (1st	AUGUST, 2	012 TO 31st	JANUA	RY, 2013)	DISTRICT J	IANG	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	raking joints, in lime, sand mortar 1:2.								
15	Lime pointing struck joints on walls, upto 20' (6.00 m) height, including raking joints in lime sand mortar 1:2.	100 Sft.	926.65	1042.85	sq.m	99.70	112.20	ditto	
16	Cement pointing flush upto 20' (6.00 m) heihgt:-							ditto	
	a) ratio 1:2	100 Sft.	809.15	1201.85	sq.m	87.05	129.30		
	b) ratio 1:3	ditto	809.15	1110.70	ditto	87.05	119.50		
17	Cement pointing 1:2 flush on floor.	100 Sft.	600.60	993.30	sq.m	64.65	106.90	ditto	
18	Cement pointing struck joints, on walls, upto 20' (6.00 m) hiehgt:-		1	5					
	a) ratio 1:2	100 Sft.	926.65	1319.35	sq.m	99.70	141.95		
	b) ratio 1:3	ditto	926.65	1228.20	ditto	99.70	132.15		
19	Pointing flush on stone work, upto 20' (6.00 m) height.	- Si			78			25.8	
	a) in lime mortar 1:2 (lime, sand)	100 Sft.	744.50	900.45	sq.m	80.10	96.90		
	b) in cement mortar 1:3	ditto	744.50	1046.00	ditto	80.10	112.55		
	c) on stone work raised:-	100 56	1396.55	1552.50	53r	150.25	167.05		
	i) in lime mortar 1:2ii) in cement mortar 1:3	100 Sft. ditto	1396.55	1552.50 1698.10	sq.m ditto	150.25 150.25	167.05 182.70		
		unto	1570.55	10,0.10	unto	150.25	102.70		
20	Raking and washing joints of stone masonry (old work).	100 Sft.	369.60	Depart	sq.m	39.75	-	ditto	
21	Raking and washing joints of brick masonry (old work).	100 Sft.	184.80	-	sq.m	19.90	-	ditto	
22	Priming coat of chalk under distemper.	100 Sft.	83.40	90.00	sq.m	8.95	9.70	25.11	
23	Distempering:-							ditto	
	a) new surface:-								
	i) one coat	100 Sft.	90.85	169.85	sq.m	9.80	18.30		
	ii) two coats	ditto	134.35	237.30	ditto	14.45	25.55		
	iii) three coats	ditto	177.80	304.80	ditto	19.15	32.80		
	b) old surface:-								
	i) one coat	100 Sft.	83.05	138.00	sq.m	8.95	14.85		
	ii) two coats	ditto	134.35	189.30	ditto	14.45	20.35		

	MRS, BI-ANNUAL PE	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUA	RY, 2013)	DISTRICT JH	IANG	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
24	Colour washing:-	_						25.10	
24	Colour washing							23.10	
	a) new surface:-								
	i) one coat	100 Sft.	66.20 99.30	94.70 141.00	sq.m ditto	7.10 10.70	10.20 15.15		
	ii) two coats	ditto	99.30	141.00	anto	10.70	15.15		
	b) old surface:-								
	i) one coat	100 Sft.	66.20	83.85	sq.m	7.10	9.00		
	ii) two coats	ditto	99.30	128.20	ditto	10.70	13.80		
25	White washing:-							25.9	
	a) new surface:- i) one coat	100 Sft.	66.20	89.65	sq.m	7.10	9.65		
	ii) two coats	ditto	99.30	134.40	ditto	10.70	14.45		
	iii) three coats	ditto	128.75	175.45	ditto	13.85	18.90		
	b) old surface:-	. 12			一以				
	i) one coat	100 Sft.	66.20	83.80	sq.m	7.10	9.00		
	ii) two coats	ditto	99.30	128.55	ditto	10.70	13.85		
26	Cabai Janaina	189	-6	!!!	183			25.7	
26	Gobri leeping:-	1			100			25.7	
	a) on walls	100 Sft.	92.65	96.20	sq.m	9.95	10.35		
	b) over roofs	ditto	78.55	82.10	ditto	8.45	8.85		
27	Striking joints of burnt bricks in lime or cement mortar.	100 Sft.	117.50	Depart	sq.m	12.65	-	25.8	Payable with fresh masonry, when
									the face of the work is not to be
28	Extra for lime, mud or cement plaster and pointing from	100 Sft.	147.45	_	sq.m	15.85	_		plastered/pointed.
20	20' (6.00 m) and above for each additional 10' (3.00 m)	100 511.	147.45		5 q .m	15.05			
	height or part thereof.								
29	Caulking joints of sleeper wall, with sand and coaltar.	100 Sft.	366.95	840.95	sq.m	39.50	90.50		
							20.00		
30	Caulking joints of sleepers, withmud and chopped straw.	100 Sft.	366.95	388.25	sq.m	39.50	41.80		
31	Extra cost of labour and material for red oxide pigment in	100 Sft.	115.50	213.00	sq.m	12.45	22.90		
	cement pointing to match with the colour of bricks.				-				
32	Providing grooved cement sand plaster 1:3 over existing								
52	plastered and roughened surface upto 20' (6.00 m) height.								
		100.07							
	i) 3/8" (10 mm) thick	100 Sft.	926.65	1296.30	sq.m	99.70	139.50		

	MRS, BI-ANNUAL PEF	RIOD (1st	AUGUST, 2	012 TO 31st	JANUA	RY, 2013)	DISTRICT JH	IANG	
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) ½" (13 mm) thick	ditto	926.65	1419.55	ditto	99.70	152.75		
	Providing and fitting expanded metal edge bead for corners, with nails on both sides of edges.	Rft.	5.50	33.75	Metre	18.05	110.70		
34	Petty repairs to fire place.								
	i) Single ii) Double	Each Each	146.00 292.00	189.50 378.95	Each Each	146.00 292.00	189.50 378.95		
35	Petty repair to main rooms.	Each	301.70	417.80	Each	301.70	417.80		Area above 100 Sft (10.76 sq.m)
36	Petty repair to small rooms.	Each	150.85	208.85	Each	150.85	208.85		Area upto 100 Sft (10.76 sq.m)
37	Petty repair to verandah.	Each	301.70	394.50	Each	301.70	394.50		
	Extra labour for white washing, colour washing, priming coat and distempering, etc. from 20' (6.00 m) height and above, requiring scaffolding, for every additional 10' (3.00m) height or part thereof.	100 Sft. Per coat	11.05		sq.m Per coat	1.20	-		The height will be taken from the floor, roof or ground uderneath as the case may be on the side towards which the work is to be done.

Finance Department

12. WOOD WORK

1 No extra rate is to be paid for sawing as the rates are inclusive of these

2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PER	DISTRICT JH	ANG						
Sr.	Description]	Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Plain wood work sawn, wrought, planed and fixed inposition, including cost of nails and screws etc.							26.1	
	a) Deodar woodb) Shisham wood	Per Cft. ditto	485.55 545.60	3410.70 2781.20	cu.m ditto	17149.65 19270.60	120465.90 98232.00		
2	Plain wood work for regulation karries or needles, etc. including sawing, planning, wroughting wood and providing and fixing steel parts of karries i.e. end strip and rods, etc.			0				26.1	
	a) Deodar woodb) Shisham wood	Per Cft. ditto	303.45 303.45	3269.15 2597.15	cu.m ditto	10717.85 10717.85	115466.40 91731.35		
3	First class teak wood wrought joinery in doors and windows, etc. panelled, panelled and glazed or fully glazed and fixed in position, including chowkat, holdfast, tower bolt, chocks, rubber stop, cleats/G.I. clamps, chords with hooks, nails, screws, etc. complete (excluding sliding bolt and lock):-			Nepan Depan		6. r		26.1 to 26.3 & 26.7	
	 i) 2" (50 mm) thick ii) 1³/₄" (45 mm) thick iii) 1¹/₂" (40 mm) thick 	Per Sft. ditto ditto	86.35 86.35 86.35	1332.65 1243.05 1155.55	sq.m ditto ditto	929.15 929.15 929.15	14339.30 13375.20 12433.70		
4	 First class teak wood wrought joinery in wire gauze doors and windows with frames 22 SWG galvanized iron wire gauze 12x12 meshes to square inch, (5x5 meshes in cn²) including brass fittings, sash bars, etc. complete:- a) teak wood framing 1³/₄" (45 mm) thick with wire gauze fixed in position:- 							26.8 to 26.10	 i) This also includes the cost of wood required for extra thickness of chowkat. ii) If 24 SWG wire gauge is used, the composite rate shall be reduced by Rs.4.70 per sft. and Rs.50.60 per sq.m.
	i) without springs or spring hinges.	Per Sft.	15.15	546.05	sq.m	163.00	5875.50		
	ii) with springs or spring hinges.	ditto	15.15	549.75	ditto	163.00	5915.30		

sr.	Description]	Rate (British Sy	stem)	ŀ	Rate (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 b) teak wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:- i) without springs or spring hinges. ii) with springs or spring hinges. 	Per Sft. ditto	15.15 15.15	503.40 507.50	sq.m ditto	163.00 163.00	5416.60 5460.70		
	 G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes per cm²) fixed to chowkat with ³/₄" (20 mm) teak wood strips and screws. 	Per Sft.	27.30	162.40	sq.m	293.75	1747.40		
	 d) G.I. wire gauze 22 SWG, 12x12 meshes per square inch (5x5 meshes per cm²) fixed with ¹/₂" (13 mm) strip on separate frame of teak wood 2"x2" (50x50 mm), for windows, etc. 	Per Sft.	25.60	522.10	sq.m	275.45	5617.80		
	P/F expanded metal ½" to ¾" (13 to 20 mm) mesh, 16 Guage, fixed to chowkat with 1" (25 mm) teak wood cover strips and screw etc., complete.	Per Sft.	32.80	263.05	sq.m	352.95	2830.40		
	Providing and fixing expanded metal ¹ / ₂ " (13 mm) to ³ / ₄ " 20 mm), 16 gauge, fixed to chowkat with 1" (25 mm)cover moulding and screws, including teak wood frame 2"x2" (50 mm x 50 mm)	Per Sft.	34.10	392.00	sq.m	366.90	4217.90		
	First class deodar wood wrought joinery in doors and windows, etc. panelled, or panelled or glazed, or fully glazed, fixed in position, including chowkat, holdfast, hinges, tower bolts, chocks, rubber stop, cleats/G.I. clamps, handles and chord with hooks, etc. complete (excluding sliding bolt or lock):-	1 de la	* A	Sepan Depan	170 6770	fa a		26.1 to 26.3 & 26.7	
	 a) 2" thick (50 mm) b) 1³/₄" thick (45 mm) c) 1¹/₂" thick (40 mm) 	Per Sft. ditto ditto	82.40 82.40 82.40	993.55 928.55 883.40	sq.m ditto ditto	886.60 886.60 886.60	10690.60 9991.30 9505.40		
	Deodar wood framed, braced and battened doors and windows, complete with iron fittings and fixed in position, including chowkats:-							26.1, 26.2 & 26.4	
	 a) 2¹/₄" (56 mm) thick, with 1¹/₄" (30 mm) battens and 1" (25 mm) planks. 	Per Sft.	91.95	620.70	sq.m	989.40	6678.75		
	 b) 1³/₄" (40 mm) thick with 1" (25 mm) battens and ³/₄" (20 mm) planks. 	ditto	83.95	536.55	ditto	903.30	5773.30		

	MRS, BI-ANNUAL PE	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUAF	RY, 2013) D	DISTRICT JH	ANG	Ι
Sr.	Description		Rate (British Sys	stem)	F	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	1" (25 mm) thick battneded doors and windows fitted in position, complete with iron fittings, without chowkats.	Per Sft.	107.85	351.05	sq.m	1160.45	3777.30		
10	Deodar battened ledged and braced doors and windows 2¼" (56 mm) thick (1¼" (30 mm) thick ledge braces and 1" (25 mm) thick battens complete with iron fittings, chowkats and fixed in position.	Per Sft.	99.00	606.05	sq.m	1065.25	6521.10	26.1, 26.2 26.4 to 26.6	
11	 a) Deodar wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges, and locking arrangements as directed by the Engineer incharge:- 							26.1, 26.2 & 26.4	If 24 gauge G.I. sheet is used, the composite rate will be reduced by Re.4.70 per Sft. (Rs. Per 50.60 Sq.m) for G.I. facing on one side and Rs.9.40 per Sft. (Rs.101.20
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	42.95 47.55	512.45 537.40	sq.m ditto	462.15 511.65	5513.95 5782.40		per Sq.m) for G.I. sheet facing on both sides.
	b) Partal wood framed with braces and 22 SWG G.I. sheet facing, including holdfast, wooden beadings, hinges and locking arrangements, as directed by the Engineer-in-charge:-	97 an-							-ditto-
	i) G.I. sheet facing on one side.ii) G.I. sheet facing on both sides.	Per Sft. ditto	42.95 47.55	204.00 229.00	sq.m ditto	462.15 511.65	2195.05 2464.05		
12	First class deodar wood wrought joinery work in wire gauze doors and windows, with 22 SWG G.I. wire gauze, 12x12 meshes per square inches (5x5 per cm ²) including iron fittings etc. complete:-	Ŧ	mance	Depart		j.		26.8 to 26.10	i) This also includes the cost of wood required for extra thickness of chowkat.
	 a) deodar wood framing 1³/₄" (45 mm) thick with wire gauze fixed in position:- 								ii) If 24 SWG wire gauze is used the composite rate shall be reduced by Rs.4.70 per sft or Rs.50.60 per sq.m.
	i) without springs or spring hinges.ii) with springs or spring hinges.	Per Sft. ditto	45.45 45.45	427.05 431.15	sq.m ditto	489.05 489.05	4595.05 4639.15		
	 b) deodar wood framing 1¹/₂" (40 mm) thick, with wire gauze fixed in position:- 								
	i) without springs or spring hingesii) with springs or spring hinges	Per Sft. ditto	45.45 45.45	396.80 399.40	sq.m ditto	489.05 489.05	4269.55 4297.55		
	 c) G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 in cm²) fixed to chowkat, with ³/₄" ('20 mm) thick deodar wood strip and screws. 	Per Sft.	34.10	139.20	sq.m	366.90	1497.80		

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUAF	RY, 2013) [DISTRICT JH	ANG	Γ
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 d) G.I. wire gauze 22 SWG 12x12 meshes per square inch, (5x5 meshes in cm²) fixed to chowkat, with ½" (13 mm) strip on separate frame of deodar wood 2" x 2" (50 mm x 50 mm). 	Per Sft.	51.15	365.55	sq.m	550.35	3933.30		
13	Making and fixing trellis doors and windows of deodar wood, complete.	Per Sft.	74.60	408.80	sq.m	802.70	4398.70	26.1 26.2	
14	Providing and fixing mild steel chowkat of doors, windows, C.window, etc. including holdfast, making and threading holes for hinges, etc. complete:-								
	a) M.S. angle iron 1½"x 1½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm)	Per Sft.	19.55	143.85	sq.m	210.35	1547.85		
	 b) M.S. tee iron 1½"x 1½"x ¼" (40x40x6 mm) welded with M.S. flat 2"x ¼" (50 mm x 6 mm) 	Per Sft.	19.55	108.55	sq.m	210.35	1168.00		
15	Providing and fixing M.S. sheet hollow pressed frame of doors, windows, C. windows, etc. (chowkat only) of 20 SWG welded with M.S. flat 6"x 1 ¹ /4" x 1/8" (150 mmx30mmx3mm) M.S. holdfast 9"x1"x1/8" (225mmx25mmx3mm) welded/screwed 4" (100 mm) long iron hinges, including filling chowkat with cement sand mortar 1:8 and embedding holdfast in cement concrete 1:2:4, complete in all respects:	E.		Nepara Depara		6. -			
	a) single rebateb) double rebate	Per Sft. ditto	26.85 32.10	127.15 146.10	1	288.90 345.40	1368.15 1572.05		
16	Extra for providing and fixing iron double spring hinges, with brass fittings (it shall include brass finger plate, 6" (150 mm) tower bolt).	Per Sft. door area	2.50	30.25	sq.m door area	26.90	325.50	26.2	
17	Providing and fixing brass spring hinges to wire gauzed doors.	Each	52.45	202.45	Each	52.45	202.45		
18	Providing and fixing sliding bolt to doors:-								
	 iron sliding bolt, 10" (250 mm) long iron sliding bolt, 12" (300 mm) long 	Each ditto	51.15 51.15	111.15 153.15		51.15 51.15	111.15 153.15		
	iii) brass sliding bolt, 10" (250 mm) long	ditto	51.15	153.15		51.15	153.15		

	MRS, BI-ANNUAL PE	RIOD (1st	AUGUST, 2	012 TO 31st	JANUAI	RY, 2013) D	DISTRICT JH	ANG	
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) brass sliding bolt, 12" (300 mm) long	ditto	51.15	309.15	ditto	51.15	309.15		
19	Extra for brass fittings to doors and windows, except for hinges, which shall be of iron:-								
	 deodar wood panelled or panelled and glazed or fully glazed. 	Per Sft.	1.50	11.40	sq.m	16.15	122.65		
	ii) deodar wood wire gauzed shutters.	ditto	1.50	9.05	ditto	16.15	97.40		
20	Extra for providing and fixing approved quality rim lock adjustable over the style surface.	Each	159.90	366.30	Each	159.90	366.30		
21	Providing and fixing, approved quality mortice lock.	Each	223.85	413.45	Each	223.85	413.45		
22	Providing and fixing, expended metal ¹ /2" to ³ /4" (13 mm to 20 mm) mesh 16 gauge.				1				
	a) fixed to chowkat with 1" (25 mm) thick deodar wood strip and screws, etc.	Per Sft.	32.80	215.55	sq.m	352.95	2319.30		
	 b) fixed with 1" (25 mm) cover moulding and screws, including deodar wood frame 2"x2" (50 x 50 mm) 	ditto	34.10	306.65	ditto	366.90	3299.55		
23	 a) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm) depth, including boxing with back, shelves, shutter and brass fittings, etc. 	Per Sft.	113.30	1422.90	sq.m	1219.10	15310.55		For hollow frame shutter with commercial ply on one side, the composite rate shall be reduced by
	complete.	Œ	man ac	Depart		-			Rs.54.00 per Sft;or Rs.580.00 per Sqm and for hollow frame shutter with commercial ply on both sides, the composite rate shall be reduced by Rs.22.80 per Sft. or Rs.245.00 per Sq. metre.
	 b) Providing and fixing deodar wood almirah 9" to 12" (225 mm to 300 mm)depth with shelves, shutters, brass fittings, etc., without boxing and back, complete. 	Per Sft.	83.95	470.60	sq.m	903.10	5063.75		51. of K3.245.00° per 54. metre.
24	Providing and fixng class room almirah consiting of 1" (25 mm) thick solid flush shutter with deodar wood lipping ¹ / ₄ " (6 mm) thick all around (Approved Factory Manufactured) fixed in deodar wood frame 3"x1" (75mm x 25mm) including full hinges C.P. fittings with RCC (1:1 ¹ / ₂ :3) shelves 1 ¹ / ₂ " (40 mm) thick including 3 coats of painting.	Per Sft.	66.20	338.75	Sq.m	712.40	3644.80		

	MRS, BI-ANNUAL PEF	RIOD (1st	AUGUST, 2	012 TO 31st	JANUAF	RY, 2013) D	DISTRICT JH	ANG	
Sr.	Description		Rate (British Sy	stem)	R	Rate (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
25	 Providing and fixing wooden box type wardrobe 22" (550 mm) deep including ³/₄" (20 mm) thick boxing and shelves, hanger rods, hard board back drawers, brass fittings, locking arrangements, handles, internal bolts, shoe rods, etc. including three coats of enamel paint:- i) Partal wood boxing and deodar wood shelves and leaves, etc. 	Per Sft.	125.90	614.00		1354.75	cc0c 75		If hollow flush door leaves 1" thick (25 mm) with commercial ply 3 ply) on both sides of deodar wood frame and partal wood bracing and deodar wood lipping is used, the composite rate will be reduced by Rs.13.00 per Sft. or Rs.140.00 per Sq. metre.
	ii) Deodar wood boxing, and deodar wood	ditto	123.90	796.05	sq.m ditto	1334.73	6606.75 8565.40		Ks.140.00 per 5q. metre.
26 27	shelves and leaves, etc. Providing and fixing wardrobe 22" (550 mm) deep consisting of RCC shelves 1½" (40 mm) thick including ½" thick vinboard boxing and back (one side ply) vinboard shutter ¾" (20 mm) thick including deodar wood lipping ¼" (6 mm) on all edges, fixes including deodar wood frame 3"x1" (75mm x 25mm) with hanger rod in centre position drawers at bottom and openable shutter on upper portion including full hinges C.P. fitting and painting 3 coats complete. Providing and fixing chowkat for doors, windows and C.	Per Sft.	48.30	530.50	Sq.m	519.55	5708.45		
	 windows, including holdfast, etc. a) Teak wood b) Deodar wood c) Shisham wood 	Per Sft. ditto ditto	23.80 15.15 17.70	454.70 329.20 167.55	Sq.m ditto ditto	255.90 163.05 190.70	4892.75 3542.20 1802.85		
28	Making and fixing deodar wood planking in eave boards, etc. planed on both sides, rebated and fixed including nails and screws, bolts and brackets:-							26.1 26.2	
	a) 1" (25 mm) thick b) 3/4" (20 mm) thick c) 1/2" (13 mm) thick	Sft. ditto ditto	28.10 28.10 28.10	267.85 207.85 148.15	sq.m ditto ditto	302.55 302.55 302.55	2881.85 2236.50 1593.85		
29	Making and fixing deodar wood shelves, including brackets:-							ditto	
	 i) 1" (25 mm) thick ii) 1¹/₂" (40 mm) thick iii) 2" (50 mm) thick 	Sft. ditto ditto	28.10 28.10 28.10	267.85 387.55 507.25	sq.m ditto ditto	302.55 302.55 302.55	2881.85 4169.80 5457.75		

	MRS, BI-ANNUAL F	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUAF	RY, 2013) I	DISTRICT JH	ANG	
Sr.	Description		Rate (British Sy	rstem)	R	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
30	 a) Making and fixing cleats for doors and windows, including hinges and screws. 	Each	32.75	104.85	Each	32.75	104.85	26.1 and 26.2	
	 Making and fixing cleats with brass hooks for roof ventilators. 	Each	42.00	78.40	Each	42.00	78.40		
	c) Providing and fixing door stops of 1¹/₂" (40 mm) dia rubber block.	Each	4.90	55.40	Each	4.90	55.40		
	d) Providing and fixing G.I. hook with clamps for doors.	Each	1.55	9.25	Each	1.55	9.25		
31	Hard wood railing of any shape and design, including bends and corners, fixed in position, including polishing complete as directed.			0				ditto	
	a) Shisham wood b) Teak wood	Per Rft. ditto	121.35 90.95	270.10 615.05	Metre ditto	397.95 298.40	885.85 2017.45		
32	Deodar wood dado or picture rail 3"x1½" (75x40 mm) as per approved design including moulding and fixed in place, cost of screws, nails, plugs, and painting complete.	Per Rft.	45.50	200.15	Metre	149.20	656.50	26.1 26.2	
33	Sawing wood by hand:-		n Sta						
	 a) Soft wood (deodar, kail or chir). b) Hard wood (shisham, kikar, teak or sahl). 	100Sft. ditto	524.70 699.60	Depart	sq.m ditto	56.45 75.30	-		
34	Sawing wood by machine:								
	a) Soft wood b) Hard wood	100Sft. ditto	314.38 472.35		sq.m ditto	33.85 50.85	-		
35	Making and fixing sun-shade of deodar wood including fixing brackets.	Per Sft.	38.60	325.85	sq.m	415.45	3506.05	26.1	
36	Making and fixing 1" (25 mm) thick kail or chir wooden notice board with frame.	Per Sft.	43.75	113.80	sq.m	470.75	1224.50	ditto	
37	Making deodar punkha pole 10'x6"x6" (3.0 m x 150 mm x 150 mm)	Each	163.70	6511.70	Each	163.70	6511.70	ditto	
38	Dismantling and refixing eave boards.	Per Rft.	11.70		Metre	38.35			

Sr.	Description		Rate (British Sy	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Making wooden stair-cases complete 2' to 3' (600 to 900 mm) wide frame 1 ¹ / ₂ " (40 mm) thick planks of deodar wood, including hand rails.	Per Rft.	174.90	2043.20	Metre	573.70	6701.65	26.1	
40	Providing and fixing partition, including frame work:-								
	a) Sheets on one side of framework:-								
	 i) Hard board ii) Ply wood ¹/4" (6 mm) thick iii) Masonite 	100Sft. ditto ditto	819.85 819.85 819.85	10974.95 12234.95 12738.95	sq.m ditto ditto	88.20 88.20 88.20	1180.90 1316.50 1370.70		
	b) Sheets on both sides of frame work:-		/ ×	\sim					
	 i) Hard board ii) Ply wood ¹/₄" (6 mm) thick iii) Masonite 	100Sft. ditto ditto	983.80 983.80 983.80	12426.95 22681.50 15954.95	sq.m ditto ditto	105.85 105.85 105.85	1337.15 2440.55 1716.75		
1	Providing and fixing ceiling, including frame work:-	100	1		1 . See				
	 i) Hard board ii) Chip board iii) Ply wood ¼" (6 mm) thick iv) Masonite 	100Sft. ditto ditto ditto	1636.25 1636.25 1636.25 1636.25	8131.50 10291.50 10411.50 10051.50	sq.m ditto ditto ditto	176.05 176.05 176.05 176.05	874.95 1107.35 1120.30 1081.55		
42	Providing and fixing thermopore false ceiling, including wooden frame panelling, cost of M.S. clamps, making holes in walls and repairing damaged surface, complete in all respects:-	Ŧ	man ce	Depart					In case of acoustic Thermopore sheet, the composite rate will be increased by Rs.9.00 per Sft.
	a) Deodar wood frame panelling:								
	i) ³ /4" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	1819.60 1819.60	8167.45 8247.25	sq.m ditto	195.80 195.80	878.80 887.40		
	b) Partal wood frame panelling:								
	i) ³ /4" (20 mm) thick ii) 1" (25 mm) thick	100Sft. ditto	1819.60 1819.60	5489.95 5615.95	sq.m ditto	195.80 195.80	590.70 604.30		
.3	a) Fixing door, including chowkats.	Each	260.70	-	Each	260.70	-		
	b) Fixing windows, including chowkats.	ditto	130.35		ditto	130.35	-		

	MRS, BI-ANNUAL PI					•			
Sr. No.	Description		Rate (British Sys	stem)	I	Rate (Metric S	ystem)	Spec. No.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite		
44	 a) Glazing with panes (16 oz. to 18 oz.,) including cost of putty. 	Per Sft.	18.75	46.25	sq.m	201.65	497.70	26.12	
	b) Glazing with panes (16 oz. to 18 oz.) using deodar wooden fillets and putty.	Per Sft.	24.20	75.55	sq.m	260.30	812.75		
45	Glazing with panes (24 oz. to 26 oz.), using putty and deodar wooden fillets.	Per Sft.	35.60	83.35	sq.m	383.30	896.75	26.12	
46	a) Cutting to required size and fixing glass panes with putty	Per Sft.	13.35	14.45	sq.m	143.55	155.55		
	 b) Cutting to required size and fixing glass panes with wooden fillets and putty. 	Per Sft.	19.70	36.40	sq.m	211.70	391.70		
47	Glazing with plate glass 1/4" (6 mm) thick including the cost of deodar wood fillets and putty:-		-						
	a) Glazing upto 8 sft (0.75 sq.m)	Per Sft.	30.15	92.75	sq.m	324.65	998.00		
	 b) Glazing exceeding 8 Sft (0.75 sq.m) but not exceeding 24 sft (2.25 sq.m). 	Per Sft.	30.15	92.95	sq.m	324.65	1000.10		
48	Providing and fixing 1½" (40 mm) thick deodar wood panelled or panelled and glazed, doors and windows, with mild steel chowkat (frame), etc. complete in all respects (excluding sliding bolt or lock) with:-				57				
	 i) M.S. angle iron 1¹/₂"x1¹/₂"x¹/₄", welded i) (40 mmx 40 mmx 6mm) with M.S. flat 2"x¹/₄" (50 mm x 6 mm) 	Per Sft.	117.15	605.90	sq.m	1260.75	6519.45		
	 ii) M.S. tee iron 1½"x1½"x¼", welded (40 mmx40 mmx 6mm) with M.S. flat ½"x¼" (13 mm x 6 mm) 	Per Sft.	117.15	559.25	sq.m	1260.75	6017.30		
49	Providing and fixing 1 ¹ / ₂ " (40 mm) thick hollow flush doors and windows with commercial ply (3 ply) on both faces of deodar wood shutter frame 1 ¹ / ₄ " (30 mm) thick and partal wood braces at about 3" (75 mm) apart and deodar wood lipping 1 ¹ / ₂ "x3/8" (40 mmx10 mm) fixed with M.S. chowkat (frame) including chromium plated fittings, etc. complete in all respects (without sliding bolt or lock):-								Teak ply would be used under the written permission of the superintending Engineer, and the composite rate of using teak ply will be increased by Rs.20.00 per Sft. (216.00 per Sq.m)
	 M.S. angle iron 1¹/₂"x1¹/₂"x¹/₄", welded (40 mmx40 mmx 6mm) with M.S. flat 2"x¹/₄" (50 mm x 6 mm) 	Per Sft.	82.40	506.80	sq.m	886.40	5453.35		

Sr.	Description		Rate (British Sys	stem)	R	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) M.S. tee iron 1¹/₂"x1¹/₂"x¹/₄", welded (40 mmx40 mmx 6mm) with M.S. flat ¹/₂"x¹/₄" (13 mm x 6 mm) 	Per Sft.	82.40	471.50	sq.m	886.40	5073.45		
50	Providing and fixing 1 ¹ / ₂ " (40mm) thick solid flush door shutter (Approved Factory Manufactured) with commercial ply (5 mm thick) on both sides double pressed and deodar wood lipping 1 ¹ / ₂ "x3/8" (40mm x 10mm) around shutter including chromium plated fitting, iron hinges with aluminium kick plate 22 SWG on both sides & finger plate complete in all respect.	Per Sft.	42.85	329.55	sq.m	460.90	3546.05		It C.P. Finger plate and kick plate are not provided/fixed the composite rate will be reduced by Rs.15.20 per Sft. Reduce composite rate by Rs.20.00 per. Sq/ft or Rs.215 per sq.meter if 3-mm commmercial ply is used
51	Providing and fixing panelled door of M.S. sheet, with forged door leaves of M.S. sheet 22 SWG fitted in hollow frame chowkat 3"x4½" (75 mmx113 mm) made of M.S. sheet 18 SWG filled with plain cement concrete 1:3:6 etc. complete with all fittings and hammer painting, including carriage to site and fixing in position.	Per Sft.	80.40	385.50	sq.m	864.85	4147.95		
52	Providing and laying 24 SWG aluminum kick plate 4" (100 mm) high, fixed with screws 4" (100 mm) centre to centre, on bottom rail of flush doors only of commercial ply.	Per Rft.	17.60	31.10	Metre	57.80	102.10		
53	Providing and fitting curtain railing to doors and windows, comprising of TOSO-elite Japan made superior type of railing or equivalent, fixed over 4"x¾" (100mmx20mm) deodar wood strip, including painting.	Per Rft.	7.35	119.35	Metre	24.10	391.45		
54	Providing and fixing M.S. flat ¹ / ₂ "x1/8" (13mm x 3mm) grill including ³ / ₄ " x 1/8" (20 mmx3 mm) M.S. flat frame, in windows of approved design, including painting three coats, complete in all respects.	Per Sft.	41.70	176.25	sq.m	448.95	1896.45		
55	Providing and fixing G.I. wire gauze 22 SWG, 12x12 meshes per square inch, (5x5 meshes in cm ²) fixed to steel window, complete with flat iron patti ¹ / ₂ "x 1/8" (13 mmx3 mm) and machine made screws.	Per Sft.	14.05	54.40	sq.m	151.05	585.20		It 24 SWG wire gauze is used, the composite rate shall be reduced by Rs.4.70 per Sft. or Rs.50.60 per square metre.
56	Providing and fixing wooden moulding stopper 2½"x5/8" (63 x 16 mm) on door frame fitted with ply of approved quality complete in all respects.								
	a) Teak wood moulding	Per Sft.	18.35	100.25	sq.m	197.50	1078.75		

	MRS, BI-ANNUAL P	DISTRICT JH	ANG						
Sr.	Description		Rate (British Sy	stem)	F	Rate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	b) Deodar wood moulding	ditto	18.35	56.30	ditto	197.50	605.60		
57	Providing and fixing deodar wood dolly frame having 1½"x1½" (40 x 40 mm) vertical and horizontal double post with 1½"x1½" (40 x 40 mm) full width of james braces at 12" (300 mm) including filling of the spaces in between braces with 1:3:6 PCC fixing ply of approved quality including holdfasts complete in all respects.								Rate shall be paid as per surface area of dolly frame e-g 0.75' x (3.5' + (2 x 7))
	a) Teak wood plyb) With commercial ply	Per Sft. ditto	40.35 40.35	284.00 276.90	sq.m ditto	434.30 434.30	3055.90 2979.50		
58	Providing and fixing ornamental wooden architrave $3" \times (1\frac{1}{2}"$ tapered to $\frac{1}{4}")$ all along the door frame complete in all respect.		~						
	a) Teak wood architraveb) Deodar wood architrave	Per Sft. ditto	8.00 8.00	62.65 32.80	sq.m ditto	85.85 85.85	674.05 353.10		
59	Providing and fixing Vin board cabinet 3/4" thick with drawers 3"deep in 'Kitchen including termite proofing and polishing with synthetic enamel as specified, with handles hinges, screws etc., complete in all respects.	uno	3.00	52.80	unto	05.05	555.10		
	 i) 1-1/2' deep, without back ii) 1-1/2' deep, with back iii) 2' deep, without back iv) 2' deep, with back 	Per Sft Per Sft Per Sft Per Sft	90.65 90.65 90.65 90.65	472.85 520.85 519.65 567.65	sq.m sq.m sq.m sq.m	975.35 975.35 975.35 975.35	5087.60 5604.10 5591.15 6107.65		
				3	1				

13. PAINTING AND VARNISHING

1 The rates include charges for scaffolding and other arrangements

2 The rates for all finished works include the removal of surplus debris, unused material and by products

	The rates for all finished works include the removal of surplus debris, unused material and by products MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG													
Sr.	Description]	Rate (British Sys	stem)	Rat	te (Metric Sy	vstem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
1	a) Cleaning painted wood work with oil and water.	100 Sft.	91.10	123.65	sq.m	9.80	13.30							
	b) Oiling woodwork with boiled linseed oil.	100 Sft.	60.70	107.50	sq.m	6.55	11.55	27.7						
2	Brushing and scraping blisters of old paints from woodwork.	100 Sft.	182.15	-	sq.m	19.60	-	27.3						
3	Scraping, brushing and removing old paint from metal surface.	100 Sft.	728.65		sq.m	78.40	-	27.9						
4	Painting old surfaces:-				目後に			27.1 27.3 &						
	 Painting corrugated surfaces, patent roofing, etc. with oil paint. 	E.	195	- , %	B			27.9						
	i) first coatii) each subsequent coat	100 Sft. ditto	229.40 173.80	401.00 261.40	sq.m ditto	24.70 18.70	43.15 28.15							
	 b) Painting sashes, fanlights, glazed or gauzed doors and windows:- 		nance (Depart	ment									
	i) first coatii) each subsequent coat	100 Sft. ditto	139.05 118.20	230.25 192.60	sq.m ditto	14.95 12.70	24.75 20.70							
	c) Painting doors and windows, any type:													
	i) first coatii) each subsequent coat	100 Sft. ditto	229.40 173.80	404.60 307.00	sq.m ditto	24.70 18.70	43.55 33.05							
	 Painting guard bars, gates of iron bars, gratings, railing (including standards, braces etc.) and similar open work:- 													
	 i) first coat ii) each subsequent coat e) Painting fillets, framings, skirtings, pipes, gutters and similar linear work not exceeding 6" in girth:- 	100 Sft. ditto	139.05 118.20	230.25 192.60	sq.m ditto	14.95 12.70	24.75 20.70							

	MRS, BI-ANNUAL PER	IOD (1st	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	1	Rate (British Sys	stem)	Rat	te (Metric Sy	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
	i) first coatii) each subsequent coat	100 Lft. ditto	118.20 83.40	209.40 157.80	Metre ditto	3.90 2.75	6.85 5.20							
	 Painting small detached articles, not exceeding one square foot (Sq.m) of painted surface:- 													
	i) first coatii) each subsequent coat	100 Nos. ditto	350.65 316.80	522.25 408.00	100 Nos. ditto	350.65 316.80	522.25 408.00							
	 g) Painting small detached articles, exceeding one square foot (Sq.m) but not exceeding three square feet (Sq.m) of painted surface:- 													
	i) first coatii) each subsequent coat	100 Nos ditto	801.45 465.75	1312.65 721.35	100 Nos ditto	801.45 465.75	1312.65 721.35							
5	Painting new surface:-				ゴム。			27.1 27.2 &						
	a) Preparing surface and painting corrugated surface, patent roofing, etc.	Sec. Sec.			18			27.2 & 27.9						
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	348.35 122.20	571.55 335.80	sq.m ditto	37.50 13.15	61.50 36.15							
	 b) Preparing surface and painting sashes, fan light, glazed or gauzed doors and windows etc. any type (including edges):- 	Fi	nance (Depart										
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	146.65 100.10	300.85 221.30	sq.m ditto	15.80 10.75	32.35 23.80							
	 Preparing surface and painting of doors and windows any type (including edges):- 													
	i) priming coat.ii) each subsequent coat of paint.	100 Sft. ditto	348.35 122.20	567.95 335.80	sq.m ditto	37.50 13.15	61.10 36.15							
	 d) Preparing surface and painting guard bars, gates of iron bars, gratings, railing (including standards, braces, etc.) and in similar open work:- i) priming coat. 	100 Sft.	224.25	357.45	5 4 m	24.15	38.45							
	i) priming coat. ii) each subsequent coat of paint.	ditto	100.10	221.30	sq.m ditto	10.75	38.45 23.80							

	Description	1	Rate (British Sys	stem)	Rat	te (Metric Sy	stem)	Spec.	Remarks
•		Unit	Labour	Composite	Unit	Labour	Composite	No.	
e)	Preparing surface and painting of fillets, framing, skirtings, pipes, gutters, and similar linear work not exceeding 6" (150 mm) girth:-								
	i) priming coat.ii) each subsequent coat of paint.	100 Lft. ditto	177.30 66.75	278.10 166.35	Metre ditto	5.80 2.20	9.10 5.45		
f)	Preparing surface and painting of small detached articles, not exceeding one sq. ft. (Sq.m) of painted surface:-								
	i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	521.40 256.85	1053.60 680.45	100 Nos. ditto	521.40 256.85	1053.60 680.45		
g)	Preparing surface and painting of small detached articles, exceeding one Sft. but not exceeding 3 Sft. (Sq.m) of painted surface:-	.de b			Ju.				
	i) priming coat.ii) each subsequent coat of paint.	100 Nos. ditto	1483.35 445.50	2354.55 1205.10	100 Nos. ditto	1483.35 445.50	2354.55 1205.10		
h)	Extra for knotting and stopping to priming coat on new surface of wood.	100 Sft.	23.50	38.60	sq.m	2.55	4.15		
Ap	pplying Khanki Mixture hot to barrage		- 0					27.10	
	tes:-	19	NANCE (Depart					
i) ii)	first coat second coat	100 Sft. ditto	173.80 138.55	425.65 298.80	sq.m ditto	18.70 14.90	45.80 32.15		
Fre	ench polishing complete:-							27.6	
a) b)	on new work on old work	100 Sft. ditto	1770.70 931.55	1833.10 965.15	sq.m ditto	190.55 100.25	197.25 103.85		
	arnishing wood work, including cleaning and preparing rface.								
a) b) c)	first coat second coat third coat	100 Sft. ditto ditto	139.05 52.15 52.15	263.25 146.30 126.70	sq.m ditto ditto	14.95 5.60 5.60	28.35 15.75 13.65		

	MRS, BI-ANNUAL PER	IOD (1st	AUGUST, 20	012 TO 31st	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description]	Rate (British Sys	stem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 20 lbs. per 100 Sft. (9.07 Kg per Sq.m) ii) 14 lbs. per 100 Sft. (6.35 Kg per Sq.m) iii) 10 lbs. per 100 Sft. (4.54 Kg per Sq.m) 	100 Sft. ditto ditto	151.80 145.75 120.25	1123.70 637.30 611.80	sq.m ditto ditto	16.35 15.70 12.95	120.90 68.60 65.85		
10	Writing letters or figures, per letter, per inch (25 mm) height.	Per No.	6.95	7.55	Per No.	6.95	7.55	27.1	
11	Writing letters or figures at any surface with reflective paint of approved quality and colour per letter per inch height.	Per Letter per inch height	6.95	7.30	Per Letter per 25 mm height	6.95	7.30	27.1	
12	Writing letters of figures on any surface with reflective tape of approved quality and colour per letter per inch (25 mm) height.	ditto	8.15	9.00	ditto	8.15	9.00	ditto	
13	Coaltar painting:	ide			Jui.			27.8 to	
	a) first coat, laid hotb) second coat, laid hot	100 Sft. ditto	121.95 73.90	891.05 556.60	sq.m ditto	13.10 7.95	95.90 59.90	27.11	
14	Solignum painting:-	100	-55		-49 197			27.8	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	129.25 195.80	155.65 238.05	sq.m ditto	13.90 21.05	16.75 25.60		
15	Creosote painting:-	Fa	nance (Depart				ditto	
	a) one coat, applied hotb) two coats, applied hot	100 Sft. ditto	155.05 234.95	270.25 428.15	sq.m ditto	16.70 25.30	29.10 46.05		
16	Burning off or rubbing down with pumice stone, old paint from wood work.	100 Sft.	460.70	476.30	sq.m	49.55	51.25	27.3	
17	Removing with caustic soda, old paint from wood work.	100 Sft.	182.15	189.90	sq.m	19.60	20.45	ditto	
18	Painting distance marks for white ground and black lettering on both sides.	Each	34.75	41.35	Each	34.75	41.35	27.1	
19	Painting two feet wide gauges, reading to 10th of a foot (metre).	Per Rft.	69.50	82.25	per Metre	228.05	269.75	ditto	
20	Painting sounding rods and other gauges, reading to 10th	Per Lft.	34.75	38.70	per Metre	114.00	127.00	27.1	

	MRS, BI-ANNUAL PER	IOD (1st	AUGUST, 2	012 TO 31st	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description]	Rate (British Sy	stem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	of a foot (metre)								
21	Painting leveling staves.	Per Lft.	108.70	115.05	per Metre	356.45	377.35		
22	a) Painting and lettering mile/Km stones, on both sides:							ditto	
	i) one coatii) two coats	Each ditto	74.50 130.35	120.10 203.55	Each ditto	74.50 130.35	120.10 203.55		
	b) Painting and lettering Furlong/½ Km stones, on both sides:-							27.1	
	i) one coatii) two coats	Each ditto	9.95 17.40	15.35 26.85	Each ditto	9.95 17.40	15.35 26.85		
	c) Painting and lettering Sign posts:-	id.			Juli.				
	i) one coatii) two coats	Each ditto	83.40 137.65	113.00 188.05	Each ditto	83.40 137.65	113.00 188.05		
23	Removing paint or varnish from wall.	100 Sft.	364.30		sq.m	39.20	-	27.12	
24	Scraping from hydraulic gates:-	_	- A	S. P.				27.1	
	a) Khanki paintb) Aluminium paint	100 Sft. ditto	728.65 728.65	Depart	sq.m ditto	78.40 78.40	- -		
25	Painting letters with shade.	per letter per inch height	11.10	11.10	per letter per 25 mm height	11.10	11.10	27.1	
26	Scraping rust from old rail or girders.	100 Sft.	546.50	585.50	sq.m	58.80	63.00	27.9 27.10	
27	Chiselling old paint from brick work.	100 Sft.	728.65	758.65	sq.m	78.40	81.65	27.12	
28	Cleaning glasses with chalk and spirit, etc.	100 Sft.	607.20	621.40	sq.m	65.35	66.85		
29	Cleaning and oiling rafter or rolled steel beams.	100 Sft.	182.15	225.80	sq.m	19.60	24.30	27.9	
30	Cleaning and painting punkha poles, including fixing	Each	115.50	123.30	Each	115.50	123.30	27.3	

	MRS, BI-ANNUAL PER	DISTRICT J	HANG						
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	hooks.								
31	Preparing surface and painting with emulsion paint:-							27.12	
	a) first coatb) 2nd and each subsequent coat	100 Sft. ditto	176.95 135.70	358.80 278.30	sq.m ditto	19.05 14.60	38.60 29.95		
32	Preparing surface and painting with water proof coloured cement finish, like duracem, buxcem or other finishes with similar specifications, on walls, etc.							27.12	
	a) new surface:								
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	176.95 135.70	256.15 205.10	sq.m ditto	19.05 14.60	27.55 22.05		
	b) old surface:	ide !			Jui.				
	i) 1st coatii) 2nd and subsequent coat	100 Sft. ditto	176.95 135.70	210.30 168.40	sq.m ditto	19.05 14.60	22.65 18.10		
32A	Providing and applying weather shield paint of approved quality on external surface of building including preparation of surface, application of primer complete in all respect:	-0710			7779438				
	a) new surface:								
	i) 1st coatii) 2nd coat	%sft %sft	599.30 329.00	1056.30 530.00	sq.m sq.m	64.50 35.40	113.65 57.05		
	b) old surface:	%sft	329.00	530.00	sq.m	35.40	57.05		
33	Painting traffic lane 5" (125 mm) wide, with road marking enamel.	Per Rft.	1.05	1.90	Metre	3.40	6.25		
34	Painting traffic lane 5" (125 mm) wide with reflective clorinated rubber (CR) paint including glass beads comlpete	Per Rft.	1.25	9.30	Metre	4.05	30.45	AASHTO M248-91	Rates shall be reduced by Rs.0.50 P.Rft or Rs.1.65 P.Mtr. If glass beads
35	in all respect. Repainting of ceiling fan (all sizes and types), including painting of blades, canopy, suspension rod and regulator, with suitable enamel paint.	Per Job	41.95	74.35	Job	41.95	74.35	(2000)	are not used.
36	Repainting of iron poles with cross arms, with bitumen or	Per Job	97.90	214.30	Job	97.90	214.30		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description	R	ate (British Syste	em)	Ra	te (Metric Sy	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	other approved paint.												
37	Repainting of pipes and specials of G.I., M.S. or conduit, etc., fixed for on surface electric wiring, with approved paint:												
	 i) upto 40 mm (1½") dia ii) above 40 mm (1½") to 50 mm (2") dia iii) above 50 mm (2") to 100 mm (4") dia 	Per Rft. ditto ditto	0.90 1.80 3.00	2.95 3.70 5.85	Metre ditto ditto	2.95 5.85 9.80	6.60 12.20 19.25						
38	Repainting main switches and branch distribution boards of all sizes and types, with approved paint (complete set).	Per Job	19.40	65.95	Job	19.40	65.95						
39	Extra labour for painting, varnishing, etc. from 20' (6.10 m) height and above, for every additional 10' (3.05 m) height, or part thereof, requiring scaffolding.	100 Sft. per coat	58.30		sq.m	6.25	-		The height will be taken from the floor, roof or ground underneath, as the case may be on the side towards which the work is to be done.				

Finance Department

14. LINING OF CANALS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts

2 The rates also include curing for specified period wherever necessary.

3 Nominal dimension of tile or brick shall be taken for the purpose of measurement and payment.

	MRS, BI-ANNUAL	13) DISTRICT	JHANG						
Sr.	Description		Rate (British Sy	rstem)	I	Rate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Formation, dressing and preparing sub-grade:-							28.1 to 28.3	
	a) in bed b) on slope	100Sft. ditto	402.50 549.10	-	sq.m ditto	43.30 59.10	-		
2	Stabilized layer of cement, sand ratio 1:30, 2" (50 mm) thick on slope.	100Sft.	966.25	1419.85	sq.m	103.95	152.80	ditto	
3	Cement plaster 1⁄2" (13 mm) thick ratio 1:10.		. ($\langle \rangle$			ditto	
	a) in bed b) on slope	100Sft. ditto	704.20 875.15	925.80 1096.80	sq.m ditto	75.75 94.15	99.60 118.00		
4	Cement plaster 3/8" (10 mm) thick ratio 1:3.	50	1 18	حکومت ینجا-	7_ <u>i</u> #	22		ditto	
	a) in bedb) on slope	100Sft. ditto	704.20 875.15	1094.05 1265.05	sq.m ditto	75.75 94.15	117.70 136.10		
5	Cement plaster 1 ¹ / ₂ " (40 mm) thick ratio 1:6.		Fimane	ne Deepa		mt		ditto	
	a) in bed b) on slope	100Sft. ditto	875.15 1083.70	1810.20 2018.80	sq.m ditto	94.15 116.60	194.80 217.20		
6	Tile lining 12"x6"x2" (300x 150x50 mm) in 1:6 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are
	a) in bedb) on slope	100Cft. ditto	4092.00 4694.25	13352.85 13955.10	cu.m ditto	1445.30 1658.00	4716.25 4928.95		payable separately.
7	Tile lining 12"x6"x2" (300x150x50 mm) in 1:3 cement, sand mortar:-							28.2 to 28.3	The rates are only for laying tiles over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to 5 above are
	a) in bed	100Cft.	4092.00	14645.40	cu.m	1445.30	5172.75		payable separately.
	b) on slope	ditto	4694.25	15247.65	ditto	1658.00	5385.45		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	vstem)]	Rate (Metric	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
8	Brick lining 9"x4 ¹ /2"x3" (225x113x75 mm) in 1:6 cement, sand mortar:- a) in bed	100Cft.	4092.00	15872.85	cu.m	1445.30	5606.30	28.2	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:6 mortar. Items 1 to 5 above are payable separately.			
9	 b) on slope Brick lining 9"x4¹/₂"x3" (225x113x75 mm), in 1:3 cement, sand mortar:- 	ditto	4694.25	16475.10	ditto	1658.00	5819.00	ditto	The rates are only for laying bricks over 1/8" (3 mm) thick layer of 1:3 mortar. Items 1 to			
	a) in bed b) on slope	100Cft. ditto	4092.00 4694.25	17165.40 17767.65	cu.m ditto	1445.30 1658.00	6062.80 6275.55		5 above are payable separately.			
10	Cement concrete lining, using washed screened and graded stone aggregate:- a) in bed:-			C*				20.1, 28.1 & 28.3				
	i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8	100Cft. ditto ditto	3597.00 3597.00 3597.00	17103.25 14917.80 13354.45	cu.m ditto ditto	1270.45 1270.45 1270.45	6040.85 5268.95 4716.80					
	 b) on slope:- i) ratio 1:2:4 ii) ratio 1:3:6 iii) ratio 1:4:8 	100Cft. ditto ditto	4153.05 4153.05 4153.05	17659.30 15473.85 13910.50	cu.m ditto ditto	1466.85 1466.85 1466.85	6237.25 5465.35 4913.20					

15. SHEET PILING

Rates for all finished works include the removal of surplus debris, unused material and by products

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Cutting Ransome and Larson piles.	Per cut	117.50	-	Per cut	117.50	-	29.1- 29.3					
2	Cutting universal piles.	Per cut	173.85	-	Per cut	173.85	-	ditto					
3	Driving steel piles, 25' to 30'. (7.5 to 9.0 m)	100Sft.	2299.45		sq.m	247.40	-	ditto	 The rate includes laying and removing of track and also carriage of piles to machine, average distance of 3 chains (90 metre). The rates are for the tackle gangs only supplied by the contractor, Mechanical staff on-machines will be supplied by Government. 				
				P	i da	2			 T-piles and adjustable junction piles will be counted as two piles. 				
4	Driving steel piles, more than 15' (4.6 m) and less than 25' (7.5 m).	100Sft.	2207.05	ce Dep	sq.m	237.50	-	ditto	ditto				
5	Driving steel piles, 15' (4.5 m) and under.	100Sft.	1652.65	-	sq.m	177.85	-	ditto	ditto				
6	Dolleying piles.	Each	146.80	-	Each	146.80	-	ditto	Upto 5' (1.5 m) dolleying.				
7	Drilling holes in piles by hand.	Each	16.15	-	Each	16.15	-	ditto					
8	Raising and lowering machine.	Per Ft.	2230.80	-	Metre	7317.00	-	ditto					
9	Turning Machine, 90°.	Per Job	3400.30	-	Per Job	3400.30	-	29.1 to 29.3					
10	Turning Machine, 135°.	Per Job	4139.50	-	Per Job	4139.50	-	ditto					
11	Turning Machine, 180°.	Per Job	5607.35	-	Per Job	5607.35	-	29.1 to 29.3					

	MRS, BI-ANNUAL	PERIOD	(1st AUGUS	ST, 2012 TO	31st JA	NUARY, 2	2013) DISTF	RICT JHAN	G
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
12	Travelling machine (light).	Per Chain	6640.90	-	30 M.	6640.90	-	ditto	
13	Loading and unloading piles.	Ton	134.80	-	Tonne	132.65	-	ditto	To be done by hand carts or ramps, including cost of ropes.
14	Dismantling piling machine.	Each	14692.90	-	Each	14692.90	-	ditto	
15	Erecting piling machine.	Each	16953.35	-	Each	16953.35	-	ditto	
16	Carriage of piling machine under different conditions.	per chain	2760.10	×	30 M	2760.10	-	ditto	



Finance Department

16. PROTECTION & DIVERSION WORKS

- 1 Rates for all finished works include the removal of surplus debris, unused material and byproducts
- 2 The composite rates of the items in which stone, boulders, shingle spawl are used do not contain the carriage of the these stone materials, which will be paid separately by road, and/or rail, whichever means of transport is adopted. The supply and carriage to site of work of all other material required in the item, is included in the composite rates.
- 3 The carriage of stone or spawl will be paid on the basis of actual stack measurement (without any reduction factor) of the stone, boulders, shingle or spawl carried.
- 4 Where stone, boulder or spawl is issued from stock and contractor is paid for its carriage and/or labour only; or where such stone product is supplied, carried or handled by the contractor in which no laying is required, the actual stack measurement (without any reduction factor) shall from the basis of payment of supply or carriage of the stone, boulder or spawl, etc. The quantity of finished and completed item of work shall form the basis of laying.
- 5 In case of the items in which the rates include carriage of stakes, bushing, Pilchi, sarkanda or farash, etc. within one mile (1.6 Km.)
 - i) the cost of the carriage within one mile (one Km) shall not be deducted from the carriage charges to follow thereafter from the point of supply.
 - ii) if the site of work happens to be within one mile (one Km.) of the source of supply, the materials will be collected and measured at site of work and no extra carriage would be admissible in such cases.
 - iii) where the site of the work is situated at more than one mile (one Km.) distance from the source of supply, the point of supply will be fixed carefully by the Engineer-in-charge in such a way that the carriage charges would be arrived at, most economically. Extra carriage will be admissible from the place of supply of the material which will be considered its starting point. The demarcation of the place of supply will be pre-determined before calling the tenders.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description	Ra	te (British Syste	em)	Rat	te (Metric Sy	rstem)	Spec.	Remarks				
No.	1	Unit	Labour	Composite	Unit	Labour	Composite	No.					
1	Cutting pilchi frash or sarkanda inlcuidng carriage within one mile.	100Cft.	692.20		cu.m	244.45							
2	Weaving matresses.	100Cft.	1311.55		cu.m	463.20							
3	 Supplying and filling jute bags 1.25 (0.035 cum) Cft., capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	20.50	35.35	Per Baq	20.50	35.35		The rate does not include supply of sand or earth for filling bags, which will be paid extra.				
	 b) Supply and filling jute bags 1.25 (0.35 ccum) Cft. capacity, with sand or earth, sewing and laying in position, under water. 	ditto	31.90	46.70	Per Baq	31.90	46.7		-ditto-				
4	 a) Supplying and filling jute bags 4 to 5 cft (0.11 to 0.14 cum) capacity, with sand or earth, sewing and stacking, in dry. 	Per Bag	49.05	100.60	Per Bag	49.05	100.60		The rate does not include supply of sand or earth for filling bags, which will be paid extra.				

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	/stem)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	 b) Supply and filling new jute bags 4 to 5 cft (0.11 to 0.14 cu.m) capacity, with sand or earth, sewing and laying in position, under water. 	ditto	70.05	121.60	ditto	70.05	121.6		-ditto-	
5	Carriage of jute bags 1.25 Cft. (0.035 cu m) capacity, filled with sand or earth:-									
	a) 1st chain (30 m)	100 Nos	182.15		% Nos	182.15				
	b) 2nd to 4th chain (30 m to 120 m)	Per chain per 100 Nos	65.60	5	Per 30 m Per 100 Nos/	65.60				
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	25.50		ditto	25.50				
6	Carriage of new jute bags 4 to 5 Cft.(0.11 to 0.14 cu.m) capacity, filled with sand or earth:-	A MAR	55		ST I					
	a) 1st chain (Ist 30 metre)	100 Nos	728.65	Depart	% Nos	728.65				
	b) 2nd to 4th chain (60 m to 120 m)	per chain per 100Nos	255.00		Per 30 m per %Nos	255.00				
	c) 5th and subsequent chains (150 m and subsequent every 30 m)	ditto	98.35		ditto	98.35				
7	Rolling matresses to river edge and floating, after unroling:-									
	a) area of matress upto 2,000 Sft. (186 sq.m)	100Sft.	409.85		sq.m	44.10				
	b) area of matress 2,000 to 2,500 Sft. (186 sq.m to 232 sq.m)	100Sft.	683.10		sq.m	73.50				
	c) area of matress over 2,500 Sft. (232 sq.m)	ditto	796.95		ditto	85.75				
8	Sewing empty cement bags in sheets.	100 Nos	637.55	671.15	% Nos	637.55	671.15			
9	Making compact round pilchi, frash or sarkanda round bundles of specified size for the work.	100Cft.	888.05	986.05	cu.m	313.65	348.3		Measured in the shape of compact round bundles and of size specified	

						···, _•·•,	DISTRICT J		
Sr.	Description	Ra	ate (British Syste	em)	Ra	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
									for the work, before filling at site.
10 La	aunching the above and placing in position.	100Cft.	437.20		cu.m	154.40			
11 St	upply within 5 chains (150 m):-								
a)) Boulders 9" (225 mm) and above	100Cft.	1318.85		cu.m	465.75			
b)) Over size shingle 3" to 9"(75 to 225 mm)	ditto	881.65		ditto	311.35			
c)) Mixed graded shingle	ditto	1045.60		ditto	369.25			
	upplying Munj or Patha Trungers 6" (150 mm) mesh to hold Cft. (0.085 cu.m)	Each	56.95	99.55	Each	56.95	99.55		
G	Providing and weaving G.I. wire netting for wire crates, with G.I. wire of approved size (including siding and partition to nake crate):-								
a)) 6" (150 mm) mesh	8			38				
	i) 15 SWG wire	100Sft.	729.95	988.70	sq.m	78.55	106.40		
	ii) 10 SWG wire iii) 8 SWG wire	ditto ditto	782.10 782.10	1622.10 2099.20	ditto ditto	84.15 84.15	174.55 225.9		
b)) 4" (100 mm) mesh	1			53				
	i) 15 SWG wire	100Sft.	938.50	1355.20	sq.m	101.00	145.8		
	ii) 10 SWG wire	ditto	1042.80	2300.30	ditto	112.20	247.50		
	iii) 8 SWG wire	ditto	1042.80	3014.30	ditto	112.20	324.35		
	roviding and laying shingle on top of bund, including and laying shingle on top of bund, including of materials within three chains.	100Cft.	455.40	785.40	cu.m	160.85	277.40		
15 Su ha	upply and dumping at site, without boat, including and ling of materials within three chains (90 m)								
a)) stone or boulder	100Cft.	796.95	1258.95	cu.m	281.45	444.6		The rate includes supply of brick
b)) shingle or spawl	ditto	796.95	1126.95	ditto	281.45	398		bats to site of work.
c)		ditto	614.80	1472.80	ditto	217.15	520.20		
w	upply and dumping by boat, including loading into boat vithin three chains (90 m) lead, and hire charges of boat and oatman.								The rate includes supply of brick bats to site of work.
رة) stone or boulder	100Cft.	1386.00	1848.00	cu.m	489.55	652.7		
a) b)		ditto	1386.00	1716.00	ditto	489.55	606.10		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	c) brick bats	ditto	1203.85	2061.85	ditto	425.20	728.25				
17	Providing and filling brick bats in crates (excluding cost of crates).	100Cft.	1054.00	1912.00	cu.m	372.30	675.35		The rate includes supply of brick bats to site of work.		
18	Supplying and filling bricks in crates and hand packing (excluding cost of crates).	100Cft.	1281.70	12081.70	cu.m	452.70	4267.25		The rate includes supply of bricks to site of work.		
19	Supply and filling in wire crates, including sewing crates (excluding cost of crates):-										
	i) stone or boulderii) shingle or spawl	100Cft. ditto	1463.90 1463.90	1925.90 1793.90	cu.m ditto	517.05 517.05	680.20 633.60				
20	Extra for anchoring boat, for dumping by boats or tipping crates.	100Cft.	160.30		cu.m	56.60	-				
21	Extra for tipping crates (in addition to anchoring boats).	100Cft.	801.50		cu.m	283.10	-				
22	Pilchi reventment, including carriage upto one mile (1.6 km.)	100Sft.	455.40	955.40	sq.m	49.00	102.8	30.1			
23	Surface protection with pilchi matresses, carriage upto one mile (1.6 Km).	100Sft.	1138.50	1188.50	sq.m	122.50	127.90	ditto			
24	Pilchi, sarkanda or frash pitching on slopes, including supply of pilchi, sarkanda or frash within one mile, (1.6 km) also supply and driving of pegs 1 ¹ /2' (460 mm) long sharpened at one end and, tying with wire or Munj Ban (excluding cost of placing earth between rolls).	100Sft.	2525.35	3609.05	sq.m	271.75	388.35		The cost of placing earth between rolls shall be paid separately, as earthwork.		
25	Constructing Groynes upto 5' (1.5 m) height, with single row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 1' (300 mm) apart, average lead one mile (1.6 km.)	100Sft.	848.10	933.70	sq.m	91.25	100.45		Measurement to be made of the area of elevation on one face only.		
26	Construction Groynes upto 10' (3.0 m) height, with double row of wooden vertical stakes 7" to 12" (175 to 300 mm) dia, 2' (600 mm) apart, average lead one mile (1.6 Km).	100Sft.	1465.20	1567.25	sq.m	157.65	168.65				
27	Providing and laying stone pitching/filling, dry hand packed, as filling behind retaining walls or in pitching and aprons.	100Cft.	917.40	1646.40	cu.m	324.05	581.5				
28	Providing and laying stone pitching with hammer dressed stones on surface, laid in courses.	100Cft.	2687.85	3335.85	cu.m	949.35	1178.2				

	MRS, BI-ANNUAL PI	ERIOD (1st	AUGUST, 20	012 TO 31st	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	R	ate (British Syst	em)	Ra	te (Metric Sy	ystem)	Spec. Remarks	
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
29	Providing and laying stone pitching, for top layer only:-								
	a) one slope b) on level	100Cft. ditto	2247.30 2019.60	2895.30 2667.60	cu.m ditto	793.75 713.30	1022.6 942.2		
30	Providing and laying stone or spawl filling:-								
	a) on level	100Cft.	602.25	902.25	cu.m	212.70	318.70		
	b) on slope	ditto	737.35	1037.35	ditto	260.45	366.4		
31	Providing and laying stone pitching, hand packed, with surface levelled off to the correct section and voids filled in 1:8 cement, sand mortar, in floors of bridges along banks and in appons etc.		~						
	 i) top layer on slope ii) top layer on level iii) stone pitching/filling on slope or on level (other than top layer). 	100Cft. ditto ditto	2965.50 2737.80 1588.30	5298.30 5070.60 4002.10	cu.m ditto ditto	1047.40 967.00 561.00	1871.35 1790.95 1413.55		
32	Grouting stone pitching or apron, etc. in:-	1			53				
	a) cement, sand mortar 1:3b) cement, sand mortar 1:8	100Sft. ditto	1019.45 864.60	4370.70 2549.40	sq.m ditto	109.70 93.05	470.3 274.30		
33	Sand grouting in stone apron, with high pressure hose.	100Sft.	345.20	885.20	sq.m	37.15	95.25		
34	Grouting stone filling or pitching, with bajri.	100Cft.	569.25	1217.25	cu.m	201.05	429.95		
35	Removing stone and repitching hand packed, on slopes or level after making good damaged slope/portion.	100Cft.	2107.50	-	cu.m	744.35	-		
36	Collecting and stacking boulders from nullah beds or loose shale, or from any other site, within 3 chains (90 m) lead.	100Cft.	728.65	-	cu.m	257.35	-		
37	Levelling and dressing stone filling under blocks and grouting with shingle.	100Cft.	602.25	1250.25	cu.m	212.70	441.60		
38	Grouting jharies between blocks with bajri.	100Cft.	602.25	1034.25	cu.m	212.70	365.30		
39	Breaking stone into spawls and stacking	100Cft.	546.50	-	cu.m	193.00	-		
	Canal and Roads								

	MRS, BI-ANNUAL PI	ERIOD (1st	AUGUST, 2	012 TO 31st	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
40	Fixing floating spurs, with material from canal plantation within one mile (1.6 Km) lead:-								
	a) upto 2.0' (600 mm) F.S. depth	Each	18.80	-	Each	18.80	-		
	b) above 2.0' to 3.0' (600 to 900 mm) F.S. depth	ditto	21.15	-	ditto	21.15	-		
	c) above 3.0' to 4.0' F.S. (900 mm to 1200mm) depth	Each	28.20	-	ditto	28.20	-		
	d) above 4.0' (1200 mm) F.S. depth	ditto	70.55	-	ditto	70.55	-		
41	Staking and bushing from canal plantation, royalty to be paid to Forest Department or cost to private owner, if and when required:-		~						
	 a) i) Cutting and supply unsharpened pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia, within one mile (1.6 Km) lead. 	100 Nos	910.80	942.30	% Nos	910.80	942.30		
	ii) Sharpening one end of 3.5' (1.07 m) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	417.10	- 19	100 Nos	417.10	-		
	 iii) Driving pegs 3.5' (1.07 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average). 	100 Nos	517.45		100 Nos	517.45	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of One Row	45.55	75.20	Per 30 Metre of one row	45.55	75.20		
	 v) Cutting and supplying brush wood from canal plantation or private owners, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	648.10	817.30	ditto	648.10	817.30		
	 b) i) Cutting and supplying unsharpened pegs 4.0' (1.20 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	86.85	122.70	100 Nos	86.85	122.70		
	ii) Sharpening one end of 4' (1.20 M) long pegs, 3" to 6" (75 to 150 mm) dia.	100 Nos	417.10	-	100 Nos	417.10	-		
	 iii) Driving pegs 4' (1.20 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.0' (300 mm) below the available bed or ground (average). 	100 Nos	635.55	-	100 Nos	635.55	-		

	MRS, BI-ANNUAL PE								
Sr.	Description	R	ate (British Syst	em)	Rat	e (Metric Sy	rstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	45.55		Per 30 M of one row	45.55			
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km). and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	ditto	1600.50		ditto	1600.50			
	 c) i) Cutting and supplying unsharpened pegs 5.0' (1.5 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	108.60	153.45	100 Nos	108.60	153.45		
	ii) Sharpening one end of 5' (1.5 m) long pegs, 3" to6" (75 to 150 mm) dia.	100 Nos	440.60		100 Nos	440.60	-		
	iii) Driving pegs 5' (1.5 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.5' (450 mm) below the available bed or ground (average).	100 Nos	733.90		100 Nos	733.90	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per Chain of one row	45.55	75.20	Per 30 M of one row	45.55	75.20		
	v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).	Per chain of one row	693.00	929.70		693.00	929.70		
	 d) i) Cutting and supplying unsharpened pegs 6.0' (1.8 m) long, 3" to 6" (75 to 150 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1821.60	1875.40	100 Nos	1821.60	1875.4		
	ii) Sharpening one end of 6' (1.8 m) long pegs, 3" to6" (75 to 150 mm) dia.	100 Nos	524.05	-	100 Nos	524.05	-		
	iii) Driving pegs 6' (1.8 m) long, 3" to 6" (75 to 150 mm) dia (driven 1.75' (530 mm) below the available bed or ground (average).	100 Nos	880.70	-	100 Nos	880.70	-		
	iv) Tying pegs with Munj, Patha ban (one line,	Per			Per Chain				

	MRS, BI-ANNUAL PE								
Sr.	Description	R	ate (British Syste	em)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	incuding tying around the pegs).	Chain of one row	45.55	75.20	of one row	45.55	75.20		
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	1828.20	2115.65	ditto	1828.20	2115.65		
	 e) i) Cutting and supplying unsharpened pegs 6'-1" to 8.0' long (1.85 to 2.45 m), 4" to 8" (100 to 200 mm) dia, from canal plantation, lead within one mile (1.6 Km). 	100 Nos	1366.20	1477.80	100 Nos	1366.20	1477.80		
	ii) Sharpening one end of 6'-1" to 8.0' (1.85 to 2.45m) long pegs, 4" to 8" (100 to 200 mm) dia.	100 Nos	667.40		100 Nos	667.40	-		
	iii) Driving pegs 6'-1" to 8.0' (1.85 to 2.45 m) long, 3"to 6" (75 to 150 mm) dia driven 2' (600 mm) belowthe available bed or ground (average).	100 Nos	972.30	- 190	100 Nos	972.30	-		
	iv) Tying pegs with Munj, Patha ban (one line, incuding tying around the pegs).	Per chain of one row	45.55	61.95	Per 30 M of one row	45.55	61.95		
	 v) Cutting and supplying brush wood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	Per Chain of one row	2059.20	2397.40	Per 30 M of one row	2059.20	2397.40		
42	Staking with Bamboo from market and bushing from canal plantation or private source (royalty of brushwood to be paid to Forest Department or cost to private owner, if and when required):-								
	 a) i) Supplying Bamboos 8'-1" to 10.0' (2.46 to 3.05 m) long, 2¹/₂" to 5" (63 m to 125 mm) dia. 	100 Nos	7200.00	-	100 Nos	7200.00	-		
	 ii) Sharpening one end of 8'-1" to 10.0' (2.46 to 30.5 m) long Bomboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	583.95	-	100 Nos	583.95	-		
	iii) Driving Bamboos 8'-1" to $10.0'$ (2.46 to 3.05 m) long $2\frac{1}{2}"$ to 5" (63 to 125 mm) dia, driven $2.5'$ (750 mm) below the available bed or ground (average).	100 Nos	1064.20	-	100 Nos	1064.20	-		

	MRS, BI-ANNUAL PE	Y, 2013) I	DISTRICT J	HANG					
Sr.	Description	Ra	ate (British Syste	em)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with Munj, Patha Ban, two lines, including tying around the Bamboos.	Per Chain of one row	68.30	114.80	Per 30 M of one Row	68.30	114.80		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km), and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	2517.90	2957.10	ditto	2517.90	2957.10		
b	 i) Supplying Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	-	10800.00	100 Nos	-	10800		
	 ii) Sharpening one end of 10'-1" to 12.0' (3.07 to 3.66 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	667.40		100 Nos	667.40	-		
	iii) Driving Bamboos 10'-1" to 12.0' (3.07 to 3.66 m) long $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia, driven 2.75' (840 mm) below the available bed or ground (average).	100 Nos	1155.80		100 Nos	1155.80	-		
	iv) Tying Bamboos $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	227.70	838.40	Per 30 M of one Row	227.70	838.40		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	3088.80	3646.80	ditto	3088.80	3646.80		
с	 i) Supplying Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	-	11400.00	100 Nos	-	11400.00		
	 ii) Sharpening one end of 12'-1" to 14.0' (3.68 to 4.27 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	750.80	-	100 Nos	750.80	-		
	iii) Driving Bamboos 12'-1" to 14.0' (3.68 to 4.27 m) long $2\frac{1}{2}$ " to 5" dia, driven 3.5' (1.07 mm) below the available bed or ground (average).	100 Nos	1321.05	-	100 Nos	1321.05	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per chain of one row	227.70	838.40	Per 30 M of one row	227.70	838.40		
	v) Cutting and supplying brushwood from canal	ditto	3659.70	4302.30	ditto	3659.70	4302.30		

	MRS, BI-ANNUAL P	ERIOD (1st	AUGUST, 20)12 TO 31st	JANUAR	Y, 2013)	DISTRICT J	HANG	
Sr.	Description	R	ate (British Syst	em)	Rat	te (Metric Sy	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average).								
	 d) i) Supplying Bamboos 14'-1" to 16.0' (4.30 to 4.90 m) long, 2¹/₄" to 5" (63 to 125 mm) dia. 	100 Nos	-	12600.00	100 Nos	-	12600.00		
	ii) Sharpening one end of $14'-1"$ to $16.0'$ (4.30 to 4.90 m) long Bamboos, $2\frac{1}{2}"$ to $5"$ (63 to 125 mm) dia.	100 Nos	834.25	-	100 Nos	834.25	-		
	iii) Driving Bamboos 14'-1" to 16.0' long (4.30 to 4.90m) $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1467.85	-	100 Nos	1467.85	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one Row	227.70	838.40	Per 30 M of one Row	227.70	838.40		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	4209.50	4953.50	ditto	4209.50	4953.50		
	 e) i) Supplying Bamboos 16'-1" to 20' (4.9 to 6.10 m) long, 2¹/₂" to 5" (63 to 125 mm) dia. 	100 Nos	the second s	13200.00	100 Nos	-	13200.00		
	ii) Sharpening one end of 16'-1" to 20' (4.9 to6.10 m) long Bamboos, 2¹/₂" to 5" (63 to 125 mm) dia.	100 Nos	1001.10	Depart	100 Nos	1001.10	-		
	iii) Driving Bamboos 16'-1" to 20' long (4.9 to 6.10 m) $2\frac{1}{2}$ " to 5" (63 to 125 mm) dia, driven 4' (1.20 m) below the available bed or ground (average).	100 Nos	1761.40	-	100 Nos	1761.40	-		
	iv) Tying Bamboos 2 ¹ / ₂ " to 5" (63 to 125 mm) dia with S.W.G. No. 10 wire, two lines, including tying around the Bamboos and third tie around the top end only.	Per Chain of one row	227.70	838.40	Per 30 M of one row	227.70	838.40		
	 v) Cutting and supplying brushwood from canal plantation or private source, lead within one mile (1.6 Km) and wattling between stakes and intertwining (thickness of wattled brushwood 1.0' (300 mm) average). 	ditto	5263.50	6210.30	ditto	5263.50	6210.30		
43	Cutting and supplying brushwood from canal plantation or from any other source, within one mile (1.6 Km).	100Cft.	227.70	295.20	cu.m	80.40	104.25		Royalty to be paid to the Forest Department or cost to the private owner, if and when required.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description	Description Rate (British System) Rate (Metric System)					Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
44	Filling brush wood only, thoroughly packed.	100Cft.	182.15	-	cu.m	64.35	-		Measured in compacted and packed shape before filling.				
45	Covering road 10' to 12' (3.00 to 3.65 m) wide, with 3" (75 mm) sarkanda or jungle upto one chain lead (30 m).	Per Chain	437.20	-	Per 30 M	437.20	-						
46	 a) Gachi pitching 1' (300 mm) thick. b) Gachi pitching done with silt clearance and berm dressing. 	100Sft. 100Sft.	2368.10 2003.75	-	Sq.m Sq.m	254.80 215.60							



Finance Department

17. OUTLETS

Rates for all finished works include the removal of surplus debris, unused material and byproducts

	MRS, BI-ANNUAL PE	T JHANG							
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Earthwork for outlets, excavation refilling, ramming and puddling:-							17.1 to 17.5	Includes consolidation of earth after refilling.
	a) channels, discharge upto 50 cusecs.	Job	759.00	-	Job	759.00	-	17.5	
	b) channels, discharge from 51 to 100 cusecs.	Job	1001.90	-	Job	1001.90	-		
	c) channels, discharge from 101 to 200 cusecs.	Job	1518.00	*)	Job	1518.00	-		
	d) channels, discharge from 201 to 350 cusecs.	Job	2049.30	-	Job	2049.30	-		
	e) channels, discharge over 350 cusecs.	Job	3036.00		Job	3036.00	-		
2	Dismantling outlets:-	55	E		Ŧ	j.		18.1	These rates are for total dismantlement and removal
	a) old types, such as K.G.O's orifices, etc.	Each	759.00	معتر مت چر	Each	759.00	-		of material. The rates do not include earth work for which
	b) A.P.M. or O.F., "H" upto 2.0 ft. (600 mm)	ditto	1138.50	H.S.	ditto	1138.50	-		rates are given in item 1, above.
	 A.P.M. or O.F., "H" from 2.1 ft. to 3.0'. (630 mm to 900 mm) 	ditto	1518.00	e Drepa	ditto	1518.00	-		
	 A.P.M. or O.F., "H" above 3.0'. (900 mm) 	ditto	1897.50	-	ditto	1897.50	-		
	e) Tail cluster bifurcation	ditto	1138.50	-	ditto	1138.50	-		
	f) Tail cluster trifurcation	ditto	1518.00	-	ditto	1518.00	-		
	g) Tail cluster quardification	ditto	1897.50	-	ditto	1897.50	-		
3	Making temporary A.P.M. bricks block and fixing at site.	Each	344.10	628.50	Each	344.10	628.50	21.1 & 21.2	
4	Dismantling walls, taking out temporary A.P.M. brick block, fixing iron block and rebuilding dismantled walls.	Job	716.75	-	Job	716.75	-	18.1, 21.1 & 21.2	

	MRS, BI-ANNUAL F	13) DISTRIC	T JHANG						
Sr.	Description	1	Rate (British Sys	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
5	Dismantling walls and fitting iron block of O.F. outlet.	Each	716.75	-	Each	716.75	-	18.1, 21.1 & 21.2	
6	Constructing, watching and removing bund for outlet built in running water:-							17.1 to 17.2	
	 a) upto 3.0' (0.300 m) depth b) above 3.0' (0.300 m) depth 	Each ditto	1821.60 2459.15	-	Each ditto	1821.60 2459.15	-	17.2	
7	Adjusting "B" of tail cluster by dismantling and rebuilding throat walls.	Each	384.35	777.45	Each	384.35	777.45	18.1, 21.1 & 21.2	
8	Adjusting "Y" of an A.P.M. outlet, including dismantling and rebuilding.	Each	749.10	1389.90	Each	749.10	1389.90	ditto	
9	Extra labour in fixing A.P.M. and O.F. outlet blocks, including dressing of bricks:-				Ju			21.1 & 21.2	Rates to be Rs. 4.00 less in case of O.F. outlets, where there is no
	 a) for channel depth of 5.0'. (1.5 m) b) for channel depth of 4.0'. (1.2 m) c) for channel depth of 3.0'. (900 mm) d) for channel depth of 2.0'. (600 mm) e) for channel depth of less than 2.0'. (600 mm) 	Each ditto ditto ditto ditto	834.25 625.70 500.55 417.10 333.70	948.75 740.20 615.05 505.65 396.35	Each ditto ditto ditto ditto	834.25 625.70 500.55 417.10 333.70	948.75 740.20 615.05 505.65 396.35		O.F. iron block.
10	Repairing damaged reducing collar of Hume pipe outlets.	Each	344.10	528.90	Each	344.10	528.90		
11	Laying iron pipes for outlets.	Per Lft.	16.70	e en veligen	Metre	54.75	-	21.1, 21.2 & 17.1 to 17.5	
12	Water allowance for constructing outlets or culverts, when canal water is not flowing.	Each	370.40 to 759.00		Each	370.40 to 759.00			At the discretion of the Engineer-in-charge depending upon the distance and source of supply.
13	Hoisting and placing R.C. slab or stone in position on outlets or W.C. culverts.	Each	275.65	-	Each	275.65	-		
14	Fixing pipe outlet, including back filling of earth and puddling:-							17.1 to 17.5 & 21.1 to 21.2	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	70.50 30.60	78.15 38.25	Metre ditto	231.35 100.40	256.35 125.45		

	MRS, BI-ANNUAL PE	RIOD (1	st AUGUST,	2012 TO 31	st JANU	JARY, 20 ⁻	13) DISTRIC	T JHANG	
Sr.	Description	I	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
16	 Removing pipe outlet, refilling earth and puddling. a) portion under bank. b) portion under road, beyond bank. Changing pipe outlets by removing one pipe and replacinş it at the same site with another pipe complete with earth and puddling. 	Rft. ditto	60.70 22.75	-	Metre ditto	199.20 74.70		17.1 to 17.5	
	a) portion under bank.b) portion under road, beyond bank.	Rft. ditto	83.75 41.85	91.35 49.50		274.70 137.35			



Finance Department

18. ROAD & ROAD STRUCTURE

1 Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction 1971".

- 2 Rates for all finished works include the removal of surplus debris, unused material and byproducts.
- 3 The rates include the provision and maintenance of field test laboratory, pay of laboratory staff, cost of material for testing, etc.

	MRS, BI-ANNUAL PER	IOD (1st A	UGUST, 20	12 TO 31st	JANUAR	Y, 2013)	DISTRICT J	IHANG	
Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Sub-base & base construction								
1	Providing and laying sub-base course of brick on edge 4 ¹ / ₂ " (113 mm) thick, including compaction to required camber and grade.	100Cft.	2405.75	12723.35	cu.m	849.70	4493.90	521-1 to 521-6	The nominal thickness of bricks shall be taken for the purpose of measurement and payment.
2	Providing and laying sub-base course of brick aggregate, including compaction of sub-base course material to required depth, camber, grade & density.	100Cft.	2003.25	2957.85	cu.m	707.55	1044.70	501-1 to 501-6	To be used only when brick aggregate is cheaper than stone aggregate.
3	a) Providing and laying sub-base course of stone product of approved quality and grade, including placing, mixing, spreading and compaction of sub-base material to required depth, camber, grade to achieve 100% maximum modified AASHO dry density, including carriage of all material to site of work except gravel and. aggregate.	Ein	unce (Ka Despart				ditto	
	i) Pit run or bed run gravel.ii) Crushed stone aggregate.	100Cft. 100Cft.	2003.25 2003.25	2471.25 2687.25	cu.m cu.m	707.55 707.55	872.85 949.15		
	(b) Subsequent carriage of gravel and crushed stone aggregate	100Cft. of consoli- dated sub-base							1) The carriage of the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
									2) It shall be payable from the nearest approved quarry.3) The quantity of pit run

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
4	 a) Providing and laying base course of crushed stone aggregate of approved quality and grade, and supply and spreading of stone screening, including placing, mixing, spreading and compaction of base course material to required depth, camber and grade to achieve 100% maximum modified AASHO dry density, including carriage of all materials to site of work except gravel and. aggregate. 	100Cft.	2234.25	4599.45	cu.m	789.15	1624.55	501-1 to 501-6	or bed run gravel and crushed stone aggregate for payment of carriage shall be taken as per actual loose volume but not more than 120 Cft.			
	b) Subsequent carriage of crushed stone aggregate.	100Cft. of console- dated base							1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.			
		12.19/18	18437678 - 12	Je para	992.8.299 T.				 It shall be payable from the nearest approved quarry. The quantity of crushed stone aggregate for payment of carriage shall be taken as pe actual loose volume but not more than 122 Cft. 			
5	Providing and laying road edging of 3" (75 mm) wide and 9" (225 mm) deep brick on end, complete in all respects.	Per Rft.	5.25	26.00	Metre	17.20	85.25	552-1 to 552-5				
	Bituminous Work & Resurfacing.											
6	Providing and laying bituminous priming coat, using 10 lbs. kerosene oil and 10 lbs. binder per 100 Sft. or 0.5 Kg kerosene and 0.5 Kg binder per square metre.	100Sft.	91.10	1069.15	sq.m	9.80	115.05	601-1 to 601-6				
7	Providing and laying bituminous tack coat, using 10 lbs. of bitumen per 100 Sft (0.49 Kg of bitumen per sq.m.)	100Sft.	91.10	563.00	sq.m	9.80	60.60	611-1 to 611-5				
8	 Providing surface treatment to roads, including supply of bitumen and bajri/crushed stone aggregate o 							612-1 to 612-6				

MRS, BI-ANNUAL PER	ERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRIC							I
Description	R	ate (British Sys	tem)	Rat	e (Metric Sy	ystem)	Spec.	Remarks
	Unit	Labour	Composite	Unit	Labour	Composite	N0.	
approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate.								
1) 1st coat:-								
 i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre 	100Sft.	89.35	2261.85	Sq.m	9.60	243.35		
 ii) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size ³/₄" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre. 	100Sft.	89.35	1976.55	Sq.m	9.60	212.65		
2) 2nd coat:-		- 550		1997 - 19				
 i) 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size ¹/₂" (13 mm) per %sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 	100Sft.	68.75	1414.65	Sq.m	7.40	152.20		
 ii) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq. metre. 	100Sft.	68.75	1038.25	Sq.m	7.40	111.70		
3) 3rd coat:-								
14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre.	100Sft.	47.00	799.70	sq.m	5.05	86.05		
Subsequent carriage of crushed stone aggregate/bajri,	100Cft.			cu.m				1) The carriage for the whole distance to the site of work shall be calculated on the basis of the rates of the actual means of transport used in carriage, i.e. road and/or rail, as the case may be.
	 Description approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. 1) 1st coat:- 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size 34" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre. 2) 2nd coat:- 25 lbs. bitumen, and 2.75 Cft. bajri of nominal size 42" (13 mm) per %Sft or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 37 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft. or 0.89 Kg bitumen and 0.006 cu.metre bajri per sq.metre. 31 ret coat:- 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size 4/4" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajri per sq.metre. 	Description R unit unit approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. 1000000000000000000000000000000000000	Description Rate (British System) approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. 1005ft. 1) 1st coat:- 1005ft. 89:35 1) 1st coat:- 1005ft. 89:35 1) 35 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cumetre bajri per square metre 1005ft. 89:35 1i) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size ¾" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cumetre bajri per sq.metre. 1005ft. 89:35 2) 2nd coat:- 1005ft. 68.75 68.75 (13 mm) per %Sft. or 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 1005ft. 68.75 3) 3rd coat:- 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajri per sq.metre. 1005ft. 47.00	Description Rate (British System) unit Labour Composite approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. 100Sft. 89.35 2261.85 i) 40 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre 100Sft. 89.35 1976.55 i) 35 lbs. bitumen, and 4.0 Cft. bajri of nominal size 3/4" (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre. 100Sft. 68.75 1414.65 i) 18 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per %Sft or 0.23 Kg bitumen and 0.006 cu.metre bajri per sq. metre. 100Sft. 68.75 1038.25 j) 3rd coat:- 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size 3/8" (10 mm) per %sft or 0.59 Kg bitumen and 0.005 cubic metre bajjri per sq.metre. 100Sft. 47.00 799.70	Description Rate (British System) Rat approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. 1005ft. 89.35 2261.85 Sq.m 1) 1st coat:- 100 sg. feet or 1.96 Kg bitumen and 0.017 1005ft. 89.35 2261.85 Sq.m (20 mm) per %Sft. or 1.72 Kg bitumen and 0.013 cu.metre bajri per sq.metre. 1005ft. 89.35 1976.55 Sq.m (1) 1st bitumen, and 2.75 Cft. bajri of nominal size ¼" (13 mm) per %Sft. or 0.28 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 1005ft. 68.75 1414.65 Sq.m (1) 1st bb. bitumen, and 2.0 Cft. bajri of nominal size ½" (10 mm) per %Sft. or 0.28 Kg bitumen and 0.006 cu.metre bajri per sq. metre. 1005ft. 68.75 1038.25 Sq.m 3) 3rd coat:- 1 1005ft. 68.75 1038.25 Sq.m 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size ¼" (6 mm) per %sft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre. 1005ft. 47.00 799.70 sq.m	Description Rate (British System) Rate (Metric S unit Labour Composite Unit Labour approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bajri and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. composite Unit Labour 1) 1st coat:- 1) 1st coat:- 100Sft. 89.35 2261.85 Sq.m 9.60 ii) 30 lbs. bitumen, and 5.5 Cft. bajri of nominal size 1" (25 mm) per 100 sq. feet or 1.96 Kg bitumen and 0.017 cu.metre bajri per square metre 100Sft. 89.35 1976.55 Sq.m 9.60 ii) 31 lbs. bitumen, and 4.0 Cft. bajri of nominal size 4" (20 mm) per %5ft. or 1.32 Kg bitumen and 0.013 cu.metre bajri per sq.metre. 100Sft. 68.75 1414.65 Sq.m 7.40 i) 2 lbs. bitumen, and 2.75 Cft. bajri of nominal size 5%" (10 mm) per %5ft. or 0.39 Kg bitumen and 0.006 cu.metre bajri per sq. metre. 100Sft. 68.75 1414.65 Sq.m 7.40 3) 3rd coat:- 14 lbs. bitumen, and 1.5 Cft. bajri of nominal size 5%" (10 mm) per %5ft or 0.69 Kg bitumen and 0.005 cubic metre bajjri per sq.metre. 100Sft. 47.00 799.70 sq.m 5.05	Description Rate (British System) Rate (Metric System) unit Labour Composite Unit Labour Composite approved quality, including cleaning of road surface, heating and spraying bitumen, spreading bari and rolling with road roller (including its operation cost, fuel and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajit/crushed stone aggregate. 10 11 Labour Composite 1) 1 st coat:- 1) 14 to composite of 1.96 Kg bitumen and 0.017 cumetre bajri per square metre 100Sft. 89.35 2261.85 Sq.m 9.60 243.35 1) 3 5 lbs, bitumen, and 4.0 Cft. bajri of nominal size ¼" (20 mm) per 100s ft. 100Sft. 89.35 1976.55 Sq.m 9.60 212.65 2) 2nd coat:- 1) 2 bls, bitumen and 0.013 cumetre bajri per sq.metre. 100Sft. 68.75 1976.55 Sq.m 7.40 152.20 13 ma) per 48 stor 1.23 Kg bitumen and 0.008 cu. metre bajri per sq.metre. 100Sft. 68.75 1038.25 Sq.m 7.40 111.70 13 ma) per 48 stor 1.23 Kg bitumen and 0.006 cumetre bajri per sq. metre. 3) 3rd coat:- 100Sft. 68.75 1038.25 Sq.m	Description Rate (British System) Rate (Metric System) Spec. No. approved quality, including cleaning of road surface, beating and spraying bitumen, speading bajri and rolling with road roller (including its operation cost, field and hire charges, etc.) etc. complete including carriage of all materials to site of work except bajjri/crushed stone aggregate. Image: Composite Com

	MRS, BI-ANNUAL PE	RIOD (1st A	UGUST, 20	12 TO 31st	JANUAR	Y, 2013)		JHANG	
Sr.	Description	R	ate (British Sys	tem)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
9	 a) Resurfacing of road, including supply of bitumen and bajri/crushed stone aggregate of approved quality, including cleaning of road surface, heating and spraying of bitumen, and spreading bajri/crushed stone aggregate and rolling with road roller (including its operation cost, fuel and hire charges, etc.) complete, including carriage of all materials to site of work. 		×					612-1 to 612-6	2) It shal be payable from the nearest approved quarry.
	 i) 22 lbs. bitumen, and 2.5 Cft. bajri of nominal size ½" (13 mm) per %Sft. or 1.07 Kg bitumen and bajjri 0.007 cu.m per sq.m. ii) 20 lbs. bitumen, and 2.0 Cft. bajri of nominal size 3/8" (10 mm) per % Sft. or 0.79 Kg bitumen and 0.006 cu.metre bajri per sq.metre. b) Subsequent carriage of crushed stone aggregate/bajri. 	100Sft. 100Sft. 100Cft.	59.55 59.55	1245.30 1131.35	sq.m sq.m cu.m	6.40 6.40	134.00 121.75		Same remarks as against item 8(b) above.
10	 Providing and laying plant premixed bituminous carpet, including compaction and finishing to required camber, grade and density. (i) 3% Bitumen (ii) 3.5% Bitumen (iii) 4% Bitumen (iv) 4.5% Bitumen (v) 5% Bitumen (vi) 5.5% Bitumen (vii) 6% Bitumen 	per inch thickness per 100Sft. -do- -do- -do- -do- -do- -do- -do- -do	1020.20 1020.20 1020.20 1020.20 1020.20 1020.20 1020.20	3242.45 3532.05 3821.65 4111.25 4400.65 4690.45 4980.05	per 25mm thickness per Sq.m -do- -do- -do- -do- -do- -do- -do- -do	109.80 109.80 109.80 109.80 109.80 109.80 109.80	349.00 380.20 411.35 442.55 473.70 504.90 536.05		
11	Scarifying old road surface including removal of debris within 1 chain (30 m).	100Sft.	151.80	-	Sq.m	16.35	-		
	Incidental Construction								
12	Providing R.C.C. railing on bridges, as per standard drawing.	Per Rft.	83.50	961.60	Metre	273.90	3154.90	901-1 to 901-4	The rate includes cost of steel, its fabrication, laying in position and fastening, including cost of binding

Sr.	MRS, BI-ANNUAL P					•			Remarks
Sr. No.	Description	K	ate (British Syst	em)	Kat	te (Metric S	ystem)	Spec. No.	Remarks
		Unit	Labour	Composite	Unit	Labour	Composite		
									wire and removal of rust from the bars, etc.
13	Providing and fixing G.I. pipe railing, as per standard drawing.	Per Rft. of 3 rows of Pipes	67.30	669.55	Metre	220.75	2196.65	ditto	
14	Providing and fixing steel bearings of standard quality and type at site of work.	Each Set of one end	*	2400.00	Each set of one end	-	2400.00	911-1 to 911-6	
15	Providing and fixing rubber bearing pad at site of work.	Per Cu. Inch		18.00	cu.cm	-	1.10	ditto	
16	Providing and laying expansion joint of neoprine strip 4"x ¹ /4" (100 mmx 6 mm) and plastic bitumen.	Per Rft.	46.20	180.80	Metre	151.60	593.25	921-1 to 921-4	
17	Providing and fixing rain water outlet of A.C. pipe.	Each	23.10	251.25	Each	23.10	251.25	931-1 to 933-4	
18	Providing and erection at site of work:-	~~	SP)	S. C. C.				941-1 to 941-5	The rate is for complete item of work according to Standard design
	i) R.C.C. mile/Km. stone	Each	1608.95	3678.05	Each	1608.95	3678.05		including cement concrete
	ii) R.C.C. furlong/½ Km. stone	Each	77.40	289.65	Each	77.40	289.65		foundation block and painting
	iii) R.C.C. boundary pillar.iv) Sign post of M.S. plate 1/8" thick (3 mm)	Each	145.75	475.05	Each	145.75	475.05		letters etc.
	a) Mandatory.	Each	510.45	4230.60	Each	510.45	4230.60		
	b) Warning/Direction/Informatory.	Each	493.80	3954.70	Each	493.80	3954.70		
	Providing and laying dry brick pavement/soling in streets or roads, etc. sand grounted, laid in proper camber, including preparation, watering, compaction of bed to proper camber, and sand cushion.	100Cft.	1876.70	12194.30	cu.m	662.85	4307.05		The nominal thickness of bricks (2-11/16" shall be taken for the purpose of measurement and payment. (9" x 4-3/8"x 2-11/16")

19. PLUMBING, SANITARY INSTALLATION & GAS FITTINGS

- 1 Rates for all finished works include the removal of surplus debris, unused material & by products.
- 2 The material used shall conform to Schedule of Rates, Vol. I, Part I, (Specifications for Materials of Construction, 1964, and the work will be executed according to Buildings & Roads Department Specifications, Vol II, 1966 (Public Health Works).
- 3 The rates include cutting and making good of the surface of walls, roof, floor, etc. where necessary.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG													
Sr. No.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec. No.	Remarks					
INO.		Unit	Labour	Composite	Unit	Labour	Composite	190.						
	Providing and fitting glazed earthen ware water closet European type, excluding seat and cover:-													
	i) white	Each	262.35	1,959.80	Each	262.35	1,959.80							
	ii) coloured	Each	262.35	2,139.80	Each	262.35	2,139.80							
2	Providing and fixing, double seat and cover only.		*E	\approx		<u>k</u> .								
	i) bakelite	Each	3.05	321.05	Each	3.05	321.05							
	ii) plastic	Each	3.05	219.05	Each	3.05	219.05							
3	Providing and fitting glazed earthen ware water closet, squatter type (Orisa pattern), combined with foot rest.					9. 9								
	i) white	Each	203.80	1,103.25	Each	203.80	1,103.25							
	ii) coloured	Each	203.80	1,295.25	Each	203.80	1,295.25							
4	Providing and fitting white glazed earthen ware water closet, squartter type, with separate foot rest.	Each	203.80	1,931.80	Each	203.80	1,931.80							
5	Providing and fitting water closet, squatter type of terrazzo concrete.	Each	203.80	527.25	Each	203.80	527.25							
6	Providing and fitting glazed earthen ware wash hand basin 56x40 cm (22"x16") including bracket set, waste pipe and waste coupling, etc.													
	i) white, with pedestal	Each	260.70	2,336.70	Each	260.70	2,336.70							
	ii) coloured, with pedestal	Each	260.70	2,528.70	Each	260.70	2,528.70							
	iii) white, without pedestaliv) coloured, without pedestal	Each Each	232.25 232.25	1,594.25 1,660.25	Each Each	232.25 232.25	1,594.25 1,660.25							
	iv) coloured, without pedestal	Each	232.25	1,000.25	Each	232.23	1,000.25							
7	Providing and fixing stainless steel sink with drain board, size 120x60 cm (48"x24") including bracket set, waste pipe and waste coupling.	Each	232.25	4,311.40	Each	232.25	4,311.40							
8	Providing and fitting terrazzo concrete sink 60x45 cm (24"x18")	Each	232.25	996.00	Each	232.25	996.00							

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description		Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	-				
	with drain board of mosaic, including bracket set, waste pipe and waste coupling.												
9	Providing and fixing glazed earthen ware sink, including bracket set, waste pipe and waste coupling:-												
	i) 60x45 cm (24"x18") ii) 37.5x45 cm (15"x18")	Each Each	232.25 232.25	1,557.25 1,377.25	Each Each	232.25 232.25	1,557.25 1,377.25						
10	Providing and fixing glazed earthen ware flat back urinal.	Each	146.85	835.25	Each	146.85	835.25						
11	Providing and fitting glazed earthen ware low down flushing cistern 13,63 litres (3 gallons) capacity, including bracket set, copper connection, etc.			*)									
	i) white ii) coloured	Each Each	232.25 232.25	1,215.45 1,287.45	Each Each	232.25 232.25	1,215.45 1,287.45						
12	Providing and fitting plastic made low down flushing cistern 1363 litre (3 gallons) capacity, including bracket set, copper connection, etc. complete.		A Contraction		Ter a								
	i) white ii) coloured	Each Each	232.25 232.25	1,047.45 1,047.45	Each Each	232.25 232.25	1,047.45 1,047.45		If rubber connection is used, the composite rate will be reduced by Rs. 12.50				
13	Providing and fixing white enameled cast iron low down flushing cistern 13.63 litres (3 gallons) capacity, including bracket set, copper connection, etc.	Each	232.25	1,227.75	Each	232.25	1,227.75						
14	Providing and fixing cast iron high level flushing cistern including cost of bracket set, copper connection, etc.												
	 i) 13.63 litres (3 gallons) capacity ii) 4.55 litres (1 gallon) capacity 	Each Each	246.90 246.90	2,352.40 1,512.40	Each Each	246.90 246.90	2,352.40 1,512.40						
15	Providing and fixing, chromium plated soap dish.	Each	14.70	182.90	Each	14.70	182.90						
16	Providing and fitting, glazed earthen ware soap dish.												
	i) white ii) coloured	Each Each	14.70 14.70	462.50 210.50	Each Each	14.70 14.70	462.50 210.50						
17	Providing and fixing, chromium plated toilet paper holder.	Each	19.60	391.00	Each	19.60	391.00						
18	Providing and fixing, chromium plated towel rail:-												

	MRS, BI-ANNUA	L PERIO	D (1st AUG	UST, 2012 T	O 31st J	ANUARY	, 2013) DIS	TRICT JHA	ANG
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 60 cm (24") long, and 2 cm (¾") dia. ii) 50 cm (20") long, and 1.5 cm (½") dia. 	Each Each	19.60 19.60	343.20 283.20	Each Each	19.60 19.60	343.20 283.20		
19	Providing and fixing looking glass 55x40 cm (22"x16") size, and 5 mm thick, first quality.	Each	36.70	356.30	Each	36.70	356.30		
20	Providing and fixing glass shelf 60x13 cm (24"x5"), with 5mm thick glass:-								
	 i) with chromium plated brackets and railing. ii) glass shelf only, without chromium plated brackets and railing. 	Each Each	43.95 29.35	339.75 73.75	Each Each	43.95 29.35	339.75 73.75		
21	Providing and fitting glazed earthen ware shelf 60x13 cm (24"x5"), with chromium plated bracket and railing:-			0					
	i) White ii) Coloured	Each Each	43.95 43.95	895.35 1,015.35	Each Each	43.95 43.95	895.35 1,015.35		
22	Providing and fitting:-		7_19	-67-	Je je	L.S.			
	 i) plastic soap dish ii) plastic toilet paper holder iii) plastic towel rail iv) plastic shelf 60x13 cm (24"x5") with bracket and railing. 	Each Each Each Each	14.70 19.60 19.60 19.60	147.40 209.40 227.40 411.05	Each Each Each Each	14.70 19.60 19.60 19.60	147.40 209.40 227.40 411.05		
23	Providing and fixing chromium plated pillar-cock, heavy:-		781. Factorialisa	848.486 - <u>111.</u> (430)	prodest tests	94.080.0834.084			
	i) 2 cm (³ / ₄ ") ii) 1.5 cm (¹ / ₂ ")	Each Each	19.60 19.60	523.60 679.60	Each Each	19.60 19.60	523.60 679.60		
24	Providing and fixing chromium plated stop cock, heavy:-								
	i) 2 cm (¾") ii) 1.5 cm (½")	Each Each	19.60 19.60	259.60 172.00	Each Each	19.60 19.60	259.60 172.00		
25	Providing and fixing underground stop cock 13 mm (¹ / ₂ "), with chromium plated cover.	Each	28.25	467.30	Each	28.25	467.30		
	Providing and fixing chromium plated bib cock:- i) 2 cm (³ / ₄ ") ii) 1.5 cm (¹ / ₂ ")	Each Each	19.60 19.60	331.60 313.60	Each Each	19.60 19.60	331.60 313.60		
27	Providing and fixing chromium plated tee stop cock 15mm (½").	Each	19.60	439.60	Each	19.60	439.60		

	MRS, BI-ANNUA	L PERIO	D (1st AUG	JST, 2012 T	O 31st J	ANUARY	, 2013) DIS	TRICT JH/	ANG
Sr.	Description]	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	-
28	Providing and fixing chromium plated shower rose:-								
	i) 1.5x10 cm (½"x4") ii) 2x15 cm (¾"x6")	Each Each	19.60 19.60	319.60 397.60	Each Each	19.60 19.60	319.60 397.60		
29	Providing and fixing, chromium plated mixing valve, for wash hand basin, sink or shower.	Each	24.50	1,524.50	Each	24.50	1,524.50		
30	Providing and fixing gun metal peet/gate valve (screwed):-								For brass peet/gate valve (screwed), the composite rates of items (i) to (v)
	 i) 30 mm (1¹/₄") dia ii) 40 mm(1¹/₂") dia iii) 50 mm(2") dia iv) 65 mm(2¹/₂") dia v) 80 mm(3") dia 	Each Each Each Each Each	29.35 29.35 29.35 29.35 29.35 29.35	419.35 575.35 791.35 1,253.35 1,859.35	Each Each Each Each Each	29.35 29.35 29.35 29.35 29.35 29.35	419.35 575.35 791.35 1,253.35 1,859.35		will be reduced by Rs. 66, 77, 95, 107 and 120 respectively.
31	Providing and fitting, chromium plated or brass oxidised, swan neck cock 15 mm (1/2") dia.		*=			1			
	 i) single way ii) two way 	Each Each	19.60 29.35	361.60 623.35	Each Each	19.60 29.35	361.60 623.35		
32	iii) three wayProviding and fixing, union brass cock.	Each	39.15	753.15	Each	39.15	753.15		
	i) 13 mm (½") dia ii) 20 mm (¾") dia	Each Each	19.60 19.60	133.60 211.60	Each Each	19.60 19.60	133.60 211.60		
33	Providing and fixing, floor trap of cast iron, including concrete chamber all round, and C.I. grating:-								
	i) 10x5 cm (4"x2") ii) 10x7.5 cm (4"x3")	Each Each	58.75 58.75	365.95 359.95	Each Each	58.75 58.75	365.95 359.95		
34	Providing and fitting "P" trap:-								
	 i) 10 cm (4") of cast iron. ii) 10 cm (4") glazed. 	Each Each	48.95 48.95	433.25 112.85	Each Each	48.95 48.95	433.25 112.85		
35	Providing and fitting 10 cm (4") gully trap, including cement concrete, cost of PVC grating 15x15 cm (6"x6") and masonry chamber 30x30 cm (12"x12").	Each	73.45	599.10	Each	73.45	599.10		
36	Providing and fitting, cast iron soil pipe with:-								
	i) lead caulked, yarn joint:-								

	MRS, BI-ANNUA	AL PERIO	D (1st AUG	JST, 2012 T	O 31st J	ANUARY	, 2013) DIS	TRICT JH	ANG
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 a) 10 cm (4") i/d b) 5 cm (2") i/d ii) cement caulked joint:- 	Per foot Per foot	22.85 9.15	215.35 91.00	Metre Metre	74.90 29.95	706.40 298.45		
37	 a) 10 cm (4") i/d b) 5 cm (2") i/d Providing and fitting, A.C. soil pipe with cement caulked 	Per foot Per foot	5.35 2.15	144.05 78.80	Metre Metre	17.55 7.00	472.50 258.50		
	joint, including all specials:- i) 60 (2¼)" mm i/d ii) 80 (3") mm i/d iii) 100 (4") mm i/d iv) 150 (6") mm i/d	Per foot Per foot Per foot Per foot	4.30 4.75 5.35 7.15	28.25 67.35 102.00 127.15	Metre Metre Metre Metre	14.05 15.60 17.55 23.40	92.60 220.90 334.60 417.15		
38	Providing and fitting cast iron specials, such as tee bend, collar, cross, etc. plain type:- i) lead caulked joint	Kg	18.90	142.20	Kg	18.90	142.20		In case of plug type, the composite rate shall be increased by Rs.2 per kg.
39	ii) cement caulked jointSupply and fitting of cast iron manhole cover with frame, etc. complete.	Kg	11.60	108.05	Kg	11.60	108.05		
	 i) 30 cm (12") dia ii) 45 cm (18") dia iii) 60 cm (24") dia 	Each Each Each	29.35 29.35 46.75	173.35 845.35 1,426.75	Each Each Each	29.35 29.35 46.75	173.35 845.35 1,426.75		
40	Providing and fitting R.C.C. pipe 10 cm (4") dia, including laying and jointing in trenches.	Per foot	11.40	36.60	Metre	37.45	120.10		
41	Providing and fitting chromium plated or oxidised, gas cock 6'mm (1/4"):-								
	 i) single way ii) two way iii) three way 	Each Each Each	19.60 29.35 39.15	187.60 281.35 471.15	Each Each Each	19.60 29.35 39.15	187.60 281.35 471.15		
42	Providing and fitting nipple or bush, 6 mm to 10 mm (¼" to 3/8") i/d.	Each	14.70	44.70	Each	14.70	44.70		
43	Providing and fixing, brass gas cock:-								
	a) 15 mm (½") dia b) 20 mm (¾") dia	Each Each	3.05 111.25	87.05 99.05	Each Each	3.05 111.25	87.05 99.05		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG													
Sr.	Description]	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
44	Providing and fixing brass stop cock/bib cock:-													
	a) 15 mm (¹ / ₂ ") dia b) 20 mm (³ / ₄ ") dia	Each Each	4.90 4.90	76.90 115.30	Each Each	4.90 4.90	76.90 115.30							
45	Hoisting and placing in position, precast R.C. latrine seats.	Each	246.70	-	Each	246.70	-							
	Replacement													
1	Providing and fixing, chromium plated waste coupling:-													
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	29.35 29.35	112.15 118.15	Each Each	29.35 29.35	112.15 118.15							
2	Providing and fixing rubber plug with chain:-													
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	1.20 1.20	45.60 52.80	Each Each	1.20 1.20	45.60 52.80							
3	Providing and fixing, waste pipe of PVC:-		7_189	-6	67	L.S.								
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	14.70 14.70	39.90 45.90	Each Each	14.70 14.70	39.90 45.90							
4	Providing and fixing, flushing bend of PVC.		Famas	ice De		a en t								
	i) 3 cm (1¼") ii) 4 cm (1½")	Each Each	13.05 13.05	38.25 44.25	Each Each	13.05 13.05	38.25 44.25							
5	Providing and fixing chromium plated bottle trap with waste pipe, etc. complete:-													
	i) 3 cm (1¼") i/d ii) 4 cm (1½")	Each Each	29.35 29.35	533.35 653.35	Each Each	29.35 29.35	533.35 653.35							
6	Providing and fixing, angle iron brackets for:-													
	i) wash hand basin and cisternii) sinks	Each Each	29.35 29.35	151.75 166.15	Each Each	29.35 29.35	151.75 166.15							
7	Providing and fixing 1.5 cm (1/2") dia connection, including check nuts, etc.:-													
	i) plastic rubber connectionii) copper connection	Each Each	11.75 11.75	42.95 80.15	Each Each	11.75 11.75	42.95 80.15							

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG													
Sr.	Description	ŀ	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks					
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.						
8	Providing and fixing brass ball float valve:-													
	i) 1.5 cm (1/2") dia	Each	24.50	216.50	Each	24.50	216.50							
	ii) 2.0 cm (³ / ₄ ") dia	Each	24.50	282.50	Each	24.50	282.50							
	iii) 2.5 cm (1") dia	Each	24.50	342.50	Each	24.50	342.50							
	iv) 3 cm (1 ¹ / ₄ ") dia	Each	24.50	372.50	Each	24.50	372.50							
	v) $4.0 \text{ cm} (1\frac{1}{2})$ dia	Each	24.50	516.50	Each	24.50	516.50							
	vi) 5 cm (2") dia	Each	24.50	900.50	Each	24.50	900.50							



Finance Department

20. SURFACE DRAINAGE

1. Specification No. correspond to Book of Specification (B & R Department) Vol. 11, 1966 (public Health Works).

2. Rates for all finished works include the removal of surplus debris, unused material and by products

2. 10	MRS, BI-ANNUAL PER			012 TO 31st	JANUA	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	1	Rate (British Sy	stem	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Tega formed of pacca bricks on end, laid in and over cement sand mortar projecting to a height of not more than 6" (150 mm) top of drain along the property side where required, laid to lines, grades, slopes and shape according to the Engineer's drawing:-		~					17.1	
	a) 3" thick (75 mm)	del			Ju.				
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	771.55 771.55	3,175.80 3,018.55	Metre ditto	25.30 25.30	104.15 99.00		
	B) 4 ¹ / ₂ " thick (113 mm)		1.5						
	i) ratio 1:3 ii) ratio 1:5	100Rft ditto	1,156.85 1,156.85	4,617.55 4,379.30	ditto ditto	37.95 37.95	151.45 143.65		
2	Pacca flat brick 3" (75 mm) thick, laid in reimbursement, in cement, sand mortar, on sides of drains and in other works where required. All joints to be completely filled and struck flush:-	Fi		Depart				17.1	
	 a) ratio 1:3 b) ratio 1:5 c) ratio 1:6 	100Sft. ditto ditto	1,138.35 1,138.35 1,138.35	4,496.45 4,244.25 4,173.30	Sqm. ditto ditto	122.50 122.50 122.50	483.80 456.70 449.05		
3	Pacca brick on edge, laid in reimbursement, in cement, sand mortar, on sides of drains and on other works where required. All joints to be completely filled and struck flush:-							17.1	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,618.30 1,618.30 1,618.30	6,683.00 6,278.50 6,177.85	Sqm. ditto ditto	174.15 174.15 174.15	719.10 675.55 664.75		
4	Pacca flat brick, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	

	MRS, BI-ANNUAL PER	JHANG							
Sr.	Description]	Rate (British Sy	stem	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,083.70 1,083.70 1,083.70	4,441.80 4,189.60 4,118.65	Sqm. ditto ditto	116.60 116.60 116.60	477.95 450.80 443.15		
5	Pacca brick on edge, Herring bond pitching in cement, sand mortar, laid to lines, grades, shapes and slopes as per Engineer's drawing:-							17.2	
	a) ratio 1:3 b) ratio 1:5 c) ratio 1:6	100Sft. ditto ditto	1,674.80 1,674.80 1,674.80	6,739.50 6,335.00 6,234.35	Sqm. ditto ditto	180.20 180.20 180.20	725.15 681.65 670.80		
6	Constructing Punjab Standard Drains. of cement concrete 1:2 ¹ / ₂ :5, with cement concrete bedding ratio 1:6:12, complete, laid to lines, grades, slopes and shapes, rendering exposed surface of concrete with 1:1 cement, sand mortar, ¹ / ₄ " (6 mm) thick, as per Engineer's drawing (excluding excavation):-	State-						17.1	
	 a) Type I b) Type II c) Type III d) Type IV e) Type V f) Type VI g) Type VII h) Type VIII i) Type IX j) Type X k) Type XII l) Type XII 	Per Rft ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto	$\begin{array}{c} 25.95\\ 51.90\\ 67.70\\ 80.70\\ 106.50\\ 122.55\\ 135.80\\ 151.70\\ 203.05\\ 223.05\\ 249.25\\ 265.70\end{array}$	78.10 140.85 182.65 217.45 296.80 339.70 373.60 419.20 597.85 655.00 728.35 771.95	Metre ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto ditto	85.10 170.15 222.05 264.65 349.40 401.90 445.45 497.50 666.05 731.55 817.50 871.50	$\begin{array}{c} 256.20\\ 462.00\\ 599.05\\ 713.20\\ 973.45\\ 1,114.30\\ 1,225.45\\ 1,374.90\\ 1,960.90\\ 2,148.45\\ 2,388.95\\ 2,532.05\\ \end{array}$		
7	Laying R.C.C hume pipes in position, including jointing:- a) 6" to 12" (150 mm to 300 mm) dia b) 12" to 24" (300 mm to 600 mm) dia c) 24" to 36" (600 mm to 900 mm) dia	Per Lft. ditto ditto	48.20 75.50 96.35	51.05 81.20 104.95	Metre ditto ditto	158.05 247.65 316.05	167.40 266.35 344.20		

21. SEWERAGE

Specification No. correspond to Book of Specification of B&R Department Vol. II, 1966 (Public Health Works). Rate for all finished works include the removal of surplus debris, unused material and byproducts. 1

2

Description	1	Rate (British Sv		-				
	Rate (British System)			Ra	te (Metric S	ystem)	Spec.	Remarks
	Unit	Labour	Composite	Unit	Labour	Composite	No.	
widing and laying R.C.C. pipe, moulded with cemer acrete 1:1½:3, with spigot socket or collar joint, etc luding cost of reinforcement, conforming to B.S. 591 t I: 1981, Class "L" including carriage of pipe fron tory to site of work, lowering in trenches to correc ment and grade, jointing, cutting pipes wher ressary, finishing and testing, etc., complet		~					Chapter - 8	
100 mm (4") i/d 150 mm (6") i/d 225 mm (9:) i/d	Rft. Rft. Rft.	13.40 16.20 31.30	65.85 104.05 267.10	Metre Metre Metre	43.95 53.15 102.65	216.00 341.30 876.10		
widing and laying non-reinforced concrete pipe ulded with cement concrete 1:11/2:3, conforming t TM Specification C-14-73, Class 2, including carriag pipe from factory to site of work, lowering in trenches rect alignment and grade, jointing, cutting pipe wher ressary, finishing and testing, etc. complete	2 B			AN A			ditto	
100 mm (4") i/d 150 mm (6") i/d 200 mm (8") i/d 225 mm (9:) i/d wall thickness 1 inch (25 mm) 250 mm (10") i/d	Rft. Rft. Rft. Rft. Rft.	10.05 12.15 19.50 21.05 21.45	33.25 47.55 65.90 83.45 92.40	Metre Metre Metre Metre Metre	32.95 39.85 63.95 69.05 70.35	109.05 155.95 216.15 273.70 303.05		
widing and laying R.C.C. pipe sewers, moulded wit nent concrete 1:1 ¹ / ₂ :3 conforming to ASTN ecification C-76-79, Class II. Wall B, including carriag- pipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring ting pipes where necessary, testing, etc., complet							ditto	
310 mm (12") i/d 380 mm (15") i/d 460 mm (18") i/d 530 mm (21":) i/d 610 mm (24") i/d 690 mm (27") i/d 760 mm (30") i/d	Rft. Rft. Rft. Rft. Rft. Rft. Rft.	32.40 40.65 49.05 61.40 70.90 103.80 124.45 154.80	339.75 416.30 450.45 580.20 695.95 972.40 1038.35 1214.85	Metre Metre Metre Metre Metre Metre Metre	106.25 133.35 160.90 201.40 232.55 340.45 408.20 507.75	1114.40 1365.45 1477.50 1903.05 2282.70 3189.45 3405.80 3984.70		
	250 mm (10") i/d viding and laying R.C.C. pipe sewers, moulded wit tent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriag- ipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring ing pipes where necessary, testing, etc., complet 310 mm (12") i/d 380 mm (15") i/d 460 mm (18") i/d 530 mm (21":) i/d 610 mm (24") i/d 690 mm (27") i/d 760 mm (30") i/d	250 mm (10") i/dRft.viding and laying R.C.C. pipe sewers, moulded wit tent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriag- ipe from factory to site of work, lowering in trenches tect alignment and grade, jointing with rubber ring- ing pipes where necessary, testing, etc., completRft.310 mm (12") i/dRft.380 mm (15") i/dRft.460 mm (18") i/dRft.530 mm (21") i/dRft.610 mm (24") i/dRft.690 mm (27") i/dRft.	250 mm (10") i/dRft.21.45viding and laying R.C.C. pipe sewers, moulded wit tent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriag- ipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring- ing pipes where necessary, testing, etc., completRft.32.40310 mm (12") i/dRft.32.40380 mm (15") i/dRft.40.65460 mm (18") i/dRft.49.05530 mm (21") i/dRft.61.40610 mm (24") i/dRft.70.90690 mm (27") i/dRft.103.80760 mm (30") i/dRft.124.45	250 mm (10") i/d Rft. 21.45 92.40 viding and laying R.C.C. pipe sewers, moulded wit ent concrete 1:1½:3 conforming to ASTN iffer the sewers is a sewer to a s	250 mm (10") i/dRft.21.4592.40Metreviding and laying R.C.C. pipe sewers, moulded wit tent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriagi ipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring ing pipes where necessary, testing, etc., completRft.32.40339.75Metre310 mm (12") i/dRft.32.40339.75MetreMetre310 mm (12") i/dRft.40.65416.30Metre380 mm (15") i/dRft.40.65416.30Metre600 mm (18") i/dRft.61.40580.20Metre610 mm (24") i/dRft.70.90695.95Metre690 mm (27") i/dRft.103.80972.40Metre760 mm (30") i/dRft.124.451038.35Metre	250 mm (10") i/d Rft. 21.45 92.40 Metre 70.35 viding and laying R.C.C. pipe sewers, moulded wit tent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriagi ipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring ing pipes where necessary, testing, etc., complet Rft. 32.40 339.75 Metre 106.25 310 mm (12") i/d Rft. 40.65 416.30 Metre 133.35 380 mm (15") i/d Rft. 49.05 450.45 Metre 106.25 380 mm (18") i/d Rft. 49.05 450.45 Metre 106.25 530 mm (18") i/d Rft. 70.90 695.95 Metre 106.25 610 mm (24") i/d Rft. 70.90 695.95 Metre 123.35 690 mm (27") i/d Rft. 103.80 972.40 Metre 340.45 760 mm (30") i/d Rft. 124.45 1038.35 Metre 408.20	250 mm (10") i/d Rft. 21.45 92.40 Metre 70.35 303.05 viding and laying R.C.C. pipe sewers, moulded wit sent concrete 1:1½:3 conforming to ASTN cification C-76-79, Class II. Wall B, including carriag- ipe from factory to site of work, lowering in trenches rect alignment and grade, jointing with rubber ring- ing pipes where necessary, testing, etc., complet Rft. 32.40 339.75 Metre 106.25 1114.40 310 mm (12") i/d Rft. 32.40 339.75 Metre 106.25 1114.40 380 mm (15") i/d Rft. 40.65 416.30 Metre 133.35 1365.45 530 mm (18") i/d Rft. 61.40 580.20 Metre 201.40 1903.05 610 mm (24") i/d Rft. 70.90 695.95 Metre 232.55 2282.70 690 mm (27") i/d Rft. 103.80 972.40 Metre 340.45 3189.45 760 mm (30") i/d Rft. 124.45 1038.35 Metre 408.20 3405.80	250 mm (10") i/d Rft. 21.45 92.40 Metre 70.35 303.05 viding and laying R.C.C. pipe sewers, moulded wit Image: concrete 1:1½:3 conforming to ASTN Image:

br.	Description	1	Rate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	x) 1070 mm (42") i/d	Rft.	247.85	2143	Metre	812.95	7029.05		
	x) 1070 mm (42") i/d xi) 1220 mm (48") i/d	Rft.	463.05	2843.3	Metre	1518.8	9326		
	xi) 1220 mm (48) 1/d xii 1370 mm (54") i/d	Rft.	636.85	3560.15	Metre	2088.85	11677.3		
	xiii) 1520 mm (60") i/d	Rft.	815.6	4063.7	Metre	2675.15	13328.95		
	xiii) 1520 mm (60") i/d xiv) 1680 mm (66") i/d	Rft.	1269.85	4842.75	Metre	4165.1	15884.2		
	xv) 1830 mm (72") i/d	Rft.	1205.85	5469.90	Metre	5156.80	17941.25		
4	Providing and laying R.C.C. pipe sewers, moulded wit							Chapter-8	
	cement concrete 1:11/2:3 conforming to ASTM Specificatio								
	C-76-79, Class III, Wall B, including carriage of pipes from								
	factory to site of work, lowering in trenches to correct		1						
	alignment and grade, jointing with rubber ring, cutting pipe		/ 7						
	where necessary, testing, etc. complete			1					
	i) 310 mm (12") i/d	Rft.	32.40	410.00	Metre	106.20	1344.80		
	ii) 380 mm (15") i/d	Rft.	40.65	505.05	Metre	133.35	1656.55		
	iii) 460 mm (18") i/d	Rft.	49.05	636.95	Metre	160.95	2089.20		
	iv) 530 mm (21":) i/d	Rft.	61.40	778.85	Metre	201.35	2554.65		
	v) 610 mm (24") i/d	Rft.	70.90	905.70	Metre	232.45	2970.70		
	vi) 690 mm (27") i/d	Rft.	103.80	1080.45	Metre	340.40	3543.90		
	vii) 760 mm (30") i/d	Rft.	124.45	1304.15	Metre	408.15	4277.60		
	viii) 840 mm (33") i/d	Rft.	154.80	1452.50	Metre	507.70	4764.20		
	ix) 910 mm (36") i/d	Rft.	190.45	1953.75	Metre	624.70	6408.30		
	x) 1070 mm (42") i/d	Rft.	247.85	2539.60	Metre	813.00	8329.90		
	xi) 1220 mm (48") i/d	Rft.	469.70	3088.85	Metre	1540.60	10131.45		
	xii 1370 mm (54") i/d	Rft.	646.15	3896.95	Metre	2119.45	12782.00		
	xiii) 1520 mm (60") i/d	Rft.	827.25	4820.70	Metre	2713.35	15811.90		
	xiv) 1680 mm (66") i/d	Rft.	1288.45	6263.30	Metre	4226.15	20543.60		
	xv) 1830 mm (72") i/d	Rft.	1595.50	7729.15	Metre	5233.20	25351.60		
5	Providing and laying R.C.C. pipe sewers, moulded wit							Chapter - 8	
	cement concrete 1:11/2:3 conforming to ASTN								
	Specification C-76-79, Class IV, Wall B, including carriag								
	of pipes from factory to site of work, lowering in trench								
	to correct alignment and grade, jointing with rubber ring								
	cutting pipes where necessary, testing, etc. complete								
	i) 310 mm (12") i/d	Rft.	32.40	511.00	Metre	106.20	1676.05		
	ii) 380 mm (15") i/d	Rft.	40.65	638.95	Metre	133.35	2095.70		
	iii) 460 mm (18") i/d	Rft.	49.05	767.00	Metre	160.95	2515.75		
	iv) 530 mm (21":) i/d	Rft.	61.40	899.00	Metre	201.35	2948.65		
	v) 610 mm (24") i/d	Rft.	70.90	1028.10	Metre	232.45	3372.20		
	vi) 690 mm (27") i/d	Rft.	103.80	1355.85	Metre	340.40	4447.20		
	vii) 760 mm (30") i/d	Rft.	124.45	1561.15	Metre	408.15	5120.70		
	viii) 840 mm (33") i/d	Rft.	154.80	1735.20	Metre	507.70	5691.55		
	ix) 910 mm (36") i/d	Rft.	190.45	2461.70	Metre	624.70	8074.35		

sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
lo.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	x) 1070 mm (42") i/d	Rft.	247.85	3017.00	Metre	813.00	9895.70		
	xi) 1220 mm (48") i/d	Rft.	469.70	3634.30	Metre	1540.35	11920.60		
	xii) 1370 mm (54") i/d	Rft.	646.15	4912.95	Metre	2119.65	16114.35		
	xiii) 1520 mm (60") i/d	Rft.	827.25	6197.70	Metre	2713.35	20328.55		
	xiv) 1680 mm (66") i/d	Rft.	1288.45	8050.35	Metre	4226.15	26405.10		
	xv) 1830 mm (72") i/d	Rft.	1595.50	9497.85	Metre	5233.20	31152.95		
5	Lowering of sub-soil water table, by installation of tubewel along sewer line and pumping out water, for excavation i open cutting below sub-soil water level, concreting, curin; laying and jointing pipes, filling haunches, etc. till th completion of sewer line, including disposal of pumped of water:-			5					 This rate shall be payable, ir addition to the item of excavation below SSWL for sewers and manholes under Chapter EARTHWORK The grant of these rates shall be
		Rft of			Metre of				subject to Superintending Engineer'
	1) 0-1 ft. (0 to 310 mm) below SSWL	laid sewer		191.00	laid sewer	-	626.50		approval.
	2) 0-2 ft. (0 to 610 mm) below SSWI	ditto		364.55	ditto	-	1195.75		
	3) 0-3 ft. (0 to 910 mm) below SSWL	ditto		620.15	ditto	-	2034.05		3) The rate includes cost of
	4) 0-4 ft. (0 to 1220 mm) below SSWL	ditto		894.75	ditto	-	2934.80		providing pumps, POL and all
	5) 0-5 ft. (0 to 1520 mm) below SSWL	ditto	5.	1244.80	ditto	-	4082.95		operation charges at the site
	6) 0-6 ft. (0 to 1830 mm) below SSWL	ditto	1.10	1540.10	ditto	-	5051.45		of work, etc.
	7) 0-7 ft. (0 to 2170 mm) below SSWL	ditto		1839.60	ditto	-	6033.90		
	8) 0-8 ft. (0 to 2480 mm) below SSWL	ditto		2112.40	ditto	-	6928.70		
	9) 0-9 ft. (0 to 2790 mm) below SSWL	ditto	- 0	2283.30	ditto	-	7489.25		
	10) 0-10 ft. (0 to 3100 mm) below SSWL	ditto	-	2630.50	ditto	-	8628.00		
	11) 0-11 ft. (0 to 3410 mm) below SSWL	ditto	0.0000000000	2924.70	ditto	÷ -	9592.95		
	12) 0-12 ft. (0 to 3720 mm) below SSWL	ditto	996 8446 A <u>6</u> 27 A Bo	3241.60	ditto		10632.50		
,	Constructing gully grating chamber, 12"x12", (300x300 mm) complete in all respects							16.2	Pipe connection to be paid separately.
	a) with C.I. gully trap, weighing 81 lbs. (36.75 Kg.) fram hinged safety type	Each	539.00	2504.45	Each	539.00	2504.45		
	b) concrete Gully trap.	ditto	539.00	2279.45	ditto	539.00	2279.45		
3	Constructing standard gully grating chamber, 3'x2½ (900x750 mm), with chinaware trap as per PHED Drawing STD/PD No. 3 of 1977, complete in all respects	Each	1627.80	7177.10	Each	1627.80	7177.10	ditto	Pipe connection to be paid separately.
)	Extra for making and finishing benching floor work i manhole chamber, with 1/8" (3 mm) thick cement finish	100Sft.	685.75	1116.00	Sq.m	73.80	120.10	14.4	
0	Restoration of brick pavement on edge, over laid servic line, with 2" (50 mm) sand cushion under soling	100Sft.	988.00	2428.40	Sq.m	106.30	261.30	13.1	
1	Restoration of flat brick pavement sand grouted, over 2	100Sft.	599.60	1622.40	Sq.m	64.50	174.55	13.1	

	MRS, BI-ANNUAL PER	IOD (1st	AUGUST, 2	012 TO 31st	t JANUA	ARY, 2013	B) DISTRIC	JHANG	
Sr.	Description	F	ate (British Sy	stem)	Ra	te (Metric S	system)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(50 mm) thick dry sand cushion, under soling on lais service line.								
12	Restoration of metalled road, on laid service line, includin compaction:-							13.1	
	a) Carpetted road, with 2" (50 mm) carpet and 10" (250 mm) depth of stone metal for sub-base and base	100Sft.	2591.25	8902.10	Sq.m	278.80	957.85		
	 b) Carpeted road, with 1¹/₂" (38 mm) carpet and 6" (150 mm) depth of stone metal, for sub-base and base 	100Sft.	1864.80	6579.55	Sq.m	200.65	707.95		
	 c) Black Topped Road with two coats of surfacing & 10" (250 mm) depth of stone metal, for sub base & base. 	100Sft.	714.60	4272.25	Sq.m	76.90	459.70		
13	Providing and fixing 1 ¹ / ₄ "x1 ¹ / ₄ "x3/16" (31x31x5 mm) angle iron step, in manhole chambers, including carriage an setting the same in work to correct lines and level:	Each	68.85	229.65	Each	68.85	229.65	14.7	
14	Fixing manhole frame and cover in R.C.C. slab includin carriage to site.	Per set	169.15		Per set	169.15	-	ditto	
	Providing and fixing 3" (75 mm) thick R.C.C. manhol- cover, 22" (550 mm) dia, with tee shaped C.I. frame of 20 (500 mm) clear i/d (frame weighing 37.324 Kg. or on maund) as per Standard Drawing STD/PD No. 5, of 1977 complete in all respects	Per set	116.10	2836.75	Per set	116.10	2836.75	ditto	
	Providing and fixing 6" thick R.C.C. manhol- cover with tee shaped C.I. frame of 22" I/d (fram weighing 37.324 Kg. or one maund as per Standard Drawing STD/PD No. 6, of 1977, complete in all respect	Per set	230.50	4098.35	Per set	230.50	4098.35		
16	Providing and fixing, 6" (150 mm) thick R.C.C. manhol- cover for 22" as per standard drawing STD/PD No. 6 of 1977, complete in all respects	Per set	207.15	2506.05	Per set	207.15	2506.05	ditto	
17	Providing and fixing, 6" (150 mm) thick R.C.C. manhol- cover with 3"x3"x¼" (75x75x6mm) angle iron frame, 22 (550 mm) i/d as per standard drawing STD/PD No. 7 of 1977, complete in all respects	Per set	178.20	4017.70	Per set	178.20	4017.70	ditto	
18	Desilting of disposal work collecting tank, includin removal of sludge within 3 chains (90 metre)	100Cft.	520.45	574.75	cum	183.85	203.00	16.2	

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description	F	ate (British Sy	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
19	Providing and installing, C.I. ventilating shaft painted wit							14.6					
	bituminous paint with foundation bolts, as per PHEI												
	Standard Drawing STD/PD No. 4 of 1977, complete in al												
	respects (except concrete foundation block)												
	a) 6" (150 mm) i/d shaft												
	i) 18 ft. (5.5 metre) long	Per Cwt	150.55	2305.35	%kg	296.40	4538.10						
	i) 24 ft. (7.30 metre) long	ditto	167.30	2305.55		329.30	4583.45						
	iii) 30 ft. (9.15 metre) long	ditto	180.70	2340.40		355.65	4607.10						
	iv) 36 ft. (11 metre) long	ditto	189.05	2349.15	ditto	372.15	4624.30						
			/ ~	1									
	b) 9" (225 mm) i/d shaft												
	i) 18 ft. (5.5 metre) long	Per Cwt	132.80	2283.80	%kg	261.40	4495.65						
	ii) 24 ft. (7.30 metre) long	ditto	143.10	2293.60	ditto	281.70	4514.95						
	iii) 30 ft. (9.15 metre) long	ditto	153.20	2304.05	ditto	301.60	4535.55						
	iv) 36 ft. (11 metre) long	ditto	184.45	2335.10	ditto	363.05	4596.70						
		637	1.5	-19/	-49								
	c) 12" (300 mm) i/d shaft	1		-10	63								
	i) 18 ft. (5.5 metre) long	Per Cwt	117.50	2269.55	%kg	231.35	4467.60						
	ii) 24 ft. (7.30 metre) long	ditto	151.10	2300.30	ditto	297.45	4528.10						
	iii) 30 ft. (9.15 metre) long	ditto	176.30	2324.80	ditto	347.00	4576.35						
20	Silt clearing 10' (3.00 m) dia walls and	128. 194	NA MARKANA ANA	serves llounes o	empicise/He								
20	Silt clearing 10' (3.00 m) dia wells, and removal of slush outside the compound:												
	removal or shash outside the compound.												
	a) upto 10' (3.00 m) depth of slusł	Per well	4266.90	-	Per well	4266.90	-						
	b) beyond 10' (3.00 m) depth of slush	Per well	8401.80	-	Per well	8401.80	-						

22. SINKING OF WELLS

1 Rates for all finished works include the removal of surplus debris, unused material and byproducts.

2 Well curbs to be laid at spring level or as deep as possible.

	MRS, BI-ANNUA	_ PERIOD (*	Ist AUGUS1	r, 2012 TO 3	1st JAN	UARY, 20	13) DISTRI	CT JHANG	
Sr.	Description	1	Rate (British Sy	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Excavation of well in dry upto 20'(6 metre) below ground level, and disposal of soil within one chain (30 metre)								
	a) in ordinary soil or sand :-	1000 Cft.			cu.m				
	i) from 0' to 5' (o to 1.5 m) depth	ditto	2706.90	-	ditto	95.60	-		
	ii) from 5.1' to 10' (1.5 to 3.0 metre) depth	ditto	2827.10	XF 3	ditto	99.85	-		
	iii) from 10.1' to 15' (3.0 to 4.5 metre) depth	ditto	3180.50	1	ditto	112.35	-		
	iv) from 15.1' to 20' (4.5 metre to 6.0 metre) depth	ditto	3650.50	-	ditto	128.95	-		
	b) in hard soil				\exists	5			
	i) from 0' to $5'(0$ to 1.5 metre) depth	1000 Cft.	3297.10		cu.m	116.45			
	ii) from 5.1' to 10'(1.5 to 3.0 metre) depth	ditto	3446.45		ditto	121.75			
	iii) from 10.1' to 15'(3.0 to 4.5 metre) depth	ditto	3767.05	^{رعا} د م <u>ب</u> ت چکا	ditto	133.05	-		
	iv) from 15.1' to 20'(4.5 to 6.0 metre) depth	ditto	4237.05		ditto	149.65	-		
	c) in hard strata, such as shingle, gravel, etc.			~~~					
	i) from 0' to $5'(0$ to 1.5 metre) depth	1000 Cft.	7111.55	e (I)tenn	cu.m	251.20	-		
	ii) from 5.1' to 10'(1.5 to 3.0 metre) depth	ditto	7366.55	8	ditto	260.20			
	iii) from 10.1' to 15'(3.0 to 4.5 metre) depth	ditto	7679.85	-	ditto	271.25	-		
	iv) from 15.1' to 20'(4.5 to 6.0 metre) depth	ditto	8244.55	-	ditto	291.20	-		
2	Dry sinking of well, including loading, and removing								
	excavated material within one chain (30 m):-								
	a) in ordinary soil :-								
	i) from 10' to $15'(3.0 \text{ to } 4.5 \text{ m})$ depth	1000 Cft.	14572.80	-	cu.m	514.70			
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	18216.00	-	ditto	643.40			
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	21859.20	-	ditto	772.05			
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	25502.40	-	ditto	900.75			
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	29145.60	-	ditto	1029.40			
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	32788.80	-	ditto	1158.10			
	vii) from 40.1'to 45'(12.0 to 13.5 m) depth	ditto	36432.00	-	ditto	1286.80			
	viii) from 45'(13.5 Sm) to any depth	ditto	40075.20	-	ditto	1415.45			
	b) in hard soil :-								
	i) from 10' to $15'(3.0 \text{ to } 4.5 \text{ m})$ depth	1000 Cft.	20037.60	-	cu.m	707.75	-		

	MRS, BI-ANNUAL P	ERIOD (1	Ist AUGUST	, 2012 TO 3	1st JAN	UARY, 20	13) DISTRIC	CT JHANG	
Sr.	Description	F	Rate (British Sys	stem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	23680.80	-	ditto	836.40	-		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	27324.00	-	ditto	965.10	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	30967.20	-	ditto	1093.75	-		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	34610.40	-	ditto	1222.45	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	38253.60	-	ditto	1351.10	-		
	vii) from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	41896.80	-	ditto	1479.80	-		
	viii) from 45'(13.5 m) to any depth	ditto	45540.00	-	ditto	1608.45	-		
	c) in hard strata, such as shingle, gravel, etc.								
	i) from 10' to 15'(3.0 to 4.5 m) depth	1000 Cft.	27324.00	~ .	cu.m	965.10			
	ii) from 15.1' to 20'(4.5 to 6.0 m) depth	ditto	30967.20	~) ·	ditto	1093.75	_		
	iii) from 20.1' to 25'(6.0 to 7.5 m) depth	ditto	34610.40		ditto	1222.45	-		
	iv) from 25.1' to 30'(7.5 to 9.0 m) depth	ditto	35065.80	-	ditto	1238.50	_		
	v) from 30.1' to 35'(9.0 to 10.5 m) depth	ditto	41896.80		ditto	1479.80	-		
	vi) from 35.1' to 40'(10.5 to 12.0 m) depth	ditto	45540.00		ditto	1608.45	-		
	vii)from 40.1' to 45'(12.0 to 13.5 m) depth	ditto	49183.20		ditto	1737.15	-		
	viii) from 45'-1" (13.5 m) to any depth	ditto	52826.40	1- 6	ditto	1865.85	-		
		1	200	مر مت برم	14	~			
3	Wet sinking of well in ordinary soil (value of C upto 5), for depths below spring level, including charges of machinery,			28 C	193			*841-1 to	The outer dimensions of the curb shall form basis of payment.
	shoring, kentledge and removal of excavated spoil within							841-9	
	one chain (30 m):-	9	Financ	e Depu	er tinne	mt –			
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	22983.55	-	cu.m	811.80	-		
	ii) above 10' to 20'(3.0 to 6.0 m) depth	ditto	48840.00	-	ditto	1725.05	-		
	iii) above 20' to 30'(6.0 to 9.0 m) depth	ditto	60110.75	-	ditto	2123.10	-		
	iv) above 30' to 40'(9.0 to 12.0 m) depth	ditto	78144.00	-	ditto	2760.05	-		
	v) above 40' to 50'(12.0 to 15.0 m) depth	ditto	86826.65	-	ditto	3066.70	-		
	vi) above 50' to 60'(15.0 to 18.0 m) depth	ditto	97680.00	-	ditto	3450.05	-		
	vii) above 60' to 70'(18.0 to 21.0 m) depth	ditto	100184.60	-	ditto	3538.50	-		
	viii) above 70' to 80'(21.0 to 24.0 m) depth	ditto	102821.05	-	ditto	3631.65	-		
	ix) above 80'(24.0 m) to any depth	ditto	111634.30	-	ditto	3942.90	-		
4	Wet sinking of well in cohesive soil (value of Cmore than							*841-1	The outer dimensions of the curb
+	5), for depths below spring level, including charges of							to	shall form basis of payment.
	machinery shoring, kentledge and removal of excavated							841-9	shan torm busis of paymont.
	spoil within one chain (30 m):-							071-7	
	i) from o' to 10'(0 to 3.0 m) depth	1000 Cft.	_	35377.10	cu.m	_	1249.50		
	i) above $10'$ to $20'(3.0 \text{ to } 6.0 \text{ m})$ depth	ditto	-	44221.35			1249.50		
	iii) above $20'$ to $30'(6.0 \text{ to } 9.0 \text{ m})$ depth	ditto	_	53065.60	ditto	_	1874.30		
	iv) above $30'$ to $40'(9.0 \text{ to } 12.0 \text{ m})$ depth	ditto	-	70754.15	ditto	_	2499.05		
		unto		, 57, 54, 15	unto	1. J	2777.03		

	WING, DI-ANNOAL	PERIOD (Ist AUGUS I	Γ, 2012 TO 3 [·]	1st JAN	UARY, 20	13) DISTRI	CT JHANG	
Sr.	Description]	Rate (British Sys	stem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 v) above 40' to 50'(12.0 to 15.0 m) depth vi) above 50' to 60'(15.0 to 18.0 m) depth vii) above 60' to 70'(18.0 to 21.0 m) depth viii) above 70' to 80'(21.0 to 24.0 m) depth ix) above 80'(24.0 m) to any depth 	ditto ditto ditto ditto ditto	- - - -	81639.40 88442.70 96482.95 100123.80 106131.25	ditto ditto ditto ditto ditto		2883.50 3123.80 3407.80 3536.35 3748.55		
5	Wet sinking of well in shingle, or gravel, etc, for depths below spring level, including charges of machinery, shoring, kentledge and removal of excavated spoil within one chain (30 m) :-							*841-1 to 841-9	The outer dimensions of the curb shall form basis of payment.
	 i) from o' to 10'(0 to 3.0 m) depth ii) above 10' to 20'(3.0 to 6.0 m) depth iii) above 20' to 30'(6.0 to 9.0 m) depth iv) above 30' to 40'(9.0 to 12.0 m) depth v) above 40' to 50'(12.0 to 15.0 m) depth vi) above 50' to 60'(15.0 to 18.0 m) depth vii) above 60' to 70'(18.0 to 21.0 m) depth viii) above 70' to 80'(21.0 to 24.0 m) depth 	1000 Cft. ditto ditto ditto ditto ditto ditto ditto		48241.45 58961.80 70754.15 96482.95 106131.25 117923.60 123408.40 126346.70	cu.m ditto ditto ditto ditto ditto ditto ditto		1703.90 2082.55 2499.05 3407.80 3748.55 4165.05 4358.80 4462.55		
ſ	ix) above 80'(24.0 m) to any depth	ditto	-	139646.35 2063.15	ditto	-	4932.30		
6 7	Making and fixing in position, kiker wood well curb. Laying well curb in position only.	Per Cft. Each	664.20 234.95	2003.15	cu.m Each	23459.35 234.95	-		
8	Providing, making and laying R.C.C. well curb in position, using coarse sand, including all kinds of form, moulds, curing, shuttering, rendering and finishing the exposed surface, (including screening and washing of aggregate :-							*841-1 to 841-9	 If concrete mixer is supplied by Government, all charges including depreciation will be recovered from the contractor. The rate does not include cost of
	a) Ratio 1:11/2:3 b) ratio 1:2:4	Per Cft. ditto	143.55 143.55	339.70 316.75	cu.m ditto	5070.20 5070.20	11997.65 11188.20		steel reinforcement and its labour for bending, which is payable, separately.
9	Providing and fixing structural steel for cutting edge.	100Kg	521.40	10875.90	100Kg	521.40	10875.90	841-1 to 841-9	
10	Making and removing false masonry on well.	100Cft.	4518.15	15423.35	cu.m	1595.80	5447.55	21.1 to 21.5 & 18.1	The rate includes dismantling of false masonry, scraping bricks obtained from dismantling and credit of byproducts.

* Specification No. correspond to Book of "Standard Specification for Road and Bridge Construction, 1971".

23. TUBEWELL AND WATER SUPPLY

Specification No. correspond to Book of "Specification for B&R Department, 1966, Vol. II (Public Health Works)". Rates for all finished works include the removal of surplus debris, unused material and byproducts. 1 2

	2 Rates for all finished works include the removal of surplus debris, unused material and byproducts. MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Boring for tubewell in all types of soil except shingle and rock, from ground level to 100 ft. (30 m) depth, including sinking and withdrawing of casing pipe, complete:-							Chap. 2				
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft. of bore ditto ditto ditto ditto ditto ditto ditto ditto	Ć	39.00 53.75 96.45 147.45 190.35 241.40 262.70 389.90 414.05	Per Metre of bore ditto ditto ditto ditto ditto ditto ditto		128.00 176.35 316.35 483.65 624.35 791.85 861.65 1278.95 1358.05	P.,				
2	 Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 100.1 ft. to 200 ft. (30 to 60 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d 	Per Rft. of bore ditto ditto ditto ditto ditto ditto	inanci	163.00 229.95 257.30 295.25 324.35 457.05 481.15	Per Metre of bore ditto ditto ditto ditto ditto ditto		534.55 754.20 844.00 968.45 1063.80 1499.15 1578.25	ditto				
3	Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 200.1 ft. to 300 ft. (60 to 90 m) below ground level, including sinking and withdrawing of casing pipe, complete:- a) 5" (125 mm) i/d b) 6" (150 mm) i/d c) 8" (200 mm) i/d d) 10" (250 mm) i/d e) 12" (300 mm) i/d f) 15" (375 mm) i/d g) 18" (450 mm) i/d Boring for tubewell in all types of soil except shingle, gravel & rock, from a depth of 300.1 ft. to 400 ft. (90 to 120 m) below ground level, including sinking and withdrawing of casing pipe, complete:-	Per Rft. of bore ditto ditto ditto ditto ditto		227.55 293.90 323.70 366.15 388.65 501.85 527.20	Per Metre of bore ditto ditto ditto ditto ditto		746.30 963.95 1061.65 1201.05 1274.80 1646.15 1729.20	ditto Chap. 2				

	MRS, BI-ANNUAL P	NG	-						
Sr.	Description		Rate (British S	ystem)	Ra	ite (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	a) 8" (200 mm) i/d b) 10" (250 mm) i/d c) 12" (300 mm) i/d d) 15" (375 mm) i/d e) 18" (450 mm) i/d	Rft of bore ditto ditto ditto ditto		390.65 437.70 461.95 613.05 616.65	Per Metre of bore ditto ditto ditto		1281.30 1435.60 1515.25 2010.80 2022.60		
5	Direct Rotary/Reverse Rotary drilling of bore for tubewells, in all types of soil except shingle, gravel and rock:-							ditto	
	 a) from ground level to 250 ft. (75 m) below ground level:- i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d 	Per Rft. of bore ditto		387.85 557.80	Per Metre of bore ditto		1272.15 1829.55		Upto 2 cusec discharge Above 2 cusec discharge
	 b) exceeding 250 ft. (75 m) depth below ground level:- 	Rft	\square	337.80	Per Metre		1629.33		Above 2 cusec discharge
6	 i) 15" to 18" (375 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d Boring for tubewell in shingle, gravel and rock, including 	of bore ditto	E	387.85 557.80	of bore ditto		1272.15 1829.55	ditto	Upto 2 cusec discharge Above 2 cusec discharge Location and depth of shingle,
	sinking and withdrawing of casing pipe:- a) from ground level to 200 ft. (60 m) below ground level:-	1		de la compañía de la	63				gravel or rock is to be determined from the bore log.
	 i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d 	Per Rft. of bore ditto	Sma n ce	874.70 1183.00	Per Metre of bore ditto		2869.05 3880.30		Upto 2 cusec discharge Above 2 cusec discharge
	b) exceeding 200 ft. (60 m) depth below ground level:-								
	 i) 12" to 18" (300 to 450 mm) i/d ii) 20" to 26" (500 to 650 mm) i/d 	ditto ditto		874.70 1183.00	ditto ditto		2869.05 3880.30		Upto 2 cusec discharge Above 2 cusec discharge
7	Providing strong substantially built box of deodar wood 4'x2½'x9" (1200x750x225 mm), with compartments, lock and locking arrangement, for preserving samples of strata from bore hole.	Job for compl- ete bore	560.65	10328.65	Job for compl- ete bore	560.65	10328.65	ditto	
8	Furnishing sample of water from bore hole.	Per Set of 2 bottles	118.80	169.20	Per Set of 2 bottles	118.80	169.20	Chap. 2	
9	Providing and installing, brass strainer in tubewell bore hole, including sockets, special sockets, studs, etc. complete:-							ditto	Cost/labour of jointing both ends is included in the rate.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	 a) 2" i/d, 5/32" (50 mm i/d 4 mm) thick b) 3" i/d, 5/32" (75 mm i/d 4 mm) thick c) 4" i/d, 3/16" (100 mm i/d 5 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick i) 10" i/d, 3/16" (250 mm i/d 5 mm) thick j) 10" i/d, 1/4" (250 mm i/d 6 mm) thick k) 12" i/d, 1/4" (300 mm i/d 6 mm) thick l) 15" i/d, 1/4" (450 mm i/d 6 mm) thick 	Per Rft. Per Rft.	$ \begin{array}{r} 19.95 \\ 19.95 \\ 26.60 \\ 29.95 \\ 33.25 \\ 38.70 \\ 46.90 \\ 46.90 \\ 52.75 \\ 52.75 \\ 52.75 \\ 53.95 \\ 61.70 \\ $	691.95 1017.45 1276.10 1499.95 1608.25 1918.20 2430.40 2430.40 2482.90 2551.75 3234.25 3676.45 4576.70 5154.20	Per Metre Per Metre	65.45 65.45 87.25 98.25 109.10 126.95 153.80 153.80 172.95 172.95 176.90 202.45 202.45	2269.60 3337.25 4185.65 4919.85 5275.10 6291.75 7971.65 8143.85 8369.65 10608.25 12058.70 15011.65 16905.85				
10	 n) 20" i/d, ¹/4" (500 mm i/d 6 mm) thick o) 22" i/d, ¹/4" (550 mm i/d 6 mm) thick Providing and installing M.S. Bail plug in tubewell bore hole: a) 2" i/d, 1.5 ft. (50 mm i/d 450 mm) long. b) 3" i/d, 1.5 ft. (75 mm i/d 450 mm) long. c) 4" i/d, 2 ft. (100 mm i/d 600 mm) long. d) 5" i/d, 2 ft. (125 mm i/d 600 mm) long. e) 6" i/d, 2 ft. (150 mm i/d 600 mm) long. f) 7" i/d, 2 ft. (175 mm i/d 600 mm) long. g) 8" i/d, 2 ft. (225 mm i/d 600 mm) long. h) 9" i/d, 2 ft. (225 mm i/d 600 mm) long i) 10" i/d, 2 ft. (300 mm i/d 600 mm) long j) 12" i/d, 2 ft. (375 mm i/d 600 mm) long k) 15" i/d, 2 ft. (450 mm i/d 600 mm) long m) 4" i/d, 2 ft. (500 mm i/d 600 mm) long 	Per Rft. Per Rft. Each Each Each Each Each Each Each Each	72.60 73.80 86.20 143.90 194.10 194.10 239.45 239.55 239.5	5690.10 6531.30 504.40 679.20 1333.55 1690.40 2139.35 2488.35 2751.30 3066.75 3958.95 4754.15 5874.25 6690.45 7413.80	Per Metre Each Each Each Each Each Each Each Each	238.20 242.15 86.20 143.90 194.10 194.10 239.45 239	18663.60 21422.75 504.40 679.20 1333.35 1690.40 2139.35 2488.35 2751.30 3066.75 3958.95 4754.15 5874.25 6690.45 7413.80		In the case of increase or decrease in the length of Bail plug, the rates will be increased or decreased as per rates given in serial No. 14 of this chapter for the respective diameter.		
11	 n) 22" i/d, 2 ft. (550 mm i/d 600 mm) long Providing and installing, P.V.C. strainer B.S.S. Class 'B', in tubewell bore hole, including sockets and solvents, etc. complete:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) Providing and installing P.V.C. strainer B.S.S. Class `D',	Each Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	375.80 14.65 16.60 17.55 20.40 28.05 28.65 28.65	8162.55 108.25 159.40 220.35 290.40 700.05 1048.65 1396.65	Per Metre	48.05 54.45 57.50 66.95 92.00 94.00 94.00	8162.55 355.05 522.85 722.70 952.55 2296.15 3439.60 4581.05	Chap. 2			

MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	complete:-										
	a) 1 ¹ / ₄ " i/d (30 mm) b) 1 ¹ / ₂ " i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	10.30 10.50 14.65 16.55 17.55 31.30	46.30 52.50 81.40 168.25 264.95 389.55 559.30	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	33.70 34.45 34.75 48.05 54.30 57.50 102.65	151.8 172.2 266.95 551.9 869.05 1277.65 1834.45				
13	Providing and installing P.V.C. Bail/End plug, in tubewell bore hole:-										
	i) B.S.S. Class `B'			*)							
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm)	Each Each Each Each Each Each	7.45 8.30 9.00 11.90 13.95	59.05 77.90 117.00 171.50 337.95	Each Each Each Each Each Each	7.45 8.30 9.00 11.90 13.95	59.05 77.90 117.00 171.50 337.95				
	 e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm) 	Each Each Each Each	13.93 14.70 17.35 17.35	470.70 635.35 659.35	Each Each Each	13.93 14.70 17.35 17.35	470.70 635.35 659.35				
	ii) B.S.S. Class `D'			H. G.							
	a) 1 ¹ / ₄ " i/d (30 mm) b) 1 ¹ / ₂ " i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each Each	5.25 5.50 5.70 7.45 8.30 9.00 11.9	31.65 45.10 64.50 85.45 111.50 157.80 206.3	Each Each Each Each Each Each Each	5.25 5.50 5.70 7.45 8.30 9.00 11.9	31.65 45.10 64.50 85.45 111.50 157.80 206.3				
14	Providing and installing M.S. blind pipe socketed/welded joint, M.S. reducer (where necessary), in tubewell bore hole, including jointing/welding with strainer, etc. complete:-							Chap. 2			
	 a) 2" i/d, 1/8" (50 mm i/d 3 mm) thick b) 3" i/d, 1/8" (75 mm i/d 3 mm) thick c) 4" i/d, 1/8" (100 mm i/d 3 mm) thick d) 5" i/d, 3/16" (125 mm i/d 5 mm) thick e) 6" i/d, 3/16" (150 mm i/d 5 mm) thick f) 7" i/d, 3/16" (175 mm i/d 5 mm) thick g) 8" i/d, 3/16" (200 mm i/d 5 mm) thick h) 9" i/d, 3/16" (225 mm i/d 5 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	51.65 51.65 64.60 92.15 92.15 107.55 107.55	232.55 311.45 409.95 752.80 905.75 1041.35 1284.95 1458.75	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	169.40 169.40 211.90 302.25 302.25 352.75 352.75	762.80 1021.55 1344.65 2469.25 2970.85 3415.65 4214.70 4784.70				
	i) 10" i/d, ¹ /4" (250 mm i/d 6 mm) thick j) 12" i/d, ¹ /4" (300 mm i/d 6 mm) thick	Per Rft. Per Rft.	107.55 129.10	1879.95 2214.10	Per Metre Per Metre	352.75 423.45	6166.25 7262.25				

	MRS, BI-ANNUAL F	DISTRICT JHA	NG						
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 k) 15" i/d, ¼" (375 mm i/d 6 mm) thick l) 18" i/d, ¼" (450 mm i/d 6 mm) thick m) 20" i/d, ¼" (500 mm i/d 6 mm) thick n) 22" i/d, ¼" (550 mm i/d 6 mm) thick 	Per Rft. Per Rft. Per Rft. Per Rft.	129.10 158.10 170.40 170.40	2735.35 3398.45 3770.80 4130.80	Per Metre Per Metre Per Metre Per Metre	423.45 518.55 558.90 558.90	8971.95 11146.90 12368.15 13549.10		
15	Providing and installing P.V.C. blind pipe, B.S.S. Class `B', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete.							ditto	
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 14" i/d (350 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	$ \begin{array}{r} 18.70\\ 21.10\\ 22.00\\ 26.45\\ 35.25\\ 36.70\\ 43.65\\ 40.65\\ \end{array} $	117.10 171.10 228.40 318.05 484.05 751.90 1042.05 1240.65	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	61.30 69.15 72.20 85.20 115.60 120.40 143.20 133.35	$\begin{array}{c} 384.05 \\ 561.15 \\ 749.20 \\ 1041.65 \\ 1587.70 \\ 2466.25 \\ 3417.95 \\ 4069.35 \end{array}$		
16	 Providing and installing P.V.C. blind pipe, B.S.S. Class 'D', in tubewell bore hole, including sockets and solvents and jointing with strainer, etc. complete. a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	12.15 12.35 13.10 16.40 21.10 22.00 27.20	47.65 58.45 84.15 170.00 279.10 404.95 584.35	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	39.85 40.50 42.90 53.75 69.15 72.20 89.15	156.35 191.65 275.95 557.55 915.55 1328.25 1916.70		
17	Testing and developing of tubewell of size 6" (150 mm) i/d and above continuously.								
	i) upto 1.5 cs. dischargeii) above 1.5 cs. discharge	Per Hour ditto		1022.50 1230.00	Per Hour ditto		1022.50 1230.00		
18	Shrouding with graded pea gravel 3/8" to 1/8" (10 to 3 mm), around tubewell in bore hole.	Per Cft.	19.80	72.70	cu.m	699.35	2567.75		The rate includes wastage, etc.
19	Laying cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with spigot and socket caulked lead joints, including cost of materials, such as lead, yarn, etc. complete in all respects:-							Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d	Per Rft. Per Rft. Per Rft.		40.90 50.80 63.60	Per Metre Per Metre Per Metre		134.05 166.60 208.55		

	MRS, BI-ANNUAL PI	ERIOD (1	st AUGUST,	2012 TO 31s	I JANUAR	Y, 2013) [DISTRICT JHA	NG	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.		75.35 91.95 137.70 161.50 209.25 276.60	Per Metre Per Metre		247.20 301.65 451.65 529.80 686.40 907.30		
20	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches, with flanged and flanged joints, complete in all respects:-							ditto	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the
	a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	C	18.65 20.70 30.65 33.65 39.55 55.50 64.90 89.05 111.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		61.15 67.95 100.50 110.45 129.75 182.05 212.95 292.00 366.85		rate, which is payable separately.
21	Laying, cutting, jointing, testing and disinfecting cast iron pipe line in trenches with Tyton joints, complete in all respects:- a) 3" (75 mm) i/d b) 4" (100 mm) i/d c) 5" (125 mm) i/d d) 6" (150 mm) i/d e) 8" (200 mm) i/d f) 10" (250 mm) i/d g) 12" (300 mm) i/d h) 15" (375 mm) i/d i) 18" (450 mm) i/d	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	inanci	9.20 10.65 13.60 15.30 20.85 26.25 31.25 46.40 55.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre		30.15 34.90 44.55 50.15 68.35 86.05 102.55 152.25 182.45	Chap. 2	 Pipes to be supplied by Government. Providing and installing specials and valves is not included in the rate, which is payable separately.
22	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipeline in trenches, with socket joints, using G.I. pipes of B.S.S. 1387-1967 complete in all respects, with specials and valves.							Chap. 2	Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	 i) Light Quality a) ¹/₂" i/d (15 mm) 2mm thick b) ³/₄" i/d (20 mm) 2.35mm thick c) 1" i/d (25 mm) 2.65mm thick d) 1¹/₄" i/d (32 mm) 2.65mm thick e) 1¹/₂" i/d (40 mm) 2.9mm thick f) 2" i/d (50 mm) 2.9mm thick g) 2"¹/₂ i/d (65 mm) 3.25mm thick h) 3" i/d (75 mm) 3.25mm thick i) 4" i/d (100 mm) 3.65mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	8.00 8.65 9.65 9.75 9.85 11.25 11.80 13.70 14.75	54.10 75.10 103.20 131.80 167.15 207.85 281.65 329.65 462.20	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	26.25 28.30 31.70 32.00 32.40 36.85 38.75 45.00 48.35	177.45 246.25 338.55 432.30 548.30 681.80 923.85 1081.30 1516.10		

	MRS, BI-ANNUAL P	ERIOD (1	st AUGUST,	2012 TO 31st	JANUAR	Y, 2013) D	DISTRICT JH	ANG	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 ii) Medium Quality a) ¹/₂" i/d (15 mm) 2.65mm thick b) ³/₄" i/d (20 mm) 2.65mm thick c) 1" i/d (25 mm) 3.25mm thick d) 1¹/₄" i/d (32 mm) 3.25mm thick 	Per Rft. Per Rft. Per Rft. Per Rft.	8.00 8.65 9.65 9.75	63.60 80.50 118.15 150.80	Per Metre Per Metre Per Metre Per Metre	26.25 28.30 31.70 32.00	208.60 264.05 387.50 494.55		 i. Cost of sockets, tees, elbow, bends, valves, crosses, unions and plugs etc is included in the rates except for internal G.I piping (1"dia, 3/4"dia & 1/2"dia) for Bath rooms/ Levorotary.
	 a) 1/4 i/d (32 iiii) 3.25min thick b) 1/2 i/d (40 mm) 3.25mm thick c) 2 i/d (50 mm) 3.65mm thick c) 2 i/2 i/d (65 mm) 3.65mm thick f) 3 i/d (75 mm) 4.05mm thick i) 4 i/d (100 mm) 4.5mm thick j) 5 i/d (150 mm) 4.85mm thick k) 6 i/d (200 mm) 4.85mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	10.05 11.25 11.80 13.70 14.75 17.05 17.40	172.80 237.70 303.35 381.20 543.60 745.25 867.60	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	33.05 36.85 38.75 45.00 48.35 56.00 57.00	566.75 779.65 995.00 1250.30 1782.95 2444.40 2845.70		 ii. For internal G.I piping (1"dia, 3/4"dia & 1/2"dia) Bath room(s)/ Levorotary of rate (composite) shall be reduced by 8% and specials mentioned above may be paid at the rates placed on Website as per actual quantity used.
	<u>iii) Heavy Quality</u>			C C					
	 a) ¹/₂" i/d (15 mm) 3.25mm thick b) ³/₄" i/d (20 mm) 3.25mm thick c) 1" i/d (25 mm) 4.05mm thick d) 1¹/₄" i/d (32 mm) 4.05mm thick e) 1¹/₂" i/d (40 mm) 4.05mm thick f) 2" i/d (50 mm) 4.5mm thick g) 2"¹/₂ i/d (65 mm) 4.5mm thick h) 3" i/d (75 mm) 4.85mm thick i) 4" i/d (100 mm) 5.4mm thick j) 5" i/d (125 mm) 5.4mm thick k) 6" i/d (150 mm) 5.4mm thick 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	8.00 8.65 9.65 9.75 10.05 11.25 11.80 13.70 14.75 17.05 17.40	89.35 117.10 221.30 251.45 344.80 430.85 554.75 753.75 932.35 1102.20	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	$\begin{array}{c} 26.25\\ 28.30\\ 31.70\\ 32.00\\ 33.05\\ 36.85\\ 38.75\\ 45.00\\ 48.35\\ 56.00\\ 57.00\\ \end{array}$	293.1 384.1 565.4 725.85 824.75 1131 1413.1 1819.6 2472.35 3058.2 3615.15		
23	Providing, laying, cutting, jointing, testing and disinfecting Asbestos cement/Fibre Cement pipe line in trenches, with comet joint and rubber ring, complete in all respects:- B Class WOrking Pressure							PS 428 & ISO 160	Providing and installing specials and valves is not included in the rate, which is payable separately.
	a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) g) 14" i/d (350 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) j) 20" i/d (500 mm) k) 24" i/d (600 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	$\begin{array}{c} 9.40\\ 10.00\\ 13.70\\ 18.95\\ 24.70\\ 31.45\\ 36.45\\ 41.20\\ 48.60\\ 57.15\\ 68.60\end{array}$	164.70 214.55 338.20 568.15 773.40 1021.30 1311.65 1664.85 2421.55 2551.90 3518.90	Per Metre Per Metre	30.90 32.80 45.00 62.10 80.95 103.10 119.50 135.05 159.40 187.50 225.00	540.30 703.65 1109.30 1863.55 2536.70 3349.80 4302.15 5460.65 7942.70 8370.25 11541.95		

	MRS, BI-ANNUAL F	PERIOD (1	st AUGUST,	2012 TO 31s	t JANUAR	Y, 2013) 🛛	DISTRICT JH/	ANG	
Sr.	Description		Rate (British S	vstem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
24	C Class Working Pressure							PS 428 &	
	a) 3" i/d (75 mm)	Per Rft.	9.40	164.70	Per Metre	30.90		ISO 160	
	b) 4" i/d (100 mm)	Per Rft.	10.00	236.00	Per Metre	32.80	774.05		
	c) $6'' i/d (150 \text{ mm})$	Per Rft.	13.70	405.10	Per Metre	45.00	1328.70		
	d) 8" i/d (200 mm) e) 10" i/d (250 mm)	Per Rft. Per Rft.	18.95 24.70	641.35 894.55	Per Metre Per Metre	62.10 80.95	2103.70 2934.15		
	f) 12" i/d (300 mm)	Per Rft.	31.45	894.55 1244.70	Per Metre	103.10	4082.60		
	g) 14" i/d (350 mm)	Per Rft.	36.45	1909.90	Per Metre	119.50	6264.45		
	h) $16'' i/d (400 \text{ mm})$	Per Rft.	41.20	2438.55	Per Metre	135.05	7998.45		
	i) 18" i/d (450 mm)	Per Rft.	48.60	3458.55	Per Metre	159.40	11344.05		
	j) 20" i/d (500 mm)	Per Rft.	57.15	3559.10	Per Metre	187.50	11673.90		
	k) $24'' i/d (600 \text{ mm})$	Per Rft.	69.55	5010.45	Per Metre	228.10	16434.30		
25	D Class Working Pressure							PS 428 &	
	a) 3" i/d (75 mm)	Per Rft.	9.40	164.70	Per Metre	30.90	540.30	ISO 160	
	b) 4" i/d (100 mm)	Per Rft.	10.00	267.55	Per Metre	32.80	877.55		
	c) 6" i/d (150 mm)	Per Rft.	13.70	487.15	Per Metre	45.00	1597.80		
	d) 8" i/d (200 mm)	Per Rft.	18.95	858.45	Per Metre	62.10	2815.75		
	e) 10" i/d (250 mm)	Per Rft.	24.70	1266.90	Per Metre	80.95	4155.40		
	f) 12" i/d (300 mm)	Per Rft.	31.45	1848.00	Per Metre	103.10	6061.45		
	g) 14" i/d (350 mm)	Per Rft.	36.45	2750.50	Per Metre	119.50	9021.65		
	h) 16" i/d (400 mm)	Per Rft.	41.20	3551.80	Per Metre	135.05	11649.85		
	i) 18" i/d (450 mm)	Per Rft.	48.60	4266.05	Per Metre	159.40	13992.65		
	j) 20" i/d (500 mm)	Per Rft.	57.15	5217.60	Per Metre	187.50	17113.80		
	k) 24" i/d (600 mm)		148 Save	and La	Sol				
26	Draviding laying outting jointing testing and disinfecting			2013				Chan	Droviding and installing appoints
20	Providing, laying, cutting, jointing, testing and disinfecting P.V.C. pipe line of B.S.S. with `B' Class working pressure		100					Chap 2	Providing and installing specials and valves is not included in the
	pipe, in trenches, complete in all respects:-		TEMELOTIN CH	Demmon	iment			2	rate, which is payable separately.
	pipe, in tenenes, complete in an respects			Barris Charles and					rate, which is payable separately.
	a) 3" i/d (75 mm)	Per Rft.	2.90	103.25	Per Metre	9.50	338.70		
	b) 4" i/d (100 mm)	Per Rft.	3.65	156.65	Per Metre	11.95	513.80		
	c) 5" i/d (125 mm)	Per Rft.	4.50	215.00	Per Metre	14.70	705.25		
	d) 6" i/d (150 mm)	Per Rft.	4.80	302.25	Per Metre	15.75	991.30		
	e) 8" i/d (200 mm)	Per Rft.	6.80	464.55	Per Metre	22.25	1523.75		
	f) 10" i/d (250 mm)	Per Rft.	8.80	738.30	Per Metre	28.90	2421.65		
	h) 12" i/d (300 mm)	Per Rft.	10.85	1029.25	Per Metre	35.65	3375.90		
	g) 14" i/d (350 mm)	Per Rft.	13.85	1237.85	Per Metre	45.45	4060.15		
27	Providing, laying, cutting, jointing, testing and disinfecting							ditto	Providing and installing specials
	pipe line in trenches with P.V.C. pipes of B.S.S. with 'D'								and valves is not included in the
	Class working pressure complete in all respects: $2^{"}$ i/d (50 mm)	Don Dft	0.25	74 00	Don Matur	7 75	245 40		rate, which is payable separately.
	a) 2" i/d (50 mm) b) 3" i/d (75 mm)	Per Rft. Per Rft.	2.35 2.85	74.80 159.50	Per Metre Per Metre	7.75 9.35	245.40 523.20		
	c) $4'' i/d (100 \text{ mm})$	Per Rit. Per Rft.	2.85 3.60	159.50 266.80	Per Metre Per Metre	9.35	875.10		
	d) 5" i/d (125 mm)	Per Rft.	4.40	395.00	Per Metre	11.73	1295.60		
	e) $6'' i/d (150 \text{ mm})$	Per Rft.	4.40	573.05	Per Metre	14.40	1879.55		
	-,,	1 01 100.		575.05	1 01 1/10/10	15.10	1077.55	ĺ	
28	Providing and fixing cast iron special of B.S.S. Class `B'							9.1	i) Labour rates include the cost of
	(such as bend, tee cross collar, reducer, tail piece,								jointing material & labour.

	MRS, BI-ANNUAL PE	ERIOD (1	st AUGUST,	2012 TO 31st	JANUAR	Y, 2013) D	ISTRICT JHA	NG	
Sr.	Description		Rate (British Sy	vstem)	Ra	ate (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 flanged spigot, cap, flanged socket, taper, angle branch, plug etc.) for cast iron pipe line , complete:- a) C.I.S.S. Specials, with spigot. and socket joint:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d 	Per Kg. Per Kg. Per Kg.	17.50 10.05 7.00	100.20 92.70 89.70	Per Kg Per Kg Per Kg	17.50 10.05 7.00	100.20 92.70 89.70		ii) The internal dia of the pipe, from which the oralich is taken out with be considered the internal dia for the purpose of payments of specials.
	 b) C.I. flanged specials, with flanged and flanged joints:- i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d c) C.I. Specials, with tyton joints:- 	Per Kg Per Kg Per Kg	7.70 2.30 3.40	90.40 84.95 84.95	Per Kg Per Kg Per Kg	7.70 2.30 3.40	90.40 84.95 84.95		
20	 i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 12" (200 to 300 mm) i/d iii) 15" to 18" (375 to 450 mm) i/d 	Per Kg Per Kg Per Kg	9.20 9.20 9.20	91.90 91.90 91.90	Per Kg Per Kg Per Kg	9.20 9.20 9.20	91.90 91.90 91.90	0.1	1) I share were include the cost of
29	 Providing and fixing cast iron specials of B.S.S. Class 'B' (such as bend, tee, cross collar, reducer, tail piece, flanged socket, flanged spigot, cap, taper, angle branch, plug, etc) for Asbestos cement pipe line, with comet joint and rubber ring, complete. i) 3" to 6" (75 to 150 mm) i/d ii) 8" to 18" (200 to 450 mm) i/d iii) 20" to 24" (500 to 600 mm) i/d 	Per Kg Per Kg Per Kg	11.40 5.95 4.80	94.05 88.65 87.45	Per Kg Per Kg Per Kg	11.40 5.95 4.80	94.05 88.65 87.45	9.1	 Labour rates include the cost of jointing material and labour. The internal dia of the pipe, from which the branch is taken out, will be considered the internal dia for the purpose of payment.
30	Providing and fixing sluice valve of B.S.S. quality and weight, Class `B', for cast iron pipe line, and Asbestos cement pipe line (including cost of jointing material):- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) e) 8" i/d (200 mm) f) 10" i/d (250 mm) g) 12" i/d (300 mm) h) 16" i/d (400 mm) i) 18" i/d (450 mm) Providing and fixing, sluice valve of B.S.S. quality and	Each Each Each Each Each Each Each Each	513.90 559.20 1006.60 1073.10 1252.95 2153.35 2419.80 3209.40 3693.85	5973.90 7039.20 8566.60 11633.10 20572.95 26393.35 34219.80 62609.40 109893.85	Each Each Each Each Each Each Each Each	513.90 559.20 1006.60 1073.10 1252.95 2153.35 2419.80 3209.40 3693.85	5973.90 7039.20 8566.60 11633.10 20572.95 26393.35 34219.80 62609.40 109893.85	9.1	Labour rates include cost of jointing material and labour. Labour rates include cost of jointing
51	 weight, for Asbestos cement pipe line, with comet joint and rubber ring, complete (including cost of jointing materials):- a) 3" i/d (75 mm) b) 4" i/d (100 mm) 	Each Each	357.90 442.60	5037.90 5866.60	Each Each	357.90 442.60	5037.90 5866.60	9.1	material and labour.

	MRS, BI-ANNUAL F	PERIOD (1	st AUGUST,	2012 TO 31st	I JANUAR	Y, 2013) D	DISTRICT JHA	NG	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 c) 6" i/d (150 mm) d) 8" i/d (200 mm) e) 10" i/d (250 mm) f) 12" i/d (300 mm) 	Each Each Each Each	561.05 924.25 1185.45 1389.50	9861.05 17964.25 22185.45 27549.50	Each Each Each Each	561.05 924.25 1185.45 1389.50	9861.05 17964.25 22185.45 27549.50		
	g) 16" i/d (400 mm) h) 18" i/d (450 mm)	Each Each	1647.10 1969.05	52887.10 94369.05	Each Each	1647.10 1969.05	52887.10 94369.05		
32	Providing and fixing, fire hydrants B.S.S. quality and weight of 2 ¹ / ₂ " (65 mm) dia (including cost of jointing material).	Each	52.95	4372.95	Each	52.95	4372.95	9.1	1) Labour rates include cost of jointing material and labour.
									 Connecting pipes and specials, if used, will be paid extra.
33	Providing and fixing, air valve 2½ (65mm) dia of B.S.S. quality and weight (complete with jointing material).			C*				ditto	
	a) single	Each	112.85	3172.85	Each	112.85	3172.85		
24	b) doubleProviding and fitting C.I. flanges on pipes, including	Each	112.85	7072.85	Each	112.85	7072.85		
34	turning, threading, facing and fitting, etc. complete in all respects:-	N.		÷,;	LE 65			ditto	
	a) 3" to 6" (75 to 150 mm) i/d	Per Kg	24.85	99.60	Per Kg	24.85	99.60		
	b) 8" to 12" (200 to 300 mm) i/d	Per Kg	15.70	90.50	Per Kg	15.70	90.50		
	c) 15" to 18" (375 to 450 mm) i/d	Per Kg	13.25	88.05	Per Kg	13.25	88.05		
35	Cutting C.I. pipe, and welding spigot or socket, flanged or tyton end, after finishing ends of pipes:	Per Inch			Per cm i/d				
	a) 3" to 6" (75 to 150 mm) i/d b) 8" to 12" (200 to 300 mm) i/d c) 15" to 18" (375 to 450 mm) i/d	i/d of pipe ditto ditto		46.65 57.30 53.05	of pipe ditto ditto		18.65 22.90 21.25		
36	Providing, laying, cutting, jointing, testing and disinfecting G.I. pipe line in trenches, with flanged joints, using G.I. pipe of B.S.S. 1387-1967 complete in all respects, including specials and valves:-								Cost of sockets, tees, elbows, bends, valves, crosses, unions and plugs, etc. is included in the rates.
	i) G.I. flanged joints (Heavy Quality)	D 50	10.6-		D 14		007 10		
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm)	Per Rft. Per Rft. Per Rft. Per Rft.	13.95 13.95 15.10 15.15	255.30 347.50 434.10 556.20	Per Metre Per Metre Per Metre	45.75 45.75 49.50 49.75	837.40 1139.85 1423.80 1824.40		
	e) 4" i/d (100 mm)	Per Rft.	17.30	756.35	Per Metre	56.80	2480.80		

	MRS, BI-ANNUAL PE	Eriod (1	st AUGUST,	2012 TO 31s	I JANUAR	Y, 2013) I	DISTRICT JHA	NG	
Sr.	Description		Rate (British S	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft.	19.45 19.45	934.75 1104.25	Per Metre Per Metre	63.75 63.90	3065.90 3622.00		
	ii) C.I. flanged joints (Medium Quality)								
	a) 1½" i/d (40 mm) b) 2" i/d (50 mm) c) 2½" i/d (65 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 6" i/d (150 mm) g) 8" i/d (200 mm)	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	15.60 14.75 16.75 16.80 19.10 21.35 21.45	197.05 267.25 341.80 426.55 608.80 833.30 969.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	51.25 48.40 54.90 55.10 62.65 70.00 70.40	646.35 876.60 1121.15 1399.10 1996.80 2733.20 3179.90		
37	Providing and installing P.V.C. bends, of B.S.S.			* >					
	 i) Class `B' working pressure:- a) 3" i/d (75 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- a) 1¹/₄" i/d (30 mm) b) 1¹/₂" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm) 	Each Each Each Each Each Each Each Each	75.80 88.25 110.30 114.30 48.55 52.75 57.55 75.80 88.25 110.30 114.30	199.40 352.25 626.30 876.30 80.95 87.55 127.15 260.60 522.65 1106.30 1518.30	Each Each Each Each Each Each Each Each	75.80 88.25 110.30 114.30 48.55 52.75 57.55 75.80 88.25 110.30 114.30	199.40 352.25 626.30 876.30 80.95 87.55 127.15 260.60 522.65 1106.30 1518.30		
38	Providing and installing P.V.C. tees, of B.S.S.								
	 i) Class `B' working pressure:- a) 3" i/d (80 mm) b) 4" i/d (100 mm) c) 5" i/d (125 mm) d) 6" i/d (150 mm) ii) Class `D' working pressure:- a) 1¼" i/d (30 mm) 	Each Each Each Each Each	113.70 134.25 162.75 171.50 74.30	569.70 1058.25 2022.75 2091.50 200.30	Each Each Each Each Each	113.70 134.25 162.75 171.50 74.30	569.70 1058.25 2022.75 2091.50 200.30		
	b) 1½" i/d (40 mm) c) 2" i/d (50 mm) d) 3" i/d (75 mm) e) 4" i/d (100 mm) f) 5" i/d (125 mm) g) 6" i/d (150 mm)	Each Each Each Each Each Each	79.40 85.85 113.70 134.25 162.75 171.50	234.20 289.85 563.70 1058.25 2010.75 2079.50	Each Each Each Each Each Each	79.40 85.85 113.70 134.25 162.75 171.50	234.20 289.85 563.70 1058.25 2010.75 2079.50		

	MRS, BI-ANNUAL PE	ERIOD (1	st AUGUST,	2012 TO 31st	JANUAR	Y, 2013) D	DISTRICT JHA	NG	
Sr.	Description		Rate (British Sy	ystem)	Ra	te (Metric S	ystem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
39	Providing and installing P.V.C. sockets, B.S.S.								
	i) Class `B' working pressure:-								
	a) 3" i/d (75 mm) b) 4" i/d (100 mm)	Each Each	55.70 68.15	137.30 212.15	Each Each	55.70 68.15	137.30 212.15		
	c) 5" i/d (125 mm)	Each	85.15	283.15	Each	85.15	283.15		
	d) 6" i/d (150 mm)	Each	89.15	365.15	Each	89.15	365.15		
	e) 8" i/d (200 mm)	Each	129.55	765.55	Each	129.55	765.55		
	f) 10" i/d (250 mm)	Each	153.55	1881.55	Each	153.55	1881.55		
	g) 12" i/d (300 mm)	Each	177.40	4137.40	Each	177.40	4137.40		
	h) 14" i/d (350 mm)	Each	200.25	3320.25	Each	200.25	3320.25		
	ii) Class `D' working pressure:-			×					
	a) 1¼" i/d (30 mm)	Each	31.75	53.35	Each	31.75	53.35		
	b) $1\frac{1}{2}$ " i/d (40 mm)	Each	35.95	65.95 88.75	Each Each	35.95	65.95 88.75		
	c) 2" i/d (50 mm) d) 3" i/d (75 mm)	Each Each	40.75 55.70	208.10	Each	40.75 55.70	208.10		
	e) 4" i/d (100 mm)	Each	68.15	350.15	Each	68.15	350.15		
	f) 5" i/d (125 mm)	Each	85.15	601.15	Each	85.15	601.15		
	g) 6" i/d (150 mm)	Each	89.15	1001.15	Each	89.15	1001.15		
		10	11	8 18/	119				
40	Providing and installing P.V.C. Tapered core, B.S.S.	1	3		in the				
	i) Class `B' working pressure:-		res V	X.C.	Sar				
	a) 3" i/d (75 mm)	Each	75.80	115.40	Each	75.80	115.40		
	b) 4" i/d (100 mm)	Each	88.25	141.05	Each	88.25	141.05		
	c) 5" i/d (125 mm)	Each	110.30	176.30	Each	110.30	176.30		
	d) 6" i/d (150 mm)	Each	114.30	193.50	Each	114.30	193.50		
	e) 8" i/d (200 mm)	Each	163.10	295.10	Each	163.10	295.10		
	f) 10" i/d (250 mm) g) 12" i/d (300 mm)	Each Each	187.10 217.65	358.70 428.85	Each Each	187.10 217.65	358.70 428.85		
	h) 14" i/d (350 mm)	Each	240.50	504.50	Each	240.50	504.50		
	ii) Class `D' working pressure:-								
	a) 1 ¹ / ₄ " i/d (30 mm)	Each	48.55	67.75	Each	48.55	67.75		
	b) 1 ¹ / ₂ " i/d (40 mm)	Each	48.33	79.15	Each	48.33	79.15		
	c) 2" i/d (50 mm)	Each	57.55	89.95	Each	57.55	89.95		
41	Making connection for new watersupply lines with the								The rate includes the component of
	running main, including excavation of trench and refilling,								bailing out water from the trench
	complete, but excluding cost of pipe and specials, etc.								and cutting of existing pipe line.
	Diameter of running main:								
	i) upto $6'' i/d (150 \text{ mm})$	Per	1057.65		Per	1057.65			
	i) upto 6" i/d (150 mm) ii) upto 8" i/d (200 mm)	Connection ditto	1057.65		Connection ditto	1057.65			
	iii) upto 10" i/d (250 mm)	ction	1330.90		ction	1330.90			
	iv) upto 12" i/d (300 mm)	ditto	2570.70		ditto	2570.70			
	v) upto 16" i/d (400 mm)	ditto	3161.55		ditto	3161.55			

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG												
Sr.	Description		Rate (British S	ystem)	Ra	ate (Metric System)		Spec.	Remarks				
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.					
	vi) upto 20" i/d (500 mm) vii) upto 24" i/d (600 mm)	ditto ditto	4083.75 4913.70		ditto ditto	4083.75 4913.70							



Finance Department

24. ELECTRIC INSTALLATION

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PEF	RIOD (1st /	AUGUST,	2012 TO 31	st JANUA	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
1	Supply and erection of G.I. pipes for wiring purposes, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.								
	a) on surface, including clamps, etc.							38.4	
	 i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d vii) 80 mm i/d b) recessed in walls, including hooks, cutting jharries and repairing surface: i) 15 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d vi) 40 mm i/d vi) 50 mm i/d vi) 50 mm i/d vii) 50 mm i/d vii) 80 mm i/d 	Per Rft. Per Rft.	12.80 12.80 12.80 15.60 15.60 18.60 23.65 18.45 18.45 19.20 19.20 20.95 28.80 46.10	58.10 72.50 95.35 121.35 149.55 185.50 291.15 61.55 76.85 100.85 124.10 153.30 194.70 313.35	Per Metre Per Metre	42.00 42.00 51.20 51.20 60.95 77.60 60.45 63.00 63.00 63.00 68.70 94.45 151.15	190.60 237.75 312.85 398.05 490.50 608.45 954.90 201.85 252.05 330.75 407.00 502.85 638.60 1,027.85	38.3	
2	Supply and erection of M.S. conduit pipes for wiring, including pull boxes, inspection boxes, bends, tees, etc. complete with all specials.	TOT INI.	10.10	515.55	Ter Mede	151.15	1,027.05	38.4 & 38.6	
	a) on surface, including clamps, etc.								
	 i) 16 mm i/d ii) 20 mm i/d iii) 25 mm i/d iv) 32 mm i/d v) 40 mm i/d vi) 50 mm i/d b) recessed in walls, including cutting jharries, cost of hooks and repairing surface etc. 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	8.90 8.90 8.90 10.00 12.30	29.35 34.60 39.80 44.25 56.35 68.85	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	29.15 29.15 29.15 29.15 32.80 40.35	96.30 113.55 130.45 145.10 184.80 225.80	38.3 & 38.7	
	i) 16 mm i/d	Per Rft.	16.45	37.95	Per Metre	54.00	124.40	30.7	

	MRS, BI-ANNUAL PERI		2012 10 31	SUJANUA	11,2013)	DISTRICT	MANG	1	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 20 mm i/d	Per Rft.	16.45	42.65	Per Metre	54.00	139.90		
1	iii) 25 mm i/d	Per Rft.	18.45	49.00	Per Metre	60.45	160.75		
l	iv) 32 mm i/d	Per Rft.	19.20	54.50	Per Metre	63.00	178.70		
l	v) 40 mm i/d	Per Rft.	20.05	65.25	Per Metre	65.70	214.05		
	vi) 50 mm i/d	Per Rft.	20.95	77.90	Per Metre	68.70	255.60		
	Supply and erection of PVC pipe for wiring recessed in walls,							38.3 &	
1	including inspection boxes, pull boxes, hooks, cutting jharries,							38.5	
	and repairing surface, etc., complete with all specials.								
	i) 12 mm i/d	Per Rft.	14.85	25.20	Per Metre	48.75	82.60		
1	ii) 20 mm i/d	Per Rft.	15.35	29.30	Per Metre	50.40	96.05		
1	iii) 25 mm i/d	Per Rft.	17.05	35.05	Per Metre	56.00	114.90		
1	iv) 32 mm i/d	Per Rft.	18.45	42.90	Per Metre	60.45	140.75		
1	v) 40 mm i/d	Per Rft.	19.20	52.90	Per Metre	63.00	173.55		
l	vi) 50 mm i/d	Per Rft.	20.05	63.95	Per Metre	65.70	209.80		
1		1.121			I & .				
	Supply and erection of PVC pipe for wiring on surface	133			1 122				
1	including clamps inspection boxes, pull boxes, bends, tees,	1617	1-6	2-29/	159				
1	repairing surface, etc., complete with all specials:-	100			100				
l	i) 12 mm i/d	Per Rft.	4.00	15.05	Per Metre	13.10	49.45		
1	i) 20 mm i/d	Per Rft.	4.00	18.60	Per Metre	13.10	61.10		
1	iii) 25 mm i/d	Per Rft.	4.00	23.90	Per Metre	13.10	78.35		
1	iv) 32 mm i/d	Per Rft.	4.55	32.15	Per Metre	15.00	105.50		
1	v) 40 mm i/d	Per Rft.	4.55	42.75	Per Metre	15.00	140.25		
	vi) 50 mm i/d	Per Rft.	5.50	57.55	Per Metre	18.10	188.80		
5	Supply and erection of G.I. flexible pipe for wiring, including							38.4	
5	welding of sockets, nipples and check nuts, etc. complete:-							50.4	
1	weitung of societas, impress and encort hats, etc. compreter								
l	i) 12 mm i/d	Per Rft.	10.55	54.45	Per Metre	34.50	178.50		
l	ii) 20 mm i/d	Per Rft.	11.25	70.50	Per Metre	36.80	231.20		
l	iii) 25 mm i/d	Per Rft.	11.60	94.65	Per Metre	38.10	310.50		
l	iv) 32 mm i/d	Per Rft.	14.05	115.75	Per Metre	46.05	379.65		
l	v) 40 mm i/d	Per Rft.	15.30	130.90	Per Metre	50.20	429.40		
l	vi) 50 mm i/d	Per Rft.	16.85	170.85	Per Metre	55.25	560.45		
	vii) 80 mm i/d	Per Rft.	22.45	331.05	Per Metre	73.65	1,085.85		
6	Supply and erection PVC pipe for recessed wiring (main and							38.2 &	
	sub-main) purpose, including bends, specials, etc. in floor,							38.3	
	wall or trenches:-								
	i) 50 mm i/d	Per Rft.	20.05	65.60	Per Metre	65.70	215.15		
l	i) 50 mm i/d ii) 80 mm i/d	Per Rit. Per Rft.	20.05	65.60 85.60	Per Metre Per Metre	75.55	215.15 280.80		
l	iii) 100 mm i/d	Per Rft.	23.05	83.00 110.70	Per Metre	75.55	363.15		
l	m, 100 mm //d	i ci Kit.	25.05	110.70	i ci mene	15.55	505.15		

	MRS, BI-ANNUAL PER	IOD (1st /	AUGUST,	2012 TO 31	st JANUAI	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
7	Supply and erection of PVC pipe for surface wiring (main and sub-main) including clamps, inspection boxes, pull boxes bends etc., complete with all specials:-								
	i) 50 mm i/d ii) 80 mm i/d iii) 100 mm i/d	Per Rft. Per Rft. Per Rft.	5.50 8.00 9.15	52.45 87.00 109.75	Per Metre Per Metre Per Metre	18.10 26.25 30.00	172.10 285.40 360.00		
8	Supply and erection of wooden strip batten for wiring purposes, including clips, insulation cleats, etc.	Per Rft.	1.60	3.80	Per Metre	5.25	12.55	38.8	Additional width required to accommodate wires will be provided by erection of additional strips.
9	Supply and erection of Sahl wood casing and capping for wiring purposes, including insulation cleats, screws, etc. complete.	Per Rft.	1.60	12.80	Per Metre	5.25	42.05	38.8	
10	Supply and erection of single core PVC insulated copper conductor cables, in prelaid PVC pipe/M.S. conduit/G.I pipe/wooden strip batten/wooden casing an capping/G.I. wire/trenches (rate for cables only):-	and the second						38.1	
	 a) 250/440 volts, PVC insulated: i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") vii) 19/1.32 mm (19/0.052") viii) 19/1.63 mm (19/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.20 3.20 3.55 4.00 4.90 11.15 13.00	9.45 9.85 13.60 20.15 28.95 70.55 113.60 155.80	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	$\begin{array}{c} 10.50\\ 10.50\\ 10.50\\ 11.65\\ 13.10\\ 16.15\\ 36.60\\ 42.70\\ \end{array}$	30.95 32.30 44.55 66.15 94.90 231.45 372.60 510.95		
	 b) 250/440 volts, PVC insulated cotton braided and compounded cables:- 								
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.55 3.55 3.55 3.75 4.20 4.85	9.80 10.20 13.95 20.40 29.15 70.50	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	11.65 11.65 11.65 12.35 13.80 15.90	32.10 33.45 45.75 66.85 95.55 231.20		
11	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 250/440 volts grade cable (BSS-2004), in prelaid PVC pipes/M.S. conduit/G.I. pipe/wooden strip batten/wooden casing and capping/trenches, etc. (rate for cable only):-								

	MRS, BI-ANNUAL PE	RIOD (1st A	AUGUST,	2012 TO 31	st JANUA	RY, 2013)	DISTRICT .	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.20 3.20 3.20 3.55 4.00 4.90	9.00 11.90 16.10 23.10 32.65 64.35	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	10.50 10.50 11.65 13.10 16.15	29.55 39.10 52.75 75.70 107.15 211.00		
12	Supply and erection of single core PVC insulated, PVC sheathed copper conductor, 660/1100 volts grade cable, in prelaid G.I. pipe/M.S. conduits/PVC pipe/G.I. wire/trenches, etc (rate for cable only):-			*				38.1 to 38.7	
	 i) 7/1.63 mm (7/0.064") ii) 19/1.32 mm (19/0.052") iii) 19/1.63 mm (19/0.064") iv) 19/2.11 mm (19/0.083") v) 37//1.83 mm (37/0.072") vi) 37/2.11 mm (37/0.083") vii) 37/2.62 mm (37/0.103") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	4.85 5.35 5.80 6.40 11.05 13.35 18.80	72.75 122.60 165.85 317.00 440.15 552.30 847.40	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	15.90 17.50 19.10 21.00 36.20 43.75 61.75	$\begin{array}{c} 238.55\\ 402.10\\ 544.00\\ 1,039.85\\ 1,443.65\\ 1,811.50\\ 2,779.55\end{array}$		
13	Supply and erection of copper conductor cables for service connection, in prelaid pipe/G.I. wire/trenches, etc. (rate for cable only):- a) PVC insulated, PVC sheathed twin core, 250/440 volts.	Ήn	ance	XX Depa	s tmeni	12 17 17		ditto	
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.55 3.55 3.55 3.75 4.20 4.85	16.45 23.10 31.40 45.75 64.85 129.10	Per Metre Per Metre Per Metre Per Metre Per Metre Per Metre	11.65 11.65 11.65 12.35 13.80 15.90	53.90 75.70 102.95 150.00 212.75 423.45		
	 b) PVC insulated, PVC sheathed 3 core, 660/1100 volt cable:- 								
	 i) 3/0.74 mm (3/0.029") ii) 3/0.91 mm (3/0.036") iii) 7/0.74 mm (7/0.029") iv) 7/0.91 mm (7/0.036") v) 7/1.12 mm (7/0.044") vi) 7/1.63 mm (7/0.064") 	Per Rft. Per Rft. Per Rft. Per Rft. Per Rft. Per Rft.	3.75 3.75 3.75 4.20 4.45 5.10	24.55 34.90 47.40 69.20 98.65 199.70		12.35 12.35 12.35 13.80 14.60 16.65	80.50 114.55 155.45 227.00 323.60 654.95		
	 c) PVC insulated, PVC sheathed 4 core, 660/1100 volt non armoured cable:- 								
	i) 3/0.74 mm (3/0.029")	Per Rft.	4.00	31.40	Per Metre	13.10	103.05		

	MRS, BI-ANNUAL PER	st JANUA	RY, 2013)	DISTRICT	JHANG				
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	vstem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 3/0.91 mm (3/0.036")	Per Rft.	4.00	43.90	Per Metre	13.10	143.95		
	iii) 7/0.74 mm (7/0.029")	Per Rft.	4.20	60.15	Per Metre	13.80	197.35		
	iv) 7/0.91 mm (7/0.036")	Per Rft.	4.20	88.95	Per Metre	13.80	291.80		
	v) 7/1.12 mm (7/0.044")	Per Rft.	4.45	127.85	Per Metre	14.60	419.40		
	vi) 7/1.63 mm (7/0.064")	Per Rft.	5.10	260.15	Per Metre	16.65	853.30		
	vii) 19/1.32 mm (19/0.052")	Per Rft.	7.10	485.60	Per Metre	23.30	1,592.75		
	 PVC insulated, PVC sheathed 4 core 660/1100 volt grade cable, armoured with G.I. wire 16 SWG. 								Cost of trenches where necessary is included in the rates.
	i) 19/1.32 mm (19/0.052")	Per Rft.	7.10	541.55	Per Metre	23.30	1,776.25		
	ii) 19/1.63 mm (19/0.064")	Per Rft.	7.60	723.90	Per Metre	25.00	2,374.40		
	iii) 19/1.83 mm (19/0.072")	Per Rft.	8.00	980.60	Per Metre	26.25	3,216.35		
	iv) 19/2.11 mm (19/0.083")	Per Rft.	8.65	1,372.50	Per Metre	28.35	4,501.80		
	v) 37//1.83 mm (37/0.072")	Per Rft.	8.90	1,869.75	Per Metre	29.15	6,132.75		
	vi) 37/2.11 mm (37/0.083")	Per Rft.	10.65	2,363.60	Per Metre	35.00	7,752.55		
	vii) 37/2.36 mm (37/0.093")	Per Rft.	12.80	2,880.80	Per Metre	42.00	9,449.05		
	viii) 37/2.62 mm (37/0.103")	Per Rft.	16.00	3,585.50	Per Metre	52.45	11,760.40		
14	Supply and erection of M.S. sheet box of 16 SWG, 10 cm (4")	1839	1	6 /	7 /1839			38.1	
	deep, with 4.75 mm thick (3/16") bakelite sheet top, for	Neg.	1	1000	Contra Co			to	
	recessed wiring, including making holes for regulators,	200	220	and la	South			38.7	
	switches, plugs, etc.			10-2					
	i) 10 x 10 cm (4"x4")	Each	52.45	118.20	Each	52.45	118.20		
	ii) 17.5 x 10 cm (7"x4")	Each	65.60	158.05	Each	65.60	158.05		
	iii) 22.5 x 10 cm (9"x4")	Each	87.45	200.90	Each	87.45	200.90		
	iv) 20 x 25 cm (8"x10")	Each	104.95	299.20	Each	104.95	299.20		
	v) 25 x 30 cm (10"x12")	Each	131.20	397.20	Each	131.20	397.20		
	vi) 30 x 35 cm (12"x14")	Each	174.90	515.80	Each	174.90	515.80		
15	Supply and erection of round block of Sahl wood, 10x4 cm (4"x11/2") thick.	Each	15.00	27.80	Each	15.00	27.80	38.1	
16	Supply and erection of teak wood board, 4.5 cm (1¾") thick.							38.1	
l	i) 17.5 x 10 cm (7"x4")	Each	21.00	76.40	Each	21.00	76.40		
	i) $22.5 \times 10 \text{ cm} (9"x4")$	Each	21.00	88.40	Each	21.00	88.40		
	iii) 20 x 25 cm (8"x10")	Each	23.30	103.90	Each	23.30	103.90		
	iv) 25 x 30 cm (10"x12")	Each	26.25	143.05	Each	26.25	143.05		
	v) 30 x 35 cm (12"x14")	Each	30.00	196.00	Each	30.00	196.00		
17	Supply and erection of Sahl wood board, 4.5 cm (1 ³ / ₄ ") thick.								
	i) 17.5 x 10 cm (7"x4")	Each	21.00	56.60	Each	21.00	56.60		
	i) $22.5 \times 10 \text{ cm} (9"x4")$	Each	21.00	74.60	Each	21.00	74.60		
	iii) 20 x 25 cm (8"x10")	Each	23.30	88.30	Each	23.30	88.30		
	iv) 25 x 30 cm (10"x12")	Each	26.25	106.85	Each	26.25	106.85		

	MRS, BI-ANNUAL PERIO	DD (1st A	AUGUST,	2012 TO 31	st JANUA	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	v) 30 x 35 cm (12"x14")	Each	30.00	126.80	Each	30.00	126.80		
18	Supply and erection of iron/aluminum clad, 500 volts main switches with kitkat fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles, etc. a) double pole:							38.1	When the base frame is already installed, the labour and composite rates will be reduced as follows:- For 15 to 35 Amps. by Rs. 21.20 and Rs. 145.50. For 60 to 65 Amps. by Rs. 38.80 and Rs. 252.60. For 100 Amps. by Rs. 38.80 and Rs. 350.80.
	i) 15/20 Amp.	Each	349.80	1,369.25	Each	349.80	1,369.25		by KS. 58.60 and KS. 550.80.
	ii) 30/35 Amp.	Each	349.80	1,651.25	Each	349.80	1,651.25		
	iii) 60/65 Amp.	Each	524.70	2,136.35	Each	524.70	2,136.35		
	iv) 100 Amp.	Each	524.70	2,676.35	Each	524.70	2,676.35		
	b) triple pole:	. h			-li-				
	i) 15/20 Amp.	Each	524.70	1,862.15	Each	524.70	1,862.15		
	ii) 30/35 Amp.	Each	349.80	2,107.25	Each	349.80	2,107.25		
	· · · · · ·	85.			1 112				
	c) triple pole with neutral link:	67	-0	رصومت ت					
	i) 30/35 Amp.	Each	349.80	2,275.25	Each	349.80	2,275.25		
	ii) 60/65 Amp.	Each	524.70	2,857.00	Each	524.70	2,857.00		
	iii) 100 Amp.	Each	667.90	3,498.25	Each	667.90	3,498.25		
19	Supply and erection of iron/aluminum clad, 500 volts main switches with triple pole and neutral link and HRC fuses, on angle iron board with 3 mm (1/8") thick M.S. sheet covering, including bonding to earth with necessary flexible pipe and thimbles.	Fan	ian ce	Depe	timeni			38.1	When the base frame is already installed, the labour & composite rates will be reduced as follows:- i) For 60/65 Amp. by Rs. 21.20 and
									Rs. 145.50.
	60/65 Amp	Each	524.70	2,906.10	Each	524.70	2,906.10		ii) For 100 to 300 Amp. by Rs. 21.20
	100 Amp	Each	667.90	4,057.35	Each	667.90	4,057.35		and Rs. 350.80
	150 Amp 200 Amp	Each Each	667.90 1,511.40	5,576.50 8,904.00	Each Each	667.90 1,511.40	5,576.50 8,904.00		iii) For 400 to 500 Amp. by Rs. 42.20 and Rs. 526.20
	300 Amp	Each	1,511.40	10,272.00	Each	1,511.40	10,272.00		and KS. 520.20
	400 Amp	Each	2,120.25	13,797.45	Each	2,120.25	13,797.45		
	500 Amp	Each	2,267.10	17,617.05	Each	2,267.10	17,617.05		
20	Supply and erection of iron/aluminum clad, branch distribution board, 250 volt, on angle iron frame of suitable size with 3 mm (1/8") M.S. sheet covering:							ditto	When the base frame is already installed the labour and composite rates will be reduced by Rs. 19.50 & Rs. 152.20 respectively.
	i) 2 way, 15 Amp per way	Each	174.90	570.30	Each	174.90	570.30		
	ii) 3 way, 15 Amp per way	Each	174.90	570.30	Each	174.90	570.30		
	iii) 4 way, 15 Amp per wayiv) 5 way, 15 Amp per way	Each	174.90 174.90	642.30 702.30	Each	174.90 174.90	642.30 702.30		
	iv) 5 way, 15 Amp per wayv) 6 way, 15 Amp per way	Each Each	174.90	702.30	Each Each	174.90 174.90	702.30		

	MRS, BI-ANNUAL PERI	OD (1st /	AUGUST,	2012 TO 31	st JANUA	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.	-	Unit	Labour	Composite	Unit	Labour	Composite	No.	
	 vi) 7 way, 15 Amp per way vii) 8 way, 15 Amp per way viii) 9 way, 15 Amp per way ix) 10 way, 15 Amp per way ix) 10 way, 15 Amp per way xi) 12 way, 15 Amp per way xii) 12 way, 15 Amp per way xii) 2 way, 30 Amp per way xiii) 3 way, 30 Amp per way xiv) 4 way, 30 Amp per way xvi) 5 way, 30 Amp per way xvi) 6 way, 30 Amp per way xvii) 7 way, 30 Amp per way xviii 8 way, 30 Amp per way xviii 8 way, 30 Amp per way viii 8 way, 30 Amp per way viii 9 way, 30 Amp per way 	Each Each Each Each Each Each Each Each	174.90 174.90 174.90 174.90 174.90 174.90 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35	798.30 846.30 900.30 978.30 1,038.30 1,092.30 657.75 663.75 723.75 789.75 831.75 897.75 951.75 999.75	Each Each Each Each Each Each Each Each	174.90 174.90 174.90 174.90 174.90 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35 262.35	798.30 846.30 900.30 978.30 1,038.30 1,092.30 657.75 663.75 723.75 789.75 831.75 897.75 897.75 951.75 999.75		
21	 xx) 10 way, 30 Amp per way Supply and erection of bus bars, for 500 volts 3 phase A.C. supply with four copper bars, including glazed porcelain bridges, on angle iron board, fixed with rag bolts and M.S. sheet box 1.5 mm thick, etc. complete:- i) 60 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm) ii) 100 Amp. with 4 copper bars size 1½"x1/8" (40 x 3 mm) iii) 200 Amp with 4 copper bars size 2"x1/8" (50x 3 mm) iv) 300 Amp with 4 copper bars size 2"x3/16" (50x 5 mm) v) 500 Amp with 4 copper 	Each Each Each Each Each Each	262.35 668.25 668.25 1,042.80 1,196.25 815.10	1,083.75 2,706.85 2,706.85 3,177.40 3,330.85 3,537.25	Each Each Each Each Each Each	262.35 668.25 668.25 1,042.80 1,196.25 815.10	1,083.75 2,706.85 2,706.85 3,177.40 3,330.85 3,537.25	38.1	When the base frame is already installed the labour and composite rates will be reduced by Rs. 21.20 and Rs. 145.50 respectively.
22	 size 2"x1/4" (50x 6 mm) i) Supply and erection of plain pendent lamp holder, complete with bakelite lamp holder and flexible twin wire 23/0.0076" upto 2 metre length (without bulb and shade). 	Each	12.25	101.70	Each	12.25	101.70	38.1	
	Extra for additional length of flexible wire, beyond2 metres.	Per Rft.		1.65	Per Metre		5.45		
23	Supply and erection of counter weight pedent with porcelain counter weight, and fitting on bakelite lamp holder, with flexible twin wire 23/0.0076" complete (without bulb and shade).	Each	24.50	227.65	Each	24.50	227.65	38.1	
24	Supply and erection of stiff pedent with brass/metal pipe 6.3 cm (2.5") long, and 15 mm (¹ / ₂ ") dia brass oxidised or painted, along with brass lamp holder with VIR/PVC cable 3/0.74 mm	Each	34.75	375.55	Each	34.75	375.55	ditto	

	MRS, BI-ANNUAL PERIC	DISTRICT	JHANG						
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(3/0.029").								
25	Supply and erection of 22.5 cm (9") long swan neck plain brass/steel brass oxidised bracket lamp holder, complete.	Each	35.95	98.95	Each	35.95	98.95	ditto	
26	Supply and erection of wall type/pole type bracket, with double cover water tight reflector, flexible wire and brass bolder.	Each	49.65	402.00	Each	49.65	402.00	ditto	
27	Supply and erection of bakelite button holder shade, large size.	Each	8.15	44.80	Each	8.15	44.80	ditto	
28	Supply and erection of call bell 220/250 volts, fixed on teak wood board 17.5x10 cm (7"x4").	Each	34.75	213.15	Each	34.75	213.15	38.1	
29	Supply and erection of bell push or bed switch, with 5 metres twin flexible wire 23/0.0076".	Each	7.35	203.95	Each	7.35	203.95	38.1	
30	Supply and erection of ceiling rose, bakelite.	Each	12.25	31.60	Each	12.25	31.60	ditto	
31	Supply and erection of switches 5 Amp.		100	الطومت ;					
	 i) open type ii) piano type iii) ring type, recessed iv) plate type, recessed v) double control, open type vi) double control, ring type recessed vii) double control, piano type 	Each Each Each Each Each Each Each	11.75 11.75 11.75 11.75 15.95 15.95 15.95	28.70 28.70 23.75 45.50 44.15 38.15 39.35	Each Each Each Each Each Each Each	11.75 11.75 11.75 11.75 15.95 15.95 15.95	28.70 28.70 23.75 45.50 44.15 38.15 39.35	ditto	
32	Supply and erection of switches 10/15 Amp.							ditto	
	i) open typeii) recessed type	Each Each	11.75 11.75	37.55 47.15	Each Each	11.75 11.75	37.55 47.15		
33	Supply and erection of wall socket with 3 pin 5 Amp, shoe.	Each	11.75	73.55	Each	11.75	73.55	ditto	
34	Supply and erection of 3 pin. 5 Amp wall socket.	Each	11.75	49.55	Each	11.75	49.55	ditto	
35	Supply and erection of 3 pin, 10/15 Amp. wall socket.							ditto	
	i) open typeii) recessed type	Each Each	11.75 11.75	43.55 79.55	Each Each	11.75 11.75	43.55 79.55		
36	Supply and erection of 3 pin switch and plug combined, recessed type.							ditto	
	i) 5 Amp	Each	11.75	63.35	Each	11.75	63.35		

	MRS, BI-ANNUAL PERIC	DISTRICT	JHANG						
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 10/15 Amp	Each	11.75	88.25	Each	11.75	88.25		
37	Supply and erection of 3 pin 10/15 Amp. wall socket with shoe, open type.	Each	11.75	139.55	Each	11.75	139.55	ditto	
38	Supply and erection of cut out, bakelite.							ditto	
	i) open typeii) recessed type	Each Each	6.55 6.55	32.35 38.35	Each Each	6.55 6.55	32.35 38.35		
39	Supply and erection of button holder.		/					38.1	
	i) bakelite large sizeii) brass	Each Each	7.35 7.35	25.95 37.95	Each Each	7.35 7.35	25.95 37.95		
40	Supply and erection of brass bracket with holder.	Each	9.80	40.40	Each	9.80	40.40	ditto	
41	Supply and erection of bell push open/recessed type (without flexible wire).	Each	6.55	26.35	Each	6.55	26.35	ditto	
42	Supply and erection of kitkat, 500 volt:				153			ditto	
	i) 15/20 Amp	Each	11.70	43.20	Each	11.70	43.20		
	ii) 30/35 Amp iii) 60/65 Amp	Each Each	12.75 19.50	44.25 64.50	Each Each	12.75 19.50	44.25 64.50		
	iv) 100 Amp	Each	21.90	108.90	Each	21.90	108.90		
	v) 200 Amp	Each	25.05	148.05	Each	25.05	148.05		
	vi) 300 Amp	Each	25.05	304.05	Each	25.05	304.05		
	vii) 400 Amp	Each	32.60	377.60	Each	32.60	377.60		
	viii) 500 Amp	Each	32.60	548.60	Each	32.60	548.60		
43	Supply and erection of tube light, including rod, choke, starter with frame, flexible wire, including connection from ceiling rose, etc., complete.							38.1	
	i) double rod (80 watts) with two chokes and 2 starters.	Per set	203.80	1,134.05	Per set	203.80	1,134.05		
	ii) single rod (40 watts) with one choke and one starter.	ditto	163.00	589.30	ditto	163.00	589.30		
	iii) round tube, 32 watt, with one choke and one starter, without cover.	Each	163.00	645.70	Each	163.00	645.70		
	iv) round tube, 32 watt with one chock and one starter, with cover.	ditto	135.85	738.55	ditto	135.85	738.55		
44	Providing and fixing M.S. iron box for housing main switches, made of 1.5 mm (1/16") thick M.S. sheet, with locking							ditto	

	MRS, BI-ANNUAL PERI	DISTRICT	JHANG						
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	arrangement, including painting:-								
	i) 60x35x15 cm (24"x14"x6")	Each	425.90	2,433.80	Each	425.90	2,433.80		
	ii) 95x40x20 cm (38"x16"x8")	Each	616.85	3,048.85	Each	616.85	3,048.85		
	iii) 105x52.5x22.5 cm (42"x21"x9")	Each	938.45	4,204.85	Each	938.45	4,204.85		
	iv) 135x70x27.5 cm (54"x28"x11")	Each	1,035.40	6,198.65	Each	1,035.40	6,198.65		
45	Supply and erection of girder clamp hook, 16 mm (5/8") with M.S. plate 25x6 mm (1"x ¹ /4"), with bolts and nuts for hanging	Each	27.15	138.75	Each	27.15	138.75	38.1 &	
	ceiling fans.							38.10	
46	Supply and erection of girder strut, of M.S. tee section 40x40x6 mm (1 ¹ / ₂ "1 ¹ / ₂ "x ¹ / ₄ "), complete with clamp, bolts and nuts, etc., including fixing with cement concrete 1:3:6.	Each	34.75	838.50	Each	34.75	838.50	ditto	
		. /							
47	Supply and erection of roof suspension hook, 16 mm (5/8") dia rod with 75x40x3 mm (3"x1½"x1/8") M.S. steel channel,	Each	37.25	1,178.75	Each	37.25	1,178.75	38.1	
	with clamp, bolts and nuts, etc., including fixing with cement	1887			-1 82				
	concrete 1:3:6.	223			7 24				
48	Supply and erection of roof suspension hook of M.S plate	Each	49.65	475.55	Each	49.65	475.55		
40	75x40x12.7mm ($3^{1}x1\frac{1}{2}^{1}x\frac{1}{2}^{1}$) with 16 mm ($5/8^{1}$) hook complete with bolts, nuts and fixing with cement concrete 1:3:6	Lach	49.05	475.55	Each	49.05	475.55		
49	Supply and erection of 3/8" (10 mm) dia M.S. bar fan hook, placed at the time of casting of slab.	Each	15.05	31.85	Each	15.05	31.85	ditto	
50	Erection of circular L.T. pole in cement concrete 1:3:6 one metre below ground level (excluding the cost of pole), including cement concrete collar (1:2:4) excavation of foundation, and finishing surface.	Each	428.50	2,210.55	Each	428.50	2,210.55	38.12	
51	Supply and erection of bracket of M.S. channel 75x40x6 mm (3"x1½"x14") section:-								
	i) 0.60 metre (2') long for 2 lines.	Each	104.90	538.55	Each	104.90	538.55		
	ii) 1.200 metre (4') long for 4 lines.	Each	122.40	1,112.60	Each	122.40	1,112.60		
52	Supply and erection of anchor rod Henley type for pole, including necessary clamps and 7/12" stay wire, straining	Per Rft.	6.55	19.60	Per Metre	21.40	64.25	38.14	
	screws, etc., erected in cement concrete 1:3:6 and collar of cement concrete.								
53	Supply and erection of stay for house service pipe, erected with straining screws and 7/14" stay wire, complete.	Per Rft.	9.15	30.35	Per Metre	30.00	99.55	ditto	
54	Supply and erection of house service pipe Henley (G.I. pipe water quality) or pole type, 50 mm (2") dia, erected to instal insulated overhead line, include shackle insulator for holding	Per Rft.	38.40	237.70	Per Metre	125.95	779.60		

	MRS, BI-ANNUAL PERIO	DISTRICT	JHANG						
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	insulated wire and straining devices for bearer wire and other								
	accessories etc., complete.								
55	Supply and erection of house service pipe 50 mm (2") dia G.I. pipe Henley or pole type for bare copper wire overhead line, including shackle insulator, straining devices and other accessories etc.	Per Rft.	38.05	235.90	Per Metre	124.85	773.80		
56	Supply and erection of lightning arrestor horn type, complete.	Each	208.55	2,368.55	Each	208.55	2,368.55		
57	Supply and erection of shackle insulator, medium size.	Each	27.70	189.70	Each	27.70	189.70	38.12	
58	Supply and erection of pin insulator, green medium size.	Each	27.70	75.70	Each	27.70	75.70	ditto	
59	Supply and erection of bare copper conductor wire No. 2 to No. 10 SWG, including binding wire No. 16 SWG.	Per Kg	14.40	1,038.00	Per Kg	14.40	1,038.00	38.1	
60	Supply and erection of G.I. wire of all sizes, including binding wire No. 16 SWG for support of rubber wire or earthing wire, pole to pole etc.	Per Kg	14.40	102.00	Per Kg	14.40	102.00	ditto	
61	Wiring overhead line in 2 single core, PVC/weather proof cable, on G.I. wire No. 8 SWG bearer wire and in house service pipe, including connection through joint box.	10			152			38.12	
	i) 3/0.74 mm (3/0.029")	Per Rft.	3.55	11.00	Per Metre	11.60	36.15		
	ii) 7/0.74 mm (7/0.029")	ditto	3.55	19.15	ditto	11.60	62.80		
	iii) 7/0.91 mm (7/0.036")	ditto	3.55	25.60	ditto	11.60	83.95		
	iv) 7/1.12 mm (7/0.044")	ditto	3.55	34.45	ditto	11.60	113.05		
62	Supply and erection of all aluminum stranded hard drawn bare conductor, of size 7/3.099 mm (7/0.122").	Per Rft.	6.90	19.80	Per Metre	22.60	64.95	38.1	
63	Supply and erection of street light pole bracket 30 mm (1¼") G.I. pipe 2 metre long, complete with 2 No. pole clamp.	Each	173.80	913.70	Each	173.80	913.70		
64	Supply and erection of pole mounted street light, holders, shade and glass, etc., for fitting 125/250 watts mercury vapour lamp (excluding cost of lamps):								
	i) G.E.C. design	Each	347.60	2,699.60	Each	347.60	2,699.60		
	ii) Philips design	ditto	347.60	3,071.60	ditto	347.60	3,071.60		
65	Supply and fitting of mercury vapour lamp, complete with choke set. i) 125 watt lamp	Each	135.85	1,035.85	Each	135.85	1,035.85		
	ii) 250 watt lamp	ditto	163.00	1,903.00	ditto	163.00	1,903.00		
66	Manufacture and erection of angle iron lattice steel structure	Each	5,940.05	22,141.40	Each	5,940.05	22,141.40	38.13	The composite rate will be reduced

	MRS, BI-ANNUAL PER	IOD (1st /	AUGUST,	2012 TO 31	st JANUA	RY, 2013)	DISTRICT	JHANG	
Sr.	Description	R	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	pole (36.0') 10,923 mm long 9348 mm (30.5') above ground level) 355 mm (14") square at base and 204 mm (8") square at top for electric distribution line, using 1 ¹ /4"x1 ¹ /4"x3/16" (30x30x5 mm) angle iron legs and ³ /4"x ³ /4"1/8" (20x20x3 mm) angle iron bracing 420 mm (17") long fixed between legs on all the four sides in diagonal position, and 1 ³ /4"x1 ³ /4"x3/16" (45x45x5 mm) angle iron on top and 4 bands of M.S. flat iron 2"x ¹ /4" (50x6 mm) 305 mm (12") centre to centre, as per standard drawing including silver painting of pole 3 coats, excavation and refilling of foundation cement concrete 1:2:4. 6'-0"x1'-8"x1'-8" (1807x500x500 mm) for foundation, etc, complete in all respects.								or increased by Rs. 36.50 for each (100 mm) of reduction or addition in the height of the pole above ground level.
67	Manufacture and erection of galvanized angle iron lattice steel structure pole 37 ft. (11.25 m) long 30 ft. (9 m) above ground level), 34" square (850 mm) at base, 13.75" (35 mm) square at top, for electric distribution line, using 2"x2"x5/32" (50x50x4mm) high tensile steel angle iron legs, and 1-3/8"x 1-3/8"x1/8" (35x35x3 mm) M.S. angle iron bracings fixed between legs on all the four sides in diagonal position as per standard drawing including silver painting of pole, excavation and refilling of foundation, one ft. (300 mm) thick cement concrete 1:3:6 foundation of outer size 8'x3½'x3½' (2400x1050x1050 mm), etc. complete in all respects.	Each	5,628.45	33,983.05	Each	5,628.45	33,983.05	38.13	The composite rate will be reduced or increased by Rs. 237.00 for each foot (300 mm) of reduction or addition in the height of the pole above ground level.
68	Earthing of iron clad/aluminum switches, etc. with G.I. wire No. 8 SWG in G.I. pipe 15 mm (½") dia, recessed or on surface of wall and floor, complete with 1.5 metre long G.I. pipe, 50 mm (2") dia with reducing socket 4 to 5 metre below ground level, and 2 metre away from building plinth.	Job	749.10	3,489.10	Job	749.10	3,489.10		
69	Earthing of Metallic cases, etc. with G.I. wire No. 8 SWG, in 15 mm ($\frac{1}{2}$ ") dia G.I. pipe, best quality:-							38.11	
	 i) on surface, including clamps, etc. ii) recessed in wall, including hooks, jharries and making good surface. 	Per Rft. ditto	7.95 18.25	52.05 63.20	Per Metre ditto	26.05 59.95	170.70 207.30		
70	Bonding to earth with wire on surface, including cost of wire, clamps, thimbles, etc.							ditto	
	a) G.I. wire:								
	i) 8 SWG ii) 16 SWG	Per Rft. ditto	3.60 3.60	9.10 5.15		11.75 11.75	29.90 16.85		
	b) Copper wire:								
	i) 16 SWG	Per Rft.	3.60	10.65	Per Metre	11.75	34.85		

	MRS, BI-ANNUAL PERIO	DISTRICT .	JHANG						
Sr.	Description	Ra	ate (British S	System)	Rat	e (Metric Sy	stem)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	ii) 20 SWG	ditto	3.60	6.30	ditto	11.75	20.60		
71	Erection only, of lightning conductor of copper tape, including supply of copper staple and copper nails and cement, sand mortar.	Per Rft.	12.70	17.10	Per Metre	41.70	56.15	38.11	Rate includes all materials required in erection (excluding copper tape lightning conductor).
72	Supply and erection of 600x600x3 mm (2'x2'x1/8") copper plate, including revitting to copper tape and placing in mixture of salt and charcoal, etc.	Each	499.40	4,266.55	Each	499.40	4,266.55	ditto	
73	Supply and erection of copper tape, including copper staple copper nails, cement, sand, etc.								
	 i) tape 40x3 mm (1¹/₂"x1/8") ii) tape 50x3 mm (2"x1/8") 	Per Rft. ditto	18.25 18.25	252.70 301.60	Per Metre ditto	59.95 59.95	828.95 989.25		
74	Supply and erection of 25 mm (1") dia and one metre long lightning conductor copper rod with 5 spikes on ball and base, etc. complete.	Job	347.60	2,615.60	Job	347.60	2,615.60		
75	Supply and erection of electric energy meter, including meter testing fee, etc.	10			153			38.1	
	a) single phase:	(Fin	SANCE	Desphon	timemi	l.			
	 i) 1x10 Amp, 250 volts ii) 1x30 Amp, 250 volts 	Each ditto	146.85 146.85	2,225.25 2,225.25	Each ditto	146.85 146.85	2,225.25 2,225.25		
	b) three phase, 4 wires:								
	 i) 3x15 Amp, 400 volts ii) 3x50 Amp, 400 volts iii) 3x80 Amp, 400 volts 	Each ditto ditto	293.70 407.55 407.55	5,890.50 6,004.35 6,004.35	Each ditto ditto	293.70 407.55 407.55	5,890.50 6,004.35 6,004.35		
76	Rewinding of A.C. ceiling fan, capacitor type, including cost of wire, leatheride paper cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.
	 i) 1200 mm (48") sweep, 275-300 RPM. ii) 1400 mm (56") sweep, 250-275 RPM. 	Each ditto	277.20 305.65	877.20 1,008.25	Each ditto	277.20 305.65	877.20 1,008.25		ulo ruce.
77	Rewinding of A.C. exhaust fan, including cost of wire, leatheride paper, cotton tape, soldering, etc.								The credit of out turn of dismantled material has been accounted for in the rate.
	 i) 375 mm (15") sweep, and 1300-1500 RPM ii) 450 mm (18") sweep, and 1300-1500 RPM 	Each ditto	195.80 195.80	612.20 690.80	Each ditto	195.80 195.80	612.20 690.80		
78	Rewinding of pedestal fan 600 mm (24") sweep, and 900-950 RPM, including wire, leatheride paper, cotton, tape, etc.	Each	234.95	801.95	Each	234.95	801.95		The credit of out turn of dismantled material has been accounted for in

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description	R	ate (British S	System)	Rat	te (Metric Sy	stem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
	Supply and fitting of regulator knob with shaft and plate of electric fan regulator.	Each	36.70	96.70	Each	36.70	96.70	38.1	the rate.			
80	Supply and fitting of capacitor 2.2 uF, for ceiling fans.	Each	29.35	53.35	Each	29.35	53.35	ditto				
	Supply and fitting of ball bearing of size 6201, 6202 or 6203 for ceiling fans.	Each	36.70	156.70	Each	36.70	156.70	ditto				
	Rewinding regulator of ceiling fan 48"/56" (1200/1400 mm) sweep, to control 3/4 speeds.	Each	73.45	183.85	Each	73.45	183.85		The credit out turn of dismantled material has been accounted for in the rate.			
	Erection of ceiling fan alongwith regulator (all sizes), including carriage from local Railway Station/Store to site of work, electric wire/cable for suspension rod and board connection, and cutting, threading on the rod, where necessary.	Each	135.70	172.75	Each	135.70	172.75					
		and the second			7							

Finance Doportment

25. IRON WORK

The Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PE	RIOD (1s	st AUGUST,	2012 TO 31s	t JANUA	RY, 2013) DISTRICT J	HANG	
Sr.	Description		Rate (British Sy	rstem)	R	ate (Metric S	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	Railway Track, etc.								
1	Laying, linking and packing tramway line.	100Lft.	1173.30		Metre	38.50			
2	Dismantling tramway track.	100Lft.	390.90		Metre	12.80			
3	Laying, linking of B.G. track, including packing, straightening and leveling.	100Lft.	3042.60		Metre	99.80			
4	Linking points and crossings, complete with fastenings.	Each	2964.05		Each	2964.05			
5	Bending or strainghtening B.G. rail with Jim Crow.	Each Point	345.20	(عبر مت ;	Each Point	345.20			
6	Fixing street lamp posts.	Each	387.10	× ÷	Each	387.10			
	Binding ends of sleepers and timber of all sizes and kinds, including spreading and restacking.	100 Nos	3728.00	Depart	100 Nos	3728.00			
8	Opening stacks of sleepers and timber of all kinds and sizes, including spreading for inspection and restacking within one chain lead.	100 Nos	455.50		100 Nos	455.50			
	IRON WORK								
	Small iron work, such as gusset plates, knees, bends, stirrups, straps, rings, etc. including cutting, drilling, riveting, handling, assembling and fixing; but excluding erection in position.	Per Cwt	2019.60	7539.25	100 Kg	3975.60	14841.00		
	Fabrication of heavy steel work, with angle, tees, flat iron round iron and sheet iron for making trusses, girders, tanks, etc., including cutting, drilling, revitting, handling, assembling and fixing, but excluding erection in position.	Per Cwt	709.50	5958.45	100 Kg	1396.65	11729.25		
11	Erection and fitting in position iron trusses, staging of water tanks, etc.	Per Cwt	231.75		100 Kg	456.15			
12	Fixing corrugated iron sheet, including revitting, etc.	100 Sft.	834.25		sq.m	89.75			
13	Erecting corrugated iron sheet tanks, upto 20'	Per Cwt	386.05		100 Kg	759.95			

MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description]	Rate (British Sy	stem)	Ra	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
	(6 m) height.										
14	Erecting rolled steel beams or old rails, in roofs, etc., erection and fixing in position.	Per Cwt	229.90		100 Kg	452.55					
15	Erecting rolled steel beams or rails, erection for posts etc. (other than in roofs).	Per Cwt	112.25		100 Kg	220.95					
16	Making bolts and nuts of iron rods.	Per Cwt	1569.15	7699.70	100 Kg	3088.90	15156.90				
17	Cutting rails, rolled steel joists and beams, with hacksaw:-		/								
	a) upto 6" size (150 mm) b) above 6" size (150 mm)	Per Cut Per Cut	156.40 232.05		Per Cut Per Cut	156.40 232.05					
18	Cutting rails or rolled steel beams of size below 6" (150 mm), with jim.	Per Cut	74.50		Per Cwt Cut	74.50					
19	Bending rolled steel beams or rails.	Per Bend	78.70	330.60	Per Bend	78.70	330.60				
20	Drilling holes, in plates upto ½" (13 mm) thick, per inch dia, (25mm) or part thereof.	Per Hole	30.10	Depart	Per Hole	30.10					
	Extra for drilling holes in plates over ¹ /2" (13 mm) thick, per inch dia, (25 mm) or part thereof.	Per Hole	16.40		Per Hole	16.40					
22	Rivetting 1/8" dia (3 mm).	100 Nos	382.25		100 Nos	382.25					
23	Cutting out Rivets, all sizes.	100 Nos	1311.75		100 Nos	1311.75					
24	Fitting and erection of gutters of sheet iron.	Per Lft.	49.80		Metre	163.40					
25	Cutting and fixing iron bars, for barred windows.	Per bar	29.80		Per bar	29.80					
26	Cutting G.I. sheets.	Each Cut	16.15		Each Cut	16.15					
27	Notching web or foot of rail posts, for housing rail beams.	Per Notch	349.80	517.80	Per Notch	349.80	517.80				
28	Hoop iron netted trellis work fixed with nails.	Per Sft.	20.85		sq.m	224.40					
29	Fixing zinc iron or G.I. sheet on table tops.	Per Sft.	12.25		sq.m	132.00					
30	Making and fixing steel grated doors, complete with locking arrangement, angle iron frame 2"x2"x3/8" (50x50x10 mm) and 34" (20 mm) square bars 4" (100 mm) centre to centre.	Per Sft.	124.00	693.20	sq.m	1334.10	7458.65				

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description	1	Rate (British Sy	stem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
31	Making and fixing steel grated door with 1/16" thick (1.5mm) sheeting, including angle iron frame 2"x2"x3/8" (50x50x10 mm) and ¾" (20 mm) square bars 4" (100 mm) centre to centre, with locking arrangement.	Per Sft.	129.25	841.60	sq.m	1390.50	9055.50				
32	Making and fixing grating in opening, including fixing at site with flat iron $2"x3/8"$ (50x10 mm) and $3/4"$ (19 mm) square bars, at 4" (100 mm) centre to centre.	Per Sft.	49.85	341.95	sq.m	536.60	3679.55				
33	Providing and fixing stair railing (all types and designs) of hard wood, including bends and corners, screwed to 5/8"x5/8" (16x16 mm) M.S. square bars 2.75 ft. (838 mm) high, at 5.5 inch (137 mm) inch centre to centre, fixed in steps of stairs, M.S. flat 1"x1/8" (25x3 mm) welded to bars, painting/polishing 3 coats, etc. complete.	Per Rft.	259.30	752.60	Metre	850.80	2469.20		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.		
34	Providing/fixing stair railing consisting of M.S. Box section size 1-1/2"x3" of 16 SWG welded with M.S. flat 1"x1/8" continuously and welded over M.S. square bars 5/8"x5/8" punched in M.S. flat 2 ¾' high @ 5½" c/c fixed in steps of stair I/C painting 3 coats complete.	Per Rft.	136.70	526.95	Metre	448.55	1728.80				
35	Providing and fixing terrace railing of 2" (50 mm) i/d conduit pipe 16 SWG, welded with 5/8"x5/8" (16x16 mm) square bar 2.75 ft. (838 mm) high fixed at 5" (125 mm) centre to centre, in reinforced cement concrete slab with suitable arrangement, complete in all respects, as per design and drawing.	Per Rft.	98.80	564.35	Metre	324.15	1851.54		-do-		
36	Providing and fixing collapsible gate made of 2"x2"x" ¹ /4" (50x50x6 mm) tee iron at top and bottom, channel iron verticals ³ /4"x ¹ /4"x ¹ /8" (20x6x6x3 mm) at 3" (75 mm) to 5" (125 mm) centre to centre (approximate) and flat iron crosses 3"x3/16" (75x5 mm), and best quality rollers at bottom of 3" (75 mm) diameter including holdfasts, handles 12" (300 mm) long of ³ /4"x ¹ /4"x ¹ /8" (20x6x6x3 mm) channel iron, locking arrangement inside and outside, painting 3 coats of black Japan enameled, complete in working order.	Per Sft.	172.95	603.70	sq.m	1860.95	6495.95				
37	Providing and fixing 24 SWG G.I. sheet rolling shutter, consisting of steel frame of M.S. channel 2"x1¼"x1/8" (50x30x3 mm), angle iron 1½"x1½"x1/8" (40x40x3 mm), M.S. plate 1'x1'x1/8" (300x300x3 mm), G.I. pipe 1½" (37 mm) dia, springs 2' (600 mm) centre to centre, rollers, 24 SWG G.I. covering 1 ft. x 1 ft. (300x300 mm), handles, holdfast, and painting three coats, complete in all respects.	Per Sft.	40.45	217.85	sq.m	434.95	2344.05				
38	Providing and fixing M.S. angle iron 11/2"x11/2"x1/4"	Per Rft.	20.75	140.00	Metre	68.00	459.30				

	MRS, BI-ANNUAL P	ERIOD (1s	st AUGUST,	2012 TO 31s	t JANUA	RY, 2013) DISTRICT J	HANG	
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric	System)	Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
	(40x40x6 mm) edge protector nozing of steps of stairs, having holdfast or 3/8" (10 mm) dia M.S. bars 8" (200 mm) long welded at 2' (600 mm) centre to centre and embedded in cement concrete on steps, complete in all respects.								
39	Providing and fixing stair railing of 2 ¹ / ₂ " (63 mm) i/d G.I. pipe, welded with 5/8"x5/8" (16x16 mm) square M.S. bars 2'-9" (838 mm) high, fixed in each step, complete in all respects, including painting, polishing three coats.	Per Rft.	112.25	636.20	Metre	368.25	2087.20		The composite rate shall be reduced or increased by Rs. 31.90 for each foot of reduction or addition in the height of the square bars.
40	Providing and fixing G.I. wire gauze 24 SWG, 12x12 meshes per square inch, fixed to steel windows or doors, etc., complete in all respects.	Per Sft.	19.60	57.85	sq.m	210.70	622.70		
41	Providing and fixing steel windows with openable glazed panels, using beam section for frame 1½"x1"x5/8"x1/8" (40x25x16x3 mm), Z-section for leaves ¾"x1"x¾"x1/8" (20x25x20x3 mm), T-section sashes 1"x1"x1/8" (25x25x3 mm), glass panes, wooden screed for glazing embedded over a thin layer of putty duly screwed with leaves, brass fittings, holdfast, duly painted, complete in all respects, including all cost of material and labour, etc. as per approved design and as directed by the Engineer-in-charge:-			Depart	13				For fixed pannels, the composite rate will be reduced by Rs.30.00 per Sft. or Rs. 305.00 per Sq. metre.
	a) without wire gauze:								
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick b) fixed with wire gauze, 22 SWG 	Per Sft. ditto ditto ditto ditto	50.85 50.85 50.85 50.85 50.85	299.15 303.95 311.15 318.35 323.15	sq.m ditto ditto ditto ditto	547.30 547.30 547.30 547.30 547.30	3219.10 3270.75 3348.20 3425.65 3477.30		
	 i) glass pane 2 mm thick ii) glass pane 2.5 mm thick iii) glass pane 3 mm thick iv) glass pane 4 mm thick v) glass pane 5 mm thick 	Per Sft. ditto ditto ditto ditto	71.30 71.30 71.30 71.30 71.30		ditto ditto ditto	767.15 767.15 767.15 767.15 767.15	3799.20 3850.85 3928.35 4005.80 4057.45		
42	Providing and fixing steel windows using M.S. sheet (16 SWG) moulded tubular pipe 1½"x1½" (40x40mm) for frame and 1½"x1¼" (30x30mm) for leaves including M.S. square bars ¼"x1¼" (6x6 mm) welded around each panel of frame, 5 mm thick glass panes fixed with double M.S. square tubular pipe 3/8"x3/8" (10x10mm) (22 SWG)								

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr.	Description		Rate (British Sy	stem)	R	ate (Metric	System)	Spec.	Remarks	
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.		
	 beading with U' shaped rubber lining, brass fitting, holdfast, including painting three coats complete in all respects. a) For openable panels fixed with wire gauze 24 SWG, 12x12 mesh and glass panes ¼" (6 mm) thick. 	Per Sft.	51.00	294.45	Sq.m	548.70	3168.25			
	b) For fixed panels without wire gauze.	ditto	49.55	177.30	ditto	532.90	1907.85			
43	Providing and fixing windows consisting of M.S. box section frame 2"x1½" (50x40mm), leaves frame 1-½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws I/C all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	52.60	366.15	Sq.m	565.80	3939.55			
44	Providing and fixing windows consisting of M.S. box section frame 2"x1½", (50x40mm) leaves frame 1½"x1" (40x25mm) box section frame for glazing 3/8"x3/8" (10x10mm) using 16 SWG sheet 'U' shaped rubber supported with 1"x1/8" (25x3mm) M.S. flat for fixing 3/16" (5 mm) thick glass panes M.S. box section ½"x½" (13x13mm) of 16 SWG for fixing 24 SWG wire gauze on outer side by means of ¾"x1/8" (20x3mm) M.S. flat and screws including grill of M.S. flat ½"x1/8" (13x3mm) or ¼"x¼" (6x6mm) square bar with independent frame of ½"x½" (13x13mm) box section of 16 SWG i/c all C.P. fitting and painting 3 coats complete in all respect.	Per Sft.	65.05	424.30	Per Sft.	700.00	4565.60			
45	Flapping G.I. pipes for bath room drains.	Each	440.55	478.95	Each	440.55	478.95			
46	Supply and fixing iron grating for fire place.	Per Sft.	81.50	183.50	sq.m	877.05	1974.55			
47	Fixing copper flashing, including cutting of sheets, grooving and rivetting.	Per Lft.	34.75		Metre	114.00				
48	Providing and fixing angle iron railing, using 2½"x2½"x3/8" (63x63x10 mm) angle iron post 4½" (113 mm) long, 5' to 6' (1500 to 1800 mm) apart, with 2½"x2½"x3/8" (63x63x10 mm) angle iron top rail, and two rows of M.S. flat 2½"x¼" (63x6 mm) including fixing to side of Bridge/structure with U.bolt 1½' (450 mm) long ¾" (20 mm) dia, painting posts, etc. complete in all respects.	Per Rft.	55.90	789.60	Metre	183.35	2590.50			

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG										
Sr.	Description		Rate (British Sy	vstem)	R	ate (Metric S	System)	Spec.	Remarks		
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.			
49	Providing and fixing barbed wire fencing on compound wall, consisting of $1\frac{1}{2}$ "x $1\frac{1}{2}$ "x $3/16$ " ($40x40x5$ mm), angle iron post $3\frac{1}{4}$ ft. (990 mm) long, 5 to 6 ft. (1500 to 1800 mm) centre to centre, embedded in cement concrete 1:4:8, base of size 9"x9"x12" ($225x225x300$ mm), and three rows of barbed wire, painting posts, etc. complete in all respects.	100Rft.	1264.80	9582.80	Metre	41.50	314.40				
50	Providing and fixing barbed wire fencing on compound wall, consisting of 1½"x1½"x3/16" (40x40x5mm) angle iron post 3' (900 mm) long, 4' (1200 mm) apart embedded in cement concrete 1:4:8 base of size 6"x6"x9" (150x150x225 mm) and 4 rows of barbed wire, including binding wire, painting posts, etc. complete in all respects.	100Rft.	2102.90	12211.00	Metre	69.00	400.60				
51	Providing and fixing all types of partly fixed and partly openable glazed anodised bronze colour aluminium doors, using delux section of M/s Al-Cop or Pakistan Cables, having chowkat frame of size 40 x 100 mm (1½" x 4") and leaf frame of 60x40mm (2½"x1½") wide sections including the cost of ¼" (5 mm) thick imported tinted glass with aluminium triangular gola and rubber gasket to support the glass and leaf edging, using approved standard fittings, locks, 3" (75 mm) wide long handles etc., and hardware any required as approved by the engineer in-charge.	Per Sft	62.55	476.85 Depute	sq. m	673.05	5130.90		 Increase rate by Rs. 40.00 per Sft or Rs.430.50 per Sq-metre if sections thickness is 2 mm. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminimum shade. Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if local glass is used. 		
52	Providing and fitting all types of glazed aluminium windows of anodised bronze colour partly fixed and partly sliding using delux sections of M/s Al-Cop or Pakistan Cables having frame size of $100 \times 20 \text{ mm} (4"x^{3}4")$ and leaf frame sections of $50 \times 20 \text{ mm} (2"x^{3}4")$, all of 1.6mm thickness including 5 mm thick imported tinted glass with rubber gasket using approved standard latches, hardware etc., as approved by the Engineer in-charge.	Per Sft	88.80	364.65	sq. m	955.50	3923.65		 (1) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if section thickness is 1.2 mm. (2) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per Sq-metre if sections are of dull aluminium shade. (3) Reduce rate by Rs.20.00 per Sft or Rs.215.20 per sq-metre if local glass is used. 		

26. MISCELLANEOUS

Rates for all finished works include the removal of surplus debris, unused material and byproducts.

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG											
Sr.	Description		Rate (British Sy	vstem)	Rat	te (Metric S	ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.				
1	Notice board made of cement, sand mortar 1:3.	Per Sft.	44.80	53.20	Per sq.m	482.00	572.65		The board is to be of cement plaster ¹ / ₂ " (13 mm) thick, with 2" (50 mm) wide and 1" (25 mm) thick beading.			
2	Fixing handles to iron hammers.	Each	61.20	-	Each	61.20	-					
	Providing and fixing barbed wire fencing, with 4 horizontal and 2 number cross wires fixed with posts of R.C.C., 1:2:4 (straining posts 7'x9"x9" (2.13 mx225x225 mm) at 100' (30 m) centre to centre, stiffening posts 7'x6"x6" (2.13 mx150x150 mm) at 50 ft. (15 m) interval and intermediate post 7'x5"x5" (2.13 mx125x125 mm) at 8 ft.(2.4 m) centre to centre), including cost of steel, its fabrication and placing of steel reinforcement, eye bolts, washers, etc. complete. <u>Surveying</u>	100Lft.	4,592.80	22,471.80	L.m.	150.70	737.25		Vertical bars in straining and stiffening posts to be 4 No. each by 1/2" (13 mm) dia and for intermediate posts to be 4 No. of 3/8" (10 mm) dia Stirrups for all posts to be 1/4" (6 mm) dia. at 12" (300 mm) centre to centre.			
	Supplying Bamboo Jhandies 10' to 12' (3.00 to 3.65 m) with iron shoes, and flags 15" (375mm) square.	Each	32.75	158.75	Each	32.75	158.75					
5	Supplying wooden pegs for levelling, 1½" (40 mm) dia, 6" (150mm) long.	100Nos.	97.90	115.05	100Nos.	97.90	115.05					
6	Supplying wooden pegs for alignment, 2" to 3" dia (50 to 75 mm), 9" (225 mm) long.	100Nos.	234.95	432.95	100Nos.	234.95	432.95					
7	Fixing enamalled iron gauges flush with masonry, including cost of hooks.	Per Lft.	52.15	60.80	Per L.M.	171.05	199.40					
8	Placing boundary pillars in position, including digging pits.	Each	34.75	-	Each	34.75	-					
9	Fixing main line type distance mark in position, including making 1:3:6 cement concrete base block, size 14"x10"x15" (350x250x375 mm).	Each	149.80	310.35	Each	149.80	310.35		Composite rate does not include cost of iron distance marks.			
	Hand Pumps & Pressure Pipes											
10	Cutting pipes, upto 2" (50 mm) dia.	Per cut	34.75	-	Per cut	34.75	-					

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG								
Sr.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
11	Cutting pipe, above 2" (50 mm) dia.	Per cut	63.90	-	Per cut	63.90	-		
12	Threading pipe ends, $1\frac{1}{2}$ " (40 mm) to 4" (100 mm) dia.	Each End	44.55	-	Each End	44.55	-		
13	Assembling 1 ¹ / ₂ " (40 mm) dia pressure pipe.	100Lft.	158.80	-	Per Metre	5.20	-		
14	Boring and fixing 1 ¹ / ₂ " (40 mm) dia pressure pipe:								
	 a) in ordinary soil b) in clay c) in shingle 	Per Lft. Per Lft. Per Lft.	54.55 105.75 157.00	C.	Per Metre Per Metre Per Metre	178.90 347.00 515.10	-		
15	Repairs to hand pump, pulling out and refitting.	Per Lft.	24.10		Per Metre	79.05	-		
16	Fixing hand pump (Machine only)	Each	117.50		Each	117.50	-		
	<u>Rest House Furniture & Fuel, etc.</u>	1	R	in the	7) 🎼				
17	Washing Niwar of bed.	Per bed	341.55	371.80	Per bed	341.55	371.80		
18	Washing Durries.	100Sft.	455.40	527.40	sq.m	49.00	56.75		
19	Recaning chairs:		ima nce	Despisor	tment				
	 i) office chairs, single caning seat only. ii) office chairs, double canning seat only. iii) office chairs, single caning back only. iv) office chairs, double caning back only. v) easy chairs, single caning seat only. vi) easy chairs, double caning seat only. vii) easy chairs, double caning seat only. viii) easy chairs, single caning only, back and seat in one piece. viii) easy chairs, double caning back & seat in one piece or couches with caned area about 16 Sft (1.5 Sqm). 	Each Each Each Each Each Each Each	205.60 264.35 146.85 234.95 146.85 411.20 587.40 881.10	240.25 313.30 149.05 253.75 193.35 480.55 873.00 1,574.70	Each Each Each Each Each Each Each	205.60 264.35 146.85 234.95 146.85 411.20 587.40 881.10	240.25 313.30 149.05 253.75 193.35 480.55 873.00 1,574.70		
20	Making and fixing Hat pegs ordinary.	Each	105.75	448.20	Each	105.75	448.20		
21	Weaving charpoy.	Each	300.30	-	Each	300.30	-		
22	Sweeping chimney.	Each	75.90	77.20	Each	75.90	77.20		
23	Picture railing, including making, fixing and painting.	Per Lft.	30.25	95.15	Per LM	99.25	312.10		
24	Cutting fuel wood, from plantation.	100Kg	101.65	-	100Kg	101.65	-		
25	Splitting fuel wood.	100Kg	212.90	-	100Kg	212.90	-		

	MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG								
Sr.	Description	Description Rate (British System) Rate (Metric System)		ystem)	Spec.	Remarks			
No.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
26	Burning charcoal, including loading, unloading and repairing kilns.	100Kg of Char- coal	334.40	-	100Kg of Char- coal	334.40	-		
27	Filling cement bags with coal and sewing (including cost of strings).	100Cft.	933.55	936.70	cu.m	329.75	330.85		
28	Supplying manure.	Cart Load	113.85	245.85	Cart Load	113.85	245.85		Capacity of cart, 20 Cft. (0.57 cu.m).
29	Washing punkha frills.	Each	92.40	-	Each	92.40	-		
30	Washing:-			*)					
	a) table clothb) napkins, dusters, etc.	Each Each	23.10 15.40		Each Each	23.10 15.40	-		
31	Hoisting and placing sleepers for centring, including carriage within one chain.	Each No.	41.50		Each No.	41.50	-		
32	Dismantling sleepers from centring, including stacking within one chain.	Each No.	45.60	(خېر ت بند	Each No.	45.60	-		
33	Dredging Sumps.	Per Shift	1,707.75	H. C	Per Shift	1,707.75	-		Not less than five gangmen to be employed for each shift to ensure effective dredging.
34	Fixing `U' bolt in masonry or concrete, including levelling and tying for fixing angle iron post.	Each	135.85	i Durp <u>i</u> on	Each	135.85	-		
35	Bailing out water:-								
	a) by hand b) by pump	1000 Cft. 1000 Cft.	1,366.20 162.95	303.75	cu.m ditto	48.25 5.75	10.75		Rate includes cost of providing pump, POL and operation charges, etc.
36	Drilling holes in R.C. Trough.	Per Nos.	86.90	-	Per Nos.	86.90	-		
37	Supplying and laying polythene sheet over D.P.C. under floors and on roofs, etc.								The rate includes overlaps.
	 i) 300 gauge (.003" thick) ii) 500 gauge (.005" thick) 	Per Sft. Per Sft.	0.70 1.40	2.25 2.70	sq.m sq.m	7.45 14.90	24.10 28.85		
38	Laying 2" (50 mm) thick sand and bitumen carpet, on top of foundation of oil tank.	100Sft.	932.95	6,333.55	sq.m	100.40	681.50		
39	Cutting hole 4"x6" (100x150 mm) in stone masonry or brick wall with chisel, repairing masonry and removing debris within one chain lead.	Per Hole	148.95	-	Per Hole	148.95	-		Same rate to be paid for other type of masonry and R.C.C. work.

MRS, BI-ANNUAL PERIOD (1st AUGUST, 2012 TO 31st JANUARY, 2013) DISTRICT JHANG									
Sr. No.	Description	Rate (British System)			Rate (Metric System)			Spec.	Remarks
NO.		Unit	Labour	Composite	Unit	Labour	Composite	No.	
40	Making 1 ¹ / ₂ "x1 ¹ / ₂ " (40x40 mm) groove in wall of stone or brick masonry in cement for fixing planks upto 9" (225 mm) deep.	Per Plank	130.35	-	Per Plank	130.35	-		
41	Drilling holes in stone or brick masonry upto 2" (50 mm) dia, per inch (25 mm) depth.	Per hole per inch depth	45.55		Per hole per c.m depth	18.20			
42	Spraying anti-termite liquid mixed with water in the ratio of 1:40.	100Sft. of each spray	58.75	197.10	sq.m of each spray	6.30	21.20		
43	Providing and fixing barbed wire fencing, with 4 horizontal and two cross wires, with R.C.C. 1:2:4 posts, 5.5'x6"x9" (1.68mx150mmx225 mm) at 8 ft. (2.45 m) centre to centre, reinforced with 4 No. 3/8" (10 mm) dia vertical bars and 1/8" (3 mm) dia stirrups 12" (300 mm) centre to centre, complete in all respects.	93 core-							
	 i) without cement concrete base. ii) in cement concrete 1:4:8 base of size 12"x12"x21" (300x300x525 mm). 	100Rft. 100Rft.	5,392.60 5,920.80	22,118.85 23,981.00	Per Metre Per Metre	176.90 194.20	725.50 786.60		

Finance Department